



HAL
open science

The SOMMA model: cortically inspired maps for multimodal learning

Mathieu Lefort, Yann Boniface, Bernard Girau

► **To cite this version:**

Mathieu Lefort, Yann Boniface, Bernard Girau. The SOMMA model: cortically inspired maps for multimodal learning. Cognitive Systems, Feb 2012, Vienna, Austria. hal-00678759

HAL Id: hal-00678759

<https://inria.hal.science/hal-00678759v1>

Submitted on 13 Mar 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

The SOMMA model: cortically inspired maps for multimodal learning

Aim:

- to learn correlations (meaning recurrent spatial patterns) from a multimodal data flow
- to generalize these correlations in order to adapt to unknown situations


Constraints:

- connectionist paradigm: computation is local, generic and decentralized
- learning is continuous and unsupervised


Means:

- 1) splitting of the data flow into multiple monomodal flows
- 2) self-organization of monomodal correlations in low dimension topology
- 3) reciprocal and topological connections between monomodal maps
- 4) learning of multimodal correlations by constrained monomodal self-organizations

Architecture:



Dynamics:



Model description:

- sensitive layer provides a tabular coding of the current stimulus
- cortical layer provides information from the other monomodal perceptions
- perceptive layer (dynamic neural fields) represents, by a spatial coding, the perception of the current stimulus as a consensus between the local (monomodal) and the multimodal activities

Learning description:


afferent weights:

- BCMu learning rule: discrimination of a correlation in the feedforward flow
- modulation by the perceptive activity combined with a synaptic regulation term: provides the multimodal self-organization of the discriminations

multimodal weights:

- Widrow Hoff learning rule: the cortical activity converges on the perceptive one

Results:



The bidimensional localisation of each sensitive discriminated Gaussian is represented by the orientation and the color of the bar.

We can observe

- 1) the self-organization of the modal correlations in each modal map
- 2) as the same input is provided to both maps, the learning of multimodal correlations forces the modal self-organizations to be similar