



**HAL**  
open science

# A maximum likelihood estimator of neural network synaptic weights

Wahiba Taouali, Bruno Cessac

► **To cite this version:**

Wahiba Taouali, Bruno Cessac. A maximum likelihood estimator of neural network synaptic weights. Twenty Second Annual Computational Neuroscience Meeting: CNS 2013, Jul 2013, Paris, France. 14 (Suppl 1), pp.P59, 2013. hal-00842312

**HAL Id: hal-00842312**

**<https://inria.hal.science/hal-00842312>**

Submitted on 8 Jul 2013

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

POSTER PRESENTATION

Open Access

# A maximum likelihood estimator of neural network synaptic weights

Wahiba Taouali\*, Bruno Cessac


From Twenty Second Annual Computational Neuroscience Meeting: CNS\*2013  
Paris, France. 13-18 July 2013

The statistics of spikes in a neuronal network is constrained on one hand by the stimulus and shared noise, and on the other hand by neuron interactions and collective dynamics. The joint spike statistics and its spatio-temporal correlations can be explicitly computed in conductance-based Integrate-and-Fire models [1,2]. The probability distribution of spike is a Gibbs distribution (in its most general definition allowing to consider non-stationarity) which encompasses existing statistical models such as Maximum Entropy models or Generalized-Linear Models.

Moreover, the dependence of spike statistics in network parameters such as synaptic weights and stimulus is explicit.

Here, we address the following reverse engineering problem. Given a conductance-based Integrate-and-Fire

model as above where the spike statistics dependence on synaptic weights is known, can one reconstruct this network of synaptic weights from the observation of a raster plot generated by the network? We have solved this inverse problem using an explicit expression of a maximum likelihood estimator based on the Newton-Raphson method. This estimator employs analytically computed gradients and Hessian of the likelihood function given by the product of conditional probabilities. The explicit form of these conditional probabilities can be found in [1]. Our results show that this method allows to estimate the set of connections weights knowing the input, the noise distribution and the leak function. Moreover, we found that, in a log scale scheme, the estimation mean percentage error Err decreases linearly with observation time  $T$  (Figure 1).



This estimator is based on a plausible probabilistic model of spiking activity, and not a Poisson likelihood processing. So, it offers a flexible framework that should allow better statistical analysis of real data.

#### Acknowledgements

This work was supported by INRIA, ERC-NERVI number 227747, KEOPS ANR-CONICYT and European Union Project # FP7-269921 (BrainScales), Revision grant agreement N 600847 and Mathemacx FP7-ICT\_2011.9.7.

Published: 8 July 2013

#### References

1. Cessac B: **Statistics of spike trains in conductance-based neural networks: Rigorous results.** *The journal of Mathematical Neuroscience* 2011, **1**:8.
2. Cofré R, Cessac B: **Dynamics and spike trains statistics in conductance-based Integrate-and-Fire neural networks with chemical and electric synapses, to appear in.** *Chaos, Solitons and Fractals* 2013.

doi:10.1186/1471-2202-14-S1-P59

**Cite this article as:** Taouali and Cessac: A maximum likelihood estimator of neural network synaptic weights. *BMC Neuroscience* 2013 **14**(Suppl 1): P59.

**Submit your next manuscript to BioMed Central  
and take full advantage of:**

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

Submit your manuscript at  
www.biomedcentral.com/submit

