

RLC and AL-FEC @ IETF: when codes meet transport protocols and practical aspects

Vincent Roca

▶ To cite this version:

Vincent Roca. RLC and AL-FEC @ IETF: when codes meet transport protocols and practical aspects. Angeles Vazquez-Castro. Algebraic approaches to storage and network coding - COST IC1104, Feb 2014, Barcelone, Spain. hal-00948895

HAL Id: hal-00948895 https://inria.hal.science/hal-00948895

Submitted on 18 Feb 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

RLC and AL-FEC @ IETF: when codes meet transport protocols and practical aspects

Vincent Roca, Inria, France

Algebraic approaches to storage and network coding COST IC1104 meeting Feb. 7th, 2014, Barcelona



Goals

 focus on AL-FEC (all kinds, RLC included) codes for the erasure channel and their use in IETF standards

- I'll discuss
 - the key IETF/IRTF Working Groups
 - RMT, FECFRAME, DTNRG, NWCRG
 - Ohow is AL-FEC standardization addressed at IETF?
 - on the importance of signaling
 - Ofocus on NetWork Coding (NWCRG) IRTF activities
 - Tetrys on-the-fly coding
 - structured RLC





A quick survey of related IETF/IRTF working groups



About IETF

- Internet Engineering Task Force http://ietf.org/
 - the place where Internet technology is standardized
 - **OTCP/IP** and much more...
 - Ohistorically focusing on protocols, but now embraces FEC
 - they play a major role in recent communication systems!
 - Oopen to everybody
 - Ono fee, open discussion lists
 - Oopen specifications (Internet-Drafts and RFCs)
 - "Internet" is the target use-case
 - Olater IETF's technology is often instantiated by other SDOs (3GPP, DVB, OMA, ISDB, ...)

IETF motto: "we believe in rough consensus and working code"

About IETF (con't)

- about IPR (Intellectual Property Rights, i.e. patents)
 - Oany IETF/IRTF contributor has to disclose any IPR he/ she is "reasonably aware of"
 - Oyou may be one of the inventors...
 - Oit may be one of your colleagues...
 - Or anybody else if there is a good reason for you to be aware of the existence of the patent
 - ○IETF/IRTF takes no position WRT IPR's validity or scope ○it only provides a registry: https://datatracker.ietf.org/ipr/
 - Obut WGS are authorized to take it into consideration
 - to know more: https://www.ietf.org/ipr/policy.html

About IETF... (cont')

- two working groups primarily concerned by AL-FEC
 - ORMT (reliable multicast transport) WG http://tools.ietf.org/wg/rmt/ (1999 2013)
 - OAL-FEC and protocols for reliable object distribution to multiple receivers simultaneously
 - **Ostandardized AL-FEC:**
 - Raptor, RaptorQ, LDPC-Staircase, Reed-Solomon
 - No-code (the most useful one ©)
 - OAL-FEC and FLUTE/ALC are now widely deployed...






Example: ISDB-Tmm (NOTTV), Japan Relies on FLUTE/ALC and LDPC-Staircase

About IETF... (cont')

- Oexample: FLUTE/ALC
 - Ounidirectional communication (no feedback)
 - Omassively scalable, from 0 to billions of receivers
 - Otransmits files (ALC) and metadata (FLUTE)
 - **Oreliability achieved thanks to:**
 - the use of AL-FEC
 - the carousel approach (several tx loops)



About IETF... (cont')

- FECFRAME (FEC Framework) WG http://tools.ietf.org/wg/fecframe/ (2006 2013)
 - **OAL-FEC** and protocols for streaming applications
 - typically RTP/UDP flows
 - **Ostandardized AL-FEC:**
 - Raptor, RaptorQ, LDPC-Staircase, Reed-Solomon, 1D/2D parity
 - Olimited deployments so far... but things may evolve

About IRTF

You said IETF or IRTF?

Internet Research Task Force

http://irtf.org/

- Ocomplements the IETF
 - Ofocuses on research more than engineering aspects
 - Oit can be the first step before launching an IETF WG
- OIETF: 125 WGs in 8 areas
- OIRTF: only 9 WGs (!)


About IRTF... (cont')


- two working groups primarily concerned by AL-FEC
 - NWCRG (NetWork Coding) RG http://irtf.org/nwcrg (brand new WG, launched on Nov. 2013)
 - ORLC and protocols for network coding
 - Omore to come...
 - DTNRG (Delay Tolerant Networks) RG http://irtf.org/dtnrg (2002 - now)
 - **ORLC** and protocols for Delay Tolerant Networks (DTN)
 - ex: space communications
 - Oincludes an RLC proposal for improved robustness




Different transm. models according to WG

end-to-end






multicast 1 ⇒ n




in-network encoding



uni/multicast, intra-flow enc.



uni/multicast, inter-flow enc.



How is FEC standardization addressed in IETF?



Situation

- focus on the erasure channel only
 - Owe're at IETF
 - Owe observe losses, not transmission errors
 - Ocauses: router congestion, bad reception conditions (wireless), intermittent connectivity, etc.
- focus on "higher" layers
 - Owe're at IETF
 - Othey are called Application-Level FEC, but they are found:
 - within the application
 - within the transport layer (e.g. between RTP/UDP for streaming, in FLUTE/ALC for filecasting)
 - within the MAC layer (e.g., in DVB-H/MPE-FEC, or in DVB-SH/MPE-IFEC)
 - NB: not sure for routing layer: AL-FEC maybe not? NC maybe?
 - Oa direct consequence: everything is done in software

Situation... (cont')

- must accommodate wide variety of different needs
 - from small blocks (k=10s) to large blocks (k=10,000s)
 - Oe.g. filecasting as in FLUTE/ALC requires large k values
 - encoding a very large object with Reed-Solomon over GF(28) is quickly limited by the "coupon collector problem"
 - Osmall rate codes are sometimes useful, but CR ≥ 2/3 is sufficient most of the time, even in "digital fountain" applications like FLUTE/ALC
 - Ocode parameters (n; k) are determined dynamically Ocode creation time is critical
 - e.g., no time to apply complex code optimization technics
 - Vandermonde matrix creation for Reed-Solomon is penalizing

Situation... (cont')

- AL-FEC is a small component of a much larger system
 - Should be standardized independently
 - Should be reusable across different protocols

Principle 1: "divide to conquer"

- define applications on top of protocols
 - Oif meaningful
 - **Ooffers specialization**
- assemble BBs and create protocol inst.
 - Oprotocol = { building
 blocks, specialized if
 needed }
 - **Oworking solution**
- "building block" (BB) approach
 - Ofocused and reusable components

Applications

Protocol Instantiations


AL-FEC

Building blocks

Principle 1: "divide to conquer"... (cont')

ex. RMT

http://www.ietf.org/proceedings/88/slides/slides-88-nwcrg-1.pdf



Principle 2: "specify FEC Schemes"

 the case of fully-specified FEC schemes (the general case...)

FEC Scheme

=


{identifier + code specifications + signaling }

- each scheme is uniquely identified (IANA registry)
 - FEC Encoding ID ex. Reed-Solomon is 5 for RMT
- all the code details are specified non ambiguously
 - interoperability is a MUST
- signaling enables encoder/decoder synchronization, for a given object transfer

Principle 2: "specify FEC Schemes" (cont')

- more details on signaling...
 - Some information is sent once (reliably) per object transfer
 - **OFEC Object Transmission Information (FEC OTI)**
 - Oinfo. for the object
 - object length, parameters to partition it into blocks (if too large), symbol size
 - Oinfo. for the FEC codec
 - internal parameters, code rate (if needed)
 - Osome information is sent in each packet
 - **OFEC Payload ID (FPI)**
 - Owhich symbol(s) does the packet contain?
 - Oe.g. LDPC-Staircase (RFC 5170)

Principle 2: "specify FEC Schemes" (cont')



Principle 2: "specify FEC Schemes" (cont')

to know more about FEC Building Blocks

```
\bigcircRMT \Rightarrow RFC 5052 <a href="http://tools.ietf.org/html/rfc5052">http://tools.ietf.org/html/rfc5052</a>
```

OFECFRAME ⇒ RFC 6363 http://tools.ietf.org/html/rfc6363

Oin any case, signaling is essential to FEC




Focus on some NetWork Coding IRTF RG activities (nwcrg)



A key aspect: what type of FEC code?

- NC use-cases ask for more flexibility than RMT/ FECFRAME do
 - Ore-encoding of coded packets, distributed encoding, sliding window encoding, etc.
 - Oblocks are really an issue in that case
- but not necessarily all potential use-cases
 - Oend-to-end NC still makes sense!
 - **Osee Tetrys and Structured RLC**

What type of FEC code... (cont')



NWCRG activities (non exhaustive list)

see IRTF meeting proceedings

OIETF86 http://www.ietf.org/proceedings/86/nwcrg.html

OIETF87 http://www.ietf.org/proceedings/87/nwcrg.html

OIETF88 http://www.ietf.org/proceedings/88/nwcrg.html

- some contributions are on RLC codes
 - various results on RLC codes and their application
 - Ostructured RLC codes Informatiques (mathématiques



- Odistributed Reed-Solomon encoding
- OKodo RLC library (comment: beware of license)
- Onot yet available, but in progress... Addition of RLC support in our http://openfec.org library http://openfec.org library

NWCRG activities... (cont')

- others are on transport protocols for NC
 - Ocoded TCP
 - Oimprove TCP goodput by sending encoded symbols
 - TCP-IR (instant recovery)
 - Oa simple and pragmatic approach to solve some of the problems
 - Tetrys
 - ODragonCast Informatiques mathématiques







Focus 1: Tetrys "on-the-fly" encoding protocol (representative of a broader class of solutions)

http://www.ietf.org/proceedings/86/slides/slides-86-nwcrg-1.pdf http://websites.isae.fr/tetrys/

P.U. Tournoux, E. Lochin, J. Lacan, A. Bouabdallah, V. Roca, "On-the-fly erasure coding for real-time video applications", IEEE Transactions on Multimedia, Vol 13, Issue 4, August 2011.



Tetrys principles


- one technique, several ways to apply it
 - Oelastic encoding window approach



- Ounicast transmission with acknowledgments
- ⇒ encoding window contains any non-acknowledged packet
- Okey parameter: code rate

Tetrys principles... (cont')

example: ACKs enable sender to adjust encoding window



code rate 2/3

Tetrys principles... (cont')

 Tetrys can be turned to a sliding window (particular case)



Ouseful in case of unicast or multicast flows, without any acknowledgment

Tetrys can be used in multi-path environments too

Tran-Thai, Tuan and Lochin, Emmanuel and Lacan, Jérôme Online multipath convolutional coding for real-time transmission. 19th Int. Packet Video Workshop, May 2012.



Focus 2: Structured RLC codes: why? what for? how?



Motivations

- RLC are naturally random
 - Oit's easy, efficient, and flexible
- but there are incentives to have "structured" codes
 - Osparse codes are faster to encode/decode
 - Oan order of magnitude difference, because:
 - fewer XOR and/or FF symbol operations
 - fast ITerative (IT) decoding works better
 - Ocertain structures are extremely efficient
 - e.g., LDPC-Staircase [RFC5170] [WiMob13]
 - e.g., irregular LDPC codes perform the best with IT decoding

[WiMob13] V. Roca, M. Cunche, C. Thienot, J. Detchart, J. Lacan, "RS + LDPC-Staircase Codes for the Erasure Channel: Standards, Usage and Performance", IEEE 9th Int. Conf. on Wireless and Mobile Computing, Networking and Communications (WiMob), October 2013. http://hal.inria.fr/hal-00850118/en/

Goals of this work

- design codes that:
 - ocan be used as sliding/elastic encoding window (convolutional) and block codes
 - Othere are use-cases for each approach
 - can be used with encoding window/block sizes in 1-10,000s symbols range
 - Odepends on the use-case
 - Ocan be used as **small-rate** codes
 - Ocan generate a large number of repair symbols
 - even if it's rarely useful

Goals of this work... (cont')

- Ohave excellent erasure recovery performance
 - Ooften a complexity versus performance tradeoff
 - Oit's good to be able to adjust it on a use-case basis
- Oenable fast encoding and decoding
 - Osender and/or receiver can be an embedded device
- Oenable compact and robust signaling
 - Otransmitting the full encoding vector does not scale
 - Oprefer a function + index to identify the symbols/coefficients
 - can be a PRNG + seed
 - the function is known to both ends and the key is carried in the packet header

Goals of this work... (cont')

- focus only on use-cases that require end-to-end encoding
 - o"end" means either "host" or "middlebox", it's the same
 - Obecause it simplifies signaling
 - Ointermediate node re-encoding requires carrying the full encoding vectors which does not scale!
 - Osure, it's a subset of NWCRG candidate use-cases
 - Obut it's well suited to Tetrysand also to FLUTE/ALC and FECFRAME


Idea 1: mix binary and non-binary

- mix binary and non binary
 - Omost equations are sparse and coefficients binary
 - ○a limited number of columns are **heavy** with non-binary coefficients (e.g., on GF(2⁸))
- there are good reasons for that:
 - Sparseness is a key for high encoding/decoding speeds
 - Odensity/non binary are good for recovery performances
 - ogathering dense coefficients in columns (i.e. to certain symbols) is a key for high speed decoding [WiMob13]

[WiMob13] V. Roca, M. Cunche, C. Thienot, J. Detchart, J. Lacan, "RS + LDPC-Staircase Codes for the Erasure Channel: Standards, Usage and Performance", IEEE 9th Int. Conf. on Wireless and Mobile Computing, Networking and Communications (WiMob), October 2013. http://hal.inria.fr/hal-00850118/en/

Idea 1: mix bin and non-bin... (cont')

- block code example
 - (sparse + non-bin. columns) only



Idea 2: add a structure


- technique 2: add a structure to the right part of H
 - we know that a "staircase" (A.K.A. double diagonal) is highly beneficial...

$$\mathbf{H} = \begin{bmatrix} s_0 s_1 & \dots & s_{k-1} & r_0 r_1 & \dots & r_{n-k+1} \\ 01001 & \dots & 001 & 1 \\ 10010 & \dots & 110 & 11 \\ 001010 & \dots & 010 & 11 \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ 01010 & \dots & 010 & 11 \end{bmatrix}$$

- O... but when used in convolutional mode, signaling turns out to be prohibitively complex
 - believe me ;-)

Idea 2: add a structure... (cont')


- So we add a single heavy row and make all repair symbols depend on it
 - Oit's now quite simple, even when used in convolutional mode
 - several sums will be transmitted (e.g., periodically), and it is sufficient to identify the last symbol of the sum in the signaling header
 - Oit's efficient (see later), at the price of extra XOR operations




ONB: other ways to define heavy rows are feasible (e.g., with random coefficients over GF(2⁸)...

Let's put ideas 1 and 2 together

- 3 key parameters
 - Ok: source block or current encoding window size
 - OD_nonbin: controls number of heavy non-binary columns
 - D_nonbin = nb_non-binary_coeffs / k
 - OD_bin: controls the density of the sparse sub-matrices
 - D_bin = nb_1_coeffs / total_nb_coeffs_in_binary_submatrix
 - ○{D_nonbin, D_bin} depend on k and target max. overhead




Preliminary results



NB: results are presented here as the concatenation of small curves... In practice it will be a single curve for a single code...

Two close-ups

- decoding failure probability curves for k=200, 500
 - Ono visible error floor at 10⁻⁶ failure probability, which is excellent ©



This is work under progress...

- many key questions remain
 - what are the **performances** when used in sliding or elastic encoding window?
 - e.g. with Tetrys
 - how **fast** is it?
 - e.g., compared to our optimized LDPC-Staircase/RS codecs
 - Ohow does it scale with k?
 - e.g., compared to our optimized LDPC-Staircase codec
 - Odefine signaling aspects
 - FEC Payload ID (in each packet sent)
 - FEC Object Transmission Information (per object/session)
- want to know more?

http://www.ietf.org/proceedings/88/slides/slides-88-nwcrg-2.pdf

Conclusions



Conclusions

- there are plenty of opportunities to contribute to IETF/IRTF
 - oit's open and academic-friendly
 - Ocompared to other SDOs
 - the directions taken by the NWCRG group depend on individuals
 - Othere's no a-priori forbidden topics
 - if it fits within the "Internet" (in its broader meaning), it's okay
 - **Obut it MUST NOT break the Internet**
 - do not create flows/protocols that do not react in front of congestion signals
 - "TCP friendliness" (to some extent) is unavoidable