



# ALTA: A BRDF analysis library

Laurent Belcour<sup>1,2</sup>, Pascal Barla<sup>2</sup>, Romain Pacanowski<sup>3,2</sup>

<sup>1</sup> Ligum, Université de Montréal

<sup>2</sup> Inria Bordeaux Sud-Ouest

<sup>3</sup> LP2N, CNRS




# Motivations & Goals



# Motivations & Goals





# The “BRDF Map”

SGD [Bagher et al. 2012]

GGX [Walter et al .2007]

Ashikmin & Shirley [2000]

He et al. [1991]

Ashikmin et al. [2000]

ABC [Löw et al. 2012]

Lafortune et al. [1997]

Hanrahan & Kruger [1993]

Ward [1992]

Cook & Torrance [1982]

Blinn [1977]

Oren & Nayar [1994]

Beard-Maxwel [1973]


Granier & Heidrich [2003]

Schlick [1994]

Rational BRDFs [Pacanowski et al. 2012]


# Motivations & Goals

- Understanding BRDF
  - 4D space is complex to visualize
  - Estimating model parameters from data is hard



BRDF Explorer

- Available tools are limited
  - Tools in CG are mostly for preview
  - Tools in other fields are specialized  
([Gwyddion](#), [MiePlot](#), ...)




BRDFLab


# Motivations & Goals

- Heterogeneous measurements

- plastics and metals mostly
- different sampling density
- a few under sampled anisotropic BRDF




Cornell



CUReT

- Heterogeneous data formats

- binary / text
- various parametrizations
- incomplete/extrapolated data



MERL

# Introducing ALTA

- Open-source C++ Library
  - Comparison of models (fitting & approx.)
  - Analysis of data
  - Cross platform
  
- Plugins mechanism
  - Easy to extend
  - Interact with existing (BRDF Explorer)



# ALTA overview

## Compatible data



MERL



ASTM

## BRDF Models or Functions

[Low et al. 2012]

[Lafortune et al. 2012]


[Beckmann & Spizzchino 1987]

[Pacanowski et al. 2012]

[Blinn 199X]

[Ward 199X]

## Tools



Data interpolation

$$\int_X x^k f(x) dx$$


Moment analysis

## Fitters

Google CERES



nonlinear optimization



QuadProg++  
Matlab




quadratic programming

## Compatibility

BRDF Explorer


OpenGL

GLSL




Matlab


# ALTA Architecture



# Usage example: data conversion



# Usage example: data conversion




$$\rho(\theta_h, \theta_d, \phi_d)$$



$$\rho(\theta_h, \theta_d), \text{ with } \phi_d = \frac{\pi}{2}$$

```
laurent$ ./build/data2data --input ~/Research/Data/Merl/gold-metallic-paint.binary --in-data ./build/libdata_merl.dylib --output ../data/2d/merl/gold-met.exr --out-data ./build/libdata_brdf_slice.dylib
```

# Fitting a rational function



# Comparing data and fitting results




input BRDF slice



conversion from BRDF  
file to data file using `brdf2data`

# XML and scripting capabilities

- Each program has a command line
- Concatenating programs
  - Create complex processes
  - Can be automated using bash scripts
- But ..
  - OS dependent
  - Not ideal for sharing




# XML and scripting capabilities


```
<?xml version="1.0"?>
<alta>
  <action name="data2data">
    <!-- Input and output arguments -->
    <input name="gold.binary" />
    <output name="gold-metallic.exr" />
    <!-- Define the data plugin to use -->
    <plugin name="in-data" name="data_merl" />
    <plugin name="out-data" name="data_brdf_slice" />
  </action>

  <action name="data2brdf">
    <!-- Input and output arguments -->
    <input name="gold-metallic.exr" />
    <output name="gold-metallic.brdf" />
    <!-- Define the function to use -->
    <function name="rational_function_chebychev" />
    <!-- Define the fitting procedure to use -->
    <fitter name="rational_fitter_parallel" />
  </action>

  <action name="brdf2data">
    <!-- Input and output arguments -->
    <input name="gold-metallic.brdf" />
    <output name="gold-rat.exr" />
    <!-- Define the data plugin to use -->
    <plugin name="data" name="data_brdf_slice" />
  </action>
</alta>
```



# XML and scripting capabilities




# XML for nonlinear fitting


```
<?xml version="1.0"?>
<alta>
<action name="data2data">
    <!-- Input and output arguments -->
    <input name="gold-metallic-paint.binary" />
    <output name="gold-metallic.exr" />
    <!-- Define the data plugin to use -->
    <plugin name="in-data" name="data_merl" />
    <plugin name="out-data" name="data_brdf_slice" />
</action>

<action name="data2brdf">
    <!-- Input and output arguments -->
    <input name="gold-metallic.exr" />
    <output name="gold-metallic.brdf" />
    <!-- Define the function to use -->
    <function name="nonlinear_function_beckmann" />
    <!-- Define the fitting procedure to use -->
    <fitter name="nonlinear_fitter_ceres" />
</action>

<action name="brdf2brdf">
    <!-- Input and output arguments -->
    <input name="gold-metallic.brdf" />
    <output name="gold-metallic-shader.brdf" />
    <!-- Define the data plugin to use -->
    <plugin name="export" name="explorer" />
</action>
</alta>
```



# XML and scripting capabilities





**ALTA NEEDS YOU**

# What can I do ?

- Try it and give us feedback!
- Write XML scripts
- Write plugins
  - Develop your new BRDF model
  - Add your data and analyze it
- Write programs
  - Provide new features for the community


# Future Work

- Web *vitrine* for BRDFs or BxDFs
  - Share your data, functions
  - get automatic comparisons with state of the art techniques
  - Online sharing of the comparisons results / graphics
- Multiple language interface to ALTA
  - Java, C#, Python, R, Matlab, Octave... (possible with SWIG)
- High (> 4D) dimension speed improvements

# Conclusion

- Already available
  - functional for research projects
  - and can be use commercially!
- Support
  - for various OS (MacOS X, Windows, Linux)
  - for various solvers
- Need feedback from companies

# Thank you !



<http://alta.gforge.inria.fr>

SOURCE CODE, TUTORIALS AND  
DOCUMENTATION ARE ALREADY  
AVAILABLE ONLINE