

Two-dimensional neural field simulator with parameter interface and 3D visualization

Eric Nichols, Axel Hutt

▶ To cite this version:

Eric Nichols, Axel Hutt. Two-dimensional neural field simulator with parameter interface and 3D visualization. 3rd International Conference on Neural Field Theory, Jun 2014, Reading, United Kingdom. hal-01064205

HAL Id: hal-01064205 https://inria.hal.science/hal-01064205

Submitted on 15 Sep 2014 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



I.N.R.I.A. Nancy - Grand Est Equipe NeuroSys 615 rue du Jardin Botanique 54600 Villers-lès-Nancy France

web: http://neurosys.loria.fr email: eric.nichols@inria.fr

Two-dimensional neural field simulator with parameter interface and 3D visualization

Eric Nichols

Axel Hutt





European Research Council Established by the European Commission

Overview

A simulator¹ calculating two-dimensional dynamic neural fields with multiple order derivatives is presented in this work. The simulated neural fields are of the type

 $\left(\eta \frac{\delta^2}{\delta t^2} + \gamma \frac{\delta}{\delta t} + 1 \right) V(x,t) = I(x,t) + \int \mathrm{d}^2 \mathbf{y} L(\|\mathbf{x}-\mathbf{y}\|) S\left[V\left(\mathbf{y},t - \frac{\|\mathbf{x}-\mathbf{y}\|}{c}\right) \right]$

where *I*, *L* and *S* are respectively a field's input, spatial delay kernel with axonal transmission speed *c* and nonlinear firing rate function $S = S_0 / (1 + exp(-\alpha(V-\Theta)))$. A Fast Fourier Transform in space is used to accelerate the integral calculation. The stochastic differential equation is useful for studying processes such as breathers, activity spread and Turing patterns shown below.

The underlying code is written in Python and is therefore cross-platform. It is also open-source, allowing researchers to modify the simulator in any manner.

Interface

- \rightarrow The simulator consists of a graphical interface (right) to facilitate modification of parameters before and during simulations that include:
 - timing of simulation and discretization of the time *td*,
 - field size and discretization of the field space,
 - starting voltage V and noise,
 - V values (minimum \rightarrow maximum) displayed on the graph,
 - derivative reducing prefactors,
 - transmission speed,
 - stimuli from external source,
 - a selection of three spatial connectivity kernels and firing rate settings.
- → The interface is used to start, pause, continue and restart new simulations.
- → Moving the mouse over the stimulus from external source, kernel and firing rate areas of the interface pauses the simulation and displays the relative values in the visualization window, allowing adjustments of these equations' parameters to be viewed.
- → The selected values in this window are saved for quick subsequent parameter modification and simulation.

ONF parameters	
Neural Field Simulation	
Start	
$ \Big(\eta_{\overline{\delta t^2}}^{\delta^2} + \gamma_{\overline{\delta t}}^{\delta} + 1 \Big) V\!(x,t) = I(x,t) + \int \! \mathrm{d}^2 \mathbf{y} L(\ \mathbf{x}-\mathbf{y}\) S\!\left[V\!\left(\mathbf{y},t - \frac{\ \mathbf{x}-\mathbf{y}\ }{c}\right) \right] $	
Simulation timing	Stimulus from external source
Duration: 0.5 💌 seconds	Type: gaussian 1 🛟
Discretize: 0.002 seconds	$I(x,t)=I_0+\Gamma \tfrac{e^{-x^2/\sigma^2}}{\pi\sigma^2}$
Field	$I_0 = 0.0$
Size: 30.0 mm	Γ = 10.0
Discretize into: 512 💌 units	$\sigma = 5.65$
Craph min and may 7 avis	Synaptic connectivity kernel
Zmax = Vmax	Kernel 3 🛟
Zmin = Vmin	$L(x) \!=\! rac{(a_e - a_i) e^{- x /s}}{2\pi s^2}$
V(x,0) and noise	<i>ae</i> = 10
$V_0 = 0.0$	<i>ai</i> = 14
noise = 0.1	<i>s</i> = 3.0
Derivative prefactors	Firing rate
$\gamma = 1$	$S - \frac{S_0}{S_0}$
$\eta = 0$	$D = \frac{1 + e^{-\alpha(V - \Theta)}}{1 + e^{-\alpha(V - \Theta)}}$
Transmission speed	$S_0 = 1.0$
<i>c</i> = 500.0	$\Theta = 0.005$

Output Visualization

- → The show3d library was created for the neural field simulator to visualize the output of simulations in three dimensions. It is built upon the Python binding to OpenGL for speed. The library is embedded within the simulator and can also be downloaded separately¹ along with documentation to view any 2D matrices in three dimensions using the Python language.
- \rightarrow The simulator output allows the researcher to...
 - move the field in every direction,
 - spin the field in every direction,
 - zoom the field in and out,
 - change the background colors,
 - change the graph colors to interpolate between 2 or 3 colors with selections of 8 colors,
 - adjust the color ranges to higher or lower values to highlight different depths,
 - save an image or make a video of the animated field for later review and
 - modify the interval of axis values.

Turing Pattern

Activity Spread

Breather



A Turing pattern appears in a noisy 90mm^2 field discretized into 512



Spatio-temporal activity spread. The graph's parameters are



A Breather is shown in a 30mm² field discretized into 512 units with

units with $V_0=5.4$, noise=0.1, td=0.01, $\gamma=1$, $\eta=0$, c=1000, I=0, S0=2, $\alpha=1.24$, $\Theta=3$, $L=((20.7 - 18(0.7^2))\exp(-|x|/0.7))/2\pi$. The graph's parameters are Zmax=Vmax and Zmin=Vmin. The pattern begins to emerge from the noise at 5 seconds (s) and V is stable at 12 seconds. Zmin=*Vmin* and Zmax=2.03, cutting off *Vmax*≈6.05. The field is 10mm², discretized into 256 units, *V*₀=2, *noise*=0, *td*=0.004, γ =1, η =0.35, *c*=10, S0=2, α =5.5, Θ =3, *I*=2+(exp(- $x^2/0.2^2$)/ π 0.2²) and *L*=0.1 $\Sigma_{i=0}^{2}$ cos(k_i , x)exp(-|x|/10)).

 $V_0=0$, noise=0.1, td=0.002, $\gamma=1$, $\eta=0$, c=500, $L=(10 - 14)\exp(-|\mathbf{x}|/3)/2\pi 3^2$, $I=10(\exp(-\mathbf{x}^2/5.657^2)/\pi 5.657^2)$, $S_0=1$, $\alpha=10000$ and $\Theta=0.005$. The graph's parameters are Zmax=0.0046 and Zmin=0.0039.

Acknowledgments

The work is funded by the European Research Council for support under the European Union's Seventh Framework Program (FP7/2007-2013), ERC grant agreement No. 257253 (MATHANA project).

References

[1] https://gforge.inria.fr/projects/nfsimulator/