Introduction	Equivalent Conditions	Numerical Results	Second Approach	Application	Perspectives

Impedance Transmission Conditions for the Electric Potential across a Highly Conductive Casing

Aralar Erdozain¹ and Victor Péron^{1,2}

¹INRIA Bordeaux Sud-Ouest, Team magique 3D ²Université de Pau et des Pays de l'Adour







- Main goal: To obtain a better characterization of the Earth's subsurface
- How: Recording borehole resistivity measurements
- Procedure:
 Well
 Logging Instrument
 Transmitters
 Receivers

Approach Application

Perspectives

MOTIVATION

- Practical Difficulties:
 - It is not easy to drill a borehole
 - It may collapse
- Practical Solutions:
 - Use a metallic casing
 - Surround with a cement layer
- Problem solved, but...



- Practical Difficulties:
 - It is not easy to drill a borehole
 - It may collapse
- Practical Solutions:
 - Use a metallic casing
 - Surround with a cement layer



• Problem solved, but... Numerical problems due to the high conductivity and thinness of the casing

h Application

Perspectives

CONFIGURATION OF INTEREST



We can reduce the 3D problem to a 2D problem due to the **axysimmetric** configuration.

Numerical Results

Second Approach

Application

Perspectives

MAIN IDEA

ASYMPTOTIC MODELS



Second Approach

Application

Perspectives

REALISTIC SCENARIO

ſ	-	<u>14 cm</u> 5 cm	
$1 \ \Omega m$	$2 \ \Omega m$	5 Ωm	5 m
		20 Ωm	2 m
		5 Ωm	5 m
	•	-1.27cm, 2.3e-7 Ωm	

• Conductivity and casing width:

$$\left\{ \begin{array}{ll} \varepsilon &= 1.27 \mathrm{e} - 2 \ \mathrm{m} \\ \sigma_c &= 4.34 \mathrm{e} 6 \ \Omega^{-1} \mathrm{m}^{-1} \end{array} \right.$$

$$\Rightarrow \sigma_c pprox arepsilon^{-3}$$

• Classical approach:

$$\sigma_c = \alpha \qquad \alpha \in \mathbb{R}$$

• High conductive case:

$$\sigma_c = \alpha \varepsilon^{-3} \qquad \alpha \in \mathbb{R}$$

Introduction	Equivalent Conditions	Numerical Results	Second Approach	Application	Perspectives
REFER	ENCES				

- A.A. Kaufman. The electrical field in a borehole with a casing. *Geophysics*, Vol.55, Issue 1, pp. 29-38, 1990.
- D.Pardo, C.Torres-Verdín and Z.Zhang. Sensitivity study of borehole-to-surface and crosswell electromagnetic measurements acquired with energized steel casing to water displacement in hydrocarbon-bearing layers. *Geophysics*, 73 No.6, F261-F268, 2008.
- M. Duruflé, V. Péron and C. Poignard. Thin Layer Models for Electromagnetism. *Communications in Computational Physics* 16(1):213-238, 2014.
- K. Schmidt, A. Chernov, Robust transmission conditions of high order for thin conducting sheets in two dimensions, *IEEE Trans. Magn.*, 50 (2014), pp. 41–44.

Application

Perspectives

OUTLINE

- 1 Introduction
- 2 Equivalent Conditions
- **3** Numerical Results
- 4 Second Approach

5 Application

6 Perspectives

Application Po

Perspectives

OUTLINE

Introduction

- 2 Equivalent Conditions
- 3 Numerical Results
- 4 Second Approach

5 Application

6 Perspectives

Numerical Results

s Second Approach

roach Application

Perspectives

MODEL PROBLEM - 3D

STATIC ELECTRIC POTENTIAL

$$\operatorname{div}\left(\left(\sigma-i\epsilon\omega\right)\nabla u\right)=f \text{ in } \Omega$$

 $\Omega = \Omega_i^\varepsilon \cup \Omega_c^\varepsilon \cup \Omega_e^\varepsilon \cup \Gamma_i^\varepsilon \cup \Gamma_e^\varepsilon$



$$\sigma = \begin{cases} \sigma_i & \text{ in } \Omega_i^{\varepsilon} \\ \sigma_c = \alpha \varepsilon^{-3} & \text{ in } \Omega_c^{\varepsilon} \\ \sigma_e & \text{ in } \Omega_e^{\varepsilon} \end{cases}$$

and the solution is expressed as

$$u = \begin{cases} u_i & \text{ in } \Omega_i^{\varepsilon} \\ u_c & \text{ in } \Omega_c^{\varepsilon} \\ u_e & \text{ in } \Omega_e^{\varepsilon} \end{cases}$$



Its Second Approach

Perspectives

MODEL PROBLEM - 2D

Reference problem (P) set in the domain $\Omega = \Omega_i^{\varepsilon} \cup \Omega_c^{\varepsilon} \cup \Omega_e^{\varepsilon} \cup \Gamma_i^{\varepsilon} \cup \Gamma_e^{\varepsilon}$.

We denote the boundary $\Gamma_0 := \left(\overline{\partial \Omega_i^\varepsilon - \Gamma_i^\varepsilon}\right) \cup \left(\overline{\partial \Omega_e^\varepsilon - \Gamma_e^\varepsilon}\right).$



Second Approach

h Application

Perspectives

EXISTENCE AND UNIQUENESS

Theorem 1

There exists $\varepsilon_0 > 0$ s.t. for all $\varepsilon \in (0, \varepsilon_0)$, if $f_i \in L^2(\Omega_i^{\varepsilon})$ and $f_e \in L^2(\Omega_e^{\varepsilon})$, then $\exists ! u \in H_0^1(\Omega)$ solution of (P) and

 $\|u\|_{1,\Omega} \le C\left(\|f_i\|_{0,\Omega_i^{\varepsilon}} + \|f_e\|_{0,\Omega_e^{\varepsilon}}\right)$



Definition 1: We define the jump and mean value of the solution u across the casing as

$$\begin{split} [u] &= u|_{\Gamma_e^{\varepsilon}} - u|_{\Gamma_i^{\varepsilon}} \\ \{u\} &= \frac{1}{2} \left(u|_{\Gamma_e^{\varepsilon}} + u|_{\Gamma_i^{\varepsilon}} \right) \end{split}$$

Definition 2: Let u be the reference solution. We say an asymptotic model is of **Order k+1**, if its solution $u^{[k]}$ satisfies

$$||u-u^{[k]}||_{H^1} \leq C \varepsilon^{k+1} \quad \text{ when } \quad \varepsilon \to 0$$

• Step1: Derive an Asymptotic Expansion for u when $\varepsilon \longrightarrow 0$

• In the casing:
$$u_c(x,y) = \sum_{n \in \mathbb{N}} \varepsilon^n U^n \left(\frac{x - r_0}{\varepsilon}, y \right)$$

• Outside the casing: $u(x,y) = \sum_{n \in \mathbb{N}} \varepsilon^n u^n(x,y)$

• Step2: Obtain Equivalent Conditions of order k + 1 by identifying a simpler problem satisfied by the truncated expansion and neglecting the higher order terms in ε

•
$$u_{k,\varepsilon} := u^0 + \varepsilon u^1 + \varepsilon^2 u^2 + \ldots + \varepsilon^k u^k$$

• Step3: Prove Convergence rates for asymptotic models

Second Approach

Application

Perspectives

MULTISCALE EXPANSION

EDURE



Approach Application

Perspectives

EQUIVALENT MODELS

FIRST APPROACH

(Transmission conditions across the casing)

• Order 2:
$$\longrightarrow$$

$$\begin{cases}
\sigma_i \Delta u_i = f_i & \text{in } \Omega_i^{\varepsilon} \\
u_i = 0 & \text{on } \partial \Omega_i^{\varepsilon} \\
\sigma_e \Delta u_e = f_e & \text{in } \Omega_e^{\varepsilon} \\
u_e = 0 & \text{on } \partial \Omega_e^{\varepsilon}
\end{cases}$$

$$\begin{cases}
\sigma_i \Delta u_i = f_i & \text{in } \Omega_e^{\varepsilon} \\
\sigma_e \Delta u_e = f_e & \text{in } \Omega_e^{\varepsilon}
\end{cases}$$

• Order 4:
$$\longrightarrow$$

$$\begin{cases} [u] = 0 \\ [\sigma \partial_x u] = -\frac{\alpha}{\varepsilon^2} \partial_x^2 \{u\} \\ u = 0 & \text{on } \Gamma_0 \end{cases}$$

 (P_4)

roach Application

Perspectives

CONVERGENCE

Theorem 2

There exists $\varepsilon_0 > 0$ s.t. for all $\varepsilon \in (0, \varepsilon_0)$, if $f_i \in L^2(\Omega_i^{\varepsilon})$ and $f_e \in L^2(\Omega_e^{\varepsilon})$, then $\exists ! u^{[k]} \in V_{k+1}$ solution of P_{k+1} , k = 1, 3, and $\|u^{[k]}\|_{1,\Omega_i^{\varepsilon} \cup \Omega_e^{\varepsilon}} \le C\left(\|f_i\|_{0,\Omega_i^{\varepsilon}} + \|f_e\|_{0,\Omega_e^{\varepsilon}}\right)$ $\|u - u^{[k]}\|_{1,\Omega_i^{\varepsilon} \cup \Omega_e^{\varepsilon}} \le C\varepsilon^{k+1}$

Where

$$V_{2} = \left\{ v : v_{i} \in H_{0}^{1}\left(\Omega_{i}^{\varepsilon}\right), v_{e} \in H_{0}^{1}\left(\Omega_{e}^{\varepsilon}\right) \right\}$$
$$V_{4} = \left\{ v : v_{i} \in H^{1}\left(\Omega_{i}^{\varepsilon}\right), v_{e} \in H^{1}\left(\Omega_{e}^{\varepsilon}\right), \nabla_{\Gamma}\left\{v\right\} \in L^{2}\left(\Gamma\right), v|_{\Gamma_{i}^{\varepsilon}} = v|_{\Gamma_{e}^{\varepsilon}}, v|_{\Gamma_{0}} = 0 \right\}$$

Application Perspectives

OUTLINE

- Introduction
- 2 Equivalent Conditions
- **3** Numerical Results
- ④ Second Approach
- 5 Application
- 6 Perspectives



- Classic Finite Element Method code
- Straight triangular elements (h refinement)
- Lagrange shape functions of any degree (p refinement)



Second Approach

Application

Perspectives

QUALITATIVE COMPARISON

Reference Model

Order 2 Model

Order 4 Model

Second Approach

Application

Perspectives

CONVERGENCE RATES



Casing Thickness (ε)	0.0117	0.0234	0.0469	0.0938	Expected ($\varepsilon \to 0$)
Order 2 Slopes	1.9969	1.9899	1.9638	1.8624	2
Order 4 Slopes	4.0046	4.0039	3.9879	3.8992	4

Application P

Perspectives

OUTLINE

- Introduction
- 2 Equivalent Conditions
- 3 Numerical Results
- 4 Second Approach

5 Application

6 Perspectives

Application

Perspectives

EQUIVALENT MODELS

SECOND APPROACH

(Transmission conditions across the interface Γ)

• Order 1:
$$\longrightarrow$$

$$\begin{cases}
\sigma_i \Delta u_i = f_i & \text{in } \Omega_i \\
u_i = 0 & \text{on } \partial \Omega_i \\
\sigma_e \Delta u_e = f_e & \text{in } \Omega_e \\
u_e = 0 & \text{on } \partial \Omega_e
\end{cases}$$
• Order 2: \longrightarrow

$$\begin{cases}
\sigma_i \Delta u_i = f_i & \text{in } \Omega_i \\
\sigma_e \Delta u_e = f_e & \text{in } \Omega_e \\
[u] = -\varepsilon \{\partial_x u\} \\
[\partial_x u] = -\frac{4}{\varepsilon} \{u\} \\
u = 0 & \text{on } \partial \Omega
\end{cases}$$
(P1)

Introduction	Equivalent Conditions	Numerical Results	Second Approach	Application	Perspectives
Stability	<i>,</i>				

Problem

Stability problems for the order 2 model of the second approach due to a non coercive term.



Solution

Use of Artificial Boundaries to move the transmission conditions and recover stability. For $\delta>0.5$

$$\Gamma_i^{\delta} = \{(x, y) : x = r_0 - \delta\varepsilon, y \in (0, y_0)\}$$
$$\Gamma_e^{\delta} = \{(x, y) : x = r_0 + \delta\varepsilon, y \in (0, y_0)\}$$

Equivalent Conditions

Numerical Results

Second Approach

bach Application

Perspectives

QUALITATIVE COMPARISON

Reference Model



1.2 1.4 1.6 1.8 2

0.2 0.4 0.6 0.8

Order 1 Model



Order 2 Model





Application Perspectives

CONVERGENCE RATES



Casing Thickness (ε)	0.0052	0.0088	0.0148	0.0249	Expected ($\varepsilon \to 0$)
Order 2 Slopes	0.9833	0.9713	0.9500	0.9103	1
Order 4 Slopes	1.9968	2.0420	2.0059	2.0460	2

COMPARISON



	Order	Stability	arepsilon-independent Domain
Model 1 No Gap	1	1	1
Model 2 No Gap	2	×	1
Model 1 Gap	2	1	×
Model 2 Gap	4	1	×

Application Perspectives

OUTLINE

- Introduction
- 2 Equivalent Conditions
- 3 Numerical Results
- 4 Second Approach

5 Application

6 Perspectives

APPLICATION

	1.27cm, 2.3e-7 ohm-m					
•	$z=z_3$ $z=z_2 \longrightarrow \text{Receivers}$ $z=z_1$					
•	$z=z_0 \longrightarrow Transmitter$					

- Equation: div $(\sigma \nabla u) = f$
- Right hand side:

 $f = \begin{cases} 1 & \text{In the transmitter} \\ 0 & \text{Outside the transmitter} \end{cases}$

• **Objective:** Measure the second difference of potential on the Receivers

$$U_2 = u(z_1) - 2u(z_2) + u(z_3)$$

• **Expected Result:** (Model of Kaufman) Relation between second difference of potential and rock resistivity of the form

$$U_2 = k \cdot \rho_{\mathsf{rock}}^{-\frac{1}{2}} \quad k \in \mathbb{R}$$

Second Approach

Application Perspectives

VARYING ROCK CONDUCTIVITY



Resistivity	[1,10]	$[10, 10^2]$	$[10^2, 10^3]$	$[10^3, 10^4]$	Expected
Reference Model Slopes	-0.4914	-0.4924	-0.4978	-0.4991	-0.5
Order 4 Slopes	-0.4914	-0.4924	-0.4977	-0.4993	-0.5

Second Approach

Application Perspectives

TWO ROCK LAYERS



ch Application

Perspectives

OUTLINE

- Introduction
- 2 Equivalent Conditions
- 3 Numerical Results
- ④ Second Approach
- 5 Application
- 6 Perspectives



- Fourier transform to reduce computational cost.
- Consider physically more realistic scenarios.
- Develop 3D electromagnetic models.
- Study highly deviated boreholes.



- Fourier transform to reduce computational cost.
- Consider physically more realistic scenarios.
- Develop 3D electromagnetic models.
- Study highly deviated boreholes.

THANK YOU FOR YOUR ATTENTION