


A distributed architecture for interacting with NAO

F. BADEIG Q. PELORSON S. ARIAS V. DROUARD . Gebru X. Li G. Evangelidis R. Horaud

INRIA Grenoble Rhône-Alpes // Perception team
{firstname.lastname}@inria.fr



1. NAO Specifications


Hardware specifications

- CPU: Intel Atom Z530 (2×1.6 GHz 32 bits)
- RAM: 1 GB
- Servomotors: 24 degrees of freedom

TACTILE SENSORS SPEAKERS [X2] AND FRONT & REAR MICROPHONES: CAMERAS [X2] LATERAL MICROPHONES (X2) SHOULDER JOINT SONARS [X4] $\{s\}$

Embedded software

- Face detection, Sound localization
- Motion control, Posture control
- Speech recognition (predefined words or sentences in several languages)




Microphone configuration

3. Toolbox to interact with NAO

	NAOLab C-				· F ()	
	Vision	Access:	getImage()	getImages()	getFaces()	
Provides the following features: 1- The middleware complexity is transparent to the users 2- A user-friendly interface is provided (NAOLab C++ and python libraries)		Control:	<pre>setResolution()</pre>	setCamera()		
	Audio	Access:	getSound()			
	Audio	Control:	<pre>textToSpeech()</pre>	playAudioFile()		
	Motion	Access:	getAllMotorInfo()	getMotorInfo()	getPosture()	
		Control:	moveHead()	moveMotor()	<pre>moveToPoint()</pre>	<pre>setPosture()</pre>

4. Example: Sound source localization (SSL) in Matlab



Acknowledgements: This research has received funding from the EU-FP7 STREP project EARS (#609465)

and ERC Advanced Grant VHIA (#340113).

Download our code

