

File dissemination in dynamic graphs: The case of independent and correlated links in series

Philippe Nain, Don Towsley

▶ To cite this version:

Philippe Nain, Don Towsley. File dissemination in dynamic graphs: The case of independent and correlated links in series. 2016. hal-01266505v1

HAL Id: hal-01266505 https://inria.hal.science/hal-01266505v1

Preprint submitted on 2 Feb 2016 (v1), last revised 21 Dec 2016 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

File dissemination in dynamic graphs: The case of independent and correlated links in series

Philippe Nain¹ and Don Towsley² ¹Inria, France – philippe.nain@inria.fr ²University of Massachusetts, Amherst, MA, USA – towsley@cs.umass.edu

February 2, 2016

Abstract

In this paper we investigate the traversal time of a file across N communication links (or ledges) subject to stochastic changes in the sending rate of each link. Each link's sending rate is modeled by a finite-state Markov process. Two cases, one where links evolve independently of one another (N mutually independent Markov processes), and the second where their behaviors are dependent (these N Markov processes are not mutually independent) are considered. A particular instance where the above is encountered is in ad hoc delay/tolerant networks where edges are subject to intermittent unavailability.

Keywords: Dynamic communication path; Traversal time; Markov process; Laplace-Stietljes transform; Pearson correlation coefficient; Stochastic bound.

1 Introduction

In this paper we investigate the traversal time of a file across *N* communication links (or edges) subject to stochastic changes. Throughout the paper the state of each link is modeled by a finite-state Markov process to account for the link's sending rate over time. We will address two cases, one where links are independent of each other and a second where they exhibit local dependencies.

The situation depicted above is encountered in mobile ad hoc and disruption/delay tolerant networks (DTNs), where edges are typically intermittently unavailable. Specifically, the state of an edge at any time t (i.e., absent, present) may be random, as well as possibly dependent on its state just before time t. In this case each Markov process has two states, on and off. If a packet is committed towards traversing such a route (as in source routing), it will simply wait in a node's buffer until the next edge in the path becomes available. Apart from source routing

in DTNs (which could be applicable in general topologies), dynamic links are observed in naturally occurring linear network topologies such as military convoys, underwater networks, traffic light networks, and linear sensor networks, e.g., for monitoring bridges. Edges in these networks exhibit varying levels of intermittence due to a variety of factors such as relative mobility of vehicles, significant signal propagation loss due to rugged terrain, or multi-path fading and shadowing.

The time spent traversing a path with such intermittent connectivity includes both the time spent crossing the edges along the path and the time spent waiting (in node buffers) for the edges to appear. Unlike the case of a static path where each edge is always available for use (and thus the path's traversal time is simply the sum of the delays to cross the constituent edges), computing the end-to-end traversal time (its distribution to be more precise as this quantity is a random variable) along a dynamic path is not trivial. This is the problem we study in this paper.

The organization and the main results of the paper are as follows. Related works are discussed in Section 2. Throughout this paper we will mainly provide an in-depth study of the case where the link dynamics are modeled by a two-state (or on-off) Markov processes, a situation of practical interest. This setting has also the advantage of yielding many qualitative as well as quantitative results without resorting to intense numerical computations as is usually the case with more general Markov models. We start in Section 3.3 by presenting a recursive scheme for the calculation of the joint Laplace-Stieltjes Transform (LST) of the joint traversal times across each link when links behave as independent Markov processes with a general state-space (under the technical condition (6)). This result holds for any initial state. When links are initially in steady-state the LST of the stationary joint link traversal times can easily be obtained as shown in Section 3.2.

Section 3.4 addresses the situation when links behave as independent on-off Markov processes. We show that the expected path traversal time can be obtained in $O(n^2)$ operations, with *n* the number of links. We also show that this quantity is minimized (resp. maximized) when all links are initially active (resp. inactive), thereby providing lower and upper bounds on the expected path traversal time. All these results hold for any initial link state and under various transmission scenarii and assumptions for the file size distribution - see Sections 3.5-3.6. Section 4 discusses the application of the results obtained in the latter two sections to the analysis developed in Sections 3.3-3.4.

Section 5 investigates the case where specific local - positive and negative - dependencies exist between the links. Both the stationary LST and the stationary expected path traversal time are obtained in explicit form as a function of the Neyman-Pearson correlation coefficient which characterizes the amount of linear dependence between adjacent links.

The paper ends with numerical results in Section 6 and concluding remarks in Section 7.

Notation: For any mapping $s \to f(s)$, f'(a) denotes the derivative of f(s) w.r.t. *s* evaluated at s = a. For any number $a \in [0, 1]$ we denote $\bar{a} = 1 - a$. The $|J| \times |J|$ diagonal matrix with diagonal elements x_j , $j \in J$, is denoted by diag $(x_j, j \in J)$. Here, |J| denotes the cardinality of the set *J*. Last, \mathbf{v}^T is the transpose of the row vector \mathbf{v} .

2 Related work

Our work can be cast into the framework of weighted graphs with stochastic weights, where in our case weights are the edge traversal times. [1] is the first paper to consider stochastic time-dependent travel times in a network. The author shows that for such networks classical shortest path algorithms (e.g. Dijkstra algorithm) do not necessarily find the best route between two nodes and proposes an adaptive decision rule to find the optimal route. More recently, a general framework for finding the optimal routing policy for stochastic time-dependent weights has been proposed in [2]. A literature review on optimal routing for graphs with both deterministic and stochastic time-dependent weights can be found in the latter paper.

Time-varying graphs [3] are useful in the study of communication networks with intermittent connectivity such as delay tolerant networks [4]. Markov random graphs have been proposed in [5], studied in the context of random walks in [6], and used to derive asymptotic scaling laws for flooding times in such networks [7]. The closest work to ours is [8], which computes the expected traversal time between a source-destination pair across a linear network where all links are described by independent and identical discrete time two state on-off models under the assumptions that service requires either zero or one unit of time. Our work considers a continuous time model where links are described by finite state, non-identical and possibly correlated Markov chains with a richer set of transmission models.

Last, our correlated link model based on local interactions is an example of an interacting particle system on a line. Typically, studies of such systems concern themselves with the existence and characterization of the stationary distribution. They are in general not concerned with metrics such as traversal times. See [9] for a background of this area and other examples. An exception is [10] where edge traversal times are modeled by correlated random variables with phase-type distributions (if the traversal time of edge u ends in phase x it will begin at edge v in phase y with probability $P_{u,v}(x, y)$ if the path (u, v) is followed). This Markovian setting is different from our setting which need not be Markovian and also does not account for different transmission models.

3 Independent links in series

3.1 Notation, definition, model

Consider *N* links in series, labeled 1, 2, ..., *N*. Unless otherwise mentioned in the following *n* is an arbitrary integer in $\{1, ..., N\}$. Let $X_n(t) \in E_n$ denote the state of link *n* at time $t \ge 0$, where E_n is a countable and finite set, and let $X(t) = (X_1(t), ..., X_N(t)) \in E := E_1 \times \cdots \times E_N$ be the state of all links at time *t*. Link states may be associated with different transmission rates to account for channel physical conditions, as discussed later on.

In the following, \mathbb{P}_x and \mathbb{E}_x will denote the probability and the expectation operator, respectively, given that $X(0) = x := (x_1, \ldots, x_N) \in E$.

Throughout the paper we assume that, for each n, $X_n := \{X_n(t), t \ge 0\}$ is an irreducible Markov process on E_n with infinitesimal generator $\mathbf{Q}_n = [q_n(i, j)]_{i,j \in E_n}$. Let $\boldsymbol{\pi}_n(t) := (\mathbb{P}(X_n(t) = j), j \in E_n)$ for $t \ge 0$.

We define by D_n the *traversal time* across link *n* so that $T_n := \sum_{i=1}^n D_i$ is the traversal time across links $1, \ldots, n$, also called hereafter the end-to-end traversal time. Define $Y_n := X_n(T_{n-1}) \in E_n$, the state of link *n* at the time T_{n-1} when the file becomes available for transmission on that link (by convention $T_0 = 0$).

The traversal time across a link is the sum of the *transmission time*, the link propagation delay and the total time during which the link was unavailable during the file transmission. For instance, if the link sending rate is constant and the file is sent according to the store-and-forward protocol (the first bit of the file cannot be transmitted across a link before the entire file is ready for transmission across that link), the transmission time is simply the length of the file (say in bits) divided by the sending rate of link n (say in bits/sec.); adding the propagation delay to the transmission time gives the link traversal time in this case.

For further use in this section, we introduce the following assumptions:

Assumption 1: The Markov processes X_1, \ldots, X_N are mutually independent.

Assumption 2: $\mathbb{P}(D_n < x | \{(Y_j, D_j), j = 1, ..., n - 1\}, Y_n = i) = \mathbb{P}(D_n < x | Y_n = i)$ for all $x > 0, i \in E_n$, n = 1, ..., N.

In words, Assumption 2 says that if the state of link *n* is known at the time T_{n-1} when the file becomes ready for transmission across that link, the traversal time across this link depends neither on the traversal times across links $1, \ldots, n-1$ nor on the state of links $1, \ldots, n-1$ when the file became ready for transmission across these links. When the links behave independently of each other – which will be assumed throughout Section 3 thanks either to Assumption 1 in Sections 3.2-3.3 or to the more restrictive Assumption 3 in Section 3.4 – Assumption 2 is very weak as it only requires that the transmission time of the file on a link does not depend on its *transmission times* across previous links. For instance, this is true when transmission rates are constant, possibly dependent on the link state and the file has a constant size or if the lengths of the file to be transmitted across links $1, \ldots, N$ form mutually independent rvs.

Our first objective is to calculate

$$G_{N,x}(s_1, \dots, s_N) := \mathbb{E}_x[e^{-(s_1D_1 + \dots + s_ND_N)}] \quad (s_i \ge 0, i = 1, \dots, N)$$
(1)

the LST of the joint traversal times across links 1, ..., N, given that the links are initially in state $x \in E$. This calculation will require the knowledge of

$$F_{n,j}(s) := \mathbb{E}_x[e^{-sD_n} | Y_n = j] \quad (s \ge 0, j \in E_n)$$
⁽²⁾

the LST of the traversal time across link n given that the link is in state j when the file becomes available for transmission at the link. Last, introduce the conditional expectation

$$\gamma_{n,j} = \mathbb{E}_x[D_n | Y_n = j] = -F'_{n,j}(0) \quad (j \in E_n).$$
(3)

When Assumption 1 holds the dependence on the initial state *x* can be dropped in both definitions (2) and (3) as D_n does not depend on *x* when the state of link *n* is known at time T_{n-1} .

3.2 Stationary initial link state distribution

When the Markov processes X_1, \ldots, X_N are in steady-steady at time t = 0, with $(\pi_n^*(j), j \in E_n)$ the stationary distribution vector of X_n , rvs D_1, \ldots, D_N are mutually independent under Assumptions 1 and 2 as shown in Appendix A, so that the unconditional LST of the joint link traversal times is given by

$$\mathbb{E}\left[e^{-(s_1D_1+\dots+s_ND_N)}\right] = \prod_{n=1}^N \sum_{j\in E_n} \pi_n^{\star}(j)F_{n,j}(s_n) \tag{4}$$

under Assumptions 1 and 2. In particular,

$$\mathbb{E}[T_N] = \sum_{n=1}^N \sum_{j \in E_n} \pi_n^{\star}(j) \gamma_{n,j}.$$
(5)

Quantities $F_{n,j}(\cdot)$ are calculated in Section 3.5 when the file size is exponentially distributed, and in Section 3.6 for general file size distributions and for different file retransmission scenarii when X_1, \ldots, X_N are two-state Markov processes.

3.3 Arbitrary initial link state distribution

In this section we do not assume that X_1, \ldots, X_N are in steady-steady at time t = 0. This introduces a dependence between the rvs D_1, \ldots, D_N since, for instance, D_n depends on the state of link *n* when the file gets ready to be transmitted on that link (given by $X(T_{n-1})$), a quantity that itself depends on both the initial state of link *n* and on $D_1 + \cdots + D_{n-1}$, the traversal time across links $1, \ldots, n-1$.

Assumption 3: There exist constants $\{c_n(i, j, k), \lambda_n(k)\}_{i,j,k \in E_n}$ such that $(i, j \in E_n, t > 0)$

$$\mathbb{P}(X_n(t) = j | X_n(0) = i) = \sum_{k \in E_n} c_n(i, j, k) e^{-\lambda_n(k)t}.$$
(6)

Thanks to the (Kolmogorov) result $\pi_n(t) = \pi_n(0)e^{\mathbf{Q}_n t}$ ($t \ge 0$), it is well known that (6) holds when \mathbf{Q}_n is diagonalizable. In this case, the constants $\{-\lambda_n(k)\}_{k\in E_n}$ in (6) are the eigenvalues of the matrix \mathbf{Q}_n and the constants $\{c_n(i, j, k)\}_{i,j,k\in E_n}$ relate to the eigenvectors of \mathbf{Q}_n .

A particular case when \mathbf{Q}_n is diagonalizable is when the Markov process X_n is reversible [11, p. 116]. This includes the two-state Markov process, which is investigated in Section 3.4. Being reversible for each *n* does not help in the calculation of $G_{N,x}(s_1, \ldots, s_N)$ (even when these Markov processes are mutually independent) beyond the fact that (6) holds, a fact that we exploit in Section 3.4 when we investigate two-state Markov processes.

Proposition 3.1 below provides a recursive scheme for calculating $G_{n,x}(s_1, \ldots, s_n)$ in terms of the mappings $\{F_{n,j}(\cdot)\}_{n,j}$ introduced in (2).

Proposition 3.1 (LST of joint traversal times)

Under Assumptions 1, 2, and 3

$$G_{1,x}(s_1) = F_{1,x_1}(s_1) \tag{7}$$

and, for n = 2, ..., N,

$$G_{n,x}(s_1,\ldots,s_n) = \sum_{j,k\in E_n} c_n(x_n,j,k) F_{n,j}(s_n) G_{n-1,x}(s_1+\lambda_n(k),\ldots,s_{n-1}+\lambda_n(k))$$
(8)

for any $x = (x_1, ..., x_N) \in E$.

Proof. Fix $x = (x_1, ..., x_N) \in E$. Eq. (7) directly follows from definitions (1) and (2) thanks to $T_0 = 0$. Now let $n \ge 2$. With the shorthand $\mathcal{A}_n((y_i, d_i)) := \{(Y_i = y_i, D_i = d_i), i = 1, ..., n - 1\}$, we find that

$$\begin{aligned} G_{n,x}(s_1,\ldots,s_n) &= \sum_{\substack{y_i \in E_i \\ i=1,\ldots,n-1}} \sum_{j \in E_n} \int_{d_1=0}^{\infty} \cdots \int_{d_{n-1}=0}^{\infty} e^{-\sum_{i=1}^{n-1} s_i d_i} \\ &\times \mathbb{E}_x \bigg[e^{-s_n D_n} \left| \mathcal{A}_n((y_i, d_i)), X_n(D_1 + \cdots + D_{n-1}) = j \right] \\ &\times \mathbb{P}_x(X_n(d_1 + \cdots + d_{n-1}) = j \left| \mathcal{A}_n((y_i, d_i))) d\mathbb{P}_x(Y_i = y_i, D_i < d_i, i = 1, \ldots, n-1) \right. \\ &= \sum_{\substack{y_i \in E_i \\ i=1,\ldots,n-1}} \sum_{j \in E_n} \int_{d_1=0}^{\infty} \cdots \int_{d_{m-1}=0}^{\infty} e^{-\sum_{i=1}^{n-1} s_i d_i} F_{n,j}(s_n) \mathbb{P}_x(X_n(d_1 + \cdots + d_{n-1}) = j) \end{aligned}$$
(9)
 &\times d\mathbb{P}_x(Y_i = y_i, D_i < d_i, i = 1, \ldots, n-1) \\ &= \sum_{j \in E_n} \int_{d_1=0}^{\infty} \cdots \int_{d_{m-1}=0}^{\infty} e^{-\sum_{i=1}^{n-1} s_i d_i} F_{n,j}(s_n) \mathbb{P}_x(X_n(d_1 + \cdots + d_{n-1}) = j) d\mathbb{P}_x(D_i < d_i, i = 1, \ldots, n-1) \\ &= \int_{d_1=0}^{\infty} \cdots \int_{d_{n-1}=0}^{\infty} \sum_{j,k \in E_n} F_{n,j}(s_n) c_n(x_n, j, k) e^{-\sum_{i=1}^{n-1} (s_i + \lambda_n(k)) d_i} d\mathbb{P}_x(D_i < d_i, i = 1, \ldots, n-1) \end{aligned} (10)

$$&= \sum_{j,k \in E_n} F_{n,j}(s_n) c_n(x_n, j, k) G_{n-1,x}(s_1 + \lambda_n(k), \ldots, s_{n-1} + \lambda_n(k)) \end{aligned}$$

where (10) is a consequence of Assumption 3.

To establish (9) we have used the fact that (i) $\mathbb{E}_x \left[e^{-s_n D_n} | \mathcal{A}_n((y_i, d_i)), X_n(D_1 + \dots + D_{n-1}) = j \right] = F_{n,j}(s_n)$ since $X_n(D_1 + \dots + D_{n-1}) = Y_n$ from the definition of Y_n along with the fact that condition on the event $\{\mathcal{A}_n((y_i, d_i)), Y_n = j\}$ the rv D_n only depends on $\{Y_n = j\}$ the latter holding from Assumption 2, and (ii) $X_n(d_1 + \dots + d_{n-1})$ does not depend on $\mathcal{A}_n((y_i, d_i))$ thanks again to Assumption 1. This concludes the proof.

Any statistics of the random vector (D_1, \ldots, D_N) can be obtained from (7)-(8). As an illustration, consider

$$T_n(x) := \mathbb{E}_x[T_n] \tag{11}$$

the expected traversal time across links $1, \ldots, n$ given that the system is in state x at time t = 0. From the relation

$$T_n(x) = -g'_{n,x}(0) \tag{12}$$

with $g_{n,x}(s) := G_{n,x}(s, \ldots, s)$ and Proposition 3.1 we immediately get the following result:

Corollary 3.1 (Expected end-to-end traversal times)

Under Assumptions 1, 2, and 3

$$T_1(x) = -F'_{1,x_1}(0) \tag{13}$$

$$T_{n}(x) = \sum_{j,k \in E_{n}} c_{n}(x_{n}, j, k) \left[\gamma_{n,j} g_{n-1,x}(\lambda_{n}(k)) - g'_{n-1,x}(\lambda_{n}(k)) \right]$$
(14)

for any $x = (x_1, \ldots, x_N) \in E$, $s \ge 0$, where

$$g_{1,x}(s) = F_{1,x_1}(s)$$
(15)
$$g_{-}(s) = \sum_{k=1}^{\infty} c_{-}(x - i_k)F_{-}(s)g_{-}(s + \lambda_{-}(k))$$

$$g_{n,x}(s) = \sum_{j,k \in E_n} c_n(x_n, j, k) F_{n,j}(s) g_{n-1,x}(s + A_n(k))$$
(16)

$$g'_{1,x}(s) = F'_{1,x_1}(s)$$

$$g'_{n,x}(s) = \sum_{j,k \in E_n} c_n(x_n, j, k) \left[F'_{n,j}(s)g_{n-1,x}(s + \lambda_n(k)) + F_{n,j}(s)g'_{n-1,x}(s + \lambda_n(k)) \right]$$

for n = 2, ..., N.

In the next section we address the case where X_1, \ldots, X_N are identical and mutually independent two-state Markov processes. We will show that $T_N(x)$ can be calculated in $O(N^2)$ operations from Corollary 3.1.

3.4 The case of on-off links

We specialize the framework of Section 3.1 to the important case where links behave as independent two-state (on-off) Markov processes.

Furthermore, all links are assumed to be identical, namely they have the same state space $E_n = \{0, 1\}$ and infinitesimal generator

$$\mathbf{Q} = \begin{pmatrix} -\lambda & \lambda \\ \mu & -\mu \end{pmatrix} \tag{17}$$

with $\lambda > 0$ (resp. $\mu > 0$) the transition rate from state 0 (resp. state 1) to state 1 (resp. state 0). In this case $F_{n,i}(s)$ and $\gamma_{n,i}$ do not depend on *n* and will be denoted by $F_i(s)$ and γ_i , respectively, for $i \in \{0, 1\}$. Let $\beta := \mu + \lambda$.

The above typically models the situation where in state 0 the link is down (or off) and cannot transmit anything while in state 1 it is up (or on) and ready to transmit at the same rate at every link.

Assumption 4: Links behave as independent and identical two-state Markov processes with state-space {0, 1}, and no transmission takes place in state 0.

Define $P_{i,j}(t) = \mathbb{P}(X_n(t) = j | X_n(0) = i)$ for $(i, j) \in \{0, 1\}^2$, where we recall that $X_n(t)$ is the state of link *n* at time *t*. Note that the l.h.s. of this definition does not depend on *n* since all links are identical.

The matrix **Q** is diagonalizable since it has two distinct eigenvalues, given by 0 and $-\beta$, so that (6) holds. More specifically

$$P_{1,0}(t) = \pi_0(1 - e^{-\beta t}), \quad P_{0,0}(t) = \pi_0 + \pi_1 e^{-\beta t}$$
(18)

$$P_{0,1}(t) = \pi_1(1 - e^{-\beta t}), \quad P_{1,1}(t) = \pi_1 + \pi_0 e^{-\beta t}$$
(19)

where $\pi_0 =: \mu/\beta$ and $\pi_1 := \lambda/\beta$ are the stationary probabilities that the link is in state 1 and in state 0, respectively. We are interested in calculating $T_N(x)$, the expected end-to-end traversal time.

Proposition 3.2 (Expected end-to-end traversal time for on-off links)

Under Assumptions 2 and 4 for any $x = (x_1, \ldots, x_N) \in \{0, 1\}^N$

$$T_1(x) = x_1 \gamma_1 + \bar{x}_1 \gamma_0 \tag{20}$$

$$T_n(x) = T_{n-1}(x) + \pi_0 \gamma_0 + \pi_1 \gamma_1 + (\gamma_0 - \gamma_1)(\pi_1 \bar{x}_n - \pi_0 x_n) g_{n-1,x}(\beta)$$
(21)

for $n = 2, \ldots, N$, which yields

$$T_N(x) = N(\pi_0 \gamma_0 + \pi_1 \gamma_1) + (\gamma_0 - \gamma_1) \sum_{n=1}^N (\pi_1 \bar{x}_n - \pi_0 x_n) g_{n-1,x}(\beta)$$
(22)

with $g_{0,x}(\beta) := 1$ and where coefficients $\{g_{n-1,x}(\beta), n = 2, ..., N\}$ are calculated from the recursions

$$g_{1,x}(k\beta) = x_1 F_1(k\beta) + \bar{x}_1 F_0(k\beta), \quad k = 1, \dots, N-1$$
(23)

$$g_{n,x}(k\beta) = \phi(k\beta)g_{n-1,x}(k\beta) + (\bar{x}_n\pi_1 - x_n\pi_0)\psi(k\beta)g_{n-1,x}((k+1)\beta),$$
(24)

 $k = 1, \dots, N - n, \ n = 2, \dots, N - 1,$

with

$$\phi(s) := \pi_0 F_0(s) + \pi_1 F_1(s), \quad \psi(s) := F_0(s) - F_1(s). \tag{25}$$

Proof. Since both Assumption 1 (this is obvious) and Assumption 3 (thanks to (18)-(19)) hold when Assumption 4 is satisfied we can use the results in Corollory 3.1. First, note from (18)-(19) that coefficients $c_n(x_n, j, k)$ in (14)

are given by

$$c_n(0,0,0) = c_n(1,0,0) = c_n(1,1,1) = -c_n(1,0,1) = \pi_0$$
(26)

$$c_n(0,0,1) = c_n(0,1,0) = c_n(1,1,0) = -c_n(0,1,1) = \pi_1.$$

(27)

By writing $c_n(x_n, j, k)$ as

$$c_n(x_n, j, k) = x_n c_n(1, j, k) + \bar{x}_n c_n(0, j, k),$$
(28)

and by substituting the values in (26)-(27) into (14), we find after elementary algebra

$$T_{n}(x) = -g'_{n-1,x}(0) + \pi_{0}\gamma_{0} + \pi_{1}\gamma_{1} + (\gamma_{0} - \gamma_{1})(\pi_{1}\bar{x}_{n} - \pi_{0}x_{n})g_{n-1,x}(\beta)$$

$$= T_{n-1}(x) + \pi_{0}\gamma_{0} + \pi_{1}\gamma_{1} + (\gamma_{0} - \gamma_{1})(\pi_{1}\bar{x}_{n} - \pi_{0}x_{n})g_{n-1,x}(\beta)$$
(29)

for n = 2, ..., N - 1, where the latter identity follows from (12). From (13) we get

$$T_1(x) = \gamma_{x_1} = x_1 \gamma_1 + \bar{x}_1 \gamma_0.$$
(30)

Let us focus on the calculation of $g_{n-1,x}(\beta)$ in (29).

From (16), (26)-(27) and (28) we get

$$g_{n,x}(s) = \phi(s)g_{n-1,x}(s) + (\bar{x}_n\pi_1 - x_n\pi_0)\psi(s)g_{n-1,x}(s+\beta)$$
(31)

for n = 2, ..., N, where $\phi(s)$ and $\psi(s)$ are defined in (25), with $g_{1,x}(s) = F_{x_1}(s) = x_1F_1(s) + \bar{x}_1F_0(s)$ from (15). It is easily seen from (31) that coefficients $\{g_{n-1,x}(\beta), n = 2, ..., N\}$ are given by (23)-(24) (Hint: $g_{N,x}(\beta)$ is known if one knows $g_{N-1,x}(\beta)$ and $g_{N-1,x}(2\beta)$ which are both known if one knows $g_{N-2,x}(\beta)$, $g_{N-2,x}(2\beta)$ and $g_{N-2,x}(3\beta)$, etc.).

Finally, (22) is derived from (29)-(30) (Hint: $x_1\gamma_1 + \bar{x}_1\gamma_0 - (\gamma_0 - \gamma_1)(\pi_i\bar{x}_1 - \pi_0x_1) = \pi_0\gamma_0 + \pi_1\gamma_1$), which completes the proof.

Remark 3.1 Proposition 3.2 extends to more general initial conditions than simply $x_i \in \{0, 1\}$. In particular, given an initial state distribution for all of the links at t = 0, $\pi_{n,1}(0)$, n = 1, ..., N, then Proposition 3.2 continues to hold in this case with the replacement of x_n and \bar{x}_n by $\pi_{n,1}(0)$ and $(1 - \pi_{n,1}(0))$ respectively, for n = 1, ..., N.

Since $D_n = T_n - T_{n-1}$ we deduce from (21) that

$$\mathbb{E}_{x}[D_{n}] = \pi_{0}\gamma_{0} + \pi_{1}\gamma_{1} + (\gamma_{0} - \gamma_{1})(\pi_{1}\bar{x}_{n} - \pi_{0}x_{n})\mathbb{E}_{x}[e^{-\beta T_{n-1}}].$$

The sum $\pi_0 \gamma_0 + \pi_1 \gamma_1$ is nothing but the expectation of D_n when link *n* is in steady-state at time t = 0. Therefore, the second term can be seen as a deviation term when the system is not in steady-state at time 0.

Let us determine the numerical complexity of calculating $\mathbb{E}_x[T_N]$ or, equivalently thanks to (22), the complexity of calculating $g_{1,x}(\beta), g_{2,x}(\beta), \dots, g_{N-1,x}(\beta)$. The coefficient $g_{1,x}(\beta)$ can be calculated with (23) in O(N) operations. For each $n = 1, \dots, N-1$, introduce the (N - n)-dimensional vector $\mathbf{v}_n := (g_{n,x}(\beta), \dots, g_{n,x}(\beta(N - n)))^T$ and the (N - (n - 1))-by-(N - n) matrix $\mathbf{M}_n : [M_n(i, j)]_{i,j}$ where non-zero entries are given by

$$M_n(i,i) := \phi(i\beta)$$
 for $i = 1, ..., N - (n-1)$

and

$$M_n(i, i+1) := (\bar{x}_n \pi_n - x_n \pi_0) \psi(i\beta)$$
 for $i = 1, \dots, N - (n-1)$

In this notation, the recursive scheme defined by (23)-(24) can be expressed as

$$\boldsymbol{v}_n = \mathbf{M}_n \, \boldsymbol{v}_{n-1} \tag{32}$$

in matrix form, for n = 2, ..., N - 1. Since the matrix \mathbf{M}_n has only two non-zero entries per row, the calculation of \mathbf{v}_n requires O(N - (n - 1)) operations and therefore the calculation of $\mathbf{v}_1, ..., \mathbf{v}_{N-1}$ or, equivalently, that of $g_{1,x}(\beta), ..., g_{N-1,x}(\beta)$ requires $O(N^2)$ operations. Therefore, $O(N^2)$ operations are required to compute $E_x[T_N]$ for any $x \in \{0, 1\}^N$.

We conclude this section by showing that the traversal time across links $1, \ldots, N$ is stochastically minimized (resp. maximized) when all links are initially in state one (resp. state zero). A more general result is actually proved below. The proof relies on the following assumption, which states that the time to traverse a link depends only on the state of the link at the time of arrival and not on the previous history of the link.

Assumption 5: $\mathbb{P}(D_n < x | \{X_n(t), 0 \le t < T_{n-1}\}, X_n(T_{n-1}) = i) = \mathbb{P}(D_n < x | Y_n = i)$ for $i \in \{0, 1\}$ and for all x > 0, n = 1, ..., N.

Let $D_{n,i}$ denote the traversal time for link *n* when $Y_n = i$, $i \in \{0, 1\}$ and denote by $D_{n,\star}$ the traversal time for link *n* when the transmission starts at the beginning of an on period (this is the case when the file arrives at a link and finds it in the off state). Clearly $D_{n,0} =_d I + D_{n,\star}$, with *I* is an exponentially distributed rv with parameter λ , independent of $D_{n,\star}$. Assumptions 4 and 5 ensure that $D_{n,\star} =_d D_{n,1}$, so that

$$D_{n,0} =_d I + D_{n,1} \tag{33}$$

with $D_{n,1}$ independent of *I*.

Note that under Assumption 4 the relation (33) will be automatically satisfied if the link's transmission rate is constant (Hint: on periods are exponentially distributed).

Last, Assumptions 4 and 5 can be used to establish the following non-pass property.

Lemma 3.1

Under Assumptions 4 and 5 $\mathbb{P}(T_n < x | T_{n-1} = t) \ge \mathbb{P}(T_n < x | T_{n-1} = t')$ for all $x > 0, 0 \le t < t', n = 2, ..., N$.

Proof. This follows from the above relationship between $D_{n,0}$ and $D_{n,1}$ and a standard sample path coupling argument.

We say that vector $\mathbf{y} = (y_1, \dots, y_N)$ dominates vector $\mathbf{x} = (x_1, \dots, x_N)$, and write $\mathbf{x} \leq \mathbf{y}$, if $\sum_{i=1}^n x_i \leq \sum_{i=1}^n y_i$ for $n = 1, \dots, N$.

Proposition 3.3 (Stochastic dominance)

Under Assumptions 2, 4 and 5 if $\mathbf{x} \leq \mathbf{y}$ with $\mathbf{x}, \mathbf{y} \in \{0, 1\}^N$ then $\mathbb{P}_{\mathbf{y}}(T_N \leq t) \geq \mathbb{P}_{\mathbf{x}}(T_N \leq t)$.

The proof makes use of the following two lemmas.

Lemma 3.2

Under Assumptions 2, 4 and 5 if $\mathbf{x} = (x_1, \dots, x_{j-1}, 0, x_{j+1}, \dots, x_N)$ and $\mathbf{y} = (x_1, \dots, x_{j-1}, 1, x_{j+1}, \dots, x_N)$, then $\mathbb{P}_{\mathbf{y}}(T_N \leq t) \geq \mathbb{P}_{\mathbf{x}}(T_N \leq t), \ j = 1, \dots, N.$

Proof. Consider *n* links with initial state configurations $\mathbf{x} = (0, x_2, ..., x_n)$ and $\mathbf{y} = (1, x_2, ..., x_n)$, $x_j \in \{0, 1\}$ for j = 2, ..., n and let $T_n^{\mathbf{x}}$ and $T_n^{\mathbf{y}}$ denote the times at which the file departs link *n* under **x** and **y** respectively. We couple the two systems so that $T_n^{\mathbf{x}} \ge T_n^{\mathbf{y}}$. We couple link 1 under **x** and **y** as follows. Let $D_1^{\mathbf{y}}$ (resp. $D_1^{\mathbf{x}}$) denote the traversal time of link 1 under configuration **y** (resp. **x**). Assumptions 4 and 5 allow us to couple the link under **x** and **y** as $D_1^{\mathbf{x}} = I + D_1^{\mathbf{y}}$, where *I* is an exponential rv with parameter λ independent of $D_1^{\mathbf{y}}$. Hence $T_1^{\mathbf{x}} = I + D_1^{\mathbf{y}}$ and $T_1^{\mathbf{y}} = D_1^{\mathbf{y}}$. Since the initial states of the remaining links are the same under **x** and **y**, we can apply Lemma 3.1 to propagate the delay inequality through the links thus arriving at $\mathbb{P}_{\mathbf{y}}(T_n < t) \ge \mathbb{P}_{\mathbf{x}}(T_n < t)$ for all t > 0 and $n = 1, \ldots, N$.

Consider now the initial configurations

$$\mathbf{x}^{j} = (x_{1}, \dots, x_{j-1}, 0, x_{j+1}, \dots, x_{N})$$

and

$$\mathbf{y}^{j} = (x_{1}, \dots, x_{j-1}, 1, x_{j+1}, \dots, x_{N})$$

for j = 2, ..., N. We couple links 1, ..., j - 1, j + 1, ..., N as above under **x** and **y** and we perform a similar coupling of links *j* as we did for links 1 above.

The file reaches link *j* at the same time, say at time *W*, under both configurations since links 1, ..., j - 1 behave the same. By conditioning on the state of link *j* at time W = w we readily get

$$\mathbb{P}_{\mathbf{y}^{j}}(T_{N} \leq t \mid W = w) - \mathbb{P}_{\mathbf{x}^{j}}(T_{N} \leq t \mid W = w) = \left[\mathbb{P}_{(1,x'_{j+1},\dots,x'_{N})}(T_{N-j+1} \leq t-w) - \mathbb{P}_{(0,x'_{j+1},\dots,x'_{N})}(T_{N-j+1} \leq t-w)\right] \times (P_{1,1}(w)P_{0,0}(w) - P_{0,1}(w)P_{1,0}(w))$$
(34)

where $X_i(w) = x'_i$, i = j + 1, ..., N and we have used the fact that the traversal time across links j, ..., N will be the same under configurations **x** and **y** (thanks to the coupling) when link j is in the same state under **x** and **y** at time

w. We know from the first part of the lemma that

$$\mathbb{P}_{(1,x'_{i+1},\dots,x'_N)}(T_{N-j+1} \le t - w) \ge \mathbb{P}_{0,x'_{i+1},\dots,x'_N}(T_{N-j+1} \le t - w).$$

On the other hand, we find from (18)-(19) that

$$P_{1,1}(w)P_{0,0}(w) - P_{0,1}(w)P_{1,0}(w) = e^{-\beta t}$$
(35)

which proves that the r.h.s. of (34) is nonnegative. Removing the conditioning on w in (34) yields

$$\mathbb{P}_{\mathbf{y}^j}(T_N \le t) \ge \mathbb{P}_{\mathbf{x}^j}(T_N \le t).$$

This completes the proof.

Lemma 3.3

Under Assumptions 2, 4 and 5 if $\mathbf{x} = (x_1, \dots, x_{j-1}, 0, 1, x_{j+2}, \dots, x_N)$ and $\mathbf{y} = (x_1, \dots, x_{j-1}, 1, 0, x_{j+2}, \dots, x_N)$, then $\mathbb{P}_{\mathbf{y}}(T_N \leq t) \geq \mathbb{P}_{\mathbf{x}}(T_N \leq t), t > 0, j = 1, \dots, N - 1.$

Proof. Consider *n* links with initial state configurations $\mathbf{x} = (0, 1, x_3, ..., x_n)$ and $\mathbf{y} = (1, 0, x_3, ..., x_n), x_j \in \{0, 1\}$ for j = 3, ..., n. As in the previous lemma, we will couple the systems under \mathbf{x} and \mathbf{y} so that $T_n^{\mathbf{x}} \ge T_n^{\mathbf{y}}$. We couple the first link under \mathbf{x} and \mathbf{y} as in the proof of Lemma 3.2, namely, $D_1^{\mathbf{x}} = I + D_1^{\mathbf{y}}$, where *I* is an exponential rv with parameter λ independent of $D_1^{\mathbf{y}}$. We now couple the second link under \mathbf{x} and \mathbf{y} . We denote by $D_2^{\mathbf{y}}$ (resp. $D_x^{\mathbf{x}}$) the traversal time of link 2 under configuration \mathbf{y} (resp. \mathbf{x}). We distinguish four cases:

- (1) under **y** (resp. **x**) link 2 is in state 1 at time $T_2^{\mathbf{y}}$ (resp. $T_2^{\mathbf{x}}$). Then $D_2^{\mathbf{y}} = D_2^{\mathbf{x}}$ yielding $T_2^{\mathbf{y}} = D_1^{\mathbf{y}} + D_2^{\mathbf{y}} \le I + D_1^{\mathbf{y}} + D_2^{\mathbf{x}} = T_2^{\mathbf{x}}$;
- (2) under **y** (resp. **x**) link 2 is in state 1 (resp. state 0) at time $T_2^{\mathbf{y}}$ (resp. $T_2^{\mathbf{x}}$). Then $D_2^{\mathbf{x}} = I' + D_2^{\mathbf{y}}$ with I' an exponential rv with parameter λ , yielding $T_2^{\mathbf{y}} = D_1^{\mathbf{y}} + D_2^{\mathbf{y}} \le I + I' + D_1^{\mathbf{y}} + D_2^{\mathbf{y}} = T_2^{\mathbf{x}}$;
- (3) under y (resp. x) link 2 is in state 0 (resp. state 1) at time T_2^y (resp. T_2^x). Then $D_2^y = I + D_2^x$, yielding $T_2^y = I + D_1^y + D_2^x = T_2^x$;
- (4) under **y** (resp. **x**) link 2 is in state 0 at time $T_2^{\mathbf{y}}$ (resp. $T_2^{\mathbf{x}}$). Then $D_2^{\mathbf{y}} = D_{\mathbf{x}}^2$, yielding $T_2^{\mathbf{y}} = D_1^{\mathbf{y}} + D_2^{\mathbf{y}} \le I + D_1^{\mathbf{y}} + D_2^{\mathbf{y}} = T_2^{\mathbf{x}}$.

This shows that $T_2^{\mathbf{y}} \leq T_2^{\mathbf{x}}$. Removing the conditioning gives $\mathbb{P}_{\mathbf{y}}(T_2 < t) \geq \mathbb{P}_{\mathbf{x}}(T_2 < t)$ for all t > 0. Since the initial states of the remaining links are the same under \mathbf{x} and \mathbf{y} , we can apply Lemma 3.1 to propagate the delay inequality through the links thus arriving at $\mathbb{P}_{\mathbf{y}}(T_n < t) \geq \mathbb{P}_{\mathbf{x}}(T_n < t)$ for all t > 0 and $n = 1, \dots, N$.

Consider now the initial configurations

$$\mathbf{x}^{j} = (x_{1}, \dots, x_{j-1}, 0, 1, x_{j+2}, \dots, x_{N})$$

and

$$\mathbf{y}^{j} = (x_1, \dots, x_{j-1}, 1, 0, x_{j+2}, \dots, x_N)$$

for j = 2, ..., N.

We can use a similar argument to that used in Lemma 3.2 to prove that $\mathbb{P}_{\mathbf{v}}(T_N < t) \ge \mathbb{P}_{\mathbf{x}}(T_N < t)$ for this case.

We are now in position to prove Proposition 3.3: **Proof.** The proof of Proposition 3.3 proceeds by constructing a sequence of link state vectors $\mathbf{x} = \mathbf{x}^0 \le \mathbf{x}^1 \le \cdots \le \mathbf{x}^m = \mathbf{y}$ where \mathbf{x}^i and \mathbf{x}^{i+1} differ in either only one position, say *j* with $x_j^i = 0$ and $x_{j+1}^{i+1} = 1$, or in two consecutive positions, say *j* and *j* + 1 with $x_j^i = 0$ and $x_{j+1}^{i+1} = 1$, and $x_{j+1}^{i+1} = 1$. When such a construction exists, then Lemmas 3.2 and 3.3 can be applied to yield the desired result. It is a straightforward exercise to show that such a construction exists when $\mathbf{x} \le \mathbf{y}$. This completes the proof.

Corollary 3.2 (Stochastic bounds)

Under Assumptions 2, 4 and 5 for any initial configuration $x = (x_1, ..., x_N) \in \{0, 1\}^N$

$$\mathbb{P}_{\mathbf{1}}(T_N \le t) \ge \mathbb{P}_{\mathbf{x}}(T_N \le t) \ge \mathbb{P}_{\mathbf{0}}(T_N \le t)$$

for t > 0, where the N-dimensional vectors **1** and **0** are (1, ..., 1) and (0, ..., 0) respectively. In particular,

$$T_N(x^1) \le T_N(x) \le T_N(x^0).$$
 (36)

3.5 Calculation of $F_{n,i}(s)$ for exponential file size distribution and arbitrary set E_n

The goal of this section is to calculate $F_{n,j}(s)$, the LST of the traversal time D_n across link n when the link is in state j at the time the file is ready for transmission (see (2)) and the length of the file (expressed in bits) has an exponential distribution with average length $1/\eta$. Assume that $K_n = |E_n|$. From now on we assume that the link propagation delay is zero. The case when the propagation delay on link n, denoted by Δ_n , is non-zero and constant can simply be obtained from the analysis below by multiplying $F_{n,j}(s)$ by $e^{-s\Delta_n}$ and by adding Δ_n to γ_j for $j \in E_n$.

When link *n* is in state $j \in E_n$ we assume that the transmission rate (in bits/second) is constant and given by $r_n(j) \ge 0$. Whenever $r_n(j) > 0$ the file is transmitted at this rate. If $r_n(j) = 0$ for some $j \in E_n$ transmission halts and resumes as soon as the transmission rate becomes positive. In Section 3.6.1 we will consider the case where transmissions are restarted after a link failure.

To simplify notation we drop the subscript *n* in K_n , $r_n(j)$, $F_{n,j}(s)$, $\gamma_{n,j}$ as well as in \mathbf{Q}_n (the infinitesimal generator of the Markov chain X_n governing the behavior of link *n* – see Section 3.1) for the rest of this section.

It is easily seen that the traversal time D_n of link *n* is the absorption time of the absorbing continous-time Markov chain on the set $E_n \times \{a\}$, with infinitesimal generator

$$\mathbf{M} = \begin{pmatrix} \mathbf{Q} - \eta \mathbf{R} & \eta \mathbf{r} \\ \mathbf{0} & 0 \end{pmatrix}$$
(37)

where $\mathbf{R} := \text{diag}(r(j), j \in E_n)$, $\mathbf{r} := (r(j), j \in E_n)^T$ and $\mathbf{0}$ is the row vector of dimension *K* with all entries equal to zero. States in E_n are transient states and $\{a\}$ is an absorbing state corresponding to the file transmission completion time on link *n*.

The vector of the pdf of the conditional travel times is obtained as (see e.g. [12, Lemma 2.2.2.])

$$(\mathbb{P}(D_n < t \mid Y_n = j), j \in E_n)^T = (\mathbf{I} - e^{(\mathbf{Q} - \eta \mathbf{R})t})\mathbf{1}$$

with 1 the column vector of dimension K whose entries equal one and I the $K \times K$ identity matrix. Hence

$$\underline{F}(s) := (F_j(s), j \in E_n) = \left(\int_0^\infty e^{-st} e^{(\mathbf{Q} - \eta \mathbf{R})t} dt\right) (\eta \mathbf{R} - \mathbf{Q}) \mathbf{1} = \eta (\mathbf{B}(s) - \mathbf{Q})^{-1} \underline{r}$$
(38)

where $\mathbf{B}(s) := \text{diag}(s + \eta r(j), j \in E_n)$ (Hint: $\int_0^\infty e^{-st} e^{\mathbf{A}t} dt = (\mathbf{I} - \mathbf{A})^{-1}$ for any square matrix \mathbf{A} and $(\eta \mathbf{R} - \mathbf{Q})\mathbf{1} = \mathbf{r}$ since $\mathbf{Q}\mathbf{1} = \mathbf{0}^T$).

In particular, the vector of the expected traversal times of link *n* starting from state $Y_n = j$, $j \in E_n$ (defined in (3)) is given by

$$(\boldsymbol{\gamma}_j, j \in E_n)^T = \eta \left(\mathbf{B}(0) - \mathbf{Q} \right)^{-2} \mathbf{r}.$$
(39)

In the next section we show that $F_i(s)$ can be obtained in explicit form for any pdf distribution of Z when E_n has two states and the transmission rate in one of the states is zero (on-off link).

3.6 Calculation of $F_{n,j}(s)$ for on-off links, arbitrary file size distribution and different transmission scenarii

In this section, we calculate $F_{n,j}(s)$ when link *n* is described by an on-off Markov process with state space $E_n = \{0, 1\}$ and transition rates $q_n(0, 1) = \lambda_n$ and $q_n(1, 0) = \mu_n$. Let $r_n(i)$ denote the transmission rate of link *n* when in state $i \in \{0, 1\}$. We assume that $r_n(0) = 0$ and without loss of generality $r_n(1) = 1$. Let $Z \in \mathbb{R}^+$ be a rv and denote by $Z(s) := \mathbb{E}[\exp(-sZ)]$ its LST. We do not make any assumption on the distribution of Z (in particular, Z may be a constant).

For the reason explained at the beginning of Section 3.5 we will assume without loss of generality that the link propagation delay is zero.

To simplify the notation we will drop the superscript *n* in $F_{n,j}(s)$, $\gamma_{n,j}$, λ_n and μ_n .

Two transmission scenarii are investigated. In the first scenario (Section 3.6.1) the file has to be entirely retransmitted if the link switches to the down state during the transmission. We will consider two cases:

- (a) Successive retransmission times across a link are all *identical*;
- (b) Successive retransmission times across a link are iid rvs $\{Z, Z_1, Z_2, \ldots\}$.

Clearly, cases (a) and (b) will yield the same result if Z is a constant. In the second scenario the file transmission is resumed after a link failure (Section 3.6.2).

Throughout $\{U, U_1, U_2, ...\}$ and $\{V, V_1, V_2, ...\}$ are non-negative independent sequences of iid rvs, with $\mathbb{P}(U < x) = 1 - e^{-\mu x}$ and $\mathbb{P}(V < x) = 1 - e^{-\lambda x}$. The rv U_i (resp. V_i) corresponds to the *i*th on period (resp. off period) of a link since the first attempt to transmit the file.

In scenario 1, case (a) (resp. in scenario 2) we assume that sequences $\{U, U_1, U_2, \ldots\}$ and $\{V, V_1, V_2, \ldots\}$ are independent of Z. In scenario 1, case (b) we assume that sequences $\{U, U_1, U_2, \ldots\}$, $\{V, V_1, V_2, \ldots\}$ and $\{Z, Z_1, Z_2, \ldots\}$ are mutually independent.

Since Assumption 2 is satisfied here as the link transmission rate is constant, we get from (33) that

$$F_0(s) = \frac{\lambda}{\lambda + s} F_1(s). \tag{40}$$

As a consequence,

$$\gamma_0 = \frac{1}{\lambda} + \gamma_1. \tag{41}$$

Let $\mathbf{1}_A$ be the indicator function of the event *A*. By convention $\sum_{l=1}^{0} \cdot = 0$.

In the remainder of this section we compute $F_1(s)$ and γ_1 for the different scenarii.

3.6.1 Scenario 1: File entirely retransmitted after link failure

Case (a): Conditioned on $X(T_{n-1}) = 1$, we have

$$D_n =_d \sum_{i \ge 0} \mathbf{1}_{\mathcal{B}_i(Z)} \left(Z + \sum_{l=1}^i (U_l + V_l) \right)$$

with $\mathcal{B}_i(u) := \{U_1 < u, \dots, U_i < u, U_{i+1} \ge u\}$. Note that $\mathcal{B}_i(u) \cap \mathcal{B}_j(u) = \emptyset$ for $i \ne j$ and $\sum_{i\ge 0} \mathbf{1}_{\mathcal{B}_i(u)} = 1$ for any u. We have

$$F_{1}(s) = \int_{0}^{\infty} \mathbb{E}\left[e^{-s\sum_{i\geq0}\mathbf{1}_{\mathcal{B}_{i}(u)}\left(u+\sum_{i=1}^{i}(U_{i}+V_{i})\right)}|Z=u\right]d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} \sum_{i\geq0} \mathbb{P}(\mathcal{B}_{i}(u))\mathbb{E}\left[e^{-s\left(u+\sum_{i=1}^{i}(U_{i}+V_{i})\right)}|Z=u,\mathcal{B}_{i}(u)\right]d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} e^{-su} \sum_{i\geq0} \mathbb{P}(\mathcal{B}_{i}(u))\mathbb{E}\left[e^{-sV}\right]^{i} \mathbb{E}\left[e^{-s\sum_{i=1}^{i}U_{i}}|\mathcal{B}_{i}(u)\right]d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} e^{-su} \sum_{i\geq0} \left(1-e^{-\mu u}\right)^{i} e^{-\mu u} \left(\frac{\lambda}{\lambda+s}\right)^{i} \left(\prod_{i=1}^{i}\int_{x_{i}=0}^{u}e^{-sx_{i}}\frac{\mu e^{-x_{i}\mu}dx_{i}}{1-e^{-\mu u}}\right)d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} e^{-(\mu+s)u} \sum_{i\geq0} \left(\frac{\lambda}{\lambda+s} \cdot \frac{\mu}{\mu+s}\left(1-e^{-(\mu+s)u}\right)\right)^{i} d\mathbb{P}(Z < u)$$

$$= (\lambda+s)(\mu+s) \int_{0}^{\infty} \frac{e^{-(\mu+s)u}}{(\lambda+s)(\mu+s) - \lambda\mu(1-e^{-(\mu+s)u})} d\mathbb{P}(Z < u). \tag{42}$$

If Z is exponentially distributed with parameter η , we find

$$F_1(s) = (\lambda + s)(\mu + s) \int_0^\infty \frac{\eta e^{-(\mu + s + \eta)u}}{(\lambda + s)(\mu + s) - \lambda\mu(1 - e^{-(\mu + s)u})} \, du.$$
(43)

The integral in (43) has no explicit form but can be easily computed numerically for given parameters μ , λ , η , s. If Z is a constant, we find $(\lambda + s)(\mu + s)e^{-(\mu + s)Z}$

$$F_1(s) = \frac{(\lambda + s)(\mu + s)e^{-(\mu + s)Z}}{(\lambda + s)(\mu + s) - \lambda\mu(1 - e^{-(\mu + s)Z})}$$
(44)

and

$$\gamma_1 = \left(\frac{1}{\lambda} + \frac{1}{\mu}\right) \left(e^{\mu Z} - 1\right). \tag{45}$$

Case (b): Conditioned on $X(T_{n-1}) = 1$, we have

$$D_n =_d \sum_{i \ge 0} \mathbf{1}_{C_i(Z_1, \dots, Z_{i+1})} \left(Z_{i+1} + \sum_{l=1}^i (U_l + V_l) \right)$$

with

$$C_i(u_1,\ldots,u_{i+1}) := \{U_1 < u_1,\ldots,U_i < u_i, U_{i+1} \ge u_{i+1}\}.$$

Hence,

$$F_{1}(s) = \sum_{i \ge 0} \mathbb{P}(C_{i}(Z_{1}, \dots, Z_{i})) \mathbb{E}\left[e^{-s(Z_{i+1} + \sum_{l=1}^{i}(U_{l} + V_{l}))} | C_{i}(Z_{1}, \dots, Z_{i})\right]$$

$$= \sum_{i \ge 0} \mathbb{P}(U < Z)^{i} \mathbb{P}(U > Z) \mathbb{E}\left[e^{-sV}\right]^{i} \mathbb{E}\left[e^{-s(Z_{i+1} + \sum_{l=1}^{i}U_{l})} | C_{i}(Z_{1}, \dots, Z_{i})\right]$$

$$= \sum_{i \ge 0} (1 - Z(\mu))^{i} Z(\mu) \left(\frac{\lambda}{\lambda + s}\right)^{i} h_{i}(s)$$
(46)

by using the identities

$$\mathbb{P}(U > Z) = \int_0^\infty \mu e^{-\mu x} \mathbb{P}(Z < x) dx = Z(\mu)$$
$$|B_i(Z_1, \dots, Z_i) = 1].$$

where $h_i(s) := \mathbb{E}\left[e^{-s(Z_{i+1}+\sum_{l=1}^i U_l)} | B_i(Z_1, \dots, Z_i)\right]$ Let us evaluate $h_i(s)$. We have

$$\begin{split} h_{i}(s) &= \int_{z_{1}=0}^{\infty} \cdots \int_{z_{i+1}=0}^{\infty} \int_{x_{1}=0}^{z_{1}} \cdots \int_{x_{i}=0}^{z_{i}} \int_{x_{i+1}=z_{i+1}}^{\infty} \mu^{i+1} e^{-(\mu+s)\sum_{l=1}^{i+1}x_{l}} \frac{dx_{i+1}d\mathbb{P}(Z < z_{l+1})^{i}}{\prod_{l=1}^{i}} \frac{dx_{l}d\mathbb{P}(Z < z_{l})}{\mathbb{P}(Z_{l} > X_{l})} \\ &= \left(\int_{z=0}^{\infty} \frac{\mu}{\mu+s} \left(1 - e^{-(\mu+s)z}\right) \frac{d\mathbb{P}(Z < z)}{1 - Z(\mu)}\right)^{i} \int_{z=0}^{\infty} e^{-(\mu+s)z} \frac{d\mathbb{P}(Z < z)}{Z(\mu)} \\ &= \left(\frac{\mu}{\mu+s} \left(\frac{1 - Z(\mu+s)}{1 - Z(\mu)}\right)\right)^{i} \frac{Z(\mu+s)}{Z(\mu)}. \end{split}$$

Introducing the above into (46) gives

$$F_1(s) = \frac{(\lambda + s)(\mu + s)Z(\mu + s)}{(\lambda + s)(\mu + s) - \lambda\mu(1 - Z(\mu + s))}$$
(47)

from which we get

$$\gamma_1 = \left(\frac{1}{\lambda} + \frac{1}{\mu}\right) \left(\frac{1 - Z(\mu)}{Z(\mu)}\right). \tag{48}$$

If Z is constant, yielding $Z(\mu + s) = e^{-(\mu+s)Z}$, then (47) (resp. (48)) reduces to (44) (resp. (45)), as expected.

3.6.2 Scenario 2: File retransmission resumes after link failure

Conditioned on $X(T_{n-1}) = 1$, we have

$$D_n = Z + \sum_{i \geq 0} \mathbf{1}_{\mathcal{D}_i(Z)} \sum_{l=1}^i V_l$$

with $\mathcal{D}_i(u) := \{U_1 + \ldots + U_i < u \le U_1 + \ldots + U_{i+1}\}.$

We have

$$F_{1}(s) = \int_{0}^{\infty} e^{-su} \mathbb{E}\left[e^{-s\sum_{i\geq 1}\mathbf{1}_{\mathcal{D}_{i}(u)}\sum_{i=1}^{i}V_{i}} | Z = u\right] d\mathbb{P}(Z < u)$$

$$= \sum_{i\geq 0} \mathbb{E}\left[e^{-sV}\right]^{i} \int_{0}^{\infty} e^{-su} \mathbb{P}(C_{i}(u)) d\mathbb{P}(Z < u)$$

$$= \sum_{i\geq 0} \left(\frac{\lambda}{\lambda+s}\right)^{i} \int_{0}^{\infty} e^{-su} (\mathbb{P}(U_{1} + \dots + U_{i} < u) - \mathbb{P}(U_{1} + \dots + U_{i+1} < u)) d\mathbb{P}(Z < u)$$

$$= \sum_{i\geq 0} \left(\frac{\lambda}{\lambda+s}\right)^{i} \int_{0}^{\infty} e^{-(\mu+s)u} \frac{(\mu u)^{i}}{i!} d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} e^{-(\mu+s)u} \sum_{i\geq 0} \frac{((\lambda\mu u)/(\lambda+s))^{i}}{i!} d\mathbb{P}(Z < u)$$

$$= \int_{0}^{\infty} e^{-u((\mu+s)(\lambda+s)-\mu\lambda)} d\mathbb{P}(Z < u)$$

$$= Z\left(\frac{(\lambda+s)(\mu+s) - \lambda\mu}{\lambda+s}\right)$$
(50)

where we have used the identity $\mathbb{P}(U_1 + \dots + U_l < u) = 1 - \sum_{j=0}^{l-1} e^{-\mu u} (\mu u)^j / j!$ (distribution of an Erlang rv with *l* stages) to derive (49). From (50) we find

$$\gamma_1 = \left(1 + \frac{\mu}{\lambda}\right) \mathbb{E}[Z]. \tag{51}$$

4 Application of the results in Sections 3.6-3.5

In this section we briefly discuss when results in Sections 3.5-3.6 can be used to calculate the joint LST of the endto-end traversal time obtained in Proposition 3.1 or the expected end-to-end traversal time obtained in Proposition 3.2. We only need to ensure that Assumption 2 is met. This will be the case if the file sizes for links $1, \ldots, N$ are mutually independent. In particular, all the results obtained in Section 3.6 can be used when the file has a constant size.

5 Dependent on-off links in series: the case of local interactions

In this section we consider a special class of dependent on-off links where the dependencies are described by local interactions among the links. Consider *N* on-off links in series, labeled 1, 2, ..., N. Let $X_n(t) \in \{0, 1\}$ be the state of link *n* at time $t \ge 0$, where link *n* is up if $X_n(t) = 1$ and down otherwise. Let $X(t) = (X_1(t), ..., X_N(t)) \in \{0, 1\}^N$ be the state of all links at time *t*.

We are interested in constructing a stationary process $\{X(t)\}_t$ where the link states are dependent and where we can induce the Pearson correlation coefficient $\xi_{X_n(t),X_{n+1}(t)} := \xi$ to take any value between -1 and 1, and whose value will

be specified shortly. Here, the Pearson correlation coefficient for two real valued rvs X and Y is defined as

$$\xi_{X,Y} = \frac{cov(X,Y)}{\sigma_X \sigma_Y}.$$

Moreover, we would like the link state process $\{X_n(t)\}_t$ to be described by a stationary Markov chain with infinitesimal generator

$$\mathbf{Q} = \begin{pmatrix} -\lambda & \lambda \\ \mu & -\mu \end{pmatrix}$$
(52)

for all *n*. In the following, X_n will denote the stationary state of link *n*. The distribution of X_n is given by $\pi(0) := \mathbb{P}(X_n = 0) = 1/(1 + \rho)$ and $\pi(1) := \mathbb{P}(X_n = 1) = \rho/(1 + \rho)$ where $\rho := \lambda/\mu$.

5.1 Stationary expected end-to-end traversal time

We consider two cases, $\xi \ge 0$ (positive correlations) and $\xi < 0$ (negative correlations).

5.1.1 Positive correlations

We couple the link process at link n + 1 to the link process of link n as follows. Here $0 \le r \le 1$,

- link *n* behaves according to a Markov chain with infinitesimal generator **Q**;
- when link *n* transitions from zero to one (X_n(t) : 0 → 1) at time *t*, and link *n* + 1 is in state zero at that time, then link *n* + 1 transitions to one (X_{n+1}(t) : 0 → 1) with probability *r* and remains unchanged otherwise. Furthermore, link *n* + 1 transitions from state zero to one according to a Poisson process with parameter *r*λ independent of the behavior of link *n* while in state zero;
- if link *n* transitions from one to zero (X_n(t) : 1 → 0) at time t, and link n + 1 is in state one at that time, then link n + 1 transitions to zero (X_{n+1}(t) : 1 → 0) with probability r and remains unchanged otherwise. Furthermore, link n + 1 transitions from state one to zero according to a Poisson process with parameter r
 µ independent of the behavior of link n while in state one;
- otherwise transitions proceed independently for the two links.

Note that the resulting process exhibits a combined spatial-temporal Markov property, i.e.,

$$\mathbb{P}(X_{n_1}(t_1) = x_1 | X_{n_2}(t_2) = x_2, \dots, X_{n_m}(t_m) = x_m) = \mathbb{P}(X_{n_1}(t_1) = x_1 | X_{n_2}(t_2) = x_2), \quad x_j \in \{0, 1\}, 1 \le j \le m$$

for all $n_1 \ge n_2 \ge \cdots \ge n_m \ge 1$, $t_1 \ge t_2 \ge \cdots \ge t_m$, and $m = 3, \ldots$. The link states $X_n(t)$ and $X_{n+1}(t)$ evolve according to the following equations:

$$dX_n = (1 - X_n)dN_{n,0} - X_n dN_{n,1}$$

$$dX_{n+1} = (1 - X_n)[(1 - X_{n+1})(B_{n+1}(t)dN_{n,0}(1 - B_{n+1}(t))dN_{n+1,0}) - X_{n+1}dN_{n+1,1}]$$

$$+X_n[(1 - X_{n+1})dN_{n+1,0} - X_{n+1}(B_{n+1}(t)dN_{n,1} + (1 - B_{n+1})(t)dN_{n+1,1})].$$

where, $\{N_{i,0}(t)\}_t$ and $\{N_{i,1}(t)\}_t$ are mutually independent Poisson processes with rates λ and μ respectively, and $B_i(t)$ is a Bernoulli rv that takes value one with probability *r* satisfying $B_i(t_1), \ldots, B_i(t_k)$ is an independent sequence for any $0 < t_1 < \cdots < t_k, k = 2, \ldots, i = 1, \ldots, N$.

It follows that the process $\{(X_n(t), X_{n+1}(t))\}_t$ is described by a Markov chain with the infinitesimal generator

$$\mathbf{R} = \mu \begin{pmatrix} -(2-r)\rho & \bar{r}\rho & \bar{r}\rho & r\rho \\ 1 & -(1+\rho) & 0 & \rho \\ 1 & 0 & -(1+\rho) & \rho \\ r & \bar{r} & \bar{r} & -(2-r) \end{pmatrix}$$
(53)

and has stationary distribution

$$\pi(0,0) = \frac{2-r+r\rho}{(2-r)(1+\rho)^2}, \quad \pi(0,1) = \pi(1,0) = \frac{2(1-r)\rho}{(2-r)(1+\rho)^2}, \quad \pi(1,1) = \rho \frac{(2-r)\rho+r}{(2-r)(1+\rho)^2}.$$

These can be used to compute $\xi_{X_n,X_{n+1}} := \xi$ yielding

$$\xi = \frac{\pi(1,1) - \pi(1)^2}{\pi(1)\pi(0)} = \frac{r}{2-r}.$$
(54)

As expected the correlation coefficient is positive, increases in *r*, and takes values zero when r = 0 and one when r = 1. Expressing the stationary distribution in terms of ξ yields

$$\pi(0,0) = \frac{1+\xi\rho}{(1+\rho)^2}, \quad \pi(0,1) = \pi(1,0) = \frac{\rho(1-\xi)}{(1+\rho)^2}, \quad \pi(1,1) = \frac{\rho(\rho+\xi)}{(1+\rho)^2}.$$
(55)

We focus now on the time required to transmit a file through this network. As before, D_n denotes the time required for the file to traverse link *n*. This time consists of two components. The first is the delay incurred waiting for the link to first come up (it is zero if the link is already up when the file arrives). The second component, S_n , is the time required to service the file once the link comes up for the first time; it depends on the retransmission scenario that is used. We assume that that S_1, \ldots, S_N are mutually independent rvs and define $S_n(s) := \mathbb{E}[\exp(-sS_n)]$.

Observe that $S(s) = F_1(s)$, where $F_1(s)$ is computed in Section 3.6 for different retransmission scenarii and file size distributions.

Our objective is to calculate $G_N(s) := \mathbb{E}[e^{-sT_N}]$, with $T_n = \sum_{n=1}^N D_n$ the path traversal time. Recall that Y_n is the state of link *n* at the time that the file arrives at that link. Clearly, $\mathbb{P}(Y_1 = i) = \pi(i)$ for i = 0, 1. The conditional

probability distribution for Y_{n+1} given that $Y_n = j$, j = 0, 1, is

$$\mathbb{P}(Y_{n+1} = i | Y_n = j) = \mathbb{P}(X_{n+1} = i | X_n = 1), \quad i, j = 0, 1$$
$$= \pi(1, i)/\pi(1).$$

Hence $\{Y_n\}_{n\geq 1}$ is a sequence of mutually independent rvs with distribution given by $\mathbb{P}(Y_1 = i) = \pi(i)$ and for $n \geq 2$,

$$\mathbb{P}(Y_n = i) = \begin{cases} (1 - \xi)/(1 + \rho) & \text{if } i = 0 \\ \\ (\rho + \xi)/(1 + \rho) & \text{if } i = 1. \end{cases}$$

It follows that $\{D_n\}_{n\geq 1}$ is also a sequence of mutually independent rvs, and moreover the sequence $\{D_n\}_{n\geq 2}$ is iid. This yields (Hint: $D_n = S_n + \mathbf{1}_{(Y_n=0)}\tau$ with τ an exponential rv with rate λ , independent of S_n and Y_n)

$$G_N(s) = \frac{(\lambda + (\lambda + s)\rho)(\lambda(1 - \xi) + (\lambda + s)\rho)^{N-1}}{(\lambda + s)^N(1 + \rho)^N} \prod_{n=1}^N S_n(s)$$
(56)

where we have used the fact that $P(Y_1 = 0) = 1/(1 + \rho)$ and $P(Y_1 = 1) = \rho/(1 + \rho)$.

The expected path traversal time is given by

$$\mathbb{E}[T_N] = N \sum_{n=1}^{N} E[S_n] + \frac{N}{\lambda(1+\rho)} - \frac{\xi(N-1)}{\lambda(1+\rho)}.$$
(57)

Note that the link correlation affects $\mathbb{E}[T_N]$ through the third term and that positive correlation decreases the expected path traversal time in a linear fashion. In the absence of correlation (i.e. when $\xi = 0$) we retrieve the expected result that $\mathbb{E}[T_N] = \sum_{n=1}^{N} \mathbb{E}[S_n] + N/(\lambda(1 + \rho))$, since in this case $\mathbb{E}[D_n] = \mathbb{E}[S_n] + \pi(0)/\lambda = \mathbb{E}[S_n] + 1/(\lambda(1 + \rho))$. When the correlation is maximum (i.e. $\xi = 1$) we retrieve the expected result that $\mathbb{E}[T_N] = \sum_{n=1}^{N} \mathbb{E}[S_n] + 1/(\lambda(1 + \rho))$ where the latter term is the average wait of the file before beginning its transmission on link 1. The expected path traversal time is minimized when $\xi = 1$ since the file will always find an active link except possibly at link 1.

5.1.2 Negative dependencies

As in the previous section each link to be governed by a two-state Markov chain with infinitesimal **Q** given by (52) but exhibiting negative correlation. Except for the case $\lambda = \mu$, it is not possible to generate a setting where $\xi = -1$ as will be observed below. We propose the following algorithm for constructing the link process at link n + 1 in terms of the process at link n. We assume that $\lambda \ge \mu$ or equivalently $\rho \ge 1$.

We couple the link process at link n + 1 to the link process of link n as follows:

• link *n* behaves according to the Markov chain with infinitesimal generator **Q**;

- if links *n* and *n* + 1 are in states zero and one respectively, then if link *n* transitions to state one, then, with probability $r\mu/\lambda \ln n + 1$ transitions to state zero. Furthermore, $\ln n + 1$ transitions from state one to state zero according to a Poisson process with rate $\bar{r}\mu$ independent of the behavior of link *n* while in state zero;
- if links *n* and *n* + 1 are in states one and zero respectively, then if link *n* transitions to zero, then with probability *r* link *n* + 1 transitions to state one. Furthermore, link *n* + 1 transitions from state zero to state one according to a Poisson process with rate $\lambda r\mu$ independent of the behavior of link *n* while in state one;
- otherwise transitions proceed independently for the two links.

This process also exhibits the combined spatial-temporal Markov property (53).

Link states $X_n(t)$ and $X_{n+1}(t)$ evolve according to the following dynamics:

$$dX_n = (1 - X_n)dN_{n,0} - X_n dN_{n,1}$$

$$dX_{n+1} = (1 - X_n)[(1 - X_{n+1})dN_{n+1,0} - X_{n+1}(C_{n+1}(t)dN_{n,0} + dN_{n+1,1})]$$

$$+X_n[(1 - X_{n+1})(B_{n+1}(t)dN_{n,1} + dN_{n+1,2}) - X_{n+1}dN_{n+1,1}].$$

Here, $\{N_{i,0}(t)\}_t$, $\{N_{i,1}(t)\}_t$ and $\{N_{i,2}(t)\}_t$ are mutually independent Poisson processes with rates λ , μ and $\lambda - r\mu$ respectively, $B_i(t)$ is a Bernoulli rv taking value one with probability r and $\{B_i(t_j)\}_{j=1}^k$ is an independent sequence of these rv's for any $0 < t_1 < \cdots < t_k$, $k = 2, \ldots$, and $C_i(t)$ is a Bernoulli rv taking value one with probability $r\mu/\lambda$ and $\{C_i(t_j)\}_{j=1}^k$) is an independent sequence of these rv's for any $0 < t_1 < \cdots < t_k$, $k = 2, \ldots, N$.

It follows that the process $\{(X_n(t), X_{n+1}(t))\}_t$ is described by a Markov chain with the following infinitesimal generator,

$$\mathbf{R} = \mu \begin{pmatrix} -2\rho & \rho & \rho & 0\\ \bar{r} & -(\bar{r}+\rho) & r & \rho-r\\ \bar{r} & r & -(\bar{r}+\rho) & \rho-r\\ 0 & 1 & 1 & -2 \end{pmatrix}$$

and has stationary distribution

$$\pi(0,0) = \frac{\bar{r}}{(1+\rho)(\bar{r}+\rho)}, \quad \pi(0,1) = \pi(1,0) = \frac{\rho}{(1+\rho)(\bar{r}+\rho)}, \quad \pi(1,1) = \frac{\rho(\rho-r)}{(1+\rho)(\bar{r}+\rho)}.$$
(58)

This yields the Pearson correlation coefficient

$$\xi = \frac{\pi(1,1) - \pi(1)^2}{\pi(1)\pi(0)} = \frac{-r}{\bar{r} + \rho}.$$
(59)

for $0 \le r \le 1$, which generates a Pearson coefficient within the range $[-1/\rho, 0]$. As expected the correlation is negative and decreases in r. Expressing the stationary distribution (58) in terms of ξ yields

$$\pi(0,0) = \frac{1+\rho\xi}{(1+\rho)^2}, \quad \pi(0,1) = \pi(1,0) = \frac{\rho(1-\xi)}{(1+\rho)^2}, \quad \pi(1,1) = \frac{\rho(\rho+\xi)}{(1+\rho)^2}.$$
(60)

Observe that the stationary distributions found for positive (see (55)) and negative (see (60)) correlations are identical as a function of ξ . This implies that in both cases the stationary performance measures will have the same form as function of ξ under the enforced assumption that the rvs S_1, \ldots, S_N are mutually independent rvs, with S_n the transmission time across link *n* once that link comes up for the first time. In particular (see (57)),

$$\mathbb{E}[T_N] = \sum_{n=1}^N \mathbb{E}[S_n] + \frac{N}{\lambda(1+\rho)} - \frac{\xi(N-1)}{\lambda(1+\rho)}$$
(61)

for negative correlations.

The case where $\mu > \lambda$ (corresponding to $\rho < 1$) proceeds along similar lines as the case $\rho \ge 1$ yielding a Pearson correlation coefficient $\xi = -\rho r/(1 + \rho \bar{r})$ within the range $[-\rho, 0]$ and same stationary distribution (58) and, in particular same expected path traversal time (61), as function of ξ . This shows that for every ρ we can generate correlations for $\xi \in [-\min\{\rho, 1/\rho\}, 0]$. As announced earlier this is in contrast with the case of positive correlations where one can generate a Pearson coefficient in the entire range [0, 1] for any value of the model parameter ρ .

We conclude from the analysis in Sections 5.1.1-5.1.2 that the mapping $\xi \to \mathbb{E}[T_N]$ is a linear and non-increasing. This mapping is plotted in Figure 7 when $\mathbb{E}[S] := \mathbb{E}[S_n]$ for all *n* and for different values of ρ (see Section 6 for detail).

6 Numerical results

We first consider the transmission scenario investigated in Section 3.6.1 where all links are independent and identical on-off links with λ (resp. μ) the transition from state 0 (off) to state 1 (on) (resp. from state 1 to state 0). On each link the transmission rate is one and the propagation delay is taken to be zero (introducing a propagation delay for each link is straightforward as explained at the beginning of Section 3.5). Recall that the stationary distribution to find a link in state 1 (resp. in state 0) is $\pi(0) = \mu/(\lambda + \mu)$ (resp. $\pi(1) = \lambda/(\lambda + \mu)$). When the link switches to the off-state during the transmission the file is entirely retransmitted when the link switches back to the on-state. In this scenario $F_1(s)$ and γ_1 are given by (44) and (45), respectively, and $F_0(s)$ and γ_0 are obtained from (40) and (41), respectively.

We assume that the length of the file is constant and equals Z, namely, in the absence of failures Z units of time are needed to transmit the file on a link. Recall that cases (a) and (b) in scenario 1 are identical when Z is constant. Without loss of generality we take Z = 1.

We select the expected on period duration, $1/\mu$, so that the file will be successfully transmitted during this period with probability 0.95, i.e. $\mathbb{P}(Z < U) = 0.95$ with U an exponential r.v. with parameter μ (and Z = 1). We find $\mu = -\log(0.95)$ which gives $1/\mu \approx 19.495$.

We are interested in calculating and comparing the expected end-to-end file transmission time for different number of links in series and different initial link states. More precisely, Figures 1-2 display the mappings $N \rightarrow T_N(x)$ for $N \in [1, 2, ..., 20]$, for $x = x^1$ (all links are initially in state 1), $x = x^0$ (all links are initially in state 0) and $x = x^*$ (all links are initially in steady-state). In Figure 1 (resp. Figure 2) $\lambda = 3\mu$ (resp. $\lambda = 9\mu$) so that 75% of the time (resp. 90% of the time) a link will be in state on, namely $\pi(1) = 0.75$ (resp. $\pi(1) = 0.9$).

For $x \in \{x^1, x^0\}$, $T_N(x)$ is computed for each N by using Proposition 3.2. As to the calculation of $T_N(x^*)$ we used (5) and (41) to find that $T_N(x^*) = N(\pi_1\gamma_1 + \pi_0\gamma_0) = N/(\lambda + \mu) + N\gamma_1$.

We now consider the setting in Section 5 when $E[S] := E[S_n]$ for n = 1, ..., N: we have plotted the mapping $\xi \to \mathbb{E}[T_N]$ in Figure 7 for three different values of ρ and $\mu = -\log(0.95)$, where $\mathbb{E}[T_N] = N\mathbb{E}[S] + (N - \xi(N - 1))/(\lambda(1 + \rho))$ is the expected traversal time of N = 10 correlated links in series and ξ is the Pearson correlation coefficient that quantifies the degree of correlation between two adjacent links as defined in Section 5. As noted in Section 5 the local dependency scheme that we have introduced allows one to generate any value of ξ in [0, 1] when $\rho = 1$ while when $\rho = 1/2$ and $\rho = 2$ it can only take value in the interval [-1/2, 0]. Here, the transmission scenario is that of Section 3.6.2 with constant file size Z = 1, so that $\mathbb{E}[S] = 1 + 1/\rho$ from (51). When $\rho = 1$, $\mathbb{E}[T_{10}]$ ranges from 205.20 obtained for $\xi = -1$ (maximum negative correlation) to 29.74 obtained for $\xi = 1$ (maximum positive correlation).

7 Concluding remarks

In this paper, we have investigated the time needed for a file to traverse a series of communication links whose physical conditions may vary over time. We have modeled the dynamics of each link as a finite-state Markov process. For statistically independent links we have obtained a recursive scheme for computing the LTS of the transient joint traversal time across the links, from which we have derived a recursive scheme for calculating the transient expected traversal time of a path. When specialized to a series on N on-off links, the latter result yields a scheme of complexity $O(N^2)$. We have also considered particular dependency structures between adjacent links (positive and negative) and have obtained explicit results for the stationary expected traversal time across a series of communication links as a function of the Pearson correlation coefficient between two adjacent links. All of these results require the knowledge of either the LST or the expectation of the link's traversal time given the state of the link when the file becomes available for transmission is fixed. These quantities have been calculated for various file transmission scenarii. We have also provided numerical examples of the lower and upper bounds that we have established for the transient expected path traversal times across a path composed of independent and identical on-off links and have displayed the expected traversal times of dependent links as a function of the correlation coefficient between adjacent links.



Figure 1: $N \to T_N(x)$ for $x \in \{x^1, x^0, x^*\}$, $\lambda = 3\mu$, $\mu = -\log(0.95)$ (yielding $(\pi(0), \pi(1)) = (0.25, 0.75)$) when transmission scenario 1 is used with Z = 1.

A Appendix: Independence of link traversal times when links initially in steady-state

Recall that $\pi_n^{\star}(i)$ is the stationary probability that link *n* is in state $i \in E_n$.

For any $x_n > 0$, $i_n \in E_n$, n = 1, ..., N,

$$\begin{split} \mathbb{P}(D_1 \leq x_1, \dots, D_N \leq x_N) &= \sum_{\substack{i_j \in E_j \\ j=1,\dots,N}} \mathbb{P}(D_1 \leq x_1, \dots, D_N \leq x_N, Y_1 = i_1, \dots, Y_N = i_N) \\ &= \sum_{\substack{i_j \in E_j \\ j=1,\dots,N}} \mathbb{P}(D_N \leq x_N \mid D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_N = i_N) \\ &\times \mathbb{P}(D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_N = i_N) \\ &= \sum_{\substack{i_j \in E_j \\ j=1,\dots,N}} \mathbb{P}(D_N \leq x_N \mid Y_N = i_N) \mathbb{P}(D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_N = i_N) \end{split}$$



Figure 2: $N \rightarrow T_N(x)$ for $x \in \{x^1, x^0, x^*\}$, $\lambda = 9\mu$, $\mu = -\log(0.95)$ (yielding $(\pi(0), \pi(1)) = (0.1, 0.9)$) when transmission scenario 1 is used with Z = 1.

by using Assumption 2 with n = N. On the other hand,

$$\begin{split} \mathbb{P}(D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_N = i_N) \\ &= P(Y_N = i_N \mid D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_{N-1} = i_{N-1}) \\ &\times \mathbb{P}(D_1 \leq x_1, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_{N-1} = i_{N-1}) \\ &= \pi_N^{\star}(i_N) \mathbb{P}(D_1 \leq x_1, \dots, D_{N-1} \leq x_{N-1}, Y_1 = i_1, \dots, Y_{N-1} = i_{N-1}). \end{split}$$

To derive the above we have used the property that link *N* does not depend on links $1, \ldots, N-1$ from Assumption 1, along with the assumption that link *N* is in steady-state which implies that $\mathbb{P}(Y_N = i_N) = \pi_N^*(i_N)$. Because links $1, \ldots, N-1$ are mutually independent, we can iterate this process to yield

$$\mathbb{P}(D_1 \le x_1, \dots, D_N \le x_N) = \sum_{\substack{i_j \in E_j \\ j=1,\dots,N}} \prod_{k=1}^N \mathbb{P}(D_k \le x_k \mid Y_k = i_k) \pi_k^{\star}(i_k)$$
$$= \mathbb{P}(D_1 \le x_1) \times \dots \times \mathbb{P}(D_N \le x_N).$$

References

 R. W. Hall, The Fastest Path Through a Network with Random Time-Dependent Travel Times, Transportation Science 20 (3) (1986) 182–188.



Figure 3: $\xi \to \mathbb{E}[T_{10}]$ for $\mu = -\log(0.95)$ and three values of ρ ($\rho = 1/2, 1, 2$ yielding ($\pi(0), \pi(1)$) = (1/2, 1/2), (2/3, 1/3), (1/3, 2/3), respectively) when transmission scenario 2 is used with Z = 1.

- [2] G. Song, I. Chabini, Optimal Routing Policy Problems in Stochastic Time-Dependent Networks, Transportation Research Part B 40 (2) (2006) 93–122.
- [3] A. Ferreira, Building a Reference Combinatorial Model for Manets, IEEE Network 18 (5) (2004) 24–29.
- [4] S. Jain, K. Fall, R. Patra, Routing in a Delay Tolerant Network, in: Proc. of ACM SIGCOMM, Computer Communication Review, Vol. 34, New York, NY, USA, 2004, pp. 145–158.
- [5] A. E. F. Clementi, A. Monti, F. Pasquale, R. Silvestri, Communication in Dynamic Radio Networks, in: Proc. of 26th ACM Symp. on Principles of Distributed Computing (PoDC), Portland, OR, USA, 2007, pp. 205–214.
- [6] D. Figueiredo, P. Nain, B. Ribeiro, E. de Souza e Silva, D. Towsley, Characterizing Continuous Time Random Walks on Time Varying Graphs, in: Proc. of joint ACM SIGMETRICS - Performance conf., Performance Evaluation Review, Vol. 40, London, UK, 2012, pp. 307–318.
- [7] A. E. F. Clementi, C. Macci, A. Monti, F. Pasquale, R. Silvestri, Flooding Time in Edge-Markovian Dynamic Graphs, in: Proc. of 27th ACM Symp. on Principles of Distributed Computing (PoDC), Toronto, Canada, 2008, pp. 213–222.
- [8] P. Nain, D. Towsley, A. Bar-Noy, P. Basu, M. Johnson, F. Yu, Estimating End-to-End Delays Under Changing Conditions, in: Proc. ACM CHANTS, 2013, pp. 1–6.

- [9] T. M. Liggett, Interactive Particle Systems, Springer Verlag, 1985.
- [10] P. Buchholz, I. Felko, PH-Graphs for Analyzing Shortest Path Problems with Correlated Traveling Times, Computers & Operations Research 59 (2015) 51–65.
- [11] J. Keilson, A Review of Transient Behavior in Regular Diffusion Birth-Death Processes. Part II, Journal of Applied Probability 2 (1965) 405–428.
- [12] M. F. Neuts, Matrix-Geometric Solutions in Stochastic Models: An Algorithmic Approach, Johns Hopkins University Press, 1981.