HAL
open science

Permutations of context-free, ET0L and indexed languages

Tara Brough, Laura Ciobanu, Murray Elder, Georg Zetzsche

To cite this version:

Tara Brough, Laura Ciobanu, Murray Elder, Georg Zetzsche. Permutations of context-free, ET0L and indexed languages. Discrete Mathematics and Theoretical Computer Science, 2016, Vol. 17 no. 3 (3), pp.167-178. 10.46298/dmtcs.2164 . hal-01352858

HAL Id: hal-01352858

https://inria.hal.science/hal-01352858v1

Submitted on 16 Aug 2016

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Discrete Mathematics and Theoretical Computer Science DMTCS vol. **17:3**, 2016, 167–178

Permutations of context-free, ET0L and indexed languages

Tara Brough[1*] Laura Ciobanu[2†] Murray Elder[3‡] Georg Zetzsche[4§]

[1] *Universidade de Lisboa, Portugal*
[2] *University of Neuchâtel, Switzerland*
[3] *The University of Newcastle, Australia*
[4] *LSV, CNRS & ENS Cachan, Université Paris-Saclay, France*

received 5th Jan. 2015, revised 19th Apr. 2016, accepted 12th May 2016.

For a language L, we consider its cyclic closure, and more generally the language $C^k(L)$, which consists of all words obtained by partitioning words from L into k factors and permuting them. We prove that the classes of ET0L and EDT0L languages are closed under the operators C^k. This both sharpens and generalises Brandstädt's result that if L is context-free then $C^k(L)$ is context-sensitive and not context-free in general for $k \geq 3$. We also show that the cyclic closure of an indexed language is indexed.

Keywords: ET0L, EDT0L, indexed, context-free, cyclic closure

1 Introduction

In this note we investigate closure properties of context-free, ET0L, EDT0L and indexed languages under the operation of permuting a finite number of factors. Let S_k denote the set of permutations on k letters. We sharpen a result of Brandstädt (1981) who proved that if L is context-free (respectively one-counter, linear) then the language

$$C^k(L) = \{w_{\sigma(1)} \dots w_{\sigma(k)} \mid w_1 \dots w_k \in L, \sigma \in S_k\}$$

is not context-free (respectively one-counter, linear) in general for $k \geq 3$. In our main result, Theorem 2.3, we prove that if L is ET0L (respectively EDT0L), then $C^k(L)$ is also ET0L (respectively EDT0L). Since context-free languages are ET0L, it follows that if L is context-free, then $C^k(L)$ is ET0L. Brandstädt (1981) proved that regular, context-sensitive and recursively enumerable languages are closed under C^k, so our results extend this list to include ET0L and EDT0L.

*Research primarily carried out while employed at the University of St Andrews, Scotland. Visit to second author supported by London Mathematical Society Scheme 4 grant 41348.
†Supported by Swiss National Science Foundation Professorship FN PP00P2-144681/1
‡Supported by Australian Research Council grant FT110100178
§Supported by a fellowship within the Postdoc-Program of the German Academic Exchange Service (DAAD)

1365–8050 © 2016 Discrete Mathematics and Theoretical Computer Science (DMTCS), Nancy, France

The language $C^2(L)$ is simply the *cyclic closure* of L, given by

$$cyc(L) = \{w_2 w_1 \mid w_1 w_2 \in L\}.$$

Maslov (1973); Oshiba (1972) proved that the cyclic closure of a context-free language is context-free. In Theorem 3.3 we show that the same is true for indexed languages.

The cyclic closure of a language, as well as the generalization C^k, are natural operations on languages, which can prove useful in determining whether a language belongs to a certain class. These operations are particularly relevant when studying languages attached to conjugacy in groups and semigroups (see Ciobanu et al. (2016)).

2 Permutations of ET0L and EDT0L languages

The acronym ET0L (respectively EDT0L) refers to E*xtended,* T*able,* 0 *interaction, and* L*indenmayer* (respectively D*eterministic*). There is a vast literature on Lindenmayer systems, see Rozenberg and Salomaa (1986), with various acronyms such as D0L, DT0L, ET0L, HDT0L and so forth. The following inclusions hold: EDT0L $\subset$ ET0L $\subset$ indexed, and context-free $\subset$ ET0L. Furthermore, the classes of EDT0L and context-free languages are incomparable.

Definition 2.1 (ET0L) *An* ET0L-system *is a tuple $H = (V, \mathcal{A}, \Delta, I)$, where*

1. *V is a finite alphabet,*
2. *$\mathcal{A} \subseteq V$ is the subset of* terminal symbols*,*
3. *$\Delta = \{P_1, \ldots, P_n\}$ is a finite set of* tables*, meaning each P_i is a finite subset of $V \times V^*$, and*
4. *$I \subseteq V^*$ is a finite set of* axioms*.*

A word over V is called a sentential form (of H)*. For $u, v \in V^*$, we write $u \Rightarrow_{H,i} v$ if $u = c_1 \cdots c_m$ for some $c_1, \ldots, c_m \in V$ and $v = v_1 \cdots v_m$ for some $v_1, \ldots, v_m \in V^*$ with $(c_j, v_j) \in P_i$ for every $j \in \{1, \ldots, m\}$. We write $u \Rightarrow_H v$ if $u \Rightarrow_{H,i} v$ for some $i \in \{1, \ldots, n\}$. If there exist sentential forms $u_0, \ldots, u_k$ with $u_i \Rightarrow_H u_{i+1}$ for $0 \leq i \leq n-1$, then we write $u_0 \Rightarrow_H^* u_k$. The language* generated by H *is defined as*

$$L(H) = \{v \in \mathcal{A}^* \mid w \Rightarrow_H^* v \text{ for some } w \in I\}.$$

A language is ET0L if it is equal to $L(H)$ for some ET0L system H.

We may write $c \to v \in P$ to mean $(c, v) \in P$. We call (c, v) a *rule for* c, and use the convention that if for some $c \in V$ no rule for c is specified in P, then P contains the rule (c, c).

Definition 2.2 (EDT0L) *An* EDT0L-system *is an ET0L system where in each table there is exactly one rule for each letter in V. A language is EDT0L if it is equal to $L(H)$ for some EDT0L system H.*

In this section we prove the following:

Theorem 2.3 *Let $\mathcal{A}$ be a finite alphabet. If $L \subseteq \mathcal{A}^*$ is ET0L (respectively EDT0L) then $C^k(L)$ is ET0L (respectively EDT0L).*

Proof: We start by showing that if $\#_0, \ldots, \#_k$ are distinct symbols not in $\mathcal{A}$ and L is ET0L (respectively EDT0L) then so is

$$L' = \{\#_0 w_1 \#_1 \ldots \#_{k-1} w_k \#_k \mid w_1 \ldots w_k \in L\}.$$

This will be done in Lemma 2.5 below. We then prove in Proposition 2.9 that if L_1 is an ET0L (respectively EDT0L) language where each word in L_1 has two symbols a, b appearing exactly once, then $L_2 = \{uabwv \mid uavbw \in L_1\}$ is ET0L (respectively EDT0L). For each permutation $\sigma \in S_k$ we apply this result to L' for

$$(a, b) = \left(\#_{\sigma(1)-1}, \#_{\sigma(1)}\right), \ldots, \left(\#_{\sigma(k)-1}, \#_{\sigma(k)}\right)$$

to obtain the ET0L (respectively EDT0L) language

$$L_\sigma = \{\#_0 \#_1 \ldots \#_k w_{\sigma(1)} \ldots w_{\sigma(k)} \mid \#_0 w_1 \#_1 \ldots \#_{k-1} w_k \#_k \in L'\}.$$

We obtain $C^k(L)$ by applying erasing homomorphisms to remove the $\#_i$, and taking the union over all $\sigma \in S^k$. Since ET0L (respectively EDT0L) languages are closed under homomorphism and finite union, this shows that $C^k(L)$ is ET0L (respectively EDT0L).

Thus the proof will be complete once we established the above facts. □

Lemma 2.4 *If $L \subseteq \mathcal{A}^*$ is EDT0L and $\#$ is a symbol not in $\mathcal{A}$ then the language*

$$L_\# = \{u\#v \mid uv \in L\}$$

is EDT0L.

Proof: Let $H = (V, \mathcal{A}, \Delta, I)$ be an EDT0L system with $L = L(H)$. Without loss of generality we can assume $I \subseteq V$. Define an EDT0L system $H_\# = (V_\#, \mathcal{A} \cup \{\#\}, \Delta_\#, I_\#)$ as follows: $V_\#$ is the disjoint union $V \cup \{c_\# \mid c \in V\}$, $I_\# = \{s_\# \mid s \in I\}$, and $m = \max_{P \in \Delta}\{|w| \mid (c, w) \in P\}$, the length of the longest right-hand side of any table. Furthermore, we define $\Delta_\#$ to be the disjoint union $\Delta \cup \{P_{i,\#}, P_{\#,i} \mid P \in \Delta, i \in [0, m]\}$, where

$$\begin{aligned} P_{i,\#} &:= \{c_\# \to u d_\# v \mid c \to udv \in P, |u| = i, d \in V\} \cup P, \\ P_{\#,i} &:= \{c_\# \to u\#v \mid c \to uv \in P, |u| = i\} \cup P. \end{aligned} \tag{1}$$

We point out that if $c \to \varepsilon \in P$, where ε denotes the empty word, then $P_{\#,0} = \{c_\# \to \#\}$, so $\{c_\# \to \# \mid c \to \varepsilon \in P\}$ will be included in $\Delta_\#$.

The new system remains finite since we have added a finite number of new letters and tables, and deterministic since letters $v_\#$ appear exactly once on the left side of each rule in the new tables.

Each word in $L(H_\#)$ is obtained starting with $s_\# \in I_\#$ and applying tables of the form $P_{i,\#}$ some number of times, until at some point, since $\mathcal{A} \cup \{\#\}$ does not contain any letter with subscript $\#$, a table of the form $P_{\#,i}$ must be applied. Before this point there is precisely one letter in the sentential form with subscript $\#$, and after there are no letters with subscript $\#$. Also, if $uv \in L(H)$, then there is some $a \in I$ with $a \Rightarrow_H^* uv$, and by construction $a_\# \Rightarrow_{H_\#}^* u\#v$. □

Lemma 2.5 *If $L \in \mathcal{A}$ is ET0L (respectively EDT0L) and $\#_0, \ldots, \#_n$ are distinct symbols not in $\mathcal{A}$, then*

$$L' = \{\#_0 u_1 \#_1 \ldots u_n \#_n \mid u_1 \ldots u_n \in L\}$$

is ET0L (respectively EDT0L).

Proof: Since ET0L languages are closed under rational transduction (Rozenberg and Salomaa (1986)), the result is immediate for ET0L. In contrast, the EDT0L languages are not closed under inverse homomorphism (for example, the language $\{a^{2^n} \mid n \in \mathbb{N}\}$ is EDT0L and its inverse homomorphic image $\{w \in \{a,b\}^* \mid \exists n \in \mathbb{N}(|w|_a = 2^n)\}$ is not (Ehrenfeucht and Rozenberg (1974), Example 3). Instead, we apply Lemma 2.4 $n+1$ times to insert single copies of the $\#_i$, then intersect with the regular language $\{\#_0 u_1 \#_1 \ldots u_n \#_n \mid u_i \in \mathcal{A}^*\}$ to ensure that the $\#_i$ appear in the correct order. □

Definition 2.6 ((a,b)-language) *Let $\mathcal{T}$ be a finite alphabet and $a, b \in \mathcal{T}$ distinct symbols. We say that $w \in \mathcal{T}^*$ is an* (a,b)-word *if $w \in X^* a X^* b X^*$, where $X = \mathcal{T} \setminus \{a,b\}$. A language $L \subseteq \mathcal{T}^*$ of (a,b)-words is called an* (a,b)-language.

We define a function π on (a,b)-words as follows. If $w = xaybz \in \mathcal{T}^*$, then $\pi(w) = xabzy$. For an (a,b)-language L, we set $\pi(L) = \{\pi(w) \mid w \in L\}$.

Suppose L is an (a,b)-language and $H = (V, \mathcal{T}, \Delta, I)$ is an ET0L or EDT0L system with $L = L(H)$.

Definition 2.7 ((a,b)-morphism) *A morphism $\varphi : V^* \to \{a,b\}^*$ is called an* (a,b)-morphism *(for H) if*

(1) $\varphi(a) = a$, $\varphi(b) = b$, and $\varphi(c) = \varepsilon$ for $c \in \mathcal{T} \setminus \{a,b\}$, and

(2) if $u, v \in V^*$ with $u \Rightarrow_H v$ then $\varphi(u) = \varphi(v)$.

Lemma 2.8 *Let L be an ET0L (respectively EDT0L) language that is an (a,b)-language. Then L can be generated by some ET0L-system (respectively EDT0L-system) that admits an (a,b)-morphism.*

Proof: Suppose L is generated by $H = (V, \mathcal{T}, \Delta, I)$, where $a, b \in \mathcal{T}$ and $\Delta = \{P_1, \ldots, P_n\}$. Without loss of generality, we may assume that $I \subseteq V$. We define a new ET0L (respectively EDT0L) system $H' = (V', \mathcal{T}, \Delta', I')$ as follows. Let $\mathcal{F} = \{\varepsilon, a, b, ab\}$ be the set of factors of ab. Let $V' = (V \times \mathcal{F}) \cup \mathcal{T}$ be the new alphabet and define the morphism $\varphi\colon V'^* \to \{a,b\}^*$ by $\varphi((c,f)) = f$ for $(c,f) \in V \times \mathcal{F}$, $\varphi(a) = a$, $\varphi(b) = b$ and $\varphi(c) = \varepsilon$ for $c \in \mathcal{T} \setminus \{a,b\}$.

The role of the $\mathcal{F}$-component of a symbol (c,f) in V' is to store the φ-image of the terminal word to be derived from c. Since H generates only (a,b)-words, we choose as axioms $I' = I \times \{ab\}$. The role of the tables is to distribute the two letters (in the $\mathcal{F}$-component) in each word along a production.

In the ET0L case, the new set of tables is $\Delta' = \{P'_1, \ldots, P'_n, P'_{n+1}\}$, where

$$P'_i = \{(c,f) \to (c_1,f_1) \cdots (c_m,f_m) \mid c \to c_1 \cdots c_m \in P_i,\ \ f = f_1 \cdots f_m\}$$

for each $i \in \{1, \ldots, n\}$ and

$$P'_{n+1} = \{(a,a) \to a,\ (b,b) \to b\} \ \cup\ \{(c,\varepsilon) \to c \mid c \in \mathcal{T} \setminus \{a,b\}\} \ \cup\ \{c \to c \mid c \in \mathcal{T}\}.$$

In the EDT0L case, we introduce a separate table for each choice of a factorisation $f = f_1 \cdots f_\ell$ for each $f \in \mathcal{F}$, where ℓ is the maximal length of any right-hand side in H.

The idea underlying the definition of the tables P_i' is that we make multiple copies of each rule in P_i based on the choices for how to partition f and distribute the factors among the c_i's.

We claim now that $H' = (V', \mathcal{T}, \Delta', I')$ admits the morphism φ. Property (1) follows from the definition of φ, and property (2) from the definition of the tables above.

Let $\psi\colon V'^* \to V^*$ be the 'first coordinate projection' morphism with $\psi((c, f)) = c$ for $(c, f) \in V \times \mathcal{F}$ and $\psi(c) = c$ for $c \in \mathcal{T}$.

For the inclusion $L(H') \subseteq L(H)$, note that $u \Rightarrow_{H'} v$ implies $\psi(u) \Rightarrow_H \psi(v)$ or $\psi(u) = \psi(v)$, so in any case $\psi(u) \Rightarrow_H^* \psi(v)$. Thus, if $v \in L(H')$ with $w \Rightarrow_{H'}^* v$ and $w \in I'$, then $\psi(w) \Rightarrow_H^* \psi(v)$ and $\psi(w) \in I$, hence $v = \psi(v) \in L(H)$. This implies $L(H') \subseteq L(H)$.

For the inclusion $L(H) \subseteq L(H')$, a straightforward induction on n yields the following claim: If $u \Rightarrow_H^n v$ with $u \in V^*$ and an (a, b)-word $v \in \mathcal{T}^*$, then we have $u' \Rightarrow_{H'}^* v$ for some $u' \in V'^*$ such that $\psi(u') = u$ and $\varphi(u') = ab$. We apply this to a derivation $s \Rightarrow_H^* v$ with $s \in I$. Then our claim yields an $s' \in V'^*$ with $s' \Rightarrow_{H'}^* v$, $\psi(s') = s \in I$, and $\varphi(s') = ab$. This means $s' \in I'$ and thus $v \in L(H')$. $\square$

Proposition 2.9 *Let L be an (a, b)-language that is ET0L (respectively EDT0L). Then $\pi(L)$ is ET0L (respectively EDT0L).*

Proof: Let $L = L(H)$, where $H = (V, \mathcal{T}, \Delta, I)$. By Lemma 2.8, we may assume that there is an (a, b)-morphism φ for H. We now use φ to define a map similar to π on words over V. A word $w \in V^*$ is said to be an (a, b)-*form* (short for (a, b)-sentential-form) if $\varphi(w) = ab$. Such a word is either of the form xCy, where $r, s \in V^*$ and $C \in V$, with $\varphi(x) = \varphi(y) = \varepsilon$ and $\varphi(C) = ab$; or it is of the form $xAyBz$ with $x, y, z \in V^*$ and $A, B \in V$ with $\varphi(x) = \varphi(y) = \varphi(z) = \varepsilon$ and $\varphi(A) = a$, $\varphi(B) = b$. In the former case, w is called *fused*, in the latter it is called *split*.

Let p, q be symbols with $p, q \notin V$. We define the function $\tilde{\pi}$ on (a, b)-forms as follows. If w is fused, then $\tilde{\pi}(w) = wpq$. If w is split with $w = xAyBz$ as above, then $\tilde{\pi}(w) = xABzpyq$. In other words, the factor between a and b in w will be moved between p and q. For a set L of (a, b)-forms, we set $\tilde{\pi}(L) = \{\tilde{\pi}(w) \mid w \in L\}$. Note that $\tilde{\pi}$ differs from π by introducing the letters p, q. This will simplify the ensuing construction.

The idea is to construct an ET0L (respectively EDT0L) system $H' = (V', \mathcal{T}', \Delta', I')$, in which V' is the disjoint union $V \cup \{p, q\}$ and $\mathcal{T}' = \mathcal{T} \cup \{p, q\}$, such that for (a, b)-forms $u, v \in V^*$, we have

$$u \Rightarrow_H v \qquad \text{if and only if} \qquad \tilde{\pi}(u) \Rightarrow_{H'} \tilde{\pi}(v) \tag{2}$$

Moreover, for each (a, b)-form $u \in V^*$ and $v' \in V'^*$ with $\tilde{\pi}(u) \Rightarrow_{H'} v'$, there is an (a, b)-form $v \in V^*$ such that

$$\begin{array}{ccc} u & \Longrightarrow_H & v \\ {\scriptstyle\tilde{\pi}}\downarrow & & \downarrow{\scriptstyle\tilde{\pi}} \\ \tilde{\pi}(u) & \Longrightarrow_{H'} & v' \end{array} \tag{3}$$

For example, if the derivation $\tilde{\pi}(xAyBz) = xABzpyq \Rightarrow_{H'} x'A'B'z'py'q$ holds (the split-split case for u and v), then $xAyBz \Rightarrow_H x'A'y'B'z'$, and similar implications hold in the other cases.

We define I' as $I' = \{\tilde{\pi}(w) \mid w \in I\}$, hence equation (2) implies $\tilde{\pi}(L(H)) \subseteq L(H')$ and equation (3) implies $L(H') \subseteq \tilde{\pi}(L(H))$. Together, we have $L(H') = \tilde{\pi}(L(H))$, meaning $\tilde{\pi}(L(H))$ is an ET0L

(respectively EDT0L) language. Furthermore, we have $\pi(L(H)) = \psi(\tilde{\pi}(L(H)))$, where ψ is the homomorphism that erases p, q. Thus, since the classes of ET0L and EDT0L languages are closed under homomorphic images, proving equations (2), (3) implies that $\pi(L(H))$ is an ET0L (respectively EDT0L) language and hence Proposition 2.9.

As before, we write $\Delta = \{P_1, \ldots, P_n\}$. Let ℓ be the maximal length of a right-hand side in the productions of H, and let $V^{\leq \ell}$ denote the set of all words in V^* of length at most ℓ. The set Δ' consists of the following tables:

P'_i	for each $1 \leq i \leq n$,
$P'_{i,w}$	for each $1 \leq i \leq n$ and $w \in V^{\leq \ell}$ with $\varphi(w) = \varepsilon$,
$P'_{i,u,v}$	for each $1 \leq i \leq n$ and $u, v \in V^{\leq \ell}$ with $\varphi(u) = \varphi(v) = \varepsilon$,

which we describe next. The table P'_i allows H' to mimic (in the sense of (2)) steps in P_i that start in a fused word and result in a fused word. Each table P'_i comprises the following productions:

$A \to z$	for each $A \to z \in P_i$ with $\varphi(A) = \varepsilon$,
$C \to xDy$	for each $C \to xDy \in P_i$ with $D \in V$ and $\varphi(C) = \varphi(D) = ab$,
$p \to p$,	
$q \to q$.	

The table $P'_{i,w}$ mimics all steps of P_i where a fused word is turned into a split one, such that between the introduced $A, B \in V$, $\varphi(A) = a$, $\varphi(B) = b$, the word w is inserted. It contains the following productions:

$A \to z$	for each $A \to z \in P_i$ with $\varphi(A) = \varepsilon$,
$C \to xABy$	for each $C \to xAwBy \in P_i$ with $\varphi(C) = ab$, $\varphi(A) = a$, and $\varphi(B) = b$,
$p \to pw$,	
$q \to q$.	

Finally, the table $P'_{i,u,v}$ mimics a step of P_i that starts in a split word and produces a split one, such that (i) the symbol A with $\varphi(A) = a$ generates u to its right and (ii) the symbol B with $\varphi(B) = b$ generates v to its left. It consists of the productions

$A \to z$	for each $A \to z \in P_i$ with $\varphi(A) = \varepsilon$,
$A \to xA'$	for each $A \to xA'u \in P_i$ with $\varphi(A) = \varphi(A') = a$,
$B \to B'y$	for each $B \to vB'y \in P_i$ with $\varphi(B) = \varphi(B') = b$,
$p \to pu$,	
$q \to vq$.	

It can be verified straightforwardly that with these tables, equations (2), (3) are satisfied. In addition, if the table P_i has exactly one rule for each letter in V then $P'_i, P'_{i,w}$ and $P'_{iu,v}$ has exactly one rule for each letter in V', so if H is EDT0L then so is H'. We have thus proven Proposition 2.9. □

3 Cyclic closure of indexed is indexed

Recall that an indexed language is one that is generated by the following type of grammar:

Definition 3.1 (Indexed grammar; Aho (1968)) *An* indexed grammar *is a 5-tuple* $(\mathcal{N}, \mathcal{T}, \mathcal{I}, \mathcal{P}, S)$ *such that*

1. $\mathcal{N}, \mathcal{T}, \mathcal{I}$ *are three mutually disjoint sets of symbols, called* nonterminals, terminals *and* indices *(or* flags*) respectively.*
2. $S \in \mathcal{N}$ *is the* start symbol.
3. $\mathcal{P}$ *is a finite set of* productions*, each having the form of one of the following:*
   (a) $A \to B^f$.
   (b) $A^f \to v$.
   (c) $A \to u$.

   where $A, B \in \mathcal{N}$, $f \in \mathcal{I}$ *and* $u, v \in (\mathcal{N} \cup \mathcal{T})^*$.

As usual in grammars, indexed grammars successively transform sentential forms, which are defined as follows. An *atom* is either a terminal letter $x \in \mathcal{T}$ or a pair (A, γ) with $A \in \mathcal{N}$ and $\gamma \in \mathcal{I}^*$. Such a pair (A, γ) is also denoted A^γ. A *sentential form* of an indexed grammar is a (finite) sequence of atoms. In particular, every string over $\mathcal{T}$ is a sentential form. The language defined by an indexed grammar is the set of all strings of terminals that can be obtained by successively applying production rules starting from the sentential form S. Let $A \in \mathcal{N}, \gamma \in \mathcal{I}^*$. Define a letter homomorphism π_γ by

$$\pi_\gamma(c) = \begin{cases} c^\gamma & \text{if } c \in \mathcal{N}, \\ c & \text{if } c \in \mathcal{T}. \end{cases}$$

In contrast to ETOL systems, where each step replaces every symbol in the sentential form, indexed grammars transform only one atom per step. Production rules transform sentential forms as follows. For an atom A^γ in the sentential form:

1. applying $A \to B^f$ replaces one occurrence of A^γ by $B^{f\gamma}$
2. if $\gamma = f\delta$ with $f \in \mathcal{I}$, applying $A^f \to v$ replaces one occurrence of A^γ (with $\gamma \in \mathcal{I}^*$) by $\pi_\delta(v)$
3. applying $A \to u$ replaces one occurrence of A^γ by $\pi_\gamma(u)$.

We call the operation of successively applying productions starting from the sentential form S and terminating at a string $u \in \mathcal{T}^*$ a *derivation* of u. We use the notation $\Rightarrow$ to denote a sequence of productions within a derivation, and call such a sequence a *subderivation*. Sometimes we abuse notation and write $u \to v$ for sentential forms u and v to denote that v results from u by applying one rule.

We represent a derivation $S \Rightarrow u \in \mathcal{T}^*$ pictorially using a *parse tree*, which is defined in the same way as for context-free grammars (see for example Hopcroft and Ullman (1979) page 83) with root labeled by S, internal nodes labeled by A^ω for $A \in \mathcal{N}$ and $\omega \in \mathcal{I}^*$ and leaves labeled by $\mathcal{T} \cup \{\varepsilon\}$.

A *path-skeleton* of a parse tree is the (labeled) 1-neighbourhood of some path from the root vertex to a leaf. See Figure 1 for an example.

Definition 3.2 (Normal form) *An indexed grammar* $(\mathcal{N}, \mathcal{T}, \mathcal{I}, \mathcal{P}, S)$ *is in* normal form *if all productions are of one of the following types:*

1. $A \to B^f$
2. $A^f \to B$
3. $A \to BC$
4. $A \to a$

where $A, B, C \in \mathcal{N}$, $f \in \mathcal{I}$ *and* $a \in \mathcal{T}$.

An indexed grammar can be put into normal form as follows. For each production $A^f \to v$ with $v \notin \mathcal{N}$, introduce a new nonterminal B, add productions $A^f \to B, B \to v$, and remove $A^f \to v$. By the same arguments used for Chomsky normal form, each production $A \to u$ without flags can be replaced by a set of productions of type 3 and 4 above.

Maslov (1973); Oshiba (1972) proved that the cyclic closure of a context-free language is context-free. A sketch of a proof of this fact is given in the solution to Exercise 6.4 (c) in Hopcroft and Ullman (1979), and we generalise the approach taken there to show that the class of indexed languages is also closed under the cyclic closure operation.

Theorem 3.3 *If* L *is indexed, then* $cyc(L)$ *is indexed.*

Proof: The idea of the proof is to take the parse-tree of a derivation of $w_1 w_2 \in L$ in Γ and "turn it upside down", using the leaf corresponding to the first letter of the word w_2 as the new start symbol.

Let $\Gamma = (\mathcal{N}, \mathcal{T}, \mathcal{I}, \mathcal{P}, S)$ be an indexed grammar for L in normal form. If $w = a_1 \dots a_n \in L$ with $a_i \in \mathcal{T}$ and we wish to generate the cyclic permutation $a_k \dots a_n a_1 \dots a_{k-1}$ of w, take some parse tree for w in Γ and draw the unique path F from the start symbol S to a_k. Consider the path-skeleton for F.

In the example given in Figure 1, the desired word $a_k \dots a_n a_1 \dots a_{k-1}$ can be derived from the string $a_k A_3^f A_4^f A_1 A_2^{gf}$, using productions in $\mathcal{P}$.

Therefore we wish to enlarge the grammar to generate all strings

$$a_k A_{k+1}^{w_{k+1}} \dots A_n^{w_n} A_1^{w_1} \dots A_{k-1}^{w_{k-1}},$$

where $A_1^{w_1}, \dots, A_{k-1}^{w_{k-1}}$ are the labels of the vertices lying immediately to the left of F (in top to bottom order), and $A_{k+1}^{w_{k+1}}, \dots, A_n^{w_n}$ are the labels of the vertices lying immediately to the right of F (in bottom to top order). We do this by introducing new 'hatted' nonterminals, with which we label all the vertices along the path F, and new productions which are the reverse of the old productions 'with hats on'. By first nondeterministically guessing the flag on the nonterminal immediately preceding a_k, we are able to essentially generate the path-skeleton in reverse.

The grammar for $cyc(L)$ is given by $\Gamma' = (\mathcal{N}', \mathcal{T}', \mathcal{I}', \mathcal{P} \cup \mathcal{P}', S_0)$, where $\mathcal{T}' = \mathcal{T}$, $\mathcal{I}' = \mathcal{I} \cup \{\$\}$ (where \$ is a new symbol not in $\mathcal{I}$), $S_0 \in \mathcal{N}' \setminus \mathcal{N}$ is the new start symbol, and $\mathcal{N}'$ and $\mathcal{P}'$ are as follows. Let $\hat{\mathcal{N}}$ be the set of symbols obtained from $\mathcal{N}$ by placing a hat on them. Then the disjoint union $\mathcal{N}' = \mathcal{N} \cup \hat{\mathcal{N}} \cup \{S_0, \tilde{S}\}$ is the new set of nonterminals.

The productions $\mathcal{P}'$ are as follows:

1. $S_0 \to S$, $S_0 \to \tilde{S}^{\$}$, $\hat{S}^{\$} \to \varepsilon$



Fig. 1: Path-skeleton in an indexed grammar.

2. for each $f \in \mathcal{I}$, a production $\tilde{S} \to \tilde{S}^f$
3. for each production $A \to a$ in $\mathcal{P}$, a production $\tilde{S} \to a\hat{A}$
4. for each production $A \to B^f$ in $\mathcal{P}$, a production $\hat{B}^f \to \hat{A}$
5. for each production $A^f \to B$ in $\mathcal{P}$, a production $\hat{B} \to \hat{A}^f$
6. for each production $A \to BC$ in $\mathcal{P}$, productions $\hat{B} \to C\hat{A}$ and $\hat{C} \to \hat{A}B$

Note that the new grammar is no longer in normal form.

Informally, the new grammar operates as follows. Let $w = w_1w_2 \in L$ and suppose we wish to produce w_2w_1. If a derivation starts with $S_0 \to S$, then the word produced is some word from L. (This corresponds to the case when one of the w_i is empty.) Otherwise derivations start with $S_0 \to \tilde{S}^{\$}$, followed by some sequence of productions $\tilde{S} \to \tilde{S}^f$, building up a flag word on $\tilde{S}$. This is how we nondeterministically guess the flag label γ on the second last node of the path-skeleton. After this we apply a production $\tilde{S} \to a\hat{A}$, where a is the first letter of w_2 (labelling the end leaf of the path-skeleton) and A is the nonterminal labelling the second last vertex of the path-skeleton. Note that the flag label $\gamma\$$ is transferred to $\hat{A}$. After this point, productions of types 4, 5, and 6 are applied to simulate going in reverse along the path-skeleton, at each step producing a sentential form with exactly one hatted symbol. The only way to remove the hat symbol is to apply the production $\hat{S}^{\$} \to \varepsilon$. Observe that all flags on nonterminals in a derivation starting from $S_0 \to \tilde{S}^{\$}$ are words in $\mathcal{I}^*\$$, and since $\$$ is always at the right end of a flag it does

not interfere with any productions from $\mathcal{P}$, so in particular rules $A \to a$ to the sides of the path-skeleton produce the same strings of terminals as they do in Γ.

We will show by induction on n that in this new grammar, if $A, A_1, \ldots, A_n \in \mathcal{N}$ then

$$A^w \Rightarrow A_1^{w_1} \ldots A_i^{w_i} \ldots A_n^{w_n} \tag{4}$$

if and only if

$$\hat{A}_i^{w_i} \Rightarrow A_{i+1}^{w_{i+1}} \ldots A_n^{w_n} \hat{A}^w A_1^{w_1} \ldots A_{i-1}^{w_{i-1}} \tag{5}$$

for all $1 \leq i \leq n$.

To see why this will suffice, suppose first that

$$S \Rightarrow A_1^{w_1} \ldots A_{i-1}^{w_{i-1}} A_i^{w_i} A_{i+1}^{w_{i+1}} \ldots A_n^{w_n} \to A_1^{w_1} \ldots A_{i-1}^{w_{i-1}} a A_{i+1}^{w_{i+1}} \ldots A_n^{w_n}$$

in the original grammar Γ. So $A_i \to a$ is in $\mathcal{P}$. Then in the new grammar

$$S_0 \Rightarrow \tilde{S}^{w_i\$} \to a\hat{A}_i^{w_i\$} \Rightarrow aA_{i+1}^{w_{i+1}\$} \ldots A_n^{w_n\$} \hat{S}^{\$} A_1^{w_1\$} \ldots A_{i-1}^{w_{i-1}\$} \to aA_{i+1}^{w_{i+1}\$} \ldots A_n^{w_n\$} A_1^{w_1\$} \ldots A_{i-1}^{w_{i-1}\$}.$$

Each $A_j^{w_j\$}$ produces exactly the same set of words in Γ' as $A_j^{w_j}$ produces in Γ. Hence every cyclic permutation of a word in L is in the new language.

Conversely, suppose $S_0 \Rightarrow aB_1^{v_1} \ldots B_n^{v_n}$ and that this subderivation does not start with $S_0 \to S$. Then the subderivation begins with $S_0 \to \tilde{S}^{\$} \Rightarrow \tilde{S}^u \to a\hat{A}^u$ for some $u \in \mathcal{I}^*\$$, $A \in \mathcal{N}$. Once a 'hatted' symbol has been introduced, the only way to get rid of the hat is via the production $\hat{S}^{\$} \to \varepsilon$. Hence we must have $\hat{A}^u \Rightarrow B_1^{v_1} \ldots B_j^{v_j} \hat{S}^{\$} B_{j+1}^{v_{j+1}} \ldots B_n^{v_n}$ for some $0 \leq j \leq n$ (with the factor before or after $\hat{S}$ being empty if $j = 0$ or $j = n$ respectively).

But then

$$S^{\$} \Rightarrow B_{j+1}^{v_{j+1}} \ldots B_n^{v_n} A^u B_1^{v_1} \ldots B_j^{v_j} \to B_{j+1}^{v_{j+1}} \ldots B_n^{v_n} a B_1^{v_1} \ldots B_j^{v_j}$$

and so if a word is produced by the new grammar, some cyclic permutation of that word is in L.

We finish by giving the inductive proof of the equivalence of (4) and (5). For the case $n = 1$, the productions of type 5 and 6 in the definition of the grammar for $cyc(L)$ show that $A^w \Rightarrow B^u$ if and only if $\hat{B}^u \Rightarrow \hat{A}^w$. For the case $n = 2$, we have $A^w \Rightarrow B^u C^v$ if and only if at some point in the parse tree, we see a subtree labeled $X^t \to Y^t Z^t$, with $A^w \Rightarrow X^t$, $Y^t \Rightarrow B^u$ and $Z^t \Rightarrow C^v$. The productions in these last three subderivations are all of the form $D \to E^f$ or $D^f \to E$, so they are equivalent to $\hat{X}^t \Rightarrow \hat{A}^w$, $\hat{B}^u \Rightarrow \hat{Y}^t$ and $\hat{C}^v \Rightarrow \hat{Z}^t$. Also $X \to YZ$ if and only if $\hat{Y} \to Z\hat{X}$ and $\hat{Z} \to \hat{X}Y$. Putting these together, we have $A^w \Rightarrow B^u C^v$ if and only if

$$\hat{B}^u \Rightarrow \hat{Y}^t \to Z^t \hat{X}^t \Rightarrow C^v \hat{A}^w$$

and

$$\hat{C}^v \Rightarrow \hat{Z}^t \to \hat{X}^t Y^t \Rightarrow \hat{A}^w B^u,$$

as required.

Now for $n > 2$, suppose our statement is true for $k < n$. Then $A^w \Rightarrow A_1^{w_1} A_2^{w_2} \ldots A_n^{w_n}$ if and only if for each $1 \leq i \leq n$ there are $X_i, Y_i, Z_i \in \mathcal{N}$ and $t \in \mathcal{I}^*$ such that $X_i \to Y_i Z_i$ and for some $1 \leq j \leq n$ either

$$A^w \Rightarrow A_1^{w_1} \ldots A_{i-1}^{w_{i-1}} X_i^t A_j^{w_j} \ldots A_n^{w_n},$$

with $Y_i^t \Rightarrow A_i^{w_i}$ and $Z_i^t \Rightarrow A_{i+1}^{w_{i+1}} \dots A_{j-1}^{w_{j-1}}$, or

$$A^w \Rightarrow A_1^{w_1} \dots A_j^{w_j} X_i^t A_{i+1}^{w_{i+1}} \dots A_n^{w_n},$$

with $Y_i^t \Rightarrow A_{j+1}^{w_{j+1}} \dots A_{i-1}^{w_{i-1}}$ and $Z_i^t \Rightarrow A_i^{w_i}$.

We will consider only the second of these, as it is the slightly more complicated one and the first is very similar. The right hand side of the displayed subderivation has fewer than n terms, so by our assumption, this subderivation is valid if and only if

$$\hat{X}_i^t \Rightarrow A_{i+1}^{w_{i+1}} \dots A_n^{w_n} \hat{A}^w A_1^{w_1} \dots A_j^{w_j}.$$

But this, together with $Y_i^t \Rightarrow A_{j+1}^{w_{j+1}} \dots A_{i-1}^{w_{i-1}}$ and $Z_i^t \Rightarrow A_i^{w_i}$, is equivalent to the existence of a derivation

$$\hat{A}_i^{w_i} \Rightarrow \hat{Z}_i^t \to \hat{X}_i^t Y_i^t \Rightarrow A_{i+1}^{w_{i+1}} \dots A_n^{w_n} \hat{A}^w A_1^{w_1} \dots A_{i-1}^{w_{i-1}}$$

such that $\hat{X}_i^t \Rightarrow A_{i+1}^{w_{i+1}} \dots A_n^{w_n} \hat{A}^w A_1^{w_1} \dots A_j^{w_j}$ and $Y_i^t \Rightarrow A_{j+1}^{w_{j+1}} \dots A_{i-1}^{w_{i-1}}$. Here, $\hat{A}_i^{w_i} \Rightarrow \hat{Z}_i^t$ follows from the equivalence of (4) and (5) for $n = 1$. □

4 Concluding remarks

The results in this paper raise the question whether for an indexed language L the language $C^k(L)$ is indexed as well, or if not, to which class of languages (within context-sensitive) it belongs.

A consequence of our main result (Theorem 2.3) is that permutations of context-free languages are indexed (a different proof of this based on parse trees can be found in Brough et al. (2015)). It would be interesting to consider the possible extension of this result to the OI- and IO-hierarchies (Damm (1982), Damm and Goerdt (1986)) of languages built out of automata or grammars that extend the pushdown automata and indexed grammars, respectively. They define level-n grammars inductively, allowing the flags at level n to carry up to n levels of parameters in the form of flags. Thus level-0 grammars generate context-free languages, and level-1 grammars produce indexed languages. We conjecture that the class of level-n languages is closed under cyclic closure, and also that if L is a level-n language then $C^k(L)$ is a level-$(n+1)$ language.

References

A. V. Aho. Indexed grammars—an extension of context-free grammars. *J. Assoc. Comput. Mach.*, 15: 647–671, 1968.

A. Brandstädt. Closure properties of certain families of formal languages with respect to a generalization of cyclic closure. *RAIRO Inform. Théor.*, 15(3):233–252, 1981.

T. Brough, L. Ciobanu, and M. Elder. Permutation closures of context-free and indexed languages. `http://arxiv.org/abs/1412.5512`, 2015.

L. Ciobanu, S. Hermiller, D. Holt, and S. Rees. Conjugacy languages in groups. *Israel Journal of Mathematics*, 211(1):311–347, 2016.

W. Damm. The IO- and OI-hierarchies. *Theoret. Comput. Sci.*, 20(2):95–207, 1982.

W. Damm and A. Goerdt. An automata-theoretical characterization of the OI-hierarchy. *Inform. and Control*, 71(1-2):1–32, 1986.

A. Ehrenfeucht and G. Rozenberg. The number of occurrences of letters versus their distribution in some EOL languages. *Information and Control*, 26:256–271, 1974.

A. Ehrenfeucht and G. Rozenberg. On inverse homomorphic images of deterministic ETOL languages. In *Automata, languages, development*, pages 179–189. North-Holland, Amsterdam, 1976.

J. E. Hopcroft and J. D. Ullman. *Introduction to automata theory, languages, and computation*. Addison-Wesley Publishing Co., Reading, Mass., 1979. Addison-Wesley Series in Computer Science.

A. N. Maslov. The cyclic shift of languages. *Problemy Peredači Informacii*, 9(4):81–87, 1973.

T. Oshiba. Closure property of the family of context-free languages under the cyclic shift operation. *Electron. Commun. Japan*, 55(4):119–122, 1972.

G. Rozenberg and A. Salomaa. *The Book of L.* Springer, 1986.