



HAL
open science

Guaranteed Cost Control for Uncertain Distributed Delay System with Neutral Type

Yuyan Zhang, Dan Zhao, Yan Zhao, Na Zhang

► **To cite this version:**

Yuyan Zhang, Dan Zhao, Yan Zhao, Na Zhang. Guaranteed Cost Control for Uncertain Distributed Delay System with Neutral Type. 5th Computer and Computing Technologies in Agriculture (CCTA), Oct 2011, Beijing, China. pp.372-382, 10.1007/978-3-642-27275-2_42 . hal-01361161

HAL Id: hal-01361161

<https://inria.hal.science/hal-01361161v1>

Submitted on 6 Sep 2016

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Guaranteed Cost Control for Uncertain Distributed Delay System with Neutral Type

Yuyan Zhang^{1,1}, Dan Zhao¹, Yan Zhao¹, Na Zhang¹

¹ Department of Automatic Control Engineering, Shenyang Institute of Engineering,
110136 Shenyang, China
{zhangyy, zhaodan, zhaoyan}@sie.edu.cn

Abstract. This paper investigates the problem of guaranteed cost control for a class of uncertain distributed delay systems with neutral type. A sufficient condition for the solvability of this problem is obtained. A novel Lyapunov-Krasovskii functional is constructed to reduce conservatism of the criterion in form of LMIs. Some mathematical techniques are utilized flexibly. Especially, the exchange of the order of repeated integral is required. Based the criterion, the control gain and the guaranteed cost are obtained. A numerical example is provided to illustrate the effectiveness of the proposed design methods.

Keywords: Distributed delay system with neutral type, Guaranteed cost control, Linear matrix inequality(LMI)

1 Introduction

Neutral delay systems are the general form of delay system and contain delays on the derivatives of some system variables. There are many physical examples for neutral delay system in practical systems(see,e.g.,[1,2,8,11]). In recent years, the stability analysis and robust guaranteed cost control problems of neutral delay system have been considered extensively[1,2,5,8,11,12]. Different from some existing results, Lien^[1] introduces a positive constant ω to obtain the corresponding LMIs using Lyapunov--Krasovskii theory and Leibniz--Newton formulae. An LMI optimization approach is proposed to find the robust non-fragile guaranteed cost control and used to minimize the guaranteed cost. Xu in [11] are concerned with the problem of non-fragile positive real control for uncertain neutral system with invariant delays in state. For both the cases with additive and multiplicative control uncertainties, sufficient conditions for the existence of the controllers are given in terms of LMIs.

On the other hand, with the increasing of the number of summands in a system equation and the decreasing of differences between neighboring argument values, systems with distributed delays will arise. Distributed delays can also be found in the

¹ This work is supported by the Natural Science Foundation of China under Grant No. 60972164, 60904101, 60904046 and the Science and Technology Program of Shenyang under Grant No. F11-264-1-70, F10-205-1-80.

modeling of feeding systems and combustion chambers in a liquid monopropellant rocket motor with pressure feeding^[3,4]. Therefore, many efforts have been made for the distributed delays systems[5,6,7].

To the best of the authors' knowledge, there are a few notes on the problem of guaranteed cost control for distributed delay systems with neutral type, which motivates the present study. In view of the importance of the choice of an appropriate Lyapunov-Krasovskii functional for deriving good stability criteria for delay system, a class of special forms of Lyapunov-Krasovskii functionals are constructed to lead to simpler and less conservative sufficient conditions. Simultaneously, some mathematical techniques are applied flexibly. Finally, a numerical example is provided to illustrate the effectiveness of the proposed design methods.

2 Problem Statement and Preliminaries

Consider the following uncertain distributed delay systems with neutral type

$$\begin{aligned} \dot{x}(t) = & [A + \Delta A(t)]x(t) + [A_\sigma + \Delta A_\sigma(t)]x(t - \sigma) + [A_\eta + \Delta A_\eta(t)]\dot{x}(t - \eta) \\ & + [A_\delta + \Delta A_\delta(t)] \int_{t-\delta}^t x(s) ds + [B + \Delta B(t)]u(t) \end{aligned} \quad (1)$$

$$x(t) = \phi(t), t \in [-l, 0]$$

where $x(t) \in \mathfrak{R}^n$ and $u(t) \in \mathfrak{R}^m$ are the state and input of system, respectively. $A, A_\sigma, A_\eta, A_\delta$, and B are known constant matrices of appropriate dimensions. $\phi(t)$ is the initial condition. σ, η , and δ are the time delays, $l = \max\{\sigma, \eta, \delta\}$. Time-varying parametric uncertainties $\Delta A(t), \Delta A_\sigma(t), \Delta A_\eta(t), \Delta A_\delta(t)$ and $\Delta B(t)$ are assumed to satisfy

$$\begin{aligned} & \begin{bmatrix} \Delta A(t) & \Delta A_\sigma(t) & \Delta A_\eta(t) & \Delta A_\delta(t) & \Delta B(t) \end{bmatrix} \\ & = DF(t) \begin{bmatrix} E_1 & E_\sigma & E_\eta & E_\delta & E_2 \end{bmatrix} \end{aligned} \quad (2)$$

where matrices $D, E_1, E_\sigma, E_\eta, E_\delta$, and E_2 are constant matrices of appropriate dimensions, and $F(t)$ is the unknown matrix function satisfying $F^T(t)F(t) \leq I, \forall t \geq 0$.

Construct the following control law

$$u(t) = -Kx(t) \quad (3)$$

where $K \in \mathfrak{R}^{m \times n}$ is the control gain to be designed, the resulting closed-loop uncertain neutral system is obtained,

$$\begin{aligned}\dot{x}(t) = & [A - BK + DF(t)(E_1 - E_2K)]x(t) + [A_\sigma + DF(t)E_\sigma]x(t - \sigma) \\ & + [A_\eta + DF(t)E_\eta]\dot{x}(t - \eta) + [A_\delta + DF(t)E_\delta]\int_{t-\delta}^t x(s) ds\end{aligned}\quad (4)$$

Define the following quadratic cost function

$$J = \int_0^\infty [x^T(t)S_1x(t) + u^T(t)S_2u(t)] dt \quad (5)$$

where $S_1 \in \mathfrak{R}^{n \times n}$ and $S_2 \in \mathfrak{R}^{m \times m}$ are two given symmetric positive definite matrices.

The objective of this note is to design a control (3) and determine a scalar J_u satisfying the following two conditions

- (a) the closed-loop system (4) is asymptotically stable,
- (b) $J \leq J_u$.

If the aforementioned control gain K and constant J_u exist, control (3) is the guaranteed cost control and J_u is the guaranteed cost for the considered system.

The following lemma is used for the proof of the main results.

Lemma 2.1 Let Z , X , S and Y be matrices of appropriate dimensions.

Assume that Z is symmetric and $S^T S \leq I$, then

$$Z + XSY + Y^T S^T X^T < 0$$

if and only if there exists a scalar $\varepsilon > 0$ satisfying

$$Z + \varepsilon XX^T + \varepsilon^{-1} Y^T Y = Z + \varepsilon^{-1} (\varepsilon X)(\varepsilon X)^T + \varepsilon^{-1} Y^T Y < 0$$

3 Main Result

Theorem 3.1 Consider system (1) with (2) and (3). If there exist positive numbers ε , τ , some symmetric positive definite matrices Q , \bar{H}_1 , \bar{H}_2 , and matrix X such that the following LMIs hold

$$\Xi = \begin{bmatrix} \Xi_{11} & A_\sigma Q & A_\eta & A_\delta Q & QA^T - X^T B^T & Q & -X^T & \varepsilon D & \Xi_{19} \\ * & -\bar{H}_1 & 0 & 0 & QA_\sigma^T & 0 & 0 & 0 & QE_\sigma^T \\ * & * & -I_n & 0 & A_\eta^T & 0 & 0 & 0 & E_\eta^T \\ * & * & * & -\bar{H}_2 & QA_\delta^T & 0 & 0 & 0 & QE_\delta^T \\ * & * & * & * & -I_n & 0 & 0 & \varepsilon D & 0 \\ * & * & * & * & * & -S_1^{-1} & 0 & 0 & 0 \\ * & * & * & * & * & * & -S_2^{-1} & 0 & 0 \\ * & * & * & * & * & * & * & -\varepsilon I_n & 0 \\ * & * & * & * & * & * & * & * & -\varepsilon I_n \end{bmatrix} < 0 \quad (6)$$

$$\Gamma = \begin{bmatrix} -I_n + \tau E_\eta^T E_\eta & A_\eta^T & 0 \\ * & -I_n & D \\ * & * & -\tau I_n \end{bmatrix} < 0 \quad (7)$$

Then control (3) with $K = XQ^{-1}$ is the guaranteed cost control of system (1) with the following guaranteed cost

$$\begin{aligned} J_u &= \phi^T(0)Q^{-1}\phi(0) + \int_{-\sigma}^0 \phi^T(s)Q^{-1}\bar{H}_1Q^{-1}\phi(s)ds + \int_{-\eta}^0 \dot{\phi}^T(s)\dot{\phi}(s)ds \\ &+ \int_{-\delta}^0 \left[\int_s^0 \phi^T(\theta)d\theta \right] Q^{-1}\bar{H}_2Q^{-1} \left[\int_s^0 \phi(\theta)d\theta \right] ds \\ &+ \int_0^\delta ds \int_{-s}^0 (\theta+s)\phi^T(\theta)Q^{-1}\bar{H}_2Q^{-1}\phi(\theta)d\theta \end{aligned} \quad (8)$$

where $\Xi_{11} = AQ + QA^T - BX - X^T B^T + \bar{H}_1 + \delta^2 \bar{H}_2$, $\Xi_{19} = QE_1^T - X^T E_2^T$.

Proof: Choose $P = Q^{-1}$, $H_1 = Q^{-1}\bar{H}_1Q^{-1}$, $H_2 = Q^{-1}\bar{H}_2Q^{-1}$, and construct the following Lyapunov functional

$$V(x(t), t) = V_1(x(t)) + V_2(x(t)) + V_3(x(t)) + V_4(x(t)) + V_5(x(t)) \quad (9)$$

where

$$\begin{aligned} V_1(x(t)) &= x^T(t)Px(t), V_2(x(t)) = \int_{t-\sigma}^t x^T(s)H_1x(s)ds, \\ V_3(x(t)) &= \int_{t-\eta}^t \dot{x}^T(s)\dot{x}(s)ds, V_4(x(t)) = \int_{t-\delta}^t \left[\int_s^t x^T(\theta)d\theta \right] H_2 \left[\int_s^t x(\theta)d\theta \right] ds, \\ V_5(x(t)) &= \int_0^\delta ds \int_{t-s}^t (\theta-t+s)x^T(\theta)H_2x(\theta)d\theta \end{aligned}$$

Obviously, $V(x(t), t) > 0$ for all $x(t) \neq 0$. The time derivative of $V(x(t), t)$ along the trajectories of system (1) with control (3) is given

$$\dot{V}(x(t), t) = \dot{V}_1(x(t)) + \dot{V}_2(x(t)) + \dot{V}_3(x(t)) + \dot{V}_4(x(t)) + \dot{V}_5(x(t)) \quad (10)$$

where

$$\begin{aligned} \dot{V}_1(x(t)) &= 2x^T(t)P[(A - BK + DF(t)(E_1 - E_2K))x(t) \\ &\quad + (A_\sigma + DF(t)E_\sigma)x(t - \sigma) + (A_\eta + DF(t)E_\eta)\dot{x}(t - \eta) \\ &\quad + (A_\delta + DF(t)E_\delta)\int_{t-\delta}^t x(s) ds \\ \dot{V}_2(x(t)) &= x^T(t)H_1x(t) - x^T(t - \sigma)H_1x(t - \sigma), \\ \dot{V}_3(x(t)) &= \dot{x}^T(t)\dot{x}(t) - \dot{x}^T(t - \eta)\dot{x}(t - \eta) \\ &= [(A - BK + DF(t)(E_1 - E_2K))x(t) + (A_\sigma + DF(t)E_\sigma)x(t - \sigma) \\ &\quad + (A_\eta + DF(t)E_\eta)\dot{x}(t - \eta) + (A_\delta + DF(t)E_\delta)\int_{t-\delta}^t x(s) ds]^T \\ &\quad \times [(A - BK + DF(t)(E_1 - E_2K))x(t) + (A_\sigma + DF(t)E_\sigma)x(t - \sigma) \\ &\quad + (A_\eta + DF(t)E_\eta)\dot{x}(t - \eta) + (A_\delta + DF(t)E_\delta)\int_{t-\delta}^t x(s) ds] \\ &\quad - \dot{x}^T(t - \eta)\dot{x}(t - \eta), \\ \dot{V}_4(x(t)) &= 2\int_{t-\delta}^t (\theta - t + \delta)x^T(t)H_2x(\theta) d\theta \\ &\quad - \left[\int_{t-\delta}^t x^T(\theta) d\theta \right] H_2 \left[\int_{t-\delta}^t x(\theta) d\theta \right] \\ &\leq \int_{t-\delta}^t (\theta - t + \delta)x^T(t)H_2x(t) d(\theta - t + \delta) \\ &\quad + \int_{t-\delta}^t (\theta - t + \delta)x^T(\theta)H_2x(\theta) d\theta \\ &\quad - \left[\int_{t-\delta}^t x^T(\theta) d\theta \right] H_2 \left[\int_{t-\delta}^t x(\theta) d\theta \right] \\ &= \frac{1}{2}\delta^2 x^T(t)H_2x(t) + \int_{t-\delta}^t (\theta - t + \delta)x^T(\theta)H_2x(\theta) d\theta \\ &\quad - \left[\int_{t-\delta}^t x^T(\theta) d\theta \right] H_2 \left[\int_{t-\delta}^t x(\theta) d\theta \right], \\ \dot{V}_5(x(t)) &= \frac{1}{2}\delta^2 x^T(t)H_2x(t) - \int_{t-\delta}^t (\theta - t + \delta)x^T(\theta)H_2x(\theta) d\theta. \end{aligned}$$

Therefore, it follows from (10) that

$$\begin{aligned}
\dot{V}(x(t), t) + x^T(t)S_1x(t) + u^T(t)S_2u(t) &= \dot{V}(x(t), t) + x^T(t)S_1x(t) \\
&\quad + x^T(t)K^T S_2 Kx(t) \quad (11) \\
&\leq \xi^T Y \xi
\end{aligned}$$

where

$$\xi^T = \begin{bmatrix} x^T(t) & x^T(t-\sigma) & \dot{x}^T(t-\eta) & \int_{t-\delta}^t x^T(s) ds \end{bmatrix},$$

$$Y = \Omega + G_1 G_1^T + G_2 S_1 G_2^T + G_3 S_2 G_3^T,$$

$$\Omega = \begin{bmatrix} \Omega_{11} & P[A_\sigma + DF(t)E_\sigma] & P[A_\eta + DF(t)E_\eta] & P[A_\delta + DF(t)E_\delta] \\ * & -H_1 & 0 & 0 \\ * & * & -I_n & 0 \\ * & * & * & -H_2 \end{bmatrix},$$

$$\Omega_{11} = P[A - BK + DF(t)(E_1 - E_2 K)] + [A - BK + DF(t)(E_1 - E_2 K)]^T P + H_1 + \delta^2 H_2,$$

$$G_1 = \begin{bmatrix} (A - BK)^T + (E_1 - E_2 K)^T F^T(t) D^T \\ A_\sigma^T + E_\sigma^T F^T(t) D^T \\ A_\eta^T + E_\eta^T F^T(t) D^T \\ A_\delta^T + E_\delta^T F^T(t) D^T \end{bmatrix}, G_2 = \begin{bmatrix} I_n \\ 0 \\ 0 \\ 0 \end{bmatrix}, G_3 = \begin{bmatrix} -K^T \\ 0 \\ 0 \\ 0 \end{bmatrix}.$$

Define

$$\bar{Y} = \begin{bmatrix} \Omega & G_1 & G_2 & G_3 \\ * & -I_n & 0 & 0 \\ * & * & -S_1^{-1} & 0 \\ * & * & * & -S_2^{-1} \end{bmatrix} \quad (12)$$

Pre- and post-multiplying the matrix \bar{Y} in (12) by U^T and U , where

$$U = \text{diag}\{P^{-1}, P^{-1}, I_n, P^{-1}, I_n, I_n, I_m\} = \text{diag}\{Q, Q, I_n, Q, I_n, I_n, I_m\},$$

and substituting KQ , QH_1Q , and QH_2Q with X , \bar{H}_1 , and \bar{H}_2 , respectively, the following matrix is obtained

$$\Theta = \begin{bmatrix} \bar{\Omega} & \bar{G}_1 & \bar{G}_2 & \bar{G}_3 \\ * & -I_n & 0 & 0 \\ * & * & -S_1^{-1} & 0 \\ * & * & * & -S_2^{-1} \end{bmatrix} \quad (13)$$

where

$$\bar{\Omega} = \begin{bmatrix} \bar{\Omega}_{11} & [A_\sigma + DF(t)E_\sigma]Q & A_\eta + DF(t)E_\eta & [A_\delta + DF(t)E_\delta]Q \\ * & -\bar{H}_1 & 0 & 0 \\ * & * & -I_n & 0 \\ * & * & * & -\bar{H}_2 \end{bmatrix},$$

$$\bar{\Omega}_{11} = AQ - BX + DF(E_1Q - E_2X) + QA^T - X^T B^T$$

$$+ (QE_1^T - X^T E_2^T)F^T(t)D^T + \bar{H}_1 + \delta^2 \bar{H}_2, \quad \text{I}$$

$$\bar{G}_1 = \begin{bmatrix} QA^T - X^T B^T + (QE_1^T - X^T E_2^T)F^T(t)D^T \\ QA_\sigma^T + QE_\sigma^T F^T(t)D^T \\ A_\eta^T + E_\eta^T F^T(t)D^T \\ QA_\delta^T + QE_\delta^T F^T(t)D^T \end{bmatrix}, \bar{G}_2 = \begin{bmatrix} Q \\ 0 \\ 0 \\ 0 \end{bmatrix}, \bar{G}_3 = \begin{bmatrix} -X^T \\ 0 \\ 0 \\ 0 \end{bmatrix}.$$

It is obvious that

$$\Theta = \begin{bmatrix} \Xi_{11} & A_\sigma Q & A_\eta & A_\delta Q & QA^T - X^T B^T & Q & -X^T \\ * & -\bar{H}_1 & 0 & 0 & QA_\sigma^T & 0 & 0 \\ * & * & -I_n & 0 & A_\eta^T & 0 & 0 \\ * & * & * & -\bar{H}_2 & QA_\delta^T & 0 & 0 \\ * & * & * & * & -I_n & 0 & 0 \\ * & * & * & * & * & -S_1^{-1} & 0 \\ * & * & * & * & * & * & -S_2^{-1} \end{bmatrix}$$

$$+ \Lambda^T F(t)\$ + \$^T F^T(t)\Lambda \quad (14)$$

where

$$\Lambda = \begin{bmatrix} D^T & 0 & 0 & 0 & D^T & 0 & 0 \end{bmatrix},$$

$$\$ = \begin{bmatrix} E_1Q - E_2X & E_\sigma Q & E_\eta & E_\delta Q & 0 & 0 & 0 \end{bmatrix}.$$

By **Lemma 2.1** and Schur complement formula, the condition $\Xi < 0$ in (6) is equivalent to $\Theta < 0$ in (14). According to (12), (13), and (14), $\Theta < 0$ is equivalent to $\bar{Y} < 0$. Applying Schur complement formula to $\bar{Y} < 0$, one can obtain $Y < 0$ in (11). From the condition $Y < 0$ in (11), there exists a constant $\rho > 0$, such that

$$\dot{V}(x(t), t) \leq -\rho \|x(t)\|_2^2 \quad (15)$$

Another, by Schur complement formula, $\Gamma < 0$ in (7) is equivalent to the following one

$$\begin{bmatrix} -I_n + \tau E_\eta^T E_\eta & A_\eta^T \\ * & -I_n \end{bmatrix} + \tau^{-1} \begin{bmatrix} 0 \\ D \end{bmatrix} \begin{bmatrix} 0 & D^T \end{bmatrix} < 0 \quad (16)$$

that is

$$\begin{bmatrix} -I_n & A_\eta^T \\ * & -I_n \end{bmatrix} + \tau \begin{bmatrix} E_\eta^T \\ 0 \end{bmatrix} \begin{bmatrix} E_\eta & 0 \end{bmatrix} + \tau^{-1} \begin{bmatrix} 0 \\ D \end{bmatrix} \begin{bmatrix} 0 & D^T \end{bmatrix} < 0 \quad (17)$$

According to **Lemma 2.1**, inequality (17) is equivalent to the following one

$$\begin{bmatrix} -I_n & A_\eta^T \\ * & -I_n \end{bmatrix} + \begin{bmatrix} 0 \\ D \end{bmatrix} F(t) \begin{bmatrix} E_\eta & 0 \end{bmatrix} + \begin{bmatrix} E_\eta^T \\ 0 \end{bmatrix} F^T(t) \begin{bmatrix} 0 & D^T \end{bmatrix} < 0 \quad (18)$$

that is

$$\begin{bmatrix} -I_n & A_\eta^T + E_\eta^T F^T(t) D^T \\ * & -I_n \end{bmatrix} < 0 \quad (19)$$

By Schur complement formula, inequality (19) is equivalent to the following one

$$(A_\eta + DF(t)E_\eta)^T (A_\eta + DF(t)E_\eta) < I_n \quad (20)$$

that is

$$\|A_\eta + \Delta A_\eta\|_2 < 1 \quad (21)$$

This means that system (1) is Lipschitz in the term $\dot{x}(t - \eta(t))$ with Lipschitz constant less than 1.

Hence, by conditions (9) and (15), and (21), one can conclude that system (1) with (2) and (3) is asymptotically stable. From (11) with $Y < 0$, one can obtain

$$\begin{aligned} \int_0^\infty \dot{V}(x(t), t) dt &= \lim_{t \rightarrow \infty} V(x(t), t) - V(x(0), 0) \\ &\leq - \int_0^\infty [x^T(t) S_1 x(t) + u^T(t) S_2 u(t)] dt \end{aligned}$$

Therefore,

$$\lim_{t \rightarrow \infty} V(x(t), t) = 0, \int_0^\infty [x^T(t) S_1 x(t) + u^T(t) S_2 u(t)] dt \leq V(x(0), 0) = J_u.$$

This completes the proof.

4 Illustrative Example

In this section, a numerical example is presented to show the validity of the control approach. A three-order system with two inputs is considered with the following parameters

$$A = \begin{bmatrix} -25.2 & 1.3 & 3.3 \\ 11.5 & -3.5 & 2.8 \\ 2.9 & -14.1 & -5.1 \end{bmatrix}, A_\sigma = \begin{bmatrix} -2.1 & -1.3 & 0.2 \\ 1.1 & 0.5 & 0.5 \\ 0.7 & -1.6 & 0.1 \end{bmatrix}, B = \begin{bmatrix} 1.5 & 2.2 \\ -2.3 & -0.1 \\ -3.5 & 1.5 \end{bmatrix},$$

$$A_\eta = \begin{bmatrix} 0.1 & -0.3 & -0.1 \\ 0.1 & 0.5 & -0.1 \\ 0.2 & 0.1 & -0.5 \end{bmatrix}, A_\delta = \begin{bmatrix} -2.1 & 0.2 & -0.4 \\ 0.1 & 0.2 & 0.2 \\ -0.8 & -0.4 & 1.4 \end{bmatrix}, \sigma = 0.1,$$

$$D = \begin{bmatrix} -0.5 & 0.2 & 0.1 \\ 0.1 & -0.7 & -0.2 \\ -0.1 & 0.3 & 0.1 \end{bmatrix}, E_1 = \begin{bmatrix} 0.3 & -0.1 & 0.1 \\ 0.4 & -0.5 & -0.1 \\ -0.1 & 0.2 & 0.1 \end{bmatrix}, \eta = 0.1,$$

$$E_\sigma = \begin{bmatrix} -0.1 & -0.1 & 0.1 \\ -0.1 & 0.2 & 0.1 \\ 0.1 & -0.1 & -0.2 \end{bmatrix}, E_\eta = \begin{bmatrix} 0.1 & 0.1 & -0.1 \\ -0.1 & 0.2 & -0.1 \\ -0.1 & -0.1 & 0.1 \end{bmatrix}, \delta = 0.2,$$

$$E_\delta = \begin{bmatrix} -0.2 & -0.2 & 0.3 \\ -0.3 & -0.2 & 0.1 \\ 0.1 & 0.4 & 0.4 \end{bmatrix}, E_2 = \begin{bmatrix} -0.6 & -0.3 \\ -0.1 & 0.1 \\ -0.4 & 0.2 \end{bmatrix}.$$

Let

$$S_1 = \text{diag}\{0.5, 0.5, 0.5\}, S_2 = \text{diag}\{2, 2\}$$

and the initial condition is given by

$$\phi(t) = [-0.1 + t \quad 0.15 \quad 0.2t + 0.05]^T$$

Applying Matlab toolbox^[9,10] to solving the LMIs (6) and (7) with above parameters, one can obtain

$$Q = \begin{bmatrix} 0.0405 & -0.0193 & -0.0007 \\ -0.0193 & 0.0611 & -0.0810 \\ -0.0007 & -0.0810 & 0.1461 \end{bmatrix}, \varepsilon = 0.6067,$$

$$X = \begin{bmatrix} -0.1478 & 0.0268 & -0.2684 \\ -0.0149 & -0.0876 & 0.2976 \end{bmatrix}, \tau = 5.1734,$$

$$\bar{H}_1 = \begin{bmatrix} 0.3369 & -0.1033 & -0.0637 \\ -0.1033 & 0.1822 & -0.0344 \\ -0.0637 & -0.0344 & 0.2582 \end{bmatrix},$$

$$\bar{H}_2 = \begin{bmatrix} 7.8186 & -2.3760 & -1.4933 \\ -2.3760 & 4.0091 & -0.0089 \\ -1.4933 & -0.0089 & 5.0074 \end{bmatrix},$$

$$P = \begin{bmatrix} 60.5751 & 73.8035 & 41.2087 \\ 73.8035 & 151.7409 & 84.4717 \\ 41.2087 & 84.4717 & 53.8685 \end{bmatrix},$$

$$K = \begin{bmatrix} -18.0362 & -29.5139 & -18.2854 \\ 4.8911 & 10.7387 & 8.0133 \end{bmatrix},$$

$$H_1 = \begin{bmatrix} 1.2164 & 1.9843 & 1.1349 \\ 1.9843 & 3.8833 & 2.2436 \\ 1.1349 & 2.2436 & 1.3066 \end{bmatrix} * 10^3,$$

$$H_2 = \begin{bmatrix} 3.0276 & 5.0207 & 2.8767 \\ 5.0207 & 9.8562 & 5.7011 \\ 2.8767 & 5.7011 & 3.3162 \end{bmatrix} * 10^4,$$

$$J_u = 10.7543.$$

5 Conclusion

The guaranteed cost control for uncertain distributed delay system with neutral type is complex and challenging. In view of the importance of the choice of an appropriate Lyapunov-Krasovskii functional for deriving good stability criteria for delay system, a special form of Lyapunov-Krasovskii functional is constructed to lead to simpler and less conservative sufficient conditions. Simultaneously, some mathematical techniques are applied flexibly. Especially, the order of repeated integral is exchanged. Based the criterion, the control gain and the guaranteed cost are obtained. Finally, the numerical example has shown the validity of the present control approach.

References

1. Lien, C. H., Non-fragile guaranteed cost control for uncertain neutral dynamic systems with time-varying delays in state and control input, *Chaos, Solitons & Fractals*, vol.31, no.4, pp.889-899, 2007.
2. Ivanevescu, D., Niculescu, S. I., Dugard, L., Dion, J. M., and Verriest, E. I., On delay-dependent stability for linear neutral systems, *Automatica*, vol.39, no.2, pp.255-261, 2003.
3. Xu, S. and Chen, T., An LMI approach to the H_∞ filter design for uncertain system with distributed delays, *IEEE Trans. on Circuits and Systems-II*, vol. 51, no. 4, pp. 195-201, 2004.
4. Zheng, F. and Frank, P. M., Robust control of uncertain distributed delay systems with application to the stabilization of combustion in rocket motor chambers, *Automatica*, vol. 38, no. 3, pp. 487-497, 2002.
5. Xu, S. Y., Lam, J., Chen, T. W. and Zou, Y., A delay-dependent approach to robust H_∞ filtering for uncertain distributed delay systems, *IEEE Transactions on Signal Processing*, vol. 53, no. 10, pp. 3764-3772, 2005.
6. Cheng, Y. C., Hwang, C., Chen, C. T., Evaluation of quadratic cost functionals for a class of distributed-delay systems, *IET Control Theory Applications*, vol. 1, no. 1, pp. 313-319, 2007.
7. Yuan, K., Li, H. X. and Cao, J. D., Robust stabilization of the distributed parameter system with time delay via fuzzy control, *IEEE Transactions on Fuzzy Systems*, vol. 16, no. 3, pp. 567-584, 2008.
8. Park, J. H., Robust guaranteed cost control for uncertain linear differential systems of neutral type, *Applied Mathematics and Computation*, vol.140, no.2-3, pp.523-535, 2003.
9. Gahinet, P., Nemirovski, A., Laub, A. J. and Chilali, M., *LMI control toolbox user's guide*, The Math Works Inc. Natick Mass., 1995.
10. Boyd, S., Ghaoui, L. E., Feron, E. and Balakrishnan, V., *Linear Matrix Inequalities in Systems and Control Theory*, SIAM, Philadelphia, 1994.
11. Xu, S. Y., Lam, J., Wang, J. L. and Yang, G. H., Non-fragile positive real control for uncertain linear neutral delay systems, *System & Control Letters*, vol.52, no.1, pp.59-74, 2004.
12. Lien, C. H. and Yu K. W., Non-fragile H_∞ control for uncertain neutral systems with time-varying delays via the LMI optimization approach, *IEEE Transactions on Systems, Man, Cybernetics-Part B: Cybernetics*, vol.37, no.2, pp.493-499, 2007.