

Linking and Consuming Agricultural Big Data with Linked Data and KOS

Guojian Xian, Ruixue Zhao, Xianxue Meng, Yuantao Kou, Liang Zhu

► To cite this version:

Guojian Xian, Ruixue Zhao, Xianxue Meng, Yuantao Kou, Liang Zhu. Linking and Consuming Agricultural Big Data with Linked Data and KOS. 8th International Conference on Computer and Computing Technologies in Agriculture (CCTA), Sep 2014, Beijing, China. pp.546-555, 10.1007/978-3-319-19620-6_61. hal-01420270

HAL Id: hal-01420270 https://inria.hal.science/hal-01420270

Submitted on 20 Dec 2016

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Linking and Consuming Agricultural Big Data with Linked Data and KOS

Guojian Xian^{1, a}, Ruixue Zhao^{1, b}, Xianxue Meng^{1, c}, Yuantao Kou^{1, d}, Liang Zhu^{1, e}

¹Agricultural Information Institution of CAAS, Beijing 100081, P. R. China ^axianguojian@caas.cn, ^bzhaoruixue@caas.cn, ^cmengxianxue@caas.cn, ^dkouyuantan@caas.cn, ^ezhuliang@caas.cn

Abstract. This paper gives brief introduction about the big data, linked data and knowledge organization systems (KOS) and their relationships. As the authors mainly focus on the variety and value characteristics of big data, the linked data and KOS technologies are used to link and consume the large amounts of literature and scientific data in agricultural research community. The results show that it is a good way to describe, connect, organize, represent, visualize and access to big data effectively and semantically based on the linked data and KOS technologies.

Keywords: Big Data, Linked Data, Knowledge Organization System (KOS), Semantic Web, Scientific Data

1 Introduction

Big data is now one of the hottest topics. Nowadays, we are generating huge amount of data every day, and the total volume of data would be doubled every 18 months, as for the rise of multimedia, social media, and the Internet of Things. It is true that of our activity, innovation, and growth are more and more based on the big data[1]. When talking about big data, people are likely to focus on technical issues, such as scalability, performance and how to deal with large quantities of heterogeneous data, but pay less attention to the connections, interoperability of data in disparate sources, and how to make sense of all the large data pools either. Actually, there are both latent and actual links, which are worth enriching, utilizing and publishing along with the raw dat. In most cases, it is the connections inside and outside of big data where the real value lies.

The formalized, structured and organized nature of linked data and its specific applications, such as the linked knowledge organization systems (KOS), have the potential to provide a solid semantic foundation for the classification, connection, representation, visualization of big data.

The reminder of this paper will firstly give a conceptual analysis of big data, linked data and KOS. And then we will illustrate how to create and consume semantic big data in agricultural research community, utilizing linked data technologies and knowledge organization systems as new tools for the describing, linking, organization, representation, visualization and access to big data.

2 Big Data, Linked Data and KOS

Big data always refers to large, diverse, complex, longitudinal, distributed data sets generated from instruments, sensors, internet transactions, email, video, click streams, and other digital sources. While there is no generally agreed understanding of what exactly is big data, an increasing number of V's has been used to characterize different dimensions and challenges of big data: volume, velocity, variety, value, and veracity[2, 10]. These terms means to the growing volume of different types of structured and unstructured data, the complex and heterogeneous nature and machine-processability. The organization, exploration, management, preservation, visualization and access to and use of these types of data pose technological and computational challenges.

Linked Data defines a set of guidelines, best practices or patterns for exposing, publishing, sharing, and connecting pieces of data, information, and knowledge on the Semantic Web using URIs and RDF[3, 11], which takes the WWW's ideas of global identifiers and links and applies them to (raw) data, not just documents[12-13]. Linked data can be effectively used as a broker, mapping and interconnecting, indexing and feeding real-time information from a variety of sources, and inferring relationships from big data analysis that might otherwise have been discarded, which is made all the more valuable by the connections (links) that tie it all together than the sum of its volume, velocity and variety.

Semantic text analysis, natural language processing, data mining and data visualization are the typical challenges in addressing the management and effective use of big data[4]. The knowledge organization systems, such as thesauri, classifications, subject headings, taxonomies, and folksonomies would increasingly important roles. As W3C's standard, the Simple Knowledge Organization System (SKOS) standard, aims to build a bridge between the world of KOS and the linked data community[17]. SKOS-based linked controlled vocabularies can provide a framework rich in semantics to effectively manage big data through combining, aligning and cross-linking multiple KOSs in order to automatic or semi-automatic analyzing, indexing and organizing text, and develop faceted, categorized or hierarchical views of big data[5].

A typical and successful example of combining the big data, linked data and KOS together is the new semantic web platform version of Agris: OpenAgris[6]. Based on nearly 4 million structured bibliographical records on agricultural science and technology, and AGROVOC vocabularies, alignment between KOS and ontologies, the OpenAgris also aggregates various open access data sources available on the Web, providing much data as possible about a topic or a bibliographical resource[7, 20].

3 Linking Agricultural Big Data

The 4th paradigm of science – data intensive scientific discovery has emerged within the last years, which means scientific innovations and breakthroughs will be powered by advanced computing capabilities that help researchers manipulate and explore massive datasets[8]. As for the several V's characteristics of big data, different disciplines highlight certain dimensions and neglect others. Fox example, people working on sensor and the internet of things may care more about the velocity, super-computing would be mostly interested in the volume dimension, and the research community pay more attentions to variety and value dimensions of big data. The Chinese governments always pay high attentions to the agricultural science and technology innovation and the development of modern agriculture. With more investments are input to this sector, a large amount of agricultural big datasets are produced, such as the 3S data, scientific research data, and academic achievements (e.g. papers, books, proceedings, reports). These data have different formats, conceptualizations or data models, temporal and spatial dependencies[9]. Effective usage of these big data is very important to promote and advance the research work in a new round.

The following parts of this paper will explain how to describe, organize, integrate, and consume parts of these agricultural big data with linked data and KOS technologies, as we just focus on the variety and value dimensions of big data.

3.1 Linking Chinese Agricultural Thesaurus to other KOS

As KOS can play important role to addressing some challenges of the big data, such as text analysis, natural language processing, data mining and data visualization of big data, the priority of our work is to convert the Chinese Agricultural Thesaurus (CAT) as linked data and link to other KOS.

CAT was developed by Agricultural Information Institution of CAAS in early 1990s and kept maintenance all the time. So far, CAT contains more than 60,000 Chinese descriptors and non-descriptors, most have corresponding English translations, and also include about 130,000 semantic relationships, such as UF, BT, NT and RT.

We describe CAT's concepts and their semantic relationships with SKOS and SKOS-XL standards. In addition, we map and link CAT to other well-known KOS such as AGROVOC, NALT, EUROVOC and LCSH, as shown in Fig.1.



Fig. 1 The SKOS Model of CAT and Link to Other KOSs

We also develop a SKOS-based CAT linked data web system, providing services such as HTTP URI dereference, CAT concepts browsing and navigation, SPARQL query endpoint and RDF Triples Dumps, as shown in Fig.2. This work could greatly improve the CAT's visibility, accessibility and interoperability with other systems, and lay fundamental base to describe, organize and link other agricultural information resources semantically as well.



Fig. 2 The Linked Open data of SKOS-Based CAT

3.2 Linking Agricultural Literature and Scientific Research Data

As the current global research data is highly fragmented, by disciplines or by domains, from oceanography, life sciences and health, to agriculture, space and climate[21]. When it comes to cross-disciplinary activities, building specific "data bridges" are becoming accepted metaphors for approaching the data complexity and enable data sharing.

The millions of books, journals, proceedings and bibliographic records of the China National Agricultural Library, and also over 700 scientific datasets holds in the National Agricultural Scientific Data Sharing Platform, are the most valuable data materials for agricultural research communities. What we want to do most here is connect these literature and research data together in a light-weighted semantically way. Fig.3 shows the available and linkable data resources we could access to.



Fig. 3 Available and Linkable Agricultural Data Resources

We analyze and abstract the main classes and properties from the literature and bibliographic records of the China National Agricultural Library, and also reuse the widely used vocabularies and ontologies such as DCMI[15], BIBO[16], etc., to formally describe and model these classes, properties and their semantic relationships. The following table shows the mapping result of the journal article (bibo:AcademicArticle) and its properties to common vocabularies and ontologies.

Property	Туре	Available Vacobulary					
title	DataProperty	dc:title、swrc:title					
alternateTitle	DataProperty	dcterms:alternative、prism:alternateTitle					
author	ObjectProperty	dc:creator、foaf:maker、swrc:creator					
keywords	ObjectProperty/	dc:subject、swrc:keywords、					
	DataProperty	prism:keyword					
abstract	DeteBroperty	bibo:abstract、dcterms:abstract、					
	DataFlopeny	swrc:abstract					
language	DataProperty	dc:language、swrc:language					
startPage	DataProperty	bibo:pageStart、prism:startingPage					
endPage	DataProperty	bibo:pageEnd、prism:endingPage					
totalPage	DataProperty	bibo:numPages、prism:pageCount					
DOI	ObjectProperty	bibo:doi、prism:doi					

Table 1. The Core Properties of Journal Article

We also describe and connect the widely used literature, such as books, journals, collections, proceedings together, and the concepts and semantic relationships of CAT are taken into consideration while designing the describing and linking model (Fig.4).



4 Bibliographic Records and Literature Linking Model

The most interested and meaningful work we done is integrating and linking the SKOS-based CAT and several kinds of literature to the scientific research datasets. So far, we have modeled and linked about 700 core metadata of the scientific research datasets, and also some particular datasets hold the data about the institutes, researchers and projects of agricultural related domain, by reusing the well-known vocabularies or ontologies (e.g. VIVO, SWRC, FOAF)[19].The multidimensional semantic linking model covering the scientific data, literatures, and thesaurus we designed is as shown in Fig 5.



Fig. 5 Multidimensional Linking Model Covering the Scientific Data, Literatures and KOS

In order to process these resource based on the SKOS-based CAT, we developed an automatic text analyzing and indexing tool based on some open source tools, such as Lucene, IKAnalyzer, etc. The tool we realized could tag the concepts and semantic links of CAT into these literatures and scientific datasets. That is a very important step to make semantic connections between several kinds of data from different sources, with the professional knowledge of KOS.

As for most of the data resources mentioned above are stored in relational database, so we construct and publish the semantic agricultural linked data based on the open source software D2R Server[14].



Fig. 6 The Linked Data Publishing Platform Based on D2R

4 Consuming Linked Agricultural Big Data

One effective way to explore and mine the linked big data is following the linked data rules and utilizing some semantic web technologies, here we do not care too much about the volume of big data and neither the computing performance. We pay more attentions to the variety and value of the big data.

The architecture and function models of domain knowledge service system have been designed, which totally driven by the linked data, as shown in Fig. 7. A prototype system was realized based on some key technologies such as SPARQL, Virtuoso[17]

and so forth, see Fig.8. Some import service functions have been provided in this system, such as integrated browsing and discovery of domain knowledge, dynamic facet navigation and searching, SPARQL query endpoint, HTTP URI dereferencing, downloading RDF triples.





/dii	关联载 # Cheber D	据驱动的领域知识服务 ata-driven & Domain Knowledge Service-	·原型系统(*# eriented System for Rese	archers		• (8)					
RDF=708(Triple	les):科技文和和	科学教派 2,572,279 个; 叙词表 477,686个 OHTMU	N范 - RDFN范 - D2R SPAN		Virtuoso Si	ARQLİĞ 🕸 🔩 🕇	TP URI算引解析			风档切换	1000.00 ×
D MAR 88 19413	AM	· · · · · · · · · · · · · · · · · · ·									
· 期刊文摘(4	48789)	約4初人员				× 🔆 🛪 🕫	FRI				* + X
- 图书(332)			The second second					-			
 文集汇编() 学术会议(4) 学术期刊(4) 会议录(A5) 	794) 469) 42) 8)				ato	Roce Science	Rice	Plant Soil Fian	Science Plant Science	rt Molecular B	Sology
• 赵硕太阳(4	4035)	BURT BOOK BILLS SHOW									
 文集汇编文 	18 (15190)	一种研究和				× 🛃 #4#10	4 相談目				(a) + X
- 会议录文编	(23840)	KUKDERE GEBERTER	0.7458	BIRD S		1010	RER	REP 445%	核素目期	126.0	
. EL 18 AU 40 (4	4154)	1 影売康布休報節報点 1972年	http://jod.apinfra.cn/p	(0859) 32	31317	1 2280	547 EL 1 22 10 10	01/01/95	12/31/00	da la	
EILETS EI (1	2007)		http://dd.aginina.com. (005		21317	1 ACROWED 4-1 KEVEL	No. + Aberlin.	10,0100	12/31/00	HIG I	
• 种知识目(科研·纳日(JUU// 2 黑龙江省黑河农业科 1968年 http://iod.agin/ra.cn/h(045		(0456)82	23635	2 76384	2 花期前标准一组核路		12/31/02	厂四农料碗发展基金		
数据库集 (769) 3 黑龙江留野生动物研 1979年 http://iod.aginfra.cn/h (045		(0451)66	02244	3 龙眼	3 龙眼低产因改造及南 4 龙眼代良品种的单株		12/31/02	广西区科技厅 广西区科技厅科技发			
 叙词概念(60493) 			D451-86665	716/139			4 龙眼(12/31/98	
 论文作者(2) 	200201)	5 開始:T留窗校研究所 1957年	http://iod.aginfra.cn/h	(0452)69	81211	5 89551	积(后子)新品种	08/12/99	08/12/01	895510	8(括子)動品種
1		8: 68 + [http://kd.acm/ra.cn/admitists/3035]		DIN.	****	参加回回: http://k	d.agastra.cn/artic	m/CA4816034			H
						Att Atta					
		E			A R	E bbo:AcademicArticle					* + 1 X
	182.94				题名	应用期保放與抗术送育木稻書朝然不育系的研究 武小会 ####					
					17.8						109566
					12.10	di					6017
	出生年月	1930					R http://od.age/ra.cn/journals/C30000006/Issues/C20000362				
	12.00	1953年目南农学院农学系毕业,分配在港南省安江农业学校	年四期次学校次学系学校,分配在湖南省安江农业学校任教,1964年开始从事杂立木稻科硕工作				Develop Thermo-sensitive Genic Male Sterile (TGMS) Rice Line by Means of Population Improvement				0017
		。现为期南杂交水稻耕实中心主任,研究员,被转为西南农业 事杂交水稻育种研究,育成我国第一个大器积应用的杂交水和	长期从 。 线指合"	关键词	水稻::温朝核不育::柱头外露車::产量::抗性::品质					6017	
	間介	优2号"、"威伐64"、"威伐49"等,在全国大面积推广,为我国水稻的窗户象出了重大告配,已培养植 5名、傅士1名,发表位文20余篇,王编《杂立水稻留明教程》、《杂立水稻窗种教给学》、《两系			起始百	589					6017
		法杂立木和论文集》等著作。1981年获国家特举业明星,先1 经足输,并要为"杂立木和之父"、派南省"比热科学宠"、"国际	期後,先后在4次国际大说,多次常获国家、邰、睿 第一、"国家培育宗出告献的专家"等。		局页数	-4(xsd:integer)					
	at class de Food gran crops					Output Resistance Roc					-
Agronomy Agronomy MF http://ind.agn/ta.co/database//6030105				_	叙词毗念						(+ + ×
	senetedat.	http://stb.agridata.cn/module_db/readnews_search.asp?rid-			SS11						
	研究方向	水稻麻种	廣神				的网络机多交加器会动物的方法,不仅同口的角度小性软件马外微索,而目而口的角配会力、尽乐、状				
	前221歳4号	410125			這等综合性状。从用985、作單4時、書20日單状1時料據的形法則多文加混合选择的影体中透電出 一个社头外寫率高。配合力、高原和現性關於対例204頁的設置設置的实用最軟結不質系第二、環境头 外露地注7666、此其關204頁749、用度154頁402、明時、776時後63度組織的原系会交招						
	81.40	研究問		76.0							
	第6 至6 工作者包 國際中心之中和時代中心 回顧和中心之中不成者。在第一年前日 前時代之子和朝年年年末回帰用 回顧					新聞合比V2 04的对应组合增产 3 8%~ 5 8% 是日度小 82 1%~ 84 4%。					
						信果员 592					
						作物学提					
小指学種類認識者對生活的ANZ資格素的ANAPO分析 二十一世界的主要的和某人的關鍵的基本目的出版中方的基本有法型的非常的 考试和其它的相對的全身和在物质的指定。這些在認識的其他的非常的 考试和其它的相對的全身和在的影响的生活。這些在認識的主要的 考试和其它的相對的全身和在的影响的生活。這些可能的一個一個一個一個一個一個一個一個一個一個一個一個一個一個一個一個一個一個一個					is 出 和明 of	発展子 期間会交水和研究中心					
	-t	stone) [et : store) [et : store tere)] et : store tere				4 T.B.(184.)	RUSON) AT THE	G/Turble) dT St(II	Troie) (AT TAR(CSV) (HIER	a _)	

Fig. 8 The Domain Knowledge Service Prototype System Driven by Linked Data

5 Conclusions

The results of this study proves that it is one of the best practices to applying the ideas, principles and methodologies of linked data, to describe, organize and merge the huge amount of agricultural information resources in a more fine described, formally structured and semantically linked way. Linked data would play a great role to increase the popularity, visibility, accessibility and value of agricultural big data resources. The knowledge organization systems in SKOS formats would help us to align and match concepts to develop a broad and high level analytical framework for managing, representing and mining big data.

Further research work are needed because we at present just now focus on the variety and value dimensions of big data, we should actually address the volume, velocity issues in practice based on the cloud computing and other efficient big data infrastructure and technologies.

As massive amounts of data are available, linked and identifiable via URIs, big data, linked data and KOS would be an integral part of the future web infrastructure, the web of data, global data space and semantic web is beginning to take shape.

Acknowledgements

The related research work of this paper was support by the National Key Technology R&D Program "Knowledge Services Application and Demonstration Based on STKOS" (2011BAH10B06) during the Twelfth Five-year Plan Period.

References

- Manyika J., Chui M., Brown B., etal. Big data: The next frontier for innovation, competition, and productivity[R/OL].(2011-05-01) [2014-06-08]http://www.mckinsey.com /insights/business_tech nology/big_data_the_next_frontier_for_innovation
- Hitzle P., and Janowicz K. (2013). Linked Data, Big Data, and the 4th Paradigm. Semantic Web, 4(3), 233 -235.

- Heath T. and Bizer C. (2011). Linked Data: Evolving the Web into a Global Data Space (1st edition). Synthesis Lectures on the Semantic Web: Theory and Technology, 1:1, 1-136. Morgan & Claypool.
- Suchanek F., & Weikum G. (2013). Knowledge harvesting in the big-data era. In Proceedings of the 2013 international conference on Management of data (pp. 933-938). ACM.
- Shiri A. (2014). Linked Data Meets Big Data: A Knowledge Organization Systems Perspective. Advances In Classification Research Online, 24(1). doi:10.7152/acro.v24i1.14672.
- Anibaldi S., Jaques Y., Celli F., etal. (2013). Migrating bibliographic datasets to the Semantic Web: The AGRIS case
- Celli F., Jaques Y., Anibaldi S. and J. Keizer. Pushing, Pulling, Harvesting, Linking: Rethinking Bibliographic Workflows for the Semantic Web". EFITA-WCCA-CIGR Conference "Sustainable Agriculture through ICT Innovation", Turin, Italy, 24-27 June 2013.
- Hey A. J., Tansley S., Tolle K. M., et al. The fourth paradigm: data-intensive scientific discovery. Microsoft Research Redmond, WA, 2009.
- Janowicz K. and Hitzler P. (2012). The digital earth as knowledge engine. Semantic Web, 3(3):213–221.
- Bizer C., Boncz P. A., Brodie M. L., etal. (2011) The Meaningful Use of Big Data: Four Perspectives -Four challenges. SIGMOD Record 40(4): 56-60.
- Bizer C., Heath T., and Lee T.B. (2009). Linked Data The Story So Far. International Journal on Semantic Web & Information Systems, 5(3): 1-22.
- Linked Data Connect Distributed Data across the Web [EB/OL]. (2012-06-18).
 [2014-05-28]. http://linkeddata.org/
- 13. Mike. The Rise of the Data Web [EB/OL]. (2012-06-18). [2014-05-28]. http://www.dataspora.com/2009/08/the-rise-of-the-data-web/
- D2R Server-Publishing Relational Databases on the Semantic Web. [EB/OL]. (2010-02-16) [2014-06-15]. http://www4.wiwiss.fu-berlin.de/bizer/d2r-server/
- 15. DCMI Metadata Terms [EB/OL]. (2012-06-14) [2013-02-03]. http://dublincore.org/documents/ 2012/06/14/dcmi-terms/
- DArcus B. and Giasson F. Bibliographic ontology specification [EB/OL]. (2009-11-04)[2014-06-12]. http://purl.org/ontology/bibo/

- Dolan-Gavitt B, Leek T, Zhivich M, etal. Virtuoso: Narrowing the Semantic Gap in Virtual Machine Introspection[C].Security and Privacy (SP), 2011 IEEE Symposium Berkeley CA: IEEE, 2011:297-312
- Isaac A. and Summers E. SKOS simple knowledge organization system primer [EB/OL]. (2008-2-21) [2014-06-04]. http://www.w3.org/TR/skos-primer/
- Sure Y, Bloehdorn S, Haase P, etal. The SWRC ontology Semantic Web for research communities. In Proceedings of the 12th Portuguese Conference on Artificial Intelligence (EPIA 2005). Springer, Covilha, Portugal, December 2005.
- 20. AGROVOC Linked Open Data [EB/OL]. (2013-03-20) [2014-06-09]. http://aims.fao.org/ standards/agrovoc/linked-open-data
- 21. Research Data Alliance [EB/OL]. (2014-06-20) [2014-06-22]. https://rd-alliance.org/