



**HAL**  
open science

# Evaluation of IoB-DTN protocol for mobile IoT Application

Yosra Zguira, Hervé Rivano

► **To cite this version:**

Yosra Zguira, Hervé Rivano. Evaluation of IoB-DTN protocol for mobile IoT Application. [Research Report] RR-9113, INSA Lyon. 2017, pp.1-13. hal-01627670v1

**HAL Id: hal-01627670**

**<https://inria.hal.science/hal-01627670v1>**

Submitted on 2 Nov 2017 (v1), last revised 1 Dec 2017 (v3)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# Evaluation of IoB-DTN protocol for mobile IoT Application

Yosra Zguira, Hervé Rivano

**RESEARCH  
REPORT**

**N° 9113**

October 2017

Project-Team Agora





## Evaluation of IoB-DTN protocol for mobile IoT Application

Yosra Zguira, Hervé Rivano

Project-Team Agora

Research Report n° 9113 — October 2017 — 13 pages

**Abstract:** Communication is essential to the coordination of public transport systems. Nowadays, cities are facing an increasing number of bikes used by citizens therefore the need of monitoring and managing their traffic becomes crucial. Public bike sharing system has been introduced as an urban transportation system that can collect data from mobile devices. In this context, we introduce "IoB-DTN", a protocol based on the Delay/Disruption Tolerant Network (DTN) paradigm adapted for an IoT-like applications running on bike sharing system based sensor network. This document presents the simulation results obtained by evaluating the Binary Spray and Wait inspired variant of IoB-DTN with four buffer management policies and by comparing three variants of IoB-DTN by varying the number of packet copies sprayed in the network.

**Key-words:** Delay Tolerant Network, Internet of Things, Public bike sharing system

**RESEARCH CENTRE  
GRENOBLE – RHÔNE-ALPES**

Inovallée  
655 avenue de l'Europe Montbonnot  
38334 Saint Ismier Cedex

## Evaluation du protocole IoB-DTN pour l'application IoT mobile

**Résumé :** La communication est essentielle à la coordination des systèmes de transport public. De nos jours, les villes font face à un nombre élevé de vélos utilisés par les citoyens, d'où la nécessité de surveiller et de gérer leur trafic. Le système de partage de vélo public a été introduit en tant que un système de transport urbain capable de collecter des données à partir des appareils mobiles. Dans ce contexte, nous introduisons « IoB-DTN » un protocole basé sur le paradigme DTN (Delay / Disruption Tolerant Network), adapté aux applications de type IoT et fonctionnant sur un réseau de capteurs basé sur un système de partage de vélos. Ce document présente les résultats de simulation obtenus en évaluant la variante Binary Spray and Wait inspirée de IoB-DTN avec quatre politiques de gestion de tampons et en comparant trois variantes de IoB-DTN en faisant varier le nombre de copies de paquets diffusés dans le réseau.

**Mots-clés :** Réseaux tolérants aux délais, Internet des objets, Système de partage de vélo public

## 1 Introduction

The United Nations Population Division shows that from 1950 to 2050, the part of world's population living in urban areas will grow from 30% to 66% [1]. This generates multiple undesirable effects such as air pollution, dirty streets, noise, dangers to our health, a lot of traffic jamming and crowded neighborhoods. Therefore, there is a need to a mechanism to monitor the air pollution, highlighting the environment and transportation issues. In our work, we are interested to the last problem. One of the major solutions of urban transportation issues is public transportation system. They have been designed to connect smart devices to the Internet and they have been used to collect data from mobile devices. Public bike sharing systems have been introduced as part of the public transportation system and could be used as a mobile sensor network. In the present document, we give a description of IoB-DTN protocol applied to a mobile network IoT (Internet of Things) devices running a data collection application and a performance evaluation of the protocol on real networks and in particular on connected bicycles.

## 2 Simulated scenario

In our work, we are interested to the use of IoT on connected bikes. We propose a simplified mechanism enabling bicycles to collect and send data to different sinks. Each bike embeds a sensor and a 802.11p communication device. Bicycles generate data every second, store it in their buffers and then transfer it to its neighbors depending on the duty cycle used. They exchange data until they reach a sink. Each neighbor is in communication range with a base station, it forwards all data stored in its buffer. In the next section, we details more the description of the protocol.

## 3 IoB-DTN: Internet Of Bikes-DTN protocol

The IoB-DTN proposed protocol is inspired by DTN flooding protocols [9]. Flooding strategies are based on the principal of replicating messages to enough nodes so that destination nodes must receive it. These protocols can not be applicable for the context of IoT because of their need for high memory storage and energy consumption. In this context, we introduce "IoB-DTN" protocol inspired, more precisely, by Binary Spray and Wait protocol [10] which can be applied to a mobile network IoT devices for data collection application.

The number of packet copies ( $N^0$ ) sprayed in the network is an interesting technique to control the level of flooding. For our study, we evaluate three variants of IoB-DTN:

$N^0 = 2$ : Two-Hop Relay protocol [8]

$N^0 = 8$ : Binary Spray and Wait protocol [11]

$N^0 = \infty$ : Epidemic Routing protocol [12]

The buffer management policies is an important parameter of IoB-DTN which leads to find a slot in the buffer node when generating or receiving a packet. When the buffer is not full, it gives the next free slot else it decides which packet will be rejected and which should be kept.

We propose four buffer management policies:

1. **KONP: Keep Oldest No Priority:** The packet generated or received is discarded if the buffer is full.
2. **NP: No Priority:** The new packet is replaced by the oldest one which has a high probability to be sent to neighbors and reached a sink.

3. **GPP: Generated Packet Priority:** If the new packet is generated, it replaces the oldest received packet. If it is a received packet, it is discarded. If the full buffer contains only generated packets, the oldest one is then rejected.
4. **LC: Lesser Copy:** The new packet replaces the packet having the smallest number of copies.

As indicated in the previous section, each bicycle generates periodically a packet and stores  $N^0$  copies in its buffer. When the duty cycle is over and the base station is in the communication range of a bike, this latter sends all data stored to the sink. If not, the bicycle verifies if it has at least two copies of each packet, then it transfers one copy and keeps the other one. If it has one copy of the packet, it keeps it until it reaches the destination.

When receiving a packet, the bike determines its position number in the neighbors list sent with the corresponding packet and calculates the number of copies that it should take as shown by this equation:

$$N' \leftarrow \frac{N}{2^{pos+1}}$$

The variable "*pos*" indicates the position of the bicycle in the neighbors list, "*N*" corresponds to the initial number of copies and "*N'*" is the new number of copies calculated. If the buffer management policy provides a slot in the buffer and the receiver bike has at least one copy, it stores the packet with the corresponding number of copies and sends an ACK to the transmitter. If not, the packet is rejected.

At the reception of an ACK, the bike verifies the sender node. If it is a base station, it deletes the packet. If it is another bicycle, it updates the number of copies of the packet.

## 4 Simulation dataset

In our work, we analyze the IoB-DTN proposed protocol in the city of Lyon. It is situated in east-central France, in the Auvergne-Rhône-Alpes region. Lyon is one of the first cities in the world that tested the self-service bicycles called Vélo'v [2]. It provides more than 4000 bikes and they are available 24/7. Each citizen takes his bike as close to his starting point and returns it as close to his point of arrival. Figure 1 depicts one of the bicycle station in the city center.



Figure 1: Vélo'v station

The Vélo'v stations data are described in the platform "Data Grand Lyon" [3]. It is characterized by reference information (name, address, number of nodes, etc.) and real-time information indicating the availability of bicycles or places. These data are integrated with the map of Lyon from OpenStreetMap [4]. Our results was simulated in the central area of the city as indicated in Figure 2.




Figure 2: City area of Lyon

These data are imported to SUMO which is an open source road traffic simulation package [7]. The urban mobility simulator allows to import and generate road networks, bike routes and obstacles.

The Veins module framework [5] connects SUMO to the discrete event simulator OMNeT++ [6] via a TCP socket. The vehicular network simulation includes a real model of 802.11p and radio propagation.

Table 1 summarizes the simulation configuration used for our scenario. We simulate four cases as shown in Table 2 by varying the buffer size and the duty cycle.

Number of bike stations	49
Number of bikes	47
Travel time	Min = 550s / Max = 1418s
Packet generation time	Every second
Communication model	802.11p

Table 1: Simulation parameters



	Buffer size	Duty cycle
Case 1	250	50
Case 2	250	150
Case 3	500	50
Case 4	500	150

Table 2: simulated cases

## 5 Simulation results

In this part, we present our simulation results. We compare the performances by evaluating two metrics: the loss rate and the delivery delay which is the time between the generation of a packet by a node and its reception by a base station.

### 5.1 First scenario

We compare the performances of the IoB-DTN protocol by fixing the number of copies to 8.

From Figure 3 we notice that GPP and LC behave better than NP and KONP policies by evaluating the loss rate in all cases. When the duty cycle is lower, GPP has better performances since it prioritizes the generated packets and therefore the redundancy provides robustness. LC has almost same performances than GPP policy since it rejects packets having the smallest number of copies and a high probability to be arrived to a base station. NP outperforms slightly KONP. It provides bad performances comparing to GPP and LC since it discards the oldest of generated and received packets. KONP is the worst, more precisely when the buffer is small. In this case, the buffer is saturated by the first generated packets quickly and then all others are discarded.

Figure 4 presents the delivery delay of received packets. NP offers the best performances since it drops both the oldest of generated and received packets. GPP and LC behave in the same way and have almost similar performances than NP. KONP gives a bad transmission delay since it forwards only the oldest packets.




Figure 3: Loss rate




Figure 4: Delivery delay

By evaluating the both metrics, we can classify two categories of policies: KONP and NP; GPP and LC. From the first one, KONP has bad performances on the loss rate and the delivery delay. GPP provides softly best performances than LC.

In our second scenario, we evaluate three variants of IoB-DTN by varying the number of copies sprayed in the network and comparing the two buffer management policies NP and GPP.

## 5.2 Second scenario

As previously mentioned, in this section, we evaluate three cases by varying the number of copies.

From Figures 5 and 6, Epidemic Routing protocol has better performances on loss rate for GPP and NP policies since it diffuses many copies in the network. GPP outperforms NP in all cases thanks to its priority to generated packets. Binary Spray and Wait has almost similar results as Epidemic Routing protocol while Two Hop relay is the worst. This phenomenon is due to the bad choice of the neighbor node chosen as relay or to the need of more than two hops to transmit the redundant packet.




Figure 5: Loss rate for GPP by varying the number of copies




Figure 6: Loss rate for NP by varying the number of copies

We observe from Figures 7 and 8 that the three variants of IoB-DTN have similar delivery delay. More precisely, Two Hop Relay is the better and Epidemic Routing is the bad. Binary Spray and Wait and Epidemic Routing disseminate a large number of copies in the network therefore they send old packets which degrades the delivery delay.




Figure 7: Delivery delay for GPP by varying the number of copies




Figure 8: Delivery delay for NP by varying the number of copies

## 6 Conclusion

In this report, we have presented IoB-DTN protocol inspired by Binary Spray and Wait applied to an IoT-like applications running on bicycle sharing system based sensor network. Our simulation results shows that by giving priority to self generated packets as buffer management and by limiting the number of copies sprayed in the network gives the best performances on loss rate and delivery delay.

## References

- [1] United Nations, World Urbanization Prospects: The 2014 Revision, <https://esa.un.org/unpd/wup>.
- [2] <https://velov.grandlyon.com/>.
- [3] <https://data.grandlyon.com/>.
- [4] <https://www.openstreetmap.org>.
- [5] <http://veins.car2x.org/>.
- [6] <https://omnetpp.org/>.
- [7] Michael Behrisch, Laura Bieker, Jakob Erdmann, and Daniel Krajzewicz. Sumo–simulation of urban mobility: an overview. In *Proceedings of SIMUL 2011, The Third International Conference on Advances in System Simulation*. ThinkMind, 2011.
- [8] Ahmad Al Hanbali, Philippe Nain, and Eitan Altman. Performance of ad hoc networks with two-hop relay routing and limited packet lifetime. In *Proceedings of the 1st international conference on Performance evaluation methodologies and tools*, page 49. ACM, 2006.
- [9] Evan PC Jones and Paul AS Ward. Routing strategies for delay-tolerant networks. *Submitted to ACM Computer Communication Review (CCR)*, 2006.
- [10] P Maitreyi and M Sreenivas Rao. Design of binary spray and wait protocol for intermittently connected mobile networks. In *Computing and Communication Workshop and Conference (CCWC), 2017 IEEE 7th Annual*, pages 1–3. IEEE, 2017.
- [11] Thrasyvoulos Spyropoulos, Konstantinos Psounis, and Cauligi S Raghavendra. Spray and wait: an efficient routing scheme for intermittently connected mobile networks. In *Proceedings of the 2005 ACM SIGCOMM workshop on Delay-tolerant networking*, pages 252–259. ACM, 2005.
- [12] Amin Vahdat, David Becker, et al. Epidemic routing for partially connected ad hoc networks. 2000.





**RESEARCH CENTRE  
GRENOBLE – RHÔNE-ALPES**

Inovallée  
655 avenue de l'Europe Montbonnot  
38334 Saint Ismier Cedex

Publisher  
Inria  
Domaine de Voluceau - Rocquencourt  
BP 105 - 78153 Le Chesnay Cedex  
[inria.fr](http://inria.fr)

ISSN 0249-6399