Statistical analysis of retinal responses.

Bruno Cessac

Biovision Team, INRIA Sophia Antipolis, France.

07-12-2017

Bruno Cessac Statistical analysis of retinal responses.

< ∃⇒

Introduction

The Biovision team



イロン 不同と 不同と 不同と

The Biovision team

Biovision team Main goals

Propose models of the visual system, normal and impaired
Develop simulation tools for the early visual system + motion
Help improving rehabilitation strategies (models, algorithms, software)
Design vision-aid systems to help patients in daily living activities

- 17

The visual system



・ロト ・回ト ・ヨト ・ヨト

æ

The visual system



イロン イヨン イヨン イヨン

The visual system



Bruno Cessac

Statistical analysis of retinal responses.

The visual system



Bruno Cessac

Statistical analysis of retinal responses.

æ

Multi Electrodes Array



Figure: Multi-Electrodes Array.

<ロ> (四) (四) (三) (三)





◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで



◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで



<ロ> (四) (四) (三) (三)



Each GCell sends a specific information to the brain.

(ロ) (部) (E) (E)



Each GCell sends a specific information to the brain. These cells are correlated via stimulus and network interactions.

(ロ) (部) (E) (E)

・ロット (四) (日) (日)

• Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"

・日・ ・ ヨ・ ・ ヨ・

- Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"
- **Experimental challenge:** Elaborate better and better techniques to record neuronal activity

・ 同 ト ・ ヨ ト ・ ヨ ト

- Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"
- **Experimental challenge:** Elaborate better and better techniques to record neuronal activity
- Mathematical challenge: Improve existing mathematical tools / Elaborate new ones

・ 同 ト ・ ヨ ト ・ ヨ ト

- Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"
- **Experimental challenge:** Elaborate better and better techniques to record neuronal activity
- Mathematical challenge: Improve existing mathematical tools / Elaborate new ones
- Technological challenge: New techniques in
 - Improving vision for visually impaired people (retinal prostheses, tools for reading, ...)
 - Computer vision
 -

・ロン ・回と ・ヨン ・ヨン

- Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"
- **Experimental challenge:** Elaborate better and better techniques to record neuronal activity
- Mathematical challenge: Improve existing mathematical tools / Elaborate new ones
- Technological challenge: New techniques in
 - Improving vision for visually impaired people (retinal prostheses, tools for reading, ...)
 - Computer vision
 -

・ロン ・回と ・ヨン ・ヨン

A challenge: "Reading" "the" neural "code"

• Mathematical challenge: Improve existing mathematical tools / Elaborate new ones

▲□→ ▲ □→ ▲ □→

Mathematical setting

< □ > < □ > < □ > < □ > < Ξ > < Ξ > = Ξ

Dentity and Section 2.1 (1997) S

< □ > < @ > < 注 > < 注 > ... 注

Descriptional
 Security and
 Security and

This spike train has been generated by an hidden dynamics / stochastic process.

What can we infer about this process from the spike train's analysis ?

(ロ) (部) (E) (E)

Desires and the second second

What do we learn about:

- the stimulus;
- the underlying network;
- the response of that network to a stimulus.

(ロ) (部) (E) (E)



Figure: Spike state.

Spike state

$$\omega_k(n) \in \{0,1\}$$

・ロト ・御ト ・ヨト ・ヨト



Figure: Spike pattern.

$$\omega_k(n) \in \{0,1\}$$

Spike pattern

$$\omega(n) = (\omega_k(n))_{k=1}^N$$

◆□>
◆□>



Figure: Spike pattern.

Spike state

$$\omega_k(n) \in \{0,1\}$$

Spike pattern

$$\omega(n) = (\omega_k(n))_{k=1}^N$$

$$\left(\begin{array}{c}
1\\
0\\
1\\
1
\end{array}\right)$$

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 - わへで



Figure: Spike block.

Spike state

$$\omega_k(n) \in \set{0,1}$$

Spike pattern

$$\omega(n) = (\omega_k(n))_{k=1}^N$$

Spike block
$$\omega_m^n = \{ \, \omega(m) \, \omega(m+1) \dots \omega(n) \, \}$$

< □ > < □ > < □ > < □ > < □ > < □ > = □



Figure: Spike block.

Spike state

$$\omega_k(n) \in \{0,1\}$$

Spike pattern

$$\omega(n) = (\omega_k(n))_{k=1}^N$$

Spike block

$$\omega_m^n = \{ \omega(m) \, \omega(m+1) \dots \omega(n) \} \\ \begin{pmatrix} 1 & 1 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 1 & 1 \end{pmatrix}$$

◆□>
◆□>



Figure: Raster plot/Spike train.

Spike state

$$\omega_k(n) \in \set{0,1}$$

Spike pattern

$$\omega(n) = (\omega_k(n))_{k=1}^N$$

Spike block $\omega_m^n = \{ \omega(m) \, \omega(m+1) \dots \omega(n) \}$

Raster plot

$$\boldsymbol{\omega} \stackrel{\mathrm{def}}{=} \boldsymbol{\omega}_{\mathbf{0}}^{T}$$

Handling temporality and memory

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Estimate:

$$P_n\left[\omega(n) \mid \omega_{n-D}^{n-1}\right]$$

where D can be

- Finite and constant (Markov chain).
- Finite and variable (Variable length Markov chain).
- Infinite (Chain with complete connection).

Simplest decoding paradigm: Neurons are independents

Each Gcell convey a local information independently from the other Gcells.

$$P_n[\omega_1(n),\omega_2(n)] = P_n[\omega_1(n)]P_n[\omega_2(n)]$$

◆□▶ ◆□▶ ◆三▶ ◆三▶ ○○ のへで

Simplest decoding paradigm: Neurons are independents

Each Gcell convey a local information independently from the other Gcells.

$$P_n[\omega_1(n),\omega_2(n)] = P_n[\omega_1(n)]P_n[\omega_2(n)]$$

If in addition we assume no dependence in the history, the model can be fit by a Bernoulli model with (time dependent) rates.

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで
Simplest decoding paradigm: Neurons are independents

Each Gcell convey a local information independently from the other Gcells.

$$P_n[\omega_1(n),\omega_2(n)] = P_n[\omega_1(n)]P_n[\omega_2(n)]$$

If in addition we assume no dependence in the history, the model can be fit by a Bernoulli model with (time dependent) rates.

Easy "decoder". A bit too naive though. What do we miss ?

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Neurons like to be connected







2 Long memory tail (conductance, plasticity, adaptation).

Ollective dynamics







A ■

Considering the effects of space-time interactions in spikes statistics

A Pandora box !



Generalization: the Generalized-Linear Model (GLM)

Paradigms of rates and receptive fields.



Figure: Generalized Linear Models.

Neurons are conditionally independent upon the past.

200

Seeking a Boltzmann-Gibbs distribution describing the statistics of spikes in a large assembly of interacting neurons.

Seeking a Boltzmann-Gibbs distribution describing the statistics of spikes in a large assembly of interacting neurons.

Equilibrium distribution.

$$P[S] = \frac{1}{Z} e^{-\beta H\{S\}}; \quad H\{S\} = \sum_{\alpha} \lambda_{\alpha} X_{\alpha} \{S\}$$

 $\lambda_{\alpha}X_{\alpha} \sim \textit{Energy}; \quad E, P \times V, \mu \times N, h \times M, \dots$

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Seeking a Boltzmann-Gibbs distribution describing the statistics of spikes in a large assembly of interacting neurons.

Equilibrium distribution.

$$P[S] = \frac{1}{Z}e^{-\beta H\{S\}}; \quad H\{S\} = \sum_{\alpha} \lambda_{\alpha} X_{\alpha}\{S\}$$

 $\lambda_{\alpha} X_{\alpha} \sim \textit{Energy}; \quad E, P imes V, \mu imes N, h imes M, \dots$

One can compute the average of X_{α} and relates it to thermodynamics relations.

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Seeking a Boltzmann-Gibbs distribution describing the statistics of spikes in a large assembly of interacting neurons.

Equilibrium distribution.

$$P[S] = \frac{1}{Z}e^{-\beta H\{S\}}; \quad H\{S\} = \sum_{\alpha} \lambda_{\alpha} X_{\alpha}\{S\}$$

 $\lambda_{\alpha} X_{\alpha} \sim \textit{Energy}; \quad E, P \times V, \mu \times N, h \times M, \dots$

One can compute the average of X_{α} and relates it to thermodynamics relations.

Inferring the behaviour of a tremendous number of microscopic variables ($\mathcal{N} = 6.022 \times 10^{23}$) with a macroscopic variables (PV = nRT).

◆□▶ ◆□▶ ◆目▶ ◆目▶ 目 のへで

Seeking a Boltzmann-Gibbs distribution describing the statitics of spikes in a large assembly of interacting neurons.

Non equilibrium.

- Gradients of λ_{α} induce fluxes of X_{α} (gradient of temperature involves heat flux).
- Onsager relations.
- Linear response.

Can be deduced (under strong assumptions) from equilibrium dynamics.

(日) (四) (王) (王) (王)

Seeking a Boltzmann-Gibbs distribution describing the statitics of spikes in a large assembly of interacting neurons.

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

- How ?
- Is it reasonable ?
- What do we learn ?

Seeking a Boltzmann-Gibbs distribution describing the statitics of spikes in a large assembly of interacting neurons.

Preamble: Physics is guided by principles. We ignore if similar principle exist for neuronal systems.

• Assume data is **stationary**.



- Assume data is **stationary**.
- Choose a set of characteristic spike events e.g. "neuron i_1 is firing at time t_1, \ldots neuron i_k is firing at time t_k "

 $m_l(\omega) = \omega_{i_1}(t_1) \dots \omega_{i_k}(t_k)$ ("spikes interaction").

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

- Assume data is **stationary**.
- Choose a set of characteristic spike events e.g. "neuron i_1 is firing at time t_1, \ldots neuron i_k is firing at time t_k "

$$m_l(\omega) = \omega_{i_1}(t_1) \dots \omega_{i_k}(t_k)$$
 ("spikes interaction").

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

• Compute π_l : empirical probability of spike event *l*.

- Assume data is **stationary**.
- Choose a set of characteristic spike events e.g. "neuron i₁ is firing at time t₁, ... neuron i_k is firing at time t_k"

$$m_l(\omega) = \omega_{i_1}(t_1) \dots \omega_{i_k}(t_k)$$
 ("spikes interaction").

- Compute π_l : empirical probability of spike event *l*.
- Find a probability distribution μ which reproduces the empirical averages:

 $\mu [Spike event I] = \pi_I \quad (C)$

without any further assumption. Maximize the entropy under constraints C.

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

- Assume data is **stationary**.
- Choose a set of characteristic spike events e.g. "neuron i₁ is firing at time t₁, ... neuron i_k is firing at time t_k"

$$m_l(\omega) = \omega_{i_1}(t_1) \dots \omega_{i_k}(t_k)$$
 ("spikes interaction").

- Compute π_l : empirical probability of spike event *l*.
- Find a probability distribution μ which reproduces the empirical averages:

 μ [Spike event I] = π_I (C)

without any further assumption. Maximize the entropy under constraints C.

Gibbs distribution.

Gibbs "potential":

$$H(\omega_0^D) = \sum_{l=0}^L h_l m_l(\omega_0^D) > -\infty$$

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

Gibbs "potential":

$$H(\omega_0^D) = \sum_{l=0}^L h_l m_l(\omega_0^D) > -\infty$$

Blocks transition: Consider two spike blocks $\varpi I, \varpi I'$ of range $D \ge 1$. The transition $\varpi I \to \varpi I'$ is *legal* if $\varpi I, \varpi I'$ have a common block ω_1^{D-1} .

Legal
$$\varpi I = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}; \ \varpi I' = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 1 & 0 \end{bmatrix}$$

Forbidden $\varpi I = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}; \ \varpi I' = \begin{bmatrix} 0 & 1 & 1 \\ 0 & 1 & 0 \end{bmatrix}$

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Gibbs "potential":

$$H(\omega_0^D) = \sum_{l=0}^L h_l m_l(\omega_0^D) > -\infty$$

Blocks transition: Consider two spike blocks $\varpi I, \varpi I'$ of range $D \ge 1$. The transition $\varpi I \to \varpi I'$ is *legal* if $\varpi I, \varpi I'$ have a common block ω_1^{D-1} .

Legal
$$\varpi I = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}; \ \varpi I' = \begin{bmatrix} 0 & 1 & 1 \\ 1 & 1 & 0 \end{bmatrix}$$

Forbidden $\varpi I = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 1 & 1 \end{bmatrix}; \ \varpi I' = \begin{bmatrix} 0 & 1 & 1 \\ 0 & 1 & 0 \end{bmatrix}$

Any block ω_0^D of range R = D + 1 can be viewed as a legal transition from the block $\varpi I = \omega_0^{D-1}$ to the block $\varpi I' = \omega_1^D$. We write $\omega_0^D \sim \varpi I \varpi I'$

Gibbs "potential":

$$H(\omega_0^D) = \sum_{l=0}^L h_l m_l(\omega_0^D) > -\infty$$

Transfer matrix

$$\mathcal{L}_{arpi l,arpi l'} = \left\{ egin{array}{cc} e^{\mathcal{H}(\omega_0^D)} & ext{if } \omega_0^D \sim arpi l arpi l' \ 0, & ext{otherwise.} \end{array}
ight.$$

From the Perron-Frobenius theorem, \mathcal{L} has a unique real positive eigenvalue *s*, strictly larger in modulus than the other eigenvalues, and with positive right, *R*, and left, *L*, eigenvectors: $\mathcal{L}R = sR$, $\mathcal{L}\mathcal{L} = sL$.

(a) The potential:

$$\phi(\omega_0^D) = \mathcal{H}(\omega_0^D) - \log R\left(\omega_0^{D-1}\right) + \log R\left(\omega_1^D\right) - \log s \quad (1)$$

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

defines an homogeneous Markov chain, $P\left[\omega(D) \mid \omega_0^{D-1}\right] = e^{\phi(\omega_0^D)}$.

(a) The potential:

$$\phi(\omega_0^D) = \mathcal{H}(\omega_0^D) - \log R\left(\omega_0^{D-1}\right) + \log R\left(\omega_1^D\right) - \log s \quad (1)$$

defines an homogeneous Markov chain, $P\left[\omega(D) \mid \omega_0^{D-1}\right] = e^{\phi(\omega_0^D)}$. (b) The unique invariant probability of this Markov chain is:

$$\mu(\omega_0^{D-1}) = R\left(\omega_0^{D-1}\right) L\left(\omega_0^{D-1}\right).$$
(2)

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

(a) The potential:

$$\phi(\omega_0^D) = \mathcal{H}(\omega_0^D) - \log R\left(\omega_0^{D-1}\right) + \log R\left(\omega_1^D\right) - \log s \quad (1)$$

defines an homogeneous Markov chain, $P\left[\omega(D) \mid \omega_0^{D-1}\right] = e^{\phi(\omega_0^D)}$. (b) The unique invariant probability of this Markov chain is:

$$\mu(\omega_0^{D-1}) = R\left(\omega_0^{D-1}\right) L\left(\omega_0^{D-1}\right).$$
(2)

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

(c)

$$\mu\left[\omega_{0}^{n}\right] = \frac{e^{\sum_{k=0}^{n-D} \mathcal{H}\left(\omega_{k}^{k+D}\right)}}{s^{n-D+1}} R\left(\omega_{n-D+1}^{n}\right) L\left(\omega_{0}^{D-1}\right).$$
(3)

(a) The potential:

$$\phi(\omega_0^D) = \mathcal{H}(\omega_0^D) - \log R\left(\omega_0^{D-1}\right) + \log R\left(\omega_1^D\right) - \log s \quad (1)$$

defines an homogeneous Markov chain, $P\left[\omega(D) \mid \omega_0^{D-1}\right] = e^{\phi(\omega_0^D)}$. (b) The unique invariant probability of this Markov chain is:

$$\mu(\omega_0^{D-1}) = R\left(\omega_0^{D-1}\right) L\left(\omega_0^{D-1}\right).$$
(2)

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

(c)

$$\mu\left[\omega_{0}^{n}\right] = \frac{e^{\sum_{k=0}^{n-D} \mathcal{H}\left(\omega_{k}^{k+D}\right)}}{s^{n-D+1}} R\left(\omega_{n-D+1}^{n}\right) L\left(\omega_{0}^{D-1}\right).$$
(3)

(d) $\mathcal{P}[\mathcal{H}] = \log s$ ("free energy" or "topological pressure") and μ obey:

$$\mathcal{P}[\mathcal{H}] = \sup_{\nu \in \mathcal{M}} \left(\mathcal{S}[\nu] + \nu[\mathcal{H}] \right) = \mathcal{S}[\mu] + \mu[\mathcal{H}]$$

(a) The potential:

$$\phi(\omega_0^D) = \mathcal{H}(\omega_0^D) - \log R\left(\omega_0^{D-1}\right) + \log R\left(\omega_1^D\right) - \log s \quad (1)$$

defines an homogeneous Markov chain, $P\left[\omega(D) \mid \omega_0^{D-1}\right] = e^{\phi(\omega_0^D)}$. (b) The unique invariant probability of this Markov chain is:

$$\mu(\omega_0^{D-1}) = R\left(\omega_0^{D-1}\right) L\left(\omega_0^{D-1}\right).$$
(2)

(c)

$$\mu\left[\omega_{0}^{n}\right] = \frac{e^{\sum_{k=0}^{n-D} \mathcal{H}\left(\omega_{k}^{k+D}\right)}}{s^{n-D+1}} R\left(\omega_{n-D+1}^{n}\right) L\left(\omega_{0}^{D-1}\right).$$
(3)

(d) $\mathcal{P}[\mathcal{H}] = \log s$ ("free energy" or "topological pressure") and μ obey:

$$\mathcal{P}[\mathcal{H}] = \sup_{\nu \in \mathcal{M}} \left(\mathcal{S}[\nu] + \nu[\mathcal{H}] \right) = \mathcal{S}[\mu] + \mu[\mathcal{H}]$$

(e) $\exists A, B > 0$ such that, for any block ω_0^n :

$$A \leq \frac{\mu \left[\omega_{0}^{n}\right]}{e^{-(n-D+1)\mathcal{P}(\mathcal{H})}e^{-\sum_{k=0}^{n-D}\mathcal{H}\left(\omega_{k}^{k+D}\right)}} \leq B. \tag{4}$$

Can we hear the shape of a Maximum Entropy potential ?

Rodrigo Cofré Cofré,, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking

neural-network models", Phys. Rev. E 89, 052117 (2014).

$\mathcal{H}(\omega_0^D)$ $\log P\left[\omega(D) \mid \omega_0^{D-1}\right]$

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Can we hear the shape of a Maximum Entropy potential ?



▲ロト ▲圖ト ▲画ト ▲画ト 三回 めんゆ

Two distinct potentials $\mathcal{H}^{(1)}, \mathcal{H}^{(2)}$ of range R = D + 1 correspond to the same Gibbs distribution (are "equivalent"), if and only if there exists a range D function f such that (Chazottes-Keller (2009)):

$$\mathcal{H}^{(2)}\left(\omega_{0}^{D}\right) = \mathcal{H}^{(1)}\left(\omega_{0}^{D}\right) - f\left(\omega_{0}^{D-1}\right) + f\left(\omega_{1}^{D}\right) + \Delta, \quad (5)$$

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

where $\Delta = \mathcal{P}(\mathcal{H}^{(2)}) - \mathcal{P}(\mathcal{H}^{(1)})$.

Summing over periodic orbits we get rid of the function f

$$\sum_{n=1}^{R} \phi(\omega \sigma^{n} l_{1}) = \sum_{n=1}^{R} \mathcal{H}^{*}(\omega \sigma^{n} l_{1}) - R\mathcal{P}(\mathcal{H}^{*}),$$
(6)

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

We eliminate equivalent constraints.

Can we hear the shape of a Maximum Entropy potential ?

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).





<ロト <四ト <注入 <注下 <注下 <

Conclusion

Given a set of transition probabilities $P\left[\left.\omega(D) \mid \omega_0^{D-1}\right.\right] > 0$ there is a unique, up to a constant, MaxEnt potential, written as a linear combination of constraints (average of spike events) with a minimal number of terms. This potential can be explicitly (and algorithmically) computed.

< □ > < @ > < 注 > < 注 > ... 注

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).

• A GLM like model has typically $O(N^2)$ parameters where N is the number of neurons.

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).

• A GLM like model has typically $O(N^2)$ parameters where N is the number of neurons.

• The equivalent MaxEnt potential has generically $2^{NR} - 2^{N(R-1)}$ parameters, non linear and redundant functions of the GLM parameters.

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).

- A GLM like model has typically $O(N^2)$ parameters where N is the number of neurons.
- The equivalent MaxEnt potential has generically 2^{NR} - 2^{N(R-1)} parameters, non linear and redundant functions of the GLM parameters.

 \Rightarrow

(日) (四) (문) (문) (문)

- Intractable determination of parameters;
- Stimulus dependent parameters;
- Overfitting.

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).

- A GLM like model has typically $O(N^2)$ parameters where N is the number of neurons.
- The equivalent MaxEnt potential has generically $2^{NR} 2^{N(R-1)}$ parameters, non linear and redundant functions of the GLM parameters.

 \Rightarrow

◆□▶ ◆□▶ ◆目▶ ◆目▶ 目 のへで

- Intractable determination of parameters;
- Stimulus dependent parameters;
- Overfitting.

BUT

Rodrigo Cofré Cofré, Bruno Cessac, "Exact computation of the maximum-entropy potential of spiking neural-network models", Phys. Rev. E 89, 052117 (2014).

- A GLM like model has typically $O(N^2)$ parameters where N is the number of neurons.
- The equivalent MaxEnt potential has generically 2^{NR} - 2^{N(R-1)} parameters, non linear and redundant functions of the GLM parameters.

• Intractable determination of parameters;

- Stimulus dependent parameters;
- Overfitting.

BUT Real neural networks are not generic

◆□▶ ◆□▶ ◆目▶ ◆目▶ 目 のへで
MaxEnt approach might be useful if there is some hidden law of nature/ symmetry which cancels most of the terms of its expansion.

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

Dimensionality reduction and information geometry

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

R. Herzog, M.-J. Escobar, A. G. Palacios, B. Cessac, Dimensionality Reduction and Reliable Observations in Maximum Entropy Models on Spiking Networks, submitted

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで



R. Herzog, M.-J. Escobar , A. G. Palacios, B. Cessac, Dimensionality Reduction and Reliable Observations in Maximum Entropy Models on Spiking Networks, submitted



R. Herzog, M.-J. Escobar , A. G. Palacios, B. Cessac, Dimensionality Reduction and Reliable Observations in Maximum Entropy Models on Spiking Networks, submitted



R. Herzog, M.-J. Escobar , A. G. Palacios, B. Cessac, Dimensionality Reduction and Reliable Observations in Maximum Entropy Models on Spiking Networks, submitted

 $\chi_{\parallel'}$



$$\chi \quad \text{Fisher metric}$$

$$\chi_{ll'} = \frac{\partial^2 d_{KL}(\pi, \mu)}{\partial h_l \partial h_{l'}}$$

$$\chi_{ll'} = \frac{\partial^2 \mathcal{P}}{\partial h_l \partial h_{l'}};$$

$$\mathcal{P} = \sup_{\mu \in M_{lnV}} h(\mu) + \mu(\mathcal{H})$$

$$\chi_{ll'} = C_{ll'}(0) + \sum_{n=0}^{+\infty} C_{ll'}(n)$$

$$\delta \mu [m] = \chi \delta h \Rightarrow \delta h = \chi^{-1} \delta \mu [m]$$

・ロト ・四ト ・ヨト ・ヨト æ

Mastromatteo I. On the typical properties of inverse problems in statistical mechanics, PhD Thesis 2013, arXiv

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

preprint arXiv:1311.0190

• Generate a raster of length T with a distribution μ .

Mastromatteo I. On the typical properties of inverse problems in statistical mechanics, PhD Thesis 2013, arXiv preprint arXiv:1311.0190

- Generate a raster of length T with a distribution μ .
- Estimate μ from the raster with a given potential H (a set of coefficients h).

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Mastromatteo I. On the typical properties of inverse problems in statistical mechanics, PhD Thesis 2013, arXiv preprint arXiv:1311.0190

- Generate a raster of length T with a distribution μ .
- Estimate μ from the raster with a given potential H (a set of coefficients h).

• $\mu^{(1)}$, $\mu^{(2)} \epsilon$, δ -indistinguishable if: $-\log \mu^* \left[h^{(1)} \stackrel{\delta}{=} h^{(2)} \right] \le \epsilon$.

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

Mastromatteo I. On the typical properties of inverse problems in statistical mechanics, PhD Thesis 2013, arXiv preprint arXiv:1311.0190

- Generate a raster of length T with a distribution μ .
- Estimate μ from the raster with a given potential H (a set of coefficients h).
- $\mu^{(1)}, \mu^{(2)} \epsilon, \delta$ -indistinguishable if: $-\log \mu^* \left[h^{(1)} \stackrel{\delta}{=} h^{(2)} \right] \leq \epsilon.$
- Set of indistinguishable distributions. Ellipsoid:

$$\mathcal{V} = \frac{1}{\sqrt{\det \chi}} \left[\frac{1}{\Gamma(\frac{L}{2}+1)} \left(\frac{2\pi\kappa}{T} \right)^{\frac{L}{2}} \right]$$

(日) (四) (문) (문) (문)

Mastromatteo I. On the typical properties of inverse problems in statistical mechanics, PhD Thesis 2013, arXiv preprint arXiv:1311.0190

- Generate a raster of length T with a distribution μ .
- Estimate μ from the raster with a given potential H (a set of coefficients h).
- $\mu^{(1)}, \mu^{(2)} \epsilon, \delta$ -indistinguishable if: $-\log \mu^* \left[h^{(1)} \stackrel{\delta}{=} h^{(2)} \right] \leq \epsilon.$
- Set of indistinguishable distributions. Ellipsoid:

$$\mathcal{V} = \frac{1}{\sqrt{\det \chi}} \left[\frac{1}{\Gamma(\frac{L}{2}+1)} \left(\frac{2\pi\kappa}{T} \right)^{\frac{L}{2}} \right]$$

• We define the *k*-volume by:

$$\log \mathcal{V}(k) = \frac{1}{2}S(k) - \log \Gamma(\frac{k}{2} + 1) + \frac{k}{2} \log \left(\frac{2\pi\kappa}{T}\right),$$
$$S(k) = -\sum_{i=1}^{k} \log \lambda_i,$$



◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 の々で

Analysis of retina data



◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Analysis of retina data



◆□ → ◆□ → ◆ = → ◆ = → ○ へ ⊙

How does the Gibbs distribution look like in a neural network model ?

▲□▶ ▲圖▶ ▲目▶ ▲目▶ 目 のへで

R.Cofré,B. Cessac: "Dynamics and spike trains statistics in conductance-based Integrate-and-Fire neural networks with chemical and electric synapses", Chaos, Solitons and Fractals, 2013. (Inspired from Rudolph, Destexhe, 2006).





◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 のへで

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

$$-\sum_{j}g_{kj}(t,\omega)(V_k-E_j)$$



www.shutterstock.com · 154156187

(日) (四) (문) (문) (문)

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

$$-\sum_{j}g_{kj}(t,\omega)(V_k-E_j)$$



<ロ> (四) (四) (四) (日) (日)

æ

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

$$-\sum_{j}g_{kj}(t,\omega)(V_k-E_j)$$



<ロト <四ト <注入 <注下 <注下 <

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

$$-\sum_{j}g_{kj}(t,\omega)(V_k-E_j)$$



<ロト <四ト <注入 <注下 <注下 <

Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$

$$-\sum_{j}g_{kj}(t,\omega)(V_k-E_j)$$

$$-\sum_{j} \bar{g_{kj}} \left(V_k - V_j \right)$$



Sub-threshold dynamics:

$$C_k \frac{dV_k}{dt} = -g_{L,k}(V_k - E_L)$$
$$-\sum_j g_{kj}(t,\omega)(V_k - E_j)$$
$$-\sum_j g_{kj}(V_k - V_j)$$
$$+i_k^{(ext)}(t) + \sigma_B \xi_k(t)$$



<ロト <四ト <注入 <注下 <注下 <

Spike generation process

• In this example, the hidden process is *non Markovian*: it has an *infinite memory*, although it can be well approximated by a Markov process.

Spike generation process

- In this example, the hidden process is *non Markovian*: it has an *infinite memory*, although it can be well approximated by a Markov process.
- Without *gap-junctions* the transition probabilities can be approximated. The form is similar to *GLM* ⇒ conditional independence, interpretation of parameters, sigmoidal transfer function.

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Spike generation process

- In this example, the hidden process is *non Markovian*: it has an *infinite memory*, although it can be well approximated by a Markov process.
- Without *gap-junctions* the transition probabilities can be approximated. The form is similar to *GLM* ⇒ conditional independence, interpretation of parameters, sigmoidal transfer function.
- With gap-junctions the *conditional independence breaks down*. The explicit form of the transition probabilities is unknown.

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Spike generation process

- In this example, the hidden process is *non Markovian*: it has an *infinite memory*, although it can be well approximated by a Markov process.
- Without *gap-junctions* the transition probabilities can be approximated. The form is similar to $GLM \Rightarrow$ conditional independence, interpretation of parameters, sigmoidal transfer function.
- With gap-junctions the *conditional independence breaks down*. The explicit form of the transition probabilities is unknown.
- The statistics of spike is described by a *Gibbs distribution* (even in the non stationary case). In the stationary case, it obeys a Maximum Entropy Principle.



B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

◆□ > ◆□ > ◆臣 > ◆臣 > ○

æ

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow *stationary Gibbs distribution*.

・ロン ・回と ・ヨン・

æ

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow *stationary Gibbs distribution*.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

▲圖▶ ★ 国▶ ★ 国▶

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow *stationary Gibbs distribution*.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

★週 ▶ ★ 注 ▶ ★ 注 ▶

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu [f(t)] = [\kappa_f * S](t)$, (linear response).

(ロ) (同) (E) (E) (E)

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu [f(t)] = [\kappa_f * S](t)$, (linear response).

$$\kappa_{k,f}(t-t_1) = \frac{1}{C_k} \sum_{r=-\infty}^{\lfloor t-t_1 \rfloor} C^{sp} \left[f(t-t_1,.), \frac{\mathcal{H}_k^{(1)}(r,.)}{\sigma_k(r-1,.)} \Gamma_k(0,r-1,.) \right]$$

(ロ) (同) (E) (E) (E)

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu [f(t)] = [\kappa_f * S](t)$, (linear response).

$$\kappa_{k,f}(t-t_1) = \frac{1}{C_k} \sum_{\substack{r = -\infty}}^{\lfloor t-t_1 \rfloor} C^{sp} \left[f(t-t_1,.), \frac{\mathcal{H}_k^{(1)}(r,.)}{\sigma_k(r-1,.)} \Gamma_k(0,r-1,.) \right]$$

 History dependence.
 Image: Constraint of the second seco

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu [f(t)] = [\kappa_f * S](t)$, (linear response).

$$\kappa_{k,f}(t-t_1) = \frac{1}{C_k} \sum_{r=-\infty}^{\lfloor t-t_1 \rfloor} C^{sp} \left[f(t-t_1,.), \frac{\mathcal{H}_k^{(1)}(r,.)}{\sigma_k(r-1,.)} \Gamma_k(0,r-1,.) \right]$$
Response to stimuli

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu [f(t)] = [\kappa_f * S](t)$, (linear response).

$$\kappa_{k,f}(t-t_1) = \frac{1}{C_k} \sum_{r=-\infty}^{\lfloor t-t_1 \rfloor} C^{sp} \left[f(t-t_1,.), \frac{\mathcal{H}_k^{(1)}(r,.)}{\sigma_k(r-1,.)} \Gamma_k(0,r-1,.) \right]$$

History dependence, observable, network dynamics

・ロン ・回 ・ モン・ モン・ モー うへつ

Response to stimuli

B. Cessac, R. Cofré, Linear Response of Gibbs measures from Spiking Neuronal Network Models, submitted

GIF model without stimulus \Rightarrow stationary Gibbs distribution.

time-dependent stimulus $S(t) \Rightarrow$ non stationary Gibbs distribution.

How is the average of an observable $f(\omega, t)$ affected by the stimulus ?

If S is weak enough: $\delta \mu[f(t)] = [\kappa_f * S](t)$, (linear response).

$$\kappa_{k,f}(t-t_1) = \frac{1}{C_k} \sum_{r=-\infty}^{[t-t_1]} C^{sp} \left[f(t-t_1,.), \frac{\mathcal{H}_k^{(1)(r,.)}}{\sigma_k(r-1,.)} \Gamma_k(0,r-1,.) \right],$$

History dependence, (spontaneous) correlation between observable and network and Bruno Classes in Statistical analysis of retinal responses.

Response to stimuli

Range R observable monomial decomposition (Hammersley-Clifford, 71)

$$f(\omega) = \sum_{l} f_{l} m_{l}(\omega)$$

Range R Gibbs potential monomial decomposition

$$\delta\phi(r,\omega)\sim\sum_{l}\delta\phi_{l}(r)m_{l}(\omega_{r-D}^{r}).$$

Linear response

$$\delta^{(1)}\mu[f_{l}(t)] = \sum_{r=n_{0}+1}^{n=[t]} \sum_{l'} f_{l}(t) \,\delta\phi_{l'}(r) \,\mathcal{C}^{(sp)}\left[\bar{m}_{l}(\omega_{n-D}^{n}), \bar{m}_{l'}(\omega_{r-D}^{r})\right].$$



Bruno Cessac Statistical analysis of retinal responses.

イロト イヨト イヨト イヨト



・ロト ・回ト ・ヨト

∃ >



・ロト ・回ト ・ヨト

→

Introduction Mathematical setting Handling temporality and memory Dimensionality reduction and information geometry Ho

Conclusion

Bruno Cessac Statistical analysis of retinal responses.

(ロ) (四) (E) (E) (E)

Introduction Mathematical setting Handling temporality and memory Dimensionality reduction and information geometry Ho

A challenge: "Reading" "the" neural "code"

• Mathematical challenge: Improve existing mathematical tools / Elaborate new ones

▲□→ ▲ □→ ▲ □→

A challenge: "Reading" "the" neural "code"

- Fundamental challenge: Understanding how visual system "encodes" /" decodes" "information"
- **Experimental challenge:** Elaborate better and better techniques to record neuronal activity
- Mathematical challenge: Improve existing mathematical tools / Elaborate new ones
- Technological challenge: New techniques in
 - Improving vision for visually impaired people (retinal prostheses, tools for reading, ...)
 - Computer vision
 -

・ロン ・回と ・ヨン ・ヨン



• Reliable estimations of spike trains statistics (finite samples, induced biases, finding the right model, estimating its parameters ...),

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

- Reliable estimations of spike trains statistics (finite samples, induced biases, finding the right model, estimating its parameters ...),
- Generate proper synthetic data to calibrate/tests methods,

◆□▶ ◆□▶ ◆注▶ ◆注▶ 注 のへで

- Reliable estimations of spike trains statistics (finite samples, induced biases, finding the right model, estimating its parameters ...),
- Generate proper synthetic data to calibrate/tests methods,
- Inferring/guessing/extrapolating hidden relations (laws ?) relating a stimulus to the collective response of neurons.

- Reliable estimations of spike trains statistics (finite samples, induced biases, finding the right model, estimating its parameters ...),
- Generate proper synthetic data to calibrate/tests methods,
- Inferring/guessing/extrapolating hidden relations (laws ?) relating a stimulus to the collective response of neurons.