



**HAL**  
open science

## Evaluating musical score difference: a two-level comparison

Francesco Foscarin, Raphaël Fournier-S'Niehotta, Philippe Rigaux, Florent Jacquemard

► **To cite this version:**

Francesco Foscarin, Raphaël Fournier-S'Niehotta, Philippe Rigaux, Florent Jacquemard. Evaluating musical score difference: a two-level comparison. Digital Music Research Network One-Day Workshop 2018 (DMRN+13), Dec 2018, London, United Kingdom. 2018. hal-01989029

**HAL Id: hal-01989029**

**<https://inria.hal.science/hal-01989029v1>**

Submitted on 8 Mar 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# EVALUATING MUSICAL SCORE DIFFERENCE

## A TWO-LEVEL COMPARISON

Francesco Foscarin<sup>1</sup>, Raphaël Fournier-S'niehotta<sup>1</sup>, Philippe Rigaux<sup>1</sup> and Florent Jacquemard<sup>2</sup>

<sup>1</sup>Vertigo, CNAM Paris, France <sup>2</sup>INRIA Paris, France

**Goal:** Have a *diff* tool for music scores, similar to the Unix *diff* utility

### Why:

- Collaborative score editing
- Music transcription evaluation
- OMR evaluation

### Issues:

- the line structure of a XML file does not reflect the its musical structure → not meaningful to apply a text *diff* to XML scores.
- What exactly we evaluate? Graphical content or musical content?

### Our Approach

**Two comparison** on two different objectives:

1. **Syntactic level:** the graphical content of the score (beamings, tuplets, dots, ties, etc.).
2. **Semantic level:** the musical content of the score (notes duration and pitch).


For both cases the output is:

- a list of the modifications to transform one score into the other,
- a value  $\Delta$ , that evaluate the difference between the two scores.

#### Graphical Content Comparison

- 1 → 2 :  $\Delta_{SYN} = 8$ , small differences in beamings, noteheads, ties and tuplets
- 1 → 3 :  $\Delta_{SYN} = 32$ , all the score is different because of the longer C in the first bar

#### Music Content Comparison




- 1 → 2 :  $\Delta_{SEM} = 0$ , no differences
- 1 → 3 :  $\Delta_{SEM} = 1$ , just one note with longer duration

## 1 Syntactic difference

We model the graphical score with **notation trees** [5]:

- Beaming Tree
- Tuplet Tree



- Find Least Common Substring (LCS) between trees hash for each voice.
- Equivalent to compute an edit distance with only insertion and deletion operations.

## 2 Semantic difference

We model the score content with timelines (similar to MIDI files).

From each timeline we:

1. build a sequence of couples <pitch, duration>.
2. Compute an edit distance with the usual operations (insert, delete and update) [4]

This difference is feature-based:

- pitch only,
- durations only,
- both features.

$$\Delta_{SEM} = \frac{\alpha \cdot \#UPD + \beta \cdot \#INS + \gamma \cdot \#DEL}{\#events}$$

where  $\alpha, \beta, \gamma$  are user-defined cost/weight values.

## Implementation

Partial implementation in the digital music library NEUMA ([neuma.humanum.fr/](http://neuma.humanum.fr/)).

Two REST API:

- Input: 2 midi files
- Input: 2 music-xml or MEI scores

A graphical representation with Verovio web library.

Example of the semantic difference computation and visualization (with Verovio) on two monophonic scores. The edit operations are notated by different figures: square (insert), triangle (update), rhombus (delete).

## REFERENCES

1. Antila, C., & Weaver, G. (2017). A hierarchic diff algorithm for collaborative music document editing. In *Third International Conference on Technologies for Music Notation and Representation (TENOR)*.
2. F. Foscarin, D. Fiala, F. Jacquemard, Ph. Rigaux, and V. Thion. Gioqoso, an on-line quality assessment tool for music notation. In *International Conference on Technologies for Music Notation and Representation (TENOR)*, 2017.
3. Lemstrom, K. (2000). String matching techniques for music retrieval. PhD thesis, University of Helsinki.
4. Foscarin, F., Fournier-S'niehotta, R., Jacquemard, F., & Rigaux, P. (2018). Évaluation de la correction rythmique des partitions numérisées. In *Journées d'Informatique Musicale (JIM)*, 2018.
5. M. Giraud and F. Jacquemard. Weighted Automata Computation of Edit Distances with Consolidations and Fragmentations. Unpublished, <https://hal.inria.fr/hal-01857267>, 2018.
6. M. Bay, A. F. Ehmann, and J. D. Downie. Evaluation of multiple-f0 estimation and tracking systems. In *International Conference on Music Information Retrieval (ISMIR)*, pages 315-320, 2009.
7. A. Cogliati and Z. Duan. A metric for music notation transcription accuracy. *International Conference on Music Information Retrieval (ISMIR)*, pages 407-413, 2017.
8. A. McLeod and M. Steedman. Evaluating automatic polyphonic music transcription. In *International Conference on Music Information Retrieval (ISMIR)*, pages 42-49, 2018.