



**HAL**  
open science

## Approximation spaces of deep neural networks

Rémi Gribonval, Gitta Kutyniok, Morten Nielsen, Felix Voigtlaender

► **To cite this version:**

Rémi Gribonval, Gitta Kutyniok, Morten Nielsen, Felix Voigtlaender. Approximation spaces of deep neural networks. SMAI 2019 - 9ème Biennale des Mathématiques Appliquées et Industrielles, May 2019, Guidel, France. pp.1. hal-02127179

**HAL Id: hal-02127179**

**<https://inria.hal.science/hal-02127179>**

Submitted on 13 May 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Approximation spaces of deep neural networks

**Rémi Gribonval**, Univ Rennes, Inria, CNRS, IRISA

**Gitta Kutyniok**, Institut für Mathematik, TU Berlin

**Morten Nielsen**, Department of Mathematical Sciences, Aalborg University

**Felix Voigtlaender**, Department of Scientific Computing, KU Eichsttt

We study the expressivity of sparsely connected deep networks. Measuring a network's complexity by its number of connections, or its number of neurons, we consider the class of functions which error of best approximation with networks of a given complexity decays at a certain rate. Using classical approximation theory, we show that this class can be endowed with a norm that makes it a nice function space, called approximation space. We establish that the presence of certain skip connections has no impact of the approximation space, and discuss the role of the network's nonlinearity (also known as activation function) on the resulting spaces, as well as the benefits of depth. For the popular ReLU nonlinearity (as well as its powers), we relate the newly identified spaces to classical Besov spaces, which have a long history associated to sparse wavelet decompositions. The established embeddings highlight that some functions of very low Besov smoothness can nevertheless be well approximated by neural networks, if these networks are sufficiently deep.

**Rémi Gribonval**, PANAMA Research Group, Univ Rennes, Inria, CNRS, IRISA, Campus de Beaulieu, 35042 Rennes cedex, France

`remi.gribonval@inria.fr`

**Gitta Kutyniok**, Institut für Mathematik, Technische Universität Berlin, Strasse des 17. Juni 136, 10623 Berlin  
`kutyniok@math.tu-berlin.de`

**Morten Nielsen**, Department of Mathematical Sciences, Aalborg University, Skjernvej 4A, DK - 9220 Aalborg  
`mnielsen@math.aau.dk`

**Felix Voigtlaender**, Department of Scientific Computing, KU Eichsttt-Ingolstadt, Ostenstrasse 26, Kollegiengebäude I Bau B, 85072 Eichsttt, Germany

`felix@voigtlaender.xyz`