

# **Asymptotically constant-free, p-robust and guaranteed a posteriori error estimates for the Helmholtz equation**

Théophile Chaumont-Frelet, Alexandre Ern, Martin Vohralík

## **To cite this version:**

Théophile Chaumont-Frelet, Alexandre Ern, Martin Vohralík. Asymptotically constant-free, p-robust and guaranteed a posteriori error estimates for the Helmholtz equation. EnuMath 2019 - European Numerical Mathematics and Advanced Applications Conference, Sep 2019, Egmond aan Zee, Netherlands. hal- $02321140$ 

## **HAL Id: hal-02321140 <https://inria.hal.science/hal-02321140>**

Submitted on 21 Oct 2019

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Asymptotically constant-free, p-robust and guaranteed a posteriori error estimates for the Helmholtz equation

T. Chaumont-Frelet (Inria project-team Nachos, CNRS, UCA LJAD) A. Ern (CERMICS, Inria project-team Serena) M. Vohralík (Inria project-team Serena, CERMICS)

Numerical methods for wave propagation with applications in electromagnetics and geophysics

Enumath 2019

Asymptotically constant-free, p-robust and guaranteed a posteriori error estimates for the Helmholtz equation

T. Chaumont-Frelet (Inria project-team Nachos, CNRS, UCA LJAD) A. Ern (CERMICS, Inria project-team Serena) M. Vohralík (Inria project-team Serena, CERMICS)

Numerical methods for wave propagation with applications in electromagnetics and geophysics

Enumath 2019

Asymptotically constant-free, p-robust and guaranteed a posteriori error estimates for the Helmholtz equation

T. Chaumont-Frelet (Inria project-team Nachos, CNRS, UCA LJAD) A. Ern (CERMICS, Inria project-team Serena) M. Vohralík (Inria project-team Serena, CERMICS)

Numerical methods for wave propagation with applications in electromagnetics and geophysics

Enumath 2019

Given  $f$ , we seek  $u$  such that

$$
\begin{cases}\n-k^2u - \Delta u &= f \text{ in } \Omega, \\
u &= 0 \text{ on } \Gamma_{\text{D}}, \\
\nabla u \cdot \mathbf{n} - iku &= 0 \text{ on } \Gamma_{\text{A}},\n\end{cases}
$$







 $1/47$  T. Chaumont-Frelet, A. Ern and M. Vohralík A posteriori error estimates for the Helmholtz equation

After integration by parts, we obtain a weak formulation: Find  $u \in H^1_{\mathsf{F}_\mathrm{D}}(\Omega)$  such that

$$
b(u,v)=(f,v)\quad \forall v\in H^1_{\Gamma_{\text{D}}}(\Omega),
$$

where

$$
b(u,v):=-k^2(u,v)-ik(u,v)_{\Gamma_A}+(\nabla u,\nabla v).
$$



The discrete problem consists in finding  $u_h \in V_h$  such that

$$
b(u_h, v_h) = (f, v_h) \quad \forall v_h \in V_h,
$$

where  $V_h$  is the usual Lagrange FE discretization subspace of degree  $p \geq 1$ 

$$
V_h := \left\{ v_h \in H^1_{\Gamma_{\rm D}}(\Omega) \mid v_h|_K \in \mathcal{P}_p(K) \ \forall K \in \mathcal{T}_h \right\},\
$$

and where  $\mathcal{T}_h$  is a "shape-regular" mesh of  $\Omega$ .



We would like to estimate the discretization error

$$
e_h:=u-u_h,
$$

in some suitable norm  $\|\cdot\|_{\star,\Omega}$ .

We associate with each  $K \in \mathcal{T}_h$  a **computable** quantity

$$
\eta_K:=\eta_K(u_h,f)
$$

that we call a local "estimator". We gather the contributions

$$
\eta := \left(\sum_{K \in \mathcal{T}_h} \eta_K^2\right)^{1/2},
$$

into a "global" estimator.



## A "good" a posteriori estimator is reliable

$$
||e_h||_{\star,\Omega}\leq C\eta,
$$

and locally efficient

$$
\eta_K\leq \mathbf{C}\|\mathbf{e}_h\|_{\star,\omega_K},
$$

where:

C is a "nice" constant,  $C$  only depends on the "shape-regularity" and  $p$ ,  $\omega_K$  is the patch of elements sharing a vertex with K.



An error estimate is guaranteed, if

 $||e_h||_{\star,\Omega} \leq C\eta,$ 

with a fully computable constant  $\overline{C}$ .

An error estimate is **constant-free** if  $C = 1$ , i.e.

 $||e_h||_{\star,\Omega} \leq \eta.$ 

Finally, we say that an error estimate is  $p$ -robust, if

 $\eta_K \leq C \|e_h\|_{\star,\omega_K}$ 

with a constant  $C$  that is independent of  $p$ .

The goal of this talk is to (try to) achieve these properties using an "equilibrated" estimator.



- 1 The low wavenumber regime: the Poisson equation
- 2 The Helmholtz equation in the high-wavenumber regime
- 3 Numerical examples
- 4 Conclusions

### 1 The low wavenumber regime: the Poisson equation

- **Error upper bounds via equilibrated fluxes**
- Practical construction of the equilibrated flux
- Reliability and  $p$ -robustness
- Summary

## 2 The Helmholtz equation in the high-wavenumber regime

## 3 Numerical examples

### **4** Conclusions

1 The low wavenumber regime: the Poisson equation

- **Error upper bounds via equilibrated fluxes**
- **Practical construction of the equilibrated flux**
- Reliability and  $p$ -robustness
- Summary

2 The Helmholtz equation in the high-wavenumber regime

3 Numerical examples

**4** Conclusions

Let us first set  $k = 0$ . We obtain a "Poisson" problem:

$$
\begin{cases}\n-\Delta u = f \quad \text{in } \Omega, \\
u = 0 \quad \text{on } \Gamma_{\text{D}}, \\
\nabla u \cdot \mathbf{n} = 0 \quad \text{on } \Gamma_{\text{A}}.\n\end{cases}
$$

Equivalently, we seek  $u \in H^1_{\Gamma_{\mathrm{D}}}(\Omega)$  such that

$$
b(u,v)=(f,v)\quad \forall v\in H^1_{\Gamma_{\rm D}}(\Omega),
$$

where now

$$
b(u,v)=(\nabla u,\nabla v).
$$

The natural norm for the analysis is

$$
|\nu|_{1,\Omega}=\|\boldsymbol{\nabla}\nu\|_{0,\Omega}.
$$



We call "equilibrated flux" an element  $\sigma \in H(\text{div}, \Omega)$  such that

$$
\left\{\begin{array}{rcl}\nabla \cdot \boldsymbol{\sigma} & = & f & \text{in } \Omega, \\
\boldsymbol{\sigma} \cdot \boldsymbol{n} & = & 0 & \text{on } \Gamma_{A}.\n\end{array}\right.
$$



8/47 T. Chaumont-Frelet, A. Ern and M. Vohralík A posteriori error estimates for the Helmholtz equation

We call "equilibrated flux" an element  $\sigma \in H(\text{div}, \Omega)$  such that

$$
\left\{\begin{array}{rcl}\nabla \cdot \boldsymbol{\sigma} & = & f & \text{in } \Omega, \\
\boldsymbol{\sigma} \cdot \boldsymbol{n} & = & 0 & \text{on } \Gamma_{A}.\n\end{array}\right.
$$

Recalling that

$$
\left\{\begin{array}{rcl}\nabla \cdot (-\nabla u) & = & f & \text{in } \Omega, \\
(-\nabla u) \cdot \mathbf{n} & = & 0 & \text{on } \Gamma_A,\n\end{array}\right.
$$

this definition mimics the properties of  $-\nabla u$ .



We call "equilibrated flux" an element  $\sigma \in H(\text{div}, \Omega)$  such that

$$
\left\{\begin{array}{rcl}\nabla \cdot \boldsymbol{\sigma} & = & f & \text{in } \Omega, \\
\boldsymbol{\sigma} \cdot \boldsymbol{n} & = & 0 & \text{on } \Gamma_{A}.\n\end{array}\right.
$$

Recalling that

$$
\left\{\begin{array}{rcl}\nabla \cdot (-\nabla u) & = & f & \text{in } \Omega, \\
(-\nabla u) \cdot \mathbf{n} & = & 0 & \text{on } \Gamma_A,\n\end{array}\right.
$$

this definition mimics the properties of  $-\nabla u$ .

We have

$$
|e_h|_{1,\Omega}=\|(-\boldsymbol{\nabla} u)+\boldsymbol{\nabla} u_h\|_{0,\Omega}\leq \|\boldsymbol{\sigma}+\boldsymbol{\nabla} u_h\|_{0,\Omega}
$$

for any equilibrated flux  $\sigma \in H(\text{div}, \Omega)$ .



This is known as the Prager-Synge theorem. How do we establish this result?



 $9/47$  T. Chaumont-Frelet, A. Ern and M. Vohralík A posteriori error estimates for the Helmholtz equation

This is known as the Prager-Synge theorem. How do we establish this result? We have the following expression for the error:

$$
\begin{aligned} |e_h|^2_{1,\Omega} &= b(e_h, e_h) \\ &= b(u, e_h) - b(u_h, e_h) \\ &= (f, e_h) - (\boldsymbol{\nabla} u_h, \boldsymbol{\nabla} e_h) \end{aligned}
$$



This is known as the Prager-Synge theorem. How do we establish this result? We have the following expression for the error:

$$
|e_h|_{1,\Omega}^2 = b(e_h, e_h)
$$
  
= b(u, e\_h) - b(u\_h, e\_h)  
= (f, e\_h) - (\nabla u\_h, \nabla e\_h)

We can rewrite the first term

$$
(f, e_h) = (\nabla \cdot \boldsymbol{\sigma}, e_h) = -(\boldsymbol{\sigma}, \nabla e_h).
$$



This is known as the Prager-Synge theorem. How do we establish this result? We have the following expression for the error:

$$
|e_h|_{1,\Omega}^2 = b(e_h, e_h)
$$
  
= b(u, e\_h) - b(u\_h, e\_h)  
= (f, e\_h) - (\nabla u\_h, \nabla e\_h)

We can rewrite the first term

$$
(f, e_h) = (\nabla \cdot \boldsymbol{\sigma}, e_h) = -(\boldsymbol{\sigma}, \nabla e_h).
$$

This leads to

$$
|e_h|_{1,\Omega}^2=-(\boldsymbol{\nabla} u_h+\boldsymbol{\sigma},\boldsymbol{\nabla} e_h)\leq \|\boldsymbol{\sigma}+\boldsymbol{\nabla} u_h\|_{0,\Omega}|e_h|_{1,\Omega},
$$

and the result follows.



Given an "equilibrated flux"  $\sigma \in H(\text{div}, \Omega)$ , we set

$$
\eta_K := \|\boldsymbol{\sigma} + \boldsymbol{\nabla} u_h\|_{0,K} \quad \forall K \in \mathcal{T}_h
$$

and

$$
\eta^2 := \sum_{K \in \mathcal{T}_h} \eta_K^2 = \|\boldsymbol{\sigma} + \boldsymbol{\nabla} u_h\|_{0,\Omega}^2.
$$

Then, we have

$$
|e_h|_{1,\Omega}\leq \eta=\|\boldsymbol{\sigma}+\boldsymbol{\nabla}u_h\|_{0,\Omega}.
$$

Equilibrated fluxes provide constant-free error estimates!



1 The low wavenumber regime: the Poisson equation **Error upper bounds via equilibrated fluxes** Practical construction of the equilibrated flux Reliability and  $p$ -robustness

- Summary
- 2 The Helmholtz equation in the high-wavenumber regime
- 3 Numerical examples
- **4** Conclusions

For the sake of simplicity, we assume that  $f|_K \in \mathcal{P}_{p-1}(K)$  for all  $K \in \mathcal{T}_h$ . All the presented result naturally extends by adding "oscillation terms"

$$
\mathsf{osc}_K(f) := \frac{h_K}{\pi} \|f - \pi_K^{p-1}f\|_{0,K}.
$$

Let  $W_h \subset H(\text{div}, \Omega)$  denote the Raviart-Thomas space of degree p. There exists  $\sigma_b \in W_b$  such that

$$
\nabla \cdot \boldsymbol{\sigma}_h = f,
$$

so that we can construct "discrete" equilibrated fluxes.



We recall that we have the upper bound

$$
|e_h|_{1,\Omega}\leq \eta:=\|\boldsymbol{\sigma}_h+\boldsymbol{\nabla} u_h\|_{0,\Omega}.
$$

Thus the "ideal" discrete flux would be

$$
\sigma_h := \operatorname*{argmin}_{\substack{\boldsymbol{\tau}_h \in \mathbf{W}_h \\ \nabla \cdot \boldsymbol{\tau}_h = \boldsymbol{0} \\ \boldsymbol{\tau}_h \cdot \boldsymbol{\eta}_h = \boldsymbol{0} \text{ on } \partial \omega_a \setminus \Gamma_{\rm D}}} ||\boldsymbol{\tau}_h + \nabla u_h||_{0,\Omega}.
$$

It is computable, through resolution of a discrete global saddle point problem.

Fortunaly, it is possible to localize the computations, vertex by vertex.



For each vertex  $a \in V_h$ , consider the following vertex-patch problem

$$
\sigma_h^a := \operatorname*{argmin}_{\substack{\boldsymbol{\tau}_h^a \in \mathbf{W}_h(\omega_a) \\ \nabla \cdot \boldsymbol{\tau}_h^a = \boldsymbol{f}^a \text{ in } \omega_a \\ \boldsymbol{\tau}_h^a \cdot \mathbf{n} = 0 \text{ on } \partial \omega_a \setminus \Gamma_{\rm D}}} ||\boldsymbol{\tau}_h^a + \psi_a \boldsymbol{\nabla} u_h||_{0,\Omega},
$$

where  $\omega_a$  is the "vertex patch" around a

$$
f^a = \psi_a f - \nabla \psi_a \cdot \nabla u_h,
$$

and  $\psi_a$  is the "hat function" associated with a.

We obtain an equilibrated flux by setting

$$
\boldsymbol{\sigma}_h := \sum_{\boldsymbol{a} \in \mathcal{V}_h} \boldsymbol{\sigma}_h^{\boldsymbol{a}}.
$$

This construction only involves patch-wise finite element problems. These problems involves a small number of dofs and can solved in parallel.



## 1 The low wavenumber regime: the Poisson equation

- **Error upper bounds via equilibrated fluxes**
- **Practical construction of the equilibrated flux**
- Reliability and  $p$ -robustness
- Summary
- 2 The Helmholtz equation in the high-wavenumber regime
- 3 Numerical examples
- **4** Conclusions

Our particular construction of  $\sigma_h$  leads to p robust estmiates: we have

$$
\eta_K := \|\boldsymbol{\sigma}_h + \boldsymbol{\nabla} u_h\|_{0,K} \leq C |\boldsymbol{e}_h|_{1,\omega_K}
$$

where  $\boldsymbol{C}$  is independent of  $p$ .

D. Braess, V. Pillwein, J. Schöberl, CMAME, 2009:

Equilibrated residual error estimates are p-robust.

A. Ern and M. Vohralík, Math. Comp., 2019:

Stable broken  $H^1$  and  $\bm{H}(div)$  polynomial extensions for p-robust potential and flux reconstruction in 3D.



#### 1 The low wavenumber regime: the Poisson equation

- **Error upper bounds via equilibrated fluxes**
- **Practical construction of the equilibrated flux**
- Reliability and  $p$ -robustness
- Summary

2 The Helmholtz equation in the high-wavenumber regime

3 Numerical examples

#### **4** Conclusions

We construct an equilibrated flux  $\sigma_h$  based on local finite element problems.

This flux provides a constant-free error estimate

$$
|e_h|_{1,\Omega}\leq \|\boldsymbol{\sigma}_h+\boldsymbol{\nabla} u_h\|_{0,\Omega}=: \eta.
$$

This estimator is locally efficient and p-robust since

$$
\eta_K:=\|\boldsymbol{\sigma}_h+\boldsymbol{\nabla} u_h\|_{0,K}\leq C|e_h|_{1,\omega_K},
$$

with a constant  $C$  that is independent of  $p$ .



#### 1 The low wavenumber regime: the Poisson equation

## 2 The Helmholtz equation in the high-wavenumber regime

- $\blacksquare$  How do we deal with the absence of coercivity?
- **Error upper bound via equilibrated fluxes**
- Practical construction, reliability and  $p$ -robustness
- **Summary**

#### 3 Numerical examples

#### **4** Conclusions

#### 1 The low wavenumber regime: the Poisson equation

#### 2 The Helmholtz equation in the high-wavenumber regime  $\blacksquare$  How do we deal with the absence of coercivity?

- **Error upper bound via equilibrated fluxes**
- **Practical construction, reliability and p-robustness**
- **Summary**
- 3 Numerical examples
- **4** Conclusions

Let us now assume that  $k$  is large. We recall that

$$
b(u,v):=-k^2(u,v)-ik(u,v)_{\Gamma_{\mathcal{A}}}+(\nabla u,\nabla v)\quad\forall u,v\in H^1_{\Gamma_{\mathcal{D}}}(\Omega).
$$

We will consider the "natural" norm

$$
||u||_{1,k,\Omega}^2 := k^2 ||u||_{0,\Omega}^2 + k||u||_{0,\Gamma_\mathcal{A}}^2 + ||\nabla u||_{0,\Omega}^2.
$$

In particular, we have

$$
|b(u,v)| \leq ||u||_{1,k,\Omega}||v||_{1,k,\Omega},
$$

which is interesting for goal-oriented error estimation and adaptivity.



The sesquilinear form is not coercive

Re 
$$
b(\phi, \phi) = |\phi|_{1,\Omega}^2 - k^2 ||\phi||_{0,\Omega}^2, \quad \phi \in H_{\Gamma_{\text{D}}}^1(\Omega).
$$

Instead, it satisfies a Gårding-like inequality:

$$
\operatorname{Re} b(\phi,\phi)=\|\phi\|_{1,k,\Omega}^2-\left(2k^2\|\phi\|_{0,\Omega}^2+k\|\phi\|_{0,\Gamma_{\rm A}}^2\right),\quad \phi\in H^1_{\Gamma_{\rm D}}(\Omega).
$$

The coercivity loss is more severe for higher wavenumber  $k$ .





 $18/47$  T. Chaumont-Frelet, A. Ern and M. Vohralík A posteriori error estimates for the Helmholtz equation

For  $\phi\in H^1_{\mathsf{F_D}}(\Omega)$ , there exists a unique  $\mathscr{S}_\phi^\star\in H^1_{\mathsf{F_D}}(\Omega)$  such that

$$
b(w,\mathscr{S}_{\phi}^{\star})=2k^2(w,\phi)+k(w,\phi)_{\Gamma_{\Lambda}}.
$$



18/47 T. Chaumont-Frelet, A. Ern and M. Vohralík A posteriori error estimates for the Helmholtz equation
For  $\phi\in H^1_{\mathsf{F_D}}(\Omega)$ , there exists a unique  $\mathscr{S}_\phi^\star\in H^1_{\mathsf{F_D}}(\Omega)$  such that  $b(w, \mathscr{S}_{\phi}^{\star}) = 2k^2(w, \phi) + k(w, \phi)_{\Gamma_{\Lambda}}.$ 

Importantly, we have

$$
b(\phi,\mathscr{S}_{\phi}^{\star})=2k^2\|\phi\|_{0,\Omega}^2+k\|\phi\|_{0,\Gamma_{\mathrm{A}}}^2,
$$

for all  $\phi \in H^1_{\mathsf{F}_\mathrm{D}}(\Omega)$ .



For  $\phi\in H^1_{\mathsf{F_D}}(\Omega)$ , there exists a unique  $\mathscr{S}_\phi^\star\in H^1_{\mathsf{F_D}}(\Omega)$  such that  $b(w, \mathscr{S}_{\phi}^{\star}) = 2k^2(w, \phi) + k(w, \phi)_{\Gamma_{\Lambda}}.$ 

Importantly, we have

$$
b(\phi,\mathscr{S}_{\phi}^{\star})=2k^2\|\phi\|_{0,\Omega}^2+k\|\phi\|_{0,\Gamma_{\mathrm{A}}}^2,
$$

for all  $\phi \in H^1_{\mathsf{F}_\mathrm{D}}(\Omega)$ .

Recalling that

$$
\text{Re } b(\phi,\phi) = \|\phi\|_{1,k,\Omega}^2 - \left(2k^2 \|\phi\|_{0,\Omega}^2 + k \|\phi\|_{0,\Gamma_{\mathcal{A}}}^2\right),
$$

we have



For  $\phi\in H^1_{\mathsf{F_D}}(\Omega)$ , there exists a unique  $\mathscr{S}_\phi^\star\in H^1_{\mathsf{F_D}}(\Omega)$  such that  $b(w, \mathscr{S}_{\phi}^{\star}) = 2k^2(w, \phi) + k(w, \phi)_{\Gamma_{\Lambda}}.$ 

Importantly, we have

$$
b(\phi,\mathscr{S}_{\phi}^{\star})=2k^2\|\phi\|_{0,\Omega}^2+k\|\phi\|_{0,\Gamma_{\mathrm{A}}}^2,
$$

for all  $\phi \in H^1_{\mathsf{F}_\mathrm{D}}(\Omega)$ .

Recalling that

$$
\text{Re } b(\phi,\phi) = \|\phi\|_{1,k,\Omega}^2 - \left(2k^2 \|\phi\|_{0,\Omega}^2 + k \|\phi\|_{0,\Gamma_{\mathcal{A}}}^2\right),
$$

we have

$$
\operatorname{Re} b(\phi, \phi + \mathscr{S}_{\phi}^{\star}) = ||\phi||_{1,k,\Omega}^{2}
$$

for all  $\phi \in H^1_{\mathsf{F}_\mathrm{D}}(\Omega)$ .



We then introduce

$$
\gamma_{\text{ba}}:=\sup_{\phi\in H^1_{\Gamma_{\rm D}}(\Omega)\setminus\{0\}}\min_{v_h\in V_h}\frac{\|\mathscr{S}^\star_{\phi}-v_h\|_{1,k,\Omega}}{\|\phi\|_{1,k,\Omega}}.
$$

It is the best constant such that

$$
\min_{v_h \in V_h} \|\mathscr{S}_{\phi}^{\star} - v_h\|_{1,k,\Omega} \leq \gamma_{\text{ba}} \|\phi\|_{1,k,\Omega} \quad \forall \phi \in H^1_{\Gamma_{\text{D}}}(\Omega).
$$

It measures how well the FE scheme can approximate the "coercivity help"  $\mathscr{S}_{\phi}^{\star}$ .



### Approximation factor

In the strong sense,  $\mathscr{S}_{\phi}^{\star}$  is defined by

$$
\begin{cases}\n-k^2 \mathscr{S}_{\phi}^{\star} - \Delta \mathscr{S}_{\phi}^{\star} &= 2k^2 \phi \text{ in } \Omega, \\
\mathscr{S}_{\phi}^{\star} &= 0 \text{ on } \Gamma_{D}, \\
\nabla \mathscr{S}_{\phi}^{\star} \cdot \mathbf{n} + ik \mathscr{S}_{\phi}^{\star} &= k \phi \text{ on } \Gamma_{A}.\n\end{cases}
$$

In particular  $\mathscr{S}_{\phi}^{\star}\in H^{1+\varepsilon}(\Omega)$  for some  $\varepsilon>0,$  so that

$$
\boldsymbol{\gamma}_{\mathrm{ba}} \leq \boldsymbol{C}(\Omega,\boldsymbol{\Gamma}_\mathrm{D},k) \left(\frac{h}{\rho}\right)^\varepsilon \rightarrow 0.
$$

For non-trapping domains, we can show that

$$
\gamma_{\text{ba}} \leq \boldsymbol{C}(\Omega,\Gamma_{\text{D}})\left(\frac{k h}{\rho} + k \left(\frac{k h}{\rho}\right)^{\rho}\right).
$$

J.M. Melenk and S. Sauter, SIAM J. Numer. Anal., 2011:

Wavenumber explicit convergence analysis for Galerkin discretizations of the Helmholtz equation.

T. Chaumont-Frelet and S. Nicaise, IMA J. Numer. Anal., 2019:

Wavenumber explicit convergence analysis for finite element discretizations of general wave propagation problems.



# **Outline**

#### 1 The low wavenumber regime: the Poisson equation

### 2 The Helmholtz equation in the high-wavenumber regime

How do we deal with the absence of coercivity?

#### **Error upper bound via equilibrated fluxes**

- **Practical construction, reliability and p-robustness**
- **Summary**

#### **3** Numerical examples

#### **4** Conclusions

We observe that  $-\nabla u \in H(\text{div}, \Omega)$  and

$$
\left\{\begin{array}{rcl}\nabla \cdot (-\nabla u) & = & f + k^2 u \quad \text{in } \Omega, \\
(-\nabla u) \cdot \mathbf{n} & = & -iku \quad \text{on } \Gamma_\mathbf{A}.\n\end{array}\right.
$$

This motivation the following definition: we say that  $\sigma \in H(\text{div}, \Omega)$  is an equilibrated flux if

$$
\begin{cases}\n\nabla \cdot \boldsymbol{\sigma} = f + k^2 u_h & \text{in } \Omega, \\
\boldsymbol{\sigma} \cdot \boldsymbol{n} = -ik u_h & \text{on } \Gamma_A.\n\end{cases}
$$

Can we relate  $||e_h||_{1,k,\Omega}$  and  $||\boldsymbol{\sigma} + \boldsymbol{\nabla} u_h||_{0,\Omega}$ ?



As a comparison, the starting point was

$$
|e_h|^2_{1,\Omega}=b(e_h,e_h)
$$

in the coercive case. Here, the situation is more complex.



As a comparison, the starting point was

$$
|e_h|^2_{1,\Omega}=b(e_h,e_h)
$$

in the coercive case. Here, the situation is more complex.

Using the definition of  $\mathscr{S}_{e_\mathsf{h}}^\star$  and Galerkin orthogonality, we have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h,e_h+\mathscr{S}_{e_h}^*) = b(e_h,e_h+\mathscr{S}_{e_h}^* - v_h) = b(e_h,\psi)
$$

where

$$
\psi:=e_h+\mathscr{S}^\star_{e_h}-v_h\qquad v_h:=\underset{\nu_h\in V_h}{\text{argmin}}\,\|\mathscr{S}^\star_{e_h}-v_h\|_{1,k,\Omega}.
$$



As a comparison, the starting point was

$$
|e_h|^2_{1,\Omega}=b(e_h,e_h)
$$

in the coercive case. Here, the situation is more complex.

Using the definition of  $\mathscr{S}_{e_\mathsf{h}}^\star$  and Galerkin orthogonality, we have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h,e_h+\mathscr{S}_{e_h}^*) = b(e_h,e_h+\mathscr{S}_{e_h}^* - v_h) = b(e_h,\psi)
$$

where

$$
\psi := e_h + \mathscr{S}_{e_h}^{\star} - v_h \qquad v_h := \underset{v_h \in V_h}{\text{argmin}} \, \| \mathscr{S}_{e_h}^{\star} - v_h \|_{1,k,\Omega}.
$$

We can show that

$$
\begin{aligned} \|\psi\|_{1,k,\Omega} &\leq \|e_h\|_{1,k,\Omega} + \min_{v_h \in V_h} \|\mathscr{S}_{e_h}^\star - v_h\|_{1,k,\Omega} \\ &\leq (1 + \gamma_{ba})\|e_h\|_{1,k,\Omega} .\end{aligned}
$$





We have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h, \psi) = b(u, \psi) - b(e_h, \psi)
$$
  
=  $(f, \psi) + k^2(u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi)$   
=  $(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi).$ 



We have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h, \psi) = b(u, \psi) - b(e_h, \psi)
$$
  
=  $(f, \psi) + k^2(u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi)$   
=  $(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi).$ 

For any equilibrated flux  $\sigma \in H(\text{div}, \Omega)$ , we have

$$
(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} = (\nabla \cdot \boldsymbol{\sigma}, \psi) - (\boldsymbol{\sigma} \cdot \boldsymbol{n}, \psi)_{\partial \Omega} = -(\boldsymbol{\sigma}, \nabla \psi).
$$



We have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h, \psi) = b(u, \psi) - b(e_h, \psi)
$$
  
=  $(f, \psi) + k^2(u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi)$   
=  $(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi).$ 

For any equilibrated flux  $\sigma \in H(\text{div}, \Omega)$ , we have

$$
(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} = (\nabla \cdot \boldsymbol{\sigma}, \psi) - (\boldsymbol{\sigma} \cdot \boldsymbol{n}, \psi)_{\partial \Omega} = -(\boldsymbol{\sigma}, \nabla \psi).
$$

It follows that

$$
\|e_h\|_{1,k,\Omega}^2=-(\boldsymbol{\sigma}+\boldsymbol{\nabla}u_h,\boldsymbol{\nabla}\psi)\leq \|\boldsymbol{\sigma}+\boldsymbol{\nabla}u_h\|_{0,\Omega}|\psi|_{1,\Omega},
$$



We have

$$
||e_h||_{1,k,\Omega}^2 = b(e_h, \psi) = b(u, \psi) - b(e_h, \psi)
$$
  
=  $(f, \psi) + k^2(u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi)$   
=  $(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} - (\nabla u_h, \nabla \psi).$ 

For any equilibrated flux  $\sigma \in H(\text{div}, \Omega)$ , we have

$$
(f + k^2 u_h, \psi) + ik(u_h, \psi)_{\Gamma_A} = (\nabla \cdot \boldsymbol{\sigma}, \psi) - (\boldsymbol{\sigma} \cdot \boldsymbol{n}, \psi)_{\partial \Omega} = -(\boldsymbol{\sigma}, \nabla \psi).
$$

It follows that

$$
\|e_h\|_{1,k,\Omega}^2=-(\boldsymbol{\sigma}+\boldsymbol{\nabla}u_h,\boldsymbol{\nabla}\psi)\leq \|\boldsymbol{\sigma}+\boldsymbol{\nabla}u_h\|_{0,\Omega}|\psi|_{1,\Omega},
$$

and we can conclude since

$$
|\psi|_{1,\Omega}\leq \|\psi\|_{1,k,\Omega}\leq (1+\gamma_{ba})\|e_h\|_{1,k,\Omega}.
$$



We thus obtain that

$$
\|e_h\|_{1,k,\Omega}\leq (1+\boldsymbol{\gamma}_{\mathrm{ba}})\|\boldsymbol{\sigma}+\boldsymbol{\nabla}\boldsymbol{u}_h\|_{0,\Omega}
$$

for any equilibrated flux  $\sigma$ .

This estimate is "asymptotically constant-free", as  $\gamma_{ba} \rightarrow 0$  as  $(h/p) \rightarrow 0$ .

Guaranteed estimates can be obtained if computabable upper-bounds

$$
\pmb{\gamma}_\mathrm{ba} \leq \widetilde{\pmb{\gamma}}_\mathrm{ba}
$$

are provided, which is possible for non-trapping domains.

T. Chaumont-Frelet, A. Ern, M. Vohralík, submittted, 2019:

On the derivation of guaranteed and p-robust a posteriori error estimates for the Helmholtz equation.



# **Outline**

#### 1 The low wavenumber regime: the Poisson equation

#### 2 The Helmholtz equation in the high-wavenumber regime

- How do we deal with the absence of coercivity?
- **Error upper bound via equilibrated fluxes**
- Practical construction, reliability and  $p$ -robustness
- **Summary**
- **3** Numerical examples
- **4** Conclusions

We follow the techniques used for the Poisson problem.

For  $a \in V_h$ , we introduce vertex-patch minimization problems

$$
\sigma_h^a := \operatorname*{argmin}_{\substack{\tau_h^a \in W_h(\omega_a) \\ \nabla \cdot \tau_h^a = d^a \text{ in } \omega_a \\ \tau_h^a \cdot n = b^a \text{ on } \partial \omega_a \setminus \Gamma_D}} ||\tau_h^a - \nabla u_h||_{0,\omega_a}.
$$

where

$$
d^a:=\psi^a(f+k^2u_h)-\boldsymbol{\nabla}\psi^a\cdot\boldsymbol{\nabla} u_h\quad b^a:=ik\psi^au_h\mathbf{1}_{\Gamma_A}.
$$

We obtain the global equilibrated flux by summation:

$$
\boldsymbol{\sigma}_h := \sum_{\boldsymbol{a}\in\mathcal{V}_h} \boldsymbol{\sigma}_h^{\boldsymbol{a}}.
$$



Thanks to our particular construction, we additionally have

$$
\eta_K := \|\boldsymbol{\sigma}_h + \boldsymbol{\nabla} u_h\|_{0,K} \leq \boldsymbol{C} \left(1 + \left(\frac{kh}{\rho}\right)^{1/2} + \frac{kh}{\rho}\right) \|e_h\|_{1,k,\omega_K},
$$

where the constant  $C$  only depends on the shape-regularity of the mesh.

The estimator is reliable and  $p$ -robust as long as

$$
\frac{kh}{p} \leq C
$$

which means that  $N_{\text{dofs}/\lambda} \geq C$ .



# **Outline**

#### 1 The low wavenumber regime: the Poisson equation

#### 2 The Helmholtz equation in the high-wavenumber regime

- How do we deal with the absence of coercivity?
- **Error upper bound via equilibrated fluxes**
- **Practical construction, reliability and p-robustness**
- Summary
- 3 Numerical examples
- **4** Conclusions

We can construct an equilibrated flux  $\sigma_h$  using local finite element problems.

The construction is very similar to the coercive case (different rhs).



The error estimates

$$
\|e_h\|_{1,k,\Omega}\leq (1+\boldsymbol{\gamma}_{\mathrm{ba}})\eta
$$

is asymptotically constant-free since  $\gamma_{ba} \rightarrow 0$  as  $h/p \rightarrow 0$ .

For non-trapping domains,  $\gamma_{ba} \ll 1$  means

$$
N_{\text{dofs}/\lambda} \gg \mathbf{C}(\Omega,\Gamma_{\text{D}})(1+k^{1/p}),
$$

i.e. many dofs per wavelength or large p.

Guaranteed upper bounds can be obtain if computable upper bounds

$$
\boldsymbol{\gamma}_{ba} \leq \widetilde{\boldsymbol{\gamma}}_{ba},
$$

are provided. It is tough, but possible for several configurations of interest!



The p-robust local lower-bound

$$
\eta_K \leq \mathcal{C}\left(1 + \left(\frac{k h}{\rho}\right)^{1/2} + \frac{k h}{\rho}\right) \|e_h\|_{1,k,\omega_K}
$$

holds.

Thus, the estimator is efficient and  $p$ -robust when we have sufficiently many dofs per wavelength:

$$
\frac{kh}{p} \leq C \quad \text{or} \quad N_{\text{dofs}/\lambda} \geq C.
$$



1 The low wavenumber regime: the Poisson equation

2 The Helmholtz equation in the high-wavenumber regime

3 Numerical examples

- A validation experiment
- A more realistic example

#### **4** Conclusions

1 The low wavenumber regime: the Poisson equation

2 The Helmholtz equation in the high-wavenumber regime

3 Numerical examples

- A validation experiment
- A more realistic example

#### 4 Conclusions

### Propagation of a plane wave

We consider the propagation of a plane wave in  $\Omega = (-1, 1)^2$ 

$$
\begin{cases}\n-k^2u - \Delta u &= 0 & \text{in } \Omega, \\
u &= 0 & \text{on } \Gamma_{D}, \\
\nabla u \cdot \mathbf{n} - iku &= g & \text{on } \Gamma_{A},\n\end{cases}
$$

where

$$
g := \nabla \xi_{\theta} \cdot \mathbf{n} - ik\xi_{\theta} \quad \xi_{\theta} := e^{ik\mathbf{d} \cdot \mathbf{x}}
$$

with  $\mathbf{d} := (\cos \theta, \sin \theta)$  and  $\theta = \pi/12$ . The solution is  $u = \xi_{\theta}$ .









Plane wave experiment  $p = 1$  and  $k = 4\pi$ 





Plane wave experiment  $p = 1$  and  $k = 10\pi$ 





Plane wave experiment  $p = 1$  and  $k = 20\pi$ 





Plane wave experiment  $p = 4$  and  $k = 10\pi$ 





Plane wave experiment  $p = 4$  and  $k = 20\pi$ 





Plane wave experiment  $p = 4$  and  $k = 40\pi$ 





Plane wave experiment  $p = 4$  and  $k = 60\pi$ 





1 The low wavenumber regime: the Poisson equation

2 The Helmholtz equation in the high-wavenumber regime

#### 3 Numerical examples

- A validation experiment
- A more realistic example

#### **4** Conclusions



We fix the wavenumber  $k = 10\pi$  and employ  $P_3$  elements.

We consider a sequence of meshes that are adaptively refined using  $\eta_K$ .


# Solution of the scattering problem



### Real (left) and imaginary (right) parts of the solution





# Estimator  $\eta_K$  (left) and elementwise error  $||e_h||_{1,k,K}$  (right)





# Estimator  $\eta_K$  (left) and elementwise error  $||e_h||_{1,k,K}$  (right)





# Estimator  $\eta_K$  (left) and elementwise error  $||e_h||_{1,k,K}$  (right)





#### Behaviors of the estimated and analytical errors in the adaptive procedure



- 1 The low wavenumber regime: the Poisson equation
- 2 The Helmholtz equation in the high-wavenumber regime
- 3 Numerical examples
- 4 Conclusions

The upper bound

$$
\|e_h\|_{1,k,\Omega}\leq (1+\boldsymbol{\gamma}_{\mathrm{ba}})\eta
$$

is "asymptotically constant-free" since  $\gamma_{ba} \rightarrow 0$  as  $h/p \rightarrow 0$ .

We "qualitatively" know the behaviour of  $\gamma_{ba}$  for non-trapping domains

$$
\gamma_{\text{ba}} \leq \boldsymbol{C}(\Omega,\Gamma_{\text{D}})\left(\frac{k h}{p} + k \left(\frac{k h}{p}\right)^p\right).
$$

It is possible to obtain (coarse) guaranteed upper bounds, by deriving computable estimates  $\pmb{\gamma}_{\text{ba}} \leq \widetilde{\pmb{\gamma}}_{\text{ba}}.$ 



We obtain lower bounds of the form

$$
\eta_K \leq \textit{\textbf{C}}\left(1+\left(\frac{kh}{\rho}\right)^{1/2}+\frac{kh}{\rho}\right)\|e_h\|_{1,k,\Omega},
$$

where the constant C only depends on the shape-regularity parameter of  $\mathcal{T}_h$ .

The proposed estimator is efficient and p-robust as long as  $N_{\text{dofs}/\lambda} \geq C$ .



#### Early work in 1D, with first-order FE:

I. Babuška, F. Ihlenburg, T. Strouboulis and S.K. Gangaraj, Int. J. Numer. Meth. Engrg., 1997:

A posteriori error estimation for finite element solutions of Helmholtz equation. Part I & II.

### Residual-based estimators in 3D with high-order FE and DG:

W. Dörfler and S. Sauter, Comput. Meth. Appl. Math., 2013:

A posteriori error estimation for highly indefinite Helmholtz problems.

S. Sauter and J. Zech, SIAM J. Numer. Anal., 2015:

A posteriori error estimation of  $hp - dG$  finite element methods for highly indefinite Helmholtz problems.

#### Recent works using equilibrated fluxes:

S. Congreve, J. Gedicke, I. Perugia, SIAM J. Sci. Comp., 2019:

Robust adaptive hp-discontinuous Galerkin finite element methods for the Helmholtz equation.

T. Chaumont-Frelet, A. Ern, M. Vohralík, submittted, 2019;

On the derivation of guaranteed and p-robust a posteriori error estimates for the Helmholtz equation.

