

Embedded Sensor Fusion and Perception for Autonomous Vehicle

Christian Laugier

▶ To cite this version:

Christian Laugier. Embedded Sensor Fusion and Perception for Autonomous Vehicle. IS Auto Europe 2019 - Image Sensors Automotive Conference, Apr 2019, Berlin, Germany. pp.1-30. hal-02434279

HAL Id: hal-02434279 https://inria.hal.science/hal-02434279v1

Submitted on 9 Jan 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Embedded Sensor Fusion & Perception for Autonomous Vehicles

Dr HDR Christian LAUGIER

Research Director at Inria & Scientific Advisor for Probayes & Baidu China INRIA Chroma team & IRT Nanoelec christian.laugier@inria.fr

Contributions from L. Rummelhard, A. Negre, N. Turro, J.A. David, J. Lussereau, T. Genevois, C. Tay Meng Keat, S. Lefevre O. Erkent, D. Sierra-Gonzalez



IS Auto Europe 2019 Berlin, Germany, 9-10 April 2019





© Inria & Laugier. All rights reserved

Technology status & Ongoing challenges for AV

- Strong involvement of Car Industry & GAFA + Large media coverage
- An expected market of 500 B€in 2035... but Legal & Regulation issues still unclear
- Technologies Validation & Certification => Numerous experiments in real traffic conditions since 2010 (*Disengagement reports* \Leftrightarrow *Insights on system maturity*)
- => But insufficient ... Realistic Simulation & Formal methods are also needed (e_{ast} Fynchab



• No pedestrians & Plenty of separations between lanes



Addition of the second second



Dense 3D mapping & Numerous vehicles 10 years R&D, 8 millions km covered since 2010 & 25 000 km/dav



"Self-Driving Taxi Service" testing in US (*Uber*, *Waymo*) & Singapore (*nuTonomy*) \Rightarrow Autonomous Mobility Service, Numerous Sensors + "Safety driver" during testing \Rightarrow Uber: System testing since 2017, Disengagement every 0.7 miles in 2017 (improved now) \Rightarrow Waymo: 1st US Self Driving Taxi Service launched in Phoenix in Dec 2018

 \Rightarrow Disengagement reports provide insights on the technology maturity

Safety issue: Tesla Autopilot "level 2" fatal accident (May 2016)

□ Tesla driver killed in a crash with Autopilot "level 2" active (ADAS mode)

The Autopilot failed to detect a white moving truck, with a brightly lit sky

• *Camera* => *White color against a brightly lit sky* ?


• *Radar* => *High height of the trailer probably confused the radar into thinking it is an overhead road sign ?*



The human driver was not vigilant



Tesla Model S – Autopilot Front perception: Camera (Mobileye)+ Radar + US sensors





Safety issue: Uber "level 3" AV fatal accident (March 2018)

Self-driving Uber AV kills a woman in the first fatal crash involving a pedestrian *Temple, Arizona, March 2018*

The vehicle was moving at 40 mph and didn't reduced its speed before the crash

- Despite the presence of multiple sensors, the perception system failed to detect the pedestrian in a poor lighting condition
- The AV didn't disengaged

□ The Safety Driver reacted too late => *He was not attentive enough, and he reacted less than 1s before the*

crash & started to brake 1s after the crash









Embedded Perception & Scene Understanding – Overview

Complex Dynamic Scenes understanding



Situation Awareness & Decision-making ⇒ Sensing + Prior knowledge + Interpretation ⇒ Navigation strategy



Perception & Decision-making for Safe Intentional Navigation



Main features

- ✓ Dynamic & Open Environments => *Real-time processing & Reactivity*
- ✓ Incompleteness & Uncertainty => *Appropriate Model & Algorithms (probabilistic approaches)*
- ✓ Sensors limitations (no sensor is perfect) => *Multi-Sensors Fusion*
- ✓ Hardware / Software integration => *Satisfying Embedded constraints*
- ✓ Human in the loop (mixed traffic) => *Human Aware Decision-making*


Taking into account Interactions + Behaviors + Social rules (including traffic rules)

Paradigm 1: Embedded Bayesian Perception



Embedded Multi-Sensors Perception ⇒ Continuous monitoring of the dynamic environment

Main challenges





- ✓ Noisy data, Incompleteness, Dynamicity, Discrete measurements
- ✓ Strong Embedded & Real time constraints

Our Approach: Embedded Bayesian Perception

- ✓ Reasoning about Uncertainty & Time window (Past & Future events)
- ✓ Improving robustness using Bayesian Sensors Fusion
- ✓ Interpreting the dynamic scene using Contextual & Semantic information
- ✓ Software & Hardware integration using GPU, Multicore, Microcontrollers...




Bayesian Perception : Basic idea

□ Multi-Sensors Observations *Lidar, Radar, Stereo camera, IMU* ...

Probabilistic Environment Model

- ✓ Sensor Fusion
- ✓ Occupancy grid integrating uncertainty
 ✓ Probabilistic representation of Velocities
- ✓ Prediction models



 \Rightarrow Occupancy & Velocity probabilities

 \Rightarrow Embedded models for <u>Motion Prediction</u>

□ Main philosophy

Reasoning at the grid level as far as possible for both :

• *Improving efficiency* => *highly parallel processing*

• Avoiding traditional object level processing problems (e.g. detection errors, wrong data association...)




The "Dynamic Probabilistic Grids" paradigm

 \Rightarrow A more and more popular approach for Autonomous Vehicles \Rightarrow A clear distinction between Static & Dynamic & Free components

Pioneer concept of "Bayesian Occupancy Filter" (Inria)

[PhD Thesis Coué 2005] [Coué & Laugier IJRR 05] [Laugier et al ITSM 2011] [Laugier, Vasquez, Martinelli Mooc uTOP 2015]






Bayesian Occupancy Filter Approach – Main Features


=> Exploiting the Dynamic Information for a better understanding of the scene

- **\Box** Estimate **Spatial occupancy for each cell of the grid** *P* (*O* / *Z*)
- □ Grid update is performed in <u>each cell in parallel</u> (using BOF equations)
- **Extract Motion Field** (using Bayesian filtering & Fused Sensor data)
- **Reason at the Grid level** (*i.e. no object segmentation at this reasoning level*)



Sensors data fusion + Bayesian Filtering + Extracted Motion Fields

HSBOF 1st Embedded & Optimized version (patent 2014)




 $P(O'_{c}, A'_{c})$



Experimental Results in dense Urban Environments



Observed Urban Traffic scene



Ego Vehicle (not visible in the video)

OG Left Lidar

OG Right Lidar

OG Fusion + Velocity Fields



Patented Improvements & Implementations

=> Several models & implementations more and more adapted to **Embedded constraints & Scene complexity**

✤ Hybrid Sampling Bayesian Occupancy Filter (HSBOF, patent 2014)

=> Drastic memory size reduction (factor 100) + Increased efficiency (complex scenes)

+ More accurate Velocity estimation (using Particles & Motion data from ego-vehicle)

Conditional Monte-Carlo Dense Occupancy Tracker (CMCDOT, 2015) [Rummelhard et al 15] => Increased efficiency using "state data" (Static, Dynamic, Empty, <u>Unknown</u>) + Integration of a "Dense **Occupancy Tracker**" (Object level, Using particles propagation & ID)


CMCDOT + Ground Estimator (Patent 2017)

=> Ground shape estimation & Improve obstacle detection => Avoid false detections on the ground surface

Ground Estimation & Point Cloud Classification (2017)


erv-high Obstacles





[Rummelhard et al 17]

[Negre et al 14] [Rummelhard et al 14]







System Integration on a commercial vehicle (2018)



- POC 2018: Complete system implemented on Nvidia TX1, and easily connected to the shuttle system network in a few days (using ROS)
- Shuttle sensors data has been fused and processed in real-time, with a successful Detection & Characterization of the Moving & Static Obstacles
- Full integration on a commercial product under development with an industrial company (confidential)










Paradigm 2: Risk Assessment & Decision-making => Decision-making for avoiding Pending & Future Collisions

Human Aware Situation

Assessment

Risk-Based Decision-making

=> Safest maneuver to execute



□ Main challenges

Uncertainty, Partial Knowledge, World changes, Real time Human in the loop + Unexpected events

□ Approach: Prediction + Risk Assessment + Bayesian Decision-making

- ✓ Reason about Uncertainty & Contextual Knowledge (using History & Prediction)
- ✓ Estimate <u>Probabilistic Collision Risk</u> at a given time horizon $t+\delta$ ($\delta = a$ few seconds)
- ✓ Make <u>Driving Decisions</u> by taking into account the Predicted behavior of <u>all the observed surrounding traffic</u> <u>participants</u> (cars, cycles, pedestrians ...) & Social / Traffic rules

Two levels of collision risk have to be considered

- ✓ *Short-term collision risk* => *Imminent collisions, time horizon <3s, conservative hypotheses*
- ✓ *Long-term collision risk* => *Future potential collisions, context & semantics, behavior models*

Concept 1: Short-term collision risk – **Basic idea**

How to deal with unexpected events ? => Exploit previous observations for anticipating a potential future collision

Autonomous Vehicle (Cycab)



Parked Vehicle (occultation)

Pioneer Results (2005)

[PhD Thesis C. Coué 2004] [Coué & Laugier IJRR 05]

Thanks to the prediction capability of the BOF technology, the Autonomous Vehicle "anticipates" the pedestrian motion and brakes *(even if the pedestrian is temporarily hidden by the parked vehicle)*

Short-term collision risk – *Main features*

=> Grid level & Conservative motion hypotheses (proximity perception)

Main Features

- Detect "Risky Situations" a few seconds ahead (3-5s)
- Risky situations are both localized in Space & Time
 - *⇒ Conservative Motion Prediction in the grid (Particles & Occupancy)*
 - \Rightarrow *Collision checking* with *Car model* (shape & velocity) for <u>every future time steps</u> (horizon h)
- o Resulting information can be used for choosing Avoidance Maneuvers

System output (real time)



Short-term collision risk – *Experimental results*

 \Rightarrow Detect potential upcoming collisions \Rightarrow Reduce drastically false alarms







Short-term collision risk – *Experimental results (video)*

CMCDOT – Collision Risk Assessment (video – 0:45)

- **Yellow** => *time to collision: 3s*
- **Orange** => *time to collision: 2s*
- **Red** => time to collision: 1s



Concept 2: Long-term Risk Assessment (Object level) => Increasing time horizon & complexity using context & semantics => Key concepts: Behaviors Modeling & Prediction + Interactions

Decision-making in complex traffic situations


- ✓ *Understand* the current traffic situation & its *likely evolution*
- ✓ Evaluate the **Risk of future collision** by reasoning on traffic participants **Behaviors**
- ✓ Takes into account Context & Semantics

Context & Semantics History + Space geometry + Traffic rules + Behavior Prediction & Interactions For all surrounding traffic participants + Probabilistic Risk Assessment

Highly structured environment + Traffic rules => Prediction more easy

Behavior-based Collision risk (Object level) Approach 1: Trajectories Prediction & Collision Risk Estimation


Patent Inria & Toyota & Probayes 2010 + [Tay thesis 2009] [Laugier et al 2011]



Experimental results: *Prediction Approach 1 – Highways*




Behavior Prediction & Risk Assessment on highway Video (Courtesy Probayes)



Behavior-based Collision risk (Object level)

Approach 2: Intention & Expectation Comparison =>Interdependent behaviors & Mixed Traffic




[Lefevre thesis 13] [Lefevre & Laugier IV'12, Best student paper]

Patent Inria & Renault 2012 (risk assessment at road intersection) Patent Inria & Berkeley 2013 (postponing decisions for safer results)




A Human-like reasoning paradigm => Detect Drivers Errors & Colliding behaviors

- ✓ Estimating "Drivers Intentions" from <u>Vehicles States Observations (X Y θ S TS) => Embedded Perception and/or V2X</u>
- ✓ Inferring "Behaviors Expectations" from <u>Drivers Intentions & Traffic rules</u>
- ✓ *Risk* = Comparing Maneuvers Intention & Expectation
 - => Taking traffic context into account (Topology, Geometry, Priority rules, Vehicles states)
 - => Digital map obtained using "Open Street Map"



Experimental results: Approach 2 – Road intersection & Mixed traffic










Experimental Vehicles & Connected Perception Units



Connected Perception Unit (infrastructure)


Same embedded perception systems than in vehicles => Exchanging only Collision Risk information





Experimental Areas

□ **Protected experimental area** => *Testing Autonomous Driving L3 & L4*



□ Open real traffic (Urban & Highway) => *Testing Autonomous Driving L2 (ADAS)*







Distributed Bayesian Perception (using V2X)




□ Data exchange & Synchronization




Experimental platform



Distributed Bayesian Perception – *Experimental results*





NANDELEC.



On going work

□ Perception + Decision-making + Control integration



Autonomous Shuttles (~15 km/h)




Autonomous Bus (Iveco) (up to 70 km/h, Urban traffic)



Autonomous Renault Zoe (up to 70 km/h, Urban traffic)


- Various Dynamics & Motion constraints & Contexts
- Adapted "Collision Risk" & "Collision avoidance maneuvers" (Risk & Maneuver characterization)
- Cooperation IRT Nanoelec, Renault, Iveco ...

□ Models enrichment using Semantic Segmentation & Deep Learning



- "Semantic Grids" concept
- Improved scene understanding & decision-making
- Cooperation Toyota
- 1 Patent & 2 publications (IROS'18, ICARCV'18)

□ Learning Driving Skills (Prediction & Planning) for Autonomous Driving



- Driver Behavior modeling using Driving dataset & Inverse Reinforcement Learning => Human-like Driver Model (for mixed traffic)
- Motion Prediction & Driving Decision-making for AD performed by combining "learned Driver models" & "Dynamic evidences"
- Cooperation Toyota
- 2 Patents & 3 publications (ITSC 2016, ICRA 2017, ICRA 2018) & PhD Thesis 2019

Start-up incubation – *Innovative concept for micro mobility*



WE PROVIDE URBAN MICRO MOBILITY SERVICES AT THE CITIZENS' FRONT DOOR WITH ON DEMAND AUTONOMOUS ELECTRIC LIGHT VEHICLES.

A FREE FLOATING SOLUTION THAT MAKES SENSE

•

/ ON DEMAND DOOR TO DOOR MOBILITY SERVICE
/ NO RANDOM & UNCONTROLLED PARKING
/ AUTONOMOUS DISPATCH & CHARGING
/ LOW OPERATING COSTS
/ REAL TIME SPEED LIMITATIONS
/ ZERO EMISSION SOLUTION

READY TO OPEN A NEW ERA FOR THE FIRST & LAST MILE

nnía PARTNERSHIP PROGRAM **AUTONOMOUS** FUNCTIONALITY **UDELEC** cea ENVIRONMENT DETECTION Schneider MOTOR CONTROL & ENERGY MANAGEMENT


Confidential Property of Schneider Electric

2

Interested in partnering with us? Contact david.gualino@se.com

Start-up incubation – *Key Features*

Start-up incubation – Ney realities	
// VALUE PROPOSITION	STARlink
STARLINK provides urban micro mobility services at the citizens' front door with on demand autonomous electric light vehicles.	
STARLINK's technology makes mobility operators' life easier and optimize their rev	enues.
STARLINK's concept provides a clear contribution to environmental issues for better places to live.	
Confidential Property of Schneider Electric	





Thank You - Any questions ?

<text><text><text><text>



IEEE RAS Technical Committee on "AGV & ITS" Numerous Workshops & Special issues since 2002 !! Membership open !! Chapman & Hall/CRC Machine Learning & Pattern Recognition Series

BAYESIAN PROGRAMMING



PIERRE BESSIËRE EMMANUEL MAZER JUAN-MANUEL MHUACTZIN KAMEL MEKHNACHA

Chapman & , Hall / CRC, Dec. 2013

NANDELEC.

