



8th Workshop on Planning, Perception and Navigation for Intelligent Vehicles
A bridge between Robotics and ITS technologies

Sensor based navigation

Philippe Martinet

Professor at Ecole Centrale of Nantes

Co-authors: G. Garcia, S. Dominguez Quijada, O. Kermorgant

November 1st, 2016

Rio de Janeiro, Brazil



Content

- **Introduction**
- Generic models for cameras
- Visual geometry for localization
- Topological navigation system
- Illustrations
- Conclusion

From LASMEA, IRCCyN to LS2N

Prof. ECN
IRCCyN (11-16)
Robotics

Prof. ECN
LS2N (1/1/17)
ARMEN



Ass. Prof. CUST
LASMEA (90-00)
GRAVIR/CSR

Prof. IFMA
LASMEA (00-11)
GRAVIR/ROSACE

ARMEN: Research Areas

Leaders: S. Briot (CNRS Researcher), P. Martinet (Pr)

V. Begoc (A.P.), S. Briot (Researcher), A. Chriette (A.P.), G. Garcia (A.P.), O. Kermorgant (A.P.), P. Martinet (Pr)

S. Dominguez (RE), X. Koreki (RE), 9 Phds, 9 masters

- **Robot Design and Environments**

- *Conceptual Design*
- *Robust Design*
- *Control-based Design*
- *Design using new materials*
- *Reduction of energy consumption*



- **Robot Interactions with the environment**


- *Multi-Sensor Based Control*
- *Control of reconfigurable Systems*
- *Autonomous Robots*

- **Robot Perception of the environment**

- *Multi robots and multisensor perception*
- *Optimal Perception*
- *Observers and identification*

Sensor based control: History

[ESPIAU87]



Lateral control in cartesian space:

Bringing $(\tilde{y}, \tilde{\theta})$ to $(0, 0)$

Explicite declaration of Δ and required cartesian localization


Lateral control in sensor space:

Bringing d to d^*


No explicite declaration of Δ and not required cartesian localization

Sensor based control: Basic concepts


[SAMSON90,ESPIAU92]



$$\mathbf{s} = \mathbf{s}(\mathbf{x}, t)$$



Interaction matrix




\mathbf{x} : 3D pose

If (fixed object) $\frac{\partial \mathbf{s}}{\partial t} = 0$

$$\dot{\mathbf{s}} = \frac{\partial \mathbf{s}}{\partial \mathbf{x}} \frac{d\mathbf{x}}{dt} + \frac{\partial \mathbf{s}}{\partial t}$$

$$\dot{\mathbf{s}} = \mathbf{L}_s \mathbf{v} + \frac{\partial \mathbf{s}}{\partial t}$$



$$\dot{\mathbf{s}} = \mathbf{L}_s \mathbf{v}$$

Sensor/Vision based control: Basic bibliography

Book, Book Chapter

Robot Control: Task function approach [C. Samson, M. Le Borgne, B. Espiau, Clarendon Press, 1991]

Visual servoing [K. Hashimoto 1993]

Robotics Handbook : Chapter 24 Visual Servoing and Visual Tracking [Chaumette, Hutchinson 2008]

Robotics: Modelling, Planning and Control chapter 10 Visual servoing [Siciliano, B., Sciavicco, L., Villani, L., Oriolo, G. 2009]

Visual Servoing via Advanced Numerical Methods [G. Chesi, K. Hashimoto 2010]

Robotics, Vision and Control : Fundamental Algorithms in MATLAB [Corke, Peter, 2011]

Tutorials, workshop

Tutorial on visual servoing, S. Hutchinson, G. Hager, P.I. Corke, 1996, Tutorial at ICRA, Minneapolis, Minnesota, USA

IROS 2004 Tutorial on Advanced Visual Servoing , P. Martinet, E. Cervera, F. Chaumette, E. Malis, K. Hashimoto, 2004, Tutorial at IROS, Sendai, Japan

IROS 2002 Workshop on Visual Servoing , P. Martinet, E. Cervera, N. Andreff, F. Chaumette, 2002, Workshop at IROS, Lausanne, Switzerland

Visual servo control : Part I Classical Approaches, S. Hutchinson, F. Chaumette, 2006, RAS Magazine

Visual servo control : Part II Classical Approaches, F. Chaumette, S. Hutchinson, 2007, RAS Magazine

Fundamental article (Citations : 1681 (october 2016))

A new approach to visual servoing in robotics. B. Espiau, F. Chaumette, P. Rives. IEEE Trans. on Robotics and Automation, 8(3):313-326, 1992

Toolboxes

Visual Servoing Toolbox, E. Cervera and P. Martinet, 2003, Matlab Toolbox, Spain and France

VISP, E. Marchand, 2008, France

Robotics Toolbox, P.I. Corke, 2011, Matlab Toolbox, Australia

Machine Vision Toolbox, P.I. Corke, 2011, Matlab Toolbox, Australia

Many authors in robotics, Few authors in ITS

Sensor/Vision based control: Basic approaches

Image Based Visual Servoing IBVS

- 2D Features are extracted from images (Points, lines, shape, moments, ...)
- Photometric based features (Histogram, Entropy, ...)
- Information based (Mutual information, ...)

Position Based Visual servoing PBVS


- 3D features are estimated from 2D features (Pose, Point, Line, plane, shape...)
- 3D features are estimated from pixels (Pose, Point, Line, plane, shape...)
- 3D feaures are directly given by the sensor system

Hybrid Based Visual Servoing HBVS


- Combination of 3D features with 2D features (2.5D, Stereo, ...)
- Multi-sensors

Basically, a teaching by showing is often used in order to limit the impact of modeling errors

Navigation scheme




Navigation scheme




Navigation

3D Map based navigation (absolute navigation)




Navigation

Memory based navigation (relative navigation)



Navigation

Memory based navigation (relative navigation)



Content

- Introduction
- **Generic models for cameras**
- Visual geometry for localization
- Topological navigation system
- Illustrations
- Conclusion

Different kind of cameras

Pinhole
Camera




Catadioptric
systems




Camera with
fisheye lenses




A unified model for camera




Planar



Parabolic





Elliptical



Hyperbolic

*Single view point system :
Classification*


[Geyer00]




Log/polar retina




A unified model for camera




Planar



Parabolic



Elliptical




Hyperbolic

*Single view point system :
Classification*

[Geyer00]

φ and ξ : Mirror parameters

Mirror type	ξ	φ
Parabolic	1	$1+2p$
Hyperbolic	$\frac{d}{\sqrt{d^2+4p^2}}$	$\frac{d+2p}{\sqrt{d^2+4p^2}}$
Elliptical	$\frac{d}{\sqrt{d^2+4p^2}}$	$\frac{d-2p}{\sqrt{d^2+4p^2}}$
Planar	0	1
Conventional	0	1

A unified model for camera*Single view point system : case of point* φ and ξ : Mirror parameters

Special cases :

- $\epsilon_1 = 1$ and $\xi = 0$ → perspective projection
 $\epsilon_1 = 0$ and $\xi = 1$ → spherical projection

$$\mathbf{M} = \begin{bmatrix} \varphi - \xi & 0 & 0 \\ 0 & \varphi - \xi & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$\mathbf{K} = \begin{bmatrix} f & fs & u_0 \\ 0 & fr & v_0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$\mathbf{f}(\mathbf{m}_{3D}) = \begin{bmatrix} \frac{X}{\epsilon_1 Z + \xi \sqrt{X^2 + Y^2 + Z^2}} \\ \frac{Y}{\epsilon_1 Z + \xi \sqrt{X^2 + Y^2 + Z^2}} \\ 1 \end{bmatrix}$$

Generic Projection function

$$\mathbf{m}_p = \mathbf{K} \mathbf{M} \mathbf{f}(\mathbf{m}_{3D})$$

Case of fisheye camera***Fisheye camera model : definition***

★ r = distance between X and the image point

★ θ = angle between the incoming ray and the principal axis

★ \mathcal{F}_m : camera frame

★ \mathcal{F}_i : image frame

Pinhole camera


$$\mathbf{x}_p = (x_p \quad y_p)^T$$

$$r_p(\theta) = f \tan \theta$$

$$\mathbf{X} = (X \ Y \ Z)^T$$

Fisheye camera

$$\mathbf{x}_f = (x_f \quad y_f)^T$$



radial distortions

Constraint 1 *the ray arriving along the distortion axis is not deformed: $r_f(0) = 0$.*

Constraint 2 *the radius $r_f(k)$ is monotonically increasing for $k > 0$.*

Case of fisheye camera

Fisheye camera model

Pinhole based models

Mapping :

$$r_p \xrightarrow{T_1} r_f$$

[T. Pajdla97,Hartley00,Zhang98,Ma2006...]

[Fitzgibbon01] [Li05] [Basu95] [Devernay01] [Hartley07]

Captured rays based models

Mapping:

$$\theta \xrightarrow{T_2} r_f$$

[Kingslake89] [Fleck94, Stevenson95] [Ray94] [Smith92]

[xiong97,kannala04,schwalbe05,Scaramuzza06] [Kumler00] [Bakstein02]

Case of fisheye camera**For fisheye camera**

[Courbon07]

$$r_f = r_f(r_p) = \frac{\frac{f_f}{f_p} r_p}{1 + \xi \sqrt{\frac{r_p^2}{f_p^2} + 1}}$$

is a T_1 -mapping linking the perspective Radius r_p and the fisheye radius r_f

Constraint 1 : easily verified ($r_f(0) = 0$)

Constraint 2 : $r_f(k)$ is monotonically increasing for $k > 0$

$$r_f = r_f(\theta) = \frac{f_f \tan \theta}{1 + \xi \sqrt{\tan^2 \theta + 1}}$$

is a T_2 -mapping linking the radius r_f and the incidence angle θ




The generic camera model is candidate
for fisheye camera modeling

Case of fisheye camera an Enhanced Unified Model

Unified Model

$$\mathbf{m} = \begin{pmatrix} x_m \\ y_m \\ 1 \end{pmatrix} = \begin{pmatrix} x \\ \frac{x}{z + \xi\rho} \\ \frac{y}{z + \xi\rho} \\ 1 \end{pmatrix}$$



Enhanced Unified Model

$$\mathbf{m} = \begin{pmatrix} \frac{x}{\alpha\rho + (1 - \alpha)z} \\ \frac{y}{\alpha\rho + (1 - \alpha)z} \\ 1 \end{pmatrix}$$

$$\rho = \sqrt{x^2 + y^2 + z^2}$$

ξ is a projection parameter

$$\rho = \sqrt{\beta(x^2 + y^2) + z^2}$$

$$K = \begin{pmatrix} f_u & 0 & u_0 \\ 0 & f_v & v_0 \end{pmatrix}$$


[MEI07, Courbon07-12]

$$\mathbf{p} = K\mathbf{m}$$

[Khomutenko RA-L16]

Case of fisheye camera an Enhanced Unified Model

Projection surface



If every projected point can be written as:

$$\mathbf{m} = \left(\frac{x}{\eta(\mathbf{X})} \quad \frac{y}{\eta(\mathbf{X})} \quad 1 \right)^T$$

$\eta : \mathbb{R}^3 \rightarrow \mathbb{R}_+$ is homogeneous of degree 1

The projection surface P is defined by:

$$\eta(\mathbf{X}) = 1$$

All the points like $\mathbf{X}_p = \frac{\mathbf{X}}{\eta(\mathbf{X})}$ belong to the projection surface:

$$\eta(\mathbf{X}_p) = \eta\left(\frac{\mathbf{X}}{\eta(\mathbf{X})}\right) = \frac{\eta(\mathbf{X})}{\eta(\mathbf{X})} = 1$$

For the Enhanced Unified Model:

$$\eta = \frac{\gamma}{\sqrt{(1-\alpha)z + \alpha\sqrt{\beta(x^2 + y^2) + z^2}}}$$

Let us define the inversion g of the projection f so that:

$$f(g(\mathbf{m})) = \mathbf{m}$$

The following mapping would transform \mathbf{m} into \mathbf{X}_p :

$$g : \begin{pmatrix} x \\ y \\ 1 \end{pmatrix} \mapsto \begin{pmatrix} x \\ y \\ z(x, y) \end{pmatrix}$$

The inverse mapping is: $\begin{aligned} z &= \frac{1 - \alpha^2 \beta r^2}{\alpha \sqrt{1 - (\alpha - \gamma) \beta r^2} + \gamma} \\ r^2 &= x^2 + y^2 \end{aligned}$

Content

- Introduction
- Generic models for cameras
- **Visual geometry for localization**
- Topological navigation system
- Illustrations
- Conclusion

Partial euclidian reconstruction Unified model - Case of points

s=sign(Z)

Introducing $\eta = s \frac{\rho}{|Z|} = \sqrt{1 + X^2/Z^2 + Y^2/Z^2} > 0$

$$\begin{cases} x = \frac{X/Z}{1+\xi\eta} \\ y = \frac{Y/Z}{1+\xi\eta} \end{cases} \quad \begin{cases} (1 + \xi\eta) x = \frac{X}{Z} \\ (1 + \xi\eta) y = \frac{Y}{Z} \end{cases} \quad \begin{cases} \eta^2 - (x^2 + y^2)(1 + \xi\eta)^2 - 1 = \end{cases}$$

$$\eta = \frac{\pm \gamma_x + \xi(x^2 + y^2)}{1 - \xi^2(x^2 + y^2)}$$

 η computed without ambiguity

where $\gamma_x = \sqrt{1 + (1 - \xi^2)(x^2 + y^2)}$


$$\mathbf{m}_m = (\eta^{-1} + \xi) \overline{\mathbf{m}} \quad \text{with} \quad \overline{\mathbf{m}} = [x \ y \ \frac{1}{1+\xi\eta}]^T$$

$\overrightarrow{\mathbf{m}}$
 m_n

Partial euclidian reconstruction Unified model - Case of points

$[X \ Y \ Z]^T$ m coordinates in \mathcal{F}_m

$[X^* \ Y^* \ Z^*]^T$ m coordinates in \mathcal{F}_m^*



Partial euclidian reconstruction Unified model - Case of points

$$\underline{\mathbf{m}}_m = (\eta^{-1} + \xi) \overline{\mathbf{m}} = \frac{1}{\rho} [\begin{array}{ccc} X & Y & Z \end{array}]^T$$

$$\overline{\mathbf{m}} = [x \ y \ \frac{1}{1+\xi\eta}]^T$$

$$\underline{\mathbf{m}}_m^* = (\eta^{*-1} + \xi) \overline{\mathbf{m}}^* = \frac{1}{\rho^*} [\begin{array}{ccc} X^* & Y^* & Z^* \end{array}]^T$$

$$\overline{\mathbf{m}}^* = [x^* \ y^* \ \frac{1}{1+\xi\eta^*}]^T$$

Homogeneous coordinates:

$$\underline{\mathbf{m}} = [X \ Y \ Z \ H]^T \text{ and } \underline{\mathbf{m}}^* = [X^* \ Y^* \ Z^* \ H^*]^T$$

$$\rho(\eta^{-1} + \xi) \overline{\mathbf{m}} = [\begin{array}{cc} \mathbf{I}_3 & 0 \end{array}] \underline{\mathbf{m}} = [\begin{array}{cc} \mathbf{R} & \mathbf{t} \end{array}] \underline{\mathbf{m}}^*$$

The distance from the world point m to the plane (π)

$$d(m, \pi) = \pi^{*T} \cdot \underline{\mathbf{m}}^* = [\mathbf{n}^{*T} \ - d^*] [X^* \ Y^* \ Z^* \ H^*]^T = \rho^*(\eta^{*-1} + \xi) \mathbf{n}^{*T} \overline{\mathbf{m}}^* - d^* H^*$$

Partial euclidian reconstruction Unified model - Case of points

$$\rightarrow H^* = \frac{\rho^*(\eta^{*-1} + \xi)}{d^*} \mathbf{n}^{*T} \overline{\mathbf{m}}^* - \frac{d(m, \pi)}{d^*}$$

$$\rho^*(\eta^{*-1} + \xi) \overline{\mathbf{m}}^* = [X^* \ Y^* \ Z^*]^T$$

$$\underline{\mathbf{m}}^* = \rho^*(\eta^{*-1} + \xi) \mathbf{A}_\pi^* \overline{\mathbf{m}}^* + \mathbf{b}_\pi^*$$

where $\begin{cases} \mathbf{A}_\pi^* = \left[\mathbf{I}_3 \ \frac{\mathbf{n}^*}{d^*} \right]^T \\ \mathbf{b}_\pi^* = \left[\mathbf{0}_{1 \times 3} \ - \frac{d(m, \pi)}{d^*} \right] \end{cases}$

$$\rho(\eta^{-1} + \xi) \overline{\mathbf{m}} = [\mathbf{R} \ \mathbf{t}] \underline{\mathbf{m}}^*$$

$$\rho(\eta^{-1} + \xi) \overline{\mathbf{m}} = \rho^*(\eta^{*-1} + \xi) \mathbf{H}_\pi \overline{\mathbf{m}}^* + \alpha \mathbf{t}$$

with $\mathbf{H}_\pi = \mathbf{R} + \frac{\mathbf{t}}{d^*} \mathbf{n}^{*T}$ and $\alpha = -\frac{d(m, \pi)}{d^*}$

Euclidian Homography

Partial euclidian reconstruction

Unified model - Case of points


$$m \in \pi$$

$$\bar{m} = \beta_{x,x^*} H_\pi \bar{m}^*$$

where $\beta_{x,x^*} = \frac{\eta^{*-1} + \xi}{\eta^{-1} + \xi} \frac{\rho^*}{\rho}$

Linear form

$$\bar{m} \times H_\pi \bar{m}^* = 0$$



$$H_\pi$$

$$R$$


$$\text{and } t_{d^*} = \frac{t}{d^*}$$

$$\sigma = \frac{\rho}{\rho^*} = (1 + \mathbf{n}^{*T} \mathbf{R}^T \mathbf{t}_{d^*}) \frac{(\eta^{*-1} + \xi) n^{*T} \bar{m}^*}{(\eta^{-1} + \xi) n^{*T} \mathbf{R}^T \bar{m}}$$

Partial euclidian reconstruction

Unified model - Case of lines

Similar results are obtained from lines (*using polar lines*)



Plücker coordinates

$$L = (\underline{u}, \underline{h}, h)^T$$

\underline{u} : unitary vector along the line L

\underline{h} : unitary vector orthogonal to the interpretation plane

h : distance between the origin of the frame and the line

$$\frac{A_0}{A_5}x^2 + \frac{A_1}{A_5}y^2 + 2\frac{A_2}{A_5}xy + 2\frac{A_3}{A_5}x + 2\frac{A_4}{A_5}y + 1 = 0$$


$$B_i(\underline{h}, \xi, K_M) = \frac{A_i}{A_5}$$

Partial euclidian reconstruction

Unified model - Case of lines

Similar results are obtained from lines (*using polar lines*)

Polar lines



ϕ a 2D conic curve

A a point in the definition plane of ϕ

l_i : the corresponding polar line

$$l_i \propto \Phi A$$


Polar line l

Partial euclidian reconstruction

Unified model - Case of lines
 Similar results are obtained from lines *(using polar lines)*
 Polar lines

$$\Omega = \begin{pmatrix} h_x^2 - \xi^2(1-h_y^2) & h_x h_y (1-\xi^2) & h_x h_z \\ h_x h_y (1-\xi^2) & h_y^2 - \xi^2(1-h_x^2) & h_y h_z \\ h_x h_z & h_y h_z & h_z^2 \end{pmatrix}$$

$$\underbrace{\underline{x}_i^T K^{-T} \Omega K^{-1} \underline{x}_i}_{\Omega_i} = 0$$



The polar line of the optical center with respect to the conic Ω_i is given by:


$$l_i \propto \Omega_i O_i$$

principal point

$$O_i = [u_0 \ v_0 \ 1]^T = K[0 \ 0 \ 1]^T$$

Partial euclidian reconstruction

Similar results are obtained from lines *(using polar lines)*




Corollary:

$$\begin{aligned} l_i &\propto K^{-T} \Omega K^{-1} O_i \\ &\propto K^{-T} \Omega K^{-1} K \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix} \\ &\propto K^{-T} \begin{pmatrix} h_x \\ h_y \\ h_z \end{pmatrix} \end{aligned}$$

The polar line l_i computed from the physical conic curve projection of L in the omnidirectional image is the perspective projection of L into the virtual camera image plane.

Partial euclidian reconstruction

Similar results are obtained from lines (*using polar lines*)



Unified model - Case of lines

$[\underline{u}, \underline{h}, h]$ L coordinates in \mathcal{F}_m
 $[\underline{u}^*, \underline{h}^*, h^*]$ L coordinates in \mathcal{F}_m^*

Reference plane π in \mathcal{F}_m^*

$$\pi^{*T} = [\mathbf{n}^{*T} \quad -d^*]$$

Partial euclidian reconstruction

Unified model - Case of lines

Similar results are obtained from lines (*using polar lines*)

\mathcal{X}_1 and \mathcal{X}_2 are two points in the 3D space lying on the line \mathcal{L}

$$\underline{h} \propto H^{-T} \underline{h}^*$$

$$l_i \propto K^{-T} \underline{h} \quad \longrightarrow \quad l_i \propto K^{-T} H^{-T} \underline{h}^*$$

$$l_i^* \propto K^{-T} \underline{h}^* \quad \longrightarrow \quad l_i \propto K^{-T} H^{-T} K^T l_i^*$$

$$l_i \propto G^{-T} l_i^*$$

$$G = KHK^{-1}$$

Linear form

$$l_i \times G^{-T} l_i^* = 0$$

with 4 couples (l_i, l_i^*)


$$\longrightarrow H \longrightarrow R$$


$$H = R + \frac{t}{d^*} n^{*T}$$

$$r = \frac{h}{h^*} = (1 + t_d^{*T} R^T n^*) \frac{\|n^* \times K^T l_i^*\|}{\|R n^* \times K^T l_i\|}$$

Content


- Introduction
- Generic models for cameras
- Visual geometry for localization
- **Topological navigation system**
- Illustrations
- Conclusion

Global system


Global system**Supervised learning step: building of the sensory memory**

Different modules**Learning step (first arc, first two nodes)**

Key images selection





Building the sensory memory



Different modules

Learning step (expanding the processus...)




Global system**Initialization: primary localization**

Differents modules


Initial localization

How to find the closest image in the database ?



Differents modules**Initial localization**

How to find the closest image in the database ?




Differents modules**Initial localization**


How to find the closest image in the database ?

Use of a regular mesh [PERSSON04]
Cubic interpolation of the image surface

Global descriptor : vector of the interpolated grey level pixels at the position of the control point



Control point distribution (one example)



Differents modules

Initial localization

How to find the closest image in the database ?

Local descriptor : interest points detected by Harris Stephen detector

Use of patches 11x11




Matching done by using the centered cross correlation score ZNCC

Use of the number of matched point to compute the similarity between 2 images


Differents modules**Initial localization**

How to find the closest image in the database ?

Evaluation of the approach [ICRA08] using three image databases regarding 3 main criteria:
 Used memory size, percentage of success, computation time for localization


Caméra	Taille image	Nb images	Images
Catadioptrique	1024×768	978	
Fisheye 110 deg	384×288	188	
Fisheye 190 deg	640×480	445	

Several approaches were compared : GONZ [GONZALES02], PHLAC [LINAKE04], CUB, SURF, SIFT, HARRIS, CUBHAR

Global system**One line navigation and control**


Differents modules**Planifying the visual route**

How to find the optimal path ?




Differents modules**Planifying the visual route**


How to find the optimal path ?



Differents modules**Planifying the visual route**

How to find the optimal path ?



Differents modules**Scaled euclidian reconstruction****One line localization**

[Nister04]

From five couples of points
E can be estimated

Epipolar constraint can be expressed by :

$$X_m^T R(t \times X_m^{*T}) = X_m^T R [t]_{\times} X_m^{*T} = 0$$


For pinhole model $X_m^T E X_m^{*T} = 0$

Outliers are rejected by
using RANSAC

Differents modules**State estimation and control (one example)**

State model of the mobile robot

$$(s, y, \theta)$$



- ★ $\mathcal{F}_i = (O_i, X_i, Y_i, Z_i)$
- ★ $\mathcal{F}_{i+1} = (O_{i+1}, X_{i+1}, Y_{i+1}, Z_{i+1})$ the frames attached to the robot when I_i

Kinematic model of the mobile robot


$$\begin{cases} \dot{s} = \frac{V \cos \theta}{1 - yc(s)} \\ \dot{y} = V \sin \theta \\ \dot{\theta} = \omega - \frac{Vc(s) \cos \theta}{1 - yc(s)} \end{cases}$$

Chained
System
theory
[IAV04]

Differents modules

State estimation and control (one example)


Path following approach



Goal: $y \rightarrow 0, \theta \rightarrow 0$ before \mathcal{F}_c reaches \mathcal{F}_{i+1}

Asymptotically stable guidance control law based on the chain system approach:

$$\delta(y, \theta) = \arctan \left(-l \left[\cos^3 \theta (-K_d \tan \theta - K_p y) \right] \right)$$

Case of vision

Case of vision**Topological map level 0 (CT₀)**


- ✓ High level representation : corridor, routes, ..

Topological map level 1 (CT₁)


- ✓ Image network representation
- ✓ Navigability
- ✓ Commandability
- ✓ Plannification

Sensory map (CS)

- ✓ Initial localization
- ✓ Sensor based control
- ✓ Visualization of the environment
- ✓ Human interface


Sensory memory


SOVIN A global software environment for topological navigation in wide spaces



SOVIN


A physical database organized in three levels






SOVIN

A generic library (generic visual sensor) for visual algorithm processing
 [Courbon 2008]




An efficient Human Machine Interface for managing applications

[Courbon 2008]



Content

- Introduction
- Generic models for cameras
- Visual geometry for localization
- Topological navigation system
- **Illustrations**
- Conclusion

Applications and projects in LASMEA***AGV using visual memory***

Indoor applications : WACIF project (2002-2005)



RNCiel
logiciel



Autonomous Robot for Telepresence navigation, localization, learning, warning and communication capabilities

- **Study and development of a demonstrator** like a personal robot fully integrated in the context of « wireless home »
- **An innovant domotic HMI** dedicated for software useful for human, family and home applications



Wireless communication and services

- **Telepresence and telesurveillance tasks**
home supervision through any wireless point, abnormal event detection in family environment (intrusion, noise, ...)



Autonomous navigation strategy

Indoor applications : WACIF project (2002-2005)



RNCiel

Global navigation strategy

Topological representation

Predefined trajectory

Graph representation


Visual memory concept

Hypothesis : knowledge

HS = HOME Space

RS_i = Room Space i

$$HS = \sum_i RS_i$$



- Starting point
- Ending point

Topological representation step
is a part of the knowledge
we get from the
HOME environment

Indoor applications : WACIF project (2002-2005)



RNCiel



Global navigation strategy

Topological representation

Predefined trajectory

Graph representation

Visual memory concept



Predefined trajectory step
is totally supervised
using robot teleoperation

Indoor applications : WACIF project (2002-2005)



RNCiel



Global navigation strategy

Topological representation

Predefined trajectory

Graph representation

Visual memory concept



Graph representation step
is deduced from
the previous step

Indoor applications : WACIF project (2002-2005)



RNCiel



Global navigation strategy

Topological representation


Predefined trajectory

Graph representation

Visual memory concept



Along the teleoperated
trajectories a set of
key images is selected



Visual memory concept
is used for navigation

Indoor applications : WACIF project (2002-2005)



RNCiel

Global navigation strategy

Topological representation



Predefined trajectory

Graph representation

Visual memory concept

E : Ending point

S : Starting point



Indoor applications : WACIF project (2002-2005)



RNCiel

Global navigation strategy

Functional decomposition


Learning Off line

Define each ${}^i\Psi_j$: learn the trajectory

- ★ Robot teleoperation
- ★ Models features extraction and selection
- ★ Mosaic construction

Re-run of trajectory : On line

- ★ Extract the reference model from the visual route
- ★ Select and track models in current images
- ★ Localization in the mosaic
- ★ Lateral control of the non holonomic robot



Ait Ader [04]
Blanc [04]
Blanc [05]

Indoor applications : WACIF project (2002-2005)




RNCI
logiciel

Global navigation strategy

Functional decomposition

Ceiling images are used



Indoor applications : WACIF project (2002-2005)

Navigation using visual memory






Topological organised images database



Set of relay images



RNCtel




Indoor applications : OMNIBOT project

From omnidirectional vision to mobile robot control

Development of a complete perception and control approach
for mobile robot using omnidirectional vision

ROBÉA



Indoor applications : OMNIBOT project


From omnidirectional vision to mobile robot control

ROBÉA



Development of a complete perception and control approach for mobile robot using omnidirectional vision :

- ✓ *Sensor design and Calibration,*
- ✓ *Image processing and Visual servoing*





Indoor applications : OMNIBOT project



H. Hadj Abdelkader [05]

Navigation with omnidirectional visual memory :
[ICRA07]




Last key image
of the visual route

Indoor applications : OMNIBOT project

ROBÉA



Omnidirectional Visual Servoing from Polar Lines [Hadj 06]



Indoor applications : ROSACE project

General framework :

*Vision based memory
navigation strategy :*

3 steps :

1. Visual memory building


2. Localization into the visual memory

3. Navigation into the visual memory

Using a fisheye camera



First current image



Current image



Online step

Online and
Real-Time step



Control input

Indoor applications : ROSACE project

Using a fisheye camera




Localization


**Vision based memory
navigation strategy :**

Localization into the visual memory

- a- Global localization
- b- Selection of key images
- c- Relative pose computation



(y, θ) evaluation





Indoor applications : ROSACE project


Current Image



Desired Image



Using a fisheye camera



Global localisation (6.5s) 306 *matchings*
 Visual route (280 key images) – Matching mean=108

- ErrImageMax:longest distance between an image point and its position in desired image
- Errpoints:Mean distance between those points

When errImageMax reaches 20
 we decide to change key image

Indoor applications : ROSACE project

Using a fisheye camera



[Courbon08]

Indoor applications : ROSACE project

Using a fisheye camera



J. Courbon [07]

Automatic Guided Vehicles robot control using a fisheye lens

Autonomous navigation using a visual memory



Outdoor applications : MOBIVIP project

Visual memory


urban context
[Royer04]

Reference
Trajectory

and

Image features
(3D points)

Experimental data
Compiègne city center
(BODEGA/MOBIVIP)





Outdoor applications : MOBIVIP project

Perception

Localization using monocular camera

urban context
[Royer04]

Reference
Trajectory
and
localization



Key images
And
features

Current
images
and
features

Outdoor applications : MOBIVIP project**urban context*****Perception and control*****[Royer06]**

2006: Les Czeaux Campus CFd



2006: Inner city of Clermont-Fd

Outdoor applications : CITYVIP project

General framework :

*Vision based memory
navigation strategy :*


3 steps :

1. Visual memory building

2. Localization into the visual memory

3. Navigation into the visual memory

[ICRA09] urban context




Outdoor applications : CITYVIP project**[ICRA09] urban context**

Localization


**Vision based memory
navigation strategy :**

Localization into the visual memory

- a- Global localization
- b- Selection of key images
- c- Relative pose computation



(y, θ) evaluation



Outdoor applications : CITYVIP project

Testbed

Experimental robot is a Robucab from Robosoft

Algorithms are implemented in *C⁺⁺* language
on a laptop using RTAI-Linux OS with a
2GHz Centrino processor

Fujinon fisheye lens, mounted onto a
Marlin F131B camera

Field-of-view of 185 deg

Image resolution in the experiments was 800×600 pixels

Frame rate of 15fps

Longitudinal velocity V has been fixed to 1 ms^{-1}

K_p and K_d are tuned regarding a double pole located at value 0.3

[ICRA09] urban context




Outdoor applications : CITYVIP project

Experiment

Loop 1200 m - 35 edges

Navigation 1700m (26 minutes, 1400 keys images, 54 edges)


[ICRA09] urban context



Outdoor applications : CITYVIP project**[ICRA09] urban context*****Experiment***

Lateral error:
 - mean: 23 cm
 - standard deviation: 30 cm.

Navigation stops after
 1700m for security reasons
 (small number of matched
 points)



Outdoor applications : CITYVIP project

[ICRA09] urban context

Video


Topological
navigation
using
visual memory
Cityvip
Clermont-Fd 2008

Using vision only
Clermont-Ferrand
LASMEA-GRAVIR



Indoor applications : µdrone project**Flying robot
[IROS09]**

cea **list**



Indoor applications : µdrone project

Topological
navigation
using
visual memory

CEA 2009
Fontenay-aux-Roses

Using vision only
Clermont-Ferrand
LASMEA-GRAVIR


Flying robot
[IROS09]



Visual navigation of a quadrotor aerial vehicle

J.Courbon, Y.Mezouar
N.Guénard, P.Martinet



Applications and projects in IRCCyN/LS2N***AGV using sensory memory***

I-CAR project



Renault Fluence



Renault ZOE



HDK DEL2023DUB



LITTLE EBOX




Robotization and instrumentation
 Robust localization (Data fusion)
 Mapping, SLAM
 Autonomous navigation (topological)
 Pedestrian Detection and tracking
 Platooning
 Parking and complex maneuvers



robotex



Mapping strategy (ITSC15)




Memory : around 4Mo/km

Mapping strategy (ITSC15)

Superindex → sub-map → $i=1 \dots n$ **Sub-map index**
 Subindex → path point → $j=1 \dots N_i$ **Path point index**


“global path” EKF fusion (GPS+Odo)




Global Optimization

Localization (ITSC15)


Enhanced localization using multi-maps localization



ROS based architecture



Drive-by-wire kit



Autonomous Navigation (ITSC16)

Autonomous Navigation

I-CAR project (2012-2016)

IRCCyN

Ecole Centrale de Nantes

S. Dominguez Quijada, G. Garcia, X. Koreki, A. Hamon, P. Martinet

Content

- Introduction
- Generic models for cameras
- Visual geometry for localization
- Topological navigation system
- Illustrations
- Conclusion

Conclusion

- Defining control in sensor space (with associated semantic level)
- Avoiding accumulation of modeling errors
- Sensor based control is effective in mobile robotic
- Sensor based control is a good alternative to path planning
- Sensor based control allows to be more reactive in dynamic environment
- We need to work hard to show results in real world with long life learning ability, try and see, and make decision...