HAL
open science

On termination of Graph Rewriting Systems through language theory

Guillaume Bonfante, Miguel Couceiro

To cite this version:

Guillaume Bonfante, Miguel Couceiro. On termination of Graph Rewriting Systems through language theory. 2020. hal-02478696

HAL Id: hal-02478696

https://inria.hal.science/hal-02478696v1

Preprint submitted on 14 Feb 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On Termination of Graph Rewriting Systems through Language Theory

Guillaume Bonfante
University of Lorraine
LORIA, Nancy, France
guillaume.bonfante@univ-lorraine.fr

Miguel Couceiro
University of Lorraine
LORIA, Nancy, France
miguel.couceiro@loria.fr

Abstract

The termination issue we tackle is rooted in natural language processing where graph rewriting systems (GRS) may contain a large number of rules, often in the order of thousands. Decidable concepts thus become mandatory to verify the termination of such systems. The notion of graph rewriting consider does not make any assumption on the structure of graphs (they are not "term graphs", "port graphs" nor drags). The lack of algebraic structure in our setting led us to proposing two orders on graphs inspired from language theory: the matrix multiset-path order and the rational embedding order. We show that both are stable by context, which we then use to obtain the main contribution of the paper: under a suitable notion of "interpretation", a GRS is terminating if and only if it is compatible with an interpretation.

2012 ACM Subject Classification Theory of computation → Rewrite systems

Keywords and phrases Graph Rewriting, Termination, Orders, Natural Language Processing

Digital Object Identifier 10.4230/LIPIcs...

1 Introduction

Computer linguists rediscovered few years ago that graph rewriting is a good model of computation for rule-based systems. They used traditionally terms, see for instance Chomsky's Syntagmatic Structures [3]. But usual phenomena such as anaphora do not fit really well within such theories. In such situations, graphs behave much better. For examples of graph rewriting in natural language processing, we refer the reader to the parsing procedure by Guillaume and Perrier [12] or the word ordering modeling by Kahane and Lareau [14]. The first named author with Guillaume and Perrier designed a graph rewriting model called GREW [2] that is adapted to natural language processing.

The rewriting systems developed by the linguists often contain a huge number of rules, e.g., those synthesized from lexicons (e.g. some rules only apply to transitive verbs). For instance, in [12], several systems are presented, some with more than a thousand of rules. Verifying properties such as termination by hand thus becomes intractable. This fact motivates our framework for tackling the problem of GRS termination.

Following the tracks of term rewriting, for which the definition is essentially fixed by the algebraic structure of terms, many approaches to graph rewriting emerged in past years. Some definitions (here meaning semantics) are based on a categorical framework, e.g., the double pushout (DPO) and the single pushout (SPO) models, see [21]. To make use of algebraic potential, some authors make some, possibly weak, hypothesis on graph structures, see for instance the main contribution by Courcelle and Engelfriet [4] where graph decompositions, graph operations and transformations are described in terms of monadic second-order logics

© Guillaume Bonfante and Miguel Couceiro;
licensed under Creative Commons License CC-BY

(with the underlying decidability/complexity results). In this spirit, Ogawa describes a graph algebra under a limited tree-width condition [18].

Another line of research follows from the seminal work by Lafont [15] on interaction nets. The latter are graphs where nodes have some extra structure: nodes have a label related to some arity and co-arity. Moreover, nodes have some "principal gates" (ports) and rules are actionned via them. One of the main results by Lafont is that rewriting in this setting is (strongly) confluent. This approach has been enriched by Fernandez, Kirchner and Pinaud [11], who implemented a fully operational system called PORGY with strategies and related semantics. Also, it is worth mentionning the graph rewriting as described by Dershowitz and Jouannaud [8]. Here, graphs are seen as a generalization of terms: symbols have a (fixed) arity, graphs are connected via some sprouts/variables as terms do. With such a setting, a good deal of term rewriting theory also applies to graphs.

Let us come back to the initial problem: termination of graph rewriting systems in the context of natural language processing. We already mentioned that rule sets are large, which making manual inspection impossible. Moreover, empirical studies fail to observe some of the underlying hypotheses of the previous frameworks. For instance, there is no clear bound on tree-width: even if input data such as dependency graphs are almost like trees, the property is not preserved along computations. Also, constraints on node degrees are also problematic: graphs are usually sparse, but some nodes may be highly connected. To illustrate, consider the sentence “The woman, the man, the child and the dog eat together”. The verb “eat” is related to four subjects and there is no a priori limit on this phenomenon. Typed versions (those with fixed arity) are also problematic: a verb may be transitive or not. Moreover, rewriting systems may be intrinsically nondeterministic. For instance, if one computes the semantics of a sentence out of its grammatical analysis, it is quite common there are multiple solutions. To further illustrate nondeterminism consider the well know phrasal construction “He saw a girl with a telescope” with two clear readings.

Some hypotheses are rather unusual for standard computations, e.g., fixed number of nodes. Indeed, nodes are usually related to words or concepts (which are themselves closely related to words). A paraphrase may be a little bit longer than its original version, but its length can be easily bounded by the length of the original sentence up to some linear factor. In GREW, node creations are restricted. To take into account the rare cases for which one needs extra nodes, a “reserve” is allocated at the beginning of the computation. All additional nodes are taken from the reserve. Doing so has some efficiency advantages, but that goes beyond the scope of the paper. Also, node and edge labels, despite being large, remain finite sets: they are usually related to some lexicons. These facts together have an important impact on the termination problem: since there are only finitely many graphs of a given size, rewriting only leads to finitely many outcomes. Thus, deciding termination for *a particular input graph* is decidable. However, our problem is to address termination in the class of *all* graphs. The latter problem is often referred to as *uniform termination*, whereas the former is refereed to as *non-uniform*. For word rewriting, uniform termination of non increasing systems constituted a well known problem, and was shown to be undecidable by Sénizergues in [24].

This paper proposes a novel approach for termination of graph rewriting. In a former paper [1], we proposed a solution based on label weights. Here, the focus is on the description (and the ordering) of paths within graphs. In fact, paths in a graph can be seen as regular languages. The question of path ordering thus translates into a question of regular language orderings. Accordingly, we define the *graph multi-set path ordering* that is related to that in [6]. Dershowitz and Jouannaud, in the context of drag rewriting, consider a similar notion of

path ordering called GPO (see [7]). Our definitions diverge from theirs in that our graph rewriting model is quite different: here, we do not benefit (as they do) from a good algebraic structure. Our graphs have no heads, tails nor hierarchical decomposition. In fact, our ordering is not even well founded! Relating the two notions is nevertheless interesting and left for further work. Plump [20] also defines path orderings for term graphs, but those behave like sets of terms.

One of our graph orderings will involve matrices, and orderings on matrices. Nonetheless, as far as we see, there is no relationship with matrix interpretations as defined by Endrullis, Waldmann and Zantemma [10].

The paper is organised as follows. In Section 2 we recall the basic background on graphs and graph rewriting systems (GRS) that we will need throughout the paper, and introduce an example that motivated our work. In Section 3 we consider a language theory approach to the termination of GRSs. In particular, we present the language matrix, and the matrix multiset path order (Subsection 3.4) and the rational embedding order (Subsection 3.5). We also introduce the notion of stability by context (Subsection 3.6) and show that both orderings are stable under this condition (Subsection 3.7). In Section 4 we propose notion of graph interpretability and show one of our main results, namely, that a GRS is terminating if and only if it is compatible with interpretations.

Main contributions: The two main contributions of the paper are the following.

1. We propose two orders on graphs inspired from language theory, and we show that both are monotonic and stable by context.
2. We introduce a notion of graph interpretation, and show that terminating GRSs are exactly those compatible with such interpretations.

2 Notations and Graph Rewriting

In this section we recall some general definitions and notations. Given an alphabet Σ, the set of words (finite sequences) is denoted by Σ^*. The concatenation of two words v and w is denoted by $v \cdot w$. The empty word, being the neutral element for concatenation, is denoted by 1_Σ or, when clear from the context, simply by 1. Note that $\langle \Sigma^*, 1, \cdot \rangle$ constitutes a monoid.

A *language* on Σ is some subset $L \subseteq \Sigma^*$. The set of all languages on Σ is $\mathcal{P}(\Sigma^*)$. The addition of two languages $L, L' \subseteq \Sigma^*$ is defined by $L + L' = \{w \mid w \in L \vee w \in L'\}$. The empty language is denoted by 0 and $\langle \mathcal{P}(\Sigma^*), +, 0 \rangle$ is also a monoid. Given some word $w \in \Sigma^*$, we will also denote by w the language made of the singleton $\{w\} \in \mathcal{P}(\Sigma^*)$. Given two languages $L, L' \subseteq \Sigma^*$, their concatenation is defined by $L \cdot L' = \{w \cdot w' \mid w \in L \wedge w' \in L'\}$. In this way, $\langle \mathcal{P}(\Sigma^*), 1, \cdot \rangle$ is also a monoid.

A *preorder* on a set X is a binary relation $\preceq \subseteq X^2$ that is reflexive ($x \preceq x$, for all $x \in X$) and transitive (if $x \preceq y$ and $y \preceq z$, then $x \preceq z$, for all $x, y, z \in X$). A preorder $\preceq$ is a *partial order* if it is anti-symmetric (if $x \preceq y$ and $y \preceq x$, then $x = y$, for all $x, y \in X$). A preorder is an *equivalence relation* if it is symmetric ($x \preceq y \Rightarrow y \preceq x$) . Observe that each preorder $\preceq$ induces an equivalence relation $\sim$: $a \sim b$ if $a \preceq b$ and $b \preceq a$. The strict part of $\preceq$ is then the relation: $x \prec y$ iff $x \preceq y$ and $\neg(x \sim y)$. We also mention the "dual" preorder $\succeq$ of $\preceq$ defined by: $x \succeq y$ iff $y \preceq x$. A preorder $\preceq$ is said to be *well-founded* if there is no infinite chain $\cdots \prec x_2 \prec x_1$ or, equivalently, $x_1 \succ x_2 \succ \cdots$.

The remainder of this section may be found in [2] and we refer the reader to it for an extended presentation. We suppose given a (finite) set Σ_{N} of *node labels*, a (finite) set Σ_{E} of *edge labels* and we define graphs accordingly. A graph is a triple $G = \langle N, E, \ell \rangle$ with

$E \subseteq N \times \Sigma_{\mathrm{E}} \times N$ and $\ell : N \to \Sigma_{\mathrm{N}}$ is the labeling function of nodes. Note that there may be more than one edge between two nodes, but at most one is labeled with some $e \in \Sigma_{\mathrm{E}}$. In the sequel, we use the notation $m \xrightarrow{e} n$ for an edge $(m, e, n) \in E$.

Given a graph G, the sets $\mathcal{N}_G$, $\mathcal{E}_G$ and ℓ_G denote respectively the sets of nodes, edges and its labeling function. We we will also (abusively) use the notation $m \in G$ and $m \xrightarrow{e} n \in G$ instead of $m \in \mathcal{N}_G$ and $m \xrightarrow{e} n \in \mathcal{E}_G$ when the context is clear. Furthermore, in  , a, b are nodes, ♣, ♡ are the respective node labels and A is the edge label (here between a and b).

The set of graphs on node labels Σ_{N} and edge labels Σ_{E} is denoted by $\mathcal{G}_{\Sigma_{\mathrm{N}},\Sigma_{\mathrm{E}}}$ or $\mathcal{G}$ in short. Two graphs G and G' are said to share their nodes when $\mathcal{N}_G = \mathcal{N}_{G'}$. Given two graphs G and G' such that $\mathcal{N}_G \subseteq \mathcal{N}_{G'}$, set $G \blacktriangleleft G' = \langle \mathcal{N}_{G'}, \mathcal{E}_G \cup \mathcal{E}_{G'}, \ell \rangle$ with $\ell(n) = \ell_G(n)$ if $n \in \mathcal{N}_G$ and $\ell(n) = \ell_{G'}(n)$, otherwise.

A graph morphism μ between a source graph G and a target graph H is a function $\mu : \mathcal{N}_G \to \mathcal{N}_H$ that preserves edges and labelings, that is, for all $m \xrightarrow{e} n \in G$, $\mu(m) \xrightarrow{e} \mu(n) \in G'$ holds, and for any node $n \in G$: $\ell_G(n) = \ell_{G'}(\mu(n))$. A *basic pattern* is a graph, and a *basic pattern matching* is an injective morphism from a basic pattern P to some graph G. Given such a morphism $\mu : G \to G'$, we define $\mu(G)$ to be the sub-graph of G' made of the nodes $\{\mu(n) \mid n \in \mathcal{N}_G\}$, of the edges $\{\mu(m) \xrightarrow{e} \mu(n) \mid m \xrightarrow{e} n \in G\}$ and node labels $\mu(n) \mapsto \ell_G(n)$.

A *pattern* is a pair $P = \langle P_0, \vec{\nu} \rangle$ made of a basic pattern P_0 and a sequence of injective morphisms $\nu_i : P_0 \to N_i$, called *negative conditions*. The basic pattern describes what must be *present* in the target graph G, whereas negative conditions say what must be *absent* in the target graph. Given a pattern $P = \langle P_0, \vec{\nu} \rangle$ and a graph G, a *pattern morphism* is an injective morphism $\mu : P_0 \to G$ for which there is no morphism ξ_i such that $\mu = \xi_i \circ \nu_i$.

▶ **Example 1.** Consider the basic pattern morphism $\mu : P_0 \to G$ (colors define the mapping):



The pattern $P = \langle P_0, [\nu] \rangle$ with ν defined by  prevents the application of the morphism above. Indeed, $\xi = b_0 \mapsto g_0, b_1 \mapsto g_1$ is such that $\xi \circ \nu = \mu$. When there is only one negative condition, we represent the pattern by crossing nodes and edges which *are not* within the basic pattern. For instance, the pattern P above looks like  that we hope is self-explanatory.

In this paper we think of graph transformations as sequences of "basic commands".

▶ **Definition 2** (The command language). *There are three basic commands:* $\texttt{label}(p, \alpha)$ *for node renaming,* $\texttt{del_edge}(p, e, q)$ *for edge deletion and* $\texttt{add_edge}(p, e, q)$ *for edge creation. In these basic commands, p and q are nodes, α is some node label and e is some edge label. A pattern $\langle P_0, \vec{\nu} \rangle$ is compatible with a command whenever p and q are nodes in P_0.*

▶ **Definition 3** (Operational semantics). *Given a pattern $P = \langle P_0, \vec{\nu} \rangle$ compatible with some command c, and some pattern matching $\mu : P \to G$ where G is the graph on which the transformation is applied, we have the following possible cases: $c = \texttt{label}(p, \alpha)$ turns the label of $\mu(p)$ into α, $c = \texttt{del_edge}(p, e, q)$ removes $\mu(p) \xrightarrow{e} \mu(q)$ if it exists, otherwise does nothing, and $c = \texttt{add_edge}(p, e, q)$ adds the edge $\mu(p) \xrightarrow{e} \mu(q)$ if it does not exists, otherwise does nothing. The graph obtained after such an application is denoted by $G \cdot_\mu c$.*

Given a sequence of commands $\vec{c} = (c_1, \ldots, c_n)$, let $G \cdot_\mu \vec{c}$ be the resulting graph, i.e., $G \cdot_\mu \vec{c} = (\cdots((G \cdot_\mu c_1) \cdot_\mu c_2) \cdot_\mu \cdots c_n)$.

▶ **Definition 4.** *A rule is a pair $R = \langle P, \vec{c} \rangle$ made of a pattern and a (compatible) sequence of commands. Such a rule R applies to a graph G when there is a pattern morphism $\mu : P \to G$. Let $G' = G \cdot_\mu \vec{c}$, then we write $G \to_{R,\mu} G'$. We define $G \to G'$ whenever there is a rule R and a pattern morphism μ such that $G \to_{R,\mu} G'$.*

2.1 The main example

Let $\Sigma_{\mathrm{N}} = \{A\}$ and $\Sigma_{\mathrm{E}} = \{\alpha, \beta, T\}$. For the discussion, we suppose that T is a working label, that is not present in the initial graphs. We want to add a new edge β between node n and node 1 each time we find a maximal chain:  within a graph G. Consider the basic pattern $P_{init} =$ together with its two negative conditions $\nu_1 =$  and $\nu_2 =$  . We consider three rules:

Init: $\langle \langle P_{init}, [\nu_1, \nu_2] \rangle, (\texttt{add_edge}(p, T, q)) \rangle$ which fires the transitive closure.

Follow: $\langle$  $, (\texttt{add_edge}(p, T, r), \texttt{del_edge}(p, T, q)) \rangle$ which follows the chain.

End: $\langle$  $, (\texttt{del_edge}(p, T, q), \texttt{add_edge}(q, \beta, p)) \rangle$ which stops the processus.

To prevent all pathological cases (e.g., when the edge β is misplaced, when two chains are crossing, and so on), we could introduce more sophisticated patterns. But, since that does not change issues around termination, we avoid obscuring rules with such technicalities.

▶ **Example 5.** Take  . By applying 'Init', 'Follow' and 'End', it rewrites as:



2.2 Three technical facts about Graph Rewriting

It is well known that the main issue with graph rewriting definitions is the way the context is related to the pattern image and its rewritten part. We shall tackle this issue with Proposition 6.

Self-application

Let $R = \langle P, \vec{c} \rangle$ be the rule made of a pattern $P = \langle P_0, \vec{\nu} \rangle$ and a sequence of commands $\vec{c}$. There is the identity morphism $1_{P_0} : P_0 \to P_0$, and thus we can apply rule R on P_0 itself, that is, $P_0 \to_{R,1_{P_0}} P_0' = P_0 \cdot_{1_{P_0}} \vec{c}$. We call this latter graph the *self-application of R*.

Rule node renaming

To avoid heavy notation, we will use the following trick. Suppose that we are given a rule $R = \langle P, \vec{c} \rangle$, a graph G and a pattern morphism $\mu : P \to G$. Let $P = \langle P_0, \vec{\nu} \rangle$. We define R_μ to be the rule obtained by renaming nodes p in P_0 to $\mu(p)$ (and their references within $\vec{c}$). For instance, the rule 'Follow' can be rewritten as $Follow_\mu =$ $\langle$  $, (\texttt{add_edge}(1, T, 3), \texttt{del_edge}(1, T, 2)) \rangle$ where μ denotes the pattern morphism used to apply 'Follow' in the derivation. Observe that: (i) the basic pattern of R_μ is actually $\mu(P_0)$, which is a subgraph of G, (ii) $\iota : \mu(P_0) \to G$ mapping $n \mapsto n$ is a pattern

matching, and (iii) applying rule R_μ with ι is equivalent to applying rule R with μ. In other words, $G \to_{R,\mu} G'$ if (and only if) $G \to_{R_\mu,\iota} G'$. To sum up, we can always rewrite a rule so that its basic pattern is *actually* a subgraph of G.

Uniform rules

Let us consider rule 'Init' above. It applies on:  , and the result is the graph itself:  . Indeed, we cannot add an already present edge (relative to a label) within a graph. Thus, depending on the graph, the rule will or will not append an edge. Such an unpredictable behavior can be easily avoided by modifying the pattern of 'Init' to:  . The same issue may come from edge deletions. A *uniform* rule is one for which commands apply (that is, modify the graph) for each rule application. Since this is not the scope of the paper, we refer the reader to [2] for a precise definition of uniformity. We will only observe two facts.

First, any rule can be replaced by a finite set of uniform rules (using negative conditions as above) that operate identically. Thus, we can always suppose that rules are uniform.

Second, the following property holds for uniform rules (see [2]§7 for a proof).

▶ **Proposition 6.** *Suppose that $G \to_{R,\iota} G'$ with $R = \langle P, \vec{c}\rangle$ and $P = \langle P_0, \vec{\nu}\rangle$ (the basic pattern P_0 being a subgraph of G). Let C be the graph obtained from G by deleting the edges in P_0. Then $G = P_0 \blacktriangleleft C$ and $G' = P_0' \blacktriangleleft C$ with P_0' being the self-application of the rule. Moreover, $\mathcal{E}_C \cap \mathcal{E}_{P_0} = \emptyset$ and $\mathcal{E}_C \cap \mathcal{E}_{P_0'} = \emptyset$.*

Throughout the remainder of the paper we assume that all rules are uniform.

3 Termination of Graph Rewriting Systems

By a *graph rewriting system* (GRS) we simply mean a set of graph rewriting rules (see Section 2). A GRS $\mathbf{R}$ is said to be *terminating* if there is no infinite sequence $G_1 \to G_2 \to \cdots$. Such sequences, whether finite or not, are called *derivations*.

Since there is no node creation (neither node deletion) in our notion of rewriting, any derivation starting from a graph G will lead to graphs whose size is the size of G. Since there are only finitely many such graphs, we can decide the termination for this particular graph G. However, the question we address here is the *uniform termination problem* (see Section 1).

▶ Remark 7. Suppose that we are given a strict partial order $\succ$, not necessarily well founded. If $G \to G'$ implies $G \succ G'$ for all graphs G and G', then the system is terminating. Indeed, suppose it is not the case, let $G_1 \to G_2 \to \cdots$ be an infinite reduction sequence. Since there are only finitely many graphs of size of G_1, it means that there are two indices i and j such that $G_i \to \cdots \to G_j$ with $G_i = G_j$. But then, since $G_i \succ G_{i+1} \succ \cdots \succ G_j$, we have that $G_i \succ G_j = G_i$ which is a contradiction.

A similar argument was exhibited by Dershowitz in [5] in the context of term rewriting. For instance, it is possible to embed rewriting within real numbers rather than natural numbers to prove termination.

Let us try to prove the termination of our main example (see Subsection 2.1). Rules such as '*Init*' and '*End*' are "simple": we put a weight on edge labels $\omega : \Sigma_{\mathrm{E}} \to \mathbb{R}$ and we say that the weight of a graph is the sum of the weights of its edges labels. Set $\omega(\alpha) = 0, \omega(\beta) = -2$ and $\omega(T) = -1$. Then, rules 'Init' and 'End' decrease the weight by 1 and, since rule 'Follow'

keeps the weight constant, it means the two former rules can be applied only finitely many times. Observe that negative weights are no problem with respect to Remark 7.

But how do we handle rule 'Follow'? No weights as above can work.

3.1 A language point of view

Let $G \to G'$ be a rule application. The set of nodes stays constant. Let us think of graphs as automata, and let us forget about node labeling for the time being. Let Σ_{E} be the set of edge labels. Consider a pair of states (nodes), choose one to be the initial state and one to be the final state. Thus the automaton (graph) defines some regular language on Σ_{E}. In fact, the automaton describes n^2 languages (one for each pair of states).

Now, let us consider the effect of graph rewriting in terms of languages. Consider an application of the 'Follow' rule: $G \to G'$. Any word to state r that goes through the transitions $p \xrightarrow{T} q \xrightarrow{\alpha} r$ can be mapped to a shorter one in G' via the transition $p \xrightarrow{T} r$. The languages corresponding to state r contain shorter words. The remainder of this section is devoted to formalizing this intuition into proper orders on graphs. For that, we will need to *count* the number of paths between any two states. Hence, we shall introduce $\mathbb{N}$-rational expressions, that is, *rational expression with multiplicity*. See, e.g., Sakarovitch's book [23] for an introduction and justifications of the upcoming constructions. We introduce here the basic ideas.

3.2 Formal series

A formal series on Σ (with coefficients in $\mathbb{N}$) is a (total) function $s : \Sigma^* \to \mathbb{N}$. Given a word w, $s(w)$ is the multiplicity of w. The set of words $\underline{s} = \{w \in \Sigma^* \mid s(w) \neq 0\}$ is the *support* of s. Given $n \in \mathbb{N}$, let n be the series defined by $\mathsf{n}(w) = 0$, if $w \neq 1$, and $\mathsf{n}(1) = n$, where 1 denotes the empty word. The empty language is $\underline{0}$, the language made of the empty word is $\underline{1}$. Moreover, for $a \in \Sigma$, the series a is given by $a(w) = 0$ if $w \neq a$ and $a(a) = 1$.

Given two series s and t, their *addition* is the series $s + t$ given by $s + t(w) = s(w) + t(w)$, and their *product* is $s \cdot t$ defined by $s \cdot t(w) = \sum_{u \cdot v = w} s(u)t(v)$. The *star operation* is defined by $s^* = 1 + s + s^2 + \cdots$. The monoïd Σ^* being graded, the operation is correctly defined whenever $s(1) = 0$.

Given a series s, let $s^{\leq k}$ be its restriction to words of length less or equal to k, i.e., $s^{\leq k}(w) = 0$ whenever $|w| > k$ and $s^{\leq k}(w) = s(w)$, otherwise.

An $\mathbb{N}$-rational expression on an alphabet Σ is built upon the grammar [22]:

$$\mathsf{E} ::= a \in \Sigma \mid n \in \mathbb{N} \mid (\mathsf{E} + \mathsf{E}) \mid (\mathsf{E} \cdot \mathsf{E}) \mid (\mathsf{E}^*).$$

Thus, given the constructions mentioned in the previous paragraph, any $\mathbb{N}$-rational expression $E \in \mathsf{E}$ denotes some formal series. To each $\mathbb{N}$-rational expression corresponds an $\mathbb{N}$-automaton, which is standard automaton with transitions labeled by a non empty linear combination $\sum_{i \leq k} n_i a_i$ with $n_i \in \mathbb{N}$ and $a_i \in \Sigma$ for all $i \leq k$.

3.3 The language matrix

Let us suppose given an edge label set Σ_{E}. Let E denote the $\mathbb{N}$-expressions over Σ_{E}. A matrix M of dimension $P \times P$ for some (finite) set P is an array $(M_{i,j})_{i \in P, j \in P}$ whose components are in E. Let $\mathfrak{M}_E$ be the set of such matrices. Given a graph G, we define the matrix M_G of dimension $\mathcal{N}_G \times \mathcal{N}_G$ as follows: $M_{G\,i,j} = T_1 + \cdots + T_\ell$ with $T_1, \ldots, T_\ell$ the set of labels on the transitions between state i and j if such transitions exist, otherwise 0.

Let 1_P be the unit matrix of dimension $P \times P$, that is $(1_P)_{i,j} = 0$ if $i \neq j$ else 1. From now on, we abbreviate the notation from 1_P to 1 if the context is clear. Then, let $M_G^* = 1 + M_G + M_G^2 + \cdots$. Each component of M_G^* is actually an $\mathbb{N}$-regular expression (see Sakarovitch Ch. III, §4 for instance). The (infinite) sum is correctly defined since for all i, j, $(M_G)_{i,j} = T_1 + \cdots + T_\ell$. Thus, $1 \notin \underline{(M_G)_{i,j}}$.

The question about termination can be reformulated in terms of matrices whose components are languages (with words counted with their multiplicity). To prove the termination of the rewriting system, it is then sufficient to prove that for any two graphs $G \to G'$, $M_G^* > M_{G'}^*$. To prove such a property in the infinite class of finite graphs, we will use the notion of "stable orders".

Recall the 'Follow' rule and consider the basic pattern L and the self-application R. Then,

$$M_L = \begin{pmatrix} 0 & T & 0 \\ 0 & 0 & \alpha \\ 0 & 0 & 0 \end{pmatrix} \quad M_R = \begin{pmatrix} 0 & 0 & T \\ 0 & 0 & \alpha \\ 0 & 0 & 0 \end{pmatrix}.$$

Observe that $(M_R)_{13} > (M_L)_{13}$. This matrix deals with edges/transitions. In order to consider paths, we need to compute M_L^* and M_R^* that are given by:

$$M_L^* = \begin{pmatrix} 1 & T & T \cdot \alpha \\ 0 & 1 & \alpha \\ 0 & 0 & 1 \end{pmatrix} \quad M_R^* = \begin{pmatrix} 1 & 0 & T \\ 0 & 1 & \alpha \\ 0 & 0 & 1 \end{pmatrix}.$$

Any word within M_R^*'s components is a sub-word of the corresponding component in M_L^*.

▶ **Example 8.** Consider now a variation of 'Follow': $\langle$ 

$$(\texttt{add_edge}(p, T, r), \texttt{del_edge}(p, T, q))\rangle.$$

By setting L' as the pattern and R' as the self-application, we get the following matrices:

$$M_{L'}^* = \begin{pmatrix} (T\alpha\gamma)^* & T(\alpha\gamma T)^* & T\alpha(\gamma T\alpha)^* \\ \alpha\gamma(T\alpha\gamma)^* & (\alpha\gamma T)^* & \alpha(\gamma T\alpha)^* \\ \gamma(T\alpha\gamma)^* & \gamma T(\alpha\gamma T)^* & (\gamma T\alpha)^* \end{pmatrix} \quad M_{R'}^* = \begin{pmatrix} (T\gamma)^* & 0 & T(\gamma T)^* \\ \alpha\gamma(T\gamma)^* & 1 & \alpha(\gamma T)^* \\ \gamma(T\gamma)^* & 0 & (\gamma T)^* \end{pmatrix}.$$

Again, words within $M_{R'}^*$ are sub-words of the corresponding ones in $M_{L'}^*$.

3.4 The matrix multiset path order

The order we shall introduce in this section is inspired by the notion of *multiset path ordering* within the context of term rewriting (see for instance [6]). However, in the present context of graph rewriting (to be compared with Dershowitz and Jouannaud's [7] or with Plump's [20]), the definition is a bit more complicated. Here, we do not consider an order on letters as it is done for terms.

Let $\trianglelefteq$ be the word embedding on Σ^*, that is, the smallest partial order such that $1 \trianglelefteq w$, and if $u \trianglelefteq v$, then $(u \cdot w \trianglelefteq v \cdot w$ and $w \cdot u \trianglelefteq w \cdot v$, for all $u, v, w \in \Sigma^*$. This order $\trianglelefteq$ can be extended to formal series, that is, the multiset-path ordering, see Dershowitz and Manna [9] or Huet and Oppen [13].

▶ **Definition 9** (Multiset path order)**.** *The multiset path order is the smallest partial order on finite series such that*

- *if there is $w \in \underline{t}$ such that for all $v \in \underline{s}$, $v \lhd w$, then $s \trianglelefteq t$, and*
- *if $r \trianglelefteq s$ and $t \trianglelefteq u$, then $r + t \trianglelefteq s + u$.*

We write $s \lhd t$ when $s \trianglelefteq t$ and $s \neq t$.

▶ **Proposition 10.** *Addition and product are monotonic with respect to the multiset-path order. Moreover, addition is strictly monotonic with respect to $\trianglelefteq$, and if $r \lhd s$, then $r \cdot t \lhd s \cdot t$ and $t \cdot r \lhd t \cdot s$, whenever $t \neq 0$ (otherwise, we have equality).*

Proof. It is not difficult to see that addition is monotonic. So suppose that $r \lhd s$. We prove that $r + t \lhd s + t$, by induction (see Definition 9). Suppose that there is $w \in \underline{s}$ such that for all $v \in \underline{r}$ we have $v \lhd w$, then $r \lhd s$. Since $r(w) = 0$, then $(r + t)(w) = t(w) < s(w) + t(w) = (s + t)(w)$, and we are done. Otherwise, $r = r_0 + r_1$ and $s = s_0 + s_1$ with $r_0 \trianglelefteq s_0$ and $r_1 \trianglelefteq s_1$. One of the two inequalities must be strict (otherwise $r = s$). Suppose $r_0 \lhd s_0$. By definition, observe that $r_1 + t \trianglelefteq s_1 + t$. But then, $r + t = r_0 + (r_1 + t)$ and $s = s_0 + (s_1 + t)$ and we apply induction on (r_0, s_0). As addition is commutative, the result holds.

For the product, suppose that $r \trianglelefteq s$ and let t be some series. We prove $r \cdot t \trianglelefteq s \cdot t$; the other inequality $t \cdot r \trianglelefteq t \cdot s$ is similar. Again, we proceed by induction on Definition 9:

- Suppose there is $w \in \underline{s}$ such that for all $v \in \underline{r}, v \lhd w$. By induction on t, if $t = 0$, $r \cdot t = 0 \trianglelefteq 0 = s \cdot t$. Otherwise, $t = t_0 + v_0$ for a word v_0. Observe that $r \cdot v_0 = \sum_{v \in \underline{r}} r(v) v \cdot v_0$. Since for all $v \in \underline{r}$, $v \cdot v_0 \lhd w \cdot v_0$, we have $r \cdot v_0 \lhd w \cdot v_0 \trianglelefteq s \cdot v_0$. Now, $r \cdot t = r \cdot (t_0 + v_0) = r \cdot t_0 + r \cdot v_0$ and $s \cdot t = s \cdot t_0 + s \cdot v_0$. By induction, $r \cdot t_0 \trianglelefteq s \cdot t_0$ and since $r \cdot v_0 \trianglelefteq s \cdot v_0$, the result holds.
- Otherwise, $r = r_0 + r_1$. In this case, $s \cdot r = s \cdot r_0 + s \cdot r_1$ and $t \cdot r = t \cdot r_0 + t \cdot r_1$. The result then follows by induction.

To show strict monotonicity, suppose $r \lhd s$ and again proceed by case analysis. Suppose that there is some $w \in \underline{s}$ such that for all $v \in \underline{r}, v \lhd w$. Since $t \neq 0$, it contains at least one word v_0 such that $t = t_0 + v_0$. By $r \lhd s$, $r \cdot v_0 = \sum_{v \in \underline{r}} r(v) v \cdot v_0 \lhd \sum_{v \in \underline{s}} s(v) v \cdot v_0 = s \cdot v_0$. The result then follows by induction on the expansion of t and using the strict monotonicity of addition. ◀

▶ **Definition 11** (Matrix multiset-path order). *Let M and M' be two matrices with dimension $P \times P$. Write $M \trianglelefteq M'$ if for all $k \geq |P|$ and for all $(i, j) \in P \times P$, we have $M_{i,j}^{\leq k} \trianglelefteq M'_{i,j}{}^{\leq k}$.*

▶ **Corollary 12.** *The addition and the multiplication are monotonic with respect to the matrix multiset-path order.*

Proof. It follows from Proposition 10 since addition and product of matrices are defined as addition and product of their components. ◀

3.5 The Rational Embedding Order

Let Σ be some fixed alphabet. For a transducer τ, we denote the function it computes by $[\tau]$.

▶ **Definition 13** (Rational Embedding Order). *Given two regular languages L and L' on Σ, write $L \lesssim L'$ if:*

- *there is an injective function $[\tau] : L' \to L$ and*
- *$[\tau]$ can be computed by a transducer τ such that $|\tau(w)| \leq |w|$, for every $w \in L'$. Such transducers are said to be decreasing (in [16]).*

The transducer τ is said to be a *witness* of $L \lesssim L'$.

We say that a transition of a transducer is *deleting* when it is of the form $a \mid 1$ for some $a \in \Sigma$. A transducer whose transitions are of the form $X \mid Y$, with $|Y| \leq |X|$, is itself decreasing. If a path corresponding to an input w passes through a deleting transition, then $|\tau(w)| < |w|$.

In the sequel we will make use of the following results that are direct consequences of Nivat's Theorem [17].

▶ **Proposition 14.** *Let $[\tau] : L \to L'$ be computed by a transducer τ, and let L'' be a regular language. Then the following assertions hold.*

1. *The restriction $\tau_{|L''} : L'' \cap L \to L'$ mappping $w \mapsto \tau(w)$ is computable by a transducer.*
2. *The co-restriction $\tau^{|L''} : L \to L' \cap L''$ mapping $w \mapsto \tau(w)$ if $\tau(w) \in L''$ and otherwise undefined, is computable by a transducer.*
3. *The function $\tau' : L \to L'$ defined by $\tau'(w) = \tau(w)$ if $w \in L''$ and otherwise undefined, is computable by a transducer.*

Observe that the identity on Σ^* is computed by a transducer (made of a unique initial/final state with transitions $a \mid a$ for all $a \in \Sigma$). Then, the identity on L is obtained by Proposition 14(1,2). Thus we have that $\lesssim$ is reflexive. Also, it is well known that both transducers and injective functions can be composed. Hence, we also have that $\lesssim$ is transitive. Thus, $\lesssim$ is a preorder.

However, we do not have anti-reflexivity in general.

▶ **Example 15.** $L_1 = A \cdot (A + B)^* \lesssim L_2 = B \cdot (A + B)^* \lesssim L_1$. Consider the transducer (in the drawing, the initial state is shown with an in-arrow and the final one by an out-arrow):



. That shows $L_1 \lesssim L_2$. Swap 'A' and 'B', the converse holds.

However, there is a simple criterion to ensure a strict inequality. Suppose $L_1 \lesssim L_2$ has a witness $\tau : L_2 \to L_1$. If τ contains one (accessible and co-accessible) deleting transition, then, the relation is strict.

As before, set $L_1 < L_2$ whenever $L_1 \lesssim L_2$ but not $L_2 \lesssim L_1$. Suppose $L_1 \lesssim L_2 \lesssim L_1$ with a transducer $\theta : L_1 \to L_2$ and τ as above. Let w be the smallest input word from the initial state to a final state through the transition $a \mid 1$. Then $\theta \circ \tau$ (the composition of the two transducers) defines an injective function. Define the set $M^{<|w|} = \{u \in L_2 \mid |u| < |w|\}$. Generally speaking, for any word u, $|\theta \circ \tau(u)| \leq |u|$. Thus $\theta \circ \tau(M^{<w}) \subseteq M^{<w}$. Since $M^{<w}$ is a finite set and $\theta \circ \tau$ is injective, it is actually bijective when restricted to $M^{<w}$. However, $|\theta \circ \tau(w)| \leq |\tau(w)| < w$ implies $\theta \circ \tau(w) \in M^{<w}$. By the Pigeon-hole Principle, there is one word in $M^{<w}$ that has two pre-images via $\theta \circ \tau$. Thus, $\theta \circ \tau$ cannot be injective, which yields a contradiction.

▶ Remark 16. Observe that, when two regular languages verify $L \subseteq L'$, it follows from Proposition 14 that $L \lesssim L'$.

▶ **Definition 17.** *The rational embedding order extends to matrices by pointwise ordering: Let M and N with dimension $P \times P$, and write $M \lesssim N$ if for every $i, j \in P \times P$, we have $M_{i,j} \lesssim N_{i,j}$.*

Recall the modified version of 'Follow' (Example 8). The following transducers show that all components strictly decrease.



In the following, to compare two graphs by means of the rational embedding order, we transform graphs into matrices as follows. Given a graph G, let M'_G be the matrix of dimension $\mathcal{N}_G \times \mathcal{N}_G$ such that $(M'_G)_{i,j} = T_1^{i,j} + T_2^{i,j} + \cdots T_\ell^{i,j}$ with $T_1, \ldots, T_\ell$ the labels of the edges from i to j. In other words, we "decorate" the labels with the source and target nodes. Then, $G \lesssim G'$ whenever $M'_G \lesssim M'_{G'}$.

3.6 Stable orders on matrices

A matrix on E is said to be *finite* whenever all its component are finite. Two matrices M and M' (of same dimension) on E are said to be disjoint if for every i, j, $M_{i,j} \cdot M'_{i,j} = 0$.

▶ **Definition 18.** *Let M be a matrix of dimension $P \times P$ and $P \subseteq G$. The extension of M to dimension $G \times G$ is the matrix $M^{\uparrow G}$ defined by:*

$$(M^{\uparrow G})_{i,j} = \begin{cases} M_{i,j} & \text{if } i, j \in P \\ 0 & \text{otherwise} \end{cases}$$

The notation $M^{\uparrow G}$ is shortened to $M^{\uparrow}$ when G is clear from the context.

▶ **Fact 1.** *Let M be a matrix of dimension $P \times P$, with $P \subseteq G$. Then $(M^{\uparrow G})^* = (M^*)^{\uparrow G}$.*

▶ **Definition 19.** *We say that a partial order $\preceq$ on E is* stable by context *if for every $P \subseteq G$, all matrices L and R of dimension $P \times P$, and every C of dimension $G \times G$, the following assertions hold.*

1. *If L, R, C are finite, L being disjoint from C, R being disjoint from C and $R^* \prec L^*$, then $(R + C)^* \prec (L + C)^*$;*
2. *If $R \prec L$, then $R^{\uparrow G} \prec L^{\uparrow G}$.*

▶ **Lemma 20.** *Let $\preceq$ be partial order stable by context and consider finite matrices L, R of dimension $P \times P$ and let C be a finite matrix of dimension $G \times G$ with $P \subseteq G$. Then, $R^* \prec L^*$ implies $(R^{\uparrow} + C)^* \prec (L^{\uparrow} + C)^*$.*

Proof. If $R^* \prec L^*$, then, $(R^*)^{\uparrow} \prec (R^*)^{\uparrow}$ by Definition 19.2. By Lemma 1, it follows that $(R^{\uparrow})^* \prec (L^{\uparrow})^*$. Clearly, $R^{\uparrow}$ and $L^{\uparrow}$ are finite, and from Definition 19.1, we have $(R^{\uparrow} + C)^* \prec (L^{\uparrow} + C)^*$ ◀

▶ **Theorem 21.** *Let $\preceq$ be a partial order stable by context. Suppose that for every rule $R = \langle P, \vec{c} \rangle$ with $P = \langle P_0, \vec{\nu} \rangle$ and P'_0 the self-application of R, we have $(P'_0)^* \prec (P_0)^*$. Then the corresponding GRS is terminating.*

Proof. Let $\preceq$ be a partial order on graphs and consider the corresponding order on matrices: $G \prec G'$ iff $M^*_G \prec M^*_{G'}$. We show that for every rule, we have $G \to G'$ implies $G' \prec G$. So let R be a graph rewriting rule and let μ be a morphism such that $G \to_{R,\mu} G'$. By the discussion in the beginning of Section 3, without loss of generality, we can suppose that μ is actually the inclusion of pattern P_0 in G. Now, let $P_0 and P'_0$ be respectively the basic pattern and the self-application of R. Define C to be the graph made of the nodes of G without edges in P_0. By Proposition 6, $M_G = M^{\uparrow}_{P_0} + M_C$ and $M_{G'} = M^{\uparrow}_{P'_0} + M_C$. Moreover, $M_{P_0}, M_{P'_0}$ and M_C are finite and M_{P_0} is disjoint from M_C and $M_{P'_0}$ is disjoint from M_C. Thus, we can apply Lemma 20, and we get $M^*_{G'} = (M^{\uparrow}_{P'_0} + M_C)^* \prec (M^{\uparrow}_{P_0} + M_C)^* = M^*_G$. ◀

3.7 Stability of the orderings

We can now prove the two announced stability results.

▶ **Proposition 22.** *The multiset path ordering is stable by context.*

Proof. We first verify that condition 2 of Definition 19 holds. Suppose that $R \lhd L$ with R, L of dimension $P \times P$. Then, for all $(i,j) \notin P \times P$, $R^{\uparrow G}_{i,j} = 0 \trianglelefteq 0 = L^{\uparrow G}_{i,j}$. Now, for all $k \geq |G| \geq |P|$ and for all $(i,j) \in P \times P$, we have $(R^{\uparrow G})^{\leq k}_{i,j} = R^{\leq k}_{i,j} \trianglelefteq L^{\leq k}_{i,j} = (L^{\uparrow G})^{\leq k}_{i,j}$.

To verify that condition 1 also holds, let $G \times G$ be the dimension of L, R and C. Take $k \geq |G|$. We have on one side $(R+C)^{*\leq k} = \sum_{(A_1,\ldots,A_\ell)\in\{R,C\}^*,\, \ell\leq k} \prod_{i\leq \ell} A_i$, and on the other side $(L+C)^{*\leq k} = \sum_{(A_1,\ldots,A_\ell)\in\{R,C\}^* | \ell\leq k} \prod_{i\leq \ell} A_i\{R \leftarrow L\}$ where $A_i\{R \leftarrow L\} = L$ if $A_i = R$, and C otherwise. As the product and the addition are (strictly) monotonic, the result follows. ◀

▶ **Proposition 23.** *The rational embedding order is stable by context.*

Proof. Since we use a component-wise ordering, it is easy to verify that condition 2 of Definition 19 holds. To verify that condition 1 also holds, let $G \times G$ be the shared dimension of L, R and C. Since $R < L$, there are decreasing transducers $\tau_{i,j} : L_{i,j} \to R_{i,j}$ with at least one of them deleting. Let P be the set of nodes corresponding to the pattern L. We build the family of transducers $(\theta_{p,q})_{p,q\in G\times G}$ as follows. The family of transducers will share the major part of the construction. First, we make a copy of all transducers $(\tau_{i,j})_{i,j}$. Then, we add as states all the nodes of C. Given an edge $i \xrightarrow{T} j \in C$, we set a transition $i \xrightarrow{T^{i,j}|T^{i,j}} j$. That is the transducer copies the paths within C. For a transition $i \xrightarrow{T} j$ with $i \notin P, j \in P$, we set the transitions: $i \xrightarrow{T^{i,j}|T^{i,j}} q_n$ for all q_n initial state of the transducer $\tau_{j,n}, n \in P$. Similarly, for any transition $i \xrightarrow{T} j$ with $i \in P, j \notin P$, we set the transitions: $r_n \xrightarrow{T^{i,j}|T^{i,j}} j$ for each terminal state r_n of the transducer $\tau_{n,i}, n \in P$. This construction can be represented as follows:



where U, T, W, X, Y range over the edge labels. Take $k, \ell \notin P$. Any path from state k to state ℓ describes a path in $C + L$ on the input side and a path in $C + R$ on the output side. Indeed, transitions within C are simply copied and the transducers $\tau_{i,j}$ transform paths in L into paths in R.

It remains to specify initial and final states. Given some component $p, q \in G$, if $i \notin P$, we set the initial state to be p. Otherwise, we introduce a new state ι which is set to be initial, and we add a transition $\iota \xrightarrow{1|1} i$ for any state i initial in $\tau_{p,r}$ for some r. If $q \notin P$, then, q is the final state. Otherwise, any state j within some $\tau_{r,q}$, $r \in P$, is final.

Consider some pair $p, q \in G$. We prove that the transducer $\theta_{p,q}$ is injective. Consider a path w in $C + L$. It can be decomposed as follows: $w = w_1\ell_1 \cdots w_k\ell_k$ where the ℓ_i's are the sub-words within L (that is the w_i's have the shape $v_i a_i$ where a_i is a transition from C to L). Consider a second word $w' = w'_1\ell'_1 \cdots w'_{k'}\ell'_{k'}$ such that the transducer $\theta_{p,q}(w) = \theta_{p,q}(w') = u$. Given the construction of $\theta_{p,q}$, consider the word $u = u_1r_1 \cdots u_kr_k$ with $r_1, \ldots, r_k$ some path within R. Indeed, only a letter within L can produce a letter within R. Consider the case where r_k is non empty. When the transducer reaches the first letter in ℓ_k, it is in a state $\tau_{k,m}$ for some m. Actually, $m = q$ since only $\tau_{k,q}$ contains a final state. Thus, the path is fixed within $\tau_{k,p}$ and then, the injection of $\tau_{k,p}$ applies. So, $\ell'_{k'} = \ell_k$. We can go back within w_k. On this part of the word, the transitions have the shape $T^{i,j} \mid T^{i,j}$. Thus, $w_k = w'_{k'}$. We can continue this process up to the beginning of w and w'. ◀

4 Interpretations for Graph Rewriting Termination

Interpretations methods are well known in the context of term rewriting, see for instance Dershowitz and Jouannaud's survey on rewriting [6]. Their usefulness comes from the fact that they belong to the class of simplification orderings, i.e., orderings for which if $t \trianglelefteq u$, then $t \preceq u$. In the context of graphs, we introduce a specific notion of "interpretation", that we will still call interpretation.

▶ **Definition 24.** *A graph* interpretation *is a triple $\langle X, \prec, \phi\rangle$ where $\langle X, \prec\rangle$ is a partially ordered set and $\phi : \mathcal{G} \to X$ is such that given two graphs P and P' having the same set of nodes and C disjoint of P and P', if $\phi(P) \prec \phi(P')$, then $\phi(P + C) \prec \phi(P' + C)$.*

An interpretation $\Omega = \langle X, \prec, \phi\rangle$ is *compatible* with a rule R if $\phi(P'_0) \prec \phi(P_0)$ where P_0 is the basic pattern of R and P'_0 its self-application. Similarly, an interpretation is compatible with a GRS if it is compatible with all of its rules.

▶ **Theorem 25.** *Every GRS compatible with an interpretation Ω is terminating.*

The theorem being a more abstract form of Theorem 21, its proof follows exactly the same steps.

Proof. Suppose that $G \prec G'$ iff $\phi(G) \prec \phi(G')$. We prove that for each rule R of the GRS, $G \to G'$ implies $G' \prec G$. Indeed, suppose that $G \to_{R,\mu} G'$. Let P_0 and P'_0 be respectively the basic pattern and the self-application of R. Then, there is a graph C such that $G = P_0 + C$, $G' = P'_0 + C$, such that P_0 and P'_0 are disjoint from C. Since $\phi(P'_0) \prec \phi(P)$, we then have $\phi(G') \prec \phi(G)$. ◀

▶ **Example 26.** The triple $\langle \mathfrak{M}, \trianglelefteq, (M_{(-)})^*\rangle$ is an interpretation for 'Follow'.

▶ **Example 27.** Let us come back to the weight analysis. Define $\overline{\omega}(G) = \sum_{p \xrightarrow{e} q \in G} \omega(e)$ with $\omega(\alpha) = 0, \omega(T) = -1, \omega(\beta) = -1$. Then, $\langle \mathbb{R}, <, \overline{\omega}(-)\rangle$ is an interpretation for 'Init' and 'End'.

▶ **Example 28.** Let $\langle X_1, \prec_1, \phi_1\rangle$ be an interpretation for a set of rules $\mathcal{R}_1$, and let $\langle X_2, \prec_2, \phi_2\rangle$ be an interpretation for a set of rules $\mathcal{R}_2$. Suppose that for every rule R in $\mathcal{R}_2$, $G \to_{R,\mu} G'$ implies $G' \preceq_1 G$ (that is without strict inequality). Then the lexicographic ordering on $X_1 \times X_2$ defined by $(x_1, x_2) \prec_{1,2} (y_1, y_2)$ iff $x_1 \prec_1 y_1$, or $x_1 \preceq_1 y_1$ and $x_2 \prec_2 y_2$, constitutes an interpretation $\langle X_1 \times X_2, \prec_{1,2}, \phi_1 \times \phi_2\rangle$ for $\mathcal{R}_1 \cup \mathcal{R}_2$.

Thus, combining Example 26 and Example 27, we have a proof of the termination of our main Example.

▶ **Corollary 29.** *The GRS given in Subsection 2.1 is terminating.*

▶ **Example 30.** Let $\mathcal{R}$ be a terminating GRS. Then there is an interpretation that "justifies" this fact. Indeed, take $\langle \mathcal{G}, \prec, 1_{\mathcal{G}}\rangle$ with $\prec$ defined to be the transitive closure of the rewriting relation $\to$. The termination property ensures that the closure leads to an irreflexive relation. The compatibility of $\prec$ with respect to $1_{\mathcal{G}}$ is immediate.

Thus the following corollary.

▶ **Corollary 31.** *A GRS is terminating iff it is compatible with some interpretation.*

5 Conclusion

We proposed a new approach based on the theory of regular languages to decide the termination of graph rewriting systems, which does not account for node additions but settles the uniform termination problem for these GRS. We think that there is room to reconsider some old results of this theory under the new light. In particular, we think of profinite topology [19], is a powerful tool that could give us some insight on underlying structure of the orders. In the two cases, we can extend the orders to take into account orders on the edge labels.

As the next natural step, we intend to consider graph rewriting with node creations and that take into account node labels. Moreover, in the experiments mentioned in the introduction about natural language processing, in principle, these two orders should still be sufficient to ensure termination. However, we need to implement these new results for an extensive and complete evaluation.

References

1. Guillaume Bonfante and Bruno Guillaume. Non-simplifying graph rewriting termination. In *Proceedings 7th International Workshop on Computing with Terms and Graphs, TERMGRAPH 2013, Rome, Italy, 23th March 2013*, pages 4–16, 2013.
2. Guillaume Bonfante, Bruno Guillaume, and Guy Perrier. *Application of Graph Rewriting to Natural Language Processing.* Logic, Linguistic and Computer Science. Wiley, 2018.
3. N. Chomsky. *Syntactic Structures.* The Hague: Mouton, 1957.
4. Bruno Courcelle and Joost Engelfriet. *Graph Structure and Monadic Second-Order Logic.* Cambridge University Press, 2012.
5. Nachum Dershowitz. A note on simplification orderings. *Information Processing Letters*, pages 212–215, 1979.
6. Nachum Dershowitz and Jean-Pierre Jouannaud. Rewrite systems. In *Handbook of Theoretical Computer Science, Volume B: Formal Models and Semantics*, pages 243–320. 1990.
7. Nachum Dershowitz and Jean-Pierre Jouannaud. Graph path orderings. In *LPAR-22. 22nd International Conference on Logic for Programming, Artificial Intelligence and Reasoning, Awassa, Ethiopia, 16-21 November 2018*, pages 307–325, 2018.

8 Nachum Dershowitz and Jean-Pierre Jouannaud. Drags: A compositional algebraic framework for graph rewriting. *Theor. Comput. Sci.*, 777:204–231, 2019.

9 Nachum Dershowitz and Zohar Manna. Proving termination with multiset orderings. *Commun. ACM*, 22(8), 1979.

10 Jörg Endrullis, Johannes Waldmann, and Hans Zantema. Matrix interpretations for proving termination of term rewriting. *Journal of Automated Reasoning*, 40(2):195–220, Mar 2008.

11 Maribel Fernández, Hélène Kirchner, and Bruno Pinaud. Strategic port graph rewriting: an interactive modelling framework. *Mathematical Structures in Computer Science*, 29(5):615–662, 2019.

12 Bruno Guillaume and Guy Perrier. Dependency parsing with graph rewriting. In *Proceedings of the 14th International Conference on Parsing Technologies, IWPT 2015, Bilbao, Spain, July 5-7, 2015*, pages 30–39, 2015.

13 Gerard Huet and Derek C. Oppen. Equations and rewrite rules: a survey. In *In formal language Theory: perspective and open problems*. Academic Press, 1980.

14 Sylvain Kahane and François Lareau. Word ordering as a graph rewriting process. In *Formal Grammar - 20th and 21st International Conferences, FG 2015, Barcelona, Spain, August 2015, Revised Selected Papers. FG 2016, Bozen, Italy, August 2016, Proceedings*, volume 9804, pages 216–239. Springer, 2016.

15 Yves Lafont. Interaction nets. In *Conference Record of the Seventeenth Annual ACM Symposium on Principles of Programming Languages, San Francisco, California, USA, January 1990*, pages 95–108, 1990.

16 Jeannine Leguy. Transductions rationnelles décroissantes. *RAIRO*. Informatique théorique, 15(2):141–148, 1981.

17 Maurice Nivat. Transducteurs des langages de Chomsky. *Ann. Inst. Fourier, Grenoble*, 18:339–455, 1968.

18 Mizuhito Ogawa. A note on algebraic structure of tree decomposition of graphs. In *The First Asian Workshop on Programming Languages and Systems, APLAS 2000, National University of Singapore, Singapore, December 18-20, 2000, Proceedings*, pages 223–229, 2000.

19 Jean-Eric Pin. Profinite methods in automata theory. In *26th International Symposium on Theoretical Aspects of Computer Science, STACS 2009, February 26-28, 2009, Freiburg, Germany, Proceedings*, volume 3 of *LIPIcs*, pages 31–50. Schloss Dagstuhl - Leibniz-Zentrum fuer Informatik, Germany, 2009.

20 Detlef Plump. Simplification orders for term graph rewriting. In Igor Prívara and Peter Ružička, editors, *Mathematical Foundations of Computer Science 1997*, pages 458–467, Berlin, Heidelberg, 1997. Springer Berlin Heidelberg.

21 Grzegorz Rozenberg, editor. *Handbook of Graph Grammars and Computing by Graph Transformation: Volume I. Foundations*. World Scientific Publishing Co., Inc., River Edge, NJ, USA, 1997.

22 Jan Rutten. Behavioural differential equations: a coinductive calculus of streams, automata, and power series. *Theoretical Computer Science*, 308(1):1 – 53, 2003.

23 Jacques Sakarovitch. *Elements of Automata Theory*. Cambridge University Press, 2009.

24 Géraud Sénizergues. Some undecidable termination problems for semi-thue systems. *Theoretical Computer Science*, 142:257–276, 1995.