



**HAL**  
open science

# Numerical Approach to the Optimal Control and Efficiency of the Copepod Swimmer

Jérémy Rouot, Bernard Bonnard, Monique Chyba, Daisuke Takagi

► **To cite this version:**

Jérémy Rouot, Bernard Bonnard, Monique Chyba, Daisuke Takagi. Numerical Approach to the Optimal Control and Efficiency of the Copepod Swimmer. 55th IEEE Conference on Decision and Control, Sep 2016, Las Vegas, United States. hal-02483321

**HAL Id: hal-02483321**

**<https://inria.hal.science/hal-02483321>**

Submitted on 18 Feb 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# **Numerical Approach to the Optimal Control and Efficiency of the Copepod Swimmer.**

55th IEEE Conference on Decision and Control

Bernard Bonnard, Monique Chyba, Jérémy Rouot and Daisuke Takagi

- Geometric optimal control
  - . Maximum principle
  - . Second order optimality conditions (local, conjugate points)
- Swimming at low Reynolds number
  - . sub-Riemannian (SR) geometry framework
  - . Variational approach to find trajectories of a Hamiltonian system with periodic projections
  - . Find optimal stroke (efficiency concept)
  - . micro-device implementation (D. Takagi, M. Chyba)

$$\begin{array}{ll} \min & c(\tilde{q}(0), \tilde{q}(T)) \\ \text{subject to} & \dot{q} = F(q, u), \quad \dot{q}^0 = L(q, u) \\ & (\tilde{q}(0), \tilde{q}(T)) \in B \end{array}$$

- final time  $T$  is fixed
- $\tilde{q} = (q, q^0)$ ,  $q$  state,  $q^0 \in \mathbb{R}$
- $u(\cdot) \in L^\infty([0, T], U)$ ,  $U \subset \mathbb{R}^m$
- $B$  : smooth closed set of  $\mathbb{R}^n \times \mathbb{R}^n$ ,  $(\tilde{q}(0), \tilde{q}(T)) \in B$  stands for **mixed** boundary conditions.

Ex. :  $B = \{q(0) = q(T), q^0(0) = 0\}$ ,  
 $B = \{q(0) = q_0, q(T) = q_f, q^0(0) = 0\} \dots$

**Necessary condition.**  $(\tilde{q}, u)$  optimal  $\implies \exists \tilde{p} = (p, p^0) : [0, T] \rightarrow (\mathbb{R}^n \times \mathbb{R})$  abs. continuous and  $\lambda \geq 0$  cst with  $(\tilde{p}, \lambda) \neq (0, 0)$  and s.t.

$$\dot{\tilde{q}} = \frac{\partial H}{\partial \tilde{p}}, \quad \dot{\tilde{p}} = -\frac{\partial H}{\partial \tilde{q}}, \quad H(\tilde{q}, \tilde{p}, u) = \max_{v \in U} \mathcal{H}(\tilde{q}, \tilde{p}, v)$$



where  $\mathcal{H}(\tilde{q}, \tilde{p}, u) = p \cdot F(q, u) + p^0 L(q, u)$ .

**Transversality conditions:**


$$(\tilde{p}(0), -\tilde{p}(T)) - \lambda \left( \frac{\partial c}{\partial \tilde{q}(0)}(\tilde{q}(0), \tilde{q}(T)), \frac{\partial c}{\partial \tilde{q}(T)}(\tilde{q}(0), \tilde{q}(T)) \right) \in (T_{(\tilde{q}(0), \tilde{q}(T))} B)^\perp$$

**Definition 1.**  $(\tilde{q}, \tilde{p}, \lambda, u)$  is a normal extremal if  $\lambda > 0$ , abnormal if  $\lambda = 0$ . An abnormal trajectory  $q$  which is not a projection of normal extremal is said strict.


# LIFE AT LOW REYNOLDS NUMBER - PURCELL, 1977



Reynolds number




Swimmer deformations



Zooplankton

## Symmetric 2-link swimmer








## Controlled dynamic (Takagi, 2014)

$$\dot{x} = \frac{\sum_{i=1}^2 l^2 \dot{\theta}_i \sin(\theta_i)}{2 + \sum_{i=1}^2 \sin^2(\theta_i)}, \quad \dot{\theta}_i = u_i, \quad i = 1, 2, \quad \text{state constraints: } 0 \leq \theta_1 \leq \theta_2 \leq \pi.$$

**Criterion :** min of the dissipative energy:  $\dot{q}S(q)\dot{q}^\top$  where  $q = (x, \theta_1, \theta_2)$  and  $S$  is a positive-definite matrix  $\implies$  quadratic form in  $(u_1, u_2)$ .

**Definition 2.** An admissible stroke is a periodic motion of the shape variables  $(\theta_1, \theta_2)$  associated with a periodic control and producing a displacement of the position variable after one period  $T$  (we can fix  $T = 2\pi$ ).



(Left) Trigonometric controls. (Right) Piecewise controls.



$$\mathcal{E} = \text{Geometric Efficiency} = x(T)/l_{SR}(q)$$

SR length:

$$l_{SR}(q) = \int_0^T \sqrt{L(q, u)} dt, \quad L(q, u) = a(q) u_1^2 + 2b(q) u_1 u_2 + c(q) u_2^2$$

$$\min l_{SR}(q) \iff \min \int_0^T |\dot{q}|_L^2 dt = \min \int_0^T L(q, u) dt$$

With  $c(\tilde{q}(0), \tilde{q}(T)) = q^0(T)$  :

$$\dot{q} = \sum_{i=1}^2 u_i F_i \leftarrow \min \int_0^T L(q, u) dt,$$

$$\max \mathcal{E} \iff \left( \min \int_0^T L(q, u) dt \quad \text{with } \mathbf{x}(T) \text{ fixed, then } \underbrace{\text{select } \max_{x(T)} \mathcal{E}}_{\text{transversality cond.}} \right)$$

Compute points on the SR-sphere  $\rightarrow$   
provide candidates to maximize the efficiency.

$$\dot{q} = \sum_{i=1}^2 u_i F_i(q), \quad q = (x, \theta_1, \theta_2)$$

$$F_i = \frac{\sin(\theta_i)}{\Delta} \frac{\partial}{\partial x} + \frac{\partial}{\partial \theta_i}, \quad \Delta = 2 + \sin^2(\theta_1) + \sin^2(\theta_2)$$

**PMP:**

$$\mathcal{H}(z, u) = u_1 H_1(z) + u_2 H_2(z) + p^0 L(q, u), \quad z = (q, p)$$

with  $H_i = p \cdot F_i$ ,  $i = 1, 2$ .

- normal case:  $p^0 = -1/2$  and  $u_i$ ,  $i = 1, 2$  given by  $\partial \mathcal{H} / \partial u = 0$

$$H_n = 1/2 (a(q) H_1^2 + 2b(q) H_1 H_2 + c(q) H_2^2)$$


- abnormal case:  $p^0 = 0$  hence  $H_1 = H_2 = \{H_1, H_2\} = 0$ , then

$$u_1 \{ \{H_1, H_2\}, H_1 \} + u_2 \{ \{H_1, H_2\}, H_2 \} = 0.$$

**Proposition 3.** *The surface  $\Sigma : \{q; \det(F_1(q), F_2(q), [F_1, F_2](q)) = 0\}$  contains abnormal trajectories and is characterized by*

- $\theta_i = 0$  or  $\pi$ , for  $i = 1, 2$ ,
- $\theta_1 = \theta_2$ .

→ **physical boundary of the state domain.**:  $\theta_i \in [0, \pi]$ ,  $i = 1, 2$ ,  $\theta_1 \leq \theta_2$ .



: abnormal trajectories  
in the plane  $(\theta_1, \theta_2)$

## Boundary conditions defined by

$$x(0) = 0, \quad x(T) = x_f, \quad \theta_i(0) = \theta_i(T), \quad i = 1, 2$$

## Transversality conditions

$$p_{\theta_i}(0) = p_{\theta_i}(T), \quad i = 1, 2$$

## Shooting problem

$$\begin{cases} \dot{z} = \vec{H}_n(z) \\ x(0) = 0, \quad x(T) = x_f \text{ (fixed) } , \\ \theta_i(0) = \theta_i(T), \quad i = 1, 2 \\ p_{\theta_i}(0) = p_{\theta_i}(T), \quad i = 1, 2 \end{cases}$$


- HamPath *indirect method*: based on the PMP, *Newton* type algorithm and compute **necessary second order optimality conditions**, not robust w.r.t. initialization.
- Bocop *direct method*: give an initialization of the shooting algorithm of the HamPath code.





**First conjugate time  $t_c$ :** the exponential mapping





$$\exp_{q_0} : \mathbb{R} \times \mathcal{C} \rightarrow M, \quad (t, p_0) \mapsto q(t, q_0, p_0)$$

is not an immersion at  $(t_c, p_0)$ .

**Theorem 4.** *Let  $q : [0, T] \rightarrow \mathbb{R}^n$  a strict normal stroke. If  $q(\cdot)$  has at least one conjugate point on  $]0, T[$ , then  $q$  is not a local minimizer for the  $L^\infty$  topology on controls, considering the fixed extremities problem.*








### Numerical fact:

Only simple loops doesn't have a conjugate point on  $]0, T[$ : they are the only candidates for optimality.

**Theorem 5** (Numerical result). *For each fixed displacement  $x(T)$ , one can find a simple loop associated with an energy level  $\implies$  one parameter family of strokes.*







# SELECT A STROKE WITH TRANSVERSALITY CONDITIONS.

Geometric efficiency,  $c(\tilde{q}(0), \tilde{q}(T)) = -x(T) / l_{SR}(\tilde{q})$

**Transversality conditions.**

$$p_x(T) = q^0(T)/x(T), \quad p^0(T) = -1/2$$



Efficiency curve with continuation method on  $x(T)$ . Corresponding optimal stroke

**Theorem 6.** *The abnormal stroke is not minimizing for the two costs (length with fixed displacement and geometric efficiency).*

- More general models,
- Local geometric study

## Nilpotent model

$$\dot{x} = u_1 \hat{F}_1 + u_2 \hat{F}_2, \quad \min \int_0^T (u_1^2 + u_2^2) dt$$

- **Interior point of the triangle:** weights  $x_1, x_2 \leftarrow 1, x_3 \leftarrow 2$

$$\hat{F}_1 = \frac{\partial}{\partial x_1} + x_2 (1 + Q(x_1, x_2)) \frac{\partial}{\partial x_3}, \quad \hat{F}_2 = \frac{\partial}{\partial x_2} - x_1 (1 + Q(x_1, x_2)) \frac{\partial}{\partial x_3}$$

$\implies$  simple loops and limaçons families

- **Point on the edges and  $\neq$  vertices of the triangle:** weights  $x_1, x_2 \leftarrow 1, x_3 \leftarrow 3$

$$\hat{F}_1 = \frac{\partial}{\partial x_1} + \frac{x_2^2}{2} \frac{\partial}{\partial x_3}, \quad \hat{F}_2 = \frac{\partial}{\partial x_2}.$$

metric :  $g = (1 + \alpha x_2)^2 dx_1 + (1 + \beta x_1 + \gamma x_2)^2 dx_2.$

$\implies$  eight strokes

