



**HAL**  
open science

# A Simple and Fast Algorithm for Computing the $N$ -th Term of a Linearly Recurrent Sequence

Alin Bostan, Ryuhei Mori

► **To cite this version:**

Alin Bostan, Ryuhei Mori. A Simple and Fast Algorithm for Computing the  $N$ -th Term of a Linearly Recurrent Sequence. SOSA'21 (SIAM Symposium on Simplicity in Algorithms), Jan 2021, Alexandria, United States. hal-02917827v1

**HAL Id: hal-02917827**

**<https://inria.hal.science/hal-02917827v1>**

Submitted on 19 Aug 2020 (v1), last revised 21 Dec 2020 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# A Simple and Fast Algorithm for Computing the $N$ -th Term of a Linearly Recurrent Sequence

Alin Bostan<sup>\*</sup> and Ryuhei Mori<sup>†</sup>

<sup>\*</sup>Inria, Palaiseau, France and <sup>†</sup>Tokyo Institute of Technology, Japan  
[alin.bostan@inria.fr](mailto:alin.bostan@inria.fr), [mori@c.titech.ac.jp](mailto:mori@c.titech.ac.jp)

August 19, 2020

## Abstract

We present a simple and fast algorithm for computing the  $N$ -th term of a given linearly recurrent sequence. Our new algorithm uses  $O(M(d) \log N)$  arithmetic operations, where  $d$  is the order of the recurrence, and  $M(d)$  denotes the number of arithmetic operations for computing the product of two polynomials of degree  $d$ . The state-of-the-art algorithm, due to Charles Fiduccia (1985), has the same arithmetic complexity up to a constant factor. Our algorithm is simpler, faster and obtained by a totally different method. We also discuss several algorithmic applications, notably to polynomial modular exponentiation, powering of matrices and high-order lifting.

**Keywords:** Algebraic Algorithms; Computational Complexity; Linearly Recurrent Sequence; Rational Power Series; Fast Fourier Transform

## 1 Introduction

### 1.1 General context

Computing efficiently selected terms in sequences is a basic and fundamental algorithmic problem, whose applications are ubiquitous, for instance in theoretical computer science [65, 49], algebraic complexity theory [59, 73], computer algebra [28, 71, 48], cryptography [31, 32, 29, 33], algorithmic number theory [72, 1], effective algebraic geometry [12, 36], numerical analysis [52, 51] and computational biology [56].

In simple terms, the problem can be formulated as follows:

---

Given a sequence  $(u_n)_{n \geq 0}$  in an effective ring<sup>0</sup>  $R$ , and given a positive integer  $N \in \mathbb{N}$ , compute the term  $u_N$  as fast as possible.

---

Here, the input  $(u_n)_{n \geq 0} \in R^{\mathbb{N}}$  is assumed to be a recurrent sequence, specified by a data structure consisting in a *recurrence relation* and sufficiently many *initial terms* that uniquely determine the sequence  $(u_n)_{n \geq 0}$ .

Efficiency is measured in terms of *ring operations* (algebraic model), or of *bit operations* (Turing machine model). The cost of an algorithm is respectively estimated in terms of *arithmetic complexity* or of *binary complexity*. Both measures have their own usefulness: the algebraic model is relevant when ring operations have essentially unit cost (typically, when  $R$  is a finite ring such as the prime field  $\mathbb{F}_p := \mathbb{Z}/p\mathbb{Z}$ ), while the bit complexity model is relevant when elements of  $R$  have a variable bitsize, and thus ring operations in  $R$  have variable cost (typically, when  $R$  is the ring  $\mathbb{Z}$  of integer numbers).

The recurrence relation satisfied by the input sequence  $(u_n)_{n \geq 0}$  might be of several types:

(C) *linear with constant coefficients*, that is of the form,

$$u_{n+d} = c_{d-1}u_{n+d-1} + \cdots + c_0u_n, \quad n \geq 0,$$

for some given coefficients  $c_0, \dots, c_{d-1}$  in  $R$ . In this case we simply say that the sequence is *linearly recurrent* (or, *C-recursive*). The most basic examples are the **geometric** sequence  $(q^n)_{n \geq 0}$ , for  $q \in R$ , and the **Fibonacci** sequence  $(F_n)_n$  with  $F_{n+2} = F_{n+1} + F_n$  and  $F_0 = 0, F_1 = 1$ .

(P) *linear with polynomial coefficients*, that is of the form,

$$u_{n+d} = c_{d-1}(n)u_{n+d-1} + \cdots + c_0(n)u_n, \quad n \geq 0,$$

for some given rational functions  $c_0(x), \dots, c_{d-1}(x)$  in  $R(x)$ . In this case the sequence is called *holonomic* (or, *P-recursive*). Among the most basic examples, other than the C-recursive ones, there is the **factorial** sequence  $(n!)_{n \geq 0} = (1, 1, 2, 6, 24, 120, \dots)$  and the **Motzkin** sequence  $(u_n)_{n \geq 0} = (1, 1, 2, 4, 9, 21, 51, \dots)$  specified by the recurrence  $u_{n+1} = \frac{2n+3}{n+3} \cdot u_n + \frac{3n}{n+3} \cdot u_{n-1}$  and the initial conditions  $u_0 = u_1 = 1$ .

---

<sup>0</sup>The ring  $R$  is assumed to be commutative with unity and *effective* in the sense that its elements are represented using some data structure, and there exist algorithms for performing the basic ring operations  $(+, -, \times)$  and for testing equality of elements in  $R$ .

(Q) *linear with polynomial coefficients in  $q$  and  $q^n$* , that is of the form,

$$u_{n+d} = c_{d-1}(q, q^n)u_{n+d-1} + \cdots + c_0(q, q^n)u_n, \quad n \geq 0,$$

for some  $q \in R$  and some rational functions  $c_0(x, y), \dots, c_{d-1}(x, y)$  in  $R(x, y)$ . In this case, the sequence is called  *$q$ -holonomic*; such a sequence can be seen as a  $q$ -deformation of a holonomic sequence (in the sense that when  $q \mapsto 1$ , the limit sequence tends to be holonomic). A typical example is the  **$q$ -factorial**  $[n]_q! := (1+q)\cdots(1+q+\cdots+q^{n-1})$ .

In all these classes of examples, the recurrence is *linear*, and the integer  $d$  that governs the length of the recurrence relation is called the *order* of the corresponding linear recurrence.

Of course, some interesting sequences satisfy *nonlinear* recurrences, as is the case for the so-called **Somos-4** sequence  $(1, 1, 1, 1, 2, 3, 7, 23, 59, \dots)$  defined by:  $u_{n+4} = (u_{n+3}u_{n+1} + u_{n+2}^2)/u_n$  together with  $u_0 = \cdots = u_3 = 1$ , but we will not consider this larger class in what follows.

For computing the  $N$ -th term  $u_N$  in a sequence of type (P), resp. (Q), the best known algorithms are presented in [16, 12], resp. in [9]. In the algebraic model, they rely on an algorithmic technique called *baby-step / giant-step*, which allows to compute  $u_N$  using a number of operations in  $R$  that is almost linear in  $\sqrt{N}$ , up to logarithmic factors. This should be contrasted with the direct iterative algorithm, of arithmetic complexity linear in  $N$ .

In the bit model, the same references provide different algorithms based on a different technique, called *binary splitting*; these algorithms are *quasi-optimal* in the sense that they are able to compute  $u_N$  in a number of bit operations almost linear (up to logarithmic factors) in the bitsize of the output value  $u_N$ . Once again, this should be contrasted with the direct iterative algorithm, whose binary complexity is larger by at least one order of magnitude (e.g., in case (P) the naive algorithm has bit complexity  $O(N^3)$ ).

## 1.2 The case of C-recursive sequences

In what follows, we will restrict our attention to the case (C) only. This case obviously is a subcase of both cases (P) and (Q). It presents an exceptional feature with respect to the algebraic model: contrary to the general cases (P) and (Q), in case (C) it is possible to compute the term  $u_N$  using a number of arithmetic operations in  $R$  that is only logarithmic in  $N$ .

For the geometric sequence  $u_n = q^n$ , this is known since Pingala ( $\sim 200$  BC) who seemingly is the inventor of the algorithmic method of *binary powering*,

or *square-and-multiply* [46, §4.6.3]. The corresponding algorithm is recursive and based on the equalities

$$q^N = \begin{cases} (q^{N/2})^2, & \text{if } N \text{ is even,} \\ q \cdot (q^{\frac{N-1}{2}})^2, & \text{else.} \end{cases}$$

The arithmetic complexity of this algorithm is bounded by  $2 \log N$  multiplications<sup>1</sup> in  $R$ , which represents a tremendous improvement compared to the naive iterative algorithm that computes the term  $q^N$  in  $N - 1$  multiplications in  $R$ , by simply unrolling the recurrence  $u_{n+1} = q \cdot u_n$  with  $q_0 = 1$ .

In the general case (C), Miller and Spencer Brown showed in 1966 [54] that a similar complexity can be obtained by converting<sup>2</sup> the scalar recurrence of order  $d$

$$u_{n+d} = c_{d-1}u_{n+d-1} + \cdots + c_0u_n, \quad n \geq 0, \quad (1)$$

into a vector recurrence of order 1

$$\underbrace{\begin{bmatrix} u_n \\ u_{n+1} \\ \vdots \\ u_{n+d-1} \end{bmatrix}}_{v_n} = \underbrace{\begin{bmatrix} 1 & & & \\ & \ddots & & \\ & & \ddots & \\ c_0 & c_1 & \cdots & c_{d-1} \end{bmatrix}}_M \times \underbrace{\begin{bmatrix} u_{n-1} \\ u_n \\ \vdots \\ u_{n+d-2} \end{bmatrix}}_{v_{n-1}}, \quad n \geq 1, \quad (2)$$

and by using binary powering in the ring  $\mathcal{M}_d(R)$ , of  $d \times d$  matrices with coefficients in  $R$ , in order to compute  $M^N$  recursively by

$$M^N = \begin{cases} (M^{N/2})^2, & \text{if } N \text{ is even,} \\ M \cdot (M^{\frac{N-1}{2}})^2, & \text{else.} \end{cases}$$

From there,  $u_N$  can be read off the matrix-vector product  $v_N = M^N \cdot v_0$ . The arithmetic complexity of this method is  $O(d^\theta \log N)$  operations in  $R$ , where  $\theta \in [2, 3]$  is any feasible exponent for matrix multiplication in  $\mathcal{M}_d(R)$ .

Strangely enough, the paper [54] of Miller and Spencer Brown was largely overlooked in the subsequent literature, and their result has been rediscovered several times in the 1980s. For instance, Shortt [68] proposed a

<sup>1</sup>In all this article, the notation  $\log$  refers to the logarithm in base 2.

<sup>2</sup>In [15, p. 74], the authors call this *un truc bien connu* (“a well-known trick”).

$O(\log N)$  algorithm for computing the  $N$ -th Fibonacci number<sup>3,4</sup> and extended it together with Wilson [76] to the computation of order- $d$  Fibonacci numbers in  $O(d^3 \log N)$  arithmetic operations. The same cost has also been obtained by Dijkstra [21] and Urbanek [75]. Pettorossi [60], and independently Gries and Levin [34], improved the algorithm and lowered the cost to  $O(d^2 \log N)$ , essentially by taking into account the sparse structure of the matrix  $M$ . See also [22, 50, 23, 24, 39, 63, 30, 44] for similar algorithms.

### 1.3 Fiduccia’s algorithm

The currently best algorithm is due to Fiduccia<sup>5</sup> [26]. It is based on the following observation: the matrix  $M$  in (2) is the transpose of the companion matrix  $C$  which represents the  $R$ -linear multiplication-by- $x$  map from the quotient ring  $R[x]/(\Gamma)$  to itself, where  $\Gamma = x^d - \sum_{i=0}^{d-1} c_i x^i$ . Therefore, denoting by  $e$  the row vector  $e = [1 \ 0 \ \dots \ 0]$ , the  $N$ -th term  $u_N$  equals

$$u_N = e \cdot v_N = e \cdot M^N \cdot v_0 = (C^N \cdot e^T)^T \cdot v_0 = \langle x^N \bmod \Gamma, v_0 \rangle, \quad (3)$$

where the inner product takes place between the vector  $v_0 = [u_0 \ \dots \ u_{d-1}]$  of initial terms of  $(u_n)_{n \geq 0}$ , and the vector whose entries are the coefficients of the remainder  $(x^N \bmod \Gamma)$  of the Euclidean division of  $x^N$  by  $\Gamma$ .

Therefore, computing  $u_N$  is reduced to computing the coefficients of  $(x^N \bmod \Gamma)$ , and this can be performed efficiently by using binary powering in the quotient ring  $A := R[x]/(\Gamma)$ , at the cost of  $O(\log N)$  multiplications in  $A$ . Each multiplication in  $A$  may be performed using  $O(M(d))$  operations in  $R$  [27, Ch. 9, Corollary 9.7], where  $M(d)$  denotes the arithmetic cost of

---

<sup>3</sup>Shortt’s algorithm had actually appeared before, in the 1969 edition of Knuth’s book [45, p. 552], as a solution of Ex. 26 (p. 421, §4.6.3). The algorithm is based on the so-called *doubling formulas*  $(F_{2n}, F_{2n-1}) = (F_n^2 + 2F_n F_{n-1}, F_n^2 + F_{n-1}^2)$ , actually due to Lucas (1876) and Catalan (1886), see e.g. [20, Ch. XVII]. The currently best implementation for computing  $F_N$  over  $\mathbb{Z}$  (`mpz_fib_ui` from `GMP`) uses a variant of this method, requiring just two squares (and a few additions) per binary digit of  $N$ .

<sup>4</sup>Already in 1899, G. de Rocquigny asked “for an expeditious procedure to compute a very distant term of the Fibonacci sequence” [19]. In response, several methods (including the one mentioned by Knuth in [45, p. 552]) have been published one year later by Rosace (alias), E.-B. Escott, E. Malo, C.-A. Laisant and G. Picou [66]. This fact does not seem to have been noticed in the modern algorithmic literature before the current paper, although the reference [66] is mentioned in Dickson’s formidable book [20, p. 404].

<sup>5</sup>The idea already appears in the 1982 conference paper [25]. We have discovered that the same algorithm had been sketched by D. Knuth in the corrections/changes to [46] published in 1981 in [47, p. 28], where he attributes the result to R. Brent. Almost surely, C. Fiduccia was not aware about this fact.

polynomial multiplication in  $R[x]$  in degree  $d$ . Using Fast Fourier Transform (FFT) methods, one may take  $M(d) = O(d \log d)$  when  $R$  contains enough roots of unity, and  $M(d) = O(d \log d \log \log d)$  in general [27, Ch. 8].

In conclusion, Fiduccia’s algorithm allows the computation of the  $N$ -th term  $u_N$  of a linearly recurrent sequence of order  $d$  using  $O(M(d) \log N)$  operations in  $R$ . Since 1985, this is the state-of-the-art algorithm for this task in case (C).

A closer inspection of the proof of [27, Corollary 9.7] shows that a more precise estimate for the arithmetic cost of Fiduccia’s algorithm is

$$F(N, d) = 3M(d) \lceil \log N \rceil + O(d \log N) \quad (4)$$

operations in  $R$ . This comes from the fact that squaring<sup>6</sup> in  $A = R[x]/(\Gamma)$  is based on one polynomial multiplication in degree less than  $d$  followed by an Euclidean division by  $\Gamma$  of a polynomial of degree less than  $2d$ . The Euclidean division is reduced to a power series division by the reversal  $Q(x) := x^d \cdot \Gamma(1/x)$  of  $\Gamma$ , followed by a polynomial multiplication in degree less than  $d$ . The reciprocal of  $Q(x)$  is precomputed modulo  $x^d$  once and for all (using a formal Newton iteration) in  $3M(d) + O(d)$  operations in  $R$ , and then each squaring in  $A$  also takes  $3M(d) + O(d)$  operations in  $R$ . The announced cost from (4) follows from the fact that binary powering uses  $\lceil \log N \rceil$  squarings and at most  $\lceil \log N \rceil$  multiplications by  $x$ .

## 1.4 Main results

We propose in this paper a new and simpler algorithm, with a better cost. More precisely, our first main complexity result is:

**Theorem 1.** *One can compute the  $N$ -th term of a linearly recurrent sequence of order  $d$  with coefficients in a ring  $R$  using*

$$T(N, d) = 2M(d) \lceil \log(N + 1) \rceil + M(d)$$

*arithmetic operations in  $R$ .*

The proof of this result is based on a very natural algorithm, which will be presented in Section 2.1. Let us remark that it improves by a factor of 1.5 the complexity of Fiduccia’s algorithm.

This factor is even higher in the FFT setting, where polynomial multiplication is assumed to be performed using Fast Fourier Transform techniques. In this setting, we obtain the following complexity result, which will be proved in Section 4.

---

<sup>6</sup>Note that multiplying by  $x$  in  $A$  is much easier and has linear arithmetic cost  $O(d)$ .

**Theorem 2.** *One can compute the  $N$ -th term of a linearly recurrent sequence of order  $d$  with coefficients in a field  $\mathbb{K}$  supporting FFT using*

$$\sim \frac{2}{3} M(d) \log(N)$$

*arithmetic operations in  $\mathbb{K}$ .*

Algorithms 1 and 2 (underlying Theorem 1) and Algorithm 11 (underlying Theorem 2) are both of LSB-first (least significant bit first) type. This prevents them from computing simultaneously *several* consecutive terms of high indices, such as  $u_N, \dots, u_{N+d-1}$ . This makes a notable difference with Fiduccia’s algorithm from §1.3. For this reason, we will design a second algorithm, of MSB-first (most significant bit first) type, by “transposing” Algorithm 1. This leads to the following complexity result.

**Theorem 3.** *One can compute the terms of indices  $N - d + 1, \dots, N$  of a linearly recurrent sequence of order  $d$  with coefficients in a ring  $R$  using*

$$2 M(d) \lceil \log(N + 1) \rceil + O(M(d))$$

*arithmetic operations in  $R$ .*

The method underlying this complexity result is based on Algorithms 5, 6 and 8, which are presented in Section 3. Along the way, using the MSB-first Algorithm 5, we improve the cost of *polynomial modular exponentiation*, which is a central algorithmic task in computer algebra, with many applications. Since this result has an interest *per se*, we isolate it here as our last complexity result.

**Theorem 4.** *Given  $N \in \mathbb{N}$  and a polynomial  $\Gamma(x)$  in  $R[x]$  of degree  $d$ , one can compute  $x^N \bmod \Gamma(x)$  using*

$$2 M(d) \lceil \log(N + 1) \rceil + M(d)$$

*arithmetic operations in  $R$ .*

This cost of  $\sim 2 M(d) \log N$  compares favorably with the currently best estimate of  $\sim 3 M(d) \log N$  obtained by square-and-multiply in the quotient ring  $R[x]/(\Gamma(x))$ , combined with fast modular multiplications performed either classically [27, Corollary 9.7], or using Montgomery’s algorithm [55]. In the FFT setting, the gain is even larger, and our results improve on the best estimates, due to Mihăilescu [53].



## 1.5 Structure of the paper

In Section 2 we propose our LSB-first (least significant bit first) algorithm for computing the  $N$ -th term of a C-recursive sequence. We design in Section 3 a second algorithm, which is an MSB-first (most significant bit first) variant, and discuss several algorithmic applications, including polynomial modular exponentiation, powering of matrices and high-order lifting. In Section 4 we specialize and analyze Algorithm 1 in the specific FFT setting, where polynomial multiplication is based on Discrete Fourier Transform techniques, and we compare it with the FFT-based Fiduccia's algorithm. We conclude in Section 5 by a summary of results and plans of future work.

## 2 The LSB-first algorithm and applications

We will prove Theorem 1 in §2.1, where we propose the first main algorithms (Algorithms 1 and 2), which are faster than Fiduccia's algorithm. Then, in §2.2 we instantiate them in the particular case of the Fibonacci sequence. The resulting algorithm is competitive with state-of-the-art algorithms.

### 2.1 The LSB-first algorithm: Proof of Theorem 1

The algorithm underlying Theorem 1 is very natural. Let us sketch now its main idea.

First, it is classical [64] that the generating functions of linearly recurrent sequences are *rational*. As a consequence, computing terms of a linearly recurrent sequence is equivalent to computing coefficients in the power series expansion (at the origin) of a rational function. More precisely, let us attach to the recurrence (1) the polynomial  $Q(x) := 1 - c_{d-1}x - \dots - c_0x^d$ , that is the reversal of the characteristic polynomial  $\Gamma(x) = x^d - \sum_{i=0}^{d-1} c_i x^i$  of recurrence (1). Let us denote by  $F(x)$  the generating function of the sequence  $(u_n)_{n \geq 0}$ ,

$$F(x) := \sum_{n \geq 0} u_n x^n.$$

Then, there exists a polynomial  $P(x)$  in  $R[x]$  of degree less than  $d$  such that  $F(x) = P(x)/Q(x)$  in  $R[[x]]$ . This is immediately seen by checking that, for any  $n \geq 0$ , the coefficient of  $x^{n+d}$  in the power series  $P(x) := Q(x) \cdot F(x)$  is equal to  $u_{n+d} - c_{d-1}u_{n+d-1} - \dots - c_0u_n$ , hence it is zero by (1), and therefore the power series  $P(x)$  is in fact a polynomial of degree less than  $d$ . Moreover, the coefficients of  $P(x)$  can be determined from the recurrence (1) and from the initial terms  $u_0, \dots, u_{d-1}$  by using  $M(d)$  operations in  $R$ .

We are thus reduced to the question of determining the  $N$ -th coefficient  $u_N$  of the rational power series  $F(x) = P(x)/Q(x)$ . Our new algorithm is based on the following observation. The polynomial  $Q(x)Q(-x)$  is even, so it writes  $V(x^2)$  for some  $V \in R[x]$  of degree  $d$ . Then, denoting by  $U(x)$  the polynomial  $P(x)Q(-x)$ , of degree less than  $2d$ , and by  $U_e$  and  $U_o$  the even and the odd parts of  $U$ , that is  $U(x) = U_e(x^2) + x \cdot U_o(x^2)$ , we have

$$\frac{P(x)}{Q(x)} = \frac{P(x)Q(-x)}{Q(x)Q(-x)} = \frac{U_e(x^2)}{V(x^2)} + x \cdot \frac{U_o(x^2)}{V(x^2)},$$

which implies that the  $N$ -th coefficient in the series expansion of  $P/Q$  is

$$[x^N] \frac{P(x)}{Q(x)} = \begin{cases} [x^{\frac{N}{2}}] \frac{U_e(x)}{V(x)}, & \text{if } N \text{ is even,} \\ [x^{\frac{N-1}{2}}] \frac{U_o(x)}{V(x)}, & \text{else.} \end{cases}$$

In other words, the problem of computing the  $N$ -th term of a rational function  $P/Q$  of degree  $d$  is reduced to that of computing the term of index  $\lfloor N/2 \rfloor$  of another rational function of degree  $d$ , that can be deduced from  $P/Q$  by using two polynomial multiplications in degree  $d$ . The desired coefficient  $u_N$  is computed after repeating this process at most  $\lceil \log(N+1) \rceil$  times, and the complexity estimate in Theorem 1 is easily deduced.

Notice that, by the duality between linearly recurrent sequences and rational functions, the new algorithm admits a nice and simple interpretation directly at the level of recurrences. The sequence  $(u_n)_{n \geq 0}$  is determined by the recurrence (1) (encoded by the denominator  $Q(x)$ ) and by the initial conditions  $u_0, \dots, u_{d-1}$  (encoded by the numerator  $P(x)$ ). To compute the  $N$ -th coefficient  $u_N$ , the new method builds a different recurrence (encoded by  $V(x) = Q(\sqrt{x})Q(-\sqrt{x})$ ) still with constant coefficients and of the same order  $d$ , together with new initial conditions (encoded by  $P(x)Q(-x)$ )<sup>7</sup>. Computing  $u_N$  is thus reduced to computing the term of index  $\lfloor N/2 \rfloor$  of the new sequence; and this reduction is applied at most  $\lceil \log(N+1) \rceil$  times.

The proposed algorithm for computing  $[x^N]P(x)/Q(x)$  is summarized in Algorithm 1, and its immediate consequence for computing the  $N$ -th term of the linearly recurrent sequence  $(u_n)_{n \geq 0}$  defined by eq. (1) is displayed in Algorithm 2. Algorithm 1 has complexity  $2M(d)\lceil \log(N+1) \rceil$  and Algorithm 2 has complexity  $2M(d)\lceil \log(N+1) \rceil + M(d)$ , which proves in Theorem 1.

Note that Algorithms 1 and 2 use an idea similar to the ones in [11, 10] which were dedicated to the larger class of algebraic power series, but

---

<sup>7</sup>In fact, the new sequence consists of the even (or odd) terms of the original sequence.

---

**Algorithm 1 (OneCoeff)**    **Input:**  $P(x), Q(x), N$     **Output:**  $[x^N] \frac{P(x)}{Q(x)}$

---

**Assumptions:**  $Q(0)$  invertible and  $\deg(P) < \deg(Q) =: d$

```

1: while  $N \geq 1$  do
2:    $U(x) \leftarrow P(x)Q(-x)$   $\triangleright U = \sum_{i=0}^{2d-1} U_i x^i$ 
3:   if  $N$  is even then
4:      $P(x) \leftarrow \sum_{i=0}^{d-1} U_{2i} x^i$ 
5:   else
6:      $P(x) \leftarrow \sum_{i=0}^{d-1} U_{2i+1} x^i$ 
7:    $A(x) \leftarrow Q(x)Q(-x)$   $\triangleright A = \sum_{i=0}^{2d} A_i x^i$ 
8:    $Q(x) \leftarrow \sum_{i=0}^d A_{2i} x^i$ 
9:    $N \leftarrow \lfloor N/2 \rfloor$ 
10: return  $P(0)/Q(0)$ 

```

---

**Algorithm 2 (OneTerm)**    **Input:** rec. (1),  $u_0, \dots, u_{d-1}, N$     **Output:**  $u_N$

---

**Assumptions:**  $\Gamma(x) = x^d - \sum_{i=0}^{d-1} c_i x^i$  with  $c_0 \neq 0$

```

1:  $Q(x) \leftarrow x^d \Gamma(1/x)$ 
2:  $P(x) \leftarrow (u_0 + \dots + u_{d-1} x^{d-1}) \cdot Q(x) \bmod x^d$ 
3: return  $[x^N] P(x)/Q(x)$   $\triangleright$  using Algorithm 1

```

---

restricted to positive characteristic only. Algorithm 1 also shares common features with the technique of *section operators* [2, Lemma 4.1] used by Allouche and Shallit to compute the  $N$ -th term of  $k$ -regular sequences [2, Corollary 4.5] in  $O(\log N)$  ring operations.

Algorithm 1 can be interpreted at the level of recurrences as computing  $\sim \log N$  new recurrences produced by the Graeffe process, which is a classical technique to compute the largest root of a real polynomial [40, 57, 58]. Interestingly, the Graeffe process has been used in a purely algebraic context by Schönhage in [67, §3] for computing the reciprocal of a power series, see also [14, §2]. However, our paper seems to be the first reference where the Graeffe process and the section operators approach are combined together.

## 2.2 New algorithm for Fibonacci numbers

To illustrate the mechanism of Algorithm 1, let us instantiate it in the particular case of the Fibonacci sequence defined by

$$F_0 = 0, F_1 = 1, \quad F_{n+2} = F_{n+1} + F_n, \quad n \geq 0.$$

---

**Algorithm 3 (NewFibonacci)**    **Input:**  $N$     **Output:**  $F_N$

---

**Assumptions:**  $N \geq 2$

```

1:  $c \leftarrow 3$ 
2: if  $N$  is even then
3:    $[a, b] \leftarrow [0, 1]$ 
4: else
5:    $[a, b] \leftarrow [1, -1]$ 
6:  $N \leftarrow \lfloor N/2 \rfloor$ 
7: while  $N > 1$  do
8:   if  $N$  is even then
9:      $b \leftarrow a + b \cdot c$ 
10:  else
11:     $a \leftarrow b + a \cdot c$ 
12:     $c \leftarrow c^2 - 2$ 
13:     $N \leftarrow \lfloor N/2 \rfloor$ 
14: return  $b + a \cdot c$ 

```

---

The generating function  $\sum_{n \geq 0} F_n x^n$  equals  $x/(1 - x - x^2)$ . Therefore, the coefficient  $F_N$  is equal to

$$[x^N] \frac{x}{1 - x - x^2} = [x^N] \frac{x(1 + x - x^2)}{1 - 3x^2 + x^4} = \begin{cases} [x^{\frac{N}{2}}] \frac{x}{1 - 3x + x^2}, & \text{if } N \text{ is even,} \\ [x^{\frac{N-1}{2}}] \frac{1-x}{1 - 3x + x^2}, & \text{else.} \end{cases}$$

The computation of  $F_N$  is reduced to that of a coefficient of the form

$$[x^N] \frac{a + bx}{1 - cx + x^2} = [x^N] \frac{(a + bx)(1 + cx + x^2)}{1 - (c^2 - 2)x^2 + x^4} = \begin{cases} [x^{\frac{N}{2}}] \frac{a + (bc+a)x}{1 - (c^2 - 2)x + x^2}, & \text{if } N \text{ is even,} \\ [x^{\frac{N-1}{2}}] \frac{(ac+b) + bx}{1 - (c^2 - 2)x + x^2}, & \text{else.} \end{cases}$$

This yields Algorithm 3 for the computation of  $F_N$ <sup>8</sup>. A close inspection reveals that this algorithm computes  $F_N$  by a recursive use of the formula

$$F_N = L_{2 \lfloor \log N \rfloor} \cdot F_{N - 2 \lfloor \log N \rfloor} + (-1)^N \cdot F_{2^{1 + \lfloor \log N \rfloor} - N},$$

which is a particular instance of the classical formula

$$F_{n+m} = L_m F_n + (-1)^n F_{m-n}$$

---

<sup>8</sup>Notice that the same algorithm can be used to compute efficiently the  $N$ -th Fibonacci polynomial, or the  $N$ -th Chebychev polynomial. Fibonacci polynomials in  $R[t]$  are defined by  $F_{n+2}(t) = t \cdot F_{n+1}(t) + F_n(t)$  with  $F_0(t) = 1$  and  $F_1(t) = t$ . It is sufficient to initialize  $c$  to  $t^2 + 2$  (instead of 3) and  $b$  to  $t$  when  $N$  is even (instead of 0). The complexity of this algorithm is  $O(M(N))$  operations in  $R$ , which is quasi-optimal.

---

**Algorithm 4**    **Input:**  $N$     **Output:**  $F_N$

---

**Assumptions:**  $N \geq 2$  and  $N$  is a power of 2

```

1:  $[b, c] \leftarrow [1, 3]$ 
2:  $N \leftarrow \lfloor N/2 \rfloor$ 
3: while  $N > 2$  do
4:    $b \leftarrow b \cdot c$ 
5:    $c \leftarrow c^2 - 2$ 
6:    $N \leftarrow \lfloor N/2 \rfloor$ 
7: return  $b \cdot c$ 

```

---

relating the Fibonacci numbers and the Lucas numbers  $L_n = F_{n+1} + F_{n-1}$ .

When  $N$  is a power of 2, then Algorithm 3 degenerates into Algorithm 4. This is equivalent to Algorithm `fib`( $n$ ) in [18, Fig. 6]<sup>9</sup>. It uses  $2 \log(N) - 3$  products (of which  $\log(N) - 2$  are squarings) and  $\log(N) - 2$  subtractions.

When  $N$  is arbitrary, Algorithm 3 has essentially the same cost: it uses at most  $2 \log(N) - 1$  products (of which at most  $\log(N) - 1$  are squarings) and  $2 \lfloor \log(N) \rfloor - 1$  additions/subtractions. In contrast, [18, Fig. 6] uses a more complex algorithm, with higher cost. An example of execution of our Algorithm 3 for computing  $F_{43}$  is explicitly displayed in Table 1.

A nice feature of Algorithm 3 is not only that it is simple and natural, but also that its arithmetic and bit complexity matches the complexity of the state-of-art algorithms for computing Fibonacci numbers [74].

$N$	$a$	$b$	$c$
21	1	-1	3
10	$1 \times 3 - 1 = 2$		$3^2 - 2 = 7$
5		$(-1) \times 7 + 2 = -5$	$7^2 - 2 = 47$
2	$2 \times 47 - 5 = 89$		$47^2 - 2 = 2207$
1		$(-5) \times 2207 + 89$ $= -10946$	$2207^2 - 2 = 4870847$
0	$89 \times 4870847 - 10946$ $= 433494437$		

Table 1: Computation of  $F_{43} = 433494437$  using the new algorithm.

---

<sup>9</sup>This algorithm had also appeared before, in Knuth's book [45, p. 552, second solution].

### 3 The MSB-first algorithm and applications

We present in §3.1 a “most significant bit” (MSB) variant (Algorithm 5) of Algorithm 1. Then we discuss various applications of Algorithms 1 and 5. In §3.2 we design a faster algorithm for polynomial modular exponentiation, that we use in §3.3 to design a faster Fiduccia-like algorithm for computing a slice of  $d$  terms of indices  $N - d + 1, \dots, N$  in  $\sim 2 M(d) \log N$  operations.

#### 3.1 The MSB-first algorithm

In Fiduccia’s algorithm (§1.3), the  $N$ -th coefficient  $u_N$  in the power series expansion  $\sum_{i \geq 0} u_i x^i$  of  $P/Q$  is given by the inner product  $\langle x^N \bmod \Gamma(x), v_0 \rangle$ , where  $\Gamma$  is the reversal polynomial of  $Q$  and  $v_0$  is the vector of initial coefficients  $[u_0 \ \dots \ u_{d-1}]$ . Here,  $x^N \bmod \Gamma(x)$  depends only on the linear recurrence equation (1), and is independent of the initial terms  $v_0$ . Hence, if we want to compute the  $N$ -th terms of  $k$  different linearly recurrent sequences that share the same linear recurrence equation (1), we can first determine  $\rho(x) := x^N \bmod \Gamma(x)$ , and then  $\langle \rho, v_0^{(i)} \rangle$  for  $i = 1, \dots, k$ , where  $v_0^{(i)}$  denotes the vector of  $d$  initial terms of the  $i$ -th sequence. The total arithmetic complexity of this algorithm is  $O(M(d) \log N + kd)$ ; this is faster than Fiduccia’s algorithm repeated independently  $k$  times, with cost  $O(k M(d) \log N)$ .

On the other hand, in Algorithm 1, we iteratively update both the denominator and the numerator, and each new numerator depends on the original numerator  $P(x)$  which encodes the initial  $d$  terms of the sequence. Hence, it is not a priori clear how to obtain with Algorithm 1 the good feature of Fiduccia’s algorithm mentioned above.

In this section, we present an algorithm that computes  $u_N$  with arithmetic complexity equal to that of Algorithm 1 and which, in addition, achieves the cost  $O(M(d) \log N + kd)$  for the above problem with  $k$  sequences.

While Algorithm 1 looks at  $N$  from the least significant bit (LSB), the main algorithm presented in this section (Algorithm 5) looks at  $N$  from the most significant bit (MSB). In fact, Algorithm 5 is in essentially equivalent to “the transposition” of Algorithm 1 in the sense of [8]. This is the reason why this MSB-first algorithm has exactly the same complexity as Algorithm 1. However, in order to keep the presentation self-contained, we are not going to appeal here to the general machinery of algorithmic transposition tools, but rather derive the transposed algorithm “by hand”, using a direct reasoning.

In order to compute the coefficient  $[x^N] P(x)/Q(x)$ , it is sufficient to compute the  $(N - d + 1)$ -th term to the  $N$ -th term of  $1/Q(x)$  since the degree of  $P(x)$  is at most  $d - 1$ . Let  $\mathcal{F}_{N,d}(\sum_{i \geq 0} a_i x^i) := \sum_{i=0}^{d-1} a_{N-d+1+i} x^i$ .

---

**Algorithm 5 (SliceCoeff)**    **Input:**  $Q(x), N$     **Output:**  $\mathcal{F}_{N,d}(1/Q(x))$

---

**Assumptions:**  $Q(0)$  invertible and  $\deg(Q) =: d$

```

1: function  $\mathcal{F}(N, Q(x))$ 
2:   if  $N = 0$  then
3:     return  $x^{d-1}/Q(0)$ 
4:    $A(x) \leftarrow Q(x)Q(-x)$   $\triangleright A = \sum_{i=0}^{2d} A_i x^i$ 
5:    $V(x) \leftarrow \sum_{i=0}^d A_{2i} x^i$ 
6:    $W(x) \leftarrow \mathcal{F}(\lfloor N/2 \rfloor, V(x))$ 
7:   if  $N$  is even then
8:      $S(x) \leftarrow xW(x^2)$ 
9:   else
10:     $S(x) \leftarrow W(x^2)$ 
11:    $B(x) \leftarrow Q(-x)S(x)$   $\triangleright B = \sum_{i=0}^{3d-1} B_i x^i$ 
12:   return  $\sum_{i=0}^{d-1} B_{d+i} x^i$ 

```

---

Our goal is to compute  $\mathcal{F}_{N,d}(1/Q(x))$ . We have the sequence of equalities

$$\begin{aligned}
\mathcal{F}_{N,d}\left(\frac{1}{Q(x)}\right) &= \mathcal{F}_{N,d}\left(\frac{Q(-x)}{Q(x)Q(-x)}\right) \\
&= \mathcal{F}_{N,d}\left(Q(-x)x^{N-2d+1}\mathcal{F}_{N,2d}\left(\frac{1}{Q(x)Q(-x)}\right)\right) \\
&= \mathcal{F}_{2d-1,d}\left(Q(-x)\mathcal{F}_{N,2d}\left(\frac{1}{V(x^2)}\right)\right),
\end{aligned}$$

where  $V(x^2) := Q(x)Q(-x)$ .

In the second equality, we ignore the terms of  $1/V(x^2)$  except for the  $(N - 2d + 1)$ -th term to the  $N$ -th term. In the third equality, we use the fact that  $\mathcal{F}_{N,d}(xA(x)) = \mathcal{F}_{N-1,d}(A(x))$ . Let now  $W(x) := \mathcal{F}_{\lfloor N/2 \rfloor, d}(1/V(x))$ . Then, it is easy to see that

$$\mathcal{F}_{N,d}\left(\frac{1}{Q(x)}\right) = \mathcal{F}_{2d-1,d}(Q(-x)S(x)),$$

where

$$S(x) := \begin{cases} xW(x^2), & \text{if } N \text{ is even} \\ W(x^2), & \text{else.} \end{cases}$$

The resulting method for computing  $\mathcal{F}_{N,d}(1/Q(x))$  is summarized in Algorithm 5, and its immediate applications to the computation of  $[x^N]P/Q$ , and to  $[x^N]P^{(i)}/Q$  for several  $i = 1, \dots, k$ , are displayed in Algorithms 6 and 7.

---

**Algorithm 6 (OneCoeffT)**    **Input:**  $P(x), Q(x), N$     **Output:**  $[x^N] \frac{P(x)}{Q(x)}$

---

**Assumptions:**  $Q(0)$  invertible and  $\deg(P) < \deg(Q) =: d$

- 1:  $U \leftarrow \mathcal{F}_{N,d}(1/Q(x))$  using Algorithm 5     $\triangleright U = u_{N-d+1} + \cdots + u_N x^{d-1}$
  - 2: **return**  $p_0 u_N + \cdots + p_{d-1} u_{N-d+1}$      $\triangleright P = \sum_{i=0}^{d-1} p_i x^i$
- 

---

**Algorithm 7**    **Input:**  $P_1, \dots, P_k, Q, N$     **Output:**  $[x^N] \frac{P_j}{Q}, j = 1, \dots, k$

---

**Assumptions:**  $Q(0)$  invertible and  $\deg(P) < \deg(Q) =: d$

- 1:  $U \leftarrow \mathcal{F}_{N,d}(1/Q(x))$  using Algorithm 5     $\triangleright U = u_{N-d+1} + \cdots + u_N x^{d-1}$
  - 2: **return**  $p_0^{(j)} u_N + \cdots + p_{d-1}^{(j)} u_{N-d+1}, j = 1, \dots, k$      $\triangleright P_j = \sum_{i=0}^{d-1} p_i^{(j)} x^i$
- 

Let us analyze the complexity of Algorithms 5 and 6 more carefully. At each step, Algorithm 5 computes  $Q(x)Q(-x)$  and  $Q(-x)S(x)$ , where the degrees of  $Q(x)$  and  $S(x)$  are  $d$  and at most  $2d - 1$ , respectively. Hence a direct analysis concludes that its complexity is  $3M(d) \log N$  operations in  $R$ . However, an improvement comes from the remark that not all coefficients of  $Q(-x)S(x)$  are needed: it is sufficient to compute the  $d$ -th coefficient to the  $(2d - 1)$ -th coefficient of  $Q(-x)S(x)$ . This operation is known as “the middle product”, and can be performed with exactly the same arithmetic complexity as the standard product of two polynomials of degrees  $d$  and  $d - 1$  [35, 8]. Therefore, if steps 11 and 12 of Algorithm 5 are performed “at once” using a middle product, then the arithmetic complexity drops to  $2M(d) \log N$ . This complexity is also inherited by Algorithm 6, which uses at most  $2d$  additional operations in the last step.

It should be obvious at this point that the slight variant Algorithm 7 of Algorithm 6 achieves arithmetic complexity  $O(M(d) \log N + kd)$  for the aforementioned problem with  $k$  sequences, and more precisely its cost is of at most  $(2M(d) + d) \log N + 2kd$  operations in  $R$ .

In conclusion, Algorithm 5 achieves the same arithmetic complexity as Algorithm 1 and it extends to Algorithms 6 and 7. All algorithmic techniques specific to the FFT setting, that we will describe in Section 4, can also be applied to Algorithms 5, 6 and 7, yielding the same complexity gains.

### 3.2 Faster modular exponentiation

The algorithms of §3.1 are not only well-suited to compute the  $N$ -th terms of several sequences satisfying the same recurrence relation. In this section, we show that they also permit a surprising application to the computation



---

**Algorithm 8 (NewModExp)**    **Input:**  $\Gamma(x), N$     **Output:**  $x^N \bmod \Gamma(x)$

---

**Assumptions:**  $\text{lc}(\Gamma)$  invertible,  $\Gamma(0) \neq 0$  and  $\deg(\Gamma) =: d$

- 1:  $Q(x) \leftarrow x^d \Gamma(1/x)$
  - 2:  $u(x) \leftarrow \mathcal{F}_{N,d}(1/Q(x))$  ▷ using Algorithm 5
  - 3:  $v(x) \leftarrow u(x)Q(x) \bmod x^d$
  - 4: **return**  $v(1/x)x^{d-1}$
- 

of *polynomial modular exponentiations*. This fact has many consequences, since modular exponentiation is a central algorithmic task in algebraic computations. In §3.3, we will discuss a first application in relation with the main topic of our article. Namely, we will design a new Fiduccia-style algorithm for the computation of the  $N$ -th term, and actually of a whole slice of  $k \geq d$  terms, in  $2M(d) \log N + O((k+d)M(d)/d)$  arithmetic operations. More consequences will be separately discussed in §3.4.

Assume we are given a polynomial  $\Gamma(x) \in R[x]$  of degree  $d$ , an integer  $N$ , and that we want to compute  $\rho(x) := x^N \bmod \Gamma(x)$ . Without loss of generality, we may assume  $\Gamma(0) \neq 0$ . Let  $Q(x) \in R[x]$  be the reversal of  $\Gamma(x)$ , that is  $Q(x) := x^d \Gamma(1/x)$ . Let us denote the power series expansion of  $1/Q$  by  $\sum_{i \geq 0} a_i x^i$ . Then, equation (3) implies that

$$\begin{bmatrix} a_N & \cdots & a_{N+d-1} \end{bmatrix} = \mathbf{r} \times \mathbf{H}, \quad (5)$$

where  $\mathbf{r} = \begin{bmatrix} r_0 & \cdots & r_{d-1} \end{bmatrix}$  with  $\rho = \sum_{i=0}^{d-1} r_i x^i$  and  $\mathbf{H}$  is the Hankel matrix

$$\mathbf{H} := \begin{bmatrix} a_0 & \cdots & a_{d-1} \\ a_1 & \cdots & a_d \\ \vdots & & \\ a_{d-1} & \cdots & a_{2d-2} \end{bmatrix}.$$

Note that the matrix  $\mathbf{H}$  is invertible, as its determinant is equal (up to a sign) to  $([x^d]Q)^{d-1} = \Gamma(0)^{d-1}$ . Therefore,  $\mathbf{r}$  (and thus  $\rho$ ) can be found by

- (1) computing  $\begin{bmatrix} u_N & \cdots & u_{N+d-1} \end{bmatrix}$  using Algorithm 5;
- (2) solving the Hankel linear system (5).

The arithmetic complexity of step (1) is  $2M(d) \log(N) + O(d \log N)$ , while step (2) has negligible cost  $O(M(d) \log d)$  using [13], see also [6, Ch. 2, §5].

It is actually possible to improve a bit more on this algorithm, by using the next lemma.

**Lemma 1.** *Let  $N \in \mathbb{N}$  and let  $\Gamma(x) \in R[x]$  be of degree  $d$  with  $\Gamma(0) \neq 0$ . Let  $Q(x) \in R[x]$  be its reversal,  $Q(x) := x^d \Gamma(1/x)$ . Denote its reciprocal  $1/Q$  by  $\sum_{i \geq 0} a_i x^i$ , and let  $u(x)$  be  $\mathcal{F}_{N,d}(1/Q(x)) = a_{N-d+1} + \cdots + a_N x^{d-1}$ . Define  $v(x)$  to be  $u(x)Q(x) \bmod x^d$ . Then  $x^N \bmod \Gamma(x) = v(1/x)x^{d-1}$ .*

*Proof.* Write the Euclidean division  $x^N = L(x) \cdot \Gamma(x) + \rho(x)$ , where  $\deg(L) = N - d$  and  $\rho(x) = r_0 + \cdots + r_{d-1}x^{d-1}$ . Replacing  $x$  by  $1/x$  on both sides, and then multiplying by  $x^N$  yields  $1 = L_{\text{rev}}(x) \cdot Q(x) + x^{N-d+1} \cdot \tilde{\rho}(x)$ , where  $L_{\text{rev}}(x) = x^{N-d} \cdot L(1/x)$  and  $\tilde{\rho}(x) = x^{d-1} \cdot \rho(1/x)$ . In other words

$$\frac{1}{Q(x)} = L_{\text{rev}}(x) + x^{N-d+1} \cdot \frac{\tilde{\rho}(x)}{Q(x)}.$$

Since  $L_{\text{rev}}(x)$  has degree at most  $N - d$ , it follows that  $u(x) = \frac{\tilde{\rho}(x)}{Q(x)} \bmod x^d$ . Therefore,  $\tilde{\rho}(x)$  is equal to  $v(x)$ , and the conclusion follows.  $\square$

The merit of Lemma 1 is that it shows that computing  $x^N \bmod \Gamma(x)$  can be reduced to computing  $\mathcal{F}_{N,d}(1/Q(x))$ , plus a few additional operations with negligible cost  $M(d)$ . The resulting method is presented in Algorithm 8, whose complexity is  $2M(d) \log N + M(d)$ . This proves Theorem 4.

Notice that Algorithm 8 is simpler, and faster by a factor of 1.5, than the classical algorithm based on binary powering in the quotient ring  $R[x]/(\Gamma(x))$ . Algorithm 8 admits a specialization into the FFT setting, with complexity  $\sim \frac{2}{3} M(d) \log N$ , in the spirit of §4 below. Similarly to the case of Algorithm 11 in §4, the FFT variant of Algorithm 8 is faster by a factor of 2.5 than Shoup’s (comparatively simple) algorithm [70, §7.3], and by a factor of 1.625 than the (much more complex) algorithm of Mihăilescu [53].

This speed-up might be beneficial for instance in applications to polynomial factoring in  $\mathbb{F}_p[x]$ , where one time-consuming step to factor  $f \in \mathbb{F}_p[x]$  is the computation of  $x^p \bmod f$ , see [27, Algorithms 14.3, 14.8, 14.13, 14.15, 14.31, 14.33 and 14.36], and also [70, 48].

It might also be so in point-counting methods such as Schoof’s algorithm and the Schoof-Elkies-Atkin (SEA) algorithm [7, Ch. VII], the second one being the best known method for counting the number of points of elliptic curves defined over finite fields of large characteristic. Indeed, the bulks of these algorithms are computations of  $x^q$  modulo the “division polynomial”  $f_\ell(x)$  and of  $x^q$  modulo the “modular polynomial”  $\Phi_\ell(x)$ , where  $\ell = O(\log(q))$  and  $\deg(f_\ell) = O(\ell^2)$ ,  $\deg(\Phi_\ell) = O(\ell)$ .

As a final remark, note that while Fiduccia’s algorithm shows that computing the terms of indices  $N, \dots, N + d - 1$  of a linearly recurrent sequence of order  $d$  can be reduced to polynomial modular exponentiation

$(x^N \bmod \Gamma(x))$ , Algorithm 8 shows that the converse is also true: polynomial modular exponentiation can be reduced to computing the terms of indices  $N, \dots, N + d - 1$  of a linearly recurrent sequence of order  $d$ . Therefore, *these two problems are computationally equivalent*. To our knowledge, this important fact seems not to have been noticed before.

### 3.3 A new Fiduccia-style algorithm

We conclude this section by discussing a straightforward application of Algorithm 8. This is based on the next equality, generalizing (5) to any  $k \geq 1$ :

$$\begin{bmatrix} u_N & \cdots & u_{N+k-1} \end{bmatrix} = \mathbf{r} \times \mathbf{H}_k, \quad (6)$$

where as before  $\mathbf{r} = [r_0 \ \cdots \ r_{d-1}]$  is the coefficients vector of  $\rho = \sum_{i=0}^{d-1} r_i x^i$ , with  $\rho = x^N \bmod \Gamma(x)$ , and  $\mathbf{H}_k$  is the Hankel matrix

$$\mathbf{H}_k := \begin{bmatrix} u_0 & \cdots & u_{d-1} & \cdots & \cdots & u_{k-1} \\ u_1 & \cdots & u_d & \cdots & \cdots & u_k \\ & \vdots & \vdots & \vdots & \vdots & \\ u_{d-1} & \cdots & u_{2d-2} & \cdots & \cdots & u_{k+d-2} \end{bmatrix}.$$

The matrix  $\mathbf{H}_k$  is built upon the first terms of the sequence  $(u_n)_{n \geq 0}$  satisfying recurrence (1) with characteristic polynomial  $\Gamma = x^d - \sum_{i=0}^{d-1} c_i x^i$ , or equivalently, from the power series expansion of the rational function  $P/Q$  with  $Q(x) = x^d \Gamma(1/x)$ .

Note that the entries of  $\mathbf{H}_k$  can be computed either from  $P$  and  $Q$ , or from the recurrence (1) together with the initial terms  $u_0, \dots, u_{d-1}$ , using  $O((k+d) M(d)/d)$  arithmetic operations, by the algorithm in [69, Thm. 3.1], see also [8, §5]. To compute  $u_N, \dots, u_{N+k-1}$  it thus only remains to perform the vector-matrix product (6).

When  $k = 1$ , the product  $\mathbf{r} \times \mathbf{H}_1$  costs  $2d$  operations and it yields the term  $u_N$ .

When  $k \geq d$ , the product  $\mathbf{r} \times \mathbf{H}_k$  can be reduced to the polynomial multiplication of  $r_{d-1} + \cdots + r_0 x^{d-1}$  by  $\sum_{i=0}^{k+d-2} u_i x^i$ , and this can be performed using  $\lceil \frac{k+d}{d} \rceil M(d)$  arithmetic operations. As a consequence, the whole slice of coefficients  $u_{N+i} = [x^{N+i}]P/Q$  for  $i = 0, \dots, k-1$ , can be computed using Algorithm 8 and eq. (6) for a total cost of arithmetic operations equal to

$$2M(d) \log N + O\left(\frac{k+d}{d} M(d)\right).$$

---

<b>Algorithm 9</b>	<b>Input:</b> rec. (1), $u_0, \dots, u_{d-1}, N$	<b>Output:</b> $u_N, \dots, u_{N+d-1}$
<b>Assumptions:</b> $\Gamma(x) = x^d - \sum_{i=0}^{d-1} c_i x^i$ with $c_0 \neq 0$		
1: $\rho(x) \leftarrow x^N \bmod \Gamma(x)$		▷ using Algorithm 8
2: $U(x) \leftarrow u_0 + \dots + u_{2d-2} x^{2d-2}$		▷ using Algorithm in [69, p. 18]
3: $V(x) \leftarrow U(x) \cdot (x^d \cdot \rho(1/x))$		▷ $V = \sum_{i=0}^{d-1} v_i x^i$
4: <b>return</b> $[v_d, \dots, v_{2d-1}]$		

---

When  $k = d$ , this proves Theorem 3. The corresponding algorithm is given as Algorithm 9.

We emphasize that this variant of Fiduccia’s algorithm is different from Algorithm 1. It is actually a bit slower than Algorithm 1 when  $k = 1$ . However, when  $k > 1$  terms are to be computed, it should be preferred to repeating  $k$  times Algorithm 1. It also compares favorably with Fiduccia’s original algorithm, whose adaption to  $k$  terms has arithmetic complexity

$$3M(d) \log N + O\left(d \log(N) + \frac{k+d}{d} M(d)\right).$$

### 3.4 Applications

In this section, we discuss three more applications of the MSB-first algorithms (Algorithm 5 and 8) presented in §3.1 and §3.2. We deal with the case of multiplicities (§3.4.1), and explain a new way to speed up computations in that case. Then, we address other applications, to faster powering of matrices (§3.4.2) and to faster high-order lifting (§3.4.3).

To simplify matters, we assume in this section that  $R = \mathbb{K}$  is a field.

#### 3.4.1 The case with multiplicities

Hyun and his co-authors [42, 41] addressed the following question: is it possible to compute faster the  $N$ -th term of a linearly recurrent sequence when the characteristic polynomial of the recurrence has multiple roots? By the Chinese Remainder Theorem, it is sufficient to focus on the case where the characteristic polynomial is a pure power of a squarefree polynomial. In other words, the main step of [42, Algorithm 1] is to compute  $x^N \bmod Q$ , where  $Q = (Q^*)^m$  and  $Q^*$  is the squarefree part of  $Q$ . Under suitable invertibility conditions, the problem is solved in [42, 41] in  $O(M(d^*) \log N + M(d) \log d)$  operations in  $\mathbb{K}$ , where  $d^* = \deg(Q^*)$  and  $d = \deg(Q) = m \cdot d^*$ . This cost is obtained using an algorithm based on bivariate computations, using the isomorphisms between  $\mathbb{K}[x]/(Q)$  and  $\mathbb{K}[y, x]/(Q^*(y), (x - y)^m)$

made effective by the so-called *tangling / untangling* operations. We now propose an alternatively fast, but simpler, algorithm with the same cost.

Let us explain this on an example, for “multiple-Fibonacci numbers”, that is when  $Q$  has the form  $(Q^*)^m$ , with  $Q^* = 1 - x - x^2$  and  $d^* = 2, d = 2d^*$ . Assume we want to compute the  $N$ -th coefficient  $u_N$  in the power series expansion of  $(x/(1 - x - x^2))^m$ . The cost of Fiduccia’s algorithm, and also of our new algorithms, is  $O(M(m) \cdot \log N)$ . Let us explain how we can lower this to  $O(\log N + M(m) \log m)$ . The starting point is the observation that, by the structure theorem of linearly recurrent sequences [15, §A.(I)] (see also [62, §2]),  $u_N$  is of the form  $u_m(N)\phi^N + v_m(N)\psi^N$ , where  $\phi$  and  $\psi$  are the two roots of  $1 + x = x^2$  and  $u_m, v_m$  are polynomials in  $\mathbb{K}[x]$  of degree less than  $m$ . By an easy linear algebra argument,  $u_N$  is thus equal to  $U_m(N)F_N + V_m(N)F_{N+1}$ , where  $U_m(x)$  and  $V_m(x)$  are polynomials in  $\mathbb{K}[x]$  of degree less than  $m$ . These polynomials can be computed by (structured) linear algebra from the first  $2m$  values of the sequence  $(u_n)$ , in complexity  $O(M(m) \log m)$ . For instance, when  $d = 2$ , we have  $U_2(x) = -(x + 1)/5$  and  $V_2(x) = 2x/5$ . Once  $U_m$  and  $V_m$  are determined, it remains to compute  $F_N$  and  $F_{N+1}$  using Algorithm 9 in  $O(\log N)$  operations in  $\mathbb{K}$ , then to return the value  $U_m(N) \cdot F_N + V_m(N) \cdot F_{N+1}$ .

The arguments extend to the general case and yields an algorithm of arithmetic complexity  $2M(d^*) \log N + O(M(d) \log d)$ .

### 3.4.2 Faster powering of matrices

Assume we are given a matrix  $M \in \mathcal{M}_d(\mathbb{K})$ , an integer  $N$ , and that we want to compute the  $N$ -th power  $M^N$  of  $M$ .

The arithmetic complexity of binary powering in  $\mathcal{M}_d(\mathbb{K})$  is  $O(d^\theta \log N)$  operations in  $\mathbb{K}$ , where as before  $\theta \in [2, 3]$  is any feasible exponent for matrix multiplication in  $\mathcal{M}_d(\mathbb{K})$ . A better algorithm consists in first computing the characteristic polynomial  $\Gamma(x)$  of the matrix  $M$ , then the remainder  $\rho(x) := x^N \bmod \Gamma(x)$ , and finally evaluating the polynomial  $\rho(x)$  at  $M$ . By the Cayley-Hamilton theorem,  $\rho(M) = M^N$ . The most costly step is the computation of  $R$ , which can be done as explained in §3.2 using  $\sim 2M(d) \log(N)$  operations in  $\mathbb{K}$ . The cost of the other two steps is independent of  $N$ , and it is respectively  $O(d^\theta \log d)$  [43] and  $O(d^{\theta + \frac{1}{2}})$ , this last cost being achieved using the Paterson-Stockmeyer *baby-step / giant-step* algorithm [59]. The total cost of this algorithm is  $2M(d) \log(N) + O(d^{\theta + \frac{1}{2}})$ .

Note that a faster variant (w.r.t.  $d$ ), of cost  $2M(d) \log(N) + O(d^\theta \log d)$ , can be obtained using [28, Corollary 7.4]. The corresponding algorithm is based on the computation of the Frobenius (block-companion) form of the

matrix  $M$ , followed by the powering of companion matrices, which again reduces to modular exponentiation.

### 3.4.3 Faster high-order lifting

The fastest known algorithms for polynomial linear algebra rely fundamentally on an algorithmic technique introduced by Storjohann [71], called *high-order lifting*.

Given an invertible polynomial matrix  $A$  of degree  $d$ , the problem is to compute the high order components  $(C_0, C_1), (C_2, C_3), (C_6, C_7), (C_{14}, C_{15}), \dots$  in the power series expansion of its inverse

$$A^{-1} = \sum_{i \geq 0} C_i(x) \cdot (x^d)^i, \quad \text{with } C_i \in \mathcal{M}_n(\mathbb{K}[x]_{<d}),$$

where  $\mathcal{M}_n(\mathbb{K}[x]_{<d})$  denotes the set of  $n \times n$  matrices whose entries are polynomials in  $\mathbb{K}[x]$  of degree less than  $d$ .

For instance, two extreme cases are (i) if  $d = 1$  and  $A = I_n - xM$ , with  $M \in \mathcal{M}_n(\mathbb{K})$ , then  $C_i = M^i$  and the high-order components can be computed as in §3.4.2; (ii)  $n = 1$ , then the problem reduces to the one we solved in §3.1. Storjohann [71, §5] proposed an algorithm for arbitrary  $d$  and  $n$ , extrapolating between the two particular cases, with complexity  $O(\text{MM}(n, d) \log(N))$ , where  $\text{MM}(n, d)$  denotes the arithmetic complexity of the product in  $\mathcal{M}_n(\mathbb{K}[x]_{<d})$ .

Storjohann's algorithm relies on the following identities:

$$\begin{cases} C_{2^i-2} &= - \left[ (C_{2^{i-1}-2} + C_{2^{i-1}-1} \cdot x^d) \cdot [A \cdot C_{2^{i-1}-2}]_{d-1}^{2d-1} \right]_{d-1}^{2d-1}, \\ C_{2^i-1} &= - \left[ (C_{2^{i-1}-2} + C_{2^{i-1}-1} \cdot x^d) \cdot [A \cdot C_{2^{i-1}-1}]_{d-1}^{2d-1} \right]_{d-1}^{2d-1}. \end{cases}$$

Here, for a polynomial matrix  $B = \sum_i B_i x^i$  with  $B_i \in \mathcal{M}_n(\mathbb{K})$ , we use the notation  $[B]_{d-1}^{2d-1}$  to denote the matrix  $\sum_{i=0}^{d-1} B_{d+i} x^i$ .

Thus, to compute  $C_N$  say when  $N$  is of the form  $2^k - 1$ , this algorithm uses  $\sim 6 \text{MM}(n, d) \log(N)$  operations in  $\mathbb{K}$  if polynomial products are used, or  $\sim 4 \text{MM}(n, d) \log(N)$  operations in  $\mathbb{K}$  if middle product techniques are used for the outmost products. Using a matrix adaptation of Algorithm 5, we can lower this to  $\sim 2 \text{MM}(n, d) \log(N)$  operations in  $\mathbb{K}$ .

Note that Nuel and Dumas compared in [56] Fiduccia's and Storjohann's algorithms (in the scalar case), but only in the under the specific assumption that naive polynomial multiplication is used, that is  $M(d) = O(d^2)$ .

## 4 Analysis under the FFT multiplication model

In this section, we specialize, optimize and analyze the generic Algorithm 1 to the FFT setting, in which polynomial multiplications are assumed to be performed using the discrete Fourier transform (DFT), and its inverse.

In order to do this, we will assume that the base ring  $R$  possesses roots of unity of sufficiently high order. To simplify the exposition, the ring  $R$  will be supposed to be a field, but the arguments also apply without this assumption, modulo some technical complications, see [27, §8.2].

### 4.1 Discrete Fourier Transform for polynomial products

Let  $\mathbb{K}$  be a field with a primitive  $n$ -th root  $\omega_n$  of unity. Let  $A \in \mathbb{K}[x]$  be a polynomial of degree at most  $d \leq n - 1$ . The DFT  $\hat{A}$  of  $A$  is defined by

$$\hat{A}_y := A(\omega_n^{-y}) = \sum_{i=0}^{n-1} A_i \omega_n^{-yi} \quad \text{for } y = 0, 1, \dots, n-1.$$

Here,  $A_y = 0$  for  $y > d$ . It is classical that the DFT map is an invertible  $\mathbb{K}$ -linear transform from  $\mathbb{K}^n$  to itself, and that the polynomial  $A$  can be retrieved from its DFT  $\hat{A}$  using the formulas

$$A_i = \frac{1}{n} \sum_{y=0}^{n-1} \hat{A}_y \omega_n^{yi} \quad \text{for } i = 0, 1, \dots, n-1.$$

For computing the polynomial multiplication  $C(x) = A(x)B(x)$  for given  $A(x), B(x) \in \mathbb{K}[x]$  of degree at most  $d$ , it is sufficient to compute the DFT of  $C(x)$  for  $n \geq 2d + 1$ . Since  $\hat{C}_y = C(\omega_n^{-y}) = A(\omega_n^{-y})B(\omega_n^{-y}) = \hat{A}_y \hat{B}_y$ , the polynomial  $C(x)$  can be computed using two DFTs and one inverse DFT.

Let  $E(n)$  be an arithmetic complexity for computing a DFT of length  $n$ . Then the cost of polynomial multiplication in  $\mathbb{K}[x]$  is governed by

$$M(d) = 3E(2d) + O(d).$$

### 4.2 Fast Fourier Transform

In this subsection, we briefly recall the Fast Fourier Transform (FFT), which gives the quasi-linear estimate  $E(n) = O(n \log n)$ .

Assume  $n$  is even. Then, for  $y = 0, 1, \dots, n/2 - 1$  we have

$$\begin{aligned}\widehat{A}_y &= \sum_{i=0}^{n/2-1} A_{2i} \omega_n^{-y(2i)} + \sum_{i=0}^{n/2-1} A_{2i+1} \omega_n^{-y(2i+1)} \\ &= \sum_{i=0}^{n/2-1} A_{2i} \omega_{n/2}^{-yi} + \omega_n^{-y} \cdot \sum_{i=0}^{n/2-1} A_{2i+1} \omega_{n/2}^{-yi} \\ &= \widehat{A}_y^e + \omega_n^{-y} \widehat{A}_y^o\end{aligned}$$

where  $A^e(x) := \sum_{i=0}^{n/2} A_{2i} x^i$  and  $A^o(x) := \sum_{i=0}^{n/2} A_{2i+1} x^i$ .

Similarly, we have  $\widehat{A}_{n/2+y} = \widehat{A}_y^e - \omega_n^{-y} \widehat{A}_y^o$ . We therefore obtain the following matrix equation

$$\begin{bmatrix} \widehat{A}_y \\ \widehat{A}_{n/2+y} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & \omega_N^{-y} \end{bmatrix} \begin{bmatrix} \widehat{A}_y^e \\ \widehat{A}_y^o \end{bmatrix} \quad \text{for } y = 0, 1, \dots, n/2 - 1. \quad (7)$$

Thus, computing a DFT in size  $n$  reduces to two DFTs in size  $n/2$ . More precisely,  $E(n) \leq 2E(n/2) + (3/2)n$ . If  $n$  is a power of two,  $n = 2^k$ , and if the field  $\mathbb{K}$  contains a primitive  $2^k$ -th root of unity (as is the case for instance when  $\mathbb{K} = \mathbb{C}$ ,  $\mathbb{K} = \mathbb{F}_p$  for a prime number  $p$  satisfying  $2^k \mid p - 1$ ), this reduction can be repeated  $k = \log n$  times, and it yields the estimate  $E(n) = \frac{3}{2}n \log n$ . The corresponding algorithm is called the *decimation-in-time* Cooley–Tukey fast Fourier transform [17], see also [5, §2].

By the arguments of §4.1, we conclude that polynomial multiplication in  $\mathbb{K}[x]$  can be performed in arithmetic complexity

$$M(d) = 9d \log d + O(d).$$

### 4.3 Efficiently doubling the length of a DFT

In the FFT setting, it is useful for many applications to compute efficiently a DFT of length  $2n$  starting from DFT of length  $n$ .

Assume  $n \geq d + 1$  and we have at our disposal the DFT  $\widehat{A}$  of  $A$ , of length  $n$ . Assume that we want to compute the DFT  $\widehat{A}^{(2n)}$  of length  $2n$ .

The simplest algorithm is to apply the inverse DFT of length  $n$  to obtain  $A$ , and then to apply the DFT of length  $2n$  to  $A$ . This costs  $E(n) + E(2n)$  arithmetic operations, that is  $\frac{9}{2}n \log n + 3n$  operations in  $\mathbb{K}$ .



---

**Algorithm 10** Doubling the length of a DFT
 

---

```

1: function UP( $\widehat{A}$ )
2:    $A \leftarrow \text{IDFT}_n(\widehat{A})$ 
3:    $B_i \leftarrow \omega_{2n}^{-i} A_i$    for  $i = 0, 1, \dots, n-1$ 
4:    $\widehat{B} \leftarrow \text{DFT}_n(B)$ 
5:    $\widehat{A}_{2y}^{(2n)} \leftarrow \widehat{A}_y$  for  $y = 0, 1, \dots, n-1$ 
6:    $\widehat{A}_{2y+1}^{(2n)} \leftarrow \widehat{B}_y$  for  $y = 0, 1, \dots, n-1$ 
7:   return  $\widehat{A}^{(2n)}$ 

```

---

This algorithm can be improved using the following formulas

$$\widehat{A}_{2y}^{(2n)} = \sum_{i=0}^{2n-1} A_i \omega_{2n}^{-2yi} = \sum_{i=0}^{n-1} A_i \omega_n^{-yi} = \widehat{A}_y,$$

$$\widehat{A}_{2y+1}^{(2n)} = \sum_{i=0}^{2n-1} A_i \omega_{2n}^{-(2y+1)i} = \sum_{i=0}^{n-1} \omega_{2n}^{-i} A_i \omega_n^{-yi} = \widehat{B}_y,$$

where  $B_i := \omega_{2n}^{-i} A_i$  for  $i = 0, 1, \dots, n-1$ . We obtain Algorithm 10 with arithmetic complexity  $2\mathbf{E}(n) + n$ , *i.e.*  $3n \log n + n$ , [5, §12.8], see also [4, 52]<sup>10</sup>. Compared with the direct algorithm, the gain is roughly a factor of 3/2.

#### 4.4 Algorithm 1 in the FFT setting

Recall that our main objective is, given  $P, Q$  in  $\mathbb{K}[x]$  with  $d = \deg(Q) > \deg(P)$ , to compute the  $N$ -th coefficient  $u_N$  in the series expansion of  $P/Q$ .

Let  $k$  be the minimum integer satisfying  $2^k \geq 2d + 1$ . Assume that there exists a primitive  $2^k$ -th root of unity in  $\mathbb{K}$ . In this case, we can employ an FFT-based polynomial multiplication in  $\mathbb{K}[x]$ . In each iteration of Algorithm 1, it is sufficient to compute  $P(x)Q(-x)$  and  $Q(x)Q(-x)$ . Here, only two FFTs and two inverse FFT of length  $2^k$  are needed since  $\widehat{Q}_y^- = \widehat{Q}_{\bar{y}}$  for  $Q^-(x) := Q(-x)$  where  $\bar{y} := y + 2^{k-1}$  if  $y < 2^{k-1}$  and  $\bar{y} := y - 2^{k-1}$  if  $y \geq 2^{k-1}$ . Hence, the arithmetic complexity  $\mathbf{S}(d)$  for a single step in Algorithm 1 satisfies  $\mathbf{S}(d) \leq 4\mathbf{E}(2^k) + O(2^k)$ .

In the following we will show the improved estimate

$$\mathbf{S}(d) \leq 4\mathbf{E}(2^{k-1}) + O(2^k).$$

---

<sup>10</sup>This ‘‘FFT doubling’’ trick is sometimes attributed to R. Kramer (2004), but we have not been able to locate Kramer’s paper.

Before entering the **while** loop in Algorithm 1, the DFTs  $\widehat{P}$  and  $\widehat{Q}$  of  $P(x)$  and  $Q(x)$  of length  $2^k$  are computed, respectively. Inside the **while** loop,  $\widehat{P}$  and  $\widehat{Q}$  are updated. The recursive formula (7) for the decimation-in-time Cooley–Tukey FFT is equivalent to

$$\begin{bmatrix} \widehat{A}_y^e \\ \widehat{A}_y^o \end{bmatrix} = \frac{1}{2} \begin{bmatrix} 1 & 0 \\ 0 & \omega_N^y \end{bmatrix} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} \widehat{A}_y \\ \widehat{A}_{2^{k-1}+y} \end{bmatrix} \quad \text{for } y = 0, 1, \dots, 2^{k-1}.$$

By using this formula,  $\widehat{A}^e$  (or  $\widehat{A}^o$ ) can be computed with  $O(2^k)$  operations from  $\widehat{A}$ . By using Algorithm 10, we obtain the updated  $\widehat{P}$  from  $\widehat{A}^e$  or  $\widehat{A}^o$ . The algorithm is summarized in Algorithm 11. In each step, UP is called twice. Hence, the total arithmetic complexity of Algorithm 11 is

$$(4\mathbf{E}(2^{k-1}) + O(2^k)) \cdot \log N.$$

When  $d$  is of the form  $2^\ell - 1$ <sup>11</sup>, then one can take  $k = \ell + 1$  and the cost simplifies to

$$\mathbf{T}(N, d) = 4\mathbf{E}(d) \log N + O(d \log N),$$

or, equivalently

$$\mathbf{T}(N, d) = 6d \log d \log N + O(d \log N).$$

The (striking) conclusion of this analysis is that, in the FFT setting, our (variant of the) algorithm for computing the  $N$ -th term of  $P/Q$  uses much less operations than in the general case, namely

$$\mathbf{T}(N, d) \sim \frac{2}{3} \mathbf{M}(d) \log N, \quad (8)$$

while for a generic multiplication algorithm the cost is  $\sim 2\mathbf{M}(d) \log N$ . This proves Theorem 2.

Note that the complexity bound (8) compares favorably with Fiducia’s algorithm combined with the best algorithms for modular squaring. For instance, Shoup’s algorithm [70, §7.3] computes one modular squaring in the FFT setting using  $\sim \frac{5}{3} \mathbf{M}(d)$  arithmetic operations, while Mihăilescu’s algorithm [53, Table 1] (based on Montgomery’s algorithm [55]) uses roughly  $\sim \frac{13}{12} \mathbf{M}(d)$  arithmetic operations. Our bound (8) is better by a factor of 2.5 than Shoup’s (comparatively simple) algorithm, and by a factor of 1.625 than the (much more complex) algorithm by Mihăilescu.

Let us point out that all the other algorithms admit similarly fast versions in the FFT setting. We will however not give them in full detail here, mainly for space reasons.

---

<sup>11</sup>In the general case, it might be useful to use the Truncated Fourier Transform (TFT), which smoothes the “jumps” in complexity exhibited by FFT algorithms [38, 37, 3].

---

**Algorithm 11 (OneCoeff-FFT)** **Input:**  $P(x), Q(x), N$  **Output:**  $[x^N] \frac{P(x)}{Q(x)}$

---

```

1:  $\hat{P} \leftarrow \text{DFT}_{2^k}(P)$ 
2:  $\hat{Q} \leftarrow \text{DFT}_{2^k}(Q)$ 
3: while  $N \geq 1$  do
4:    $\hat{U}_y \leftarrow \hat{P}_y \hat{Q}_{\bar{y}}$  for  $y = 0, 1, \dots, 2^k - 1$ 
5:   if  $N$  is even then
6:      $\hat{U}_y^e \leftarrow (\hat{U}_y + \hat{U}_{y+2^{k-1}})/2$  for  $y = 0, 1, \dots, 2^{k-1} - 1$ 
7:      $\hat{P} \leftarrow \text{UP}(\hat{U}_y^e)$ 
8:   else
9:      $\hat{U}_y^o \leftarrow \omega_N^y (\hat{U}_y - \hat{U}_{y+2^{k-1}})/2$  for  $y = 0, 1, \dots, 2^{k-1} - 1$ 
10:     $\hat{P} \leftarrow \text{UP}(\hat{U}_y^o)$ 
11:    $\hat{A}_y \leftarrow \hat{Q}_y \hat{Q}_{\bar{y}}$  for  $y = 0, 1, \dots, 2^{k-1} - 1$ 
12:    $\hat{Q} \leftarrow \text{UP}(\hat{A})$ 
13:    $N \leftarrow \lfloor N/2 \rfloor$ 
14:  $P(0) \leftarrow \sum_{y=0}^{2^k-1} \hat{P}_y$ 
15:  $Q(0) \leftarrow \sum_{y=0}^{2^k-1} \hat{Q}_y$ 
16: return  $P(0)/Q(0)$ 

```

---

## 5 Conclusion

We have proposed several algorithmic contributions to the classical field of linearly recurrent sequences.

Firstly, we have designed a simple and fast algorithm for computing the  $N$ -th term of a linearly recurrent sequence of order  $d$ , using  $\sim 2M(d) \log N$  arithmetic operations, which is faster by a factor of 1.5 than the state-of-the-art 1985 algorithm due to Fiduccia [26]. When combined with FFT techniques, the algorithm has even better arithmetic complexity  $\sim \frac{2}{3}M(d) \log N$  which is faster than the fastest variant of Fiduccia's algorithm in the FFT setting by a factor of 1.625. The new algorithms are based on a new method (Algorithm 1) for computing the  $N$ -th coefficient of a rational power series.

Secondly, using algorithmic transposition techniques, we have derived from Algorithm 1 a new method (Algorithm 5) for computing simultaneously the coefficients of indices  $N - d + 1, \dots, N$  in the power series expansion of the reciprocal of a degree- $d$  polynomial, using again  $\sim 2M(d) \log N$  arithmetic operations. Using Algorithm 5, we have designed a new algorithm for computing the remainder of  $x^N$  modulo a given polynomial of degree  $d$ , using  $\sim 2M(d) \log N$  arithmetic operations as well. This is better

by a factor of 1.5 than the previous best algorithm for modular exponentiation, with an even better speed-up in the FFT setting, as for Algorithm 1. Combined with the basic idea of Fiduccia’s algorithm, our new algorithm for modular exponentiation yields a faster Fiduccia-like algorithm (by the aforementioned constant factors) that computes a slice of  $d$  consecutive terms (of indices  $N - d + 1, \dots, N$ ) of a linearly recurrent sequence of order  $d$  using  $\sim 2M(d) \log N$  arithmetic operations.

Thirdly, we have discussed applications of the new algorithms to a few other algorithmic problems, including powering of matrices, high-order lifting (a basic brick for modern polynomial linear algebra algorithms) and the computation of terms of linearly recurrent sequences when the recurrence has roots with (high) multiplicities.

As future work, we plan to investigate further the full power of our technique. To which extent can it be generalized to larger classes of power series? For instance, although it perfectly works for bivariate rational power series  $U(x, y)$ , the corresponding method does not directly provide a  $O(\log N)$ -algorithm for computing the  $(N, N)$ -th coefficient  $u_{N,N}$ , the reason being that the  $\log N$  new bivariate recurrences produced by the Graeffe process do not have constant orders, as in the univariate case. This is disappointing, but after all not surprising, because the generating function of the sequence  $(u_{n,n})_n$  is known to be algebraic, but not rational anymore [61]. As of today, no algorithm is known for computing the  $N$ -th coefficient of an algebraic power series faster than in the P-recursive case (P), namely in a number of ring operations almost linear in  $\sqrt{N}$ .

**Acknowledgements.** Our special thanks go to Kevin Atienza, whose editorial on <https://discuss.codechef.com> was our initial source of inspiration, and to Sergey Yurkevich, for his careful reading of a first draft of this work. A. Bostan was supported in part by [DeRerumNatura](#) ANR-19-CE40-0018. R. Mori was supported in part by JST PRESTO Grant #JPMJPR1867 and JSPS KAKENHI Grant #JP17K17711, #JP18H04090 and #JP20H04138.

## References

- [1] Manindra Agrawal, Neeraj Kayal, and Nitin Saxena. PRIMES is in P. *Ann. of Math. (2)*, 160(2):781–793, 2004.
- [2] Jean-Paul Allouche and Jeffrey Shallit. The ring of  $k$ -regular sequences. *Theoret. Comput. Sci.*, 98(2):163–197, 1992.

- [3] Andrew Arnold. A new truncated Fourier transform algorithm. In *Proceedings of ISSAC'13*, pages 15–22. ACM Press, 2013.
- [4] D. J. Bernstein. Removing redundancy in high-precision Newton iteration, 2004. Preprint, <http://cr.yp.to/fastnewton.html>.
- [5] Daniel J. Bernstein. Fast multiplication and its applications. In *Algorithmic number theory: lattices, number fields, curves and cryptography*, volume 44 of *Math. Sci. Res. Inst. Publ.*, pages 325–384. Cambridge Univ. Press, 2008.
- [6] Dario Bini and Victor Y. Pan. *Polynomial and matrix computations. Vol. 1*. Progress in Theoretical Computer Science. Birkhäuser Boston, Inc., Boston, MA, 1994. Fundamental algorithms.
- [7] I. Blake, G. Seroussi, and N. Smart. *Elliptic curves in cryptography*, volume 265 of *London Math. Soc. Lecture Note Ser.* Cambridge University Press, 1999.
- [8] A. Bostan, G. Lecerf, and É. Schost. Tellegen’s principle into practice. In *Proceedings of ISSAC'03*, pages 37–44. ACM Press, 2003.
- [9] Alin Bostan. Computing the  $N$ -th Term of a  $q$ -Holonomic Sequence. In *Proceedings of ISSAC'20*, pages 46–53. ACM Press, 2020.
- [10] Alin Bostan, Xavier Caruso, Gilles Christol, and Philippe Dumas. Fast coefficient computation for algebraic power series in positive characteristic. In *Proceedings of the Thirteenth Algorithmic Number Theory Symposium*, volume 2 of *Open Book Ser.*, pages 119–135. Math. Sci. Publ., Berkeley, CA, 2019.
- [11] Alin Bostan, Gilles Christol, and Philippe Dumas. Fast computation of the  $N$ th term of an algebraic series over a finite prime field. In *Proceedings of ISSAC'16*, pages 119–126. ACM Press, 2016.
- [12] Alin Bostan, Pierrick Gaudry, and Éric Schost. Linear recurrences with polynomial coefficients and application to integer factorization and Cartier-Manin operator. *SIAM J. Comput.*, 36(6):1777–1806, 2007.
- [13] Richard P. Brent, Fred G. Gustavson, and David Y. Y. Yun. Fast solution of Toeplitz systems of equations and computation of Padé approximants. *J. Algorithms*, 1(3):259–295, 1980.

- [14] Neil Calkin, Jimena Davis, Kevin James, Elizabeth Perez, and Charles Swannack. Computing the integer partition function. *Math. Comp.*, 76(259):1619–1638, 2007.
- [15] L. Cerlienco, M. Mignotte, and F. Piras. Suites récurrentes linéaires. Propriétés algébriques et arithmétiques. *L’Enseignement Mathématique*, 33:67–108, 1987.
- [16] D. V. Chudnovsky and G. V. Chudnovsky. Approximations and complex multiplication according to Ramanujan. In *Ramanujan revisited (Urbana-Champaign, Ill., 1987)*, pages 375–472. Academic Press, Boston, MA, 1988.
- [17] James W. Cooley and John W. Tukey. An algorithm for the machine calculation of complex Fourier series. *Math. Comp.*, 19:297–301, 1965.
- [18] Paul Cull and James L. Holloway. Computing Fibonacci numbers quickly. *Inform. Process. Lett.*, 32(3):143–149, 1989.
- [19] G. de Rocquigny. Question 1541. [I25a]. *L’Intermédiaire des mathématiciens*, 6:148, 1899.
- [20] Leonard Eugene Dickson. *History of the theory of numbers. Vol. I: Divisibility and primality*. Publication No. 256. Washington: Carnegie Institution of Washington, Vol. 1, 1919.
- [21] E.W. Dijkstra. In honour of Fibonacci. In *Program Construction. Lecture Notes in Computer Science 69*, ed. F.L. Bauer et al., pages 49–50. Springer, Berlin, Heidelberg, 1979.
- [22] M. C. Er. Computing sums of order- $k$  Fibonacci numbers in log time. *Inform. Process. Lett.*, 17(1):1–5, 1983.
- [23] M. C. Er. A formal derivation of an  $O(\log n)$  algorithm for computing Fibonacci numbers. *J. Inform. Optim. Sci.*, 7(1):9–15, 1986.
- [24] M. C. Er. An  $O(k^2 \log(n/k))$  algorithm for computing generalized order- $k$  Fibonacci numbers with linear space. *J. Inform. Optim. Sci.*, 9(3):343–353, 1988.
- [25] Charles M. Fiduccia. The  $n$ -th power of a companion matrix: Fast solutions to linear recurrences. 20th Proceedings of the Annual Allerton Conference on Communication, Control and Computing, pages 934–940, 1982.

- [26] Charles M. Fiduccia. An efficient formula for linear recurrences. *SIAM J. Comput.*, 14(1):106–112, 1985.
- [27] J. von zur Gathen and J. Gerhard. *Modern computer algebra*. Cambridge Univ. Press, third edition, 2013.
- [28] Mark Giesbrecht. Nearly optimal algorithms for canonical matrix forms. *SIAM J. Comput.*, 24(5):948–969, 1995.
- [29] Kenneth J. Giuliani and Guang Gong. New LFSR-Based Cryptosystems and the Trace Discrete Log Problem (Trace-DLP). In Tor Helleseth, Dilip Sarwate, Hong-Yeop Song, and Kyeongcheol Yang, editors, *Sequences and Their Applications - SETA 2004*, pages 298–312, Berlin, Heidelberg, 2005. Springer Berlin Heidelberg.
- [30] Kenneth J. Giuliani and Guang Gong. A new algorithm to compute remote terms in special types of characteristic sequences. In *Sequences and their applications—SETA 2006*, volume 4086 of *Lecture Notes in Comput. Sci.*, pages 237–247. Springer, Berlin, 2006.
- [31] Guang Gong and Lein Harn. Public-key cryptosystems based on cubic finite field extensions. *IEEE Trans. Inform. Theory*, 45(7):2601–2605, 1999.
- [32] Guang Gong, Lein Harn, and Huapeng Wu. The GH public-key cryptosystem. In *Selected areas in cryptography*, volume 2259 of *Lecture Notes in Comput. Sci.*, pages 284–300. Springer, Berlin, 2001.
- [33] Santos González, Llorenç Huguet, Consuelo Martínez, and Hugo Villafañe. Discrete logarithm like problems and linear recurring sequences. *Adv. Math. Commun.*, 7(2):187–195, 2013.
- [34] David Gries and Gary Levin. Computing Fibonacci numbers (and similarly defined functions) in log time. *Inform. Process. Lett.*, 11(2):68–69, 1980.
- [35] Guillaume Hanrot, Michel Quercia, and Paul Zimmermann. The middle product algorithm. I. *Appl. Algebra Engrg. Comm. Comput.*, 14(6):415–438, 2004.
- [36] David Harvey. Counting points on hyperelliptic curves in average polynomial time. *Ann. of Math. (2)*, 179(2):783–803, 2014.

- [37] David Harvey and Daniel S. Roche. An in-place truncated Fourier transform and applications to polynomial multiplication. In *Proceedings of ISSAC'10*, pages 325–329. ACM Press, 2010.
- [38] Joris van der Hoeven. The truncated Fourier transform and applications. In *Proceedings of ISSAC'04*, pages 290–296. ACM Press, 2004.
- [39] J. L. Holloway. Algorithms for computing Fibonacci numbers quickly. MSc Thesis. Oregon State Univ. 1988.
- [40] Alston S. Householder. Dandelin, Lobačevskiĭ, or Graeffe? *Amer. Math. Monthly*, 66:464–466, 1959.
- [41] Seung Gyu Hyun, Stephen Melczer, Éric Schost, and Catherine St-Pierre. Change of basis for  $m$ -primary ideals in one and two variables. In *Proceedings of ISSAC'19*, pages 227–234. ACM Press, 2019.
- [42] Seung Gyu Hyun, Stephen Melczer, and Catherine St-Pierre. A fast algorithm for solving linearly recurrent sequences. *ACM Communications in Computer Algebra*, page 100–103, 2019.
- [43] Walter Keller-Gehrig. Fast algorithms for the characteristic polynomial. *Theoret. Comput. Sci.*, 36(2-3):309–317, 1985.
- [44] Dmitry I. Khomovskiy. Efficient computation of terms of linear recurrence sequences of any order. *Integers*, 18:Paper No. A39, 12, 2018.
- [45] Donald E. Knuth. *The art of computer programming. Vol. 2: Seminumerical algorithms*. Addison-Wesley Publishing Co., Reading, Mass.-London-Don Mills, Ont, first edition, 1969.
- [46] Donald E. Knuth. *The art of computer programming. Vol. 2*. Addison-Wesley Publishing Co., Reading, Mass., second edition, 1981. Seminumerical algorithms, Addison-Wesley Series in Computer Science and Information Processing.
- [47] Donald E. Knuth. The Last Whole Errata Catalog, 1981. Department of Computer Science, Stanford University, Report. No. STAN-CS-81-868, <http://infolab.stanford.edu/pub/cstr/reports/cs/tr/81/868/CS-TR-81-868.pdf>.
- [48] Grégoire Lecerf. New recombination algorithms for bivariate polynomial factorization based on Hensel lifting. *Appl. Algebra Engrg. Comm. Comput.*, 21(2):151–176, 2010.



- [49] Katharina Lürwer-Brüggemeier and Martin Ziegler. On faster integer calculations using non-arithmetic primitives. In *Unconventional computation*, volume 5204 of *Lecture Notes in Comput. Sci.*, pages 111–128. Springer, Berlin, 2008.
- [50] Alain J. Martin and Martin Rem. A presentation of the Fibonacci algorithm. *Inform. Process. Lett.*, 19(2):67–68, 1984.
- [51] J. M. McNamee and V. Y. Pan. *Numerical methods for roots of polynomials. Part II*, volume 16 of *Studies in Computational Mathematics*. Elsevier/Academic Press, Amsterdam, 2013.
- [52] Marc Mezzarobba. NumGfun: a package for numerical and analytic computation and D-finite functions. In *Proceedings of ISSAC'10*, pages 139–146. ACM Press, 2010.
- [53] Preda Mihăilescu. Fast convolutions meet Montgomery. *Math. Comp.*, 77(262):1199–1221, 2008.
- [54] J. C. P. Miller and D. J. Spencer Brown. An algorithm for evaluation of remote terms in a linear recurrence sequence. *Computer Journal*, 9:188–190, 1966.
- [55] Peter L. Montgomery. Modular multiplication without trial division. *Math. Comp.*, 44(170):519–521, 1985.
- [56] Gregory Nuel and Jean-Guillaume Dumas. Sparse approaches for the exact distribution of patterns in long state sequences generated by a Markov source. *Theoret. Comput. Sci.*, 479:22–42, 2013.
- [57] V. Pan. Algebraic complexity of computing polynomial zeros. *Comput. Math. Appl.*, 14(4):285–304, 1987.
- [58] Victor Y. Pan. Solving a polynomial equation: some history and recent progress. *SIAM Rev.*, 39(2):187–220, 1997.
- [59] Michael S. Paterson and Larry J. Stockmeyer. On the number of non-scalar multiplications necessary to evaluate polynomials. *SIAM J. Comput.*, 2:60–66, 1973.
- [60] Alberto Pettorossi. Derivation of an  $O(k^2 \log n)$  algorithm for computing order- $k$  Fibonacci numbers from the  $O(k^3 \log n)$  matrix multiplication method. *Inform. Process. Lett.*, 11(4-5):172–179, 1980.

- [61] G. Pólya. Sur les séries entières, dont la somme est une fonction algébrique. *Enseignement Math.*, 22:38–47, 1921/1922.
- [62] A. J. van der Poorten. Some facts that should be better known, especially about rational functions. In *Number theory and applications (Banff, AB, 1988)*, volume 265 of *NATO Adv. Sci. Inst. Ser. C Math. Phys. Sci.*, pages 497–528. Kluwer Acad. Publ., Dordrecht, 1989.
- [63] Marco Protasi and Maurizio Talamo. On the number of arithmetical operations for finding Fibonacci numbers. *Theoret. Comput. Sci.*, 64(1):119–124, 1989.
- [64] Arthur Ranum. The general term of a recurring series. *Bull. Amer. Math. Soc.*, 17(9):457–461, 1911.
- [65] B. Ravikumar and G. Eisman. Weak minimization of DFA—an algorithm and applications. *Theoret. Comput. Sci.*, 328(1-2):113–133, 2004.
- [66] Rosace, E.-B. Escott, E. Malo, C.-A. Laisant, and G. Picou. Answers to Question 1541. [I25a] asked by G. de Rocquigny. *L'Intermédiaire des mathématiciens*, 7:172–177, 1900.
- [67] Arnold Schönhage. Variations on computing reciprocals of power series. *Inform. Process. Lett.*, 74(1-2):41–46, 2000.
- [68] Joseph Shortt. An iterative program to calculate Fibonacci numbers in  $O(\log n)$  arithmetic operations. *Inform. Process. Lett.*, 7(6):299–303, 1978.
- [69] Victor Shoup. A fast deterministic algorithm for factoring polynomials over finite fields of small characteristic. In *Proceedings of ISSAC'91*, pages 14–21. ACM Press, 1991.
- [70] Victor Shoup. A new polynomial factorization algorithm and its implementation. *J. Symbolic Comput.*, 20(4):363–397, 1995.
- [71] A. Storjohann. High-order lifting. In *Proceedings of ISSAC'02*, pages 246–254. ACM Press, 2002.
- [72] V. Strassen. Einige Resultate über Berechnungskomplexität. *Jahresbericht der Deutschen Mathematiker-Vereinigung*, 78(1):1–8, 1976/77.
- [73] Volker Strassen. Polynomials with rational coefficients which are hard to compute. *SIAM J. Comput.*, 3:128–149, 1974.

- [74] Daisuke Takahashi. A fast algorithm for computing large Fibonacci numbers. *Inform. Process. Lett.*, 75(6):243–246, 2000.
- [75] Friedrich J. Urbanek. An  $O(\log n)$  algorithm for computing the  $n$ th element of the solution of a difference equation. *Inform. Process. Lett.*, 11(2):66–67, 1980.
- [76] Thomas C. Wilson and Joseph Shortt. An  $O(\log n)$  algorithm for computing general order- $k$  Fibonacci numbers. *Inform. Process. Lett.*, 10(2):68–75, 1980.