



Data Augmentation by Generative Adversarial Networks for Semantic Segmentation of Satellite Images

Onur Tasar, Alain Giros, Yuliya Tarabalka, Pierre Alliez, Sébastien Clerc

► To cite this version:

Onur Tasar, Alain Giros, Yuliya Tarabalka, Pierre Alliez, Sébastien Clerc. Data Augmentation by Generative Adversarial Networks for Semantic Segmentation of Satellite Images. SophIA Summit, Nov 2020, Sophia Antipolis, France. hal-03116718

HAL Id: hal-03116718

<https://inria.hal.science/hal-03116718>

Submitted on 20 Jan 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

DATA AUGMENTATION BY GENERATIVE ADVERSARIAL NETWORKS FOR SEMANTIC SEGMENTATION OF SATELLITE IMAGES

Onur Tasar¹(onur.tasar@inria.fr), Alain Giros³, Yuliya Tarabalka⁵, Pierre Alliez^{1,2}, Sébastien Clerc⁴

INRIA SOPHIA ANTIPOLIS TITANE TEAM¹, UNIVERSITÉ CÔTE D'AZUR², CENTRE NATIONAL D'ÉTUDES SPATIALES (CNES)³, ACRI-ST⁴, LUXCARTA TECNOLOGIES⁵

PROBLEM DEFINITION


- Semantic segmentation consists in assigning a correct class label to each pixel in the image.
- Semantic segmentation of satellite images is a crucial step for automatic map generation. Training a Convolutional Neural Network (CNN) on an annotated set, and using the trained CNN to automatically generate maps for new satellite images is a common approach.
- CNNs generate unsatisfactory maps when training and test images look significantly different.



Training image



Test image




Unsatisfactory Map

- Changing contrast, brightness, etc. of the images in the training stage is a common data augmentation approach to better generalize CNNs [1, 2]. However, when training and test images have largely different color distributions, these augmentation methods cannot yield an excellent performance.

TRAINING A CLASSIFIER WITH THE DATA AUGMENTOR


- We propose to use Generative Adversarial Networks (GANs) for better data augmentation by performing style transfer between images.
- Our proposed learning method consists of a data augmentor and a classifier.
- In each training iteration, the data augmentor, which is a GAN, can stylize each image as one of the randomly selected training and test images. We call this operation random diversification. The diversified images are then used to train the classifier.



- In the first stage, we train the data augmentor to be able to stylize each image like any other. In the second stage, we freeze the data augmentor and train the classifier.
- The data augmentor allows the classifier to learn from data that is representative for both training and test images.
- More details can be found in our papers related to GAN based data augmentation by performing style transfer between satellite images [3, 4, 5, 6].

STYLE TRANSFER BETWEEN MULTIPLE SATELLITE IMAGES

- Leibnitz, Bad Ischl, and Vaduz are test cities, the others are used for training.
- The cells in yellow represent real images, the others are fake images generated by our data augmentor.



- Since the data augmentor enables the classifier to learn from data that is similar to those of each training and test images, the classifier generates much better maps.

IoU scores for each class when we train a classifier without (top) and with (bottom) the data augmentor.

Bad Ischl				Vaduz				Leibnitz			
Build.	Road	Tree	Ovr.	Build.	Road	Tree	Ovr.	Build.	Road	Tree	Ovr.
51.86	39.33	79.80	56.99	38.04	34.33	75.88	49.42	2.29	1.13	0.04	1.15
60.52	53.08	82.87	65.49	53.03	39.44	71.77	54.75	43.31	34.28	73.18	50.26

REFERENCES

- [1] O. Tasar, Y. Tarabalka, and P. Alliez. Incremental learning for semantic segmentation of large-scale remote sensing data. *IEEE JSTARS*, 2019.
- [2] O. Tasar, Y. Tarabalka, and P. Alliez. Continual learning for dense labeling of satellite images. *IEEE IGARSS*, 2019.
- [3] O. Tasar, S L Happy, Y. Tarabalka, and P. Alliez. ColorMapGAN: Unsupervised domain adaptation for semantic segmentation using color mapping generative adversarial networks. *IEEE TGRS*, 2020.
- [4] O. Tasar, S L Happy, Y. Tarabalka, and P. Alliez. SemI2I: Semantically consistent image-to-image translation for domain adaptation of remote sensing data. *IEEE IGARSS*, 2020.
- [5] O. Tasar, Yuliya Tarabalka, A. Giros, P. Alliez, and S. Clerc. StandardGAN: Multi-source domain adaptation for semantic segmentation of very high resolution satellite images by data standardization. *IEEE/CVF CVPRW*, 2020.
- [6] O. Tasar, A. Giros, Y. Tarabalka, P. Alliez, and S. Clerc. DAugNet: Unsupervised, multi-source, multi-target, and life-long domain adaptation for semantic segmentation of satellite images. *IEEE TGRS*, 2020.