

## Deep learning for eye fundus diagnosis based on multispectral imaging

Francisco J Burgos-Fernandez, Buntheng Ly, Fernando Díaz-Doutón, Meritxell Vilaseca, Jaume Pujol, Maxime Sermesant

## ▶ To cite this version:

Francisco J Burgos-Fernandez, Buntheng Ly, Fernando Díaz-Doutón, Meritxell Vilaseca, Jaume Pujol, et al.. Deep learning for eye fundus diagnosis based on multispectral imaging. ARVO 2022 - Annual meeting of the Association for Research in Vision and Ophthalmology, May 2022, Denver, United States. , Investigative Ophthalmology & Visual Science (IOVS), 63 (7), pp.1, 2022. hal-03695867

## HAL Id: hal-03695867 https://inria.hal.science/hal-03695867v1

Submitted on 15 Jun2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## CONTROL ID: 3710089

SUBMITTER (NAME ONLY): Francisco Burgos-Fernandez

TITLE: Deep learning for eye fundus diagnosis based on multispectral imaging

SESSION TITLE: Machine Learning: Segmentation and Classification

SESSION TYPE: Poster Session

**AUTHORS/INSTITUTIONS:** F.J. Burgos-Fernandez, F. Díaz-Doutón, M. Vilaseca, J. Pujol, Universitat Politecnica de Catalunya, Barcelona, Catalunya, SPAIN|F.J. Burgos-Fernandez, B. Ly, M. Sermesant, Inria Centre de Recherche Sophia Antipolis Mediterranee, Sophia Antipolis, Provence-Alpes-Côte d'Azu, FRANCE|M. Sermesant, Electrophysiology and Heart Modelling Institute (IHU, Liryc), Pessac, FRANCE|

**Commercial Relationships Disclosure:** Francisco Burgos-Fernandez: Commercial Relationship: Code N (No Commercial Relationship) | Buntheng Ly: Commercial Relationship: Code N (No Commercial Relationship) | Fernando Díaz-Doutón: Commercial Relationship: Code N (No Commercial Relationship) | Meritxell Vilaseca: Commercial Relationship: Code N (No Commercial Relationship) | Jaume Pujol: Commercial Relationship: Code N (No Commercial Relationship) | Maxime Sermesant: Commercial Relationship: Code N (No Commercial Relationship) ABSTRACT BODY:

**Purpose:** A new deep-learning based method for automatic eye fundus diagnosis using multispectral images is proposed. The method discriminates between healthy and diseased eyes exploiting the potential of multispectral data. Among other pathologies, those mainly considered were age-related macular degeneration (ARMD), glaucoma and diabetic retinopathy as the leading causes of vision loss affecting the retina.

**Methods:** We analyzed 68 healthy and 68 diseased eyes from 89 subjects, 63% females and 37% males (19-95 years); only patients with retinal and/or choroidal pathologies were included. For each eye, 15 images from 400 nm to 1300 nm were acquired with a novel multispectral fundus camera. The deep learning network was adapted from that developed by Ly et al. (Ly B. et al. Lect. Notes Comput. Sc., vol. 12738, 2021) for sustained ventricular arrhythmia prediction, which involves a conditional variational autoencoder (CVAE) and a classifier model. The low dimensional features generated by the encoder are the inputs for the classifier and the decoder, which reconstructs the original sequence of 15 spectral images. These features contain information of healthy and diseased structures such as drusen, scars, edemas and neovascularization. The error between the encoder-decoder outputs is used to improve the performance of the network. The dataset was divided in training/validation (80% data) and test (20% data) datasets.

**Results:** The multispectral images offered very relevant information of healthy (Fig. 1 left) and diseased (Fig. 1 right) eye fundus structures to be used as input data for the proposed algorithm. The CVAE ran for 85 epochs leading to a classification accuracy of 96.43%, a loss of 0.20, a sensitivity of 92.86% and a specificity of 100.00% when discriminating between healthy and diseased fundus of the test dataset.

**Conclusions:** The proposed CVAE for the automatic classification of healthy and diseased eyes from multispectral eye fundus images produced an excellent outcome, highlighting the power of an encoder-decoder network and the significant information retrieved from multispectral images in the visible and near-infrared beyond 900 nm, a relatively unexplored range. Future work will focus on differentiating among pathologies by means of approaches such as attention maps, which help identifying abnormal structures.