

Pythae: Unifying Generative Autoencoders in Python -A Benchmarking Use Case

Clément Chadebec, Louis J Vincent, Stéphanie Allassonnière

► To cite this version:

Clément Chadebec, Louis J Vincent, Stéphanie Allassonnière. Pythae: Unifying Generative Autoencoders in Python - A Benchmarking Use Case. Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmark, Nov 2022, New Orleans, United States. hal-03697439

HAL Id: hal-03697439 https://inria.hal.science/hal-03697439

Submitted on 16 Jun 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Pythae: Unifying Generative Autoencoders in Python A Benchmarking Use Case

Clément Chadebec * Université Paris Cité, INRIA, Inserm, SU clement.chadebec@inria.fr Louis J. Vincent * Implicity[†] Université Paris Cité, INRIA, Inserm, SU louis.vincent@inria.fr

Stéphanie Allassonnière * Université Paris Cité, INRIA, Inserm, SU stephanie.allassonniere@inria.fr

Abstract

In recent years, deep generative models have attracted increasing interest due to their capacity to model complex distributions. Among those models, variational autoencoders have gained popularity as they have proven both to be computationally efficient and yield impressive results in multiple fields. Following this breakthrough, extensive research has been done in order to improve the original publication, resulting in a variety of different VAE models in response to different tasks. In this paper we present **Pythae**, a versatile *open-source* Python library providing both a *unified implementation* and a dedicated framework allowing *straightforward*, *reproducible* and *reliable* use of generative autoencoder models. We then propose to use this library to perform a case study benchmark where we present and compare 19 generative autoencoder models representative of some of the main improvements on downstream tasks such as image reconstruction, generation, classification, clustering and interpolation. The open-source library can be found at https://github.com/clementchadebec/benchmark_VAE.

1 Introduction

Over the past few years, generative models have proven to be a promising approach for modelling datasets with complex inherent distributions such a natural images. Among those, Variational AutoEncoders (VAE) [33, 50] have gained popularity due to their computational efficiency and scalability, leading to many applications such as speech modelling [8], clustering [21, 62], data augmentation [12] or image generation [48]. Similarly to autoencoders, these models encourage good reconstruction of an observed input data from a latent representation, but they further assume latent vectors to be random variables involved in the generation process of the observed data. This imposes a latent structure wherein latent variables are driven to follow a prior distribution that can then be used to generate new data. Since this breakthrough, various contributions have been made to enrich the original VAE scheme through new generating strategies [21, 57, 24, 4, 44], reconstruction objectives [37, 54] and more adapted latent representations [27, 31, 58, 3, 12] to cite a few. A drawback of VAEs is that due to the intractability of the log-likelihood objective function, VAEs have to resort to optimizing a lower bound on the true objective as a proxy, which has proven to be a major limitation of the model [9, 1, 27, 18, 63]. Hence, extensive research has been proposed to improve this bound

^{*}Centre de Recherche des Cordeliers, 15 Rue de l'École de Médecine, 75006 Paris

[†]https://www.implicity.com - Implicity Paris, France.

through richer distributions [51, 49, 34, 11]. More recently, it has been shown that autoencoders can be turned into generative approaches through latent density estimation [24], extending the concept of *Generative AutoEncoders* (GAE) to a more general class of autoencoder models.

Nonetheless, most of this research has been done in parallel across disjoint sub-fields of research and to the best of our knowledge little to no work has been done on homogenising and integrating these distinct methods in a common framework. Moreover, for many of the aforementioned publications, implementations may not be available or maintained, therefore requiring time-consuming re-implementation. This induces a strong bottleneck for research to move forward in this field and makes reproducibility challenging, which calls for the need of a unified generative autoencoder framework. To address this issue we introduce **Pythae** (**Python AutoEncoder**), a versatile open source Python library for generative autoencoders providing unified implementations of common methods, along with a reproducible framework allowing for easy model training, data generation and experiment tracking. We then propose to illustrate the usefulness of the proposed library on a benchmark case study of 19 generative autoencoder methods on classical image datasets. We consider five different downstream tasks: image reconstruction and generation, latent vector classification and clustering, and image interpolation on three well known imaging datasets.

2 Variational autoencoders

In this section, we recall the original VAE setting and present some of the main improvements that were proposed to enhance the model.

2.1 Background

Given $x \in \mathbb{R}^D$, a set of observed variables deriving from an unknown distribution p(x), a VAE assumes that there exists $z \in \mathbb{R}^d$ such that z is a latent representation of x. The generation process of x thus decomposes as

$$p_{\theta}(x) = \int_{\mathcal{Z}} p_{\theta}(x|z) p_z(z) dz , \qquad (1)$$

where p_z is the *prior distribution* on the latent space \mathbb{R}^d . The distribution $p_{\theta}(x|z)$ is referred to as the *decoder* and is modelled with a simple parametric distribution whose parameters are given by a neural network. Since the true posterior $p_{\theta}(z|x)$ is most of the time intractable due to the integral in Eq. (1) recourse to Variational Inference [29] is needed and a variational distribution $q_{\phi}(z|x)$ which we refer to as the *decoder* is introduced. The approximate posterior q_{ϕ} is again taken as a simple parametric distribution whose parameters are also modelled by a neural network. This allows to define an unbiased estimate \hat{p}_{θ} of the marginal distribution $p_{\theta}(x)$ using importance sampling with $q_{\phi}(z|x)$ *i.e.* $\hat{p}_{\theta}(x) = \frac{p_{\theta}(x|z)p_{z}(z)}{q_{\phi}(z|x)}$ and $\mathbb{E}_{z \sim q_{\phi}}[\hat{p}_{\theta}] = p_{\theta}$. Applying Jensen's inequality leads to a lower bound on the likelihood given in Eq. (1):

$$\log \underbrace{\mathbb{E}_{z \sim q_{\phi}}\left[\widehat{p}_{\theta}(x)\right]}_{p_{\theta}(x)} \ge \mathbb{E}_{z \sim q_{\phi}}\left[\log \widehat{p}_{\theta}(x)\right] = \underbrace{\mathbb{E}_{z \sim q_{\phi}}\left[\log p_{\theta}(x|z)\right]}_{\text{reconstruction}} - \underbrace{\mathcal{D}_{KL}\left[q_{\phi}(z|x)||p_{z}(z)\right]}_{\text{regularisation}},$$
(2)

where $\mathcal{D}_{KL}(p||q)$ is the Kullback-Leibler divergence between distributions p and q. This bound is referred to as the Evidence Lower Bound (ELBO) [33] and is used as the training objective to maximize in the traditional VAE scheme. It can be interpreted as a two terms objective [24] where the *reconstruction* loss forces the output of the decoder to be close to the original input x, while the *regularisation* loss forces the posterior distribution $q_{\phi}(z|x)$ outputted by the encoder to be close to the prior distribution $p_z(z)$. Under standard VAE assumption, the prior distribution is a multivariate standard Gaussian $p_z = \mathcal{N}(0, I_d)$, the approximate posterior is set to $q_{\phi}(z|x) = \mathcal{N}(z|\mu(x), \Sigma(x))$ where $(\mu(x), \Sigma(x))$ are outputs of the encoder network. $p_{\theta}(x|z)$ is chosen depending on the modelling of the data (*e.g.* $\mathcal{N}(\mu_{\theta}(z), \sigma \cdot I_D), \sigma > 0$) with μ_{θ} given by the decoder network). Building on the breakthrough of VAEs, several papers have proposed improvements to the model.

2.2 Enhancing the model

Improving the prior It has been shown that the role of the prior distribution p_z is crucial in the good performance of the VAE [28] and choosing a family of overly simplistic priors can lead

to over-regularization [17] and poor reconstruction performance [19]. Hence, multi-modal priors [42, 21, 57] were proposed, followed by hierarchical latent variable models [55, 35] and prior learning based approaches [15, 2] to address the poor expressiveness of the prior distribution and model richer generative distributions. Considering a specific geometry of the latent space also led to alternative priors taking into account geometrical aspects of the latent space [20, 22, 41, 3, 13, 53, 30, 12]. Another interesting approach proposed for instance in [58, 24] consists in using density estimation post training with another distribution or normalising flows [49] on the learnt latent codes to generate.

Towards a better lower bound Another major axis of improvement of the VAE model has been to tighten the gap between the ELBO objective and the true log probability [9, 1, 27, 18, 63]. The ELBO objective can indeed be rewritten as the difference between the true log probability and a KL divergence between the approximate posterior and the true posterior

$$\mathcal{L}_{\text{ELBO}}(x) = \log p_{\theta}(x) - \mathcal{D}_{KL} \left[q_{\phi}(z|x) || p(z|x) \right].$$
(3)

Hence, if one wants to make the ELBO gap tighter, particular attention should be paid to the choice in the approximate posterior $q_{\phi}(z|x)$. In the original model, $q_{\phi}(z|x)$ is chosen as a simple distribution for tractability of the ELBO in Eq. (2). However, several approaches have been proposed to extend the choice of q_{ϕ} to a wider class of distributions using MCMC sampling [51] or normalising flows [49]. For instance, Kingma et al. [34] improve upon the works of [49] with inverse auto-regressive normalising flow (IAF), a new type of normalizing flow that better scales to high-dimensional latent spaces. With this objective in mind a Hamiltonian VAE aimed at targeting the true posterior during training with a Hamiltonian Monte Carlo [43] inspired scheme was proposed [11] and extended to Riemannian latent spaces in [12].

Encouraging disentanglement One key interest of VAEs is to learn a more representative and interpretable latent representation of the input data. In that regard, several approaches have been proposed encouraging a better disentanglement of the features in the latent space. Higgins et al. [27] first argue that increasing the weight of the KL divergence term in the ELBO loss enforces a higher disentanglement of the latent features as the posterior probability is forced to match a multivariate normal standard Gaussian. Several other methods were developed following this idea by for instance gradually increasing the proximity between the posterior and the prior [10], augmenting the VAE objective with a penalty that encourages factorial representation of the marginal distributions [31] or enforcing an added penalty on the total correlation favouring disentanglement [14].

Amending the distance between distributions It can be stressed that the reconstruction term $\mathbb{E}_{z \sim q_{\phi}(z|x)}[\log p_{\theta}(x|z)]$ in eq. (2) has a crucial role in the reconstruction and that its choice should be dependent of the application. For instance, methods such as using a discriminator [37] or using a deterministic differentiable loss function [54] acting as a distance between the input data and its reconstruction were also proposed. The second term in the ELBO measures the distance between the approximate posterior and the prior distribution through the KL divergence and it has however been argued that other distances between probability distributions could be used instead. Hence, approaches using a GAN to distinguish samples from the posterior from samples from the prior distribution [40] or methods based on optimal transport were also proposed [56, 64].

3 The Pythae library

Why Pythae ? To the best of our knowledge, there exists no framework combining and unyfing implementations of state-of-the-art Generative AutoEncoder (GAE) methods. This induces both a strong brake for reproducible research and democratisation of the models since implementations might be difficult to adapt to other use-cases, no longer maintained, or completely unavailable.

Project vision Starting from this observation, we created **Pythae**, an open-source python library inspired from [47, 61] providing unified implementations of generative autoencoding methods, allowing for easy use and training of GAE models. This provides *on-the-shelf* ready-to-use implementations directly applicable to any use case. This library is distributed under the Apache2.0 licence. Pythae is unit-tested ensuring code quality and continuous development with a code coverage of 97% as of release 0.1. To make it as accessible as possible, the library has an online documentation³ and is also

³The full documentation can be found at https://pythae.readthedocs.io/en/latest/.

explained and illustrated through tutorials available either on a local machine or on the *Google Colab* platform [7]. This library is intended to evolve with the addition of new models through time to enrich the existing model base. Furthermore, beyond providing unified implementations, we believe that Pythae can also provide an open model testing environment driven by the community where people can contribute by adding their own models, and by doing so encourage reproducible research and the gathering of proposed methods at a same location.

Code structure Pythae was thought for easy model training and data generation, while striving for simplicity with a quick and user-friendly model selection and configuration. The backbone of the library is the module *pythae.models* in which all the autoencoder models are implemented. Each model implementation is accompanied with a configuration *dataclass* containing any hyperparameters relative to the model and allowing easing configuration loading and saving from json files. All the models are implemented using a common API allowing for a seamless integration with pythae.trainers (for training) and pythae.samplers (for generation) along with a simplified usage as illustrated in Fig. 1. In particular, Pythae provides pipelines allowing to train an autoencoder model or to generate new data with only a few lines of code. It mainly relies on the Pytorch [46] framework and in its basic usage only essential hyper-parameter configurations and data (arrays or tensors) are needed to launch a model training or generation. More advanced options allowing further flexibility such as defining custom encoder and decoder neural nets are also available and can be found in the documentation and tutorials. Moreover, the library also integrates an easy-to-use experiments tracking tool (wandb) [6] allowing to monitor runs launched with Pythae and compare them through a graphic interface. It can adapt to various types of data through the use of different already-implemented or user provided encoder and decoder neural-network architectures. In addition, Pythae also provides several ways to generate new data through different popular sampling methods in the *pythae.samplers* module. We detail some aspects of the library in Appendix. A.



Figure 1: Pythae library diagram

4 Case study benchmark

We now propose a case study where we use this library to perform a benchmark comparison of implemented models on image reconstruction and generation, latent vector classification and clustering, and image interpolation on 3 datasets and 2 distinct autoencoding architectures.

4.1 Benchmark setting

In this section, we present the setting of the benchmark. Comprehensive results for all the experiments are available through the monitoring tool [6] used in Pythae to allow complete transparency. We also intend to share the trained models upon acceptance.

The data To perform the different tasks presented in this paper, 3 classical image datasets are considered: MNIST [38], CIFAR10 [36] and CELEBA [39]. These datasets are publicly available, widely used for generative model related papers and have well known associated metrics in the literature. Each dataset is split into a train set, a validation set and a test set. For MNIST and CIFAR10 the validation set is composed of the last 10k images extracted from the official train set and the test set corresponds to the official one. For CELEBA, we use the official train/val/test split.

The models We propose to compare 19 generative autoencoder models representative of the improvements proposed in the literature and presented in Sec. 2.2. Descriptions and explanations of each implemented model can be found in Appendix. D.4. We use as baseline an Autoencoder (AE) and a Variational Autoencoder (VAE). To assess the influence of a more expressive prior, we propose using a VAE with VAMP prior (VAMP) [57] and regularised autoencoders with either a gradient penalty (RAE-GP) or a L2 penalty on the weights of the decoder (RAE-L2) that use ex-post density estimation [24]. To represent models trying to reach a *better lower bound*, we choose a Importance Weighted Autoencoder (IWAE) [9] and VAEs adding either simple linear normalising flows (VAE-lin-NF) [49] or using IAF (VAE-IAF) [34]. For disentanglement-based models, we select a β -VAE [27], a Factor VAE [31] and a β -TC VAE [14]. To stress the *influence of the distance* used between distributions we add a Wasserstein Autoencoder (WAE)[56] and an InfoVAE [64] with either Inverse Multi-Quadratic (IMQ) or a Radial Basis Function kernel (RBF) together with an Adversarial Autoencoder (AAE)[40], a VAEGAN[37] and a VAE using structural similarity metric for reconstruction (MSSSIM-VAE) [54]. Finally, we add a VQVAE [58] since having a discrete latent space has proven to yield promising results. Models implemented in Pythae requiring too much training time or more intricate hyper-parameter tuning were excluded from the benchmarks.

In the following, we will distinguish *AE-based* (autoencoder-based) methods (AE, RAE, WAE and VQVAE) from the other *variational-based* methods.

Training paradigm Each of the aforementioned models is equipped with the same neural network architecture for both the encoder and decoder leading to a comparable number of parameters ⁴. For each task, 10 different configurations are considered for each model, allowing a simple exploration of the models' hyper-parameters, leading to 10 trained models for each dataset and each neural network type (ConvNet or ResNet) leading to a total of 1140 models⁵. It is important to note that the hyper-parameter exploration is not exhaustive and models sensitive to hyper-parameter tuning may have better performances with a more extensive parameter search. The sets of hyper-parameters explored are detailed in Appendix. D.4 for each model.

4.2 Experiments

In this section, we present the main results observed on 5 downstream tasks.

4.2.1 Fixed latent dimension

In this first part, latent dimensions are set to 16, 256 and 64 for the MNIST, CIFAR10 and CELEBA datasets respectively. See results per model and across the 10 configurations specified in Appendix. D.4 to assess the influence of the parameters on the tasks.

Task 1: Image reconstruction For each model reconstruction error is evaluated by selecting the configuration minimising the Mean Square Error (MSE) on the validation set, while results are shown on the test set⁶. We show in Table. 1 the MSE and Frechet Inception Distance⁷ (FID) [26] of the reconstructions from this model on the test set. It is important to note that using the MSE as a metric places models using different reconstruction losses (VAEGAN and MSSSIM-VAE) at a disadvantage. As expected, the autoencoder-based models seem to perform best for the reconstruction task. Nonetheless, this experiment also shows the interest of adding regularisation to the autoencoder since improvements over the AE (RAE-GP, RAE-L2) achieve better performance than the regular AE. Moreover, β -VAE type models demonstrate their versatility as small enough β values can lead to less regularisation, therefore favouring a better reconstruction.

Task 2: Image generation We consider an image generation task with the trained models. In this experiment, we also explore different ways of sampling new data, either 1) using a simple distribution

⁴Some models may actually have additional parameters in their intrinsic structure *e.g.* a VQVAE learns a dictionary of embeddings, a VAMP learns the pseudo-inputs, a VAE-IAF learns the auto-regressive flows. Nonetheless, since we work on images, the number of parameters remains in the same order of magnitude.

⁵The training setting (curves, configs ...) can be found at https://wandb.ai/benchmark_team/ trainings while detailed experimental set-up is available in Appendix. C

⁶See the whole results at https://wandb.ai/benchmark_team/reconstructions

⁷We used the implementation of https://github.com/bioinf-jku/TTUR

chosen as $\mathcal{N}(0, I_d)$ and corresponding to the prior for variational approaches (\mathcal{N}); 2) fitting a 10 components mixture of Gaussian in the latent space post training as proposed in [24] (GMM), 3) fitting a normalising flow taken as a Masked Autoregressive Flow (MAF) [45] or 4) fitting a VAE in a similar fashion as [19]. For the MAF, two-layer MADE [23] are used. For each sampler, we select the models achieving the lowest FID on the validation set and compute the Inception Score⁸ (IS) [52] and the FID on the test set⁹. The main results are shown in Table. 3 for the normal and GMM sampler (see Appendix. D.2 for the other sampling schemes). One of the key findings of this experiment is that performing *ex-post* density (therefore not using the standard Gaussian prior) for the variational approach tends to almost always lead to better generation metrics even when a simple 10-components mixture of Gaussian is used. Interestingly, we note that when a more advanced density estimation model such as a MAF is used, results appear equivalent to those of the GMM (see Appendix. D.2). This may be due to the simplicity of the database we used and in consequence of the distribution of the latent codes that can be approximated well enough with a GMM. It should nonetheless be noted that the number of components in the GMM remains a key parameter which was set to the number of classes for MNIST and CIFAR10 since it is known, however too high a value may lead to overfitting while a low one may lead to worse results. For this task the adversarial approach proposed in the VAEGAN clearly surpasses peers on MNIST and CELEBA with impressive results when compared to other models. Nonetheless, fitting such a model may be challenging due to the adversarial approach and results can be considerably affected if parameters are not chosen correctly (see Appendix. D.4).

Task 3: Classification To measure the meaningfulness of the learned latent representations we perform a simple classification task with a single layer classifier as proposed in [16]. The rationale behind this is that if a GAE succeeds in learning a disentangled latent representation a simple linear classifier should perform well [5]. A single layer classifier is trained in a supervised manner on the latent embeddings of MNIST and CIFAR10. The train/val/test split used is the same as for the autoencoder training. For each model configuration, we perform 20 runs of the classifier on the latent embeddings and define the best hyper-parameter configuration as the one achieving the highest mean accuracy on these 20 runs on the validation set. We report the mean accuracy on the test set across the 20 runs for the selected configuration in Table. 2 (left)¹⁰. As expected, models explicitly encouraging disentanglement in the latent space such as the β -VAE and β -TC VAE achieve better classification when compared to a standard VAE. Nonetheless, AE-based models seem again the best suited for such a task since variational approaches tend to enforce a continuous space, consequently bringing latent representations of different classes closer to each other.

Task 4: Clustering As a complement to the previous task, performing clustering directly in the latent space of the trained autoencoders can give insights on the quality of the latent representation. Indeed, a well defined latent space will maintain the separation of the classes inherent to the datasets, leading to easy and stable k-means performances. To do so, we propose to fit 100 separate runs of the k-means algorithm and we show the mean accuracy obtained on the train embeddings in Table. 2 (right)¹¹. This experiment allows us to explore and measure the *clusterability* of the generated latent spaces [5]. To measure accuracy we assign the label of the most prevalent class to each cluster. The conclusions of this experiment are slightly different from the previous one since models targeting disentanglement seem to be equalled by the original VAE. Interestingly, adversarial approaches and other alternatives to the standard VAE KL regularisation method seem to achieve the best results.

Task 5: Interpolation Finally, we propose to assess the ability of the model to perform meaningful interpolations. For this task, we consider a starting and ending image in the test set of MNIST and CIFAR10 and perform a linear interpolation in the generated latent spaces between the two encoded images. We show in Appendix. B the decoding along the interpolation curves. For this task, no metric was found relevant since the notion of "good" interpolation can be disputable. Nonetheless, the obtained interpolated images can be reconstructed and qualitatively evaluated. For this task, variational approaches were found to obtain better results as the inherent structure the posterior distribution imposes in the latent space results in a "smoother" transition from one image to another

⁸We used the implementation of https://github.com/openai/improved-gan

⁹See the whole results at https://wandb.ai/benchmark_team/generations

¹⁰See the whole results at https://wandb.ai/benchmark_team/classifications

¹¹See the whole results at https://wandb.ai/benchmark_team/clustering

when compared to autoencoders that mainly superpose images, especially in higher dimensional latent spaces.

4.2.2 Varying latent dimension

An important parameter of autoencoder models which is too often neglected in the literature is the dimension of the latent space. We now propose to keep the same configurations as previously but re-evaluate Tasks 1 to 5 with the latent space varying in the range [16, 32, 64, 128, 256, 512]. Results are shown in Fig. 2 for MNIST and a ConvNet¹² (see Appendix. B and D for CIFAR, ResNet and interpolations). For the generation task, we select the sampler with lowest FID on the validation set.

Assessing the influence of the latent dimension A clear difference in behaviour is exhibited between variational-based and AE-based methods. For each given task, AEs share a common trend with respect to the evolution of the latent dimension: a common optimal latent dimension is found for each task, but differs drastically among different tasks (e.g 512 for reconstruction, 16 for generation, either 16 or 512 for classification and 512 for clustering with the MNIST dataset). This suggests the existence of a common intra-group optimal latent space dimension for a given task. In addition, we observe that β -VAE type methods (with the right hyper-parameter choice) can exhibit similar behaviours to AE models. The same observation can be made for variational-based methods, where it is interesting to note that although lower performances are achieved, the optimal latent dimension varies less with respect to the choice of the task. Therefore, a latent dimension of 16 to 32 appears to be the optimal choice for all 4 Tasks on the MNIST dataset, and 32 to 128 on the CIFAR10 dataset. It should be noted that unsupervised tasks such as clustering of the latent representation of the CIFAR10 dataset are hard and models are expected to perform poorly leading to less interpretable results.



Figure 2: *From top to bottom:* Evolution of the reconstruction MSE, generation FID, classification accuracy and clustering accuracy with respect to the latent space dimension on the MNIST dataset.

5 Conclusion

In this paper, we introduced **Pythae**, a new open-source Python library unifying common and state-of-the-art Generative AutoEncoder (GAE) implementations, allowing reliable and reproducible

¹²MSSSIM-VAE was removed from this plot for visualisation purposes.

Model	$\begin{array}{ll} \text{MNIST} (16) \\ \text{MSE} \downarrow & \text{FID} \downarrow \end{array}$		$\begin{array}{c} ConvNet\\ CIFAR10 (256)\\ MSE \downarrow FID \downarrow \end{array}$		CELEF MSE↓	BA (64) FID ↓	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$		Res CIFARI MSE↓	Net 10 (256) FID ↓	CELEBA (64) MSE \downarrow FID \downarrow		
VAE	16.85	30.71	16.24	218.66	9.83	49.22	17.24	36.06	16.33	176.63	10.59	58.75	
VAMP	24.17	44.95	17.45	221.40	10.81	51.64	17.11	37.58	16.87	177.03	11.50	60.89	
IWAE	14.14	34.28	16.19	237.14	9.47	50.00	15.79	38.74	16.02	183.37	10.14	60.18	
VAE-lin-NF	16.75	31.14	16.57	221.39	9.90	49.84	17.23	36.74	16.59	177.08	10.68	58.73	
VAE-IAF	16.71	30.64	16.33	223.65	9.87	50.05	17.05	35.98	16.39	177.05	10.63	58.41	
β -VAE	5.61	10.55	3.60	50.55	7.28	46.96	5.87	15.81	2.40	55.67	7.78	51.59	
β -TC VAE	6.78	14.11	5.06	53.49	7.65	50.82	7.12	18.44	4.05	66.89	8.08	52.70	
Factor VAE	17.27	30.39	16.41	224.3	10.16	53.61	18.13	37.97	16.55	176.8	10.93	59.46	
InfoVAE-IMQ	16.65	30.62	16.19	216.44	9.81	50.51	17.17	37.33	16.32	173.79	10.63	58.04	
InfoVAE-RBF	16.59	30.63	16.23	217.52	9.85	50.14	17.01	37.04	16.32	175.37	10.64	58.68	
AAE	5.59	10.87	2.60	40.66	7.25	50.22	5.98	17.01	2.33	55.93	7.76	50.97	
MSSSIM-VAE	32.60	37.91	39.42	276.70	35.60	124.52	33.67	40.25	39.61	254.34	35.43	119.92	
VAEGAN	15.49	5.54	31.40	289.35	8.91	86.58	23.25	11.35	30.22	300.07	9.32	86.32	
AE	5.47	11.61	2.82	41.98	7.03	51.08	6.13	13.74	2.34	55.43	7.74	50.54	
WAE-IMQ	5.55	11.29	2.81	41.79	7.04	52.11	5.78	16.21	2.34	56.55	7.74	50.50	
WAE-RBF	5.53	11.34	2.82	42.21	7.03	51.43	5.80	16.14	2.34	56.00	7.74	51.38	
VQVAE	5.59	11.02	2.84	44.60	7.06	52.27	6.00	15.27	2.34	55.84	7.73	50.29	
RAE-L2	5.24	15.37	2.25	49.28	6.90	53.98	5.76	17.27	2.35	57.85	7.74	51.07	
RAE-GP	5.31	12.08	2.81	41.15	7.06	51.85	5.83	15.69	2.34	56.71	7.76	51.36	

Table 1: Mean Squared Error (10^{-3}) and FID (lower is better) computed with 10k samples on the test set. For each model, the best configuration is the one achieving the lowest MSE on the validation set.

Table 2: *Left:* Mean test accuracy of a single layer classifier on the embedding obtained in the latent spaces of each model average on 20 runs. *Right:* Mean accuracy of 100 k-means fitted on the training embeddings coming from the autoencoders.

		Classif	ication			Clustering							
Model	Con	vNet	Res	sNet		Con	vNet	ResNet					
	MNIST	CIFAR10	MNIST	CIFAR10		MNIST	CIFAR10	MNIST	CIFAR10				
VAE	86.75 (0.05)	32.61 (0.03)	86.80 (0.03)	32.37 (0.03)		69.71 (2.01)	17.18 (0.68)	74.21 (0.97)	18.12 (0.74)				
VAMP	92.17 (0.02)	33.46 (0.17)	92.58 (0.04)	33.03 (0.22)		67.26 (1.25)	24.03 (0.24)	72.48 (0.96)	23.35 (0.11)				
IWAE	87.96 (0.04)	31.86 (0.04)	88.18 (0.03)	32.26 (0.04)		63.93 (1.73)	19.55 (0.67)	73.66 (2.30)	18.44 (0.86)				
VAE-lin-NF	86.04 (0.04)	31.57 (0.02)	85.85 (0.05)	31.74 (0.03)		65.48 (2.76)	17.09 (0.64)	68.80 (3.65)	18.74 (0.68)				
VAE-IAF	88.32 (0.02)	33.52 (0.02)	87.91 (0.02)	32.41 (0.02)		75.31 (1.69)	17.81 (0.73)	76.11 (2.15)	18.42 (0.66)				
β -VAE	93.67 (0.02)	45.15 (0.03)	94.10 (0.03)	40.01 (0.07)		73.13 (1.64)	24.64 (0.90)	76.54 (1.60)	24.78 (0.73)				
β -TC VAE	90.96 (0.02)	45.40 (0.05)	91.91 (0.02)	42.17 (0.07)		65.68 (0.91)	24.14 (0.65)	68.98 (2.67)	25.57 (0.61)				
Factor VAE	86.08 (0.06)	31.38 (0.04)	83.44 (0.05)	31.76 (0.04)		51.02 (1.73)	15.77 (0.60)	60.79 (2.06)	17.56 (0.68)				
InfoVAE-IMQ	86.33 (0.04)	32.48 (0.02)	86.31 (0.06)	32.10 (0.05)	11	68.17 (2.34)	16.65 (0.80)	71.31 (2.62)	18.10 (0.79)				
InfoVAE-RBF	85.94 (0.03)	32.50 (0.03)	86.12 (0.04)	31.67 (0.03)		66.02 (1.14)	16.22 (0.69)	71.93 (1.91)	18.61 (0.67)				
AAE	93.28 (0.03)	43.93 (0.07)	94.31 (0.03)	40.62 (0.11)		74.19 (3.22)	24.72 (0.75)	80.41 (2.09)	24.76 (0.53)				
MSSSIM-VAE	78.30 (0.03)	20.26 (0.06)	76.54 (0.03)	20.24 (0.04)	11	49.33 (1.32)	11.70 (0.19)	48.58 (1.37)	11.70 (0.17)				
VAEGAN	92.34 (0.02)	26.56 (0.04)	90.31 (0.03)	29.90 (0.03)		77.29 (1.19)	17.20 (0.45)	79.67 (0.90)	22.23 (0.44)				
AE	93.81 (0.02)	42.15 (0.07)	94.26 (0.03)	40.47 (0.13)	11	73.55 (0.60)	23.19 (0.52)	77.30 (0.84)	23.18 (0.37)				
WAE-IMQ	93.60 (0.02)	45.89 (0.07)	94.62 (0.03)	41.35 (0.03)		72.33 (2.92)	23.81 (0.61)	78.46 (3.48)	25.09 (0.82)				
WAE-RBF	93.72 (0.02)	43.38 (0.08)	94.51 (0.02)	40.63 (0.08)		74.20 (1.94)	23.70 (0.71)	77.33 (1.92)	24.66 (0.63)				
VQVAE	93.45 (0.02)	42.89 (0.07)	94.63 (0.04)	40.40 (0.09)		72.61 (0.40)	23.85 (0.48)	76.68 (2.36)	23.68 (0.37)				
RAE-L2	94.75 (0.01)	42.76 (0.08)	94.43 (0.03)	40.22 (0.05)		74.07 (0.36)	23.77 (0.54)	78.66 (0.29)	24.84 (0.73)				
RAE-GP	94.10 (0.02)	43.66 (0.07)	94.45 (0.02)	40.93 (0.14)		72.88 (0.52)	24.84 (0.53)	77.66 (1.29)	23.86 (0.32)				

model training, data generation and experiment tracking. This library was designed as an open model testing environment driven by the community, wherein peers are encouraged to contribute by adding their own models, and by doing so favour reproducible research and accessibility to ready-to-use GAE models. As an illustration of the capabilities of Pythae, we perform a benchmarking of 19 generative autoencoder models on 5 downstream tasks (image reconstruction, generation, classification, clustering and interpolation) leading to some key findings. We show that performing *ex-post* density estimation in the latent space to balance the potential poor expressiveness of the prior distribution (GMM sampling) tends to almost always improve image quality generation. Interestingly, using more complex density estimators than a GMM did not improve results. We also show that AE-based generative methods achieve the best results on most common tasks (reconstruction, generation, classification). However, they tend to be more sensitive to the choice of the latent dimension and don't scale well to high dimension on more complex tasks such as interpolation. Finally we show

Model	Sampler	MNI FID	IST IS ↑	Convl CIFAI FID	Net R10 IS	CELI FID	EBA IS ↑	MNI FID	ST IS ↑	ResN CIFAI FID	et R10 IS	CELE FID	EBA
VAE	パ GMM	28.5 26.9	2.1	241.0 235.9	2.2 2.3	54.8 52.4	1.9 1.9	31.3 32.3	2.0	181.7 179.7	2.5 2.5	66.6 63.0	1.6 1.7
VAMP	VAMP	64.2	2.0	329.0	1.5	56.0	1.9	34.5	2.1	181.9	2.5	67.2	1.6
IWAE		29.0	2.1	245.3	2.1	55.7	1.9	32.4	2.0	191.2	2.4	67.6	1.6
VAE-lin NF		29.3	2.1	240.3	2.1	56.5	1.9	32.5	2.0	185.5	2.4	67.1	1.7
VAE-IAF		28.4	2.1	237.0 236.0	2.2	55.5 55.4	1.9	30.6	2.1	183.6	2.5	62.8 66.2	1.7
	GMM	27.0	2.1	235.4	2.2	53.0	1.9	32.2	2.1	124.0	2.5	62.7	1./
β -VAE	GMM	9.2	2.1	92.2	3.0	51.7	1.9	19.1	2.0	1124.9	3.4	59.3	1.0
β -TC VAE	SMM GMM	21.3 11.6	2.1 2.2	116.6 89.3	2.8 4.1	55.7 51.8	1.8 1.9	20.7 13.3	2.0 2.1	125.8 106.5	3.4 3.7	65.9 59.3	1.6 1.7
FactorVAE	SMM GMM	27.0 26.9	2.1 2.1	236.5 234.0	2.2 2.2	53.8 52.4	1.9 2.0	31.0 32.7	2.0 2.1	185.4 184.4	2.5 2.5	66.4 63.3	1.7 1.7
InfoVAE - RBE	N	27.5	2.1	235.2	2.1	55.5	1.9	31.1	2.0	182.8	2.5	66.5	1.6
InfoVAE - IMO	GMM N	26.7 28.3	2.1 2.1	230.4 233.8	2.2 2.2	52.7 56.7	1.9 1.9	32.3 31.0	2.1 2.0	179.5 182.4	2.5 2.5	62.8 66.4	1.7 1.6
Into VAL - INIQ	GMM N	27.7	2.1 2.2	231.9 139.9	2.2 2.6	53.7 59.9	1.9 1.8	32.8 19.1	2.1 2.1	180.7 164.9	2.6 2.4	62.3 64.8	1.7 1.7
AAE	GMM	9.3	2.2	92.1	3.8	53.9	2.0	11.1	2.1	118.5	3.5	58.7	1.8
MSSSIM-VAE	M GMM	26.7	2.2 2.2	279.9 279.7	1.7 1.7	124.3 124.3	1.3 1.3	28.0 28.8	2.1	254.2 253.1	1.7 1.7	119.0 119.2	1.3 1.3
VAEGAN	N GMM	8.7 6.3	2.2 2.2	199.5 197.5	2.2 2.1	39.7 35.6	1.9 1.8	12.8 6.5	2.2 2.2	198.7 188.2	2.2 2.6	122.8 84.3	2.0 1.7
AE	 GMM	26.7	2.1	201.3	2.1	327.7	1.0	221.8	1.3	210.1	2.1	275.0 57.4	2.9
WAE - RBF	N GMM	21.2	2.2	175.1	2.0	332.6 55.0	1.0	21.2	2.1	170.2	2.3 3.4	69.4 58.3	1.6
WAE - IMQ	N GMM	18.9	2.2	164.4 96.5	2.2	64.6 51.7	1.7	20.3	2.1	150.7	2.5	67.1 57.7	1.6
VQVAE	N	28.2	2.0	152.2	2.0	306.9	1.0	170.7	1.6	195.7	1.9	140.3	2.2
RAE-L2	N	25.0	2.2	156.1	2.6	86.1	2.0	63.3	2.1	170.9	2.2	168.7	3.1
RAE - GP		9.1 27.1 9.7	2.2 2.1 2.2	85.3 196.8 96.3	2.1 3.7	55.2 86.1 52.5	1.9 2.4 1.9	61.5 11.4	2.1 2.2 2.1	122.5 229.1 123.3	3.4 2.0 3.4	201.9 59.0	1.8 3.1 1.8

Table 3: Inception Score (higher is better) and FID (lower is better) computed with 10k samples on the test set. For each model and sampler we report the results obtained by the model achieving the lowest FID score on the validation set.

that the choice of the latent dimension exhibits noteworthy distinguishable trends between 2 distinct groups: AE-based and variational-based methods.

Acknowledgments and Disclosure of Funding

The research leading to these results has received funding from the French government under management of Agence Nationale de la Recherche as part of the "Investissements d'avenir" program, reference ANR-19-P3IA-0001 (PRAIRIE 3IA Institute) and reference ANR-10-IAIHU-06 (Agence Nationale de la Recherche-10-IA Institut Hospitalo-Universitaire-6). This work was granted access to the HPC resources of IDRIS under the allocation AD011013517 made by GENCI (Grand Equipement National de Calcul Intensif).

References

- [1] Alexander A Alemi, Ian Fischer, Joshua V Dillon, and Kevin Murphy. Deep variational information bottleneck. In *International Conference on Learning Representations*, 2017.
- [2] Jyoti Aneja, Alexander Schwing, Jan Kautz, and Arash Vahdat. NCP-VAE: Variational autoencoders with noise contrastive priors. *arXiv:2010.02917 [cs, stat]*, 2020.
- [3] Georgios Arvanitidis, Lars Kai Hansen, and Sören Hauberg. Latent space oddity: On the curvature of deep generative models. In 6th International Conference on Learning Representations, ICLR 2018, 2018.
- [4] Matthias Bauer and Andriy Mnih. Resampled priors for variational autoencoders. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 66–75. PMLR, 2019.
- [5] David Berthelot*, Colin Raffel*, Aurko Roy, and Ian Goodfellow. Understanding and improving interpolation in autoencoders via an adversarial regularizer. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=S1fQSiCcYm.
- [6] Lukas Biewald. Experiment tracking with weights and biases, 2020. URL https://www.wandb.com/. Software available from wandb.com.
- [7] Ekaba Bisong. Google Colaboratory, pages 59–64. Apress, Berkeley, CA, 2019. ISBN 978-1-4842-4470-8.
 doi: 10.1007/978-1-4842-4470-8_7. URL https://doi.org/10.1007/978-1-4842-4470-8_7.
- [8] Merlijn Blaauw and Jordi Bonada. Modeling and transforming speech using variational autoencoders. Morgan N, editor. Interspeech 2016; 2016 Sep 8-12; San Francisco, CA.[place unknown]: ISCA; 2016. p. 1770-4., 2016. Publisher: International Speech Communication Association (ISCA).
- [9] Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders. *arXiv:1509.00519 [cs, stat]*, 2016.
- [10] Christopher P. et al. Burgess. Understanding disentangling in β -vae. *arXiv preprint arXiv:1804.03599*, 2018.
- [11] Anthony L Caterini, Arnaud Doucet, and Dino Sejdinovic. Hamiltonian variational auto-encoder. In *Advances in Neural Information Processing Systems*, pages 8167–8177, 2018.
- [12] Clément Chadebec, Elina Thibeau-Sutre, Ninon Burgos, and Stéphanie Allassonnière. Data Augmentation in High Dimensional Low Sample Size Setting Using a Geometry-Based Variational Autoencoder. arXiv preprint arXiv:2105.00026, 2021.
- [13] Nutan Chen, Alexej Klushyn, Richard Kurle, Xueyan Jiang, Justin Bayer, and Patrick Smagt. Metrics for deep generative models. In *International Conference on Artificial Intelligence and Statistics*, pages 1540–1550. PMLR, 2018.
- [14] Ricky TQ Chen, Xuechen Li, Roger B Grosse, and David K Duvenaud. Isolating sources of disentanglement in variational autoencoders. *Advances in neural information processing systems*, 31, 2018.
- [15] Xi Chen, Diederik P Kingma, Tim Salimans, Yan Duan, Prafulla Dhariwal, John Schulman, Ilya Sutskever, and Pieter Abbeel. Variational lossy autoencoder. *arXiv preprint arXiv:1611.02731*, 2016.
- [16] Adam Coates, Andrew Ng, and Honglak Lee. An analysis of single-layer networks in unsupervised feature learning. In *Proceedings of the fourteenth international conference on artificial intelligence and statistics*, pages 215–223. JMLR Workshop and Conference Proceedings, 2011.
- [17] Marissa Connor, Gregory Canal, and Christopher Rozell. Variational autoencoder with learned latent structure. In *International Conference on Artificial Intelligence and Statistics*, pages 2359–2367. PMLR, 2021.

- [18] Chris Cremer, Xuechen Li, and David Duvenaud. Inference suboptimality in variational autoencoders. In International Conference on Machine Learning, pages 1078–1086. PMLR, 2018.
- [19] Bin Dai and David Wipf. Diagnosing and Enhancing VAE Models. In International Conference on Learning Representations, 2018.
- [20] Tim R Davidson, Luca Falorsi, Nicola De Cao, Thomas Kipf, and Jakub M Tomczak. Hyperspherical variational auto-encoders. In 34th Conference on Uncertainty in Artificial Intelligence 2018, UAI 2018, pages 856–865. Association For Uncertainty in Artificial Intelligence (AUAI), 2018.
- [21] Nat Dilokthanakul, Pedro A. M. Mediano, Marta Garnelo, Matthew C. H. Lee, Hugh Salimbeni, Kai Arulkumaran, and Murray Shanahan. Deep unsupervised clustering with gaussian mixture variational autoencoders. arXiv:1611.02648 [cs, stat], 2017.
- [22] Luca Falorsi, Pim de Haan, Tim R. Davidson, Nicola De Cao, Maurice Weiler, Patrick Forré, and Taco S. Cohen. Explorations in homeomorphic variational auto-encoding. arXiv:1807.04689 [cs, stat], 2018.
- [23] Mathieu Germain, Karol Gregor, Iain Murray, and Hugo Larochelle. Made: Masked autoencoder for distribution estimation. In *International Conference on Machine Learning*, pages 881–889. PMLR, 2015.
- [24] Partha Ghosh, Mehdi SM Sajjadi, Antonio Vergari, Michael Black, and Bernhard Schölkopf. From variational to deterministic autoencoders. In 8th International Conference on Learning Representations, ICLR 2020, 2020.
- [25] Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012.
- [26] Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In Advances in Neural Information Processing Systems, 2017.
- [27] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-VAE: Learning basic visual concepts with a constrained variational framework. *ICLR*, 2(5):6, 2017.
- [28] Matthew D Hoffman and Matthew J Johnson. Elbo surgery: yet another way to carve up the variational evidence lower bound. In *Workshop in Advances in Approximate Bayesian Inference, NIPS*, volume 1, page 2, 2016.
- [29] Michael I Jordan, Zoubin Ghahramani, Tommi S Jaakkola, and Lawrence K Saul. An introduction to variational methods for graphical models. *Machine Learning*, 37(2):183–233, 1999.
- [30] Dimitrios Kalatzis, David Eklund, Georgios Arvanitidis, and Soren Hauberg. Variational autoencoders with riemannian brownian motion priors. In *International Conference on Machine Learning*, pages 5053–5066. PMLR, 2020.
- [31] Hyunjik Kim and Andriy Mnih. Disentangling by factorising. In *International Conference on Machine Learning*, pages 2649–2658. PMLR, 2018.
- [32] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.
- [33] Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. arXiv:1312.6114 [cs, stat], 2014.
- [34] Durk P. Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. *Advances in neural information processing systems*, 29, 2016.
- [35] Alexej Klushyn, Nutan Chen, Richard Kurle, and Botond Cseke. Learning Hierarchical Priors in VAEs. Advances in neural information processing systems, page 10, 2019.
- [36] Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.
- [37] Anders Boesen Lindbo Larsen, Søren Kaae Sønderby, Hugo Larochelle, and Ole Winther. Autoencoding beyond pixels using a learned similarity metric. In *International conference on machine learning*, pages 1558–1566. PMLR, 2016.
- [38] Yann LeCun. The MNIST database of handwritten digits. 1998.

- [39] Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In Proceedings of International Conference on Computer Vision (ICCV), December 2015.
- [40] Alireza et al. Makhzani. Adversarial autoencoders. arXiv preprint arXiv:1511.05644, 2016.
- [41] Emile Mathieu, Charline Le Lan, Chris J Maddison, Ryota Tomioka, and Yee Whye Teh. Continuous hierarchical representations with poincaré variational auto-encoders. In Advances in neural information processing systems, pages 12565–12576, 2019.
- [42] Eric Nalisnick, Lars Hertel, and Padhraic Smyth. Approximate inference for deep latent gaussian mixtures. In NIPS Workshop on Bayesian Deep Learning, volume 2, page 131, 2016.
- [43] Radford M Neal. Hamiltonian importance sampling. In *talk presented at the Banff International Research Station (BIRS) workshop on Mathematical Issues in Molecular Dynamics*, 2005.
- [44] Bo Pang, Tian Han, Erik Nijkamp, Song-Chun Zhu, and Ying Nian Wu. Learning latent space energy-based prior model. *Advances in Neural Information Processing Systems*, 33, 2020.
- [45] George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. *Advances in neural information processing systems*, 30, 2017.
- [46] Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.
- [47] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.
- [48] Ali Razavi, Aaron van den Oord, and Oriol Vinyals. Generating diverse high-fidelity images with vq-vae-2. Advances in Neural Information Processing Systems, 2020.
- [49] Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International Conference on Machine Learning*, pages 1530–1538. PMLR, 2015.
- [50] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pages 1278–1286. PMLR, 2014.
- [51] Tim Salimans, Diederik Kingma, and Max Welling. Markov chain monte carlo and variational inference: Bridging the gap. In *International Conference on Machine Learning*, pages 1218–1226, 2015.
- [52] Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29, 2016.
- [53] Hang Shao, Abhishek Kumar, and P. Thomas Fletcher. The riemannian geometry of deep generative models. In 2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW), pages 428–4288. IEEE, 2018. ISBN 978-1-5386-6100-0. doi: 10.1109/CVPRW.2018.00071.
- [54] Jake Snell, Karl Ridgeway, Renjie Liao, Brett D Roads, Michael C Mozer, and Richard S Zemel. Learning to generate images with perceptual similarity metrics. In 2017 IEEE International Conference on Image Processing (ICIP), pages 4277–4281. IEEE, 2017.
- [55] Casper Kaae Sønderby, Tapani Raiko, Lars Maaløe, Søren Kaae Sønderby, and Ole Winther. Ladder variational autoencoder. In 29th Annual Conference on Neural Information Processing Systems (NIPS 2016), 2016.
- [56] I Tolstikhin, O Bousquet, S Gelly, and B Schölkopf. Wasserstein auto-encoders. In 6th International Conference on Learning Representations (ICLR 2018), 2018.
- [57] Jakub Tomczak and Max Welling. Vae with a vampprior. In International Conference on Artificial Intelligence and Statistics, pages 1214–1223. PMLR, 2018.
- [58] Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.
- [59] Zhou Wang, Eero P Simoncelli, and Alan C Bovik. Multiscale structural similarity for image quality assessment. In *The Thrity-Seventh Asilomar Conference on Signals, Systems & Computers, 2003*, volume 2, pages 1398–1402. Ieee, 2003.

- [60] Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 13(4):600–612, 2004.
- [61] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online, October 2020. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2020.emnlp-demos.6.
- [62] Linxiao Yang, Ngai-Man Cheung, Jiaying Li, and Jun Fang. Deep clustering by gaussian mixture variational autoencoders with graph embedding. In *Proceedings of the IEEE/CVF International Conference* on Computer Vision, pages 6440–6449, 2019.
- [63] Cheng Zhang, Judith Bütepage, Hedvig Kjellström, and Stephan Mandt. Advances in variational inference. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(8):2008–2026, 2018.
- [64] Shengjia Zhao, Jiaming Song, and Stefano Ermon. Infovae: Information maximizing variational autoencoders. *arXiv preprint arXiv:1706.02262*, 2016.

A Example of Pythae use

In this section we illustrate through simple examples how to use **Pythae** pipelines. The library is documented¹³ and also available on pypi¹⁴ allowing a wider use and easier integration in other codes. All of the implementations proposed in the library are adaptations of the official code when available and allowed by the licence. If not, the method is re-implemented. Table. 4 lists all the implemented models as of June 2022.

1. **Training configuration** Before launching a model training, one must specify the training configuration that should be used. This can be done easily by instantiating a **BaseTrainerConfig** instance taking as input all the hyper-parameters related to the training (number of training epochs, learning rate to apply...). See the full documentation for additional arguments that can be passed to the **BaseTrainerConfig**.

1	<pre>from pythae.trainers import BaseTrainerConfig</pre>
2	# Set up the model configuration
3	<pre>my_training_config = BaseTrainerConfig(</pre>
4	<pre>output_dir='my_model',</pre>
5	num_epochs=50,
6	<pre>learning_rate=1e-3,</pre>
7	<pre>batch_size=200)</pre>

2. **Model configuration** Similarly to the TrainerConfig, the model can then be instantiated with the model configuration specifying any hyper-parameters relevant to the model. Note that each model has its own configuration with specific hyper-parameters. See the online documentation for more details.

1	from <pre>pythae.models import BetaVAE, BetaVAEConfig</pre>
2	# Set up the model configuration
3	<pre>my_vae_config = BetaVAEConfig(</pre>
4	input_dim=(1, 28, 28),
5	<pre>latent_dim=16,</pre>
6	beta=2)
7	# Build the model
8	<pre>my_vae_model = BetaVAE(model_config=my_vae_config)</pre>

3. **Training** A model training can then be launched by simply using the built-in training pipeline in which only the training/evaluation data need to be specified.

1	from <pre>pythae.pipelines import TrainingPipeline</pre>
2	pipeline = TrainingPipeline(
3	<pre>training_config=my_training_config,</pre>
4	model=my_vae_model)
5	# Launch the Pipeline
6	pipeline(
7	<pre>train_data=your_train_data, # arrays or tensors</pre>
8	eval_data=your_eval_data)

¹³https://pythae.readthedocs.io/en/latest/?badge=latest

¹⁴https://pypi.org/project/pythae/

4. **Model reloading** The weights and configuration of the trained model can be reloaded using the **AutoModel** instance proposed in Pythae.

1	from pythae.models import AutoModel
2	<pre>my_trained_vae = AutoModel.load_from_folder('path/to/trained_model')</pre>

5. Data generation A data generation pipeline can be instantiated similarly to a model training. The pipeline can then be called with any relevant arguments such as the number of samples to generate or the training and evaluation data that may be needed to fit the sampler.

1	<pre>from pythae.samplers import GaussianMixtureSamplerConfig</pre>
2	from <pre>pythae.pipelines import GenerationPipeline</pre>
3	# Define your sampler configuration
4	<pre>gmm_sampler_config = GaussianMixtureSamplerConfig(</pre>
5	n_components=10)
6	# Build the pipeline
7	<pre>pipeline = GenerationPipeline(</pre>
8	<pre>model=my_trained_vae,</pre>
9	<pre>sampler_config=gmm_sampler_config)</pre>
10	# Launch generation
11	<pre>generated_samples = pipeline(</pre>
12	num_samples=100,
13	return_gen=True,
14	train_data=train_data,
15	eval_data=None)

Table 4: List	of implemented	VAEs
---------------	----------------	------

Name	Reference
Variational Autoencoder (VAE)	Kingma and Welling [33]
Beta Variational Autoencoder (BetaVAE)	Higgins et al. [27]
VAE with Linear Normalizing Flows (VAE_LinNF)	Rezende and Mohamed [49]
VAE with Inverse Autoregressive Flows (VAE_IAF)	Kingma et al. [34]
Disentangled β -VAE (DisentangledBetaVAE)	Higgins et al. [27]
Disentangling by Factorising (FactorVAE)	Kim and Mnih [31]
Beta-TC-VAE (BetaTCVAE)	Chen et al. [14]
Importance Weighted Autoencoder (IWAE)	Burda et al. [9]
VAE with perceptual metric similarity (MSSSIM_VAE)	Snell et al. [54]
Wasserstein Autoencoder (WAE)	Tolstikhin et al. [56]
Info Variational Autoencoder (INFOVAE_MMD)	Zhao et al. [64]
VAMP Autoencoder (VAMP)	Tomczak and Welling [57]
Hyperspherical VAE (SVAE)	Davidson et al. [20]
Adversarial Autoencoder (Adversarial_AE)	Makhzani [40]
Variational Autoencoder GAN (VAEGAN)	Larsen et al. [37]
Vector Quantized VAE (VQVAE)	Van Den Oord et al. [58]
Hamiltonian VAE (HVAE)	Caterini et al. [11]
Regularized AE with L2 decoder param (RAE_L2)	Ghosh et al. [24]
Regularized AE with gradient penalty (RAE_GP)	Ghosh et al. [24]
Riemannian Hamiltonian VAE (RHVAE)	Chadebec et al. [12]

B Interpolations

In this section, we show the interpolations obtained on the three considered datasets. For each model, we select both a starting image and an ending image from the test set and perform a linear interpolation between the corresponding embeddings in the learned latent space. We then show the decoded trajectory all along the interpolation line. For this task, we use the model configuration that obtained the lowest FID on the validation set with a GMM sampler from the generation task. We show the resulting interpolations for latent spaces of dimension 16 and 256 for MNIST, 32 and 256 for CIFAR10 and 64 for CELEBA. As mentioned in the paper, for this complex task, variational approaches tend to outperform the AE-based methods. This is well illustrated on MNIST with a latent space of dimension 256 since all the AE-based approaches eventually superpose the starting and ending image, making the interpolation visually irrelevant. Impressively, the regularisation imposed by the variational approaches prevents such undesirable behaviours from occurring. This adds to the observation made in Sec. 4.2.2 of the paper where we note some robustness to the latent dimension for the variational methods. Nonetheless, as stated in the paper this regularisation can also degrade image reconstruction, leading to very blurry interpolations, as illustrated on Fig. 5.

MNIST (16)

MNIST (256)

VAE	759	759	759	759	2 5 9	234	230	230	236	236	759	759	759	759	000	えうか	よろの	236	236	236
VAMP	759	759	759	159	eo (1) eo	S	とうい	とろし	とろし	ころし	759	759	759	759	0 n 01	こうゆ	とろし	236	ころし	236
IWAE	759	759	759	759	ah in 9	al n J	e n s	236	236	236	759	759	759	759	nt 10 9	234	236	236	236	236
VAE-lin-NF	759	759	759	うじゅ	~ M ~	ころら	236	236	236	236	759	759	759	759	3009	303	2334	236	236	236
VAE-IAF	7 3 9	739	739	739	239	234	236	236	236	236	7 5 9	759	759	259	259	239	230	236	236	236
β -VAE	75 9	759	759	てらい	734	ころの	236	236	236	236	759	759	759	759	059	338	236	236	236	236
β -TC-VAE	75 9	75 9	759	13509	1 do de 1	1 m 3	えきの	236	236	236	759	759	759	759	239	236	とろの	236	236	236
Factor-VAE	75 9	75 9	759	759	うろの	300	230	236	236	236	759	759	759	259	239	230	230	236	236	236
InfoVAE - IMQ	759	759	759	759	NB 9	ころら	235	236	236	236	75 9	759	759	m 15 9	250	239	236	236	236	236
InfoVAE - RBF	759	759	759	m 50 9	ころの	230	230	236	236	236	75 9	759	759	n 10 9	2000	230	236	236	236	236

Figure 3: Interpolations on MNIST with the same starting and ending images for latent spaces of dimension 16 and 256. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.

MNIST (256)

AAE	7777222222 5553333333 99944466666	7777722222 55555333333 999994446666
MSSSIM-VAE	7 7 7 7 2 2 2 2 2 2 5 5 5 5 5 3 3 3 3 3 <i>9 9 9 9 0 0 6 6 6 6</i>	7779982222 5555533333 99994446666
VAEGAN	7777332222 5555533333 99999466666	7773322222 5555333333 99999966666
AE	77777222222 5555333333 99944466666	777722222 5555533333 99999866666
WAE-IMQ	7777222 222 5555533333 999444666666	777722222 55555533333 999999666666
WAE-RBF	77777222222 5555533333 999444666666	7777722222 5555533333 99999966666
VQVAE	7777722222 5553333333 999944466666	7777722222 5555533333 99999966666
RAE-12	7777222222 5555533333 999944666666	777722222 5555533333 99999966666
RAE-GP	7773222222 55555333333 99996666666	777722222 5555533333 99999866666

Figure 4: Interpolations on MNIST with the same starting and ending images for latent spaces of dimension 16 and 256. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.



Figure 5: Interpolations on CIFAR10 with the same starting and ending images for latent spaces of dimension 32 and 256. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.

Figure 6: Interpolations on CIFAR10 with the same starting and ending images for latent spaces of dimension 32 and 256. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.



Figure 7: Interpolations on CELEBA with the same starting and ending images for a latent space of dimension 64. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.

	CELEBA (64)	CELEBA (64)
AAE		
MSSSIM-VAE		
VAEGAN		
AE		
WAE-IMQ	55555666666666666666666666666666666666	
WAE-RBF		
VQVAE		
RAE-12		
RAE-GP		

Figure 8: Interpolations on CELEBA with the same starting and ending images for a latent space of dimension 64. For each model we select the configuration achieving the lowest FID on the generation task on the validation set with a GMM sampler.

C Detailed experiments set-up

We detail here the main experimental set-up and implementation choices made in the benchmark. We let the reader refer to the code available online for specific implementation aspects

The data To perform the benchmaks presented in the paper, we select 3 classical *free-to-use* image datasets: MNIST [38], CIFAR10 [36] and CELEBA [39]. These datasets are publicly available, widely used for generative model related papers and have well known associated metrics in the literature. Each dataset is split into a train set, a validation set and a test set. For MNIST and CIFAR10 the validation set is composed of the last 10k images extracted from the official train set and the test set corresponds to the official one. For CELEBA, we use the official train/val/test split.

Training paradigm We equip each model used in the benchmark with the same neural network architecture for both the encoder and decoder, taken as a ConvNet and ResNet (architectures given in Tables. 5 and 6) leading to a comparable number of parameters ¹⁵. For the 19 considered models, due to computational limitations, 10 different configurations are considered, allowing a simple exploration of the models' hyper-parameters. The sets of hyper-parameters explored are detailed in Appendix. D.4 for each model. The models are then trained on MNIST and CIFAR10 for 100 epochs, a starting learning rate of $1e^{-4}$ and batch size of 100 with Adam optimizer [32]. A scheduler reducing the learning rate by half if the validation loss does not improve for 10 epochs is also used. For CELEBA, we use the same setting but we train the models for 50 epochs with a starting learning rate of $1e^{-3}$. Models with unstable training (NaN, huge training spikes...) are iteratively retrained with a starting learning rate divided by 10 until training stabilises. All 19 models are trained on a single 32GB V100 GPU. This leads to 10 trained models for each method, each dataset (MNIST, CIFAR10 or CELEBA) and each neural network (ConvNet or ResNet) leading to a total of 1140 models. The training setting (curves, configs ...) can be found at https://wandb.ai/benchmark_team/trainings.

Sampling paradigm for the MAF and VAE samplers For the Masked Autoregressive Flow sampler used for sampling we use a 3-layer MADE [23] with 128 hidden units and ReLU activation for each layer and stack 2 blocks of MAF to create the flow. For the masked layers, the mask is made sequentially and the ordering is reversed between each MADE. For this normalising flow we consider a starting distribution given by a standard Gaussian. For the auxiliary VAE sampling method proposed in [19], we consider a simple VAE with a Multi Layer Perceptron (MLP) encoder and decoder, with 2 hidden layers composed of 1024 units and ReLU activation. Both samplers are fitted with 200 epochs using the train and evaluation embeddings coming from the trained autoencoder models. A learning rate of $1e^{-4}$, a scheduler decreasing the learning rate by half if the validation loss does not improve for 10 epochs and a batch size of 100 are used for these samplers.

Table 5: Neural net	twork architecture use	d for the convolutional	networks.
---------------------	------------------------	-------------------------	-----------

	MNIST	CIFAR10	CELEBA			
Encoder	(1, 28, 28)	(3, 32, 32)	(3, 64, 64)			
Layer 1	Conv(128, 4, 2), BN, ReLU	Conv(128, 4, 2), BN, ReLU	Conv(128, 4, 2), BN, ReLU			
Layer 2	Conv(256, 4, 2), BN, ReLU	Conv(256, 4, 2), BN, ReLU	Conv(256, 4, 2), BN, ReLU			
Layer 3	Conv(512, 4, 2), BN, ReLU	Conv(512, 4, 2), BN, ReLU	Conv(512, 4, 2), BN, ReLU			
Layer 4	Conv(1024, 4, 2), BN, ReLU	Conv(1024, 4, 2), BN, ReLU	Conv(1024, 4, 2), BN, ReLU			
Layer 5	Linear(1024, latent_dim)*	Linear(4096, latent_dim)*	Linear(16384, latent_dim)*			
Decoder						
Layer 1	Linear(latent_dim, 16384)	Linear(latent_dim, 65536)	Linear(latent_dim, 65536)			
Layer 2	ConvT(512, 3, 2), BN, ReLU	ConvT(512, 4, 2), BN, ReLU	ConvT(512, 5, 2), BN, ReLU			
Layer 3	ConvT(256, 3, 2), BN, ReLU	ConvT(256, 4, 2), BN, ReLU	ConvT(256, 5, 2), BN, ReLU			
Layer 4	Conv(1, 3, 2), Sigmoid	Conv(3, 4, 1), Sigmoid	ConvT(128, 5, 2), BN, ReLU			
Layer 5		-	ConvT(3, 5, 1), Sigmoid			

*Doubled for VAE-based models

¹⁵Some models may actually have additional parameters in their intrinsic structure *e.g.* a VQVAE learns a dictionary of embeddings, a VAMP learns the pseudo-inputs, a VAE-IAF learns the auto-regressive flows. Nonetheless, since we work on images, the number of parameters remains in the same order of magnitude.

Table 6: Neural network architecture used for the residual networks.

	MNIST	CIFAR10	CELEBA
Encoder	(1, 28, 28)	(3, 32, 32)	(3, 64, 64)
Layer 1	Conv(64, 4, 2)	Conv(64, 4, 2)	Conv(64, 4, 2)
Layer 2	Conv(128, 4, 2)	Conv(128, 4, 2)	Conv(128, 4, 2)
Layer 3	Conv(128, 3, 2)	Conv(128, 3, 1)	Conv(128, 3, 2)
Layer 4	ResBlock**	ResBlock**	Conv(128, 3, 2)
Layer 5	ResBlock**	ResBlock**	ResBlock**
Layer 6	Linear(2048, latent_dim)*	Linear(8192, latent_dim)*	ResBlock**
Layer 7	-	-	Linear(2048, latent_dim)*
Decoder			
Layer 1	Linear(latent_dim, 2048)	Linear(latent_dim, 8192)	Linear(latent_dim, 2048)
Layer 2	ConvT(128, 3, 2)	ResBlock**	ConvT(128, 3, 2)
Layer 3	ResBlock**	ResBlock**	ResBlock**
Layer 4	ResBlock**, ReLU	ConvT(64, 4, 2)	ResBlock**
Layer 5	ConvT(64, 3, 2), ReLU	ConvT(3, 4, 2), Sigmoid	ConvT(128, 5, 2), Sigmoid
Layer 6	ConvT(1, 3, 2), Sigmoid	-	ConvT(64, 5, 2), Sigmoid
Layer 6	-	-	ConvT(3, 4, 2), Sigmoid

*Doubled for VAE-based models **The ResBlocks are composed of one Conv(32, 3, 1) followed by Conv(128, 1, 1) with ReLU.

D Additional results

D.1 Effect of the latent dimension on the 4 tasks with the CIFAR10 database

Analogously to the results shown in the paper on the MNIST dataset for the 4 chosen tasks (reconstruction, generation, classification and clustering), Fig. 9 shows the impact the choice of the latent space dimension has on the performances of the models on the CIFAR10 dataset, whose image arguably have a greater intrinsic latent dimension than images of the MNIST dataset. Similarly to MNIST, two distinct groups appear: the AE-based methods and variational methods. Again, for all tasks but clustering, variational based methods demonstrate good robustness properties with respect to the dimension of the latent space when compared to AE approaches.



Figure 9: *From top to bottom:* Evolution of the reconstruction MSE, generation FID, classification accuracy and clustering accuracy with respect to the latent space dimension on the CIFAR dataset.

D.2 Complete generation table

In Table. 7 are presented the full results obtained for generation *i.e.* including the MAF and 2-stage VAE sampler [19]. As mentioned in the paper, it is interesting to note that fitting a GMM instead of using the prior for the variational-based approaches seems to often allow a better image generation since it allows a better prospecting of the learned latent space of each model. Interestingly, it seems that fitting more complex density estimators such as a normalising flow (MAF sampler) or another VAE (2-stage sampler) does not improve the generation results when compared to the GMM for those datasets.

Model	Sampler	MNI FID↓	IST IS ↑	Conv CIFA FID	Net R10 IS	CELI FID	EBA IS ↑	MN FID↓	IST IS↑	ResN CIFA FID	et R10 IS	CELE FID	EBA IS
VAE	N GMM VAE	28.5 26.9 40.3	2.1 2.1 2.0	241.0 235.9 337.5	2.2 2.3 1.7	54.8 52.4 70.9	1.9 1.9 1.6	31.3 32.3 48.7	2.0 2.1 1.8	181.7 179.7 358.0	2.5 2.5 1.3	66.6 63.0 76.4	1.6 1.7 1.4
	MAF	26.8	2.1	239.5	2.2	52.5	2.0	31.0	2.1	181.5	2.5	62.9	1.7
VAMP	VAMP	64.2	2.0	329.0	1.5	56.0	1.9	34.5	2.1	181.9	2.5	67.2	1.6
	N GMM	29.0	2.1	245.3	2.1	55.7 52.7	1.9	32.4	2.0	191.2	2.4	67.6 64.1	1.6
IWAE	VAE	42.4	2.0	346.6	1.5	74.3	1.5	50.1	1.9	364.8	1.2	76.4	1.7
	MAF N	28.1 29.3	2.1 2.1	243.4 240.3	2.1 2.1	52.7 56.5	1.9 1.9	32.5 32.5	2.1 2.0	190.4 185.5	2.4 2.4	64.3 67.1	1.7 1.6
VAE-lin NF	GMM	28.4	2.1	237.0	2.2	53.3	1.9	33.1	2.1	183.1	2.5	62.8	1.7
	MAF	27.7	2.0	239.1	2.1	53.4	2.0	32.4	2.0	184.2	2.5	62.7	1.4
	N GMM	27.5	2.1	236.0	2.2	55.4 53.6	1.9	30.6	2.0	183.6	2.5	66.2 62.7	1.6
VAE-IAF	VAE	39.4	2.0	330.5	1.1	73.0	1.5	44.8	1.9	322.7	1.5	76.7	1.4
	MAF	26.9	2.1	236.8	2.2	53.6	1.9	30.6	2.1	182.5	2.5	63.0	1.7
	N GMM	21.4	2.1	115.4 92.2	3.6 3.9	56.1 51.7	1.9 1.9	19.1 11.4	2.0	124.9 112.6	3.4 3.6	65.9 59.3	1.6 1.7
β -VAE	VAE	14.0	2.2	139.6	3.6	55.0	1.9	20.3	2.1	152.5	3.5	61.5	1.7
	MAF N	9.5	2.2	100.9	2.8	51.5	2.0	20.7	2.1	120.0	3.6	59.7 65.9	1.8
β -TC VAE	GMM	11.6	2.2	89.3	4.1	51.8	1.9	13.3	2.1	106.5	3.7	59.3	1.7
	MAF	18.4	2.2	127.9 95.6	4.2 3.6	59.7 52.2	1.8	28.3	2.0	164.0 116.6	3.3 3.4	66.4 60.1	1.5
	N	27.0	2.1	236.5	2.2	53.8	1.9	31.0	2.0	185.4	2.5	66.4	1.7
FactorVAE	GMM VAE	26.9	2.1	234.0 338.3	2.2	52.4 75.0	2.0	32.7 54.7	2.1	184.4 316.2	2.5	63.3 77.7	1.7
	MAF	26.7	2.2	236.7	2.2	52.7	1.9	32.8	2.1	185.8	2.5	63.4	1.7
	N GMM	27.5	2.1	235.2 230.4	2.1	55.5 52.7	1.9	31.1	2.0	182.8 179.5	2.5	66.5 62.8	1.6
InfoVAE - RBF	VAE	39.7	2.0	327.2	1.5	73.7	1.5	50.6	1.9	363.4	1.2	75.8	1.4
	MAF	25.9	2.1	233.5	2.2	52.2	2.0	30.5	2.1	181.3	2.5	62.7	1.7
	N GMM	28.3	2.1	233.8	2.2	56.7 53.7	1.9	31.0	2.0	182.4 180.7	2.5	66.4 62.3	1.6
InfoVAE - IMQ	VAE	40.4	1.9	323.8	1.6	73.7	1.5	49.9	1.9	341.8	1.8	75.7	1.4
	MAF	27.2	2.1	232.3	2.1	53.8	2.0	30.6	2.1	182.5	2.5	62.6	1.7
AAE	GMM	9.3	2.2	92.1	3.8	53.9	2.0	11.1	2.1	118.5	3.5	58.7	1.8
AAL	VAE	13.4	2.2	144.0	3.4	58.2	1.8	15.1	2.1	145.2	3.6	59.0 59.2	1.7
		1 267	2.2	270.0	1.7	124.2	1.2	1.28.0	2.1	254.2	1.7	110.0	1.0
MEESIM VAE	GMM	20.7	2.2	279.9	1.7	124.3	1.3	28.0	2.1	254.2 253.1	1.7	119.0	1.3
M333IM-VAL	VAE	51.2	1.9	355.5	1.1	137.9	1.2	51.6	1.9	372.1	1.1	136.5	1.2
	N NAF	8.7	2.2	199.5	2.2	39.7	1.5	12.8	2.1	198.7	2.2	122.8	2.0
VAEGAN	GMM	6.3	2.2	197.5	2.1	35.6	1.8	6.5	2.2	188.2	2.6	84.3	1.7
	MAF	6.9	2.1	199.0	2.0	36.7	1.8	9.2 6.6	2.1	191.9	2.0	84.8	1.0
	I N	26.7	2.1	201.3	2.1	327.7	1.0	221.8	1.3	210.1	2.1	275.0	2.9
AE	GMM	9.3	2.2	97.3	3.6	55.4	2.0	11.0	2.1	120.7	3.4	57.4	1.8
	MAF N	21.2	2.2	108.3	2.0	332.6	2.0	21.2	2.1	136.5	2.3	58.3 69.4	1.8
WAE - RBF	GMM	9.2	2.2	97.1	3.6	55.0	2.0	11.2	2.1	120.3	3.4	58.3	1.7
	MAF	9.8	2.2	108.2 164.4	3.1	56.0 64.6	2.0	20.3	2.2	135.3	3.0	58.3 67.1	1.8
WAE - IMQ	GMM	8.6	2.2	96.5	3.6	51.7	2.0	11.2	2.1	119.0	3.5	57.7	1.8
	MAF	9.5	2.2	107.8	3.1	51.6 306.9	2.0	11.8	2.1	130.2	3.0	58.7 140 3	1.7
VQVAE	GMM	9.1	2.2	95.2	3.7	51.6	2.0	10.7	2.1	120.1	3.4	57.9	1.8
	MAF N	9.6	2.2	104.7 156.1	3.2	52.3 86.1	1.9 2.8	11.7 63.3	2.2	136.8 170.9	3.0 2.2	57.9 168.7	1.8
RAE-L2	GMM	9.1	2.2	85.3	3.9	55.2	1.9	11.5	2.1	122.5	3.4	58.3	1.8
	MAF	9.5	2.2	93.4 196.8	3.5	55.2 86.1	2.0	12.3	2.2	136.6 229.1	3.0	59.1 201.9	1.7
RAE - GP	GMM	9.7	2.2	96.3	3.7	52.5	1.9	11.4	2.1	123.3	3.4	59.0	1.8
	MAF	9.7	2.2	106.3	3.2	52.5	1.9	12.2	2.2	139.4	3.0	59.5	1.8

Table 7: Inception Score (higher is better) and FID (lower is better) computed with 10k samples on the test set. For each model and sampler we report the results obtained by the model achieving the lowest FID score on the validation set.

D.3 Further interesting results

Generated samples In addition to quantitative metrics, we also provide in Fig. 10 and Fig. 11 some samples coming from the different models using either a $\mathcal{N}(0, I_d)$ or fitting a GMM with 10 components on MNIST and CELEBA. This allows to visually differentiate the quality of the different sampling methods.

	MNIST - \mathcal{N}	MNIST - GMM						
VAE	7806478166	0032235291						
IWAE	0822372441	7926155616						
VAE-lin-NF	6733659797	9394842753						
VAE-IAF	3384715310	5986735831						
β -VAE	0250579178	2305543693						
β -TC-VAE	4647714821	2069096077						
Factor-VAE	2305543698	2394995765						
InfoVAE - IMQ	2189293913	8407613564						
InfoVAE - RBF	1398693793	6191439602						
AAE	3082914878	7319324861						
MSSSIM-VAE	4640214227	8532909211						
VAEGAN	4987393664	2932149136						
AE	23823933329	4874153367						
WAE-IMQ	2433129160	3201100718						
WAE-RBF	7691318069	002 0 58 849 8						
VQVAE	8009122033	3330424631						
RAE-L2	8398540493	9987100996						
RAE-GP	まうえのロピのやみょう	9107116281						

Figure 10: Generated samples on MNIST for a latent space of dimension 16 and ConvNet architecture. For each model, we select the configuration achieving the lowest FID on the validation set.



Figure 11: Generated samples on CELEBA for a latent space of dimension 64 and ConvNet architecture. For each model, we select the configuration achieving the lowest FID on the validation set.

Sampler ablation study Fig. 12 shows the same results as Table. 7 but under a different prism. In this plot, we show the influence each sampler has on the generation quality for all the models considered in this study. Note that sampling using a $\mathcal{N}(0, I_d)$ for an AE, RAE or VQVAE is far from being optimal since those models do not enforce explicitly the latent variables to follow this distribution. As mentioned in the paper, this experiment shows that using more complex density estimators such as a GMM or a normalising flow almost always improves the generation metric.



Figure 12: Evolution of the FID for the generation task depending on the sampler, for a ConvNet, the MNIST dataset and a latent dimension of 16. For each sampler and model, we select the configuration achieving the lowest FID on the validation set.

Neural network architecture ablation study As explained in the paper and in Appendix. C, we consider two different neural architectures for the encoder and decoder of each model: a ConvNet (convolutional neural network) and a ResNet (residual neural network). Fig. 13 shows the influence the choice of the neural architecture has on the ability of the model to perform the 4 tasks presented in the paper. The results are computed for each model on MNIST and a latent dimension of 16. The ConvNet architecture has approximately 20 times more parameters than the ResNet in such conditions. We select the best configuration for each model and each task on the validation set and report the results on the test set. Unsuprisingly, we see in Fig. 13 that the ConvNet architecture, more adapted to capture features intrinsic to images, leads to the best performances for reconstruction and generation. Interestingly, the ResNet outperforms the ConvNet for the classification and clustering tasks, meaning that in addition to the network complexity, its structure can play a major role in the representation learned by the models.

Training time Fig. 14 shows the training times required for each model for both network architectures on the MNIST dataset. For each model, we show the results obtained with the configuration giving the best performances on the generation task with fixed latent dimension 16. It is interesting to note that although VAEGAN outperforms other models on the generation task, it is at the price of a higher computational time. This is due to the discriminator network (a convolutional neural net) that is called several times during training and takes images as inputs. It should be noted that methods applying normalising flows to the posterior (VAE-lin-NF and VAE-IAF) maintain a reasonable training time, as the flows were chosen for their scalability.



Figure 13: Evolution of the metrics for the 4 tasks depending on the network type on the MNIST dataset and a latent dimension of 16.



Figure 14: Total training time for the models trained on the MNIST dataset with latent dimension 16 with the best performance on the generation task.

D.4 Configurations and results by models

In this section we briefly explain each model considered in the benchmark, and show the evolution of performances on the 4 tasks and the training speed with respect to the choice of the hyper-parameters. For all 4 tasks we consider the MNIST dataset and a fixed latent space of dimension 16, as well as the Normal Gaussian sampler (if applicable) and the convolutional network architecture. For each model, 10 configuration runs with different hyper-parameters were tested. It should be noted that this configuration search was done empirically and is not exhaustive, therefore models with multiple hyper-parameters or that are sensitive to the choice of hyper-parameters will tend to have sub-optimal configuration choices. Although hyper-parameter choices are dependent on both the auto-encoder architecture and the dataset, it is interesting to note the relative evolution of the performances on the different tasks and the training time induced by different hyper-parameter choices.

Notations In order to better underline the differences between different models and for clarity purposes, we set the following unified notations:

- $X = \{x_1, \ldots, x_N\} \in \mathcal{X}^N$ the input dataset
- $x \in \mathcal{X}$ an observation from the dataset, and $z \in \mathcal{Z} = \mathbb{R}^d$ its corresponding latent vector
- \hat{x} the reconstruction of x by the auto-encoder model
- $p_z(z)$ the prior distribution, with $p_z \equiv \mathcal{N}(0, I_d)$ under standard VAE assumption
- $q_{\phi}(z|x)$ the approximate posterior distribution, modelled by the encoder. Kingma and Welling [33] set

$$q_{\phi}(z|x) \equiv \mathcal{N}\big(\mu_{\phi}(x), \Sigma_{\phi}(x))\big)$$

where $\Sigma_{\phi}(x) = diag[\sigma_{\phi}(x)]$ and $(\mu_{\phi}(x), \sigma_{\phi}(x)) \in \mathbb{R}^{2 \times d}$ are outputs of the encoder network. The sampling process $z \sim q_{\phi}(z|x)$ is therefore performed by sampling $\varepsilon \sim \mathcal{N}(0, I_d)$ and setting $z = \mu_{\phi}(x) + \Sigma_{\phi}(x)^{1/2} \cdot \varepsilon$ (re-parametrization trick).

- $p_{\theta}(x|z)$ the distribution of x given z
- $p_{\theta}(x) = \int_{\mathcal{Z}} p_{\theta}(x|z) p_z(z) dz$ the marginal distribution of x
- $q_{\phi}(z) = \frac{1}{N} \sum_{i=1}^{N} q_{\phi}(z|x_i)$ the aggregated posterior integrated over the training set.
- \mathcal{D}_{KL} the Kullback-Leibler divergence

We further recall that Kingma and Welling [33] use the unbiased estimate $\hat{p}_{\theta}(x)$ of $p_{\theta}(x)$ defined as

$$\widehat{p}_{\theta}(x) = \frac{p_{\theta}(x|z)p_z(z)}{q_{\phi}(z|x)}$$

to derive the standard Evidence Lower Bound (ELBO) of the log probability $\log p_{\theta}(x)$ which we wish to maximize:

$$\mathcal{L}_{ELBO} = \mathbb{E}_{x \sim p_{\theta}(x)} \left[\mathcal{L}_{ELBO}(x) \right]$$

with

$$\mathcal{L}_{ELBO}(x) = \underbrace{\mathbb{E}_{z \sim q_{\phi}}[\log p_{\theta}(x|z)]}_{\text{reconstruction}} - \underbrace{\mathcal{D}_{KL}[q_{\phi}(z|x)||p_{z}(z)]}_{\text{regularisation}}$$

The reconstruction loss is maximized when \hat{x} is close to x, thus encouraging a good reconstruction of the input x, while the regularisation term is maximized when $q_{\phi}(z|x)$ is close to $p_z(z)$, encouraging the posterior distribution to follow the chosen prior distribution.

The integration over $p_{\theta}(x)$ is approximated by the empirical distribution of the training dataset, and the negative ELBO function acts as a loss function to minimize for the encoder and decoder networks.

VAE with a VampPrior (VAMP) Starting from the observation that a standard Gaussian prior may be too simplistic, Tomczak and Welling [57] proposes a less restrictive prior: the Variational Mixture of Posteriors (VAMP). A VAE with a VAMP prior aims at relaxing the posterior constraint by replacing the conventional normal prior with a multimodal aggregated posterior given by:

$$p_z(z) = \frac{1}{K} \sum_{k=1}^{K} q_\phi(z|u_k),$$

where u_k are pseudo-inputs living in the data space \mathcal{X} learned through back-propagation and acting as anchor points for the prior distribution. For the VAMP VAE implementation, we use the same architecture as the authors' implementation for the network generating the pseudo-inputs: a MLP with a single layer and Tanh activation.





Figure 15: Results on VAMP

Importance Weighted Autoencoder (IWAE) Burda et al. [9] introduce an alternative lower bound to maximize, derived from importance weighting where the new unbiased estimate $\hat{p}_{\theta}(x)$ of the marginal distribution $p_{\theta}(x)$ is computed with L samples $z_1, \ldots, z_L \sim q_{\phi}(z|x)$:

$$\widehat{p}_{\theta}(x) = \frac{1}{L} \sum_{i=1}^{L} \frac{p_{\theta}(x|z_i)p_z(z_i)}{q_{\phi}(z_i|x)} \,.$$

This estimate induces a new lower bound of the true marginal distribution $p_{\theta}(x)$ using Jensen's inequality:

$$\mathcal{L}_{\text{IWAE}}(x) := \mathbb{E}_{z_1, \dots, z_L \sim q(z|x)} \left[\log \frac{1}{L} \sum_{i=1}^L \frac{p_\theta(x|z_i) p_z(z_i)}{q_\phi(z_i|x)} \right] \le \log \underbrace{\mathbb{E}_{z_1, \dots, z_L \sim q(z|x)} \left[\widehat{p}_\theta(x) \right]}_{p_\theta(x)}$$

As the number of samples L increases, $\mathcal{L}_{\text{IWAE}}(x)$ becomes closer to $\log p_{\theta}(x)$, therefore providing a tighter bound on the true objective. Note that when L = 1 we recover the original VAE framework.

As expected the reconstruction quality increases with the number of samples. Nonetheless, we note that increasing the number of samples has a significant impact on the computation of a single training step, therefore leading to a much slower training process.

Table 9: IWAE configurations										
Config	1	2	3	4	5	6	7	8	9	10
Number of samples (L)	2	3	4	5	6	7	8	9	10	12



Figure 16: Results on IWAE

Variational Inference with Normalizing Flows (VAE-lin-NF) In order to model a more complex family of approximate posterior distributions, Rezende and Mohamed [49] propose to use a succession of normalising flows to transform the simple distribution $q_{\phi}(z|x)$, allowing it to model more complex behaviours. In practice, after having sampled $z_0 \sim q_{\phi}(z|x)$, z_0 is passed through a chain of K invertible smooth mappings from the latent space \mathbb{R}^d to itself:

$$z_K = f_K \circ \cdots \circ f_2 \circ f_1(z_0) \,.$$

The modified latent vector z_K is then used as input z for the decoder network. In their paper, the authors propose to use two types of transformations: planar and radial flows.

$$f_{\text{planar}}(z) = z + uh(w^{\top}z + b)$$
; $f_{\text{radial}}(z) = z + \beta g(\alpha, r)(z - z_0)$

where h is a smooth non-linearity with tractable derivatives and $g(\alpha, r) = \frac{1}{\alpha+r}$. The parameters are such that $r = ||z - z_0||, u, w, z_0 \in \mathbb{R}^d, \alpha \in \mathbb{R}^+$ and $b, \beta \in \mathbb{R}$. We can easily compute the resulting density q given by

$$\log q(z_K) = \log q_{\phi}(z_0|x) - \sum_{k=1}^K \log \left| \det \frac{\partial f_k}{\partial z} \right|.$$

This makes the ELBO tractable and optimisation possible.

Results by configuration

Table 10: VAE-lin-NF configurations

Config	1	2	3	4	5	6	7	8	9	10
Flow sequence	PPPPP	RRRRR	PRPRP	10P	15P	20P	30P	PRPRPRPRPR	PPP	PRPPRPPPR
'P' stands for planer flow 'P' stands for radial flow										

'P' stands for planar flow - 'R' stands for radial flow



Figure 17: Results on VAE-lin-NF

Variational Inference with Inverse Autoregressive Flow (VAE-IAF) Kingma et al. [34] improve upon the works of [49] with a new type of normalising flow that better scales to high-dimensional latent spaces. The main idea is again to apply several transformations to a sample from a simple distribution in order to model richer distributions. Starting from $z_0 \sim q_{\phi}(z|x)$, the proposed IAF flow consists in applying consecutively the following transformation

$$z_k = \mu_k + \sigma_k \cdot z_{k-1} \,,$$

where μ_k and σ_k are the outputs of an autoregressive neural network taking z_{k-1} as input. Inspired from the original paper, to implement one Inverse Autoregressive Flow we use MADE [23] and stack multiple IAF together to create a richer flow. The MADE mask is made sequentially for the masked autoencoders and the ordering is reversed after each MADE.

Table 11: VAE-IAF configurations										
Config	1	2	3	4	5	6	7	8	9	10
hidden size in MADE	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0	64.0	128.0
number hidden units in MADE	2.0	2.0	2.0	2.0	2.0	2.0	4.0	6.0	2.0	2.0
number of IAF blocks	1.0	2.0	5.0	10.0	20.0	4.0	4.0	4.0	4.0	4.0



Figure 18: Results on VAE-IAF

 β -VAE Higgins et al. [27] argue that increasing the weight of the KL divergence term in the ELBO loss enforces a stronger disentanglement of the latent features as the posterior probability is forced to match a multivariate standard Gaussian. They propose to add a hyper-parameter β in the ELBO leading to the following objective to maximise:

$$\mathcal{L}_{\beta\text{-VAE}}(x) = \mathbb{E}_{z \sim q_{\phi}}[\log p_{\theta}(x|z)] - \beta \mathcal{D}_{KL}[q_{\phi}(z|x)||p_{z}(z)].$$

Although the original publication specifies $\beta > 1$ to encourage a better disentanglement, a smaller value of β can be used to relax the regularisation constraint of the VAE. Therefore, for this model we consider a range of values for β from $1e^{-3}$ to $1e^3$.

As expected, we see in Fig. 19 a trade-off appearing between reconstruction and generation. Indeed, a very small β will tend to less regularise the model since the latent variables will no longer be driven to follow the prior, favouring a better reconstruction. On the other hand, a higher value for β will constrain the model, leading to a better generation quality. Moreover, as can be seen in Fig. 19, too high a value of β will lead to over-regularisation, resulting in poor performances on all evaluated tasks.

Table 12: β -VAE configurations

			· /·	-	-	0		-		
Config	1	2	3	4	5	6	7	8	9	10
β	$1e^{-3}$	$1e^{-2}$	$1e^{-1}$	0.5	2	5	10	20	$1e^2$	$1e^3$



Figure 19: Results on β -VAE

 β -TC-VAE Chen et al. [14] extend on the ideas of Higgins et al. [27] by rewriting and re-weighting specific terms in the ELBO loss with multiple hyperparameters. The authors note that the KL-divergence term of the ELBO loss can be rewritten as

$$\mathbb{E}_{x \sim p_{\theta}} \left[\mathcal{D}_{KL} \left[q_{\phi}(z|x) || p_{z}(z) \right] \right] = \underbrace{I(x, z)}_{\text{Mutual information}} + \underbrace{\mathcal{D}_{KL} \left[q_{\phi}(z) || \prod_{j=1}^{d} q_{\phi}(z_{j}) \right]}_{\text{TC-loss}} + \underbrace{\sum_{j=1}^{d} \mathcal{D}_{KL} \left[q_{\phi}(z_{j}) || p_{z}(z_{j}) \right]}_{\text{Dimension-wise KL}} \right]$$

- The mutual information term corresponds to the amount of information shared by x and its latent representation z. It is claimed that maximising the mutual information encourages better disentanglement and a more compact representation of the data.
- The TC-loss corresponds to the total correlation between the latent distribution and its fully disentangled version, maximising it enforces the dimensions of the latent vector to be uncorrelated.
- Maximising the dimension-wise KL prevents the marginal distribution of each latent dimension from diverging too far from the prior Gaussian distribution

The authors therefore propose to replace the classical regularisation term with the more general term

$$\mathcal{L}_{\text{reg}} := \alpha I(x, n) + \beta \mathcal{D}_{KL} \left[q_{\phi}(z) || \prod_{j} q_{\phi}(z_{j}) \right] + \gamma \sum_{j} \mathcal{D}_{KL} \left[q_{\phi}(z_{j}) || p_{z}(z_{j}) \right]$$

Similarly to the authors, we set $\alpha = \gamma = 1$ and only perform a search on the parameter β . Fig. 20 shows a reconstruction-generation trade-off similar to the β -VAE model

Table 13: β -TC-VAE configurations											
Config	1	2	3	4	5	6	7	8	9	10	
β	$1e^{-3}$	$1e^{-2}$	$1e^{-1}$	0.5	1	2	5	10	50	$1e^2$	

37



Figure 20: Results on β -TC-VAE

Factor VAE Kim and Mnih [31] augment the VAE objective with a penalty that encourages factorial representation of the marginal distributions, enforcing a stronger disentangling of the latent space. Noting that a high β value in β -VAE ELBO loss encourages disentanglement at the expense of reconstruction quality, FactorVAE proposes a new lower bound of the log likelihood with an added disentanglement term:

$$\mathcal{L}_{\text{FactorVAE}}(x) := \mathcal{L}_{ELBO}(x) - \gamma \mathcal{D}_{KL}(q_{\phi}(z)) ||\bar{q}_{\phi}(z)) \text{, with } \bar{q}_{\phi}(z) := \prod_{j=1}^{d} q_{\phi}(z_j)$$

The distribution of representations $q_{\phi}(z) = \frac{1}{N} \sum_{i=1}^{N} q_{\phi}(z|x_i)$ of the entire dataset is therefore forced to be close to its fully-disentangled equivalent $\bar{q}_{\phi}(z)$ while leaving the ELBO loss as it is. They further propose to approximate the KL divergence with a discriminator network D that is trained jointly to the VAE:

$$\mathcal{D}_{KL}(q(z)||\bar{q}(z)) \approx \mathbb{E}_{q_z(z)}\left[\log \frac{D(z)}{1 - D(z)}\right]$$

As suggested in the authors's paper, the discriminator is set as a MLP composed of 6 layers each with 1000 hidden units and LeakyReLU activation.

Table	$14 \cdot$	Factor	VAE	configurations
raute	1	I actor	VAL	conneurations

Config	1	2	3	4	5	6	7	8	9	10	
γ	1	2	5	10	15	20	30	40	50	100	



Figure 21: Results on FactorVAE

InfoVAE Zhao et al. [64] note that the traditional VAE ELBO objective can lead to both inaccurate amortized inference and VAE models that tend to ignore most of the latent variables, therefore not fully taking advantage of the modelling capacities of the VAE scheme and learning less meaningful latent representations. In order to counteract these two issues, they propose to rewrite and re-weight the ELBO objective in order to counterbalance the imbalance between the distribution in the data space and the latent space, and add a mutual information term between x and z to encourage a stronger dependency between the two variables, preventing the model from ignoring the latent encoding. One can re-write the ELBO loss in order to explicit the KL divergence between the marginalised posterior and the prior

$$\mathcal{L}_{\text{ELBO}}(x) := -\mathcal{D}_{KL}[q_{\phi}(z)||p_{z}(z)] - \mathbb{E}_{z \sim p_{z}} \left[\mathcal{D}_{KL}[q_{\phi}(x|z)||p_{\theta}(x|z)] \right].$$

Introducing an additional mutual information term $I_q(x; z)$ and extending the objective function to use any given divergence D between probability measures instead of the KL objective, the authors propose a new objective defined as

$$\mathcal{L}_{\text{InfoVAE}}(x) := -\lambda D[q_{\phi}(z)||p_{z}(z)] - \mathbb{E}_{z \sim p_{z}} \left[\mathcal{D}_{KL}[q_{\phi}(x|z)||p_{\theta}(x|z)] \right] + \alpha I_{q}(x;z)$$

where λ and α are hyperparameters. In our experiments, α is set to 0 as recommended in the paper in the case where $p_{\theta}(x|z)$ is a simple distribution. *D* is chosen as the Maximum Mean Discrepancy (MMD) [25], defined as

$$\mathbf{MMD}_{k}(p_{\lambda}(z), q_{\phi}(z)) = || \int_{\mathcal{Z}} k(z, .) dp_{\lambda}(z) - \int_{\mathcal{Z}} k(z, .) dq_{\phi}(z) ||_{\mathcal{H}_{k}}$$

with $k : \mathbb{Z} \times \mathbb{Z} \to \mathbb{R}$ a positive-definite kernel and its associated RKHS \mathcal{H}_k . We choose to differentiate 2 cases in the benchmark: one with a Radial Basis Function (RBF) kernel, the other with the Inverse MultiQuadratic (IMQ) kernel as proposed in [56] where the kernel is given by $k(x,y) = \sum_{s \in S} \frac{s \cdot C}{s \cdot C + ||x-y||_2^2}$ with $s \in [0.1, 0.2, 0.5, 1, 2, 5, 10]$ and $C = 2 \cdot d \cdot \sigma^2$, d being the dimension of the latent ensurement of the latent ensurement.

dimension of the latent space and σ a parameter part of the hyper-parameter search.

The authors underline that choosing $\lambda > 0$, $\alpha = 1 - \lambda$ and $D = \mathcal{D}_{KL}$, we recover the β -VAE model [27], while choosing $\alpha = \lambda = 1$ and setting D as the Jensen Shannon divergence we recover the Adversarial AE model [40].

Table 15: InfoVAE configurations

Config	1	2	3	4	5	6	7	8	9	10
kernel bandwidth - σ λ	$1e^{-2}$ 10	$1e^{-1}$ 10	0.5 10	$1 \\ 1e^{-2}$	$1 \\ 1e^{-1}$	1 10	1 100	1 100	2 10	5 10



Figure 22: Results on InfoVAE-RBF



Figure 23: Results on InfoVAE-IMQ

Adversarial AE (AAE) Makhzani [40] propose to use a GAN-like approach by replacing the regularisation induced by the KL divergence with a discriminator network *D* trained to differentiate between samples from the prior and samples from the posterior distribution. The encoder network therefore acts as a generator network, leading to the following objective

$$\mathcal{L}_{AAE}(x) = \mathbb{E}_{z \sim q_{\phi}(z|x)}[\log p_{\theta}(x|z)] + \alpha \mathcal{L}_{GAN},$$

with \mathcal{L}_{GAN} the standard GAN loss defined by

$$\mathcal{L}_{\text{GAN}} = \mathbb{E}_{\tilde{z} \sim p_{z}(z)} \left[\log(1 - D(\tilde{z}))) \right] + \mathbb{E}_{x \sim p_{\theta}} \left[\mathbb{E}_{z \sim q_{\phi}(z|x)} [\log D(z)] \right].$$

For the Adversarial Autoencoder implementation, we use a MLP neural network for the discriminator composed of a single hidden layer with 256 units and ReLU activation.

We observe a similar trade-off between reconstruction and generation quality as observed with β -VAE type models, as the α term acts like the β term, balancing between regularisation and reconstruction.

	Table 16: AAE configurations										
Config	1	2	3	4	5	6	7	8	9	10	
α	$1e^{-3}$	$1e^{-2}$	$1e^{-1}$	0.25	0.5	0.75	0.9	0.95	0.99	0.999	



Figure 24: Results on Adversarial AE

EL-VAE (MSSSIM-VAE) Snell et al. [54] propose an extension of the ELBO loss to a more general case where any deterministic reconstruction loss $\Delta(x, \hat{x})$ can be used by replacing the probabilistic decoder p_{θ} with a deterministic equivalent f_{θ} such that the reconstruction \hat{x} of x given $z \sim q_{\phi}(z|x)$ is defined as $\hat{x} = f_{\theta}(z)$. The modified ELBO objective is thus defined as

$$\mathcal{L}_{\mathrm{EL-VAE}}(x) = \Delta(x, \hat{x}) - \beta \mathcal{D}_{KL}(q_{\phi}(z|x)||p(z)),$$

with $\beta \leq 1$. As suggested in the original paper we use a multi scale variant of the single scale SSIM [60]: the Multi Scale Structural Similarity Metric (MS-SSIM) [59].

Table 17: MSSSIM-VAE configurations											
Config	1	2	3	4	5	6	7	8	9	10	
β window size in MSSSIM	$1e^{-2}$ 3	$1e^{-2}$ 5	$1e^{-2}$ 11	$1e^{-1}$ 5	$1e^{-1}$ 3	$1e^{-1}$ 11	1 11	1 5	1 3	1 15	



Figure 25: Results on MSSSIM-VAE

VAE-GAN Larsen et al. [37] use a GAN like approach by training a discriminator to distinguish real data from reconstructed data. In addition, the discriminator learns to distinguish between real data and data generated by sampling from the prior distribution in the latent space.

Noting that intermediate layers of a discriminative network trained to differentiate real from generated data can act as data-specific features, the authors propose to replace the reconstruction loss of the ELBO with a Gaussian log-likelihood between outputs of intermediate layers of a discriminative network D:

$$\mathcal{L}_{\text{VAE-GAN}} = \underbrace{\mathbb{E}_{z \sim q_{\theta}(z|x)} \left[\log \mathcal{N}(D_{l}(x)|D_{l}(\hat{x}), I) \right]}_{\text{reconstruction}} - \underbrace{\mathcal{D}_{KL} \left[q_{\phi}(z|x) || p_{z}(z) \right]}_{\text{regularisation}} - \mathcal{L}_{GAN} ,$$

where D_l is the output of the l^{th} layer of the discriminator D, chosen to be representative of abstract intermediate features learned by the discriminator, and \mathcal{L}_{GAN} is the standard GAN objective defined as

$$\mathcal{L}_{\text{GAN}} = \log\left(\frac{D(x)}{1 - D(x_{\text{gen}})}\right),$$

where x_{gen} is generated using $z \sim p_z(z)$. As encouraged by the authors, we add a hyper-parameter α to the reconstruction loss for the decoder only, such that a higher value of α will encourage better reconstruction abilities with respect to the features extracted at the l^{th} layer of the discriminator network, whereas a smaller value will encourage fooling the discriminator, therefore favouring regularisation toward the prior distribution. For the VAEGAN implementation, we use a discriminator whose architecture is similar to the model's encoder given in Table. 5. For MNIST and CIFAR we remove the BatchNorm layer and change the activation of layer 2 to Tanh instead of ReLU. For CELEBA, the BatchNorm layer is kept and the activation of layer 2 is also changed to Tanh. For all datasets, the output size of the last linear layer is set to 1 instead of d and followed by a Sigmoid activation.

Table 18: VAEGAN configurations

						0				
Config	1	2	3	4	5	6	7	8	9	10
α reconstruction layer (l)	0.3 3	0.5 3	0.7 3	0.8 3	0.8 2	0.8 4	0.9 3	0.9 3	0.99 3	0.999 3



Figure 26: Results on VAEGAN

Wasserstein Autoencoder (WAE) Tolstikhin et al. [56] generalise the VAE objective by replacing both terms in the ELBO: similarly to [54] (EL-VAE), the reconstruction loss is replaced by any measurable cost function Δ , and the standard KL divergence is substituted with any arbitrary divergence D between two distributions, leading to the following objective function

$$E_{q_{\phi}(z|x)}[\Delta(x,\hat{x})] + \lambda \mathcal{D}_{z}(p_{z}(z), q_{\phi}(z))$$

with λ a hyper-parameter. The authors propose two different penalties for \mathcal{D}_z :

1. GAN-based: WAE-GAN

An adversarial discriminatory network D(z, z') is trained jointly to separate the "true" points sampled from the prior $p_z(z)$ from the "fake" ones sampled from $q_{\phi}(z|x)$, similarly to [40] (Adversarial AE).

2. MMD-based

The Maximum Mean Discrepancy is used as a distance between the prior and the posterior distribution. This is the case considered in the benchmark. We choose to differentiate 2 cases in the benchmark: one with a Radial Basis Function (RBF) kernel, the other with the Inverse MultiQuadratic (IMQ) kernel as proposed in [56] where the kernel is given by $k(x,y) = \sum_{s \in S} \frac{s \cdot C}{s \cdot C + ||x - y||_2^2}$ with $s \in [0.1, 0.2, 0.5, 1, 2, 5, 10]$ and $C = 2 \cdot d \cdot \sigma^2$, d being

the dimension of the latent space and σ a parameter part of the hyper-parameter search. As proposed by the authors, for this model we choose to use a deterministic encoder meaning that $q_{\phi}(z|x) = \delta_{\mu_{\phi}(x)}$.

Table 19: WAE configurations											
Config	1	2	3	4	5	6	7	8	9	10	
kernel bandwidth - σ λ	$1e^{-2}$ 1	$1e^{-1}$ 1	0.5 1	$1 \\ 1e^{-2}$	$1 \\ 1e^{-1}$	1 1	1 10	1 100	2 1	5 1	



Figure 27: Results on WAE-RBF



Figure 28: Results on WAE-IMQ

Vector Quantized VAE (VQ-VAE) Van Den Oord et al. [58] propose to use a discrete space. Therefore, the latent embedding space is defined as a $\mathbb{R}^{K \times D}$ vector space of K different D dimensional embedding vectors $\mathcal{E} = \{e_1, \ldots, e_K\}$ which are learned and updated at each iteration.

Given an embedding size d and an input x, the output of the encoder $z_e(x)$ is of size $\mathbb{R}^{d \times D}$. Each of its d elements is then assigned to the closest embedding vector resulting in an embedded encoding $z_q(x) \in \mathcal{E}^d$ such that $(z_q(x))_j = e_l$ where $l = \operatorname{argmin}_{1 \le l \le d} ||(z_e(x))_j - e_l||_2$ for $j \in [1, d]$. Since the argmin operation is not differentiable, learning of the embeddings and regularisation of the latent space is done by introducing the stopgradient operator sg in the training objective:

$$\mathcal{L}_{\text{VQ-VAE}}(x) := \log p(x|z_q(x)) + \alpha ||sg[z_e(x)] - e||_2^2 + \beta ||z_e(x) - sg[e]||_2^2.$$

For the VQVAE implementation we use the Exponential Moving Average update as proposed in [58] to replace the term $||sg[z_e(x)] - e||_2^2$ in the loss. Thus, we consider only two hyper-parameters in the search: the size of the dictionary of embeddings K and the regularisation factor β .

		Ta	ble 20): VQ	VAE	config	uratio	ns		
Config	1	2	3	4	5	6	7	8	9	10
$K \\ \beta$	128 0.25	256 0.25	512 0.9	512 0.1	512 0.5	512 0.25	512 0.75	512 0.25	1024 0.25	2948 0.25



Figure 29: Results on VQVAE

RAE L2 and RAE GP Ghosh et al. [24] propose to replace the stochastic VAE with a deterministic autoencoder by adapting the ELBO objective to a deterministic case. Under standard VAE assumption with Gaussian decoder, both the reconstruction and the regularisation terms in the ELBO loss can be written in closed form as

$$\begin{cases} \mathcal{L}_{\text{reconstruction}}(x) = ||x - \hat{x}||_2^2, \\ \mathcal{L}_{\text{regularisation}}(x) = \frac{1}{2} \Big[||z||_2^2 - d + \sum_{i=1}^d (\sigma_\phi(x)_i - \log \sigma_\phi(x)_i) \Big]. \end{cases}$$

Arguing that the regularisation of the VAE model is done through a noise injection mechanism by sampling from the approximate posterior distribution $z \sim \mathcal{N}(\mu_{\phi}, diag(\sigma_{\phi}))$, the authors propose to replace this stochastic regularisation with an explicit regularisation term, leading to the following deterministic objective:

$$\mathcal{L}_{\text{RAE}} = ||x - \hat{x}||_2^2 + \frac{\beta}{2} ||z||_2^2 + \lambda \mathcal{L}_{\text{REG}} , \qquad (4)$$

where \mathcal{L}_{REG} is an explicit regularisation. They propose to use either

- a L2 loss on the weights of the decoder (RAE-L2), which amounts to applying weight decay on the parameters of the decoder.
- a gradient penalty on the output of the decoder (RAE-GP), which amounts to applying a L2 norm on the gradient of the output of the decoder.

Table 21: RAE configurations

						0				
Config	1	2	3	4	5	6	7	8	9	10
$egin{array}{c} eta \ \lambda \end{array}$	$1e^{-6}$ $1e^{-3}$	$1e^{-4}$ $1e^{-3}$	$1e^{-3}$ $1e^{-6}$	$1e^{-3}$ $1e^{-4}$	$1e^{-3}$ $1e^{-2}$	$1e^{-3}$ $1e^{-1}$	$1e^{-3}$ 1	$\frac{1e^{-2}}{1e^{-3}}$	$1e^{-1}$ $1e^{-3}$	$1 \\ 1e^{-3}$



Figure 30: Results on RAE-L2



Figure 31: Results on RAE-GP