



HAL
open science

Discrete element method models of deformable cells in 2D and 3D environments to explore traction generation mechanisms

Diego Vargas, Tommy Heck, Bart Smeets, Paul van Liedekerke, Herman Ramon, Hans van Oosterwijck

► To cite this version:

Diego Vargas, Tommy Heck, Bart Smeets, Paul van Liedekerke, Herman Ramon, et al.. Discrete element method models of deformable cells in 2D and 3D environments to explore traction generation mechanisms. 8th World Congress of Biomechanics, Jul 2018, Dublin, Ireland. hal-03700074

HAL Id: hal-03700074

<https://inria.hal.science/hal-03700074v1>

Submitted on 21 Jun 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Discrete element method models of deformable cells in 2D and 3D environments to explore traction generation mechanisms

Diego A. Vargas¹, Tommy Heck¹, Bart Smeets², Paul Van Liedekerke^{2,3}, Herman Ramon², and Hans Van Oosterwyck^{1,4}

¹Mechanical Engineering Department, Biomechanics section, KU Leuven, Belgium

²Division of Mechatronics, Biostatistics and Sensors (MeBioS), KU Leuven, Belgium

³Institut National de Recherche en Informatique et en Automatique, France

⁴Prometheus, Division of Skeletal Tissue Engineering, KU Leuven, Belgium

Mechanics plays a significant role in cellular behavior; cells exert forces on their surroundings and sense mechanical properties of the extracellular matrix (ECM). Subcellular processes such as protrusion formation, cell-ECM adhesion, and actomyosin contraction are mechanically regulated through signaling pathways. To improve our understanding of the role of mechanics in cell behavior, we developed multiscale mechanical models of single cells in 2D and 3D.

Methods

Two separate models were developed that capture a mechanically active cell in either a 2D or 3D environment. The discrete element method is used to describe the actin cortex mechanics (viscoelasticity and bending rigidity) of the cell[1].

The first model describes a three-dimensional cell on a plane (Fig. 1a). Retrograde flow is modeled as actin diffusion along the cell surface; outward forces proportional to this flow are modeled along a protrusive front, behind which force sensitive discrete focal adhesions can form. Stress fibers can connect adhesions, generating the largest traction forces.

The second model describes a 2D representation of a mechanically active cell embedded in a viscoelastic ECM (Fig. 1b). The ECM is modeled by means of smoothed particle hydrodynamics, which allows for large deformations and ECM degradation[2]. Protrusions are modeled by local reduction of actin cortex stiffness and application of small outward forces, followed by adhesion formation. Curvature-dependent cortex contractility then leads to traction generation.

Results

The models comprise three sets of parameters: Cell mechanical properties, ECM mechanical properties, and traction exertion dynamics. By quantifying parameter sensitivity, we described each set's effect on the ability of cells to exert tractions. We specifically vary protrusion, adhesion, actomyosin contraction, ECM stiffness, and ECM degradation. We quantify the effect on traction polarization, morphology, and cellular traction magnitude.

Simulations are compared to experimental results obtained by means of traction force microscopy for cells interacting with a homogeneous matrix, i.e. 2D culture on polyacrylamide and 3D culture in polyethylene glycol. The models generate realistic traction distributions.




Fig. 1: (a) Bottom view of simulated cell on a substrate: Arrows indicate traction forces, red areas on cell surface represent focal adhesions, and white lines represent stress fibers. (b) Displacement field for a contractile cell model after protrusion formation in a degradable viscoelastic ECM model.

Discussion

Experimental measurements at the subcellular scale can be technically difficult to obtain. Our models allow to investigate the role of various cellular processes and ECM mechanical properties and therefore can lead to a better understanding of the role of mechanics in cell behavior.

Acknowledgements

ERC (FP7/2007-2013, n° 308223), FWO-Vlaanderen (n° G.0821.13), and FWO and EU's Horizon 2020 research and innovation programme (n° 665501).

References

1. Odenthal *et al.*, (2013). *PLoS Comp Biol*, 9(10)
2. Heck *et al.*, (2017). *Comput Methods in Appl Mech Eng*, 322 p515