

A Robust Optimization Model for a Community Healthcare Service Network Design Problem

Congke Wang, Yankui Liu, Jinfeng Li, Guoqing Yang

▶ To cite this version:

Congke Wang, Yankui Liu, Jinfeng Li, Guoqing Yang. A Robust Optimization Model for a Community Healthcare Service Network Design Problem. IFIP International Conference on Advances in Production Management Systems (APMS), Sep 2021, Nantes, France. pp.568-573, 10.1007/978-3-030-85910-7_60. hal-03806476

HAL Id: hal-03806476 https://inria.hal.science/hal-03806476

Submitted on 7 Oct 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License



This document is the original author manuscript of a paper submitted to an IFIP conference proceedings or other IFIP publication by Springer Nature. As such, there may be some differences in the official published version of the paper. Such differences, if any, are usually due to reformatting during preparation for publication or minor corrections made by the author(s) during final proofreading of the publication manuscript.

A Robust Optimization Model for A Community Healthcare Service Network Design Problem

Congke Wang¹, Yankui Liu¹, Jinfeng Li¹, and Guoqing Yang²

¹ College of Mathematics and Information Science, Hebei University, Baoding 071002, Hebei, China

² School of Management, Hebei University, Baoding 071002, Hebei, China ygq@hbu.edu.cn

Abstract. In this paper, we present a robust model for the community healthcare service network design problem. The community healthcare service network can determine the location of central hospitals and the allocation of the community medical service stations in order to minimize that cost of the whole network. Beside, we employ the Box+ellipsoidal set to deal with the objective which obtain the uncertain parameter. In addition, we reformulate the proposed model into a computationally tractable robust counterpart form under Box+ellipsoidal set. Finally, we verify the validity of the model by a case study.

Keywords: 2-service network · Community healthcare service network · Robust optimization.

1 Introduction

In recent years, community health service networks have become an increasing research hot spot for scholars. It is necessary to establish a reasonable and efficient community health care network to meet the health care needs of the community. The community healthcare service network is a typical facility location problem. [1] first proposed the study of location-allocation in the field of healthcare facilities, and many scholars have since conducted extensive research on the issue of healthcare facilities different perspectives [2–4]. [5] put forward that some healthcare facility location models are based on p-median model. Based on the 2-allocation p-hub model proposed in [6], this paper proposes a community medical service network model with 2-service structure. The community healthcare network with 2-service structure that needs to decided pcentral hospitals and each community medical service station is served by exactly two central hospitals. We conduct a 2-service community healthcare network that can effectively immunize against unforeseen circumstances and reduce the risk of uncertainty. For example, the emergence of covid-19 is an unexpected and unforeseen event that requires specialized designated hospital to test. Our proposed 2-service community healthcare network that indicates a designated hospital is served by two central hospitals has a stronger ability to cope with the outbreak of the epidemic.

2 C.K. Wang et al.

Our primary concern with this study also contains uncertain factors in the service network. In recent years, the research on uncertainty in medical field has attracted more and more attention from scholars. [7] studied a stochastic optimization of primary health care network to deal with random variables in the network, and proposed a random model of integer nonlinear programming to improve the service level of the whole service network. In practice, the precise probability of the realization of uncertain variables is difficult to obtain. Distributionally robust optimization [8–10] is an emerging approach to deal with uncertainty by limiting uncertain variables through an uncertainty set with certain characteristics. [11] proposed a new hybrid robust possibility programming for hierarchical health network design based on input parameter uncertainty. In this paper, we propose a distributionally robust model for the proposed 2-service network problem and use Box+ellipsoid uncertain set to deal with the uncertain demand in medical network.

2 Problem statement of CHSN

In this section, we introduce structure of the community health care service network network. As shown in Figure 1, the community health care service network design problem includes a fixed central hospitals, a group of community medical service stations and the allocation structure between them. In particular, we assumed that any community health service station was assigned to exactly two central hospitals for service. We believe that the identified central hospitals serve the community medical service stations allocated to them and that medical resources are shared among the central hospitals.

3 The robust healthcare service network model

In this section, we introduce the robust model for the community health care service network.

$$\min_{\mathbf{h},\mathbf{Y},\mathbf{x}} \sum_{k \in [N]} F_k h_k + \sum_{i,k \in [N]} C_{ik} Y_{ik} + \\
\max_{\mathbb{P} \in \mathscr{F}} \mathbf{E}_{\mathbf{u} \sim \mathbb{P}} \left[\sum_{i,k \in [N]} u_i x_{ik} d_{ik} \beta + \sum_{k \in [N]} P_k (\sum_{i \in N} u_i x_{ik} - Q_k) \right]$$
(1)



Fig. 1. The network of community medical service design problem

1

s.t.
$$\sum_{k \in [N]} Y_{ik} + (2-p)h_i = 2 \quad \forall i \in [N]$$
 (2)

$$Y_{kk} = h_k \qquad \forall k \in [N] \tag{3}$$

$$\sum_{k \in [N]} h_k = p \tag{4}$$

$$Y_{ik} \le h_k \qquad \forall i \in [N], k \in [N] \tag{5}$$

$$n_{kl} \le h_k \qquad \forall k \in [N], l \in [N] \tag{6}$$

$$m_{kl} \le h_l \qquad \forall l \in [N], k \in [N]$$
 (7)

$$m_{kl} \ge h_l + h_k - 1 \qquad \forall l \in [N], k \in [N]$$
(8)

$$x_{ik} \le Y_{ik} \qquad \forall i \in [N], k \ne i \in [N] \tag{9}$$

$$\sum_{k \in [N]} x_{ik} = 1 \qquad \forall i \in [N]$$
(10)

$$x_{ik} \ge 0, h_k, Y_{ik}, m_{kl} \in \{0, 1\} \quad \forall i \in [N], k \in [N], l \in [N]$$
(11)

The purpose of objective (1) is to minimize all the fixed cost and the maximum of the expected operating cost by limiting the distributions of the uncertain variables to Box+ellipsoidal sets. Constraint (2) indicates that one community medical service station is assigned to two central hospitals. Constraint (3) implies that community medical service stations can only be allocated to central 4 C.K. Wang et al.

hospitals. Constraint (4) ensures that P central hospitals are selected. Constraint (5) shows that a community medical service station can only be assigned to an open central hospital. Constraints (6)-(8) indicate the contact of the central hospital. Constraint (9) implies that community service stations can only be assigned to open links. Constraint (10) requires that all demands be served by the central hospital. Constraint (11) is standard binary and non-negative integral constraint.

For the objective with uncertain parameters, we use the Box+ellipsoidal uncertain set to process. We assume that the uncertain parameter $E_{\mathbb{P}}[u]$ has the following form: $E_{\mathbb{P}}[u] = E_{\mathbb{P}}^{0}[u] + \sum_{l \in L} \zeta_{l} E_{\mathbb{P}}^{l}[u]$. In this study, we assume that the first moment $E_{\mathbb{P}}[u]$ is subject to a Box+ellipsoidal set, which can be depicted by the following distributional set $\mathscr{F}: \mathscr{F} = \{\zeta_{l} \in \mathbf{R}^{l} : -1 \leq \zeta_{l} \leq 1, l \leq L, \sqrt{\sum_{l \in [L]} \zeta_{l}^{2} / \sigma_{l}^{2} \leq \Omega, l \in L}\}$, where σ_{l} is the given parameter, and Ω is the adjustable safe parameter controlling the size of the distributional set. Finally, we obtain the computationally processable form of the robust community healthcare service network.

$$\min \sum_{k \in [N]} F_k h_k + \sum_{i,k \in [N]} C_{ik} Y_{ik} + \sum_{k \in [N]} P_k Q_k + 2t$$

s. t.
$$\sum_{l \in [L]} |z_l| + \Omega \sqrt{\sum_{l \in [L]} w_l^2 \sigma_l^2} \le t - (E_p^0[u])^T \mathbf{x} \mathbf{d}^T \beta$$
$$z_l + w_l = -(E_p^l[u])^T \mathbf{x} \mathbf{P}^T \quad \forall l \in [L]$$
$$\sum_{l \in [L]} |s_l| + \Omega \sqrt{\sum_{l \in [L]} w_l^2 \sigma_l^2} \le t - (E_p^0[u])^T \mathbf{x} \mathbf{d}^T \beta$$

$$\sum_{l \in [L]} |s_l| + \Omega \sqrt{\sum_{l \in [L]} v_l^2 \sigma_l^2} \le t - (E_p^s[u])^T \mathbf{x} \mathbf{d}$$
$$s_l + v_l = -(E_p^l[u])^T \mathbf{x} \mathbf{P}^T \quad \forall l \in [L]$$

(2)-(11)

where t, z, w, s, v are auxiliary decision variables.

4 Case study

In this section, we apply our model to a small-scale case. We selected ten community medical service stations as shown in Figure 2 for experimental study. Figure 3 and Table 1 show our experimental results. As shown in Figure 3, the optimal solution of the robust model selects community medical service stations 2,7 and 9 as central hospitals, and gives the corresponding demand allocation. The topology of the robust model shows that the demand of each district service station is served by two central hospitals, thus improving the overall service level of the medical service network.



Fig. 2. The network of community medical service design problem

 Table 1. The result of robust model

Optimal value Hubs			Routes	
RobustModel	863939.2	$2,7,9 \ 3,4,6 \rightarrow (2,7)$	$1, 10 \rightarrow (2, 9)$	$5,8 \rightarrow (7,9)$

5 Conclusions

In this paper, we aimed to minimize the total cost of service network, and proposed a community healthcare network system to enable markers to make an effective location-allocations decision. For the uncertain parameters in the community healthcare network, we use robust optimization to deal with the objective with uncertain parameters, and obtain a exact model which can be processed. We also provide an illustrative example and highlight the impact of uncertain parameters on the model. The results show that the robust community healthcare network model proposed by this paper can well resist the uncertainty of the uncertain parameters.

References

- Rahman, S-u., Smith, D.K.: Use of location-allocation models in health service development planning in developing nations. European Journal of Operational Research 123(3), 437–52 (2000)
- Rais, A., Viana, A.: Operations research in healthcare: a survey. International Transactions in Operational Research 18(1), 1–31 (2011)
- 3. Zhang, Y., Berman, O., Verter, V.: The impact of client choice on preventive healthcare facility network. OR Spectrum **34**, 349–370 (2012)
- Ahmadi-Javid, A., Seyedi, P., Syam, S.S.: A survey of healthcare facility location. Computers and Operations Research 79, 223–263 (2017)
- Daskin, M.S., Dean, L.K.: Location of health care facilities. In: Brandeau ML, Sainfort F, Pierskalla WP, editors. Operations Research and Health Care. NewYork: Springer(2004) pp. 43–76.



Fig. 3. Topology analysis of the robust model.

- Mokhtar, H., Krishnamoorthy, M., Ernst, A.T. : The 2-allocation p-hub median problem and a modified Benders decomposition method for solving hub location problems. Computers and Operations Research 104, 375–393 (2019)
- Ahmadi-Javid, A., Ramshe, N.: A stochastic location model for designing primary healthcare networks integrated with workforce cross-training. Operations Research for Health Care 24, 100–226 (2020)
- 8. Ben-Tal, A., Hochman, E.: More bounds on the expectation of a convex function of a random variable. Journal of Applied Probability **9**(4), 803–812 (1972)
- 9. Ben-Tal, A., Nemirovski, A. : Robust solutions of linear programming problems contaminated with uncertain data. Mathematical Programming 88, 411–424 (2008)
- Bertsimas, D., Sim, D. : The price of robustness. Operations Research 52(1), 1– 22(2004)
- Mousazadeh, M., Torabi, S.A., Pishvaee, M.S., Abolhassani, F: Health service network design: a robust possibilistic approach. International Transactions in Operational Research 25, 337–373 (2018)