

Frictional three-point bending test: disentangling the role of friction through real and numerical experiments

Émile Hohnadel, Joel Marthelot, Ignacio Andrade-Silva, Thibaut Métivet, Olivier Pouliquen, Florence Bertails-Descoubes

▶ To cite this version:

Émile Hohnadel, Joel Marthelot, Ignacio Andrade-Silva, Thibaut Métivet, Olivier Pouliquen, et al.. Frictional three-point bending test: disentangling the role of friction through real and numerical experiments. European Solid Mechanics Conference ESMC 2022, Jul 2022, Galway, Ireland. hal-03960300

HAL Id: hal-03960300 https://inria.hal.science/hal-03960300

Submitted on 27 Jan 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.


Frictional three-point bending test: disentangling the role of friction through real and numerical experiments

Emile Hohnadel¹, Joël Marthelot², Ignacio Andrade², Thibaut Metivet¹, Olivier Pouliquen², Florence Bertails-Descoubes¹

E-mail: emile.hohnadel@inria.fr

Keywords: thin elastic rods, dry frictional contact, numerical simulation








Fig. 1: Left: Picture of the experimental manipulation. Center: illustration of one arbitrary step of the simulation, showing the forces applied on the indented fiber (arrow colors indicate the stick (red) or slip (green) regimes). Right: plot of the deflection force as a function of the indentation for a full indentation cycle, computed with our simulator.

The three-point bending test is a classical test, widely used to determine the bending modulus of a rod. However, the role of friction on this single test has been scarcely studied [1]. Our objective in this work is therefore to investigate the role of friction in this archetypical test in both the small and large deflection regimes by combining experimental and numerical studies.

On the one hand, we design a three-point bending experimental setup with fixed – non-rolling – supports, with precision measurements of the forces applied at the deflection point together with the corresponding displacement of the fiber along one of the two supports. On the other hand, thanks to our carefully validated numerical model coupling a rod model to frictional contact [2], we manage to predict accurately the geometry and forces of the system in the full nonlinear regime.

By comparing the numerical results with the experimental ones and expanding on a wider range of parameters, the role of friction is quantified and analysed, extending the usual rolling three-point bending test. A mathematical study is also conducted, based on the numerical observations to complement the results. Finally, we demonstrate that the frictional three-point bending test provides a simple way to measure the friction coefficient of a slender structure.

References

- [1] Van Paepegem, W., De Geyter, K., Vanhooymissen, P., Degrieck, J., "Effect of friction on the hysteresis loops from three-point bending fatigue tests of fibre-reinforced composites", Composite Structures, 72, 212-217, 2006.
- [2] Romero, V., Ly, M., Rasheed, A.-H., Charrondière, R., Lazarus, A., Neukirch, S., Bertails-Descoubes, F., "Physical validation of simulators in Computer Graphics: A new framework dedicated to slender elastic structures and frictional contact", ACM Transactions on Graphics, 40, Article 66: 1-19, 2021.

¹ Univ. Grenoble Alpes, Inria, CNRS, Grenoble INP, LJK, Grenoble, France

² Aix-Marseille Univ. CNRS, IUSTI, Marseille, France