

Elastic Rods for Fluid Dance Movements Modeling

Manon Vialle, Mélina Skouras, Rémi Ronfard

▶ To cite this version:

Manon Vialle, Mélina Skouras, Rémi Ronfard. Elastic Rods for Fluid Dance Movements Modeling. AFIG 2021, 2021, Sofia Antipolis, France. hal-04136667

HAL Id: hal-04136667 https://inria.hal.science/hal-04136667

Submitted on 22 Jun 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Elastic Rods for Fluid Dance Movements Modeling

Manon Vialle¹, Melina Skouras¹ and Remi Ronfard¹

¹Inria Grenoble



Figure 1: Our model in different poses of the dance

Abstract

We present a new abstract representation of choreographic motion that conveys the typical fluidity of modern dances, such as those by Isadora Duncan, better than traditional human-like or skeleton-based representations. Our model is formed by five flexible ribbons joining at the solar plexus and is animated from motion capture data using a optimization-based algorithm.

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

CCS Concepts

•Human-centered computing \rightarrow Visualization; •Computing methodologies \rightarrow Animation;

1 1. Introduction

2 Isadora Duncan's choreography is one of the foundation of modern dance. In her work, Duncan wanted to uncover what she described 3 as "the natural movement". In her definition, natural movement 4 is unrestricted, respecting both the structure of the body and the 5 pull of gravity: "Such movements will always have to depend on 6 and correspond to the form that is moving" [Dun28]. That is, each 7 movement performed is seen through the lens of a dancer's body. 8 In her "natural movement" philosophy, she also expressed that the 9 center of movement and energy is the solar plexus. 10

Unfortunately, Isadora Duncan always refused to be filmed, be-11 cause she thought that the frame rate of the camera at the time 12 (about 24 frames per seconds) was not enough to represent the flu-13 idity of her choreography. Therefore her choreographic knowledge 14 was transmitted mostly orally from one generation of Duncanian 15 dancers to another. Although part of her repertoire has been trans-16 lated into dance notations (such as Laban and Sutton notations), 17 those notations are hard to decipher and not well known amongst 18 the dance community. One can also wonder if the fluidity of her 19 natural movement can be expressed through such succinct notation. 20

In this paper we propose a graphical model that represents Duncan's danced choreography while staying as close as possible to her movement qualities and philosophy. To this end, we worked closely with a professional Duncanian dancer from the third generation of Duncan's students. We recorded the expert as she danced several pieces using motion capture at a high frame rate. Through multiple discussions with our expert, we were able to design a model which stays faithful to Duncan's philosophy and style. Our result is a starshaped representation made of 5 flexible rods that can bend, twist and stretch and smoothly deform to follow the pre-recorded motion capture markers positions.

2. Related Work

2.1. Physical models for dance

Previous work has traditionally addressed this issue by introducing physical models of the dancer. Mass-spring systems have been a main part of physical models used to represent motion, especially in dance, as these systems can easily represent the joints and bones of the human skeleton. In particular, Piana et al. [PAN*16] use mass-spring figures to analyze movement fluidity. Hsieh [Hsi07] creates a new grammar using verbs and adjectives and associate a special mass-spring system to convey motion. Fdili Alaoui et al. [FABJB13] propose an interactive installation to capture the dancer's movements, and run physical simulations to analyze their motion qualities. Our model of elastic rod can be seen as a new contribution to this long line of research.

2

83

84

85

86

87

88

89

90

91

92

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109 110

111

112

113

114

115

116

117

118

119

121

122

123

124

125

126

129

131

132

133

2.2. Dance visualization 46

Video is one of the first technology to be used by choreogra-47 phers to represent dance motion, such as Wiliam Forsythe in 48 [FS99, PSF*09]. However in [Bro89], Brooks demonstrates how 49 the traditional tools of cinematography affect and distort the per-50 ception of choreographic movement. Moreover, De Boer et al. [dB-51 JTAPN18] investigated which representations conveyed movement 52 the best between textual description, 2d animations, 3d animations 53 and auditory description and found that dancers prefered 3d an-54 imations. Motion capture has thus emerged as a promising tool 55 for dance representation as it allows to have a precise 3D record-56 ing. While the preferred visualization style for motion capture in 93 57 most previous work is stick figures or human-like avatars, some au-58 thors and artists have chosen to explore more abstract visualization 59 styles. D. Poulin and M. Époque developed a concept of "dance 60 without bodies" by using particle animation guided by motion cap-61 ture data [Szp14]. Astier shows the motion capture markers without 62 revealing the dancers bodies in his movie Clinamen [Arc20]. Our 63 method is a new way of using motion capture data to represent 64 65 dance in an abstract way.

3. Input Data 66

The input of our model is a prerecorded dance captured using a 67

motion capture system. Our mocap set-up relies on 64 spherical 68 trackers (markers) whose positions in the 3d space is recorded at 69

100 frames per second (see Figure 2 for an illustration of the marker 70 locations). 71




Figure 2: Positions of the markers on the dancer's body.

4. Modeling the dancer 72

Our model of the dancer was co-designed with an expert Duncanian 127 73 dancer of the third generation, following the general principles of 128 74 natural movement, as expressed by Isadora Duncan in her autobi-75 ography [Dun27] and other writings [Dun28]. In her autobiogra-76 phy Duncan describes her attempts to find "the central spring of all 77 movement" and her discovery that it should be located in the solar 130 78 plexus : "I know only one dance and it is this movement: draw-79 ing back your hands to the solar plexus, whereupon an inner force 80 opens up your arms and raises them" [Dun27]. 81

82 4.1. Dancer Representation

Taking into account the above requirements expressed by our expert dancer, we propose to model the dancer's body as an abstract figure in the shape of a starfish, with five ribbons attached together at the solar plexus. Using ribbons instead of a rigid skeleton would follow the fact that the dance of Isadora Duncan is unconstrained to one's body. We also hope that it will convey the fluidity of the movement better, as rods are not restricted to bend and twist at a fixed set of locations only (the joints of a skeleton). In practice, our ribbons are modeled as isotropic rods, i.e. have a circular crosssection, which let them equally bend and twist in any direction. However, we display them as flat ribbons to better visualize their twist.

4.1.1. Natural shapes of rods' centerlines

We assume that the natural shape (ie. shape at rest) of the rod is straight, so as not to favor any particular direction for bending and twisting. We define the natural shapes of the rods by using the mocap data when the dancer takes a T-pose. It is a pose most mocap systems ask the user to take to calibrate the system and is present at the beginning of all our recordings. Therefore, using this pose allows us to make sure that the natural shape of our rods is consistent across all animations, while exhibiting low bending of the limbs, which is coherent with our assumption for the rods to be straight at rest.

We process each limb (arms and legs) and the head separately and create a rod for each. To this end, we first manually group all the markers according to their body location. To make sure all rods join at the solar plexus we precompute the position of the later (defined, in our implementation, as the midpoint between the markers CLAV and C7, as labelled in Figure 2) and make the centerline of our rod - a straight segment in our case - start at this position. To define the direction of the segment, we perform principal component analysis on the positions of the markers of the group associated to the body part being processed and use the vector associated to the largest variance. Finally, we size the segment by projecting all the markers of the group onto the line defined by the solar plexus and the direction computed above and set as segment's end point the projected point furthest away from the solar plexus.

4.1.2. Orientation of the ribbons in the natural pose 120

Since we process each group separately, there is no guarantee that the obtained centerlines pass through a common plane, and, in practice, the arms are indeed slightly tilted forward. As we still want our ribbons to be orientated consistently, we rotate them around their respective centerlines so that their normals are as close as possible to a common vector, chosen to be the normal to the solar plexus and defined as the normal to the plane passing through the markers RCLAV. LCLAV and CLAV.

4.2. The Discrete Elastic Rod model

In order to deform and animate our ribbons, we need to associate them to a numerical physical model for rods. We choose Discrete *Elastic Rods* [BWR^{*}08], a discrete geometric model for the simulation of elastic rods that can stretch, bend and twist. In this model,




Figure 3: Left: natural pose, Right: deformed pose

a rod is defined by a centerline, and a set of material frames, track-134 ing the rotations of the rods' cross-sections around the centerline 135 with respect to an untwisted rod configuration. The vertices of the 136 centerline Γ will be denoted by $(x_i)_{i \in [0,n+1]}$ and its edges $e^i =$ 137 $x_{i+1} - x_i$, $i \in [0, n]$. The set of material frames $M^i = \{t^i, m_1^i, m_2^i\}$ are 175138 defined per edge, and are considered to be adapted to the centerline 139 curve, that is $t^i = e^i / ||e^i||$. The rotation angle with respect to the 140 176 untwisted reference frame $\{t^i, u^i, v^i\}$ at is denoted θ^i . Throughout 141 this paper, we will use the following convention: lower (resp. up-142 per) indices refer to quantities associated to a vertex x_i (resp. edge 143 e^{l}). Three types of energies are associated to the rod : $E_{bend}(\Gamma)$ and 144 $E_{stretch}(\Gamma)$ which depend on the x_i in the case of a straight isotropic 145 rod and $E_{twist}(\Gamma)$ which depends on the θ^{i} in the case of a straight 146 isotropic rod (see more details in [BWR*08]). 147

5. From mocap to dancing rods 148

We want the rods to follow the dancer's movements. To achieve 149 this, we connect each ribbon to the different markers associated to 150 it using springs. We want to be able to determine the position of 151 the ribbon and its orientation at each time frame. To do so we will 152 minimize the total energy of the physical model which combines 2 153 types of energies: the energy associated to the ribbon's internal de-154 formation (twist, bend and stretch) and the energy associated with 177 155 the springs that were attached to the ribbon. 156

5.1. Adding energies to follow the dance 157

181 In this section, we introduce energies which will enable the rod to 158 follow the data (i.e. the markers positions) and therefore to match 159 183 the dancer's movement closely. We use two kinds of energies: the 160 184 linear position energy and the angular position energy. For that pur-161 185 pose we will introduce springs between each marker and its pro-162 186 jection onto the ribbon. Therefore the total energy of our ribbon 163 187 becomes $E(\Gamma) = E_{bend}(\Gamma) + E_{twist}(\Gamma) + E_{stretch}(\Gamma) + E_{linear}(\Gamma) +$ 164 188 $E_{angular}(\Gamma)$. In the following section, we denote s_k the position at 165 189 current time of marker number k. 166

5.1.1. Linear spring associated with data 167

Each marker is associated to an edge. At time $\tau=0$ we project $\ ^{191}$ 168 the marker $\bar{s_k}$ onto the centerline. This projection gives a point $\bar{c_k}$ 169 193 which belongs to the edge e_{i_k} as displayed in Figure 4. We express 170 194 c_k with respect to the two vertices of the edge x_{i_k+1} and x_{i_k} using 171 195 barycentric coordinates : $c_k = y_k x_{i_k} + (1 - y_k) x_{i_k+1}$ with $y_k \in [0, 1]$. 172 We denote $z^k = s_k - c_k$. The energy associated to a marker s_k is 173 then : 174




Figure 4: Angular spring connecting a marker to an edge

$$E_{linear}(\Gamma) = \sum_{k=0}^{p} E_{linear}(e^{i_k}) = \frac{1}{2} \sum_{k=0}^{p} a_k (\|\bar{z^k}\| - \|z^k\|)^2,$$

where a_k is the rigidity of the spring.

5.1.2. Angular spring associated with data

We want the angular difference between the marker and its associated edge to remain constant in order for a change of angle to impact the position of the material frame. We therefore evaluate the rotation around the tangent t^{i_k} . For that purpose, we first project z^k to the reference frame u^{i_k} and $v^{i_k} : w^k = (z^k \cdot u^{i_k})u^{i_k} + (z^k \cdot v^{i_k})v^{i_k}$. Then we denote λ^{i_k} the minimum angle required to move $m_1^{i_k}$ to w^k see Figure 4. The energy for this angular spring associated with the edge e^{i_k} is $E_{angular}(e^{i_k}) = \frac{1}{2}q_k(\lambda^{i_k} - \lambda^{i_k})^2$, where q_k is the rigidity of the spring. We want to express this angle with respect to θ . We denote $u^{i_k} \overline{z^k}$ the angle between u^{i_k} and z^k . We then have $\lambda = \widehat{u^{i_k} z^k} - \theta^{i_k}$. The total energy can then be written as

$$E_{angular}(\Gamma) = \frac{1}{2} \sum_{k=0}^{p} q_k (\widehat{\bar{u}^{i_k} \bar{z}^k} - \bar{\theta}^{i_k} - \widehat{\bar{u}^{i_k} \bar{z}^k} + \theta^{i_k})^2.$$

5.2. Enforcing an orientation

178

179

180

190

Throughout the simulation, we want the different rods to remain joined at the plexus. This translates into the following constraints $e^{0} = p$, where p is the current position of the plexus as defined in Section 4.1. We also want to ensure that the orientation of the material frame and the reference frame remain stable to avoid overtwisting of the rods. To this end, we will ask the second vector of the reference frame of each rod at the solar plexus, v_0 , to align as closely as possible to the normal n at the solar plexus, i.e. we will ask v_0 to match the normal *n* when projected onto the plane of the rod's cross section, orthogonal to the tangent t_0 . We then ask the initial material frame to match the reference frame using the constraints $\theta^0 = 0$.

5.3. Procedure to create motion

We onsider that at each time frame the rod is at a state of equilibrium, i.e. a state that minimizes its total energy, which enables to perform optimization on the energy function. Therefore, at each time step we want to find the optimal rod which minimizes its total energy.

Since we decided to have a straight isotropic rod, each energy term either depends on the position of the centerline (x_i) or on the 239

243 244

245

251

252

angles of the material frames θ_i . We recall that the total energy of the system is

$$E(\Gamma) = E_{bend}(\Gamma) + E_{twist}(\Gamma) + E_{stretch}(\Gamma) + E_{linear}(\Gamma) + E_{angular}(\Gamma) + E_{$$

We know that $E_{bend}(\Gamma)$, $E_{stretch}(\Gamma)$ and $E_{linear}(\Gamma)$ depend only on the position of the centerline whereas $E_{twist}(\Gamma)$ and $E_{angular}(\Gamma)$ depends on the angles θ^i .

This lets us treat the optimization of the two sets of variables 199 independently. Since the reference frame is necessary to evaluate 200 the angular spring energy and depends on the centerline position 201 (because it is adapted), we first find the optimal centerline posi-202 tion and then we find the optimal position of the material frame 203 as shown in Algorithm 1. The variables for the first optimization 204 233 problem are the vertices x_i and the variables for the second prob-205 lem are the θ^i . In order to solve the optimization problem we used ²³⁴ 206 a Newton's method from the Ipopt library [WB06]. To speed op- 235 207 208 timization, we use the solution corresponding to the previous time ²³⁶ frame as the starting state of Newton's method for the current time 237 209 238 210 frame. Finally, each rod is treated as an independent problem.

	gorithm 1: Simulation steps for one rod	
	nput : Set of markers	
0	output: Animated rod	24
1 (Create initial rod;	
2 f	or each time frame do	
3	Find optimal $(x_i)_{i \in [0,N]}$ and set centerline;	
4	Compute and set reference frames;	
5	Find optimal $(\theta^i)_{i \in [0, N-1]}$ and set material frames;	

211 5.4. Implementation

212 We implemented this method in C++ using Ipopt [WB06] library

²¹³ for the optimization, Eigen [GJ*10] for linear algebra, Mapple soft-

ware to compute the Hessian and gradient of the functions and libigl for visualization [JP*18].

216 6. Experimental results

We evaluated our system on a set of 6 dances (*Prelude*, *Mo-*²⁴⁶ *ment Musical, Folatrerie, Etude Revolutionaire, Water Study* and ²⁴⁷ *Mother*), recorded twice (exept *Water Study*) all choreographed by ²⁴⁸
Isadora Duncan and performed by our expert dancer, giving us a ²⁴⁹
total of 11 recordings. We assess our model by looking at the data ²⁵⁰
produced during the process described by Algorithm 1.

223 6.1. Number of segments

With this model, we have the choice of the number of segments 253 224 used to discretize the rods. Figure 5 shows the resulting ribbons 254 225 corresponding to different discretizations. We also have the free- 255 226 dom to create a skeleton like figure as shown in Figure 5 (a) by 256 227 using ribbon edges of different sizes. A rod, in the continuous set- 257 228 ting, is smooth and can bend at any location. Such a behavior can 258 229 be approximated by using a high number of segments. We decided 259 230 to go with 100-edge ribbons that offered a good trade-off between 260 231 smoothness and tractability (see Figure 5 (d)). 232 261




Figure 5: Output ribbons corresponding to the same input data but different number of segments

6.2. Weights of the energy terms

We also need to set the stiffnesses of the different energies that we use in our formulation (η for stretch, β for twist, α for bend, a_k for linear data and q_k for angular data). The more weight we put on the data terms, the closer to the data the rods will be, and the highest the weights of the rods' energies the smoother the rods are going to be. We found that the best tradeoff for a smooth yet close to the data rod was chosing $\eta = \alpha = \beta = 100$ and $a_k = q_k = 0.1$

6.3. Energies Analysis




Figure 6: Histogram of total linear/angular energy for Folatrerie

We also looked at the error related to the input data to know how far our model is from our source data, measured via our linear and angular energies. In Figure 6a, we can see that most errors are between 0 and 0.05 cm and are majored by 2.5 cm. This means the total linear displacement in *Folatrerie* for any time frame for all ribbons is at most 2.5 cm. In Figure 6b we can see that the angular displacement is mainly between 0 and 0.05 radian. We conclude that our rods remain close to the input markers, ensuring that they follow the dance closely.

7. Conclusion

In this paper we presented a new visualization method for dance motion, with the special goal of transmitting important principles in Isadora Duncan's dance heritage. Our method was co-designed with Duncan experts. As a result, we are now planning to create and distribute a novel corpus of Duncan dances, acquired with modern motion capture techniques and displayed as dancing elastic rods, for use by Duncan scholars and students. The new visualization appears to be much more readable than the traditional dance notations (Sutton, Laban) used to transcribe the choreographic style of Isadora Duncan in the past.

262 **References**

- 263 [Arc20] ARCIER H.: Clinamen. https://www.operadeparis. 264 fr/3e-scene/art-video/clinamen, 2020. 2
- [Bro89] BROOKS V.: Restoring the meaning in cinematic movement:
 What is the text in a dance film? *Iris*, 9 (1989), 69–103. 2

 [BWR*08] BERGOU M., WARDETZKY M., ROBINSON S., AUDOLY
 B., GRINSPUN E.: Discrete Elastic Rods. ACM Transactions on Graphics (SIGGRAPH) 27, 3 (aug 2008), 63:1–63:12. 2, 3

- [dBJTAPN18] DE BOER V., JANSEN J., TJON-A-PAUW A.-L., NACK
 F.: Interactive dance choreography assistance. In *Advances in Computer Entertainment Technology* (Cham, 2018), Cheok A. D., Inami M.,
 Romão T., (Eds.), Springer International Publishing, pp. 637–652. 2
- 274 [Dun27] DUNCAN I.: *My life*. Liveright (2013 edition), 1927. 2
- [Dun28] DUNCAN I.: *The Art of the Dance*. Theatre Arts Books, 1928.
 1, 2
- [FABJB13] FDILI ALAOUI S., BEVILACQUA F., JACQUEMIN C.,
 BERMUDEZ B.: Dance interaction with physical model visuals based
 on movement qualities. *The International Journal of Arts and Technology* (2013). URL: https://hal.archives-ouvertes.fr/
 hal-01572626.1
- [FS99] FORSYTHE W., SOMMER A.: William forsythe: Improvisation
 technologies: A tool for the analytical dance eye. 2
- [GJ*10] GUENNEBAUD G., JACOB B., ET AL.: Eigen v3.
 http://eigen.tuxfamily.org, 2010. 4
- [Hsi07] HSIEH C.-M.: Grammar of Physically Based Modeling of Dance
 Movements: Use for Choreographic Composition. Theses, Institut Na tional Polytechnique de Grenoble, Sept. 2007. 1
- [JP*18] JACOBSON A., PANOZZO D., ET AL.: libigl: A simple C++
 geometry processing library, 2018. https://libigl.github.io/. 4
- [PAN*16] PIANA S., ALBORNO P., NIEWIADOMSKI R., MANCINI M.,
 VOLPE G., CAMURRI A.: Movement fluidity analysis based on performance and perception. In *Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems* (New York, NY, USA, 2016), CHI EA '16, Association for Computing Machinery,
 p. 1629–1636. 1
- [PSF*09] PALAZZI M., SHAW N., FORSYTHE W., LEWIS M., ALBRIGHT B., ANDERECK M., BHATAWADEKAR S., BAN H., CALHOUN
 A., DROZD J., FRY J., QUINTANILHA M., REED A., SCHROEDER B.,
- SKOVE L., THORNDIKE A., TWOHIG M., AHLQVIST O., CHAN P.,
 NOE A.: Synchronous objects for one flat thing, reproduced. 2
- Szp04] SZPORER P.: Dancing the rite of spring today: Bodies, particles, technologies and affects. Dance
 Current, Canada's Dance Magazine (2014). URL:
- 305 https://www.thedancecurrent.com/column/
- 306 dancing-rite-spring-today-bodies-particles-technologies-and-affects.
- 307 2
- 308 [WB06] WÄCHTER A., BIEGLER L.: On the implementation of an
- 309 interior-point filter line-search algorithm for large-scale nonlinear pro-
- gramming. *Mathematical programming 106* (03 2006), 25–57. 4