



**HAL**  
open science

## Parametric optimization of fold bifurcation points

Adrien Mélot, Enora Denimal, Ludovic Renson

► **To cite this version:**

Adrien Mélot, Enora Denimal, Ludovic Renson. Parametric optimization of fold bifurcation points. Nodycon 2023 - Third International Nonlinear Dynamics Conference, Jun 2023, Rome, Italy. pp.1. <hal-04166242>

**HAL Id: hal-04166242**

**<https://inria.hal.science/hal-04166242v1>**

Submitted on 19 Jul 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire HAL, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons CC BY 4.0 - Attribution - International License

# Parametric optimization of fold bifurcation points

Adrien Mélot\*, Enora Denimal\* and Ludovic Renson \*\*

\*Univ. Gustave Eiffel, Inria, COSYS-SII, I4S, Campus Beaulieu, 35042 Rennes, France

\*\*Vibration University Technology Centre, Department of Mechanical Engineering, Imperial College London

**Abstract.** The aim of this work is to optimize the parameters of a mechanical system in order to force fold bifurcation points to appear at targeted frequencies. To this end, an original harmonic balance-based optimization procedure is developed. Functions similar to those employed during bifurcation tracking analyses are used to characterize fold bifurcations in the objective function. The proposed approach is illustrated on a Duffing oscillator with cubic nonlinearity.

## Introduction

The ever-increasing demand for lighter structures and more efficient systems requires that the effects of nonlinearities be evaluated at the design stage. One of the most notable characteristic that sets apart nonlinear systems from their linear counterparts is bifurcation phenomena. When a parameter is varied, e.g. the forcing frequency, a bifurcation may occur, resulting in qualitatively different responses such as quasi-periodic or chaotic oscillations. Bifurcation analysis, which aims at predicting and studying such phenomena is a thriving research field. Recent research investigated the computation of the stability of periodic solutions [1] or the parametric analysis of bifurcation points [2, 3, 4]. However, very few studies [5] attempted optimizing the structural parameters of a mechanical system for it to exhibit bifurcations at desired locations and never in the context of nonlinear vibrations. In this work, we develop a computational optimization framework based on the harmonic balance method (HBM), which is widely used in the nonlinear mechanical vibration community. The formulation of the objective function for the optimization strategy relies on a bifurcation measure formulated via a bordering technique and Hill stability analysis and allows one to simultaneously handle multiple bifurcation without two being matched to the same target location.

## Results and discussion

The proposed methodology is applied to a Duffing oscillator with hardening cubic nonlinearity. The initial forced response curve shown in Figure 1 (left) exhibits 8 bifurcations: 6 folds and 2 branch points. Two target locations for the fold bifurcations are defined as  $\Omega_{tar,1} = 2$  and  $\Omega_{tar,2} = 2.5$  rad/s and the optimization is carried out with respect to the damping coefficient. Figure 1 (right) shows the forced response curve computed with the optimized value of the damping coefficient. It is clear that the fold bifurcations located on the primary resonance match with the imposed target locations. One can also note that only two folds are present as the objective function is defined such that the minimum is reached when the number of detected bifurcations match the number of targeted locations [6]. These results are promising and give confidence for application on industrial test cases.




Figure 1: Forced response curve of the Duffing oscillator before (left) and after (right) optimization of the damping coefficient. Target locations  $\Omega_{tar,1} = 2$  and  $\Omega_{tar,2} = 2.5$  rad/s (vertical black dashed lines). Fold bifurcations and branch points represented by red and orange circle markers, respectively.

## References

- [1] Lazarus A., Thomas O. (2010) A harmonic-based method for computing the stability of periodic solutions of dynamical systems. *C. R. Méc.* **338**:510–517
- [2] Detroux T., Renson L., Masset L., Kerschen G. (2015) The harmonic balance method for bifurcation analysis of large-scale nonlinear mechanical systems. *Comput. Methods Appl. Mech. Eng.* **296**:18–38
- [3] Xie L., Baguet S., Prabel B., Dufour R. (2017) Bifurcation tracking by Harmonic Balance Method for performance tuning of nonlinear dynamical systems. *Mech. Syst. Signal Process.* **88**:445–461
- [4] Mélot A., Rigaud E., Perret-Liaudet J. (2022) Bifurcation tracking of geared systems with parameter-dependent internal excitation. *Nonlinear Dyn.* **107**:413–431
- [5] Boullé N., Farrell P. E., Paganini A. (2022) Control of bifurcation structures using shape optimization. *SIAM J. Sci. Comput.* **44**:A57-A76
- [6] Szep G., Dalchau N., Csikasz-Nagy A. (2021) Parameter inference with bifurcation diagrams. Preprint