

SmartM2M; Scenarios for evaluation of oneM2M deployments

Bob Flynn, Luigi Liquori (1, 2, 3), Marie-Agnès Peraldi-Frati (3, 2), Samir Medjiah (4, 5, 6), Thierry Monteil (7, 8)

1 CRISAM - Inria Sophia Antipolis - Méditerranée

2 KAIROS - Logical Time for Formal Embedded System Design

3 UCA - Université Côte d'Azur

4 UT - Université de Toulouse

5 UT3 - Université Toulouse III - Paul Sabatier

6 LAAS-SARA - Équipe Services et Architectures pour Réseaux Avancés

7 IRIT-SEPIA - Système d'exploitation, systèmes répartis, de l'intergiciel à l'architecture

8 INSA Toulouse - Institut National des Sciences Appliquées - Toulouse

Executive summary

The present document proposes three use cases scenario of IoT systems specially selected and defined for representing situations where a modelling and an analysis of the application performances is mandatory. These uses cases are compliant with the oneM2M standard. They will serve to define a data and a behavioural model for an evaluation of the application but also the deployment on a oneM2M implementation. The first use case is currently deployed in a smart campus environment, the second is a generic one that highlight IoT application with event-triggered and time-triggered characteristics. The last one is a traffic light control system with synchronization features. For all of them, we have identified specific temporal and behavioural constraints to be verified and Key Performance Indexes that have to be verified.

Protected by ETSI IPR. Please refer this document as

B. Flynn, L. Liquori, M.A. Peraldi-Frati, S. Medjiah, T. Monteil. ETSI Technical Report TR 103839. SmartM2M; Scenarios for evaluation of oneM2M deployments, 34 pages, 2023.

The full document can be downloaded at

https://www.etsi.org/deliver/etsi_tr/103800_103899/103839/01.01.01_60/tr_103839v010101p.pdf