



**HAL**  
open science

## SmartM2M; Model for oneM2M Performance Evaluation

Samir Medjiah, Thierry Monteil, Luigi Liquori, Marie-Agnès Peraldi-Frati,  
Bob Flynn

► **To cite this version:**

Samir Medjiah, Thierry Monteil, Luigi Liquori, Marie-Agnès Peraldi-Frati, Bob Flynn. SmartM2M; Model for oneM2M Performance Evaluation. ETSI Technical Specification 103840, 2023, pp.29. hal-04229478

**HAL Id: hal-04229478**

**<https://inria.hal.science/hal-04229478>**

Submitted on 13 Dec 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Copyright

# SmartM2M; Model for oneM2M Performance Evaluation

Samir Medjiah (4, 5, 6), Thierry Monteil (7, 8), Luigi Liquori (1, 2, 3), Marie-Agnès Peraldi-Frati (3, 2), Bob Flynn

1 CRISAM - Inria Sophia Antipolis - Méditerranée

2 KAIROS - Logical Time for Formal Embedded System Design

3 UCA - Université Côte d'Azur

4 UT - Université de Toulouse

5 UT3 - Université Toulouse III - Paul Sabatier

6 LAAS-SARA - Équipe Services et Architectures pour Réseaux Avancés

7 IRIT-SEPIA - Système d'exploitation, systèmes répartis, de l'intergiciel à l'architecture

8 INSA Toulouse - Institut National des Sciences Appliquées - Toulouse

---

## Executive summary

The present document proposes a Meta-Model (MM), i.e., a general-purpose modelling of oneM2M applications, written using an UML-like general purpose language that is intended to provide a general pattern for representing IoT applications, using all the entities defined in the oneM2M standard, and offering a pragmatic tool for rapidly prototyping the most important characteristic we want to highlight and measure.

The MM will be instantiated to real examples to express some (but not all) application requirements (e.g., response time, level of scalability, hardware requirement) and resource representation (e.g., smart campus, traffic light system). The MM is composed of three subsets, each one representing a part of operational IoT systems and expressing an abstraction with four layers: the Application Scenario layer, the oneM2M resource layer, the oneM2M service platform layer and the infrastructure layer. Such onion-like view proves useful in the work to conceive, model, inject and decompose into the oneM2M standard almost any IoT application in full detail and make it ready to be explored from the performance evaluation standpoint. Those layers are expressed in three model views called, respectively: 1- oneM2M Application Scenario Descriptor (OASD), 2- oneM2M CSE Performance Descriptor (OCPD), and 3- oneM2M Solution Deployment Descriptor (OSDD).

**Protected by ETSI IPR. Please refer this document as**

S. Medjiah, T. Monteil, L. Liquori, M.A. Peraldi-Frati, B. Flynn. ETSI Technical Specification TS 103840. SmartM2M; Model for oneM2M Performance Evaluation, 29 pages, 2023.

**The full document can be downloaded at**

[https://www.etsi.org/deliver/etsi\\_ts/103800\\_103899/103840/01.01.01\\_60/ts\\_103840v010101p.pdf](https://www.etsi.org/deliver/etsi_ts/103800_103899/103840/01.01.01_60/ts_103840v010101p.pdf)