



**HAL**  
open science

# Towards high-performance linear potential flow BEM solver with low-rank compressions

Matthieu Ancellin, Pierre Marchand, Frédéric Dias

► **To cite this version:**

Matthieu Ancellin, Pierre Marchand, Frédéric Dias. Towards high-performance linear potential flow BEM solver with low-rank compressions. 2023. hal-04233952v1

**HAL Id: hal-04233952**

**<https://inria.hal.science/hal-04233952v1>**

Preprint submitted on 9 Oct 2023 (v1), last revised 13 Feb 2024 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

# Towards high-performance linear potential flow BEM solver with low-rank compressions

Matthieu Ancellin<sup>\*1</sup>, Pierre Marchand<sup>2</sup>, and Frédéric Dias<sup>3</sup>

<sup>1</sup>Eurobios Mews Labs, 191 avenue Aristide Briand, 94230 Cachan, France

<sup>2</sup>POEMS, CNRS, Inria, ENSTA Paris, Institut Polytechnique de Paris, 91120 Palaiseau, France

<sup>3</sup>Université Paris-Saclay, ENS Paris-Saclay, CNRS, Centre Borelli, 91190 Gif-sur-Yvette, France

October 9, 2023

## Abstract

The interaction of water waves with floating bodies can be modelled with linear potential flow theory, numerically solved with the Boundary Element Method (BEM). This method requires the construction of dense matrices and the resolution of the corresponding linear systems. The cost in time and memory of the method grows at least quadratically with the size of the mesh and the resolution of large problems (such as large farms of wave energy converters) can thus be very costly. Approximating some blocks of the matrix by data-sparse matrices can limit this cost. While matrix compression with low-rank blocks has become a standard tool in the larger BEM community, the present paper provides its first application (to our knowledge) to linear potential flows. In this paper, we assess that low-rank blocks can efficiently approximate interaction matrices between distant meshes when using the Green function of linear potential flow. Due to the complexity of this Green function, a theoretical study is difficult and numerical experiments are used to test the approximation method. Typical results on large arrays of floating bodies show that 99% of the accuracy can be reached with 10% of the coefficients of the matrix.

*Keywords*— PDE; BEM; low-rank matrices; water waves; potential flow;

## 1 Introduction

The Boundary Element Method (BEM) is an efficient approach to solve elliptical Partial Differential Equations (PDE) since it only requires the discretization of the boundary of the studied domain. However, the method can still be costly, since its computational cost grows at least quadratically with the number of panels in the mesh of the boundary. This cost comes from the computation of a dense matrix of size  $N \times N$  (where  $N$  is the number of panels in the mesh) and from the resolution of the corresponding linear system.

Linear potential flow problems, solved with the BEM, form the basis of many marine engineering applications, such as the design of Wave Energy Converters (WECs) [21]. To

---

<sup>\*</sup>Corresponding author: [matthieu.ancellin@eurobios.com](mailto:matthieu.ancellin@eurobios.com)

increase the economic viability of the energy extraction, many wave energy projects are considering the developments of “wave farms” composed of many WECs [8]. But the linear potential flow BEM resolution of a complete farm is often too computationally costly to be solved with the currently available tools. To work around this limitation, some simpler approximate models, such as the one of [35] or [22], have been proposed.

Instead, in the present paper, we investigate a more general technique to limit the computational cost of the simulation of large linear potential flow problems, without any particular hypothesis. The main idea is that the interaction between distant panels in the mesh do not need to be computed with the same high accuracy as close panels.

One such technique is the Fast Multipole Method (FMM), which is based on a multipole expansion of the considered Green function and a hierarchical clustering of the physical domain. Then, it approximates far-away interactions grouping panels’ interactions and transferring their influence along the cluster tree. Thus, it provides a fast matrix-vector product in linear complexity without the need to compute far-away interactions. This method has been applied to hydrodynamics by several works in the past, such as [36, 19, 14].

An alternative is to use low-rank approximations with hierarchical matrices ( $\mathcal{H}$ -matrices). Reference works on the topic of  $\mathcal{H}$ -matrices include [12] and [23]. Panels are also grouped in clusters and the interactions between distant clusters are stored in the influence matrix as low-rank blocks. This approach does not directly rely on the explicit expression of the Green function contrary to FMM. It only assumes some properties on the Green function, and low-rank approximations are computed generating a fraction of the coefficients of the approximated blocks. More generally matrix structures involving off-diagonal low-rank block have been shown to be an efficient representation for many physical applications.

Unlike most other BEM problems, the Green function of the linear potential flow problem is complex to express and to compute (see [37] for a discussion of the infinite depth case; the finite depth case is even more difficult). Unlike the multipole expansion required for the FMM (as implemented in e.g. [14]), the low-rank approximation does not require any particular explicit expression of the Green function. It is thus easier to adapt low-rank approximations strategies to the variety of implementations of the Green functions found in the literature.

Let us also briefly mention the *precorrected Fast Fourier Transform* (pFFT) method which can also be used to improve the performance of BEM problems. Applications to linear potential flow include [26, 24].

Despite their popularity, low-rank compression techniques have never (to our knowledge) been applied to linear potential flow problems. The goal of the present paper is to test their performance using a prototype implemented in the open-source linear potential solver *Capytaine* [6], which is derived from *Nemoh* (version 2) [17, 10]. The implementation of the prototype of low-rank compression takes inspiration from the open-source codes of [3] and [29].

In the next section, the theory of the BEM resolution of linear potential flow problem is briefly recalled. An application of low-rank compression is then presented. In Section 3, some numerical results are presented, in order to test the efficiency of the method.

## 2 Theoretical background

### 2.1 Linear potential flow

Let us first briefly recall the theory of the BEM resolution of linear potential flow problems, as done in *Nemoh* and *Capytaine* [17, 10]. A detailed presentation can be found in many textbooks, such as [9, 20, 27, 30, 31].

Assuming an incompressible, non-viscous and irrotational flow, the mass conservation equation can be rewritten as the 3D Laplace equation

$$\nabla^2 \phi(x, t) = 0, \quad \text{in } \mathbb{R}^2 \times [-h, 0] \quad (1)$$

where  $\phi$  is the velocity potential defined as  $u = \nabla\phi$ , the free surface is assumed to be at altitude 0 and  $h$  is the water depth. The partial differential equation (1) is completed with boundary conditions on the free surface, the (flat and horizontal) sea bottom at depth  $h$ , the wet surface of the floating body as well as asymptotically far away from the body. By assuming small wave amplitude and small motion of the body, the boundary conditions are linearized. Then the time dependency can be modeled as an harmonic oscillation

$$\phi(x, t) = \operatorname{Re} \left( \Phi(x) e^{-i\omega t} \right), \quad (2)$$

with a complex-valued scalar field  $\Phi$ .

The partial differential equation and its boundary conditions can be rewritten as a boundary integral problem. Let us denote by  $G(x, \xi)$  the Green function associated to (1) with the free surface, sea bottom and the far-field boundary conditions. In infinite depth, the complex-valued Green function for a wave number  $k$  reads (see also [17, 37]):

$$G(x, \xi) = -\frac{1}{4\pi} \left( \frac{1}{\|x - \xi\|} + k \mathcal{G}(r, z) \right) \quad (3)$$

where

$$r = k\sqrt{(x_1 - \xi_1)^2 + (x_2 - \xi_2)^2}, \quad z = k(x_3 + \xi_3).$$

The first term is the usual Green function for Laplace problems and the second term  $\mathcal{G}$  accounts for the boundary conditions of linear potential flow problems and reads:

$$\mathcal{G}(r, z) = \frac{1}{\sqrt{r^2 + z^2}} + 4\Re \left( \int_0^{\pi/2} e^{\zeta(\theta)} \left( \frac{E_1(\zeta(\theta))}{\pi} + i \right) d\theta \right) + 4i\Re \left( \int_0^{\pi/2} e^{\zeta(\theta)} d\theta \right) \quad (4)$$

with

$$\zeta(\theta) = z + ir \cos \theta$$

for  $r \in [0, +\infty)$ ,  $z \in (-\infty, 0]$  and  $E_1$  is the first exponential integral, defined as

$$E_1(\zeta) = \int_{\zeta}^{\infty} \frac{e^{-t}}{t} dt. \quad (5)$$

In practice, the integrals with respect to  $\theta$  in  $\mathcal{G}$  are too expensive to be integrated numerically for each  $r$  and  $z$ . In Capytaine, as in its parent Nemoh and grand-parent Aquaplan, a tabulation is pre-computed for a given range of values of  $r$  and  $z$ . Then, the Green function is evaluated by interpolating locally in the tabulation with the help of Lagrange polynomials. Outside the range of the tabulation, for large  $r$  and  $z$ , asymptotic approximations are used. For the infinite depth Green function, it reads:

$$\mathcal{G}(r, z) \simeq \frac{-1}{\sqrt{r^2 + z^2}} + 2\sqrt{\frac{2\pi}{r}} e^{z+i(r+\pi/4)} + 2\frac{z}{(r^2 + z^2)^{3/2}}. \quad (6)$$

As we will see later, the use of this kind of approximation when evaluating the Green function may interfere with the low-rank compression. For the sake of brevity, the expression for the gradient of the Green function is not presented here.

With the help of this Green function  $G$ , the potential  $\Phi$  and the normal velocity on the body  $u \cdot n$  can be rewritten as integrals of a source distribution  $\sigma$  on the wet surface of the floating body  $\Gamma$ :

$$\Phi(x) = \iint_{\Gamma} \sigma(\xi) G(x, \xi) dS(\xi), \quad (7)$$

$$(u \cdot n)(x) = \frac{\sigma(x)}{2} + \iint_{\Gamma} \sigma(\xi) (\nabla_1 G(x, \xi) \cdot n) dS(\xi), \quad (8)$$

for all  $x \in \Gamma$ , where  $n$  denotes the unit normal vector to  $\Gamma$  and  $\nabla_1 G$  denote the gradient with respect to the first variable of  $G$ , that is  $x$ . The integrals on the other boundaries of the domain (free surface and sea bottom) are zero by construction of the Green function.

The equations (7) and (8) can be discretized using a collocation method. Considering a mesh of the surface of the floating body  $\Gamma = \cup_{i=1}^n \Gamma_i$ , we define

$$\Phi_i = \Phi(x_i), \quad \sigma_i = \sigma(x_i), \quad u_i = (u \cdot n)(x_i), \quad (9)$$

and

$$S_{ij} = \iint_{\Gamma_j} G(x_i, \xi) dS(\xi), \quad K_{ij} = \frac{\delta_{ij}}{2} + \iint_{\Gamma_j} \nabla_1 G(x_i, \xi) \cdot n_i dS(\xi), \quad (10)$$

where for all  $i$ ,  $x_i$  is the center of the face  $\Gamma_i$ . In practice, the numerical computation of the integral over a panel in  $S$  and  $K$  may be done differently for each term of the Green function and each pair of panels. The singular  $1/||x - \xi||$ -type terms for nearby panels are integrated using exact analytical expressions [17]. For distant panels and for the other terms, the integration is done with quadrature points (by default a single point at the center in Capytaine, four points in the latest version of Nemoh, see also [33] for an extended discussion on this topic). When considering distant panels, we might approximate the matrices as

$$S_{ij} \simeq \text{area}(\Gamma_j) G(x_i, x_j), \quad K_{ij} \simeq \frac{\delta_{ij}}{2} + \text{area}(\Gamma_j) \nabla_1 G(x_i, x_j) \cdot n_i. \quad (11)$$

The matrices  $S$  and  $K$  relate the vectors  $\Phi$ ,  $u$  and  $\sigma$  through the following linear systems approximating (7) and (8):

$$\Phi_i = \sum_j S_{ij} \sigma_j, \quad u_i = \sum_j K_{ij} \sigma_j. \quad (12)$$

A Neumann problem is solved: for a given velocity  $u \cdot n$  of the floating body, we are looking for the reaction of the fluid as a pressure field  $p(x) = i\omega\rho\Phi(x)$ , where  $\rho$  is the density of the fluid. The main tasks of the resolution of the BEM problem are then the computation of the complex-valued matrices  $S$  and  $K$  and the resolution of the linear system associated with  $K$ .

## 2.2 Approximation with low-rank blocks

Each coefficient of the matrices corresponds to the interaction between two panels of the mesh. Then, each block of coefficient in the matrix can be seen as the interaction between two sets of panels (see Figure 1).




Figure 1: Schematic representation of the matrix blocks encoding the interaction between two sets of panels. Blocks B and D might be approximated by low-rank matrices.

For distant sets of panels in the mesh, not all the information contained in the block might be necessary. The main idea of the low-rank approximation is to compute only approximately some blocks and store them in a compressed way.

### 2.2.1 Introduction of low-rank matrices

A *low-rank matrix* of size  $N \times M$  and of rank  $r$  (usually taken small with respect to  $N$  and  $M$ ) is a matrix writable under the form  $AB^T$  where  $A$  and  $B$  are matrices of size respectively  $N \times r$  and  $M \times r$ . In particular, a matrix of rank 1 can be written as  $a \otimes b$  where  $a$  and  $b$  are vectors and  $\otimes$  denotes the tensor product.

The storage cost of a low-rank matrix of rank  $r$  is  $(N + M)r$  instead of  $NM$ . The multiplication of the matrix with a vector  $x$  of size  $M$  can be expressed as  $A(B^T x)$ , that is as  $(N + M)r$  scalar multiplications instead of  $NM$ . Thus, its use in iterative linear solver can be faster.

### 2.2.2 Theoretical study of the approximability by low-rank matrices

Assuming a kernel function  $\mathcal{K}$  has a separable expansion of the form

$$\mathcal{K}(x, y) = \sum_{k=1}^r u_k(x)v_k(y) \quad (13)$$

where for each  $k$   $u_k$  and  $v_k$  are any functions, then for any sets of points  $(x_i)$  and  $(y_j)$ , a matrix  $M_{ij} = \mathcal{K}(x_i, y_j)$  has rank at most  $r$ . To justify that off-diagonal blocks of  $M_{ij}$  can be approximated with low-rank matrices, it is then sufficient to show that the kernel function  $\mathcal{K}(x, y)$  can be approximated by a separable expansion for distant  $x$  and  $y$ .

Instead of (13), the assumption that the kernel is *asymptotically smooth* as in (14) (see [23, Thm. 4.17 and 4.22]) is a sufficient condition for the existence of a separable expansion that approximates  $M$  exponentially in  $r$ . More precisely, if

$$|\partial^\alpha \partial^\beta \mathcal{K}(x, y)| \leq c_{as}(\alpha + \beta) |x - y|^{-|\alpha| - |\beta| - s}, \quad (14)$$

holds for some  $s \in \mathbb{R}$ , with  $c_{as} > 0$ ,  $x \neq y$ ,  $\alpha, \beta \in \mathbb{N}_0^3$ ,  $\alpha + \beta \neq 0$ , and if  $x$  and  $y$  are  $\eta$ -admissible, i.e.

$$\min(\text{diam}(x), \text{diam}(y)) \leq \eta \text{dist}(x, y) \quad (15)$$

then there exists a separable expansion which approximates  $M$  with an error that decreases exponentially with  $r$  for  $\eta$  small enough.

Unfortunately, the complexity of the explicit expression of the Green function for linear potential flow (3) and (4) make it difficult to prove (14). The (“simpler”) 3D Green function of the Helmholtz equation is a priori not asymptotically smooth at high-frequencies [11], nevertheless, in [15], a study of the approximability of the Helmholtz kernel shows that

- for a fixed frequency, the rank for a given wave number does not increase with the number of points by wavelength,
- and for a fixed number of points by wavelength, the rank should not increase more than  $O(k)$  until it reaches the *high-frequency regime* where the block is not low-rank anymore.

Considering only the asymptotic expression (6), we expect a similar behavior because of the oscillating term  $e^{ir} / \sqrt{r}$ , which is also the asymptotic approximation of the 2D Helmholtz kernel [1, Eq. 9.2.3].

### 2.2.3 Numerical methods for compression

The optimal low rank compression of any matrix can be constructed by truncating the Singular Value Decomposition (SVD) of the matrix. However, the computation of the SVD can be costly and other techniques are used in practice. The most common one is the *Adaptive Cross Approximation* (ACA), which allows to build an approximation with only  $(2N - 1)r$  coefficients from the full matrix [13].




Figure 2: Schematics of the Adaptive Cross Approximation of a square matrix: on the left, the lines and columns that are evaluated in the full matrix, on the right, the assembly of a low rank compression of rank 4. Note that the lines and columns in the low-rank compression do not have the same values as the lines and columns with the same color in the full matrix, but are derived from them.

The ACA is a compression technique that builds a low-rank matrix iteratively by picking only one line and one column of the matrix at each iteration (see Figure 2). In the first step, a line and a column of the full matrix are picked arbitrarily (either chosen at random, or fixed arbitrarily to be the top row and leftmost column as in the numerical studies of Section 3) to build an approximation of rank one of the matrix. Then, at iteration  $n + 1$ , a new line and a new column are chosen based on the existing low-rank compression of rank  $n$ . They are added to the low-rank compression to build a low-rank compression of rank  $r = n + 1$ . The norm of the new matrix of rank  $r = n + 1$  is computed and compared to the previous one of rank  $r = n$ . If the change of the norm is lower than a given threshold, the method is supposed to have converged.

Note that not all the coefficients of the full matrix are used. In practice, it means that the Green function needs only to be evaluated on the lines and the columns that are picked up. This is especially useful for linear potential flow problems since the Green function is costly to evaluate.

#### 2.2.4 Structures of matrices with low-rank blocks

Matrices stemming from the discretization of boundary integral equations cannot generally be directly approximated by low-rank matrices, but sub-blocks corresponding to far interactions satisfying (15) can. There exist several data-sparse formats which incorporate low-rank approximations, they all have different theoretical complexities and their implementation can be more or less involved.

The most common data-sparse format is the  $\mathcal{H}$ -matrix format, see [12, 23]. It is based on a hierarchical partition of the physical domain, a *cluster tree*. The matrix can then be represented via a *block tree* corresponding to interactions between nodes in the cluster tree. To build the actual  $\mathcal{H}$ -matrix, the block tree is traversed as follows: starting from the root block,

- if a block satisfies (15), it is compressed as described in Section 2.2.3,
- otherwise, we visit its children, unless their corresponding blocks are too small, in which case they are represented with a dense block.

One advantage of  $\mathcal{H}$ -matrices is that all the usual matrix operations can be performed, for example it can be used for matrix-vector operation and its cost is  $O(N \log(N))$ . But due to its hierarchical nature, the implementation is not straightforward. Other formats exist, for example  $\mathcal{H}^2$ -matrices, HOLDR, and block low-rank (BLR). In the following numerical experiments, we will also use the BLR format. It is very similar to the  $\mathcal{H}$ -matrix format, but without the hierarchical clustering. Only one level of partition is used, in our case each cluster corresponds to one object, and if two objects satisfy (15), their interaction is compressed. The BLR format has been studied in [4, 5].

### 3 Numerical experiments

Given the complexity of the Green function for linear potential flow, the best way to assess the validity of low-rank compression is to experimentally test them in real conditions in an existing BEM solver. For this purpose, the open-source BEM solver Capytaine [6] has been used.

Unless stated otherwise, all experiments have been done by computing the full expression of the Green function (4) and not by using the tabulation and the asymptotic expression (6).

#### 3.1 Two floating hemispheres at varying distance

Let us consider two identical floating spheres of diameter 1 meter, with center at the free surface, separated by a distance  $d$ , and discretized with  $N$  panels each. (Since only the

immersed part of the body is discretized, the mesh is actually two half-spheres at distance  $d$ .) Unless stated otherwise, we consider a mesh resolution of  $N = 400$  panels, a wavelength of  $\lambda = 1$  meter and a water depth  $h \rightarrow \infty$ .

All interaction matrices  $S$  and  $K$  are of size  $2N \times 2N$  and can be decomposed into four blocks: two diagonal blocks  $A$  encoding the interactions of a sphere with itself and two non-diagonal blocks  $B$  encoding the interactions of a sphere with the other. Since the spheres are identical, the blocks are actually identical and the matrices have the following form:

$$M = \begin{pmatrix} A & B \\ B & A \end{pmatrix}.$$

For this numerical experiment, the non-diagonal blocks  $B$  are approximated by low-rank blocks of given rank  $r$ ,  $\tilde{B}_r$ , using either the Singular Value Decomposition (SVD) or the Adaptive Cross Approximation (ACA). The resulting approximated matrix  $\tilde{M}_r$  reads

$$\tilde{M}_r = \begin{pmatrix} A & \tilde{B}_r \\ \tilde{B}_r & A \end{pmatrix}. \quad (16)$$

The relative error of this approximation is evaluated as follow:

$$\text{error}(r) = \frac{\|M - \tilde{M}_r\|}{\|M\|} = \frac{\|B - \tilde{B}_r\|}{\sqrt{\|A\|^2 + \|B\|^2}}$$

where  $\|\cdot\|$  denotes the Frobenius norm.

The same procedure is repeated for several distances  $d$  between the spheres. Each time, the relative error for each rank  $r$  is computed for both matrices  $S$  and  $K$  using both the SVD and the ACA.

### 3.1.1 Influence of the distance and the rank on the error

For the first experiment, we want to study the influence of the rank on the relative Frobenius error as a function of the distance. Results are presented on Figure 3.

Firstly, as expected, the error of the low-rank compression decreases when the distance between the two spheres increases. The error also decreases when the rank of the low-rank compression matrix increases. A rank 0 matrix (that is a zero matrix, that is completely neglecting the interaction between the two spheres) is a poor approximation. But a rank 2 or 3 matrix is sufficient to have an error of less than 1%. For a  $100 \times 100$  block, a compression of rank 2 stores 4% as many coefficients as the full block, meaning that we can reach 99% accuracy with less than 10% of the computation.

The errors on the compression of  $S$  and  $K$  are fairly similar. Both matrices are as difficult as the other to approximate with such a method.

Finally, we can check the efficiency of the ACA with respect of the optimal low-rank compression obtained with the SVD. The compression obtained from the ACA is noisier and slightly less accurate than with the SVD, but still is decreasing with the rank and the distance in the same way as the SVD one.

### 3.1.2 Influence of the distance and the wavelength on the error

For this experiment, we study the influence of the wavelength. The rank of the low-rank compression is now fixed to 2, while several wavelengths between  $10^{-0.5}$  m and  $10^{1.5}$  m are now tested. (Smaller wavelengths would require a finer mesh to be accurately captured.) The Rankine  $1/\|x - \zeta\|$  term of the Green function alone (that is without the frequency-dependent wave term) has also been tested. Results are presented on Figure 4.




Figure 3: Relative Frobenius error between the full matrix and the low-rank compressed matrix as a function of the distance between the two bodies, for two methods of low-rank compression (SVD and ACA) and two BEM matrices (S and K), for varying rank of the low-rank compression.




Figure 4: Relative Frobenius error between the full matrix and the low-rank compressed matrix as a function of the distance between the two bodies, for two methods of low-rank compression (SVD and ACA) and two BEM matrices (S and K), for several wavelengths (colored lines) as well as for the Rankine  $1/||x - \zeta||$  kernel (dashed gray line).

The most efficient compression is obtained when the Green function is only the Rankine  $1/||x - \xi||$  kernel. For the full Green functions with a wave term, the error always decreases more slowly with the distance than for the Rankine term.

As expected from the discussion in Section 2.2.2, the compression is more efficient for long wavelengths, that is low frequencies.

### 3.1.3 Influence of the computation method for the Green function on the error

Now we study the role of the method used to compute the Green function. In the previous experiments, the exact expression of the Green function (4) was used. However, the default method in Capytaine is not to compute this costly exact expression, but instead to use approximations. For close panels, values are interpolated from a pre-computed table of exact expressions (4). For distant panels, the asymptotic expression (6) is used.

When introducing two independent ways to approximate the matrices, there are more ways to compute the error. On Figure 5, the three errors that we consider are summarized in a diagram. Error 1 is the error due to the low-rank compression of the matrix computed with the exact Green function (4), as presented in the previous graphs. Since the goal of this paper is to evaluate the performance of the low-rank compression, we are interested in error 2, that is the error due to the low-rank compression with working with the approximate Green function. However since the end goal would be to use both the low-rank compression and the Green function approximation, we plot also error 3 that incorporates the error due to the approximation of the Green function.

Results of the comparison of the exact and the approximate expressions are presented on Figure 6. Here, the rank of the compression has been fixed to 5 (as the difference is less visible for lower ranks) and the wavelength is fixed to 1 meter.




Figure 5: Schematics of the different kind of errors of the low-rank compression that can be computed when introducing an approximate expression for the Green function. Error 1 and 2 only measures the effect of the low-rank approximation, but error 3 is the one actually relevant to study the accuracy of a BEM solver with low-rank compression.

A jump is clearly visible in the error of the full approximate matrix with respect to the low-rank approximate matrix (error 2). It corresponds to the switch from the tabulated approximation to the asymptotic approximation, occurring near  $d_0 = 20$  m. For distances below  $d_0$ , the approximation of the tabulated Green function shows worse results than the exact Green function. One can suppose that the interpolation in the tabulation introduces spurious “information” in the matrix that is not accurately captured by the low-rank compression. On the contrary, for distance above  $d_0$ , the approximation of the asymptotic Green function shows better results than the exact Green function. Similarly, one can suppose that the asymptotic expression contains less “information” than the exact Green function and is thus easier to compress with a low-rank block.

The errors due to both the compression and the approximation (error 3) are always higher. The use of an approximate formula for the Green function leads to relative errors of the order of  $10^{-3}$ . It means that it is useless to try to reach a low-rank compression error of less than




Figure 6: Relative Frobenius error between the full matrix and the low-rank compressed matrix as a function of the distance between the two bodies, for two methods of low-rank compression (SVD and ACA) and two BEM matrices (S and K), for several methods of computation of the Green function as described in Figure 5.

$10^{-3}$  when working with the approximate Green function, as the approximation will be the bottleneck. The tuning of the Delhommeau's approximation of the Green function as used in Capytaine is out of the scope of this paper.

### 3.1.4 Influence of the resolution on the rank

In all the previous experiments, the rank of the compression has been fixed, and then the error has been computed. In practice, the opposite is done: a tolerance  $\varepsilon$  is set on the error and then the SVD or ACA searches for the lowest rank allowing the compression of the matrix block with such an error. In all test cases from now on, the tolerance  $\varepsilon$  will be fixed instead of the rank.

In this new test case, we test experimentally if the oscillatory kernel has the same behavior as theoretically predicted by [15] for the Helmholtz equation. In particular, the influence of the resolution of the mesh on the rank of the approximation is studied. The distance is fixed to 4 m and the tolerance to  $\varepsilon = 10^{-3}$ . For several wavelengths and mesh resolutions (such that the mesh resolution is sufficient to capture waves of that wavelength), a low-rank approximation is built using the given tolerance.

Results are presented on Figure 7. As already noticed in Section 3.1.2, the lower wavelength cases are harder to compress with low-rank blocks. As predicted in [15], the rank is basically constant when the mesh resolution increase when the approximation is computed with the SVD. The results of the ACA are noisier, but the same tendency can be assumed.




Figure 7: Rank of the best low-rank compression for a given error threshold, as a function of the mesh resolution, for two methods of low-rank compression (SVD and ACA) and two BEM matrices (S and K), for several wavelengths. Points for which the mesh resolution is insufficient for a given wavelength have been removed from the graph.

For a given geometry and a given wavelength, the rank of the approximation for a given error can be assumed to be constant with the resolution of the mesh. Consequently, the cost

of the low-rank blocks only grows like  $O(N)$  with the number of panels  $N$ . In other words, providing a resolution that is too high for the desired accuracy will not be as much a burden on the performance as it would be for a full matrix.

### 3.2 Array of random floating spheres

In this section, we introduce a new experiment that is closer to a real application. 40 hemispheres of random radius (between 0.5 m and 1 m) are positioned randomly on the free surface in a square of size  $30\text{ m} \times 30\text{ m}$ . (When collision between two spheres is detected, the random positioning algorithm is restarted until no collision is found.) Depending on the size of the spheres, the full problem is composed of around 5000 panels, which is large enough to be worth approximating with low-rank blocks while being small enough to be also solvable with a full matrix within a reasonable amount of RAM (circa 750 MB with Capytaine’s default settings).

The accuracy of the method is not computed on the matrix itself any more, but rather on a physical output of the solver. For this purpose, the diffraction force  $F_{d,i}$  on body  $i$  with respect to the *Heave* degree of freedom (that is the vertical component of the diffraction force on the body) has been chosen. The reference solution is computed using full matrices, and the relative error on the diffraction force is computed as

$$\text{error} = \frac{\|\widetilde{F}_d - F_d\|}{\|F_d\|}$$

where  $\widetilde{F}_d$  is the diffraction force vector computed with the low-rank block compression,  $F_d$  is the reference diffraction force vector and  $\|\cdot\|$  is the infinite norm.

The range of wavelengths of interest is chosen to be between 6 m and 30 m. Lower wavelengths were not studied in order to avoid irregular frequencies appearing around wavelengths of 2 m.




Figure 8: On the left: example of mesh with 40 spheres of random radii and positioned at random. On the right: example of diffraction force on four of the spheres as a function of the wavelength.

The interaction matrices can be seen as  $40\text{ blocks} \times 40\text{ blocks}$  matrices where each block is the interaction between two of the hemispheres in the domain. A block in this matrix will be computed with a low-rank approximation if the admissibility criterion (15) is satisfied, where  $\eta$  has here been set to  $\eta = 1$ . See Figure 9 for a graphical representation of such a matrix. When computing the low-rank approximation with the ACA, a tolerance on the error has to be set as stopping criterion for the iterative process. A higher tolerance leads to sparser matrices with higher errors and a lower tolerance leads to denser matrices with lower errors. Three different relative error tolerance have been tested in this experiment:  $10^{-1}$ ,  $3 \times 10^{-3}$  and  $10^{-4}$ .




Figure 9: Structure of the resulting interaction matrix where red blocks are fully stored in memory and green are low-rank blocks with a rank corresponding to the number displayed in the block.

Beside the relative error on the diffraction force, the main output of interest is the density of the matrix, that is the ratio of the number of coefficients stored in the matrix on the size of the matrix. The density of the reference method with a full matrix is 1. The density is strongly correlated with the gain in speed and memory of using the compressed matrix.

For each wavelength and each ACA tolerance, the simulation has been repeated five times with different random generation of the array of floating spheres. The main result are presented on Figure 10. As expected, a lower tolerance on the ACA leads to a lower error and to a denser matrix. By choosing a tolerance of  $3 \times 10^{-3}$ , we observe that the error is below 1%, while the density of the matrix is around 10%. In other words, the solver reached 99% accuracy with only 10% of the coefficients.

The effect of the wavelength is not as clear. For the lower tolerance  $10^{-4}$ , the higher frequencies (lower wavelength) seems to leads to denser matrices, which is consistent with the discussion of Section 3.1.2. For higher tolerance, the wavelength does not have a clear effect on the result.

Note that with the Block Low-Rank matrix structure (as illustrated in Figure 9), the complexity of the method is still  $O(N_b^2)$ , where  $N_b$  is the number of bodies. The complexity could be reduced to  $O(N_b \log N_b)$  by using a more complex block structure such as the  $\mathcal{H}$ -matrix structure described in Section 2.2.4. The optimization of the matrix block structure is out of the scope of this paper.

## 4 Discussion and conclusion

This paper is about the suitability of the low-rank approximation for linear potential flow. Due to the complexity of the expression of the Green function, the theoretical sufficient




Figure 10: For 60 simulations, density of the matrix with low-rank blocks versus relative error on the diffraction forces caused by the approximation of the matrix.

condition for compressibility with low-rank blocks could not be proved. We thus relied on numerical experiments to test the efficiency of the low-rank approximation.

In the numerical examples presented in Section 3, the clusters of panels used to define the blocks of the matrix correspond to disjoint bodies. This is the most natural way to split the mesh when studying problems such as farms of wave energy converters. But each cluster matching one and only one disjoint body is not a requirement of the method. For instance, the mesh a single large floating body can be split into clusters of panels and the interaction between these distant clusters can be approximated with low-rank blocks. An illustration is given on Figure 11 in which the mesh of a realistic ship (provided by the authors of [18]) is split in a hierarchical cluster of panels which is used to build a  $\mathcal{H}$ -matrix. In this illustrative example of possible further applications, the matrices are approximated with a density of  $\sim 21\%$  while the relative error on the heave component of the diffraction force is around 2%.

Only infinite depth results have been presented in this paper. Early tests with the finite depth Green function show similar efficiency for the low-rank approximation. However, the influence of the computation of the Green function as presented in Section 3.1.3 would need to be reconsidered with the additional approximation done to compute the finite depth Green function with Delhommeau's method [17].

The prototype implementation in Capytaine is available to all users of the code and can be used e.g. to solve very large problems that would not otherwise fit in RAM. However, for most small to middle-sized problems, its usage is not recommended, as it is often less performant than the default full-matrix method. This lower performance of the more advanced method can be explained by two main factors:

Firstly, the handling of matrices with low-rank blocks requires more bookkeeping than plain full matrices. This is critical in the current implementation of Capytaine, where this bookkeeping is implemented in Python which is a relatively slow programming language. This is why no time benchmark is presented in this paper. A solution would be to use another library using a low-level language as a dependency for dealing with the compression, and additionally to use  $\mathcal{H}$ -matrices which will also offer better performances in terms of complexity




Figure 11: Above: Top and side view of the ship hull mesh where panels colors correspond to the 60 clusters of panels composing the mesh. Below: Resulting  $\mathcal{H}$ -matrix for the  $S$  matrix with a density of  $\sim 21\%$  where red blocks are fully stored in memory and green blocks are low-rank blocks with a rank corresponding to the number displayed in the block.

thanks to their hierarchical nature. Examples of such libraries are Hlib<sup>1</sup>, HiCMA<sup>2</sup>, hmat-oss<sup>3</sup>, and Htool<sup>4</sup>. The latter is developed by one of the authors.

Secondly, the low-rank blocks compression is interfering with other optimizations used by Capytaine. As an example, the evaluation of the Green function for  $S$  and the evaluation of its derivative for  $K$  share a lot of common code and the two matrices are built together by Capytaine. Using matrix compressions would require coupling the compression of both matrices, which has never been done to our knowledge.

Another example is the choice of the linear solver: the low-rank block prototype presented here uses a GMRES solver. The default method in Capytaine is to compute the LU decomposition once and apply it for all the right-hand sides associated with the matrix. When GMRES is used with the block low-rank approximation, it is currently restarting the resolution of the linear system from scratch for each right-hand side. One possibility to overcome this issue is to factorize the block low-rank matrix, which can be done efficiently depending on the maximal rank. This approach has been studied recently in the context of finite element matrices [4, 5]. Another possibility is to use the more involved  $\mathcal{H}$ -matrix format that can also perform all matrix operations contrary to other data-sparse formats, and in particular factorisations, while having even better theoretical complexities. Thus, to solve problems with multiple right-hand sides, a solution to avoid iterative solvers would be to use the approximate LU factorisation associated with  $\mathcal{H}$ -matrices, see [23, Section 7.6] or [12, Section 2.7]. An alternative solution would be to use a more efficient iterative solver, and in the case of multiple right-hand sides, block iterative methods have been investigated (see [34] and [32, Section 6.12]). Instead of solving each right-hand side separately, these methods solve them all at the same time using matrix-matrix operations, which is more efficient than several matrix-vector operations, and it allows building a larger search space. These methods are also usually coupled with recycling techniques, to reuse some previous information built before a restart or in a previous solve, see [28, 2, 25]. Finally, the performance of the GMRES could be improved by the use of a good preconditionner [16].

Beyond low-rank compressions, other data-sparse matrices can be used to reduce the computational cost of BEM solver. For instance, the local symmetries of the mesh lead to Toeplitz-type matrix structures [7]. One can imagine in the future coupling these optimizations to reduce even further the computational cost of BEM solvers for large problems.

## References

- [1] ABRAMOWITZ, M., AND STEGUN, I. A. *Handbook of Mathematical Functions with Formulas, Graphs, and Mathematical Tables*. National Bureau of Standards Applied Mathematics Series 55. Tenth Printing. 1972.
- [2] AGULLO, E., GIRAUD, L., AND JING, Y.-F. Block GMRES method with inexact breakdowns and deflated restarting. *SIAM Journal on Matrix Analysis and Applications* 35, 4 (jan 2014), 1625–1651.
- [3] ALOUGES, F., AND AUSSAL, M. FEM and BEM simulations with the gypsilab framework. 297–318.
- [4] AMESTOY, P., ASHCRAFT, C., BOITEAU, O., BUTTARI, A., L'EXCELLENT, J.-Y., AND WEISBECKER, C. Improving multifrontal methods by means of block low-rank representations. *SIAM Journal on Scientific Computing* 37, 3 (jan 2015), A1451–A1474.

---

<sup>1</sup><http://hlib.org>

<sup>2</sup><https://ecrc.github.io/hicma/>

<sup>3</sup><https://github.com/jeromeroberth/hmat-oss>

<sup>4</sup><https://htool-documentation.readthedocs.io>

- [5] AMESTOY, P., BUTTARI, A., L'EXCELLENT, J.-Y., AND MARY, T. On the complexity of the block low-rank multifrontal factorization. *SIAM Journal on Scientific Computing* 39, 4 (jan 2017), A1710–A1740.
- [6] ANCELLIN, M., AND DIAS, F. Capytaine: a Python-based linear potential flow solver. 1341.
- [7] ANCELLIN, M., AND DIAS, F. Using the floating body symmetries to speed up the numerical computation of hydrodynamics coefficients with Nemoh. In *ASME 2018 37th International Conference on Ocean, Offshore and Arctic Engineering (OMAE2018)*, p. V009T13A031.
- [8] BABARIT, A. On the park effect in arrays of oscillating wave energy converters. *Renewable Energy* 58 (oct 2013), 68–78.
- [9] BABARIT, A. *L'énergie des vagues: Ressource, technologies et performance*. ISTE Group, 2018.
- [10] BABARIT, A., AND DELHOMMEAU, G. Theoretical and numerical aspects of the open source bem solver NEMOH. In *11th European Wave and Tidal Energy Conference (EWTEC2015)*, Proceedings of the 11th European Wave and Tidal Energy Conference.
- [11] BANJAI, L., AND HACKBUSCH, W. Hierarchical matrix techniques for low- and high-frequency helmholtz problems. *IMA Journal of Numerical Analysis* 28, 1 (mar 2007), 46–79.
- [12] BEBENDORF, M. *Hierarchical matrices*. Springer.
- [13] BEBENDORF, M., AND RJASANOW, S. Adaptive low-rank approximation of collocation matrices. *Computing* 70 (2003), 1–24.
- [14] BORGARINO, B., BABARIT, A., AND FERRANT, P. An implementation of the fast multipole algorithm for wave interaction problems on sparse arrays of floating bodies. *Journal of Engineering Mathematics* 77, 1 (jun 2012), 51–68.
- [15] CHAILLAT, S., DESIDERIO, L., AND CIARLET, P. Theory and implementation of h-matrix based iterative and direct solvers for helmholtz and elastodynamic oscillatory kernels. *Journal of Computational physics* 351 (2017), 165–186.
- [16] CIARAMELLA, G., GAMBARINI, M., AND MIGLIO, E. A preconditioner for free-surface hydrodynamics bem. Tech. Rep. 84/2022, MOX, Dipartimento di Matematica, Politecnico di Milano, 2022.
- [17] DELHOMMEAU, G. *Problèmes de diffraction-radiation et de résistance des vagues : étude théorique et résolution numérique par la méthode des singularités*. PhD thesis.
- [18] DONATINI, L., HERDAYANDITYA, I., VERAO FERNANDEZ, G., PRIBADI, A. B. K., LATAIRE, E., AND DELEFORTRIE, G. Implementation of forward speed effects on an open source seakeeping solver. In *6th MASHCON: International Conference on Ship Manoeuvring in Shallow and Confined Water (2022)*, Knowledge Centre for Manoeuvring in Shallow and Confined Water, pp. 20–33.
- [19] FOCESATO, C., AND DIAS, F. A fast method for nonlinear three-dimensional free-surface waves. 2715–2735.
- [20] FOLLEY, M. *Numerical modelling of wave energy converters: state-of-the-art techniques for single devices and arrays*. Academic Press, 2016.
- [21] FOLLEY, M., BABARIT, A., CHILD, B., FOREHAND, D., O'BOYLE, L., SILVERTHORNE, K., SPINNEKEN, J., STRATIGAKI, V., AND TROCH, P. A review of numerical modelling of wave energy converter arrays. In *Volume 7: Ocean Space Utilization; Ocean Renewable Energy*, ASME.
- [22] FÀBREGAS FLAVIÀ, F., MCNATT, C., RONGÈRE, F., BABARIT, A., AND CLÉMENT, A. A numerical tool for the frequency domain simulation of large arrays of identical floating bodies in waves. 299–311.
- [23] HACKBUSCH, W. *Hierarchical matrices: algorithms and analysis*. Springer.

- [24] JIANG, S.-C., TENG, B., GOU, Y., AND NING, D.-Z. A precorrected-fft higher-order boundary element method for wave-body problems. *Engineering Analysis with Boundary Elements* 36, 3 (2012), 404–415.
- [25] JOLIVET, P., AND TOURNIER, P.-H. Block iterative methods and recycling for improved scalability of linear solvers. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis* (2016), SC '16, IEEE Press.
- [26] KORSMEYER, T., PHILLIPS, J., AND WHITE, J. A precorrection-FFT algorithm for accelerating surface wave problems.
- [27] MOLIN, B. *Hydrodynamique des structures offshore*. Editions Technip, 2002.
- [28] MORGAN, R. B. Restarted block-GMRES with deflation of eigenvalues. *Applied Numerical Mathematics* 54, 2 (jul 2005), 222–236.
- [29] NEUMANN, M. Hierarchical matrices, an implementation in Python. Master’s thesis.
- [30] NEWMAN, J. N. *Marine hydrodynamics*. The MIT press, 2018.
- [31] NING, D., AND DING, B. *Modelling and Optimization of Wave Energy Converters*. CRC Press, 2022.
- [32] SAAD, Y. *Iterative Methods for Sparse Linear Systems*. Society for Industrial and Applied Mathematics, jan 2003.
- [33] SAVERIN, J. R., AND GRÜTER, L. Quadrature schemes for the integration of the free-surface green’s function within the open-source boundary element method library bemuse. In *International Conference on Offshore Mechanics and Arctic Engineering* (2022), vol. 85925, American Society of Mechanical Engineers, p. V007T08A057.
- [34] SIMONCINI, V., AND GALLOPOULOS, E. Convergence properties of block GMRES and matrix polynomials. *Linear Algebra and its Applications* 247 (nov 1996), 97–119.
- [35] SINGH, J., AND BABARIT, A. A fast approach coupling boundary element method and plane wave approximation for wave interaction analysis in sparse arrays of wave energy converters. *Ocean engineering* 85 (2014), 12–20.
- [36] UTSUNOMIYA, T., WATANABE, E., ET AL. Accelerated higher order boundary element method for wave diffraction/radiation problems and its applications. In *The Twelfth International Offshore and Polar Engineering Conference*, International Society of Offshore and Polar Engineers.
- [37] XIE, C., CHOI, Y., RONGÈRE, F., CLÉMENT, A. H., DELHOMMEAU, G., AND BABARIT, A. Comparison of existing methods for the calculation of the infinite water depth free-surface green function for the wave-structure interaction problem. *Applied Ocean Research* 81 (2018), 150–163.