



HAL
open science

Interpretable reduced order modeling using neural autoencoders

Emmanuel Menier, Sebastian Kaltenbach, Mouadh Yagoubi, Marc Schoenauer, Koumoutsakos Petros

► **To cite this version:**

Emmanuel Menier, Sebastian Kaltenbach, Mouadh Yagoubi, Marc Schoenauer, Koumoutsakos Petros. Interpretable reduced order modeling using neural autoencoders. MORTech 2023 – 6th International Workshop on Model Reduction Techniques, Nov 2023, Gif-sur Yvette, France. hal-04296372

HAL Id: hal-04296372

<https://inria.hal.science/hal-04296372v1>

Submitted on 20 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Interpretable Learning of Effective Dynamics for multiscale systems

E. Menier, S. Kaltenbach, M. Yagoubi, M. Schoenauer, P. Koumoutsakos


MORTech 2023 – 6th International Workshop on Model Reduction Techniques

Dimensionality Reduction

Neural AutoEncoders can be used to identify low dimensional representation spaces for dynamical systems. On the left, the 1D Fitz-Hugh Nagomo model is reduced from a representation on a 100 points spatial mesh to two latent coordinates (z_1 and z_2).

Unfortunately, the dynamics of this low dimensional representation are a-priori unknown :

$$\frac{dz}{dt} = ?$$



Form of the Dynamics

$$\frac{dz}{dt} = \mathbf{A}z + \mathbf{B}_\infty \int_0^t e^{\mathbf{D}_\infty s} \mathbf{C}_\infty \mathbf{z}_s ds + \mathbf{F}(t)$$

Results from dynamical systems theory, mainly the theory of the Koopman Operator (see [1]) can be used to derive an ansatz for the reduced dynamics.

The proposed form of the dynamics requires the learning of two linear operators (\mathbf{A} and $\mathbf{\Lambda}$) and two neural networks (Ψ_1 and Ψ_2).

$$\frac{dz}{dt} = \mathbf{A}_\theta z + \Psi_1 \left[\int_{-\infty}^t e^{\mathbf{\Lambda}_\theta(t-s)} \Psi_2(\mathbf{z}_s) ds \right]$$


Markovian Part

Memory Effects

Application : Cylinder Flow

The 2D cylinder flow can also be reduced to a two dimensional representation. After training the proposed dynamical model, a model is obtained, able to forecast the state of the system efficiently and accurately for multiple periods of the system.

It is interesting to note that the dynamics are almost completely linear, yielding a highly interpretable model.



Application : Kuramoto-Sivashinsky

The method is able to learn chaotic dynamics as well. In these cases, the non-linear memory effects become critical to the model.

