

Keynote: Large-scale trustworthy distributed collaborative systems - challenges and prospective solutions

Claudia-Lavinia Ignat

► To cite this version:

Claudia-Lavinia Ignat. Keynote: Large-scale trustworthy distributed collaborative systems - challenges and prospective solutions. INFORSID (INFormatique des ORganisations et Systèmes d'Information et de Décision) 2024, May 2024, Nancy, France. hal-04595294

HAL Id: hal-04595294 https://inria.hal.science/hal-04595294v1

Submitted on 31 May 2024 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License




Large-scale trustworthy distributed collaborative systems: challenges and prospective solutions

Claudia-Lavinia Ignat COAST - Centre Inria de l'Université de Lorraine

Inforsid 2024 May 30, 2024 claudia.ignat@inria.fr

Douglas Engelbart: Augmenting Human Intellect



The Mother of all Demos, December 9, 1968



NLS: Online System https://archive.org/details/dougengelbartarchives



Groupware, early 1990s

« Computer-based systems that support groups of people engaged in a common task (or goal) and that provide an interface to a shared environment. » [EGR91]

 Lotus Notes (HCL Notes today), one of the first commercial groupware allowing remote group collaboration



Groupware Time Space Matrix [388]

same time different time synchronous asynchronous Face to face interactions Continuous task decision rooms, single display large public display, team co-located groupware, shared table, wall rooms, shift work groupware, displays, roomware, ... project management, ... Time/Space Groupware **Matrix** remote **Communication + Remote interactions** coordination video conferencing, instance email, bulletin boards, blogs, messaging, chats/MUDs/virtual asynchronous conferencing, worlds, shared screens, multigroup calendars, workflow, user editors version control, wikis



same place

different place

Collaborative Systems: from users to community of users



	VIEW 1 Outline Title 1. Item 1 is readable and writable. 1.1. Item 1.1 is also readable and writable. *. Shared item is readable and writable. *.*. Shared item is read-only.	<u></u>
SHAF	RED R D B	

"Isn't it chaotic to all edit in the same document, even the same paragraph, at the same time?" "Why would a group ever want to edit in the same line of text at the same time?" [EGR91]

GROVE, 1989

From users to community of users: new practices



Main page Contents Current events Random article About Wikipedia Contact us Donate Contribute Help Learn to edit Community portal Recent changes Upload file Tools What links here **Related changes** 🔝 Atom Special pages Page information Wikidata item Languages

Article Talk

View logs for this page (view filter log)

Read Edit View history Search Wikipedia

Q PHelp

Log in Talk Contributions Create account Log in

WIKIPEDIA The Free Encyclopedia

Ô

✓ Filter revisions				
xternal tools: Find	addition/removal (Alternate	• Find edits by user • Page statistics • Pageviews • Fix dead links		
For any version listed below, click on its date to view it. For more help, see Help:Page history and Help:Edit summary. (cur) = difference from current version, (prev) = difference from preceding version, m = minor edit, → = section edit, ← = automatic edit summary newest I oldest) View (newer 20 I older 20) (20 I 50 I 100 I 250 I 500)				
Compare selecte	ed revisions			
(cur I prev)	22:56, 6 January 2021	Sleyece (talk I contribs) (83,551 bytes) (+96) (Be Concise) (undo)		
(cur I prev) 💿	22:53, 6 January 2021	Thanoscar21 (talk I contribs) m (83,455 bytes) (-39) (Rollback edit(s) by 49.195.0.222 (talk): per WP:NPOV (RW 16)) (undo) (Tag: Rollback)		
● (cur l prev) 〇	22:52, 6 January 2021	49.195.0.222 (talk) (83,494 bytes) (+39) (undo) (Tag: Reverted)		
∙ (cur l prev) ◯	22:52, 6 January 2021	Sleyece (talk I contribs) m (83,455 bytes) (-3) (Grammar) (undo)		
∙ (cur l prev) ◯	22:52, 6 January 2021	2605:a601:ada1:2a00:ad83:9ec8:20bc:44c5 (talk) (83,458 bytes) (+4) (→Major events: Fixed punctuation) (undo) (Tags: Mobile edit, Mobile web edit)		
(cur I prev) O	22:51, 6 January 2021	Sleyece (talk contribs) (83,454 bytes) (+423) (Bot Reverted too Much) (undo)		
(cur l prev) 〇 edit, Mobile web e	1	2605:a601:ada1:2a00:ad83:9ec8:20bc:44c5 (talk) (83,031 bytes) (+15) (→Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump recorded message) (undo) (Tags: Major events: Cleaned up wording on Trump r		
edit, Mobile web e	1	2605:a601:ada1:2a00:ad83:9ec8:20bc:44c5 (talk) (83,016 bytes) (-1) (→Major events: Replaced one other instance of "rioters" with "people") (undo) (Tags:		
● (cur I prev) 〇	22:45, 6 January 2021	2605:a601:ada1:2a00:ad83:9ec8:20bc:44c5 (talk) (83,017 bytes) (-8) (→Major events: Typo) (undo) (Tags: Mobile edit, Mobile web edit)		
(cur I prev) O	22:45, 6 January 2021	2600:1700:2b9c:5010:a145:6992:7d5a:8714 (talk) (83,025 bytes) (+81) (→Major events) (undo)		
● (cur I prev) 〇	22:44, 6 January 2021	2605:a601:ada1:2a00:ad83:9ec8:20bc:44c5 (talk) (82,944 bytes) (+52) (→Major events: Rephrased "rioters") (undo) (Tags: Mobile edit, Mobile web edit)		
(cur I prev) O	22:39, 6 January 2021	Jeswinj (talk I contribs) (82,892 bytes) (-351) (undo) (Tag: Visual edit)		
(cur I prev) 〇 <i>Report False Pc</i>		ClueBot NG (talk I contribs) <u>m</u> (83,243 bytes) (-47) (Reverting possible vandalism by 2603:9001:4903:D811:9052:EFE:155C:2134 to version by 81.167.188		
∙ (cur l prev) ◯	22:39, 6 January 2021	2603:9001:4903:d811:9052:efe:155c:2134 (talk) (83,290 bytes) (+47) (undo) (Tags: Mobile edit, Mobile web edit, Reverted)		
o (cur I prev) O	22:35, 6 January 2021	81.167.188.42 (talk) (83,243 bytes) (+40) (undo)		
(cur I prev) O	22:34, 6 January 2021	72.217.56.18 (talk) (83,203 bytes) (-58) (person shot has not been reported dead as of yet!) (undo)		
(cur I prev) O	22:33, 6 January 2021	2600:1700:1c60:41d0:e5a9:3248:c03e:eb02 (talk) (83,261 bytes) (+73) (Adding the President's reaction to the event.) (undo) (Tag: extraneous markup)		
(cur I prev) O	22:31, 6 January 2021	2603:8000:8e42:cb00:55ec:35dc:94e4:c9be (talk) (83,188 bytes) (+1) (undo) (Tag: Possible vandalism)		
(cur prev) O	22:29, 6 January 2021	92.21.72.53 (talk) (83,187 bytes) (+40) (Adding info) (undo) (Tags: Mobile edit, Mobile web edit, Visual edit, Possible vandalism)		
,				

Compare selected revisions

(newest | oldest) View (newer 20 | older 20) (20 | 50 | 100 | 250 | 500)

United States Capitol: Revision history

Inría

From users to community of users: new practices




Example: Intergovernmental Panel Climate Change (IPCC) assessment report editing

- Expert contributions: hundreds of scientists from different countries
- Review stages by experts and governments
- Approval sessions: government delegates and lead authors
- Editing teams: review editors




Limitations of Central Authority Systems




RIVACY

Vision: Peer-to-Peer Collaborative Systems






Collaboration Modes – Concurrent Changes





Collaboration Modes – Offline Work



Inría

Collaboration Modes – Ad-hoc Collaboration



(nría_

Research issues

How to **maintain consistency of different copies** in the face of concurrent modifications?

2 How to secure collaboration data?

3 How to make a collaboration **trustworthy**?

nain

Research issues

How to **maintain consistency of different copies** in the face of concurrent modifications?

2 How to secure collaboration data?

3 How to make a collaboration **trustworthy**?


naío

CAP Theorem [B00]

- Properties of shared-data systems
 - Data consistency
 - System availability
 - Tolerance to network partition
- Only two out of three properties can be achieved at a given time
- Relax consistency for availability in the presence of network partitions



Operational transformation (OT) [EG89]



T(ins(p1,c1), ins(p2,c2)) :if (p1<p2) return ins(p1,c1) else return ins(p1+1,c1) endif


- Transforms non commuting operations to make them commute
- Genericity
 - Time complexity Average: O(H.c) ⊢ Worst case: O(H²) c
 - H: #ops c: avg. #conc. ops
- Difficult to write correct transformation functions
- State vectors used for detecting concurrency ⇒ scalability limitations
- Not very suitable for large scale peer-to-peer collaboration

Conflict-free Replicated Data Types (CRDT)[SPBZ11]

- Design operations to be commutative by construction
- Abstract data types
 - Designed to be replicated at multiple sites
 - Any replica can be modified without coordination
 - State convergence is guaranteed
- State-based and operation-based approaches



Conflict-free Replicated Data Types (CRDT) State-based Replication



- Algorithm
 - Periodically, replica at p_i sends its current state to p_i
 - Replica p_j merges received state into its local state by executing m
- After receiving all updates (irrespective of order), each replica will have same state




Conflict-free Replicated Data Types (CRDT) State-based Replication

- Merge operator:
 - Commutative: x y = y x
 - Associative: $(x \bullet y) \bullet z = x \bullet (y \bullet z)$
 - Idempotent : $x \bullet x = x$
- A semi-lattice is a Partial order ≤ set S with a least upper bound (LUB), denoted ⊔
 - m = x ⊔ y is a LUB of { x, y } under ≤ if and only if
 ∀ m', x ≤ m' ∧ y ≤ m' ⇒ x ≤ m ∧ y ≤ m ∧ m ≤ m'
 - It follows that ⊔ is commutative, associative and idempotent



Conflict-free Replicated Data Types (CRDT) Operation-based Replication



- An update split into (t,u): t is a side-effect-free prepare-update method and u is an effect-update method
- Algorithm

•Updates delivered to all replicas

•Causally-ordered broadcast, every message delivered to every node exactly once w.r.t. happen-before order

• Commutativity holds for concurrent updates



Conflict-free Replicated Data Types (CRDT) Operation vs. State-based Replication

- Both approaches are equivalent
 - A state-based object can emulate an operation-based object, and vice-versa
- Operation-based:
 - More efficient since you only ship small updates
 - But require exactly once causally-ordered broadcast
- State-based:
 - Only require reliable broadcast
 - Communication overhead of shipping the whole state
- Delta State-based [ASB18] :
 - Small messages
 - Dissemination over unreliable communication channels

Consistency Maintenance Conflict-free Replicated Data Types (CRDT)

- Register
 - Last-Writer Wins
 - Multi-Value
- Set
 - Grow-Only
 - 2-Phase
 - Observed-Remove
 - Observed-Update-Remove





Conflict-free Replicated Data Types (CRDT) (Text) Sequence [PMSL09][WUM09]

- Document = linear sequence of elements
 Each element has a unique identifier
 - •Identifier constant for the lifetime of the document
 - Dense total order of identifiers consistent with element order:
 → id_x, id_y: id_x < id_y ⇒ ∃ id_z: id_x < id_z < id_y
- •Different approaches for generating identifiers:





Conflict-free Replicated Data Types (CRDT) Logoot [WUM09]

Logoot identifiers: $\langle p_1, s_1, h_1 \rangle \langle p_2, s_2, h_2 \rangle \cdots \langle p_k, s_k, h_k \rangle$ <1,2,1> p_i integer С <1.2.2> 0 s_i site identifier <2,1,2> n h_i logical clock at site s_i <3,1,3> С <3,1,3><8,4,5> u <3,2,5> r ins(<3,2,5><13,1,7>, r) <4,1,7> е <4,1,7><9,2,6> n <7,2,8> С <9,1,7> у <10,2,8> (12,3,1> С ins(<12,3,1><7,8,2><13,3,6><7,2,9>, o) (12,3,1><6,5,1> 0 <12.3.1><7.8.2> n <12,3,1><7,8,2><12,3,5> t <12,3,1><7,8,2><13,3,6> r 1 <12,3,1><7,8,2><14,3,7>

Innía


Time complexity
 Time complexity
 Average: O(k log(n))
 Worst case: O(H*log(H))
 H: #ops

n: doc. size (non deleted chars.) k: avg. size of Logoot identifier

- No need for concurrency detection
- Identifiers storage cost
- New design for each data type
- Suitable for large-scale collaboration

Conflict-free Replicated Data Types (CRDT) LogootSplit [AM0I13]


Aggregation of elements to limit metadata



(nría_

Conflict-free Replicated Data Types (CRDT) LogootSplit - Impact

- Implemented in MUTE P2P collaborative editor [NEOIC17] [github.com/coast-team/mute, OpenPaaS::NG, ADT MUTE]
- Better performances than GoogleDocs [DI16a]




• Related approach on wikis transferred to XWiki [1A021]



User Study: The effect of delay on users [10FSC15]

- Delays in seeing modifications of other users
 - Network delay
 - Time complexity of consistency maintenance algorithms
 - Types of architecture



Thin client architecture



Thick client architecture


How does delay influence group performance?

Experiment design

- 20 groups of 4 students
 - Perform several collaborative editing tasks
 - A proofreading task
 - A sorting task
 - A note taking task
 - Use the provided collaborative editor (Etherpad) + chat
 - Each group experienced a certain delay (0, 4, 6, 8, 10 s)
- Registration of user keyboard inputs
- Video recording of user activities on desktop




Note-taking [IOFSC15]



Innía


Delay reduces Group Performance



Delay increases error rate and redundancy



Delay reduces Group Performance



Delay decreases proportion of keywords



Design implications

- Reduce the delay by the choice of the architecture and synchronisation algorithms
- Make users aware of existing delays such that they can compensate for the delay by coordination strategies
- Analyse real collaboration traces to understand collaboration patterns and behavior [NI18]



Perspectives – Replication for complex data

- Composition of replication mechanisms for simple data
 - Maintaining global invariants (e.g. integrity constraints) over CRDTs for replicated relational databases [IEB24]
 - Replication mechanisms for P2P cloud storage [AII23]
 - Automated approach to combine CRDTs meeting expressed constraints
- Validate with users the defined merge semantics

naío

Research issues

How to maintain consistency of different copies in the face of concurrent modifications?

2 How to secure collaboration data?

3 How to make a collaboration trustworthy?

nain


Security in peer-to-peer collaboration



- Client-side E2E encryption
- Group key management
- Access control without central authority

Encryption for mutable data by means of CRDTs


CRDTs suitable for client-side E2E encryption





Group key management for large and dynamic groups

- TreeKEM Message Layer Security (MLS) RFC 9420
 - Operations: Add, Remove and Update



Updating member B

Adding member E

С

В

Modified/updated keys

Keys on co-path, used to encrypt new keys to subgroups

- Delivery Service: a central server that resolves conflicts among operations
- Goal: Distribute the Delivery Service [PIFTI23]
 - Use of reliable broadcast protocols for operation delivery
 - Use consensus between group members for operation commits


Access control for peer-to-peer systems without central authority

Goals

- Replicated data
- Replicated access rights
- Multiple administrators

Approach

- Compose CRDTs for data with CRDTs for access rights [RIP23]
- Dependencies
 - Between access rights operations
 - Between document and access rights



Site₂: Admin,Read,Write



P2P Cloud Storage – Défi Alvearium with hive Replication and security mechanisms application

- A distributed peer-to-peer cloud exploiting unused capacity of computers
 - +20% of computing resources remain unused
 - Allows users to share these computing resources
 - Builds a virtual cloud to offer compute and **storage services**



- Sustainable
- Secure & private
- Data sovereignty
- Affordable

P2P Cloud Storage – collaboration with hive Research topics

- How to place data in the peer-to-peer storage in order to ensure high availability?
- How to manage data that can be modified by different peers?
- How to deal with Byzantine nodes? How to handle Sybil attacks?
- How to define a peer-to-peer security mechanism (manage access rights, client-side E2E encryption, group key management)

nnía

Research issues

1 How to **maintain consistency of different copies** in the face of concurrent modifications?

2 How to secure collaboration data?

3 How to make a collaboration **trustworthy**?

naío

Trust in collaborative tools [L21]

- Crisis management issues on information sharing
- Technical issues: tools' complexity, network delay, no interoperability
- Communicational issues





Peer-to-peer user trust

• Prediction of future collaborative user behavior based on the quality of user contributions




Trust computation - contribution

- Evaluate collaborators trust based on their past behavior
 - Contract-based collaborative editing
 - Trust game

Innia


Trust computation in collaborative editing

• Respect/Violation of contracts [TI11,TIBM11,TIM12,ID21]





Peer-to-peer trust metric in trust game [BDM95]



- Design a trust metric dealing with fluctuating user behaviour [DI16a]
 - For a round: $current_trust_t = log(send_proportion_t * (e-1) + 1)$

send _ proportion_t =
$$\frac{sending _amount_t}{max _sending _amount}$$


• For accumulated rounds:

 $aggregate_trust_{t} = \alpha_{t} * current_trust_{t} + (1 - \alpha_{t}) * aggregate_trust_{t-1}$



Validation of the trust metric – experimental design [IDS19]

 Experiment with users on 4 trust games: Simple Game, Identity Game, Score game and Combine game



- Showing either trust score or identity improves the measure
- Showing both of them does not change the measure
- Trust-based systems can be a replacement of identity-based systems
- Collaboration with Department of Psychology Wright State University



PEPR eNSEMBLE (https://pepr-ensemble.fr/) PILOT – Practices and infrastructure for long term collaboration

- Socio-technical models for long-term collaboration
- Multi-organizational, sovereign, secure, interoperable collaboration platforms promoting trust and digital well-being
- Coordinators
 - Claudia-Lavinia Ignat, Inria
 - François Charoy, Université de Lorraine
 - Myriam Lewkowicz, Université de Technologie de Troyes




PILOT – Project axes

- Axis 1: Understanding current and future forms of longterm collaboration
- Axis 2: Open technical frameworks and protocols for long-term collaboration
- Axis 3: Conceptual Frameworks for long-term collaboration
- Axis 4: Actionable guidelines and demonstrators for long term collaboration



PILOT architecture



Ínría

PILOT – Resources

- Budget: 5 M€
- Period: 7 years (Sept. 2023 Aug. 2030)
- Non permanent resources
 - 18 PhD theses
 - 4 postdocs of 2 years
 - 2 engineers of 4 years
 - 12 internships of 6 months
- 14 partner institutions: Inria, CNRS, Univ. Paris-Saclay, Univ. Grenoble Alpes, Sorbonne Univ., IMT, UTT, INSA Lyon, UCB, Nantes Université, ENSAM, Univ. de Lille, Univ. de Toulouse



Large-scale trustworthy distributed collaborative systems

- New uses and new practices due to large scale adoption
- New challenges
 - Consistency of replicated complex data
 - Security mechanisms without a central authority
 - Trust in collaborative platforms and trust among collaborators





COAST Team http://team.inria.fr/coast/



Ínría

References

- **[All23]** Quantifying the Performance of Conflict-free Replicated Data Types in InterPlanetary File System. Q. Acher, C.-L. Ignat, S. Ibrahim. DICG@Middleware 2023
- [AMOI13] Supporting Adaptable Granularity of Changes for Massive Scale Collaborative Editing. L. André, S. Martin, G. Oster, C.-L. Ignat. CollaborateCom 2013.
- **[ASB18]** Delta state replicated data types. P. S. Almeida, A. Shoker, C. Baquero. Journal of Parallel and Distributed Computing, 2018
- **[B00]** Brewer, E.A. "Towards robust distributed systems". In Proc. of PODC, 2000.
- **[BDM95]** Trust, social history, and reciprocity. J. Berg, J. Dickhaut, and K. McCabe, Games and Econ. Behav.1995.
- [DI16a] Performance of real-time collaborative editors at large scale: User perspective.
 Q. V. Dang, C.-L. Ignat. Networking 2016
- [DI16b] Computational Trust Model for Repeated Trust Games. Q. V. Dang, C.-L. Ignat. Trustcom 2016
- [EG89] Concurrency Control in GroupWare Systems, C.A. Ellis and S.J. Gibbs. ACM SIGMOD Record 18(2), 1989.
- [EGR91] Groupware: Some issues and experiences, C.A. Ellis, S. J. Gibbs and G. Rein, Communications of the ACM,1991



References

- [IAO21] Enhancing rich content wikis with real-time collaboration. C.-L. Ignat, L. André, G. Oster. Concurr. Comput. Pract. Exp. 2021
- [ID21] Users trust assessment based on their past behavior in large scale collaboration.
 C.-L. Ignat, Q.-V. Dang. ICCP 2021
- [IDS19] The influence of trust score on cooperative behavior. C.-L. Ignat, Q.-V. Dang, and V. L. Shalin. ACM Trans. Internet Technol. 2019
- [IEB24] Synql: A CRDT-based Approach for Replicated Relational Databases with Integrity Constraints. C.-L. Ignat, V. Elvinger, H. Ba. DAIS 2024
- [IOFSC15] How Do User Groups Cope with Delay in Real-Time Collaborative Note Taking. C.-L. Ignat, G. Oster, O. Fox, V. L. Shalin, F. Charoy. ECSCW 2015
- [J88] GroupWare: Computer Support for Business Teams. R. Johansen. The Free Press, New York, NY, USA, 1988.
- [L21] Confiance dans les situations de travail collaboratifs médiatisés par des environnements numériques. B. Linot. Thèse de doctorat, Univ. de Lorraine, 2021
- [NEOIC17] MUTE: A Peer-to-Peer Web-based Real-time Collaborative Editor. M. Nicolas, V. Elvinger, G. Oster, C.-L. Ignat, F. Charoy. ECSCW, 2017



References

- [NI18] An Analysis of Merge Conflicts and Resolutions in Git-Based Open Source Projects. H. L. Nguyen, C.-L. Ignat. Journal of CSCW, 2018
- [PIFTI23] Design of an Efficient Distributed Delivery Service for Group Key Agreement Protocols. L. Paillat, C.-L. Ignat, D. Frey, M. Turuani, A. Ismail. FPS 2023
- [PMSL09] A commutative replicated data type for cooperative editing, N. Preguica, M. Joan, M. Shapiro, and M. Letia. ICDCS 2009.
- [RIP23] Access control based on CRDTs for Collaborative Distributed Applications.
 P.-A. Rault, C.-L. Ignat, O. Perrin. TrustCom 2023
- [SPBZ11] Conflict-free Replicated Data Types, M. Shapiro, N. Preguica, C. Baquero, M. Zawirski. Research Report, RR-7687, INRIA, 2011
- [TI11] H. T. T. Truong, C.-L. Ignat. Log Auditing for Trust Assessment in Peer-to-Peer Collaboration. ISPDC 2011
- [TIBM11] A contract-extended push-pull-clone model. H. T. T. Truong, C.-L. Ignat, M.-R. Bouguelia, P. Molli. CollaborateCom 2011
- **[TIM12]** Authenticating operation-based history in collaborative systems. H. T. T. Truong, C.-L. Ignat, P. Molli. GROUP 2012
- **[WUM09]** Logoot : a Scalable Optimistic Replication Algorithm for Collaborative Editing on P2P Networks, S. Weiss, P. Urso and P. Molli. ICDCS 2009.

Innia