



SmartM2M; oneM2M Performances Evaluation Tool

Samir Medjiah, Thierry Monteil, Luigi Liquori, Marie-Agnès Peraldi-Frati,
Bob Flynn

► To cite this version:

Samir Medjiah, Thierry Monteil, Luigi Liquori, Marie-Agnès Peraldi-Frati, Bob Flynn. SmartM2M; oneM2M Performances Evaluation Tool. ETSI Technical Specification, 2024, pp.26. hal-04753193

HAL Id: hal-04753193

<https://inria.hal.science/hal-04753193v1>

Submitted on 25 Oct 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

Copyright

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

ETSI TC SmartM2M; SmartM2M; oneM2M Performances Evaluation Tool

Samir Medjiah (4, 5, 6), Thierry Monteil (7, 8), Luigi Liquori (1, 2, 3), Marie-Agnès Peraldi-Frati (3, 2), Bob Flynn

1 CRISAM - Inria Sophia Antipolis - Méditerranée

2 KAIROS - Logical Time for Formal Embedded System Design

3 UCA - Université Côte d'Azur

4 UT - Université de Toulouse

5 UT3 - Université Toulouse III - Paul Sabatier

6 LAAS-SARA - Équipe Services et Architectures pour Réseaux Avancés

7 IRIT-SEPIA - Système d'exploitation, systèmes répartis, de l'intergiciel à l'architecture

8 INSA Toulouse - Institut National des Sciences Appliquées – Toulouse

Executive summary

The present document present the simulation tool and the profiler tool developed to that aim. More precisely, the simulation tool is a OMNeT++ library implementing either the deployment model and the case studies as described in previous cited documents. The profiler is a standalone software to be run together with a real open-source oneM2M implementation dealing from scripts creating oneM2M "burst" till real case study. The profiler provides KPIs values concerning the oneM2M implementation efficiency and/or the case study: these values will be injected in the OMNeT++ simulator allowing a realistic large-scale simulation.

Protected by ETSI IPR. Please refer this document as

S. Medjiah, T. Monteil, L. Liquori, M.A. Peraldi-Frati, B. Flynn. ETSI Technical Report TR 103 841. SmartM2M; oneM2M Performances Evaluation Tool, 26 pages, 2024.

The full document can be retrieved on

https://www.etsi.org/deliver/etsi_tr/103800_103899/103841/01.01.01_60/tr_103841v010101p.pdf