



HAL
open science

Algorithmic ersatz for VSA: Macroscopic simulation of Vector Symbolic Architecture

Chloé Mercier, Thierry Viéville

► **To cite this version:**

Chloé Mercier, Thierry Viéville. Algorithmic ersatz for VSA: Macroscopic simulation of Vector Symbolic Architecture. 2024. hal-04852953

HAL Id: hal-04852953

<https://inria.hal.science/hal-04852953v1>

Preprint submitted on 31 Dec 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Algorithmic ersatz for VSA: Macroscopic simulation of Vector Symbolic Architecture

Chloé Mercier^{a,*} and Thierry Viéville^{a,**}

^a *Mnemosyne Team, Inria Bordeaux, U. Bordeaux, LaBRI and IMN, France*

E-mails: chloe.mercier@inria.fr, thierry.vieville@inria.fr

Submitted to Neurosymbolic Artificial Intelligence

Abstract.

Spiking neuronal networks are biologically plausible implementations of brain circuit computations, meaning that they can provide a way to manipulate symbols embedded as numeric vectors that carry semantic information. More precisely, the Neural Engineering Framework (NEF), relying itself on a vector symbolic architecture (VSA) formalism, bridges the gap between tightly interleaved numerical and symbolic (including formal) computations. Determining how the brain can implement such processing is an important issue.

In the present work, following this track, we consider such a VSA-based formalism, and propose an implementation at a macroscopic level, thus a higher order of magnitude of scale than usual mesoscopic implementations. We also attempt to provide a better natural representation of usual human symbolic operations, considering an implementation of modal logic.

Beyond usual VSA data structures such associative memories we also introduce the notion of “relation maps” corresponding to relational memories, as observed in the brain.

An open-source implementation is provided with a benchmark and experimental observation of the method performance and limitation.

Keywords: Vector Symbolic Architecture, Semantic Pointer Architecture, Modal Logic, Neuro-symbolism

1. Introduction

1.1. Biologically plausible neurosymbolic representations

As a possible entry point to considering a biologically plausible implementation at a symbolic level, vector symbolic architectures (VSAs) were introduced as a way to manipulate symbolic information represented as numeric vectors (see, e.g., [302] for an introduction). VSAs have been proven to be helpful in modeling high-level cognition and accounting for multiple biological features [164, 189]. More specifically, the semantic pointer architecture (SPA) [164] instantiates so-called semantic pointers (i.e., vectors that carry semantic information) and makes it possible to manipulate them in networks of spiking neurons. This approach takes a significant step towards the unification of symbolic and sub-symbolic processing, in that it provides a way to translate the former into the latter. Consequently, complex knowledge representations in the form of compositional structures that are traditionally restricted to symbolic approaches can now be distilled in numerical and even neural¹ systems [122].

*Supported by <https://team.inria.fr/mnemosyne/en/aide>. E-mails: chloe.mercier@inria.fr, thierry.vieville@inria.fr.

** Corresponding author. E-mail: thierry.vieville@inria.fr.

¹The term “neural” refers to any type of nerve cell, whereas “neuronal” is specifically related to neurons.

How can we represent a symbol in a neuronal assembly? A localist representation (one neuron or neuron group represented by a symbol) does not correspond to what is observed in the brain, and the basic idea is that a symbol corresponds to a pattern of activity distributed over the whole assembly. Let us consider a spiking neuron network and quantify its activity using, e.g., the neuron rates or higher-order statistics (see, e.g., [85] for a discussion). As developed by [165], this includes timing codes and population codes (i.e., relative timing codes between neurons). In the Neural Engineering Framework (NEF) [165], this high-dimensional set of bounded quantitative values can be collected and normalized, as a unitary stochastic vector in a high-dimensional space (with a few thousand dimensions for a biological neuronal map and often a few hundred dimensions at the simulation level), thus defining a SPA (building upon a particular case of VSA). The NEF provides a set of principles for implementing such an architecture through synaptic connections, including a time representation in spiking neuron systems (rather than, e.g., other representations based on synchrony within the neural assembly; (see [165] for technical details). This framework is a rather scalable alternative for a biologically plausible implementation of VSA, and it has already been implemented into a simulator called Nengo [38].

In the present study, we consider these developments as prerequisites and will simply consider that neural assembly activity is represented by a high-dimensional unary stochastic vector. We also need to specify transformations and define them at this abstract algebraic level. Mainly, following [335], we will consider the auto-association mechanism, as developed in [472], and functional transformations, as detailed in [165].

1.2. What is this paper about?

We first revisit how to encode symbols within the VSA approach based on the framework introduced in [164], targeting a macroscopic level of modeling. We describe how to generalize symbol encoding considering a related degree of belief, beyond binary information, and following [335], we explain the semantic interest of such a generalization. We consider the Vector-Derived Transformation Binding (VTB) operator [203], for which we recall its algebraic properties in Appendix C.

We then consider hierarchical knowledge structures in the sense of, e.g., [159], as a complement to associative and sequential memorization, and we revisit how to implement such a memory structure using the VSA formalism. To this end, we review VSA data structures and demonstrate that they are related to cognitive memory classification according to [159]. To better understand their computational properties, we also illustrate how such data structures compare to programming language containers, in Appendix B. We introduce a new data structure implementing “relational maps” expressing semantic knowledge [396]. This data structure is important for symbolic derivations and exemplifies the benefits of our macroscopic implementation.

We finally illustrate the proposed mechanism comparing to an existing simulation at the mesoscopic level, utilizing Nengo simulator [38], with a simulation at the macroscopic scale. We show that such computations may be, up to a certain point, approximated without explicitly performing mesoscopic computations at the vector component level; instead, an algorithmic ersatz can be used.

Notations and Layout. We write vectors and matrices in bold letters (bold capital letters for matrices), and scalars in italic. The dual quantity of a vector \mathbf{x} is represented as its transpose \mathbf{x}^T . The dot product between two vectors $\mathbf{x} \cdot \mathbf{y}$ can thus also be written $\mathbf{x}^T \mathbf{y}$. Components of vectors and matrices are represented here using subscripts.

We use the Kronecker notation $\delta_{\mathcal{P}} \stackrel{\text{def}}{=} \begin{cases} 1 & \text{if } \mathcal{P} \text{ is true} \\ 0 & \text{if } \mathcal{P} \text{ is false} \end{cases}$

In this paper, we consider normal distributions $\mathcal{N}(0, \sigma)$, i.e., Gaussian distribution with a null mean and a standard deviation σ , and we write the related random variable $v(\sigma)$.

Non straightforward derivations are done within a symbolic computing environment (our open-source program is available on <https://gitlab.inria.fr/line/aide-group/macrovs>) while trivial demonstrations of most statements are given in footnotes.

2. Symbolic information encoding

Let us first revisit how VSA approaches implement symbolic computation, providing complementary details to be used for the macroscopic simulation of mesoscopic mechanisms.

2.1. Symbol encoding

At the numerical level, each symbol is implemented as a randomly drawn fixed unit d -dimensional vector $\mathbf{x} \in \mathcal{R}^d$. Typically, $d \simeq 100 \cdots 1000$, and we expect to manipulate $k \simeq 100 \cdots 10000$ symbols at the simulation level. Here, our macroscopic implementation uses a dimension of 256, also typically found in related studies such as [335]. In a cortical or brain map, the order of magnitude is higher since the vector corresponds to the neuronal map activity (closer to $10^{5 \cdots 6}$) and the number of encoded symbols depends on which map is considered.

The vector components are drawn from a normal distribution $\mathcal{N}(0, 1/\sqrt{d})$, in order to have an average magnitude² of 1.

A similarity measure is now introduced in order to semantically compare two vectors. Classically, the cosine similarity (i.e., normalized dot product, denoted \cdot) is used to compute the semantic similarity between two unit vectors³:

$$\mathbf{x} \cdot \mathbf{y} \stackrel{\text{def}}{=} \mathbf{x}^\top \mathbf{y} = \cos(\widehat{\mathbf{x}, \mathbf{y}}),$$

where \mathbf{x}^\top denotes the transpose of \mathbf{x} . This measure also corresponds to the angular distance between the vectors.

The key property is that, provided that the space dimension d is large enough, two randomly chosen different vectors will be approximately orthogonal. More precisely⁴,

$$\mathbf{x}^\top \mathbf{y} \sim \delta_{\mathbf{x}=\mathbf{y}} + \nu(1/d),$$

i.e., it is almost 1 if equal and 0 otherwise, plus centered normal noise [443]. At the numerical level, using basic mean and standard-deviation calculi⁵, drawing vectors from such a distribution, and measuring the magnitude, orthogonality, and standard-deviation average values, we have verified for $d \simeq 100 \cdots 1000$ that we generate unary vectors with a relative precision on the magnitude below 0.3%, while orthogonality is verified with a relative precision below 0.4%; the noise standard deviation prediction relative precision is below 0.3%.

This allows us to define a hypothesis to decide whether the \mathcal{H}_0 hypothesis $\mathbf{x} \cdot \mathbf{y} = 0$ can be rejected, as detailed in Appendix A.

2.2. Modality encoding

2.2.1. The notion of belief

Most VSA approaches consider that two vectors \mathbf{x} and \mathbf{y} contain (not exclusively) equivalent information that is semantically equivalent, when the similarity τ equals 1, but there are different ways to interpret this result. Here, we enrich the notion of something being either false or true using a numeric representation of, e.g., partial knowledge, as illustrated in Fig. 1. The true value corresponds to 1 (fully possible and fully necessary), the false value to -1 (neither possible nor necessary, i.e., impossible), and the unknown value to 0, which corresponds to a fully possible but absolutely not necessary value.

Our representation is in one-to-one correspondence with the dual notions of necessity and possibility representation in the standard possibility theory. Information is always related to a certain degree of what is called “belief” in this formalism. While almost all partially known information is related to probability, Piaget proposed that the human “level of truth” is more subtle and related to possibility and necessity [460], as formalized in modal logic. These notions are further developed in the possibility theory discussed in [136] and [137].

²Given independent normal samples of zero mean and standard-deviation σ , the square of the magnitude is the sum of d independent normal samples product, thus a chi-square distribution of standard-deviation $1/d$. Its sum is thus of standard-deviation 1 and so is the magnitude.

³Let us consider two vectors $v_1 = \mathbf{u} + \mathbf{w}_1$ and $v_2 = \mathbf{u} + \mathbf{w}_2$, carrying the same semantic information encoded in \mathbf{u} , plus some additional information \mathbf{w}_1 and \mathbf{w}_2 independent from \mathbf{u} and from each other. Since independent vectors are orthogonal, $v_1^\top v_2 = u^\top u = 1$: this is the meaning of semantic similarity.

⁴The product of these two zero mean random variables of standard-deviation $1/\sqrt{d}$ is a random variable of standard-deviation $1/\sqrt{d^2}$. The product of these two normal random variables is not a normal variable but a linear combination of two independent Chi-square random variables, but we approximate then by a normal distribution, which is a conservative choice as detailed in Appendix A.

The dot-product can be considered as the d times the average value of this chi-square combination distribution over d samples, thus of the same variance, since an average value over d samples divides the variance by d , which is multiplied by d in this case.

⁵See https://raw.githubusercontent.com/vthierry/onto2spa/main/figures/z_score.mpl for the open-source code used in this subsection.




Fig. 1. Representation of partial truth $\tau \in [-1, 1]$ in relation to necessity and possibility, as defined in the possibility theory. The interpretation is that something partially possible but not necessary is unlikely, whereas what is likely is entirely possible but only partially necessary. Such a formulation corresponds qualitatively to the human appreciation of the degree of belief as proposed by, e.g., [460].

In other words, the possibility theory is devoted to the modeling of incomplete information, which is related to an observer's belief regarding a potential event and surprise after the event's occurrence. This is considered representative of what is modeled in educational science and philosophy [433]. Furthermore, in symbolic artificial intelligence, i.e., knowledge representation and logical inference, a link has been drawn between this necessity/-possibility dual representation and ontology [482]. This must be understood as a deterministic theory, in the sense that partial knowledge is not represented by randomness⁶. This modal notion of partial belief has several semantic interpretations depending on the context [176] (i.e. not only epistemic⁷ or doxastic⁸ but also deontic⁹ and so on). This representation has also been designed to be compatible with the ternary Kleene logic, in addition to being coherent with respect to the possibility theory, as discussed in detail in [502], where this deterministic representation of partial knowledge is generalized in order to include a probabilistic representation (using a 2D representation).

2.2.2. Implementing partial similarity knowledge

Let us now propose a design choice to apply this quantification to VSA symbols. A symbol representing a piece of information with a partial degree of belief $\tau \in [-1, 1]$ could be defined as:

$$\hat{\mathbf{x}} \stackrel{\text{def}}{=} \tau \mathbf{x},$$

where \mathbf{x} corresponds to the numerical grounding of a symbol, and $\hat{\mathbf{x}}$ corresponds to the numerical grounding of a symbol, given its degree of belief τ .

Interestingly enough, this representation is coherent with the semantic similarity in the following sense: Are two vectors containing similar information? Considering $\mathbf{x} \cdot \mathbf{y}$, if this value is close to 1, then it is considered true, and the modal representation and semantic similarity are coherent. If it is almost equal to 0, then the modal representation is *not true*. Since our design choice is to consider being in an open world in which all that is not true is not necessarily false, but that we simply can not claim is its true, say it is unknown. To take this a step further, if this value is negative (down to -1), the modal representation considers that it is false, i.e., that the contrary is true, which is coherent with the semantic similarity, although negative values are not explicitly used, to the best of our knowledge, in the literature quoted in this paper.

Given these atomic ingredients, let us now study how they can be stored and manipulated in different data structure.

⁶This deterministic representation of partial knowledge can be generalized in order to also include a representation of the randomness belief. In the vanilla possibility theory, the possibility can be seen as an upper probability: Any possibility distribution defines a set of admissible probability distributions, i.e., a consonant plausibility measure in the Dempster–Shafer theory of evidence [47]. In [494, 502], it is proposed to bound the approximate probability, reconsidering the original notion of necessity, in order to also consider a lower bound of probability. This could be an interesting extension of the present work.

⁷Epistemic modal logic is concerned with reasoning about knowledge.

⁸Doxastic logic is a type of logic concerned with reasoning about beliefs.

⁹Deontic logic is the field of logic that is concerned with obligation, permission, and related concepts.

3. Knowledge structure encoding

3.0.1. Using bundling and binding to store information

As developed in detail in Appendix B and summarized in Table 1, the VSA formalism makes it possible to implement different data structures corresponding to different memory architectures, as defined by [159], and to different programming containers. Further details on a scalable biologically plausible knowledge representation can be found in [122]. A key point of the present work is to verify that these VSA mechanisms generalize to modal symbol encoding (see Appendix B for an exhaustive development, after [335] who introduce such a design choice).

All data structures rely only on the two following operations:

- The bundling operation of N symbolic vectors \mathbf{s}_i corresponds to a simple addition $\mathbf{s} \stackrel{\text{def}}{=} \sum_{k=1}^N \mathbf{s}_k$ while the similarity operator $\mathbf{s} \cdot \mathbf{s}_j$ allows to detect if the symbol related to \mathbf{s}_j belongs to the bundling \mathbf{s} .
- The binding operation of a symbol \mathbf{s}_1 with another symbol \mathbf{s}_2 writes $\mathbf{s} \stackrel{\text{def}}{=} B_{\mathbf{s}_1} \mathbf{s}_2$ and enjoys the property that the corresponding unbinding operator $B_{\mathbf{s}_1}^{-1}$ allows to retrieve \mathbf{s}_2 , i.e., $\mathbf{s}_2 \simeq B_{\mathbf{s}_1}^{-1} \mathbf{s}$.

A reader not familiar with the related VSA formalism will find in Appendix B a didactic introduction, while the choice of the binding operator from among several available binding operators [443] is discussed in Appendix C. For this section to be self-contained, one may simply consider that binding makes it possible to create a key-value symbol pair, while the unbinding operation makes it possible to retrieve the value from the key, as discussed below.

Container	VSA mechanism	Cognitive usage	Main available operations
Set	Bundling or superposition	Self-associative memory	+ Element insertion/modification + Membership check - No enumeration
Map or dictionary	Binding superposition	Auto-associative and hetero-associative memory	+ Element insertion/modification + Value-s check from key + Key-s check from value + Symbol check from approximate input - No enumeration
Indexed and chained list	Ordinal binding superposition	Sequential memory	+ Element insertion/modification + Value enumeration
Relational map	(see next subsection)	Hierarchical memory	+ Element insertion/modification - No enumeration

Table 1

Biologically plausible data containers; see Appendix B for details.

3.0.2. Relational maps

From early artificial intelligence knowledge representation to modern web semantic data structures, the basic idea of symbolic representation is to express knowledge through relationships, i.e., triple statements of the form $(\$subject, \$predicate, \$object)$, as schematized in Fig. 2, [80, 300]. We consider this structure here to demonstrate that beyond existing data structures implemented with VSA, we can also easily define more complex structures at a macroscopic level.

Such information can be implemented through a distributed representation using bundling and binding operations, i.e., associative maps. Following and generalizing [335], we propose to start with an architecture of combined associative memories as represented in Fig. 3. Each associative map stands for a predicate, as proposed and developed by, e.g., [469]. It integrates a demultiplexor which is nothing but another associative map, allowing to index the previous $subject \rightarrow object$ associative maps. At the algebraic level, this writes:




Fig. 2. Atomic representation of knowledge: To express some knowledge regarding a symbol, the subject, we define a feature with a predicate that has an object as an attribute (i.e., a quantitative data value or a qualitative symbol).

$$\mathbf{t}_{\text{ps}0} \stackrel{\text{def}}{=} \sum_i \mathbf{B}_{\mathbf{p}_i} \mathbf{t}_{\mathbf{p}_i}, \text{ with } \mathbf{t}_{\mathbf{p}_i} \stackrel{\text{def}}{=} \sum_{j, \mathbf{p}_i = \mathbf{p}_j} \mathbf{B}_{\mathbf{s}_j} \mathbf{o}_j,$$

where:

- $\mathbf{s}_i, \mathbf{p}_i, \mathbf{o}_i$ are vectors encoding the subject, predicate and object symbols;
- each $\mathbf{B}_{\mathbf{y}} \mathbf{x}$ is a binding which corresponds to a key-value pair (the key is \mathbf{y} and the value is \mathbf{x});
- combining these with bundling (i.e., a simple sum) in $\mathbf{t}_{\mathbf{p}_i}$ allows to define an associative map, which unbinding operation allows to retrieve the object of a given subject and predicate:

$$\mathbf{B}_{\mathbf{s}_i} \sim \mathbf{t}_{\mathbf{p}_j} \simeq \mathbf{o}_{ij} + \mathbf{unknown};$$

where “**unknown**” stands for a vector which is almost orthogonal, thus not similar, to any other vectors, as made explicit in Appendix B.

- selecting the associative map, given a predicate, is also done through the $\mathbf{t}_{\text{ps}0}$, implementing the demultiplexor:

$$\mathbf{B}_{\mathbf{p}_i} \sim \mathbf{t}_{\text{ps}0} = \mathbf{t}_{\mathbf{p}_i} + \mathbf{unknown}.$$

To obtain such properties the choice of a non-commutative binding operator from among several available binding operators [443] is important, in order not mix predicates, subjects and objects.




Fig. 3. A relational map as a row of associative memory. For each predicate, an associative memory stores the hetero-associations between subject and object. An input associative memory acting as demultiplexor allowing to choose for a given predicate which associative memory to choose. At the algebraic level this corresponds to a simple combination of bundling and binding operations.

Given a triple $(\mathbf{s}_0, \mathbf{p}_0, \mathbf{o}_0)$, it is straightforward to verify to what extent it is stored in the relational map through unbinding:

$$(\mathbf{B}_{\mathbf{s}_0} \sim \mathbf{B}_{\mathbf{p}_0} \sim \mathbf{t}_{\text{ps}0} \cdot \mathbf{o}_0),$$

and this obviously generalizes to a triple multiplied by a modal τ value.

We can also further obtain all objects of a given subject for a given property,

$$\mathbf{t}_{\mathbf{p}_j, \mathbf{s}_j} \stackrel{\text{def}}{=} \sum_{\mathbf{p}_j = \mathbf{p}_i, \mathbf{s}_j = \mathbf{s}_i} \mathbf{o}_i \simeq B_{\mathbf{s}_j} \sim B_{\mathbf{p}_j} \sim \mathbf{t}_{\mathbf{pso}} + \mathbf{unknown},$$

using the notation of Appendix C. We can also easily define:

$$\mathbf{t}_{\mathbf{p}_j, \mathbf{o}_j} \stackrel{\text{def}}{=} \sum_{\mathbf{p}_j = \mathbf{p}_i, \mathbf{o}_j = \mathbf{o}_i} \mathbf{s}_i \simeq B_{\mathbf{s}_j} \sim \mathbf{B}_{\leftrightarrow} \sim B_{\mathbf{p}_j} \sim \mathbf{t}_{\mathbf{pso}} + \mathbf{unknown}.$$

However such a construction, up to the best of our knowledge, cannot allow to retrieve, for instance each predicate of a given subject. More precisely, there is no operation to recover $\mathbf{t}_{\mathbf{s}_j}$ or $\mathbf{t}_{\mathbf{s}_j, \mathbf{o}_j}$ from $\mathbf{t}_{\mathbf{pso}}$, and no operation to recover $\mathbf{t}_{\mathbf{p}_j}$ or $\mathbf{t}_{\mathbf{p}_j, \mathbf{o}_j}$ from $\mathbf{t}_{\mathbf{pso}}$. nevertheless, to this end, a dual construction, $\mathbf{t}_{\mathbf{spo}} \stackrel{\text{def}}{=} \sum_i \mathbf{B}_{\mathbf{s}_i} \mathbf{B}_{\mathbf{p}_i} \mathbf{o}_i$, with similar decoding formulae makes it possible to further access the properties of a given subject $\mathbf{t}_{\mathbf{s}_j} \stackrel{\text{def}}{=} \sum_{i, \mathbf{s}_j = \mathbf{s}_i} \mathbf{B}_{\mathbf{p}_i} \mathbf{o}_i$ or the properties of a given subject-object couple $\mathbf{t}_{\mathbf{s}_j, \mathbf{o}_j} \stackrel{\text{def}}{=} \sum_{i, \mathbf{s}_j = \mathbf{s}_i, \mathbf{o}_j = \mathbf{o}_i} \mathbf{p}_i$ using similar formulae. We thus have now two relation maps $\mathbf{t}_{\mathbf{pso}}$ and $\mathbf{t}_{\mathbf{spo}}$. This is an important constraint, and it would be interesting to verify if such a constraint is observed at the level of the brain's semantic memory.

Again, in order to enumerate the different elements of these maps \mathbf{t}_{\bullet} , we need the corresponding indexing mechanisms discussed previously. If the basic operation is to enumerate all triples, with order constraints, then the choice of the storage architecture is not crucial; this is going to be the case later in this paper.

To take this a step further, we can also consider an additional symbol “something,” and each time a triplet $(\mathbf{s}_i, \mathbf{p}_i, \mathbf{o}_i)$ is added, we can also add $(\sigma, \mathbf{p}_i, \mathbf{o}_i)$, $(\mathbf{s}_i, \sigma, \mathbf{o}_i)$, and $(\mathbf{s}_i, \mathbf{p}_i, \sigma)$. This makes it possible to retrieve the fact that there is a link between the predicate and object, subject and object, and subject and predicate, without requiring the enumeration of the different elements¹⁰.

At the cognitive level, this corresponds to cognitive maps interacting with each other and is a proposal to formalize the notion of hierarchical memory organization, as discussed in, e.g., [159].

At the computer programming level, this corresponds to a “triple store” used in ontology reasoners and is in fact a distributed representation of an oriented graph, in the form of an adjacency set for $\mathbf{t}_{\mathbf{spo}}$ construction and a hierarchical edge set for $\mathbf{t}_{\mathbf{pso}}$ construction.

However, comparing to existing development in the literature, defining and manipulating such relational maps, especially when considering rather large data ensembles, might become intractable to simulate at the microscopic level, or even at the mesoscopic level, and it might be useful for large scale application to study to what extent this could also be implemented at a macroscopic level, as developed now.

4. Implementation at the macroscopic scale

The VSA, when implemented using the NEF, allows a microscopic simulation of the neuronal processes, at the spiking neuronal network level, for memorization and processing operations. At a higher scale, when the VSA is implemented as described in Appendix C using linear algebra and permutation operations, we are at a mesoscopic scale, allowing us to perform the same operations without explicitizing the neuronal state value and evolution, but only random vectors linear algebra. This is one major advantage of this class of approaches.

To take this a step further, at a higher macroscopic scale, we could directly consider the previous operations, predicting the results of the different algebraic operations without explicitly working at the vector component level. Let us describe how this approach can be designed and implemented using what could be called an “algorithmic ersatz.”

4.1. Symbol indexing

In the VSA, each symbol of the vocabulary is associated with a d -dimensional random vector. At the macroscopic scale, we only need to register each unary vector \mathbf{u}_k using an integer number k , incremented for each new symbol. At

¹⁰This has been proposed by Gabriel Doriath Döhler (unpublished research report).

the input/output level, the human-readable string (s_k) representation of the symbol is utilized, but it is not considered further here.

Weighted symbols of index i , correspond to a unary vector number k_i , with also a “belief” value $\tau_i \in [-1, 1]$, as discussed in subsection 2.2, that is equal to 1 by default. They are also estimated up to a certain normal centered additive noise $v(\sigma)$ of standard deviation $\sigma_i \geq 0$, which is equal to 0 by default when no approximate operation has been applied to the symbol.

Two symbols may thus have the same unary vector number but different belief levels or different noise levels. The associative table of symbols is thus a simple associative array data structure of (k_i, τ_i, σ_i) , corresponding to

$$\mathbf{x}_{k_i} = \tau_i \mathbf{u}_{k_i} + v(\sigma_i),$$

as illustrated in a more programmatic format in Fig. 4.

If and only if comparison with mesoscopic computation is required, the explicitization of the unary vector value with $\|\mathbf{u}_{k_i}\| = 1$ is added to the data structure.

```

14 Symbol : {
15     unsigned int key;           // index
16     double      tau;           // belief level
17     double      sigma;        // noise level
18     enum        type;         // symbol type
19     string      name;         // human readable name
20     double      mesoscopic_value[dimension]; // optional vector
21 }
22

```

Fig. 4. Programmatic implementation of a symbol at the macroscopic scale, adding an optional mesoscopic numeric vectorial value, to compare macroscopic and mesoscopic calculations.

The symbol type can be *atomic*, i.e. scalar, such a symbol is only defined by its name, without including binding or bundling, or either *bundling* or *binding* with a complementary data structure, as developed below.

With this representation

- Two symbols \mathbf{x} and \mathbf{x}' are approximately colinear if and only if they have the same unary vector index.
- Two colinear symbols \mathbf{x} and \mathbf{x}' are indistinguishable if and only if:

$$0 \simeq \|\mathbf{x} - \mathbf{x}'\| \simeq (\tau - \tau') \mathbf{u}_k + v(\sigma + \sigma'),$$

up to the first order, with $|\tau - \tau'| < \sigma + \sigma'$ as developed in Appendix 11.

- The similarity between two symbols \mathbf{x} and \mathbf{x}' writes:

$$\mathbf{x}^T \mathbf{x}' \simeq \tau \tau' \delta_{k=k'} + v(\sigma + \sigma'),$$

up to the first order.

At this stage we thus have specified atomic symbol, or the dual of such a symbol.

4.2. Symbolic derivation of compounded symbols

Given atomic symbols that are randomly drawn, using the enumerating operations given in Appendix C, we have to compute compounded symbols composed through bundling and binding (while unbinding is a simple binding with the dual symbol, thus taken into account with binding), while in order to compute entailment rules, we need to be able to compute the similarity between any of these compounded symbols.

At the macroscopic level, it is straightforward to define an “oracle” that can calculate the result of all operations as follows:

Bundling canonical representation. A symbol corresponding to the *bundling* of other symbols is fully defined by the symbol set, as illustrated in Fig. 5, and an operation over a bundling (binding or similarity) mainly results from applying the operation to each element. The key point is to have chosen an implementation which allows to maintain a normalized representation of the bundling elements.

```

1 Bundling : {
2     map< symbol-id, Symbol> symbols;
3 }
4

```

Fig. 5. Programmatic implementation of a bundling:

- When a new symbol is added, if already present in the bundling, the τ and σ values are updated, otherwise a new map entry is created.
 - If the added symbol is itself a bundling, its component are directly expanded, making use of associativity.
 - Deleting a symbol corresponds to adding it with zero τ value.
- This allows to maintain a canonical representation of a bundling set of symbols.

The representation is canonical in the sense where, if equality is well-defined on their components, two bundling are semantically equal, if and only if they are syntactically equal, i.e., if they have the same symbol map, and each corresponding symbols are indistinguishable.

Binding canonical representation. A symbol corresponding to the *binding* of one symbol onto another is fully defined by the pair of symbols and yields either a reduction, if it is the corresponding unbinding operation, or a binding combination.

Then, to reduce such an expression we thus simply have to recursively¹¹:

- + Expands $\mathbf{B}_y \mathbf{x}$ binding on the \mathbf{y} argument if it is a bundling.
- + Expands $\mathbf{B}_y \mathbf{x}$ binding on the \mathbf{x} argument if it is a bundling.
- + Reduces dual $\mathbf{B}_y \mathbf{B}_{y\sim} \mathbf{x}$ or $\mathbf{B}_{y\sim} \mathbf{B}_y \mathbf{x}$ binding / unbinding operation, on elementary or compounded symbols.

Let us call “atomic binding case”, when for every \mathbf{B}_y , \mathbf{y} is an atomic symbol. When considering all binding operation regarding used data structures, as discussed in details in Appendix B, or literature quoted in this paper, we are in this atomic binding case. In such a case, the iterative application of these three operations allows to obtain all expression in a canonical form, written:

$$\sum_k \prod_{l=1}^{l_k} \mathbf{B}_{y_{kl}} \mathbf{x}_k$$

where \mathbf{x}_k and \mathbf{y}_{kl} are atomic symbols and $\mathbf{y}_{kl} \neq \mathbf{y}_{k(l+1)}$, while we may have $l_k = 0$ thus omitting the binding operation.

At the programmatic level, binding and unbinding are simply defined by their two operators, and a flag to specify binding or unbinding.

For the sake of generality, let us also discuss canonical forms beyond the “atomic binding case”. Interesting enough, there are no more reduction in terms of a flatter or reduced expression in this general case¹². In other words,

¹¹More formally, we consider the following rules:

$$\begin{aligned}
 e_y \quad \mathbf{B}_{\sum_k \mathbf{y}_k} \mathbf{x} &\rightarrow \sum_k \mathbf{B}_{\mathbf{y}_k} \mathbf{x} \\
 e_x \quad \mathbf{B}_y \sum_k \mathbf{x}_k &\rightarrow \sum_k \mathbf{B}_y \mathbf{x}_k \\
 r_1 \quad \mathbf{B}_y \mathbf{B}_{y\sim} \mathbf{x} &\rightarrow \mathbf{x} \\
 r_2 \quad \mathbf{B}_{y\sim} \mathbf{B}_y \mathbf{x} &\rightarrow \mathbf{x}
 \end{aligned}$$

where

- e_y and e_x corresponds to bundling expansion over binding,
- r_1 and r_2 corresponds to the binding / unbinding reductions.

Applying recursively e_y and e_x obviously yields to an expression of the form

$$\sum_k \prod_l \mathbf{B}_{y_{kl}} \mathbf{x}_k$$

where \mathbf{x}_k are scalar symbols; otherwise one of the three expansion can be applied to reduce the expression.

Applying recursively r_1 and r_2 on the resulting expression allows to guaranty that no binding / unbinding couple of operation remains.

¹²Let us consider the idempotent mirroring matrix $\mathbf{B}_{\leftrightarrow}$, and the related dual operator \sim , also well-defined and detailed in appendix C.:

$$\mathbf{B}_{\leftrightarrow} \mathbf{x} = \mathbf{x}^{\sim} \text{ and } \mathbf{B}_{\leftrightarrow} \mathbf{B}_y \mathbf{x} = \mathbf{B}_x \mathbf{y}$$

We now have to consider expressions where the binding left parameter is also a binding, i.e., of the form $\mathbf{B}_{\mathbf{B}_y \mathbf{z}} \mathbf{x}$. Thanks to the dual operator, it expands as:

$$e_b \quad \mathbf{B}_{\mathbf{B}_y \mathbf{z}} \mathbf{x} \rightarrow \mathbf{B}_{\leftrightarrow} \mathbf{B}_x \mathbf{B}_y \mathbf{z} = [\mathbf{B}_x \mathbf{B}_y \mathbf{z}]^{\sim}.$$

we still derive a canonical form of an expression with binding.

These results enlighten the symbolic manipulations performed at the macroscopic level.

As a consequence, the notion of approximate colinearity or equality (i.e., indistinguishably) between two binding symbols is easily defined, as it is simply induced by the same notion of the two left and right symbols.

Limit of the implementation. This symbolic derivation assumes that no symbol with two different names have a hidden similarity, i.e.:

$$\forall \mathbf{x}, \mathbf{y}, \mathbf{x} \cdot \mathbf{y} \simeq 0 \text{ and } \mathbf{x} \cdot \mathbf{y}^{\sim} \simeq 0.$$

These symbolic derivation rules are in fact nothing but a subset of usual algebraic normalization rules, where the bundling stands for the sum, what it is here, and the bundling a non-commutative product, with a left-inversion mechanism. We refer to symbolic computation textbook for further details.

4.3. Symbol noise derivation

At the mesoscopic scale, calculations are made up to the floating-point machine precision, which is not taken into account here. The operations rely on the fact that we consider random vectors in a high-dimensional space, and thus they are approximately orthogonal up to, up to the first order, a normal centered additive noise. The main operations are the dot product used to calculate the similarity, as detailed in subsection 2.1, and the approximation of the matrix inverse using its transpose for unbinding, as detailed in Appendix C.

We must thus consider a level of noise for each symbol and update this level of noise after each calculation; this noise, up to the first order, can still be represented by a centered normal distribution. This cannot be neglected, because we also introduce a level of belief value that can be small and thus is not negligible with respect to the noise level. We denote by $\sigma_{\bullet} \stackrel{\text{def}}{=} O(1/d)$ the order of magnitude added by an approximate operation, as discussed previously in this paper.

On the one hand, considering the similarity operation between two symbols, we obtain¹³ for the dot product

$$(\tau_i \mathbf{u}_{k_i} + \nu(\sigma_i)) \cdot (\tau_j \mathbf{u}_{k_j} + \nu(\sigma_j)) = \tau_i \tau_j \delta_{k_i=k_j} + \nu(\sigma_{ij}), \sigma_{ij} < \sigma_i + \sigma_j + \sigma_{\bullet},$$

up to the first order, considering that the noise is independent of the vector values up to the first order. We can thus perform this operation without explicitly computing the dot product.

However, as discussed in Appendix C, beyond idempotence, the dual operator \sim neither expands nor simplifies over binding operations. It only expands over bundling. This means that we can not further reduce or normalize binding expressions for which the left argument, named \mathbf{y} here, is not atomic.

In other words, the three form on the left-hand and right-hand size of e_b are simply equivalent and do not lead to further derivation, except trivial useless ones (e.g., adding a zero). Therefore, up to our best understanding, no other expression with \mathbf{x} , \mathbf{y} , and \mathbf{z} , can be semantically equal to one of the three equivalent expressions.

It means that two expressions for which the right parameter is in canonical form as discussed previously and the left parameter is a binding itself in canonical form, are semantically equal if and only if they are syntactically equal.

¹³The derivation is written as follows:

$$\begin{aligned} & ((\tau_i \mathbf{u}_{k_i} + \nu(\sigma_i)) \cdot (\tau_j \mathbf{u}_{k_j} + \nu(\sigma_j))) = \\ & \tau_i \tau_j \mathbf{u}_{k_i} \cdot \mathbf{u}_{k_j} + \tau_i \mathbf{u}_{k_i} \cdot \nu(\sigma_j) + \tau_j \mathbf{u}_{k_j} \cdot \nu(\sigma_i) + \nu(\sigma_i) \cdot \nu(\sigma_j). \end{aligned}$$

If $k_i \neq k_j$, then $\mathbf{u}_{k_i} \cdot \mathbf{u}_{k_j} = \nu(\sigma_{\bullet})$ since these random vectors are approximately orthogonal up to normal noise with a standard deviation with an order of magnitude of σ_{\bullet} [505], whereas if $k_i = k_j$, then $\mathbf{u}_{k_i} \cdot \mathbf{u}_{k_j} = 1$ since these are unary vectors.

Then, $\mathbf{u}_{k_i} \cdot \nu(\sigma_j)$ is the dot product, and it is a random variable of mean $\mathbb{E}[\mathbf{u}_{k_i} \cdot \nu(\sigma_j)] = 0$, since vectors are assumed to be independent of other sources of noise up to the first order, and variance $\mathbb{E}[\mathbf{u}_{k_i}^T \nu(\sigma_j) \nu(\sigma_j)^T \mathbf{u}_{k_i}] = \sigma_j^2$ since the covariance $\nu(\sigma_j) \cdot \nu(\sigma_j)^T = \sigma_j^2 \mathbf{I}$ because the noise is isotropic; meanwhile, $\mathbf{u}_{k_i}^T \mathbf{u}_{k_i} = 1$ since it is a unary vector. Note that here, \mathbf{u}_{k_i} is not a random variable; it stands for the mean of the random vector drawn.

The derivation for $\mathbf{u}_{k_j} \cdot \nu(\sigma_i)$ is identical.

Assuming that $\nu(\sigma_i)$ and $\nu(\sigma_j)$ are independent and of zero mean, as hypothesized, its related variance is known to be $\sigma_i^2 \sigma_j^2$. The product of these two normal distributions is not a normal distribution; instead, it is a linear combination of chi-square distributions in the general case. However, here, as it is a second-order term, with respect to the expected small values of σ_i and σ_j , it is negligible. Collecting these results, we obtain that up to the first order,

Here, we show a conservative choice by proposing an upper bound for the noise, while the exact value, up to the first order, of σ_{ij} can also easily be used, and is implemented. This design choice is also conservative with respect to a mesoscopic implementation, because it increases the noise at each operation, whereas at the mesoscopic level, each numerical random vector is drawn once; thus, depending on the combination of operations, the noise may not increase. We consider here that noise must be added at each step, and we wonder if this is not more realistic than a frozen noise value. However, it would have been possible (but quite computationally heavy) to consider freezing noise values and caching them in some table.

On the other hand, considering a symbol of index j binded by a symbol of index i and unbinded by a symbol of index i' so that $k = k_i = k_{i'}$, in order to ensure a valid binding/unbinding operation, we obtain, up to the first order¹⁴,

$$\mathbf{B}_{(\tau_i \mathbf{u}_i + \nu(\sigma_i))}(\tau_j \mathbf{u}_j + \nu(\sigma_j)) = \tau_i \tau_j \bar{\mathbf{u}}_{ij} + \nu(\sigma'_{ij}), \sigma'_{ij} \leq (1 + \sigma_i + \sigma_j) \sigma_{\bullet}^{1/4},$$

where $\bar{\mathbf{u}}_{ij} \stackrel{\text{def}}{=} \mathbb{E}[\mathbf{B}_{\mathbf{u}_i} \mathbf{u}_j]$ is a new vector orthogonal to \mathbf{u}_i and \mathbf{u}_j , while the noise related to the binding operation is integrated into σ'_{ij} .

Since an unbinding operation is simply a binding operation with a dual vector, the noise calculation is the same.

Finally, since bundling is a simple summation, additive noise standard-deviations simply add. The tricky point is the approximation of τ , as summarized here¹⁵:

$$\sum_{i=1}^I \mathbf{x}_i = \tau_{\bullet} \mathbf{u}_{\bullet} + \nu(\sum_i \sigma_i), \tau_{\bullet} \stackrel{\text{def}}{=} \sqrt{\sum_k (\sum_{i,k_i=k} \tau_i)^2},$$

where \mathbf{u}_{\bullet} is a new unary vector approximately orthogonal to the others, while τ_{\bullet} is the related magnitude. We thus will use τ_{\bullet} as the approximate value of a bundling belief, which is rather arbitrary at this stage, but could easily be improved.

4.4. Other possible features

Similar considerations would easily allow us to implement the same approach at a macroscopic for the dual operator \sim , related to the commutator operator $\mathbf{B}_{\leftrightarrow}$ and the composition operator \odot given in Appendix C. However,

$$(\tau_i \mathbf{u}_{k_i} + \nu(\sigma_i)) \cdot (\tau_j \mathbf{u}_{k_j} + \nu(\sigma_j)) = \tau_i \tau_j \delta_{k_i=k_j} + \nu \left(\underbrace{|\tau_j| \sigma_i + |\tau_i| \sigma_j + |\tau_i \tau_j| \sigma_{\bullet}}_{\stackrel{\text{def}}{=} \sigma'_{ij}} \right),$$

yielding the expected result.

¹⁴As made explicit in Appendix C, the binding of two independent vectors \mathbf{y} and \mathbf{x} is a random vector and we can write

$$\begin{aligned} \mathbf{B}_{(\tau_i \mathbf{u}_i + \nu(\sigma_i))}(\tau_j \mathbf{u}_j + \nu(\sigma_j)) &= \\ \tau_i \tau_j \mathbf{B}_{\mathbf{u}_i} \mathbf{u}_j + \tau_i \mathbf{B}_{\mathbf{u}_i} \nu(\sigma_j) + \tau_j \mathbf{B}_{\nu(\sigma_i)} \mathbf{u}_j + \mathbf{B}_{\nu(\sigma_i)} \nu(\sigma_j) &= \\ \tau_i \tau_j \mathbb{E}[\mathbf{B}_{\mathbf{u}_i} \mathbf{u}_j] + \tau_i \tau_j \nu(1/d^{1/4}) + \tau_i \sigma_j \nu(1/d^{1/4}) + \tau_j \sigma_i \nu(1/d^{1/4}) + \sigma_j \sigma_i \nu(1/d^{1/4}) &\simeq \\ \tau_i \tau_j \bar{\mathbf{u}}_{ij} + (\tau_i \tau_j + \tau_j \sigma_i + \sigma_j \sigma_i) \nu(1/d^{1/4}) &\simeq \\ \tau_i \tau_j \bar{\mathbf{u}}_{ij} + \nu \left(\underbrace{(|\tau_i \tau_j| + |\tau_i| \sigma_j + |\tau_j| \sigma_i) \sigma_{\bullet}^{1/4}}_{\sigma'_{ij}} \right) & \end{aligned}$$

up to the first order, since $\nu(\sigma)$ is a random vector of magnitude σ , while

$$\mathbb{E}[\mathbf{B}_{\mathbf{u}_i} \nu(\sigma_j)] = \mathbb{E}[\mathbf{B}_{\nu(\sigma_i)} \mathbf{u}_j] = \mathbb{E}[\mathbf{B}_{\nu(\sigma_i)} \nu(\sigma_j)] = 0,$$

because these random vectors correspond to centered random vectors.

¹⁵

$$\begin{aligned} \sum_i \mathbf{x}_i &= \sum_i \tau_i \mathbf{u}_{k_i} + \nu(\sigma_i) \\ &= \sum_k \tau_k \mathbf{u}_k + \nu(\sum_i \sigma_i) \tau_k \stackrel{\text{def}}{=} \sum_{i,k_i=k} \tau_i \\ &= \tau_{\bullet} \mathbf{u}_{\bullet} + \nu(\sum_i \sigma_i) \end{aligned}$$

with:

$$\tau_{\bullet} \simeq \sqrt{\sum_k \tau_k^2}, \|\mathbf{u}_{\bullet}\| = 1,$$

since \mathbf{u}_k are approximately orthogonal.

as explored in the previous section, unless explicitly used to defined expressions, they are not useful in our case. This is also the case for the \mathbf{i} identity element.

Interesting enough, deriving a macroscopic ersatz of complex instead of real VSA specification, seems straightforward, since algebraic relations easily generalizes to these case, as reviewed in Appendix C.

Furthermore, we consider binding/unbinding operations using the VTB algebra, but the same reasoning could also be performed for other binding/unbinding operations, including and especially for heavily calculated operators, including if a commutative binding operation is considered, yielding obvious additional reduction rules.

This is another argument to consider macroscopic algorithmic ersatz: while VTB-algebra or almost one order of magnitude heavier than, for instance, convolution operators ($O(d^{3/2})$ instead of $O(d \log(d))$), and this is also the case for other non-commutative binding operations (see Appendix C), the macroscopic simulation of both have similar computational costs.

4.5. Available implementation

We are thus in a position to propose an algorithmic ersatz of the usual VSA mesoscopic linear algebra calculations involving high-dimensional random vectors. This has been implemented and made available as public documented open-source code¹⁶. For the generation of a symbol, at a given level of belief τ and for a given level of first-order random normal noise with a standard deviation σ , the usual similarity, bundling, and binding operations are made available, and the data-structures made explicit here also¹⁷.

5. Experimental results

5.1. Benchmarking macroscopic simulation

Symbolic expression syntax. In order to input or output expression we use the usual JSON¹⁸ syntax in a weak form¹⁹, namely:

- Bundlings are represented by lists:

```
[symbol_1 ...].
```

- Bindings are represented by the construct:

```
{b y: symbol x: symbol },
```

where b stands for binding and is replaced by u for unbinding.

- Atomic symbols are represented by the construct:

```
{ name: symbol-name tau: tau-value sigma: tau-value },
```

τ and σ being optional, while atomic symbols with $\tau=1$ and $\sigma=0$ are also represented by strings.

At the implementation level, this requires no more than a few lines of code.

Symbolic derivation examples. In Table 2, four illustrative examples of symbolic reduction are given:

-The 1st one illustrates the canonical representation of bundling where, in this case $[a, b]$ and $[b, a]$ have the same internal representation, while expansion of binding over bundling is performed for the reduced form.

-The 2nd one illustrates that bundling of bundling are flatten while empty bundling or singleton bundling are reduced, it also shows an example of τ and σ computation.

-The 3rd and 4th ones illustrate binding/unbinding reduction and related belief computation including in complex expressions.

¹⁶<https://line.gitlabpages.inria.fr/aide-group/macrovsa.html>.

¹⁷Additional mechanisms of rule derivations are also present, beyond the present work.

¹⁸See <https://www.json.org>.

¹⁹See <https://line.gitlabpages.inria.fr/aide-group/wjson>.

Numerical noise estimation. In Table 3, the comparison between mesoscopic similarities measures of elementary expressions, and the related macroscopic prediction is reported. Noise of order of magnitude $O(1/d)$ for similarities and $O(1/d^{1/4})$ for binding has been considered. We observe that with respect to our simple 1st order and conservative derivations, noise is overestimated at the macroscopic level, and this overestimation increases with the dimension.

This overestimation increases almost logarithmically with the space dimension, and may partially be compensated by a rather simple rule of thumb, which could easily be improved in the future. This is especially important since macroscopic simulation is mainly useful when the space dimension is to be increased.

After numerical adjustment, it appears that an experimental rule of thumb of:

$$\sigma_{\bullet} = O(1/d) \simeq \underbrace{\frac{1}{1024 d}}_{\sigma_{\bullet}^0} \simeq \underbrace{\frac{1}{1024 (6 \log_{10}(d) - 11) d}}_{\sigma_{\bullet}^1}$$

leads to reasonable results: using σ_{\bullet}^0 allows one to maintain the standard-deviation over-estimation above almost 1 and below 5, for $d < 10^5$, while using rule of the thumb defined by σ_{\bullet}^1 allows one to maintain the standard-deviation over-estimation 0.75 and below 2, for $d < 10^5$, which corresponds to the result in Fig. 3.

This allows to conclude from these numbers that our rather simple, 1st order, estimation of mesoscopic noise, allowing to predict it at the macroscopic level, being conservative, we observe an expected overestimation of the noise, which increases with the space dimension. Obtaining such an overestimation is a conservative choice, in the sense that some deductions may be missed, whereas false deductions will be avoided, as discussed in Appendix A.

A step further, we have investigated to what extents the usual approximation, here and in the literature, of chi-square distribution by a normal distribution, regarding the dot-product similarity operation is appropriate. This is shown in Fig. 6. The main result is that this difference is below 1 bit (i.e., we miss less than 1 bit for information, about half a bit, to consider it as a normal distribution instead of a combination of chi-square ones), and it might decrease with the dimension, although the result is not obvious.




Fig. 6. Average divergence in bits (i.e., using \log_2 in the formula) between the observed mesoscopic noise distribution and a normal distribution with the same standard-deviation, as a function of the space dimension.

Another interesting aspect is that our macroscopic model is consistent with that of [443], which obtains the following (from Fig. 4 of that paper) for the VTB representation:

$$d \gtrsim 32 (s + 0.575)$$

represents the minimal dimension d needed to obtain a 99% accuracy with a bundling of size s , using a similarity calculation to extract vectors from the bundling. Our model does not take the negligible bias 0.575 into account but allows us to calibrate the level of noise to $\sigma \simeq \frac{0.016}{d}$, in order to perform a simple z-score test under the normal hypothesis

$$\tau > 2\sigma$$

to decide if the related τ value of the similarity is distinguishable from the noise. On the other hand, we do not consider two vectors to be similar if the similarity is below the standard deviation of the noise, preferring a more conservative threshold.

To take this a step further, we also implemented the $(1/d^{1/4})$ noise dependency for unbinding, with the same calibration.

Studying, at the mesoscopic level, the numerical precision of unbinding on associative maps is to the best of our knowledge, this was not studied in the papers quoted in this one.

Binding magnitude verification In Table 4, we have verified another aspect of our formal developments: The VTB binding magnitudes. This is important, contrary to previous studies, because we have introduced the notion of belief via the τ magnitude parameter. As formally derived $\|\mathbf{B}_y \mathbf{x}\| \simeq 1$ and $\|\mathbf{B}_y \mathbf{y}\| \simeq \sqrt{2}$, while other magnitudes have not been derived a-priori only observed numerically. If simulation is run at the mesoscopic level, these values matters, and computations must be re-normalized. If simulation is run at the macroscopic level, the normalization assumption is always considered.

Binding computation duration. In Fig. 7, we observe the VTB binding mechanism computation time, which is expected to evolve with $O(d^{\frac{3}{2}})$. In fact, at the implementation level, we observe that due to compiler and on-line processor optimization, the average computation time is an order of magnitude lower, because the VTB binding formula in eq. (1) is easy to optimize, at both the compilation and multi-core processor levels. Fitting the results we obtain, for one binding computation average time, something like:

$$T_{\text{milli-seconds}} = 0.048 + \frac{0.28 d^{1.35}}{10000},$$

on a standard Intel® Core™ i5-8265U CPU @ 1.60GHz × 8 processor, while the obtained result is not very stable around $O(d^{1.3})$. This instability obviously depends on the processor multi-core actual state, when running the simulation.




Fig. 7. Binding average computation time as function of the space dimension. Although not very stable, a better fit is always obtain for a $O(d^p)$, $1 < p < \frac{3}{2}$ interpolation.

This result is not directly useful for our purpose, but is in favor of using the VTB algebra, including at the mesoscopic level, despite a less performing computation time.

5.2. A preliminary experiment

To illustrate the use of macroscopic mechanism beyond basic formulae, we reconsider the example proposed in [335] which has been simulated at the mesoscopic level and is based on a minimal ontology in Fig. 8.




Fig. 8. An example of a simple ontology with three individuals. The black arrows correspond to factual statements input into the database and the green arrows correspond to inferred statements. Rectangular boxes stand for individuals, round boxes stand for classes, and properties are used to label arrows. Here, from the fact that a subject eats an object, we deduce that this subject is a Person, and the object is Food. This is illustrated by a red arrow. From the fact that the object is a Margherita pizza, which is a Pizza, which is a Food, according to the class hierarchy, we deduce that the object is a Pizza, and re-deduce that it is a Food. Furthermore, because Luigi (among other activities, since it is an open world) eats a pizza, we deduce that Luigi is a Person. Because of property heritage, meaning that here a Topping is an Ingredient, we also deduce from the fact that this pizza has mozzarella as a topping that it also has mozzarella as an ingredient. In the macroscopic implementation, this property is deduced from the fact that Margherita pizza always has mozzarella as a topping, allowing us to generate compounded inferences. From [335].

We have considered a symbol encoding dimension of $d = 256$ to be consistent with previous mesoscopic experiments, such as those in [335]. This is tested with an associative map and relational map, as described in the previous

section, and we have implemented the tiny Pizza experiment²⁰, obtaining, in the simplest case, the expected closure, as given in Fig. 9.

5.3. Macroscopic implementation of the VSA system

<i>Input triples</i>	<i>Inferred triples</i>
(Luigi eats thisPizza)	(Luigi rdf:type Person)
(thisPizza rdf:type MargheritaPizza)	(thisPizza rdf:type Pizza)
(MargheritaPizza rdfs:subClassOf Pizza)	(thisPizza rdf:type Food)
(Pizza rdfs:subClassOf Food)	(MargheritaPizza rdfs:subClassOf Food)

Fig. 9. The expected inferences using the proposed RDFS subset of entailment rules obtained by the macroscopic algorithmic ersatz of the VSA implementation.

More interesting is what happens when modality is considered, e.g.,

(Luigi 0.5 eats thisPizza).

In other words, it is possible but not completely necessary that Luigi eats the given pizza. In that case,

- it is still possible but no longer entirely true that Luigi is a person;
- it is still entirely true that this pizza is some food, even if Luigi did not eat it, because it is true that it is a pizza, which is food.

This is what is obtained by the implementation, as shown by the open-source tiny experiment output²⁰.

Although it is far from being complete, this macroscopic implementation of an algorithmic ersatz of VSA mesoscopic operations seems sound and it is consistent with previous results. It has a final non-negligible advantage: It is quite “simple” in the sense that it does not require very complicated or twisted mechanisms. It requires a bit more than 500 lines of formatted C++ code, including formal symbolic operations on the algebraic operators.

6. Discussion and conclusion

6.1. Contributions

In this paper, we have been able to propose, up to the implementation level, a reformulation of the powerful VSA approach with a few additions:

- We explicitized a degree of belief for each knowledge item that is linked to the possibility theory related to modal logic, and we revisited the main proposed abstraction of biologically plausible data structures to verify their compatibility with this generalization while comparing them with usual programming data structures and discussing how to efficiently scan (i.e., enumerate) such data structures.
- We proposed an implementation of hierarchical or relational semantic data structures within the VSA formalism in relation to hierarchical cognitive memory, allowing us to introduce symbolic derivations.
- We introduced the idea of simulating such a mechanism at a macroscopic, more symbolic level in order to obtain computations independent of the VSA dimension space, thus making it possible to scale up such mechanisms. This idea has been applied to VTB algebra but is also obviously reusable with other VSA algebras, through the macroscopic implementation is even more interesting for binding operations requiring more operations.

²⁰ The source code is available at

https://gitlab.inria.fr/line/aide-group/macrovsal/blob/master/src/pizza_experiments.cpp

and it is noticeable that the C/C++ implementation of such rules is straightforward to write, as documented in the source code. This piece of code output is available at

https://gitlab.inria.fr/line/aide-group/macrovsal/raw/master/src/pizza_experiments.out.txt,

in accordance with Fig. 9, and it also shows the intermediate inference steps.

6.2. On biological plausibility and numerical versus semantic grounding

We thus propose an anchoring, i.e., a numerical grounding of semantic information. This, indeed, does not mean that the brain performs such operations as it, but this anchoring is biologically plausible in the sense that algorithms can be implemented in a VSA, as developed in this paper, which itself is a model of spiking neuron assembly activity, as developed by [164] with the NEF approach reviewed in this paper.

Numerical grounding, or anchoring, fundamentally differs from the semantic symbol grounding problem, as reviewed and discussed in [479], where symbols are linked to their meanings and anchored in sensorimotor features, which involves the capacity to pick referents of concepts and a notion of consciousness. In a nutshell, this is still an open problem that we are not going to address here. However, proposals of methods to link abstract symbols to neuronal reality enrich the issue of how mental states can be meaningful. Furthermore, the fact that our abstract representation is anchored in sensorimotor features means that it is also a link between symbols and their potential referents. To take this a step further, when we represent concepts, the chosen design choice associates prototypes, allowing us to anchor an abstract element to a concrete example.

Another aspect not targeted by the present study is the emergence of symbols, i.e., the fact that a symbolic representation emerges from a biological or any physical system in interaction with its environment. This issue corresponds to the ungrounding of concrete signs²¹, as discussed in, e.g., [400], in relation to the emergence of symbolic thinking (see, e.g., [498] for a detailed discussion). At the computational neuroscience level, the issue is addressed in [428] for a toy experiment; that paper emphasizes that to address such an issue, we must avoid explicitly embedding any symbol anywhere in the model, a priori or a posteriori. Here, we do not address the emergence issue, but in a sense, we do address a *feasibility* issue: To what extent can sophisticated symbolic processing be anchored in numerical processing, not just rudimentary operators? We also address an *interpretation* issue, i.e., we consider to what extent sub-symbolic sensorimotor anchored processing corresponds to symbolic processing, as discussed later in this paper.

6.3. Approach limitations and perspectives

The macroscopic simulator is operational but still limited to basic VSA operations of bundling and binding, and their applications to set, associative maps, and other data structures detailed in Appendix B. The symbolic mechanisms are implemented directly at a procedural level, because relatively simple. More complex symbolic algebra could require specific software such as `Maple`²² or equivalent ones, but at the cost of relying on close software or middle-ware and at the cost of a decrease of performances, because using very general mechanisms instead of tuned dedicated coding. Interesting enough, the present implementation is easily generalize to other binding operators or other VSA mechanism, and also to VSA in with complex numbers, as detailed in appendix C. As a next step, the present macroscopic package will be used to study biologically plausible inference mechanisms implemented with VSA.

Following the usual VSA approaches, the symbolic information is embedded in a compact Riemannian manifold with a very simple topology, a hyper-sphere, and we have made explicit the fact that finally, the number of encodable symbols is rather limited. Other geometries may offer better performances, and the particular hyperbolic embedding of hierarchical representations benefits from the fact that due to the hyperbolic negative curvature of the space, even an exponentially growing data structure can be parsimoniously represented [363] because of the expanding geometry (to make a long story short). The idea to embed the data representation in non-Euclidean spaces and especially hyperbolic spaces has already been explored in detail, for instance, in [132], showing that the satisfiability and algorithmic complexity can be drastically different²³. This might be an interesting extension of typical VSA approaches that makes it possible to consider the symbol's numerical embedding in such a Riemannian differential manifold. This could be a fruitful perspective of such work.

²¹In the semiotic hierarchical meaning of an “icon” built only from sensorimotor features, structures at an “index” level built by concrete relationships between given objects give rise to a “symbol” in the semiotic sense, which corresponds to abstract general relationships between concrete concepts or sensorimotor features.

²²See <https://www.maplesoft.com>.

²³A version of these elements intended for a wider audience is available in a science popularization journal: ..

Acknowledgments Terrence C. Stewart is gratefully acknowledged for his inspiring advice that helped us with some aspects of this work. Gabriel Doriath Döhler is thanked for his work on clarifying the use of the VTB algebra and introducing interesting ideas during his undergraduate internship. Frédéric Alexandre and Hugo Chateau-Laurent are gratefully acknowledged for their valuable advice and their contributions to previous works on this subject. We are especially thankful for the reviewing work on this article, which deeply helped us to make the draft valuable. This work is supported by the <https://team.inria.fr/mnemosyne/en/aide> exploratory action.

Conflict of interest: This work is not subject to any conflict of interest.

References

- [1] H. Abbes and F. Gargouri, Modular Ontologies Composition: Levenshtein-Distance-Based Concepts Structure Comparison, *International Journal of Information Technology and Web Engineering* **13**(4) (2018), 35–60.
- [2] A.M. Abou Elfotouh, E.S. Nasr and M.H. Gheith, Serious Educational Games’ Ontologies: A Survey and Comparison, in: *Proceedings of the International Conference on Advanced Intelligent Systems and Informatics 2016*, A.E. Hassanien, K. Shaalan, T. Gaber, A.T. Azar and M.F. Tolba, eds, Advances in Intelligent Systems and Computing, Springer International Publishing, Cham, 2017, pp. 732–741. ISBN 978-3-319-48308-5.
- [3] A. Abyaa, M. Khalidi Idrissi and S. Bennani, Learner modelling: systematic review of the literature from the last 5 years, *Educational Technology Research and Development* **67**(5) (2019), 1105–1143.
- [4] X. Aimé and F. Arnould, Chapitre 2. Apport de l’ingénierie ontologique à la psychologie cognitive, in: *Modélisation ontologique & psychologies. Une influence réciproque*, Éditions matériologiques edn, Modélisations, simulations, systèmes complexes, Éditions Matériologiques, 2021, pp. 95–160, Bibliographie_available: 0 Cairndomain: www.cairn.info Cite Par_available: 0. ISBN 978-2-37361-260-8. <https://www.cairn.info/modelisation-ontologique-et-psychologies--9782373612608-page-95.htm>.
- [5] B. Albero and J. Guérin, L’intérêt pour l’activité en sciences de l’éducation. Vers une épistémologie fédératrice ?, *TransFormations : Recherches en éducation et formation des adultes* **11** (2014), 11–45, Publisher: Institut CUEEP, Lille 1. <https://hal.archives-ouvertes.fr/hal-01712411>.
- [6] F. Alexandre, A global framework for a systemic view of brain modeling, *Brain Informatics* **8**(1) (2021), 3.
- [7] F. Alexandre, Modèles connexionnistes de la mémoire, *Thérapie* (2000), 525, Number: 55. <https://hal.inria.fr/inria-00099242>.
- [8] F. Alexandre, A Behavioral Framework for Information Representation in the Brain, in: *Computational Models of Brain and Behavior*, A.A. Moustafa, ed., John Wiley & Sons, Ltd, Chichester, UK, 2017, pp. 401–412. ISBN 978-1-119-15919-3 978-1-119-15901-8 978-1-119-15906-3.
- [9] F. Alexandre, De quelles façons l’intelligence artificielle se sert-elle des neurosciences ?, *The Conversation* (2019). <https://hal.inria.fr/hal-03085820>.
- [10] F. Alexandre, Creativity explained by Computational Cognitive Neuroscience, in: *ICCC’20 - International Conference on Computational Creativity*, 2020, p. 4. <https://hal.inria.fr/hal-02891491>.
- [11] F. Alexandre, Les relations difficiles entre l’Intelligence Artificielle et les Neurosciences, *Interstices* (2020). <https://hal.inria.fr/hal-02925517>.
- [12] F. Alexandre, C. Mercier and T. Viéville, Aha ! Le cri de la créativité, 2022, <https://hal.inria.fr/hal-03557770>. <https://www.lemonde.fr/blog/binaire/2022/02/04/aha-le-cri-de-la-creativite/>.
- [13] F. Alexandre, J. Becker, M.-H. Comte, A. Lagarrigue, R. Liblau, M. Romero and T. Viéville, Open Educational Resources and MOOC for Citizen Understanding of Artificial Intelligence, 2020. <https://hal.inria.fr/hal-03024034>.
- [14] D. Allemang, J. Hendler and F. Gandon, *Semantic Web for the Working Ontologist: Effective Modeling for Linked Data, RDFS, and OWL*, 3rd edn, Association for Computing Machinery, New York, NY, USA, 2020. ISBN 978-1-4503-7617-4.
- [15] T.M. Amabile, *Componential Theory of Creativity.*, Vol. 12-096, Harvard Business School, 2012.
- [16] A.-R. Amidu, D. Boyd and F. Gobet, A protocol analysis of use of forward and backward reasoning during valuation problem solving, *Property Management* **37** (2019), 638–661.
- [17] G. Anderson, A. Verma, I. Dillig and S. Chaudhuri, Neurosymbolic Reinforcement Learning with Formally Verified Exploration, *arXiv:2009.12612 [cs, stat]* (2020), arXiv: 2009.12612. <http://arxiv.org/abs/2009.12612>.
- [18] M.L. Anderson, W. Gomaa, J. Grant and D. Perlis, An Approach to Human-Level Commonsense Reasoning, in: *Paraconsistency: Logic and Applications*, K. Tanaka, F. Berto, E. Mares and F. Paoli, eds, Springer Netherlands, Dordrecht, 2013, pp. 201–222. ISBN 978-94-007-4437-0 978-94-007-4438-7.
- [19] A.L. Antes and M.D. Mumford, Effects of Time Frame on Creative Thought: Process Versus Problem-Solving Effects, *Creativity Research Journal* **21**(2–3) (2009), 166–182.
- [20] J. Arnett, *Adolescence and Emerging Adulthood: A Cultural Approach*, 2nd edn, 2001.
- [21] S. Arora and P. Doshi, A Survey of Inverse Reinforcement Learning: Challenges, Methods and Progress, arXiv, 2020, arXiv:1806.06877 [cs, stat]. <http://arxiv.org/abs/1806.06877>.
- [22] L. Asprino, A.G. Nuzzolese, A. Russo, A. Gangemi, V. Presutti and S. Nolfi, An Ontology Design Pattern for supporting behaviour arbitration in cognitive agents, in: *Advances in Ontology Design and Patterns*, Studies on the Semantic Web, Vol. 32, 2017, p. 10.

- [23] C. Atlan, J.-P. Archambault, O. Banus, F. Bardeau, A. Blandeau, A. Cois, M. Courbin-Coulaud, G. Giraudon, S.-C. Lefèvre, V. Letard, B. Masse, F. Massegli, B. Ninassi, S.d. Quatrebarbes, M. Romero, D. Roy and T. Viéville, Apprentissage de la pensée informatique : de la formation des enseignant-e-s à la formation de tou-te-s les citoyen-ne-s, 2019. <https://hal.inria.fr/hal-02145480>.
- [24] A. Aubret, L. Matignon and S. Hassas, Étude de la motivation intrinsèque en apprentissage par renforcement, in: *Journées Francophones sur la Planification, la Décision et l'Apprentissage pour la conduite de systèmes*, Toulouse, France, 2019. <https://hal.archives-ouvertes.fr/hal-02272091>.
- [25] A. Augello, I. Infantino, G. Pilato, R. Rizzo and F. Vella, Introducing a creative process on a cognitive architecture, *Biologically Inspired Cognitive Architectures* **6** (2013), 131–139. <https://www.sciencedirect.com/science/article/pii/S2212683X13000467>.
- [26] A. Augello, I. Infantino, A. Lieto, G. Pilato, R. Rizzo and F. Vella, Artwork creation by a cognitive architecture integrating computational creativity and dual process approaches, *Biologically Inspired Cognitive Architectures* **15** (2015). <http://arxiv.org/abs/1601.00669>.
- [27] C.M. Axtell, D.J. Holman, K.L. Unsworth, T.D. Wall, P.E. Waterson and E. Harrington, Shopfloor innovation: Facilitating the suggestion and implementation of ideas, *Journal of Occupational and Organizational Psychology* **73**(3) (2000), 265–285, Number: 3.
- [28] A. Ayadi, A. Samet, F.d.B. de Beuvron and C. Zanni-Merk, Ontology population with deep learning-based NLP: a case study on the Biomolecular Network Ontology, *Procedia Computer Science* **159** (2019), 572–581. <http://www.sciencedirect.com/science/article/pii/S1877050919313961>.
- [29] D.R. Bacon, Comparing Direct Versus Indirect Measures of the Pedagogical Effectiveness of Team Testing, *Journal of Marketing Education* **33**(3) (2011), 348–358, Publisher: SAGE Publications Inc.
- [30] D. Badre, Cognitive control, hierarchy, and the rostro-caudal organization of the frontal lobes, *Trends in Cognitive Sciences* **12**(5) (2008), 193–200, Publisher: Elsevier. [https://www.cell.com/trends/cognitive-sciences/abstract/S1364-6613\(08\)00061-2](https://www.cell.com/trends/cognitive-sciences/abstract/S1364-6613(08)00061-2).
- [31] S. Badreddine, A.d. Garcez, L. Serafini and M. Spranger, Logic Tensor Networks, *arXiv:2012.13635 [cs]* (2021). <http://arxiv.org/abs/2012.13635>.
- [32] M. Baer and G.R. Oldham, The curvilinear relation between experienced creative time pressure and creativity: Moderating effects of openness to experience and support for creativity., *Journal of Applied Psychology* **91**(4) (2006), 963–970.
- [33] A. Baevski, W.-N. Hsu, Q. Xu, A. Babu, J. Gu and M. Auli, data2vec: A General Framework for Self-supervised Learning in Speech, Vision and Language, *arXiv:2202.03555 [cs]* (2022), arXiv: 2202.03555. <http://arxiv.org/abs/2202.03555>.
- [34] D.H. Ballard, M.M. Hayhoe, P.K. Pook and R.P.N. Rao, Deictic codes for the embodiment of cognition, *Behavioral and Brain Sciences* **20**(4) (1997), 723–742. https://www.cambridge.org/core/product/identifier/S0140525X97001611/type/journal_article.
- [35] S. Barnabé, L. Denet, M. Manrique, D. Menon, E. Pascual, M. Romero and T. Viéville, A low-cost tabletop game to collect learning analytics during computational thinking using unplugged or tangible activities, Research report, RR-9379, Inria, 2020. <https://hal.inria.fr/hal-03040909>.
- [36] T.K. Basantia, Culture, Value and Personality: Three Flowering Agents of Creativity Development Process, *American Journal of Applied Psychology* **5**(1) (2017), 1–6, Number: 1 Publisher: Science and Education Publishing. <http://pubs.sciepub.com/ajap/5/1/1/index.html>.
- [37] R.E. Beaty, M. Benedek, P.J. Silvia and D.L. Schacter, Creative Cognition and Brain Network Dynamics, *Trends in Cognitive Sciences* **20**(2) (2016), 87–95.
- [38] T. Bekolay, J. Bergstra, E. Hunsberger, T. DeWolf, T.C. Stewart, D. Rasmussen, X. Choo, A.R. Voelker and C. Eliasmith, Nengo: A Python tool for building large-scale functional brain models, *Frontiers in Neuroinformatics* **7** (2014).
- [39] M. Belkaid, N. Cuperlier and P. Gaussier, Emotional metacontrol of attention: Top-down modulation of sensorimotor processes in a robotic visual search task, *PLOS ONE* **12**(9) (2017), e0184960, Publisher: Public Library of Science.
- [40] A.V. Belopolsky, A.F. Kramer and J. Theeuwes, The Role of Awareness in Processing of Oculomotor Capture: Evidence from Event-related Potentials, *Journal of Cognitive Neuroscience* **20**(12) (2008), 2285–2297.
- [41] J.H.M. Bergmann, P.M. Langdon, R.E. Mayagoitia and N. Howard, Exploring the Use of Sensors to Measure Behavioral Interactions: An Experimental Evaluation of Using Hand Trajectories, *PLoS ONE* **9**(2) (2014), e88080. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3917885/>.
- [42] J.-L. Berthier, Les neurosciences et l’avenir de l’éducation, *Futuribles* **428**(1) (2019), 81–91, Bibliographie_available: 0 Cairndomain: www.cairn.info Cite Par_available: 0 Publisher: Futuribles. <https://www.cairn.info/revue-futuribles-2019-1-page-81.htm>.
- [43] M. Besançon, B. Barbot and T. Lubart, Évolution de l’évaluation de la créativité chez l’enfant de Binet à nos jours, *Recherches & Éducatives* (2011), 215–226. <http://journals.openedition.org/rechercheseducations/840>.
- [44] J.-M. Besnier, *Les théories de la connaissance*, Presses universitaires de France edn, Que sais-je ?, 2021, ISSN: 0768-0066. ISBN 978-2-7154-0603-2. <http://www.cairn.info/les-theories-de-la-connaissance--9782715406032.htm>.
- [45] T.R. Besold, A.d. Garcez, S. Bader, H. Bowman, P. Domingos, P. Hitzler, K.-U. Kuehnberger, L.C. Lamb, D. Lowd, P.M.V. Lima, L. de Penning, G. Pinkas, H. Poon and G. Zaverucha, Neural-Symbolic Learning and Reasoning: A Survey and Interpretation, *arXiv:1711.03902 [cs]* (2017), arXiv: 1711.03902. <http://arxiv.org/abs/1711.03902>.
- [46] R. Betzel and D. Bassett, Multi-scale brain networks, *NeuroImage* **160** (2016).
- [47] M. Beynon, B. Curry and P. Morgan, The Dempster-Shafer theory of evidence: An alternative approach to multicriteria decision modelling, *Omega* **28**(1) (2000), 37–50. <https://www.sciencedirect.com/science/article/pii/S030504839900033X>.
- [48] R. Bhattacharyya, Z. Bhuyan and S.M. Hazarika, O-PrO: An Ontology for Object Affordance Reasoning, in: *Intelligent Human Computer Interaction*, A. Basu, S. Das, P. Horain and S. Bhattacharyya, eds, Lecture Notes in Computer Science, Springer International Publishing, Cham, 2017, pp. 39–50. ISBN 978-3-319-52503-7.
- [49] J. Biard, La théorie de la connaissance entre sémiologie et ontologie (2019), 85, Publisher: Académie des Inscriptions et Belles Lettres ; De Boccard. <https://halshs.archives-ouvertes.fr/halshs-02156623>.

- [50] P. Bille, A survey on tree edit distance and related problems, *Theoretical Computer Science* **337**(1) (2005), 217–239. <https://www.sciencedirect.com/science/article/pii/S0304397505000174>.
- [51] E. Birmingham, W.F. Bischof and A. Kingstone, Social Attention and Real-World Scenes: The Roles of Action, Competition and Social Content, *Quarterly Journal of Experimental Psychology* **61**(7) (2008), 986–998, Publisher: SAGE Publications.
- [52] C. Blanchard-Laville, De la co-disciplinarité en sciences de l'éducation, *Revue française de pédagogie* (2000), 55–66, Number: 132., <http://www.jstor.org/stable/41201594>.
- [53] D.B. Blumenthal, New Techniques for Graph Edit Distance Computation, *arXiv:1908.00265 [cs]* (2019), arXiv: 1908.00265. <http://arxiv.org/abs/1908.00265>.
- [54] J. Bochnak, M. Coste and M.-F. Roy, *Real Algebraic Geometry*, Springer Science & Business Media, 2013, Google-Books-ID: GJv6CAAQBAJ. ISBN 978-3-662-03718-8.
- [55] M.A. Boden, Creativity and artificial intelligence, *Artificial Intelligence* **103**(1) (1998), 347–356. <https://www.sciencedirect.com/science/article/pii/S0004370298000551>.
- [56] M.A. Boden, *The Creative Mind: Myths and Mechanisms*, Psychology Press, 2004, Google-Books-ID: 6Zkm4dz32Y4C. ISBN 978-0-415-31452-7.
- [57] M.A. Boden, Creativity in a nutshell, *Think* **5**(15) (2007), 83–96, Publisher: Cambridge University Press. <https://www.cambridge.org/core/journals/think/article/creativity-in-a-nutshell/E74A8FA0906C3AA5A1813FFBD56860F9>.
- [58] R. Bogacz, Optimal decision-making theories: linking neurobiology with behaviour, *Trends in Cognitive Sciences* **11**(3) (2007), 118–125, Number: 3. <https://linkinghub.elsevier.com/retrieve/pii/S1364661307000290>.
- [59] R. Bogacz, Dopamine role in learning and action inference, *eLife* **9** (2020), e53262. <https://elifesciences.org/articles/53262>.
- [60] R. Bogacz, M. Usher, J. Zhang and J.L. McClelland, Extending a biologically inspired model of choice: multi-alternatives, nonlinearity and value-based multidimensional choice, *Philosophical Transactions of the Royal Society B: Biological Sciences* **362**(1485) (2007), 1655–1670, Number: 1485.
- [61] S. Bohler, D'où vient la curiosité ?, Publisher: Pour la Science. <https://www.cerveauetpsycho.fr/sd/neurosciences/d-ou-vient-la-curiosite-21975.php>.
- [62] J.-F. Bonnefon and I. Rahwan, Machine Thinking, Fast and Slow, *Trends in Cognitive Sciences* **24**(12) (2020), 1019–1027. <https://www.sciencedirect.com/science/article/pii/S1364661320302229>.
- [63] R.H. Bordini and J.F. Hübner, Jason – A Java-based interpreter for an extended version of AgentSpeak, 2007. <http://jason.sourceforge.net/Jason.pdf>.
- [64] R.H. Bordini, J.F. Hübner and M. Wooldridge, *Programming Multi-Agent Systems in AgentSpeak using Jason*, Wiley Series in Agent Technology, John Wiley & Sons, Ltd, Chichester, UK, 2007. ISBN 978-0-470-06184-8 978-0-470-02900-8.
- [65] V. Borghesani, The neuro-cognitive representation of word meaning resolved in space and time, phdthesis, Université Pierre et Marie Curie - Paris VI ; Università degli studi (Trente, Italie), 2017. <https://tel.archives-ouvertes.fr/tel-02054668>.
- [66] M. Botvinick, S. Ritter, J.X. Wang, Z. Kurth-Nelson, C. Blundell and D. Hassabis, Reinforcement Learning, Fast and Slow, *Trends in Cognitive Sciences* **23**(5) (2019), 408–422. <https://linkinghub.elsevier.com/retrieve/pii/S1364661319300610>.
- [67] B. Bouchon-Meunier, *La logique floue*, Que sais-je ?, Vol. 4e éd., Presses Universitaires de France, Paris cedex 14, 2007, Issue: 2702. ISBN 978-2-13-056260-3. <https://www.cairn.info/la-logique-floue--9782130562603.htm>.
- [68] B. Bouchon-Meunier, Raisonement possibiliste, in: *Que sais-je? La logique Floue*, Que sais-je ?, Vol. 4e éd., Presses Universitaires de France, Paris cedex 14, 2007, pp. 97–103. ISBN 978-2-13-056260-3. <https://www.cairn.info/la-logique-floue--9782130562603-p-97.htm>.
- [69] A. Boumaza and B. Scherrer, Optimal control subsumes harmonic control, IEEE, 2007, p. 2841. <https://hal.inria.fr/inria-00170185>.
- [70] A. Boumaza and B. Scherrer, Optimal control subsumes harmonic control, IEEE, 2007, p. 2841. <https://hal.inria.fr/inria-00170185>.
- [71] M. Bourassa, M. Menot-Martin and R. Phillion, *Neurosciences et éducation. Pour apprendre et accompagner*, Pédagogies en développement, De Boeck Supérieur, Louvain-la-Neuve, 2017. ISBN 978-2-8073-0748-3. <https://www.cairn.info/neurosciences-et-education--9782807307483.htm>.
- [72] J.-P. Boutinet, *L'ABC de la VAE*, Éducation - Formation, Érès, Toulouse, 2009. ISBN 978-2-7492-1109-1. <https://www.cairn.info/l-abc-de-la-vae--9782749211091.htm>.
- [73] S. Brand-Gruwel, I. Wopereis and Y. Vermetten, Information problem solving by experts and novices: analysis of a complex cognitive skill, *Computers in Human Behavior* **21**(3) (2005), 487–508. <https://linkinghub.elsevier.com/retrieve/pii/S0747563204001591>.
- [74] K. Brennan and M. Resnick, New frameworks for studying and assessing the development of computational thinking (2012), 25.
- [75] A. Brown, metacognition.png, 1987. <https://joanakompa.files.wordpress.com/2017/08/overview.png>.
- [76] G. Bugmann, Biologically plausible neural computation, *Biosystems* **40**(1) (1997), 11–19. <https://www.sciencedirect.com/science/article/pii/0303264796016255>.
- [77] S. Bull and J. Kay, Open Learner Models, in: *Advances in Intelligent Tutoring Systems*, R. Nkambou, J. Bourdeau and R. Mizoguchi, eds, Studies in Computational Intelligence, Springer, Berlin, Heidelberg, 2010, pp. 301–322. ISBN 978-3-642-14363-2.
- [78] C. Burges, Dimension Reduction: A Guided Tour, *Foundations and Trends in Machine Learning* **2** (2010).
- [79] T. Busscher, C. Zuidema, T. Tillema and J. Arts, Learning in the face of change: The Dutch National Collaboration Programme on Air Quality., *Environment and Planning C: Politics and Space* **37**(5) (2019), 929–945, Publisher: SAGE Publications Sage UK: London, England.
- [80] S.T. Cao, L.A. Nguyen and A. Szalas, The Web Ontology Rule Language OWL 2 RL + and Its Extensions, in: *Transactions on Computational Intelligence XIII*, N.-T. Nguyen and H.A. Le-Thi, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2014, pp. 152–175. ISBN 978-3-642-54455-2.

- [81] P. Carré and F. Fenouillet, *Traité de psychologie de la motivation. Théories et pratiques*, Éducation Sup, Dunod, Paris, 2019. ISBN 978-2-10-078304-5. <https://www.cairn.info/traité-de-psychologie-de-la-motivation--9782100783045.htm>.
- [82] B.T. Carter and S.G. Luke, Best practices in eye tracking research, *International Journal of Psychophysiology* **155** (2020), 49–62. <https://www.sciencedirect.com/science/article/pii/S0167876020301458>.
- [83] S. Censabella, Chapitre 5 : les fonctions exécutives, in: *Bilan neuropsychologique de l'enfant*, PSY-Évaluation, mesure, diagnostic, Mardaga, Wavre, 2007, pp. 117–137. ISBN 978-2-87009-964-3. <https://www.cairn.info/bilan-neuropsychologique-de-l-enfant--9782870099643-p-117.htm>.
- [84] R. Cera, C. Cristini and A. Antonietti, Conceptions of Learning, Well-being, and Creativity in Older Adults, *Journal of Educational, Cultural and Psychological Studies (ECPS Journal)* (2018), 241–273, Number: 18. <https://www.ledonline.it/index.php/ECPS-Journal/article/view/1475>.
- [85] B. Cessac and T. Viéville, On dynamics of integrate-and-fire neural networks with adaptive conductances, *Frontiers in Neuroscience* **2**(2) (2008). <https://hal.inria.fr/inria-00338369>.
- [86] C.-Y. Chang, C. Tijus and E. Zibetti, Les apprentissages à l'heure des technologies cognitives numériques, *Administration & Éducation* **146**(2) (2015), 91–98, Number: 2 Place: Paris Publisher: Association Française des Acteurs de l'Éducation. <https://www.cairn.info/revue-administration-et-education-2015-2-page-91.htm>.
- [87] S. Charron,
L'architecture fonctionnelle intégrant le contrôle cognitif et le contrôle motivationnel dans le cortex préfrontal humain., 196.
- [88] H. Chateau-Laurent and F. Alexandre, Towards a Computational Cognitive Neuroscience Model of Creativity, in: *IEEE ICCI*CC'21 - 20th IEEE International Conference on Cognitive Informatics and Cognitive Computing*, 2021. <https://hal.inria.fr/hal-03359407>.
- [89] W. Chen, J.S.H. Tan and Z. Pi, The spiral model of collaborative knowledge improvement: an exploratory study of a networked collaborative classroom, *International Journal of Computer-Supported Collaborative Learning* **16**(1) (2021), 7–35.
- [90] R. Cheung, C. Wan and C. Cheng, An Ontology-Based Framework for Personalized Adaptive Learning, in: *Advances in Web-Based Learning – ICWL 2010*, X. Luo, M. Spaniol, L. Wang, Q. Li, W. Nejdl and W. Zhang, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2010, pp. 52–61. ISBN 978-3-642-17407-0.
- [91] M.T.H. Chi, Active-Constructive-Interactive: A Conceptual Framework for Differentiating Learning Activities, *Topics in Cognitive Science* **1**(1) (2009), 73–105.
- [92] M.T.H. Chi and R. Wylie, The ICAP Framework: Linking Cognitive Engagement to Active Learning Outcomes, *Educational Psychologist* **49**(4) (2014), 219–243, Number: 4.
- [93] F.-X. Choo, Spaun 2.0: Extending the World's Largest Functional Brain Model, PhD Thesis, University of Waterloo (CA), 2018. <https://uwspace.uwaterloo.ca/handle/10012/13308>.
- [94] X. Choo and C. Eliasmith, General Instruction Following in a Large-Scale Biologically Plausible Brain Model, in: *35th Annual Conference of the Cognitive Science Society*, Cognitive Science Society, 2013, pp. 322–327.
- [95] I. Chraïbi Kaadoud, A. Bennetot, B. Mawhin, V. Charisi and N. Díaz-Rodríguez, Explaining Aha! moments in artificial agents through IKE-XAI: Implicit Knowledge Extraction for eXplainable AI, *Neural Networks* **155** (2022), 95–118. <https://www.sciencedirect.com/science/article/pii/S0893608022003021>.
- [96] C.K. Chui and H.N. Mhaskar, Deep Nets for Local Manifold Learning, *Frontiers in Applied Mathematics and Statistics* **4** (2018), Publisher: Frontiers.
- [97] S. Cinan, G. Özen and A. Hampshire, Confirmatory factor analysis on separability of planning and insight constructs, *Journal of Cognitive Psychology* **25**(1) (2013), 7–23, Publisher: Routledge _eprint: <https://doi.org/10.1080/20445911.2012.729035>.
- [98] D. Ciucci, D. Dubois and J. Lawry, Borderline vs unknown: comparing three-valued representations of imperfect information, *International Journal of Approximate Reasoning* **55**(9) (2014), 1866–1889. <https://www.sciencedirect.com/science/article/pii/S0888613X14001157>.
- [99] N. Clairis and M. Pessiglione, Value, confidence and deliberation: a functional partition of the medial prefrontal cortex across preference tasks, Technical Report, bioRxiv, 2021, Section: New Results Type: article.
- [100] B. Clement, D. Roy, P.-Y. Oudeyer and M. Lopes, Developmental learning for Intelligent Tutoring Systems, in: *4th International Conference on Development and Learning and on Epigenetic Robotics*, IEEE, Genoa, Italy, 2014, p. 10. ISBN 978-1-4799-7540-2. <http://ieeexplore.ieee.org/document/6983019/>.
- [101] J. Clemente, J. Ramírez and A. de Antonio, A proposal for student modeling based on ontologies and diagnosis rules, *Expert Systems with Applications* **38**(7) (2011), 8066–8078. <https://www.sciencedirect.com/science/article/pii/S0957417410015095>.
- [102] B. Clément, D. Roy, P.-Y. Oudeyer and M. Lopes, Online Optimization of Teaching Sequences with Multi-Armed Bandits, 2014. <https://hal.inria.fr/hal-01016428>.
- [103] B. Clément, D. Roy, P.-Y. Oudeyer and M. Lopes, Multi-Armed Bandits for Intelligent Tutoring Systems, *Journal of Educational Data Mining* **7**(2) (2015), 20–48, Number: 2. <https://hal.inria.fr/hal-00913669>.
- [104] J.D. Co-Reyes, Guiding policies with language via meta-learning (2019), 17.
- [105] W.W. Cohen, F. Yang and K.R. Mazaitis, TensorLog: Deep Learning Meets Probabilistic DBs, *arXiv:1707.05390 [cs]* (2017), arXiv: 1707.05390. <http://arxiv.org/abs/1707.05390>.
- [106] T.R. Colin, T. Belpaeme, A. Cangelosi and N. Hemion, Hierarchical reinforcement learning as creative problem solving, *Robotics and Autonomous Systems* **86** (2016), 196–206. <https://linkinghub.elsevier.com/retrieve/pii/S0921889016305371>.
- [107] Collective, *La motivation*, Petite bibliothèque, Éditions Sciences Humaines, Auxerre, 2017. ISBN 978-2-36106-427-3. <https://www.cairn.info/la-motivation--9782361064273.htm>.

- [108] A. Collins, Apprentissage et contrôle cognitif: une théorie computationnelle de la fonction exécutive préfrontale humaine, 252.
- [109] A. Collins and E. Koechlin, Reasoning, Learning, and Creativity: Frontal Lobe Function and Human Decision-Making, *PLoS Biology* **10**(3) (2012), e1001293.
- [110] A.G.E. Collins and J. Cockburn, Beyond simple dichotomies in reinforcement learning., *Nature Reviews Neuroscience* **21**(10) (2020), 576–586, Number: 10 Publisher: Nature Publishing Group. <https://www.nature.com/articles/s41583-020-0355-6>.
- [111] C. Conchinha, P. Osorio and J.C. de Freitas, Playful learning: Educational robotics applied to students with learning disabilities, in: *2015 International Symposium on Computers in Education (SIIE)*, IEEE, Setubal, 2015, pp. 167–171. ISBN 978-1-5090-1435-4. <http://ieeexplore.ieee.org/document/7451669/>.
- [112] C. Connolly and R. Grupen, Nonholonomic Path Planning Using Harmonic Functions (1994), 21.
- [113] C.I. Connolly, Harmonic Functions and Collision Probabilities, *The International Journal of Robotics Research* **16**(4) (1997), 497–507, Publisher: SAGE Publications Ltd STM.
- [114] C.I. Connolly and J.B. Burns, A Model for the Functioning of the Striatum, *Biological Cybernetics* **68** (1993), 535–544.
- [115] C.I. Connolly and R.A. Grupen, The applications of harmonic functions to robotics, *Journal of Robotic Systems* **10**(7) (1993), 931–946, [_eprint: https://onlinelibrary.wiley.com/doi/pdf/10.1002/rob.4620100704](https://onlinelibrary.wiley.com/doi/pdf/10.1002/rob.4620100704).
- [116] M. Constantinou, L. Ashendorf and R.J. McCaffrey, Effects of a Third Party Observer During Neuropsychological Assessment: When the Observer Is a Video Camera, *Journal of Forensic Neuropsychology* **4**(2) (2005), 39–47.
- [117] M. Corbetta and G.L. Shulman, Control of goal-directed and stimulus-driven attention in the brain, *Nature Reviews Neuroscience* **3**(3) (2002), 201–215, Bandiera_abtest: a Cg_type: Nature Research Journals Number: 3 Primary_atype: Reviews Publisher: Nature Publishing Group. <https://www.nature.com/articles/nrn755>.
- [118] A.L. Cosgrove, Y.N. Kenett, R.E. Beaty and M.T. Diaz, Quantifying flexibility in thought: The resiliency of semantic networks differs across the lifespan, *Cognition* **211** (2021), 104631. <https://www.sciencedirect.com/science/article/pii/S0010027721000500>.
- [119] M. Coste, [PDF] AN INTRODUCTION TO SEMIALGEBRAIC GEOMETRY | *Semantic Scholar*, Institut de Recherche Mathématique de Rennes. <https://www.semanticscholar.org/paper/AN-INTRODUCTION-TO-SEMIALGEBRAIC-GEOMETRY-Coste/77f4f0f1de8e80afc0fe0591ddd4bf3d52098329>.
- [120] N. Cowan, What are the differences between long-term, short-term, and working memory?, *Progress in brain research* **169** (2008), 323–338. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC2657600/>.
- [121] N. Cowan, Sensory and Immediate Memory, *Encyclopedia of Consciousness* (2010).
- [122] E. Crawford, M. Gingerich and C. Eliasmith, Biologically plausible, human-scale knowledge representation, *Cognitive Science* **40**(4) (2016), 782–821.
- [123] S.H. Creem and D.R. Proffitt, Defining the cortical visual systems: “What”, “Where”, and “How”, *Acta Psychologica* **107**(1) (2001), 43–68. <https://www.sciencedirect.com/science/article/pii/S000169180100021X>.
- [124] P. Cui, X. Wang, J. Pei and W. Zhu, A Survey on Network Embedding, *IEEE Transactions on Knowledge and Data Engineering* **31**(5) (2019), 833–852. Conference Name: IEEE Transactions on Knowledge and Data Engineering.
- [125] P.G. Curran, Exploration and exploitation: A new explanation of differential goal-setting effects, PhD thesis, Michigan State University, 2008. <https://search.proquest.com/openview/c616a4f6dd3ff1835b2450da541d68fa/1?pq-origsite=gscholar&cbl=18750&diss=y>.
- [126] E. Davis and G. Marcus, Commonsense reasoning and commonsense knowledge in artificial intelligence, *Communications of the ACM* **58**(9) (2015), 92–103.
- [127] W.S. De Grave, H.P.A. Boshuizen and H.G. Schmidt, Problem based learning: Cognitive and metacognitive processes during problem analysis, *Instructional Science* **24**(5) (1996), 321–341.
- [128] H.L.H. De Penning, A.S.D. Garcez, L.C. Lamb and J.-J.C. Meyer, A Neural-Symbolic Cognitive Agent for Online Learning and Reasoning, in: *Proceedings of the Twenty-Second international joint conference on Artificial Intelligence - Volume Volume Two*, IJCAI’11, AAAI Press, Barcelona, Catalonia, Spain, 2011, pp. 1653–1658. ISBN 978-1-57735-514-4.
- [129] M.M. de Wit, S. de Vries, J. van der Kamp and R. Withagen, Affordances and neuroscience: Steps towards a successful marriage, *Neuroscience and Biobehavioral Reviews* **80** (2017), 622–629.
- [130] L. DeBlois, S. Barma and S. Lavallée, L’enseignement ayant comme visée la compétence à résoudre des problèmes mathématiques: quels enjeux?, *Éducation et francophonie* **44**(2) (2016), 40–67, Publisher: Association canadienne d’éducation de langue française.
- [131] J. Delacour, Conscience et cerveau - Introduction, in: *Conscience et cerveau*, Neurosciences & cognition, De Boeck Supérieur, Louvain-la-Neuve, 2001, pp. 5–8. ISBN 978-2-8041-3766-3. <https://www.cairn.info/conscience-et-cerveau--9782804137663-p-5.htm>.
- [132] J.-P. Delahaye, *Complexités : Aux limites des mathématiques et de l’informatique*, HAL, 2006, Number: hal-00731936. <https://ideas.repec.org/p/hal/journal/hal-00731936.html>.
- [133] J.-P. Delahaye, *Complexités : Aux limites des mathématiques et de l’informatique*, 2006, Number: hal-00731936 Publisher: HAL. <https://ideas.repec.org/p/hal/journal/hal-00731936.html>.
- [134] S. Denervaud, A.P. Christensen, Y.N. Kenett and R.E. Beaty, Education shapes the structure of semantic memory and impacts creative thinking, *npj Science of Learning* **6**(1) (2021), 1–7, Bandiera_abtest: a Cc_license_type: cc_by Cg_type: Nature Research Journals Number: 1 Primary_atype: Research Publisher: Nature Publishing Group Subject_term: Human behaviour;Long-term memory Subject_term_id: human-behaviour;long-term-memory. <https://www.nature.com/articles/s41539-021-00113-8>.
- [135] L. Denet, Le dispositif Tabletop du projet AIDE : développement de son interface utilisateur., report, Inria Bordeaux Sud-Ouest, 2020. <https://hal.inria.fr/hal-02935633>.

- [136] T. Denœux, D. Dubois and H. Prade, Representations of uncertainty in AI: Beyond probability and possibility, in: *A Guided Tour of Artificial Intelligence Research: Volume I: Knowledge Representation, Reasoning and Learning*, P. Marquis, O. Papini and H. Prade, eds, Springer International Publishing, Cham, 2020, pp. 119–150. ISBN 978-3-030-06164-7.
- [137] T. Denœux, D. Dubois and H. Prade, Representations of Uncertainty in AI: Probability and Possibility, in: *A Guided Tour of Artificial Intelligence Research: Volume I: Knowledge Representation, Reasoning and Learning*, P. Marquis, O. Papini and H. Prade, eds, Springer International Publishing, Cham, 2020, pp. 69–117. ISBN 978-3-030-06164-7.
- [138] R. Desislavov, F. Plumed and J. Hernandez-Orallo, *Compute and Energy Consumption Trends in Deep Learning Inference*, 2021.
- [139] A. Diamond and D.S. Ling, Conclusions about interventions, programs, and approaches for improving executive functions that appear justified and those that, despite much hype, do not, *Developmental Cognitive Neuroscience* **18** (2016), 34–48, Place: Netherlands Publisher: Elsevier Science.
- [140] A. Dietrich, The cognitive neuroscience of creativity, *Psychonomic Bulletin & Review* **11**(6) (2004), 1011–1026. <http://link.springer.com/10.3758/BF03196731>.
- [141] A. Dietrich and H. Haider, A Neurocognitive Framework for Human Creative Thought, *Frontiers in Psychology* **7** (2017), 2078.
- [142] P. Dillenbourg and J. Self, A Framework for Learner Modelling, *Interactive Learning Environments* **2**(2) (1992), 111–137.
- [143] Z. Djebbara, L.B. Fich, L. Petrini and K. Gramann, Sensorimotor brain dynamics reflect architectural affordances, *Proceedings of the National Academy of Sciences* **116**(29) (2019), 14769–14778.
- [144] M. Dojchinovski, J. Forberg, J. Frey, M. Hofer, D. Streitmatter and K. Yankov, The DBpedia Technology Tutorial, in: *Proceedings of the Workshops and Tutorials held at LDK 2021*, S. Carvalho, R.R. Souza, E. Daga, J. Gracia, B. Kabashi, I. Kernerman, A. Meroño-Peñuela, V. Presutti, S. Tonelli, R. Troncy, M.v. Erp and S. Žitnik, eds, CEUR Workshop Proceedings, Vol. 3064, CEUR, Zaragoza, Spain, 2021, pp. 221–228, ISSN: 1613-0073. <https://ceur-ws.org/Vol-3064/#DBpedia-Technology-tutorial>.
- [145] P. Domenech and E. Koechlin, Executive control and decision-making in the prefrontal cortex, *Current Opinion in Behavioral Sciences* **1** (2015), 101–106. <https://linkinghub.elsevier.com/retrieve/pii/S2352154614000278>.
- [146] P. Domingos, Unifying instance-based and rule-based induction, *Machine Language* **24**(2) (1996), 141–168.
- [147] I. Donadello, L. Serafini and A. d’Avila Garcez, Logic Tensor Networks for Semantic Image Interpretation, in: *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence*, International Joint Conferences on Artificial Intelligence Organization, Melbourne, Australia, 2017, pp. 1596–1602. ISBN 978-0-9992411-0-3. <https://www.ijcai.org/proceedings/2017/221>.
- [148] M. Donoso, Le cerveau stratège : les fondements du raisonnement dans le cortex préfrontal humain, PhD Thesis, 2013. <http://www.theses.fr/2013PA066535>.
- [149] G. Doriath-Döhler, Implémentation neuronale d’inférences logiques dans une SPA, Research report, in preparation, Inria Bordeaux Sud-Ouest, 2021.
- [150] G. Dowek, *Langues et langages : Ce dont on ne peut parler, il faut l’écrire*, Le pommier edn, 2019. ISBN 978-2-7465-1800-1. <https://www.editions-lepommier.fr/ce-dont-ne-peut-parler-il-faut-lecrire>.
- [151] K. Doya, K. Samejima, K.-i. Katagiri and M. Kawato, Multiple Model-Based Reinforcement Learning, *Neural Computation* **14**(6) (2002), 1347–1369, Number: 6.
- [152] G.P. Drago and S. Ridella, Possibility and Necessity Pattern Classification using an Interval Arithmetic Perceptron, *Neural Computing & Applications* **8**(1) (1999), 40–52.
- [153] W. Dubitzky, T. Kötter, O. Schmidt and M. Berthold, Towards Creative Information Exploration Based on Koestler’s Concept of Bisociation, in: *Bisociative Knowledge Discovery*, 2012, pp. 11–32, Journal Abbreviation: Bisociative Knowledge Discovery.
- [154] D. Dubois and H. Prade, Practical Methods for Constructing Possibility Distributions, *International Journal of Intelligent Systems* **vol. 31**(n° 3) (2015), pp. 215–239, Number: n° 3 Publisher: Wiley. <https://hal.archives-ouvertes.fr/hal-01538306>.
- [155] D. Dubois and H. Prade, Possibility Theory and Its Applications: Where Do We Stand?, in: *Springer Handbook of Computational Intelligence*, J. Kacprzyk and W. Pedrycz, eds, Springer Handbooks, Springer, Berlin, Heidelberg, 2015, pp. 31–60. ISBN 978-3-662-43505-2.
- [156] D. Dubois and H. Prade, Possibility Theory and Its Applications: Where Do We Stand?, in: *Springer Handbook of Computational Intelligence*, J. Kacprzyk and W. Pedrycz, eds, Springer Handbooks, Springer, Berlin, Heidelberg, 2015, pp. 31–60. ISBN 978-3-662-43505-2.
- [157] R.-E. Eastes, Processus d’apprentissage, savoirs complexes et traitement de l’information: un modèle théorique à l’usage des praticiens, entre sciences cognitives, didactique et philosophie des sciences., 330.
- [158] F.v. Ede, A.G. Board and A.C. Nobre, Goal-directed and stimulus-driven selection of internal representations, *Proceedings of the National Academy of Sciences* **117**(39) (2020), 24590–24598, Publisher: National Academy of Sciences Section: Biological Sciences. <https://www.pnas.org/content/117/39/24590>.
- [159] H. Eichenbaum, Memory: Organization and control, *Annual Review of Psychology* **68**(1) (2017), 19–45.
- [160] Z. Eidoon, N. Yazdani and F. Oroumchian, Ontology Matching Using Vector Space, in: *Advances in Information Retrieval*, C. Macdonald, I. Ounis, V. Plachouras, I. Ruthven and R.W. White, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2008, pp. 472–481. ISBN 978-3-540-78646-7.
- [161] N. Eisenberg, Prosocial Behavior, in: *Children’s needs III: Development, prevention, and intervention*, National Association of School Psychologists, Washington, DC, US, 2006, pp. 313–324. ISBN 978-0-932955-79-1.
- [162] A.M.A. Elfotouh, E.S. Nasr and M.H. Gheith, Towards A Comprehensive Serious Educational Games’ Ontology, in: *Proceedings of the 3rd Africa and Middle East Conference on Software Engineering*, ACM, Cairo Egypt, 2017, pp. 25–30. ISBN 978-1-4503-5512-4.
- [163] S. elia nadira, R. Omar and C.K.N. Hailma, Potential field methods and their inherent approaches for path planning **11** (2016), 10801–10805.

- [164] C. Eliasmith, *How to Build a Brain: A Neural Architecture for Biological Cognition*, OUP, USA, 2013, Google-Books-ID: BK0YRJPmuzgC. ISBN 978-0-19-979454-6.
- [165] C. Eliasmith and C.H. Anderson, *Neural Engineering: Computation, Representation, and Dynamics in Neurobiological Systems*, A Bradford Book, The MIT Press, 2002. <https://mitpress.mit.edu/books/neural-engineering>.
- [166] C. Eliasmith, T.C. Stewart, X. Choo, T. Bekolay, T. DeWolf, Y. Tang and D. Rasmussen, A Large-Scale Model of the Functioning Brain, *Science* **338**(6111) (2012), 1202–1205, Publisher: American Association for the Advancement of Science Section: Report. <https://science.sciencemag.org/content/338/6111/1202>.
- [167] Y. Engestrom, Activity theory as a framework for analyzing and redesigning work, *Ergonomics* **43**(7) (2000), 960–974.
- [168] Y. Engestrom, *Learning by Expanding: An Activity Theoretical Approach to Developmental Research.*, Orienta-Konsultit, Helsinki, 1987.
- [169] M. Eppe, C. Gumbsch, M. Kerzel, P.D.H. Nguyen, M.V. Butz and S. Wermter, Intelligent problem-solving as integrated hierarchical reinforcement learning, *Nature Machine Intelligence* **4**(1) (2022), 11–20, Number: 1 Publisher: Nature Publishing Group. <https://www.nature.com/articles/s42256-021-00433-9>.
- [170] H. Eriksson, Y. Shahar, S.W. Tu, A.R. Puerta and M.A. Musen, Task modeling with reusable problem-solving methods, *Artificial Intelligence* **79**(2) (1995), 293–326. <https://www.sciencedirect.com/science/article/pii/0004370294000409>.
- [171] G. Fauconnier and M. Turner, Conceptual Blending, Form and Meaning, *Recherches en Communication; No 19: Sémiotique cognitive — Cognitive Semiotics; 57-86* **19** (2003).
- [172] D. Fensel, E. Motta, S. Decker and Z. Zdrahal, Using ontologies for defining tasks, problem-solving methods and their mappings, in: *Knowledge Acquisition, Modeling and Management*, Vol. 1319, J.G. Carbonell, J. Siekmann, G. Goos, J. Hartmanis, J. van Leeuwen, E. Plaza and R. Benjamins, eds, Springer Berlin Heidelberg, Berlin, Heidelberg, 1997, pp. 113–128, Series Title: Lecture Notes in Computer Science. ISBN 978-3-540-63592-5 978-3-540-69606-3.
- [173] M. Fernández-López, A. Gómez-Pérez and N. Juristo, METHONTOLOGY: From Ontological Art Towards Ontological Engineering, in: *Proceedings of the Ontological Engineering AAAI-97 Spring Symposium Series*, Facultad de Informática (UPM), Stanford University, EEUU, 1997. <http://oa.upm.es/5484/>.
- [174] H.N.M. Ferreira, T. Brant-Ribeiro, R.D. Araujo, F.A. Dorca and R.G. Cattelan, An Automatic and Dynamic Student Modeling Approach for Adaptive and Intelligent Educational Systems Using Ontologies and Bayesian Networks, in: *2016 IEEE 28th International Conference on Tools with Artificial Intelligence (ICTAI)*, IEEE, San Jose, CA, USA, 2016, pp. 738–745. ISBN 978-1-5090-4459-7. <http://ieeexplore.ieee.org/document/7814676/>.
- [175] R. Fikes and T. Kehler, The role of frame-based representation in reasoning, *Communications of the ACM* **28**(9) (1985), 904–920.
- [176] B. Fischer, *Modal Epistemology: Knowledge of Possibility & Necessity*, 2018. <https://1000wordphilosophy.com/2018/02/13/modal-epistemology/>.
- [177] H. Flum and A. Kaplan, Exploratory Orientation as an Educational Goal (2006).
- [178] S. Forestier, R. Portelas, Y. Mollard and P.-Y. Oudeyer, Intrinsically Motivated Goal Exploration Processes with Automatic Curriculum Learning, *arXiv:1708.02190 [cs]* (2020), arXiv: 1708.02190. <http://arxiv.org/abs/1708.02190>.
- [179] J. Fraysinhes, Compétence, expérience, connaissances et savoirs transférables, *Éducation permanente* (2019), 43–54, Number: 218 Publisher: Arcueil : Éducation permanente. <https://hal.archives-ouvertes.fr/hal-02939062>.
- [180] C. Freksa, Strong Spatial Cognition, in: *Spatial Information Theory*, S.I. Fabrikant, M. Raubal, M. Bertolotto, C. Davies, S. Friendschuh and S. Bell, eds, Lecture Notes in Computer Science, Springer International Publishing, Cham, 2015, pp. 65–86. ISBN 978-3-319-23374-1.
- [181] K. Friston, Learning and inference in the brain, *Neural Networks: The Official Journal of the International Neural Network Society* **16**(9) (2003), 1325–1352.
- [182] K. Fuchs and P.A. Henning, Cognitive Space Time: A Model for Human-Centered Adaptivity in E-Learning, in: *2018 IEEE International Conference on Engineering, Technology and Innovation (ICE/ITMC)*, IEEE, Stuttgart, 2018, pp. 1–9. ISBN 978-1-5386-1469-3. <https://ieeexplore.ieee.org/document/8436283/>.
- [183] B. Galand, La motivation en situation d'apprentissage : les apports de la psychologie de l'éducation, *Revue française de pédagogie. Recherches en éducation* (2006), 5–8, ISBN: 9782734210474 Number: 155 Publisher: ENS Éditions. <http://journals.openedition.org/rfp/59>.
- [184] A.d. Garcez and L.C. Lamb, Neurosymbolic AI: The 3rd Wave, *arXiv:2012.05876 [cs]* (2020). <http://arxiv.org/abs/2012.05876>.
- [185] A.d. Garcez, A.R.R. Dutra and E. Alonso, Towards Symbolic Reinforcement Learning with Common Sense, *arXiv:1804.08597 [cs, stat]* (2018), arXiv: 1804.08597. <http://arxiv.org/abs/1804.08597>.
- [186] A.d. Garcez and L.C. Lamb, Neurosymbolic AI: the 3rd wave, *Artificial Intelligence Review* **0** (2023).
- [187] M. Garnelo, K. Arulkumaran and M. Shanahan, Towards Deep Symbolic Reinforcement Learning, *arXiv:1609.05518 [cs]* (2016), arXiv: 1609.05518. <http://arxiv.org/abs/1609.05518>.
- [188] B. Gaut, The Philosophy of Creativity, *Philosophy Compass* **5**(12) (2010), 1034–1046, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1111/j.1747-9991.2010.00351.x>.
- [189] R. Gayler, Vector Symbolic Architectures answer Jackendoff's challenges for cognitive neuroscience, in: *Frontiers in Artificial Intelligence and Applications*, 2003, ICCS/ASCS International Conference on Cognitive Science.
- [190] C. George, L'abduction et l'explication, in: *Polymorphisme du raisonnement humain*, Psychologie et sciences de la pensée, Presses Universitaires de France, Paris cedex 14, 1997, pp. 113–128. ISBN 978-2-13-048046-4. <https://www.cairn.info/polymorphisme-du-raisonnement-humain--9782130480464-p-113.htm>.
- [191] G. George and A.M. Lal, Review of ontology-based recommender systems in e-learning, *Computers & Education* **142** (2019), 103642. <https://www.sciencedirect.com/science/article/pii/S0360131519301952>.

- [192] S.J. Gershman and N.D. Daw, Reinforcement Learning and Episodic Memory in Humans and Animals: An Integrative Framework, *Annual Review of Psychology* **68**(1) (2017), 101–128.
- [193] S.J. Gershman, A.B. Markman and A.R. Otto, Retrospective revaluation in sequential decision making: A tale of two systems., *Journal of Experimental Psychology: General* **143**(1) (2014), 182–194.
- [194] J.J. Gibson, The theory of affordances, in: *Perceiving, acting, and knowing: toward an ecological psychology*, J.B. Robert E Shaw, ed., Hillsdale, N.J. : Lawrence Erlbaum Associates, 1977, pp. pp.67–82. <https://hal.archives-ouvertes.fr/hal-00692033>.
- [195] J.J. Gibson, *The Ecological Approach to Visual Perception: Classic Edition*, Psychology Press, 1979, Google-Books-ID: 8BSLBQAAQBAJ. ISBN 978-1-317-57938-0.
- [196] P. Gleeson, M. Cantarelli, B. Marin, A. Quintana, M. Earnshaw, S. Sadeh, E. Piasini, J. Birgiolas, R.C. Cannon, N.A. Cayco-Gajic, S. Crook, A.P. Davison, S. Dura-Bernal, A. Ecker, M.L. Hines, G. Idili, F. Lanore, S.D. Larson, W.W. Lytton, A. Majumdar, R.A. McDougal, S. Sivagnanam, S. Solinas, R. Stanislovas, S.J.v. Albada, W.v. Geit and R.A. Silver, Open Source Brain: A Collaborative Resource for Visualizing, Analyzing, Simulating, and Developing Standardized Models of Neurons and Circuits, *Neuron* **103**(3) (2019), 395–411.e5, Publisher: Elsevier. [https://www.cell.com/neuron/abstract/S0896-6273\(19\)30444-1](https://www.cell.com/neuron/abstract/S0896-6273(19)30444-1).
- [197] A. Glennerster, Computational theories of vision, *Current biology: CB* **12**(20) (2002), R682–685.
- [198] F. Gobet and G. Sala, How Artificial Intelligence Can Help Us Understand Human Creativity, *Frontiers in Psychology* **10** (2019). <https://www.frontiersin.org/article/10.3389/fpsyg.2019.01401>.
- [199] J.I. Gold and M.N. Shadlen, The Neural Basis of Decision Making, *Annual Review of Neuroscience* **30**(1) (2007), 535–574, Number: 1.
- [200] S. Goldman, La croyance : aux confins mystérieux de la cognition, *Cahiers de psychologie clinique* **25**(2) (2005), 87–109, Number: 2 Place: Louvain-la-Neuve Publisher: De Boeck Supérieur. <https://www.cairn.info/revue-cahiers-de-psychologie-clinique-2005-2-page-87.htm>.
- [201] A.S. Gordon and J.R. Hobbs, Formalizations of Commonsense Psychology, *AI Magazine* **25**(4) (2004), 49–49, Number: 4. <https://ojs.aaai.org/index.php/aimagazine/article/view/1784>.
- [202] J. Gosmann, An Integrated Model of Context, Short-Term, and Long-Term Memory, PhD Thesis, University of Waterloo (CA), 2018, Accepted: 2018-07-27T20:24:12Z Publisher: University of Waterloo. <https://uwspace.uwaterloo.ca/handle/10012/13498>.
- [203] J. Gosmann and C. Eliasmith, Vector-Derived Transformation Binding: An Improved Binding Operation for Deep Symbol-Like Processing in Neural Networks, *Neural Computation* **31**(5) (2019), 849–869.
- [204] J. Gottlieb, P.-Y. Oudeyer, M. Lopes and A. Baranes, Information-seeking, curiosity, and attention: computational and neural mechanisms, *Trends in Cognitive Sciences* **17**(11) (2013), 585–593, Number: 11. <https://linkinghub.elsevier.com/retrieve/pii/S1364661313002052>.
- [205] A. Goudyme, N. Chetcuti-Sperandio, S. Lagrue and T. De Lima, Intention et logique épistémique dynamique, in: *Rencontres des Jeunes Chercheurs en Intelligence Artificielle (RJCIA 2019)*, Toulouse, France, 2019, pp. 1–9. <https://hal.archives-ouvertes.fr/hal-02161427>.
- [206] V. Goutte and A.-M. Ergis, Traitement des émotions dans les pathologies neurodégénératives : une revue de la littérature, *Revue de neuropsychologie* **3**(3) (2011), 161–175, Number: 3 Place: Montrouge Publisher: John Libbey Eurotext. <https://www.cairn.info/revue-de-neuropsychologie-2011-3-page-161.htm>.
- [207] A. Graves, G. Wayne and I. Danihelka, Neural Turing Machines, *arXiv:1410.5401 [cs]* (2014), arXiv: 1410.5401. <http://arxiv.org/abs/1410.5401>.
- [208] S. Grimm and B. Motik, Closed World Reasoning in the Semantic Web through Epistemic Operators, 10.
- [209] G. Gris and C. Bengtson, Assessment Measures in Game-based Learning Research: A Systematic Review, *International Journal of Serious Games* **8** (2021), 3–26.
- [210] B.N. Grosz, I. Horrocks, R. Volz and S. Decker, Description logic programs: combining logic programs with description logic, in: *Proceedings of the 12th international conference on World Wide Web, WWW '03*, Association for Computing Machinery, New York, NY, USA, 2003, pp. 48–57. ISBN 978-1-58113-680-7.
- [211] A. Gruszka and M. Tang, The 4P's Creativity Model and its application in different fields., in: *Handbook of the Management of Creativity and Innovation*, World Scientific Press, 2017, pp. 51–71. ISBN 978-981-314-187-2.
- [212] N. Guarino, BFO and DOLCE: So Far, So Close... **4**(4) (2017), 9.
- [213] N. Guarino and C. Welty, Evaluating ontological decisions with ontoclean, *Communications of the ACM* **45** (2002), 61–65.
- [214] N. Guarino and C. Welty, An Overview of OntoClean, 2009, pp. 201–220.
- [215] N. Guberman, On Complex Valued Convolutional Neural Networks, *arXiv:1602.09046 [cs]* (2016), arXiv: 1602.09046. <http://arxiv.org/abs/1602.09046>.
- [216] J. Guggemos, On the predictors of computational thinking and its growth at the high-school level, *Computers & Education* **161** (2021), 104060. <http://www.sciencedirect.com/science/article/pii/S036013152030258X>.
- [217] J.P. Guilford, *The nature of human intelligence*, The nature of human intelligence, McGraw-Hill, New York, NY, US, 1967.
- [218] S. Guo, Q. Wang, L. Wang, B. Wang and L. Guo, Jointly Embedding Knowledge Graphs and Logical Rules, in: *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, Association for Computational Linguistics, Austin, Texas, 2016, pp. 192–202. <https://aclanthology.org/D16-1019>.
- [219] A.K. Gupta, K.G. Smith and C.E. Shalley, The Interplay Between Exploration and Exploitation, *Academy of Management Journal* **49**(4) (2006), 693–706, Number: 4.
- [220] P. Gärdenfors, Conceptual spaces as a framework for knowledge representation, *Mind and Matter* **2** (2004), 9–27.
- [221] J. Han, F. Shi, L. Chen and P.R.N. Childs, A computational tool for creative idea generation based on analogical reasoning and ontology, *Artificial Intelligence for Engineering Design, Analysis and Manufacturing* **32**(4) (2018), 462–477. https://www.cambridge.org/core/product/identifier/S0890060418000082/type/journal_article.

- [222] V.G. Hardcastle and K. Hardcastle, Marr's Levels Revisited: Understanding How Brains Break, *Topics in Cognitive Science* **7**(2) (2015), 259–273, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1111/tops.12130>.
- [223] E. Harmon-Jones, T. Gerdjikov and C. Harmon-Jones, The effect of induced compliance on relative left frontal cortical activity: a test of the action-based model of dissonance, *European Journal of Social Psychology* **38**(1) (2008), 35–45, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/ejsp.399>.
- [224] S. Harnad, The symbol grounding problem, *Physica D: Nonlinear Phenomena* **42**(1) (1990), 335–346. <https://www.sciencedirect.com/science/article/pii/0167278990900876>.
- [225] A. Haro, I. Essa and M. Flickner, A non-invasive computer vision system for reliable eye tracking, in: *CHI '00 Extended Abstracts on Human Factors in Computing Systems*, CHI EA '00, Association for Computing Machinery, New York, NY, USA, 2000, pp. 167–168. ISBN 978-1-58113-248-9.
- [226] J. Harris, Deep reinforcement learning, symbolic learning and the road to AGI, 2020. <https://towardsdatascience.com/language-models-symbolic-learning-and-the-road-to-agi-75725985cdf7>.
- [227] J. Hastings, W. Ceusters, M. Jensen, K. Mulligan and B. Smith, Representing Mental Functioning: Ontologies for Mental Health and Disease, in: *Towards an Ontology of Mental Functioning, Third International Conference on Biomedical Ontology*, Graz, 2012. <https://www.semanticscholar.org/paper/Representing-Mental-Functioning%3A-Ontologies-for-and-Hastings-Ceusters/b65a0ab5fdf277fcdf782ca59ac4bd510159d31b>.
- [228] L. Heiser, M. Romero and V. Prokofieva Nelson, Analyse des activités technocréatives au collège en contexte d'éducation FabLab, Technical Report, Université Côte d'Azur, 2022.
- [229] A. Herbert, *The Pedagogy of Creativity*, Routledge, London, 2010. ISBN 978-0-203-85546-1.
- [230] A. Hieronymi, Creativity from a systems perspective: Bridging theory and practice, *Kybernetes: The International Journal of Systems & Cybernetics* **42** (2013).
- [231] M. Hilario, C. Pellegrini and F. Alexandre, Modular Integration of Connectionist and Symbolic Processing in Knowledge-Based Systems, in: *In Proceedings of the International Symposium on Integrating Knowledge and Neural Heuristics*, Morgan-Kaufmann, 1994, pp. 123–132.
- [232] V. Hoareau, Etudes des mécanismes de maintien en mémoire de travail chez les personnes jeunes et âgées : approches computationnelle et comportementale basées sur les modèles TBRS* et SOB-CS, phdthesis, Université Grenoble Alpes, 2017. <https://tel.archives-ouvertes.fr/tel-01746120>.
- [233] R. Hoekstra, Ontology Representation - Design Patterns and Ontologies that Make Sense, *Frontiers in Artificial Intelligence and Applications* (2009), IOS Press is an international science, technical and medical publisher of high-quality books for academics, scientists, and professionals in all fields. Some of the areas we publish in: -Biomedicine -Oncology -Artificial intelligence -Databases and information systems -Maritime engineering -Nanotechnology -Geoengineering -All aspects of physics -E-governance -E-commerce -The knowledge economy -Urban studies -Arms control -Understanding and responding to terrorism -Medical informatics -Computer Sciences.
- [234] C. Hoffmann, The influence of different forms of camera surveillance and personality characteristics on deviant and prosocial behaviour, 2011, Publisher: University of Twente. <https://essay.utwente.nl/61250/>.
- [235] P. Hohenecker and T. Lukasiewicz, Ontology Reasoning with Deep Neural Networks, *Journal of Artificial Intelligence Research* **68** (2020), arXiv: 1808.07980. <http://arxiv.org/abs/1808.07980>.
- [236] J. Holt, Two Brains Running, *The New York Times* (2011), Chapter Books. <https://www.nytimes.com/2011/11/27/books/review/thinking-fast-and-slow-by-daniel-kahneman-book-review.html>.
- [237] B. Hommel and R.W. Wiers, Towards a Unitary Approach to Human Action Control, *Trends in Cognitive Sciences* **21**(12) (2017), 940–949. <https://www.sciencedirect.com/science/article/pii/S1364661317301973>.
- [238] D. Hooshyar, M. Pedaste, K. Saks, E. Bardone and M. Wang, Open learner models in supporting self-regulated learning in higher education: A systematic literature review, *Computers & Education* **154** (2020), 103878. <https://linkinghub.elsevier.com/retrieve/pii/S0360131520300774>.
- [239] M. Horridge, A Practical Guide To Building OWL Ontologies Using Protégé 4 and CO-ODE Tools Edition 1.3, 2011.
- [240] H.J.t. Horst, Completeness, Decidability and Complexity of Entailment for RDFSchema and a Semantic Extension Involving the OWL Vocabulary, *Journal of Web Semantics* **3**(2–3) (2005), 79–115. <https://papers.ssrn.com/abstract=3199251>.
- [241] O. Houdé, *Le raisonnement*, Que sais-je ?, Vol. 2e éd., Presses Universitaires de France, Paris cedex 14, 2018. ISBN 978-2-13-080389-8. <https://www.cairn.info/le-raisonnement--9782130803898.htm>.
- [242] O. Houdé, *La Psychologie de l'enfant*, Que sais-je ?, Vol. 9e éd., Presses Universitaires de France, Paris cedex 14, 2020. ISBN 978-2-7154-0489-2. <https://www.cairn.info/la-psychologie-de-l-enfant--9782715404892.htm>.
- [243] W. Huang and C.-K. Looi, A critical review of literature on “unplugged” pedagogies in K-12 computer science and computational thinking education, *Computer Science Education* **0**(0) (2020), 1–29, Publisher: Routledge _eprint: <https://doi.org/10.1080/08993408.2020.1789411>.
- [244] Y.-C. Hung, The Effect of Problem-Solving Instruction on Computer Engineering Majors' Performance in Verilog Programming, *IEEE Transactions on Education* **51**(1) (2008), 131–137. Conference Name: IEEE Transactions on Education.
- [245] E.L. Hutchins, J.D. Hollan and D.A. Norman, Direct Manipulation Interfaces, 28.
- [246] H. Ishibuchi, R. Fujioka and H. Tanaka, Possibility and necessity pattern classification using neural networks, *Fuzzy Sets and Systems* **48**(3) (1992), 331–340. <https://www.sciencedirect.com/science/article/pii/0165011492903488>.

- [247] L. Jamone, E. Ugur, A. Cangelosi, L. Fadiga, A. Bernardino, J. Piater and J. Santos-Victor, Affordances in Psychology, Neuroscience, and Robotics: A Survey, *IEEE Transactions on Cognitive and Developmental Systems* **10**(1) (2016), 4–25. <http://ieeexplore.ieee.org/document/7523298/>.
- [248] K. Janowicz and M. Compton, The Stimulus-Sensor-Observation Ontology Design Pattern and its Integration into the Semantic Sensor Network Ontology, in: *Proceedings of the 3rd International Conference on Semantic Sensor Networks - Volume 668*, SSN'10, CEUR-WS.org, Aachen, DEU, 2010, pp. 64–78.
- [249] A.M. Jansen, E. Giebels, T.J.L. van Rompay and M. Junger, The Influence of the Presentation of Camera Surveillance on Cheating and Pro-Social Behavior, *Frontiers in Psychology* **9** (2018). <https://www.frontiersin.org/article/10.3389/fpsyg.2018.01937>.
- [250] A. Jiménez, B. Elizalde and B. Raj, Sound event classification using ontology-based neural networks, in: *Proceedings of the Annual Conference on Neural Information Processing Systems*, 2018, p. 9.
- [251] D.W. Johnson, R.T. Johnson and E.J. Holubec, *The New Circles of Learning: Cooperation in the Classroom and School*, ASCD, 1994, Google-Books-ID: jZVRDwAAQBAJ. ISBN 978-0-87120-227-7.
- [252] P.N. Johnson-Laird, P. Legrenzi, V. Girotto, M.S. Legrenzi and J.P. Caverni, Naive probability: a mental model theory of extensional reasoning, *Psychological Review* **106**(1) (1999), 62–88.
- [253] P.N. Johnson-Laird, Analogy and the exercise of creativity, in: *Similarity and analogical reasoning*, Cambridge University Press, New York, NY, US, 1989, pp. 313–331. ISBN 978-0-521-36295-5 978-0-521-38935-8.
- [254] P.N. Johnson-Laird and M. Ragni, Possibilities as the foundation of reasoning, *Cognition* **193** (2019), 103950. <https://linkinghub.elsevier.com/retrieve/pii/S0010027719301039>.
- [255] R. Jung, B. Mead, J. Carrasco and R. Flores, The structure of creative cognition in the human brain, *Frontiers in Human Neuroscience* **7** (2013), 330.
- [256] D. Kahneman, *Thinking, Fast and Slow*, Farrar, Straus and Giroux, 2011.
- [257] I. Kajić, J. Gosmann, T.C. Stewart, T. Wennekers and C. Eliasmith, A Spiking Neuron Model of Word Associations for the Remote Associates Test, *Frontiers in Psychology* **8** (2017), 99.
- [258] G. Kalmipourtzis, A definition of educational games, 2020. <https://georgekalmipourtzis.com/a-definition-of-educational-games/>.
- [259] G. Kalmipourtzis and M. Romero, Artifactual Affordances in Playful Robotics, in: *International Conference on Games and Learning Alliance*, I. Marfisi-Schottman, F. Bellotti, L. Hamon and R. Klemke, eds, Lecture Notes in Computer Science, Springer International Publishing, Cham, 2020, pp. 316–325. ISBN 978-3-030-63464-3.
- [260] D. Kao, The effects of observation in video games: how remote observation influences player experience, motivation, and behaviour, *Behaviour & Information Technology* **0**(0) (2021), 1–23, Publisher: Taylor & Francis _eprint: <https://doi.org/10.1080/0144929X.2021.1906321>.
- [261] A. Kaplan and H. Flum, Achievement goal orientations and identity formation styles, *Educational Research Review* **5**(1) (2010), 50–67. <https://www.sciencedirect.com/science/article/pii/S1747938X09000347>.
- [262] N. Kapoor and N. Bahl, Comparative Study Of Forward And Backward Chaining In Artificial Intelligence, *International Journal of Engineering and Computer Science* (2016).
- [263] V. Kaptelinin, Activity Theory: Implications for Human-Computer Interaction, *Context and consciousness: Activity theory and human-computer interaction* (1996), 102–116.
- [264] A.E. Kazdin, Single-Case Research Designs - Methods for clinical and applied settings, 1982, Cc: cz Lang: en Tab: overview. //global.oup.com/ushe/product/single-case-research-designs-9780190079970.
- [265] L.A. Keefer and M.J. Landau, Metaphor and analogy in everyday problem solving, *WIREs Cognitive Science* **7**(6) (2016), 394–405.
- [266] Y.N. Kenett and M. Faust, A Semantic Network Cartography of the Creative Mind, *Trends in Cognitive Sciences* **23**(4) (2019), 271–274. <https://www.sciencedirect.com/science/article/pii/S1364661319300245>.
- [267] R. Khalil and A.A. Moustafa, A neurocomputational model of creative processes, *Neuroscience & Biobehavioral Reviews* **137** (2022), 104656. <https://www.sciencedirect.com/science/article/pii/S0149763422001452>.
- [268] I. Khanfir Kallel, Mécanismes de raisonnement possibiliste pour l'aide à la décision et l'interprétation de scènes, Habilitation à diriger des recherches, Ecole Nationale des Ingénieurs de Sfax, Université de Sfax, 2019. <https://hal.archives-ouvertes.fr/tel-02868499>.
- [269] S.S. Khemlani, A.K. Barbey and P.N. Johnson-Laird, Causal reasoning with mental models, *Frontiers in Human Neuroscience* **8** (2014).
- [270] S.S. Khemlani, M. Lotstein and P.N. Johnson-Laird, Naive probability: Model-based estimates of unique events, *Cognitive Science* **39**(6) (2015), 1216–1258, Place: United Kingdom Publisher: Wiley-Blackwell Publishing Ltd.
- [271] J. Kilpatrick, J. Swafford and B. Findell, *Adding it up: Helping children learn mathematics*, Citeseer, 2002.
- [272] A.J. King, N. Bol, R.G. Cummins and K.K. John, Improving Visual Behavior Research in Communication Science: An Overview, Review, and Reporting Recommendations for Using Eye-Tracking Methods, *Communication Methods and Measures* **13**(3) (2019), 149–177, Publisher: Routledge _eprint: <https://doi.org/10.1080/19312458.2018.1558194>.
- [273] P. Kitcher, Marr's Computational Theory of Vision, *Philosophy of Science* **55**(1) (1988), 1–24, Publisher: [The University of Chicago Press, Philosophy of Science Association]. <https://www.jstor.org/stable/187817>.
- [274] E. Koechlin, An evolutionary computational theory of prefrontal executive function in decision-making, *Philosophical Transactions of the Royal Society of London. Series B, Biological Sciences* **369**(1655) (2014), 20130474.
- [275] B. Komer, T.C. Stewart, A.R. Voelker and C. Eliasmith, A neural representation of continuous space using fractional binding, in: *41st Annual Meeting of the Cognitive Science Society*, Cognitive Science Society, Montreal, Canada, 2019, p. 6. <http://compneuro.uwaterloo.ca/publications/komer2019.html>.
- [276] Y. Kotseruba, O. Avella and J. Tsotsos, A Review of 40 Years of Cognitive Architecture Research: Focus on Perception, Attention, Learning and Applications (2016).

- [277] J. Kounios and M. Beeman, The Cognitive Neuroscience of Insight, *Annual review of psychology* **65** (2014), 71–93. 1
- [278] I. Krajbich and A. Rangel, Multialternative drift-diffusion model predicts the relationship between visual fixations and choice in value-based decisions, *Proceedings of the National Academy of Sciences* **108**(33) (2011), 13852–13857, Number: 33. 2
- [279] E. Kupers, A. Lehmann-Wermser, G. McPherson and P. van Geert, Children’s Creativity: A Theoretical Framework and Systematic Review, *Review of Educational Research* **89**(1) (2019), 93–124, Publisher: American Educational Research Association. 3
- [280] E. Kurilovas and A. Juskeviciene, Creation of Web 2.0 tools ontology to improve learning, *Computers in Human Behavior* **51** (2015), 1380–1386. <https://linkinghub.elsevier.com/retrieve/pii/S0747563214005494>. 4
- [281] S. Kurt, TPACK: Technological Pedagogical Content Knowledge Framework, 2018. <https://educationaltechnology.net/technological-pedagogical-content-knowledge-tpack-framework/>. 5
- [282] J. Kwisthout, Relevancy in Problem Solving: A Computational Framework, *The Journal of Problem Solving* **5**(1) (2012). <https://docs.lib.purdue.edu/jps/vol5/iss1/4>. 6
- [283] J.-P. Lachaux, Éduquer la métacognition, la clé du succès pour les enfants! (2018), 3. 7
- [284] J. Laird, P. Rosenbloom and A. Newell, Soar - A General Problem-Solving Architecture, in: *Universal Subgoaling and Chunking: The Automatic Generation and Learning of Goal Hierarchies*, J. Laird, P. Rosenbloom and A. Newell, eds, The Kluwer International Series in Engineering and Computer Science, Springer US, Boston, MA, 1986, pp. 286–288. ISBN 978-1-4613-2277-1. 8
- [285] J. Laird, P. Rosenbloom and A. Newell, Soar—A General Problem-Solving Architecture, in: *Universal Subgoaling and Chunking: The Automatic Generation and Learning of Goal Hierarchies*, J. Laird, P. Rosenbloom and A. Newell, eds, The Kluwer International Series in Engineering and Computer Science, Springer US, Boston, MA, 1986, pp. 286–288. ISBN 978-1-4613-2277-1. 9
- [286] J.E. Laird, C. Lebiere and P.S. Rosenbloom, A Standard Model of the Mind: Toward a Common Computational Framework across Artificial Intelligence, Cognitive Science, Neuroscience, and Robotics, *AI Magazine* **38**(4) (2017), 13–26. <https://ojs.aaai.org/index.php/aimagazine/article/view/2744>. 10
- [287] J.E. Laird, C.B. Congdon, M. Assanie, N. Derbinsky and J. Xu, The Soar User’s Manual Version 9.6.0, 313. 11
- [288] B.M. Lake, T.D. Ullman, J.B. Tenenbaum and S.J. Gershman, Building machines that learn and think like people, *Behavioral and Brain Sciences* **40** (2017), e253. https://www.cambridge.org/core/product/identifier/S0140525X16001837/type/journal_article. 12
- [289] S.K. Lakkaraju and Y. Zhang, Rule Based Abduction, in: *Proceedings of the 12th International Symposium on Foundations of Intelligent Systems, ISMIS ’00*, Springer-Verlag, Berlin, Heidelberg, 2000, pp. 525–533. ISBN 978-3-540-41094-2. 13
- [290] Y. Lallement, M. Hilario and F. Alexandre, Neurosymbolic Integration: Cognitive Grounds and Computational Strategies, in: *Proceedings World Conference on the Fundamentals of Artificial Intelligence*, 1995, p. 12. 14
- [291] L.C. Lamb, R.V. Borges and A.S. d’Avila Garcez, A connectionist cognitive model for temporal synchronisation and learning, in: *Proceedings of the 22nd national conference on Artificial intelligence - Volume 1, AAAI’07*, AAAI Press, Vancouver, British Columbia, Canada, 2007, pp. 827–832. ISBN 978-1-57735-323-2. 15
- [292] B. Latané and S. Wolf, The social impact of majorities and minorities, *Psychological Review* **88**(5) (1981), 438–453, Place: US Publisher: American Psychological Association. 16
- [293] N. Law, S. Järvelä and C. Rosé, Exploring multilayered collaboration designs, *International Journal of Computer-Supported Collaborative Learning* **16**(1) (2021), 1–5. 17
- [294] Y. Le Franc, A.P. Davison, P. Gleeson, F.T. Imam, B. Kriener, S.D. Larson, S. Ray, L. Schwabe, S. Hill and E. De Schutter, Computational Neuroscience Ontology: a new tool to provide semantic meaning to your models, *BMC Neuroscience* **13**(1) (2012), P149. 18
- [295] D. Le Gall, J. Besnard, V. Havet, K. Pinon and P. Allain, Contrôle exécutif, cognition sociale, émotions et métacognition, *Revue de neuropsychologie* **1**(1) (2009), 24, Number: 1. <http://www.cairn.info/revue-de-neuropsychologie-2009-1-page-24.htm?ref=doi>. 19
- [296] A. Lebis, M. Lefevre, V. Luengo and N. Guin, Recherche intelligente de processus d’analyse de traces d’e-learning via des inférences sémantiques, in: *Journées francophones d’Ingénierie des Connaissances (IC)*, Toulouse, France, 2019. <https://hal.archives-ouvertes.fr/hal-02155496>. 20
- [297] S. Leblanc and C. Gaudin, Exploiter les corpus vidéo à des fins de recherche : innovations méthodologiques et effets sur les pratiques en sciences de l’éducation, *Éducation et socialisation. Les Cahiers du CERFEE* (2020), Number: 55 Publisher: Presses universitaires de la méditerranée. <http://journals.openedition.org/edso/9034>. 21
- [298] M. Lengyel and P. Dayan, Hippocampal Contributions to Control: The Third Way, 8. 22
- [299] A. Leroy, M. Romero and L. Cassone, Interactivity and materiality matter in creativity: educational robotics for the assessment of divergent thinking, *Interactive Learning Environments* **0**(0) (2021), 1–12, Publisher: Routledge _eprint: <https://doi.org/10.1080/10494820.2021.1875005>. 23
- [300] H.J. Levesque, Knowledge Representation and Reasoning, *Annual Review of Computer Science* **1**(1) (1986), 255–287, Publisher: Annual Reviews. 24
- [301] D.J. Levy and P.W. Glimcher, The root of all value: a neural common currency for choice, *Current opinion in neurobiology* **22**(6) (2012), 1027–1038. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4093837/>. 25
- [302] S.D. Levy and R. Gayler, Vector Symbolic Architectures: A New Building Material for Artificial General Intelligence, in: *Frontiers in Artificial Intelligence and Applications*, 2008, p. 6. 26
- [303] M. Lhuiller and I. Chraïbi Kaadoud, Interprétabilité, biais, éthique et transparence : quelles relations ? (3/3), 2020. <http://www.scilogs.fr/intelligence-mecanique/interpretabilite-biais-ethique-et-transparence-queles-relations-3-3/>. 27
- [304] M. Lhuiller and I. Chraïbi Kaadoud, Interprétabilité vs explicabilité : comprendre vs expliquer son réseau de neurones (1/3), 2020. <http://www.scilogs.fr/intelligence-mecanique/interpretabilite-vs-explicabilite-comprendre-vs-expliquer-son-reseau-de-neurone-1-3/>. 28

- [305] M. Lhuiller and I. Chraïbi Kaadoud, Interprétabilité vs explicabilité : l'interprétabilité selon différentes approches (2/3), 2020. <http://www.scilogs.fr/intelligence-mecanique/interpretabilite-vs-explicabilite-linterpretabilite-selon-differentes-approches-2-3/>.
- [306] A. Lieto and G.L. Pozzato, A description logic framework for commonsense conceptual combination integrating typicality, probabilities and cognitive heuristics, *Journal of Experimental & Theoretical Artificial Intelligence* **32**(5) (2020), 769–804, Publisher: Taylor & Francis _eprint: <https://doi.org/10.1080/0952813X.2019.1672799>.
- [307] A. Lieto, F. Perrone, G.L. Pozzato and E. Chiodino, Beyond subgoalng: A dynamic knowledge generation framework for creative problem solving in cognitive architectures, *Cognitive Systems Research* **58** (2019), 305–316. <https://www.sciencedirect.com/science/article/pii/S1389041719304632>.
- [308] A. Lieury and L. Léger, *Introduction à la psychologie cognitive*, Psycho Sup, Vol. 2e ed., Dunod, Paris, 2020. ISBN 978-2-10-080186-2. <https://www.cairn.info/introduction-a-la-psychologie-cognitive--9782100801862.htm>.
- [309] D. Liu, K. Jiang, C.E. Shalley, S. Keem and J. Zhou, Motivational mechanisms of employee creativity: A meta-analytic examination and theoretical extension of the creativity literature, *Organizational Behavior and Human Decision Processes* **137** (2016), 236–263. <https://www.sciencedirect.com/science/article/pii/S0749597816304794>.
- [310] M. Lodi, Introducing Computational Thinking in K-12 Education: Historical, Epistemological, Pedagogical, Cognitive, and Affective Aspects, phdthesis, Dipartimento di Informatica - Scienza e Ingegneria, Alma Mater Studiorum - Università di Bologna, 2020. <https://hal.inria.fr/tel-02981951>.
- [311] C. Luce and J.P. Kirnan, Using Indirect vs. Direct Measures in the Summative Assessment of Student Learning in Higher Education, *Journal of the Scholarship of Teaching and Learning* **16**(4) (2016), 75–91, Number: 4. <https://scholarworks.iu.edu/journals/index.php/josotl/article/view/19371>.
- [312] Z. Ma, Y. Zhuang, P. Weng, D. Li, K. Shao, W. Liu, H.H. Zhuo and J. Hao, Interpretable Reinforcement Learning With Neural Symbolic Logic, *ICLR 2021 Ninth International Conference on Learning Representations* (2020). https://openreview.net/forum?id=M_gk451txIp.
- [313] G. Mandler, From Association to Organization, *Current Directions in Psychological Science* **20**(4) (2011), 232–235, Publisher: SAGE Publications Inc.
- [314] J. Mandler, The spatial foundations of the conceptual system, *Language and Cognition* **2** (2010).
- [315] R.S. Mansfield, T.V. Busse and E.J. Krepelka, The Effectiveness of Creativity Training, *Review of Educational Research* **48**(4) (1978), 517–536, Publisher: American Educational Research Association.
- [316] J.G. March, Exploration and Exploitation in Organizational Learning, *Organization Science* **2**(1) (1991), 71–87, Publisher: INFORMS. <https://www.jstor.org/stable/2634940>.
- [317] G. Markowski, Types et rôle de la mémoire humaine, Technical Report.
- [318] P. Marquis, O. Papini and H. Prade, Chapitre 3 : Représentation de l'incertitude en intelligence artificielle, in: *Représentation des connaissances et formalisation des raisonnements*, Cepadues edn, Panorama de l'intelligence artificielle, Vol. 1, 2014. ISBN 978-2-36493-041-4. <https://www.cepadues.com/livres/representation-des-connaissances-formalisation-des-raisonnements-volume-1serie-panorama-intelligence-artificielle-9782364930414.html>.
- [319] S. Masmoudi and A. Naceur, *Du percept à la décision. Intégration de la cognition, l'émotion et la motivation*, Neurosciences & cognition, De Boeck Supérieur, Louvain-la-Neuve, 2010. ISBN 978-2-8041-3798-4. <https://www.cairn.info/du-percept-a-la-decision--9782804137984.htm>.
- [320] C. Masolo, S. Borgo, A. Gangemi, N. Guarino and A. Oltramari, Wonderweb deliverable d18: Ontology library, Technical report, IST-2001-33052 del-18, Laboratory For Applied Ontology - ISTC-CNR, Trento, Italy, 2003.
- [321] F. Math, *Neurosciences cliniques. De la perception aux troubles du comportement*, Neurosciences & cognition, De Boeck Supérieur, Louvain-la-Neuve, 2008. ISBN 978-2-8041-5672-5. <https://www.cairn.info/neurosciences-cliniques--9782804156725.htm>.
- [322] S. Matthiesen, M. Meboldt, A. Ruckpaul and M. Mussnug, Eye tracking, a method for engineering design research on engineers' behavior while analyzing technical systems, *DS 75-7: Proceedings of the 19th International Conference on Engineering Design (ICED13), Design for Harmonies, Vol.7: Human Behaviour in Design, Seoul, Korea, 19-22.08.2013* (2013), 277–286, ISBN: 9781904670506. <https://www.designsociety.org/publication/34592/Eye+tracking%2C+a+method+for+engineering+design+research+on+engineers%27+behavior+while+analyzing+technical+systems>.
- [323] L. McCay-Peet and E.G. Toms, Investigating serendipity: How it unfolds and what may influence it, *Journal of the Association for Information Science and Technology* **66**(7) (2015), 1463–1476, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/asi.23273>.
- [324] J.L. McClelland and T.T. Rogers, The parallel distributed processing approach to semantic cognition, *Nature Reviews Neuroscience* **4**(4) (2003), 310–322. <http://www.nature.com/articles/nrn1076>.
- [325] T.S. McNeerney, From turtles to Tangible Programming Bricks: explorations in physical language design, *Personal and Ubiquitous Computing* **8**(5) (2004), 326–337.
- [326] S. Mednick, The associative basis of the creative process., *Psychological review* (1962).
- [327] S.A. Mednick, The Remote Associates Test*, *The Journal of Creative Behavior* **2**(3) (1968), 213–214, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/j.2162-6057.1968.tb00104.x>.
- [328] V. Mekern, B. Hommel and Z. Sjoerds, Computational models of creativity: a review of single-process and multi-process recent approaches to demystify creative cognition, *Current Opinion in Behavioral Sciences* **27** (2019), 47–54. <https://www.sciencedirect.com/science/article/pii/S2352154618301256>.
- [329] D. Menon, S. Bp, M. Romero and T. Viéville, *Going beyond digital literacy to develop computational thinking in K-12 education*, Taylor&Francis (Routledge), 2019. ISBN 978-0-367-33379-9. <https://hal.inria.fr/hal-02281037>.

- [330] C. Mercier, An Ontology to Formalize a Creative Problem Solving Activity, *IEEE Transactions on Cognitive and Developmental Systems* (2022), 1–1, Conference Name: IEEE Transactions on Cognitive and Developmental Systems.
- [331] C. Mercier and T. Vieville, Creative problem solving with tangible artifacts: an overview of computational cognitive frameworks, in: *23rd International Conference on Artificial Intelligence in Education*, Dunham, UK, 2022, submitted.
- [332] C. Mercier, F. Alexandre and T. Viéville, Reinforcement Symbolic Learning, in: *Artificial Neural Networks and Machine Learning – ICANN 2021*, I. Farkaš, P. Masulli, S. Otte and S. Wermter, eds, Lecture Notes in Computer Science, Springer International Publishing, Bratislava, Slovakia, 2021, pp. 608–612. ISBN 978-3-030-86380-7.
- [333] C. Mercier, F. Alexandre and T. Viéville, Ontology as manifold: towards symbolic and numerical artificial embedding, in: *Workshop on VSA and hyperdimensional computing - Winter 2022 session*, 2022. <https://hal.inria.fr/hal-03550354>.
- [334] C. Mercier, L. Roux, M. Romero, F. Alexandre and T. Viéville, Formalizing Problem Solving in Computational Thinking : an Ontology approach, in: *2021 IEEE International Conference on Development and Learning (ICDL)*, Beijing, China, 2021, pp. 1–8.
- [335] C. Mercier, H. Chateau-Laurent, F. Alexandre and T. Viéville, Ontology as neuronal-space manifold: Towards symbolic and numerical artificial embedding, in: *KRHCAL-21@KR2021*, 2021.
- [336] C. Mercier, M. Romero, F. Alexandre and T. Vieville, An ontology to formalize a creative problem solving task, *IEEE Transactions on Cognitive and Developmental Systems* **Submitted** (2022).
- [337] J. Metcalfe and D. Wiebe, Intuition in insight and noninsight problem solving, *Memory & Cognition* **15**(3) (1987), 238–246.
- [338] T. Mikolov, K. Chen, G. Corrado and J. Dean, Efficient Estimation of Word Representations in Vector Space, *arXiv:1301.3781 [cs]* (2013), arXiv: 1301.3781. <http://arxiv.org/abs/1301.3781>.
- [339] B. Milivojevic, A. Vicente-Grabovetsky and C. Doeller, Insight Reconfigures Hippocampal-Prefrontal Memories, *Current Biology* **25**(7) (2015), 821–830. <https://linkinghub.elsevier.com/retrieve/pii/S0960982215000652>.
- [340] K.J. Miller, E.A. Ludvig, G. Pezzulo and A. Shenhav, Realigning Models of Habitual and Goal-Directed Decision-Making, in: *Goal-Directed Decision Making*, R. Morris, A. Bornstein and A. Shenhav, eds, Academic Press, 2018, pp. 407–428. ISBN 978-0-12-812098-9. <http://www.sciencedirect.com/science/article/pii/B9780128120989000188>.
- [341] A.D. Milner and M.A. Goodale, Two visual systems re-viewed, *Neuropsychologia* **46**(3) (2008), 774–785. <https://www.sciencedirect.com/science/article/pii/S0028393207003545>.
- [342] S. Modeste, S. Beauvoir, J. Chappelon, V. Durand-Guerrier, N. León and A. Meyer, Proof, reasoning and logic at the interface between Mathematics and Computer Science : toward a framework for analyzing problem solving, in: *CERME 10*, T. Dooley and G. Gueudet, eds, DCU Institute of Education, Dublin, Ireland, 2017, pp. 1634–1641. <https://hal.archives-ouvertes.fr/hal-02398483>.
- [343] T.M. Moerland, J. Broekens and C.M. Jonker, Model-based Reinforcement Learning: A Survey, *arXiv:2006.16712 [cs, stat]* (2020), arXiv: 2006.16712. <http://arxiv.org/abs/2006.16712>.
- [344] G. Molnár, S. Greiff and B. Csapó, Inductive reasoning, domain specific and complex problem solving: Relations and development, *Thinking skills and Creativity* **9** (2013), 35–45, Publisher: Elsevier.
- [345] I. Momennejad and M.W. Howard, Predicting the Future with Multi-scale Successor Representations, preprint, Neuroscience, 2018.
- [346] A. Moors, C. Fini, T. Everaert, L. Bardi, E. Bossuyt, P. Kuppens and M. Brass, The role of stimulus-driven versus goal-directed processes in fight and flight tendencies measured with motor evoked potentials induced by Transcranial Magnetic Stimulation, *PLOS ONE* **14**(5) (2019), e0217266.
- [347] S. Morgagni, Repenser la notion d’affordance dans ses dynamiques sémiotiques, *Intellectica. Revue de l’Association pour la Recherche Cognitive* **55**(1) (2011), 241–267, Number: 1. https://www.persee.fr/doc/intel_0769-4113_2011_num_55_1_1170.
- [348] B. Motik, U. Sattler and R. Studer, Query Answering for OWL-DL with rules, *Journal of Web Semantics* **3**(1) (2005), 41–60. <https://www.sciencedirect.com/science/article/pii/S157082680500003X>.
- [349] M. Musial and A. Tricot, *Précis d’ingénierie pédagogique*, 1st edn, PEDAGOGIES EN DEVELOPPEMENT, De Boeck Supérieur, 2020. ISBN 978-2-8073-2419-0.
- [350] B.T. Nallapu, A closed loop framework of decision-making and learning in primate prefrontal circuits., These de doctorat, Bordeaux, 2019. <https://www.theses.fr/2019BORD0300>.
- [351] M. Negri, Partial Probability and Kleene Logic, *arXiv:1310.6172 [math]* (2013), arXiv: 1310.6172. <http://arxiv.org/abs/1310.6172>.
- [352] D. Ness and S.J. Farenga, *Knowledge Under Construction: The Importance of Play in Developing Children’s Spatial and Geometric Thinking*, Rowman & Littlefield, Lanham, MD, US, 2007, p. xxiii, 257. ISBN 978-0-7425-4789-6 978-0-7425-4788-9.
- [353] D. Ness and S.J. Farenga, Blocks, Bricks, and Planks: Relationships between Affordance and Visuo-Spatial Constructive Play Objects, *American Journal of Play* **8**(2) (2016), 201–227, Publisher: The Strong. <https://eric.ed.gov/?id=EJ1096889>.
- [354] T. Netzer, Real Algebraic Geometry and its Applications, *arXiv:1606.07284 [math]* (2016), arXiv: 1606.07284. <http://arxiv.org/abs/1606.07284>.
- [355] P. Neubert, S. Schubert and P. Protzel, Learning Vector Symbolic Architectures for Reactive Robot Behaviours, in: *Workshop on Machine Learning Methods for High-Level Cognitive Capabilities in Robotics*, 2017, p. 3. https://www.tu-chemnitz.de/etit/proaut/publications/IROS2016_neubert.pdf.
- [356] A. Newell, Reasoning, problem solving and decision processes: the problem space as a fundamental category (1979), 31.
- [357] A. Newell, The Knowledge Level: Presidential Address, *AI Magazine* **2**(2) (1981), 1–1, Number: 2. <https://ojs.aaai.org/index.php/aimagazine/article/view/99>.
- [358] A. Newell and H.A. Simon, *Human problem solving*, Prentice-Hall, Englewood Cliffs, N.J., 1972, OCLC: 622041645.
- [359] L.D. Newton and D.P. Newton, Creativity in 21st-century education, *PROSPECTS* **44**(4) (2014), 575–589.
- [360] A. Nguyen-Xuan, Les mécanismes cognitifs d’apprentissage, *Revue française de pédagogie* **112**(1) (1995), 57–67, Publisher: Persée - Portail des revues scientifiques en SHS. https://www.persee.fr/doc/rfp_0556-7807_1995_num_112_1_1226.

- [361] A. Nguyen-Xuan, *Les mécanismes cognitifs de l'apprentissage*, 2021, OCLC: 1239319636. ISBN 978-1-78405-715-2.
- [362] M. Ni, L. Yang, J. Chen, H. Chen and X. Li, How to Improve Divergent Thinking Capability by Information Technology and Extenics, *Procedia Computer Science* **31** (2014), 158–164.
- [363] M. Nickel and D. Kiela, Poincaré Embeddings for Learning Hierarchical Representations, in: *Advances in Neural Information Processing Systems*, Vol. 30, Curran Associates, Inc., 2017. <https://papers.nips.cc/paper/2017/hash/59dfa2df42d9e3d41f5b02bfc32229dd-Abstract.html>.
- [364] M. Nickel and D. Kiela, Poincaré Embeddings for Learning Hierarchical Representations, in: *Advances in Neural Information Processing Systems*, Vol. 30, Curran Associates, Inc., 2017. <https://papers.nips.cc/paper/2017/hash/59dfa2df42d9e3d41f5b02bfc32229dd-Abstract.html>.
- [365] A. Nieder, Representation of Numerical Information in the Brain, in: *Representation and Brain*, S. Funahashi, ed., Springer Japan, Tokyo, 2007, pp. 271–283. ISBN 978-4-431-73021-7.
- [366] B. Nijstad, C. De Dreu, E. Rietzschel and M. Baas, The Dual Pathway to Creativity Model: Creative Ideation as a Function of Flexibility and Persistence, *European Review of Social Psychology* **21** (2010), 34–77.
- [367] A. Noura, L. Cheniti-Belcadi and R. Braham, An ontology-based framework of assessment analytics for massive learning, *Computer Applications in Engineering Education* **27**(6) (2019), 1343–1360, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/cae.22155>. <https://onlinelibrary.wiley.com/doi/abs/10.1002/cae.22155>.
- [368] N. Noy, Ontology Development 101: A Guide to Creating Your First Ontology, Technical Report, Stanford University, 2001. /paper/Ontology-Development-101%3A-A-Guide-to-Creating-Your-Noy/c15cf32df98969af5eaf85ae3098df6d2180b637.
- [369] M. Oaksford and N. Chater, Précis of Bayesian Rationality: The Probabilistic Approach to Human Reasoning, *Behavioral and Brain Sciences* **32**(1) (2009), 69–84. https://www.cambridge.org/core/product/identifier/S0140525X09000284/type/journal_article.
- [370] A.-M. Olteşeanu, *Cognition and the Creative Machine: Cognitive AI for Creative Problem Solving*, Springer International Publishing, Cham, 2020. ISBN 978-3-030-30321-1 978-3-030-30322-8.
- [371] R.C. O'Reilly, T.E. Hazy, J. Mollick, P. Mackie and S. Herd, Goal-Driven Cognition in the Brain: A Computational Framework, *arXiv:1404.7591 [q-bio]* (2014). <http://arxiv.org/abs/1404.7591>.
- [372] A. Ouangraoua and P. Ferraro, A Constrained Edit Distance Algorithm Between Semi-ordered Trees, *Theoretical Computer Science* **410**(8–10) (2009), 837–846, Publisher: Elsevier. <https://hal.archives-ouvertes.fr/hal-00350113>.
- [373] P.-Y. Oudeyer, J. Gottlieb and M. Lopes, Intrinsic motivation, curiosity, and learning: Theory and applications in educational technologies, in: *Progress in Brain Research*, Motivation, Vol. 229, Elsevier, 2016, pp. 257–284. ISBN 978-0-444-63701-7. <https://linkinghub.elsevier.com/retrieve/pii/S0079612316300589>.
- [374] E. Oztop and M.A. Arbib, Schema design and implementation of the grasp-related mirror neuron system, *Biological Cybernetics* **87**(2) (2002), 116–140.
- [375] R.C. O'Reilly, The What and How of Prefrontal Cortical Organization, *Trends in neurosciences* **33**(8) (2010), 355–361. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC2916029/>.
- [376] R.C. O'Reilly, R. Bhattacharyya, M.D. Howard and N. Ketz, Complementary Learning Systems, *Cognitive Science* **38**(6) (2014), 1229–1248, _eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1111/j.1551-6709.2011.01214.x>.
- [377] C. Pahl and E. Holohan, Ontology Technology for the Development and Deployment of Learning Technology Systems - a Survey, 8.
- [378] J.-J. Pailler, Spinoza avait raison. Joie et tristesse, le cerveau des émotions, d'Antonio R. Damasio, *Revue française de psychosomatique* **25**(1) (2004), 165–172, Number: 1 Place: Paris cedex 14 Publisher: Presses Universitaires de France. <https://www.cairn.info/revue-francaise-de-psychosomatique-2004-1-page-165.htm>.
- [379] C.-V. Pal, F. Leon, M. Paprzycki and M. Ganzha, A Review of Platforms for the Development of Agent Systems, *arXiv:2007.08961 [cs]* (2020), 40, arXiv: 2007.08961. <http://arxiv.org/abs/2007.08961>.
- [380] D. Pandove, R. Rani and S. Goel, Local graph based correlation clustering, *Knowledge-Based Systems* **138** (2017), 155–175. <https://www.sciencedirect.com/science/article/pii/S0950705117304537>.
- [381] S.J. Parnes, R.B. Noller and A.M. Biondi, *Guide to creative action*, MacMillan Publishing Company, 1977.
- [382] V.T. Paschos, An overview on polynomial approximation of NP-hard problems, 2007. <https://hal.science/hal-00186549>.
- [383] E.S. Paul and S.B. Kaufman (eds), *The Philosophy of Creativity: New Essays*, Oxford University Press, New York, 2014. ISBN 978-0-19-983696-3.
- [384] J. Perisic, M. Milovanovic and Z. Kazi, A semantic approach to enhance moodle with personalization, *Comput. Appl. Eng. Educ.* (2018).
- [385] G. Petrucci, C. Ghidini and M. Rospocher, Ontology Learning in the Deep, in: *Knowledge Engineering and Knowledge Management*, E. Blomqvist, P. Ciancarini, F. Poggi and F. Vitali, eds, Lecture Notes in Computer Science, Springer International Publishing, Cham, 2016, pp. 480–495. ISBN 978-3-319-49004-5.
- [386] P. Peykani, E. Mohammadi, M. Pishvae, M. Rostamy-Malkhalifeh and A. Jabbarzadeh, A Novel Fuzzy Data Envelopment Analysis Based on Robust Possibilistic Programming: Possibility, Necessity and Credibility-Based Approaches, *RAIRO - Operations Research* **52** (2018), 1445–1463.
- [387] N. Phan, D. Dou, H. Wang, D. Kil and B. Piniewski, Ontology-based deep learning for human behavior prediction with explanations in health social networks, *Information Sciences* **384** (2017), 298–313. <https://www.sciencedirect.com/science/article/pii/S0020025516306090>.
- [388] P.R. Pintrich, Multiple goals, multiple pathways: The role of goal orientation in learning and achievement, *Journal of Educational Psychology* **92**(3) (2000), 544–555, Place: US Publisher: American Psychological Association.
- [389] Z. Pizlo, Human Problem Solving - An Extension of Newell and Simon's Paradigm (2006), 20.

- [390] T.A. Plate, Holographic reduced representations, *IEEE Transactions on Neural Networks* **6**(3) (1995), 623–641. <http://ieeexplore.ieee.org/document/377968/>.
- [391] R. Poldrack, A. Kittur, D. Kalar, C. Seppa, Y. Gil, D. Parker, F. Sabb and R. Bilder, The Cognitive Atlas: Toward a Knowledge Foundation for Cognitive Neuroscience, *Frontiers in neuroinformatics* **5** (2011), 17.
- [392] G. Polya, *How to Solve It: A New Aspect of Mathematical Method*, Princeton university press edn, Princeton Science Library, 1945. ISBN 0-691-11966-X. <https://b-ok.cc/book/2216490/258273>.
- [393] P.M. Poortvliet, Mastery Goals, in: *Encyclopedia of Personality and Individual Differences*, V. Zeigler-Hill and T.K. Shackelford, eds, Springer International Publishing, Cham, 2016, pp. 1–4. ISBN 978-3-319-28099-8.
- [394] P.M. Poortvliet, O. Janssen, N.W.V. Yperen and E.V.d. Vliert, Achievement Goals and Interpersonal Behavior: How Mastery and Performance Goals Shape Information Exchange, *Personality and Social Psychology Bulletin* **33**(10) (2007), 1435–1447, Publisher: Sage PublicationsSage CA: Los Angeles, CA.
- [395] L. Popa, O. Selejan, A. Scott, D.F. Mureşanu, M. Balea and A. Rafila, Reading beyond the glance: eye tracking in neurosciences, *Neurological Sciences* **36**(5) (2015), 683–688.
- [396] F. Pulvermüller, How neurons make meaning: brain mechanisms for embodied and abstract-symbolic semantics, *Trends in Cognitive Sciences* **17**(9) (2013), 458–470. <http://www.sciencedirect.com/science/article/pii/S1364661313001228>.
- [397] D. Purves, G.J. Augustine, D. Fitzpatrick, L.C. Katz, A.-S. LaMantia, J.O. McNamara and S.M. Williams, The interplay of emotion and reason, in: *Neuroscience*, 2nd edn, Sinauer Associates, Sunderland, MA, 2001. <https://www.ncbi.nlm.nih.gov/books/NBK10822/>.
- [398] L. Qiu, J. Su, Y. Ni, Y. Bai, X. Zhang, X. Li and X. Wan, The neural system of metacognition accompanying decision-making in the prefrontal cortex, *PLOS Biology* **16**(4) (2018), e2004037, Publisher: Public Library of Science.
- [399] J.-B. Quillien, The Roles of Convergent, Divergent Thinking, and Contextual Focus during Scientific Reasoning: Birth of the “Z” Model (2019), Accepted: 2020-11-17T13:56:35Z. <http://conservancy.umn.edu/handle/11299/217149>.
- [400] J. Raczaszek-Leonardi and T. Deacon, Ungrounding symbols in language development: implications for modeling emergent symbolic communication in artificial systems, in: *Joint IEEE 8th International Conference on Development and Learning and Epigenetic Robotics*, 2018, p. 237.
- [401] W. Radji, C. Léger and L. Bardisbanian, Early Empirical Results on Reinforcement Symbolic Learning, Research Report, RR-9509, Inria & Labri, Univ. Bordeaux, 2023, Pages: 9. <https://inria.hal.science/hal-04103795>.
- [402] M. Ragni and P.N. Johnson-Laird, Reasoning about possibilities: Human reasoning violates all normal modal logics, *CogSci* (2018), 6.
- [403] E. Raufaste, R. da Silva Neves and C. Mariné, Testing the descriptive validity of possibility theory in human judgments of uncertainty, *Artificial Intelligence* **148**(1) (2003), 197–218. <https://www.sciencedirect.com/science/article/pii/S0004370203000213>.
- [404] E. Raufaste, R. da Silva Neves and C. Mariné, Testing the descriptive validity of possibility theory in human judgments of uncertainty, *Artificial Intelligence* **148**(1) (2003), 197–218. <https://www.sciencedirect.com/science/article/pii/S0004370203000213>.
- [405] A. Repetto and C.E. Catalano, A Semantic Layer for Knowledge-Based Game Design in Edutainment Applications, in: *Proceedings of the 7th International Conference on Intelligent Technologies for Interactive Entertainment*, IEEE, Torino, Italy, 2015. ISBN 978-1-63190-061-7.
- [406] K. Rezgui, H. Mhiri and K. Ghédira, An Ontology-based Profile for Learner Representation in Learning Networks, *International Journal of Emerging Technologies in Learning (IJET)* **9**(3) (2014), 16. <https://online-journals.org/index.php/i-jet/article/view/3305>.
- [407] M. Rhodes, An Analysis of Creativity, *The Phi Delta Kappan* **42**(7) (1961), 305–310, Publisher: Phi Delta Kappa International. <https://www.jstor.org/stable/20342603>.
- [408] C.H.C. Ribeiro, Embedding a Priori Knowledge in Reinforcement Learning, *Journal of Intelligent and Robotic Systems* **21**(1) (1998), 51–71.
- [409] R. Riegel, A. Gray, F. Luus, N. Khan, N. Makondo, I.Y. Akhalwaya, H. Qian, R. Fagin, F. Barahona, U. Sharma, S. Ikbal, H. Karanam, S. Neelam, A. Likhyan and S. Srivastava, Logical Neural Networks, Technical Report, 2020, arXiv: 2006.13155. <http://arxiv.org/abs/2006.13155>.
- [410] D.D. Riley and K.A. Hunt, *Computational Thinking for the Modern Problem Solver*, CRC Press, 2014, Google-Books-ID: 7AQ-NAwAAQBAJ. ISBN 978-1-4665-8777-9.
- [411] E.F. Risko and A. Kingstone, Eyes wide shut: implied social presence, eye tracking and attention, *Attention, Perception, & Psychophysics* **73**(2) (2011), 291–296.
- [412] G. Ritchie, A closer look at creativity as search, in: *Proceedings of the Third International Conference on Computational Creativity*, 2012. https://www.academia.edu/5626724/A_closer_look_at_creativity_as_search.
- [413] M. Rmus, S.D. McDougale and A.G. Collins, The role of executive function in shaping reinforcement learning, *Current Opinion in Behavioral Sciences* **38** (2021), 66–73. <https://www.sciencedirect.com/science/article/pii/S2352154620301480>.
- [414] A. Rodríguez-Arias, B. Guijarro-Berdiñas and N. Sánchez-Marroño, An Intelligent and Collaborative Multiagent System in a 3D Environment, *Proceedings* **54**(1) (2020), 36, Number: 1. <https://www.mdpi.com/2504-3900/54/1/36>.
- [415] M. Romero, Métacognition dans les EIAH, *Mémoire de DEA, LIUM, Université du Maine, Le Mans* (2004).
- [416] M. Romero, CreaCube, analyse de la résolution créative de problèmes par le biais d’une tâche de robotique modulaire, in: *Journées Nationales de la Recherche en Robotique, JNRR 2017, Femto-st*, 2017, p. 1.
- [417] M. Romero, Analyzing Cognitive Flexibility in Older Adults Through Playing with Robotic Cubes, in: *Human Aspects of IT for the Aged Population. Social Media, Games and Assistive Environments*, J. Zhou and G. Salvendy, eds, Lecture Notes in Computer Science, Springer International Publishing, Cham, 2019, pp. 545–553. ISBN 978-3-030-22015-0.
- [418] M. Romero and G. Giraudon, Le numérique va révolutionner l’éducation . . . vraiment ?, *Binaire* (2020). <https://hal.inria.fr/hal-02895694>.

- [419] M. Romero, D. David and B. Lille, CreaCube, a Playful Activity with Modular Robotics, in: *Games and Learning Alliance*, Vol. 11385, M. Gentile, M. Allegra and H. Söbke, eds, Springer International Publishing, Cham, 2019, pp. 397–405, Series Title: Lecture Notes in Computer Science. ISBN 978-3-030-11547-0 978-3-030-11548-7.
- [420] M. Romero, M. Dufлот and T. Viéville, Le jeu du robot : analyse d’une activité d’informatique débranchée sous la perspective de la cognition incarnée., *Review of science, mathematics and ICT education* **13**(1) (2019), Number: 1. <https://hal.inria.fr/hal-02144467>.
- [421] M. Romero, V. Freiman and M. Rafalska, Techno-creative problem solving (TCPS) framework for transversal epistemological and didactical positions: the cases of CreaCube and the Tower of Hanoi task, 2022.
- [422] M. Romero, T. Laferrière and T.M. Power, elearn Magazine: The Move is On! From the Passive Multimedia Learner to the Engaged Co-creator, *eLearn Magazine, an ACM Publication* (2016). <https://elearnmag.acm.org/archive.cfm?aid=2893358>.
- [423] M. Romero, A. Lepage and B. Lille, Computational thinking development through creative programming in higher education, *International Journal of Educational Technology in Higher Education* **14**(1) (2017), 1–15, Number: 1 Publisher: SpringerOpen.
- [424] M. Romero, T. Vieville and L. Heiser, Analyse d’activités d’apprentissage médiatisées en robotique pédagogique, in: *Traité de méthodologie de la recherche en Sciences de l’Éducation et de la Formation*, B. Alberto and J.Thievenaz, 2021, Publisher: Unpublished. <https://hal.inria.fr/hal-02957270>.
- [425] M. Romero, B. Lille, T. Viéville, M. Dufлот-Kremer, C.d. Smet and D. Belhassein, Analyse comparative d’une activité d’apprentissage de la programmation en mode branché et débranché, 2018, p. 11. <https://hal.inria.fr/hal-01861732>.
- [426] M. Romero, F. Alexandre, T. Viéville and G. Giraudon, LINE-Mnésosyne : Des neurosciences computationnelles aux sciences de l’éducation computationnelles pour la modélisation du cerveau de l’apprenant et du contexte de l’activité d’apprentissage, *Bulletin de l’Association Française pour l’Intelligence Artificielle* (2020). <https://hal.inria.fr/hal-02541099>.
- [427] X. Rong, word2vec Parameter Learning Explained, Technical Report, 2016, arXiv: 1411.2738. <http://arxiv.org/abs/1411.2738>.
- [428] N.P. Rougier, Implicit and Explicit Representations, *Neural Networks* **22**(2) (2009), 155–160. <https://hal.inria.fr/inria-00336167>.
- [429] N.P. Rougier, Open Science, 2016, p. 35. <https://hal.inria.fr/hal-01418314>.
- [430] L. Roux, M. Romero, F. Alexandre, T. Viéville and C. Mercier, Développement d’une ontologie pour l’analyse d’observables de l’apprenant dans le contexte d’une tâche avec des robots modulaires, report, Inria, 2020. <https://hal.inria.fr/hal-03013685>.
- [431] L. Roux, M. Romero, F. Alexandre and T. Viéville, Les hauts de Otesia, *Binaire* (2020). <https://hal.inria.fr/hal-03089962>.
- [432] A. Roy, Approche neuropsychologique des fonctions exécutives de l’enfant : état des lieux et éléments de prospective, *Revue de neuropsychologie* **7**(4) (2015), 245–256, Number: 4 Place: Montrouge Publisher: John Libbey Eurotext. <https://www.cairn.info/revue-de-neuropsychologie-2015-4-page-245.htm>.
- [433] A.L. Rusawuk, Possibility and Necessity: An Introduction to Modality, 2018. <https://1000wordphilosophy.com/2018/12/08/possibility-and-necessity-an-introduction-to-modality/>.
- [434] F. Sado, C.K. Loo, W.S. Liew, M. Kerzel and S. Wermter, Explainable Goal-Driven Agents and Robots: A Comprehensive Review, *arXiv:2004.09705 [cs]* (2021), 41, arXiv: 2004.09705. <http://arxiv.org/abs/2004.09705>.
- [435] H.P. Sajjad, A. Docherty and Y. Tyshetskiy, Efficient Representation Learning Using Random Walks for Dynamic Graphs, *arXiv:1901.01346 [cs, stat]* (2019), arXiv: 1901.01346. <http://arxiv.org/abs/1901.01346>.
- [436] A. Sannino and Y. Engeström, Cultural-historical activity theory: founding insights and new challenges, *Cultural-Historical Psychology* **14**(3) (2018), 43–56, Number: 3. https://psyjournals.ru/en/kip/2018/n3/Sannino_Engestrom.shtml.
- [437] A. Sannino and A. Laitinen, Double stimulation in the waiting experiment: Testing a Vygotskian model of the emergence of volitional action, *Learning, Culture and Social Interaction* **4** (2015), 4–18. <http://www.sciencedirect.com/science/article/pii/S2210656114000634>.
- [438] D. Santos-Pata, A.F. Amil, I.G. Raikov, C. Rennó-Costa, A. Mura, I. Soltesz and P.F.M.J. Verschure, Entorhinal mismatch: A model of self-supervised learning in the hippocampus, *iScience* **24**(4) (2021), 102364. <https://www.sciencedirect.com/science/article/pii/S2589004221003321>.
- [439] T. Sauerwald and L. Zanetti, Random Walks on Dynamic Graphs: Mixing Times, HittingTimes, and Return Probabilities, *arXiv:1903.01342 [cs, math]* (2019), arXiv: 1903.01342. <http://arxiv.org/abs/1903.01342>.
- [440] R.K. Sawyer, V. John-Steiner, S. Moran, R.J. Sternberg, D.H. Feldman, M. Csikszentmihalyi, H. Gardner and J. Nakamura, *Creativity and Development*, Oxford University Press, 2003, Google-Books-ID: TWdnDAAAQBAJ. ISBN 978-0-19-514900-5.
- [441] S. Scardapane, S. Van Vaerenbergh, A. Hussain and A. Uncini, Complex-valued Neural Networks with Non-parametric Activation Functions, *arXiv:1802.08026 [cs]* (2018), arXiv: 1802.08026. <http://arxiv.org/abs/1802.08026>.
- [442] J. Schatz and J. Laird, An Architecture Approach to Modeling the Remote Associates Test, in: *Proceedings of the 16th international conference on cognitive modelling (iccm)*., 2018, p. 6. <https://www.semanticscholar.org/paper/An-Architecture-Approach-to-Modeling-the-Remote-Schatz-Laird/7c18c58517a9c4e40117186198b1008b03d291fe>.
- [443] K. Schlegel, P. Neubert and P. Protzel, A comparison of vector symbolic architectures, *arXiv:2001.11797 [cs]* **55** (2020). <http://arxiv.org/abs/2001.11797>.
- [444] M.L. Schlichting and A.R. Preston, Memory integration: neural mechanisms and implications for behavior, *Current Opinion in Behavioral Sciences* **1** (2015), 1–8.
- [445] G. Schraw, M.E. Dunkle and L.D. Bendixen, Cognitive processes in well-defined and ill-defined problem solving, *Applied Cognitive Psychology* **9**(6) (1995), 523–538. <https://onlinelibrary.wiley.com/doi/abs/10.1002/acp.2350090605>.
- [446] G.H. Seijts and G.P. Latham, Learning versus performance goals: When should each be used?, *Academy of Management Perspectives* **19**(1) (2005), 124–131, Publisher: Academy of Management Briarcliff Manor, NY 10510.
- [447] L. Serafini and A.d. Garcez, Logic Tensor Networks: Deep Learning and Logical Reasoning from Data and Knowledge, Technical Report, 2016, arXiv: 1606.04422. <http://arxiv.org/abs/1606.04422>.

- [448] M. Shanahan, An abductive event calculus planner, *The Journal of Logic Programming* **44**(1) (2000), 207–240. <https://www.sciencedirect.com/science/article/pii/S0743106699000771>.
- [449] S. Shi, H. Chen, W. Ma, J. Mao, M. Zhang and Y. Zhang, Neural Logic Reasoning, in: *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, CIKM '20, Association for Computing Machinery, New York, NY, USA, 2020, pp. 1365–1374. ISBN 978-1-4503-6859-9.
- [450] A. Shleifer, Psychologists at the Gate: A Review of Daniel Kahneman's Thinking, Fast and Slow, *Journal of Economic Literature* **50**(4) (2012), 1080–91.
- [451] P. Shvaiko and J. Euzenat, Ontology matching: state of the art and future challenges, *IEEE Transactions on Knowledge and Data Engineering* **25**(1) (2013), 158. <https://hal.inria.fr/hal-00917910>.
- [452] M. Siedlecka, B. Paulewicz and M. Wierchoń, But I Was So Sure! Metacognitive Judgments Are Less Accurate Given Prospectively than Retrospectively, *Frontiers in Psychology* **7** (2016), Publisher: Frontiers.
- [453] H.A. Simon, The functional equivalence of problem solving skills, *Cognitive Psychology* **7**(2) (1975), 268–288. <http://www.sciencedirect.com/science/article/pii/0010028575900122>.
- [454] H.A. Simon and J.B. Kadane, Optimal problem-solving search: All-or-none solutions, *Artificial Intelligence* **6**(3) (1975), 235–247. <http://www.sciencedirect.com/science/article/pii/0004370275900028>.
- [455] H.A. Simon and S.K. Reed, Modeling strategy shifts in a problem-solving task, *Cognitive Psychology* **8**(1) (1976), 86–97, Publisher: Academic Press. <http://www.sciencedirect.com/science/article/pii/0010028576900050>.
- [456] C. Simpkin, I. Taylor, G. Bent, G. de Mel and R. Ganti, A Scalable Vector Symbolic Architecture Approach for Decentralized Workflows, Venice, Italy, 2018. <http://orca.cf.ac.uk/112242/>.
- [457] S. Singh, R.L. Lewis, A.G. Barto and J. Sorg, Intrinsically Motivated Reinforcement Learning: An Evolutionary Perspective, *IEEE Transactions on Autonomous Mental Development* **2**(2) (2010), 70–82. <http://ieeexplore.ieee.org/document/5471106/>.
- [458] A. Sloman, Possibility and Necessity (2011), 40.
- [459] B. Smith, Basic Formal Ontology 2.0, 2015.
- [460] L. Smith, The development of modal understanding: Piaget's possibility and necessity, *New Ideas in Psychology* **12**(1) (1994), 73–87. <https://www.sciencedirect.com/science/article/pii/0732118X94900590>.
- [461] L. Smith, The development of modal understanding: Piaget's possibility and necessity, *New Ideas in Psychology* **12**(1) (1994), 73–87. <https://www.sciencedirect.com/science/article/pii/0732118X94900590>.
- [462] M. Smithson, Human Judgment And Imprecise Probabilities (1970).
- [463] E. Spens and N. Burgess, A generative model of memory construction and consolidation, bioRxiv, 2023.
- [464] J. St. B. T. Evans, S.J. Handley, C.N.J. Harper and P.N. Johnson-Laird, Reasoning about necessity and possibility: A test of the mental model theory of deduction, *Journal of Experimental Psychology: Learning, Memory, and Cognition* **25**(6) (1999), 1495–1513, Place: US Publisher: American Psychological Association.
- [465] K.L. Stachenfeld, M.M. Botvinick and S.J. Gershman, The hippocampus as a predictive map, *Nature Neuroscience* **20**(11) (2017), 1643–1653, Bandiera_abtest: a Cg_type: Nature Research Journals Number: 11 Primary_atype: Research Publisher: Nature Publishing Group Subject_term: Hippocampus;Learning and memory;Reward Subject_term_id: hippocampus;learning-and-memory;reward. <https://www.nature.com/articles/nn.4650>.
- [466] K. Stancin, P. Poscic and D. Jaksic, Ontologies in education – state of the art, *Education and Information Technologies* **25**(6) (2020), 5301–5320.
- [467] K. Stanovich and R. West, Individual Differences in Reasoning: Implications for the Rationality Debate, *The Behavioral and brain sciences* **23** (2000), 645–65; discussion 665.
- [468] N. Stehr and R. Grundmann, *Knowledge: Critical Concepts*, Taylor & Francis, 2005, Google-Books-ID: dd64yyo7Cp4C. ISBN 978-0-415-31737-5.
- [469] J. Steinberg and H. Sompolinsky, Associative memory of structured knowledge, *Scientific Reports* **12**(1) (2022), 1–15, Number: 1 Publisher: Nature Publishing Group. <https://www.nature.com/articles/s41598-022-25708-y>.
- [470] T. Stewart and C. Eliasmith, Neural Cognitive Modelling: A Biologically Constrained Spiking Neuron Model of the Tower of Hanoi Task, *Proceedings of the Annual Meeting of the Cognitive Science Society* **33**(33) (2011). <https://escholarship.org/uc/item/6kv930kg>.
- [471] T.C. Stewart, X. Choo and C. Eliasmith, Symbolic Reasoning in Spiking Neurons: A Model of the Cortex/Basal Ganglia/Thalamus Loop (2010), 7.
- [472] T.C. Stewart, Y. Tang and C. Eliasmith, A biologically realistic cleanup memory: Autoassociation in spiking neurons, *Cognitive Systems Research* **12**(2) (2011), 84–92. <https://linkinghub.elsevier.com/retrieve/pii/S1389041710000525>.
- [473] A. Stocco, C. Sibert, Z. Steine-Hanson, N. Koh, J.E. Laird, C.J. Lebiere and P. Rosenbloom, Analysis of the Human Connectome Data Supports the Notion of A “Common Model of Cognition” for Human and Human-Like Intelligence Across Domains, preprint, Neuroscience, 2019.
- [474] G. Stoilos, G. Stamou and S. Kollias, *A String Metric for Ontology Alignment*, Vol. 3729, 2005, Pages: 637. ISBN 978-3-540-29754-3.
- [475] R. Sun and F. Alexandre, *Connectionist-Symbolic Integration: From Unified to Hybrid Approaches*, 3rd edition edn, Taylor & Francis Group, 2013. <https://www.taylorfrancis.com/books/9780203763667>.
- [476] J. Sweller, J.J.G. Van Merriënboer and F. Paas, Cognitive Architecture and Instructional Design, *Educational Psychology Review* **10** (1998), 251.
- [477] J. Sweller, J.J.G. van Merriënboer and F. Paas, Cognitive Architecture and Instructional Design: 20 Years Later, *Educational Psychology Review* **31**(2) (2019), 261–292.

- [478] L. Taconnat, Fonctionnement et dysfonctionnement de la mémoire humaine, *Le Journal des psychologues* **297**(4) (2012), 18, Number: 4. <http://www.cairn.info/revue-le-journal-des-psychologues-2012-4-page-18.htm>.
- [479] M. Taddeo and L. Floridi, Solving the Symbol Grounding Problem: A Critical Review of Fifteen Years of Research, *Journal of Experimental and Theoretical Artificial Intelligence* **17** (2005).
- [480] S. Tang and M. Hanneghan, Game Content Model: An Ontology for Documenting Serious Game Design, in: *2011 Developments in E-systems Engineering*, 2011, pp. 431–436.
- [481] A. Tcherkassof and N.H. Frijda, Les émotions : une conception relationnelle, *L'Année psychologique* **114**(3) (2014), 501–535, Number: 3 Place: Paris Publisher: NecPlus. <https://www.cairn.info/revue-l-annee-psychologique1-2014-3-page-501.htm>.
- [482] A. Tettamanzi, C.F. Zucker and F. Gandon, Possibilistic testing of OWL axioms against RDF data, *International Journal of Approximate Reasoning* **91** (2017). <https://hal.inria.fr/hal-01591001>.
- [483] S. Thill, D. Caligiore, A.M. Borghi, T. Ziemke and G. Baldassarre, Theories and computational models of affordance and mirror systems: An integrative review, *Neuroscience & Biobehavioral Reviews* **37**(3) (2013), 491–521. <https://www.sciencedirect.com/science/article/pii/S0149763413000134>.
- [484] M. Thurlings, A.T. Evers and M. Vermeulen, Toward a Model of Explaining Teachers' Innovative Behavior: A Literature Review, *Review of Educational Research* **85**(3) (2015), 430–471, Publisher: American Educational Research Association.
- [485] E.P. Torrance and K. Goff, A quiet revolution., *The journal of creative behavior* (1989), Publisher: Creative Education Foundation.
- [486] J. Torrente, P. Moreno-Ger, I. Martínez-Ortiz and B. Fernández-Manjon, Integration and Deployment of Educational Games in e-Learning Environments: The Learning Object Model Meets Educational Gaming, *Journal of Educational Technology & Society* **12**(4) (2009), 359–371, Publisher: International Forum of Educational Technology & Society. <https://www.jstor.org/stable/jeductechsoci.12.4.359>.
- [487] R. Tous and J. Delgado, A Vector Space Model for Semantic Similarity Calculation and OWL Ontology Alignment, in: *Database and Expert Systems Applications*, S. Bressan, J. Küng and R. Wagner, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2006, pp. 307–316. ISBN 978-3-540-37872-3.
- [488] F. Toyoshima, A. Barton and O. Grenier, Foundations for an Ontology of Belief, Desire and Intention, *Formal Ontology in Information Systems* (2020), 140–154, Publisher: IOS Press.
- [489] S. Trausan-Matu, K.E. Boyer, M. Crosby, K. Panourgia, D. Hutchison, T. Kanade, J. Kittler, J.M. Kleinberg, A. Kobsa, F. Mattern, J.C. Mitchell, M. Naor, O. Nierstrasz, C. Pandu Rangan, B. Steffen, D. Terzopoulos, D. Tygar and G. Weikum (eds), *Intelligent Tutoring Systems: 12th International Conference, ITS 2014, Honolulu, HI, USA, June 5-9, 2014. Proceedings*, Lecture Notes in Computer Science, Vol. 8474, Springer International Publishing, Cham, 2014. ISBN 978-3-319-07220-3 978-3-319-07221-0.
- [490] M.C.M. Troffaes, E. Miranda and S. Destercke, On the connection between probability boxes and possibility measures, in: *Proceedings of the 7th conference of the European Society for Fuzzy Logic and Technology (EUSFLAT-2011)*, Atlantis Press, France, 2011. ISBN 978-90-78677-00-0. <http://www.atlantis-press.com/php/paper-details.php?id=2335>.
- [491] R. Tubb and S. Dixon, A Four Strategy Model of Creative Parameter Space Interaction, in: *ICCC*, 2014.
- [492] J.A. Turner and A.R. Laird, The cognitive paradigm ontology: design and application, *Neuroinformatics* **10**(1) (2012), 57–66.
- [493] M. Usart, M. Romero and E. Almirall, Impact of the Feeling of Knowledge Explicitness in the Learners' Participation and Performance in a Collaborative Game Based Learning Activity, in: *Serious Games Development and Applications*, M. Ma, M. Fradinho Oliveira and J. Madeiras Pereira, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2011, pp. 23–35. ISBN 978-3-642-23834-5.
- [494] T. Vallaeys, Généraliser les possibilités-nécessités pour l'apprentissage profond, Report, Inria, 2021. <https://hal.inria.fr/hal-03338721>.
- [495] N.V. Valtakari, I.T.C. Hooge, C. Viktorsson, P. Nyström, T. Falck-Ytter and R.S. Hessels, Eye tracking in human interaction: Possibilities and limitations, *Behavior Research Methods* **53**(4) (2021), 1592–1608.
- [496] T. Van Rompay, D. Vonk and M. Fransen, The Eye of the Camera Effects of Security Cameras on Prosocial Behavior, *Environment and Behavior - ENVIRON BEHAV* **41** (2009), 60–74.
- [497] K.M. Varadarajan and M. Vincze, AfNet: The Affordance Network, in: *Computer Vision – ACCV 2012*, K.M. Lee, Y. Matsushita, J.M. Rehg and Z. Hu, eds, Lecture Notes in Computer Science, Springer, Berlin, Heidelberg, 2013, pp. 512–523. ISBN 978-3-642-37331-2.
- [498] T.D. Villiers, Why Peirce Matters: The Symbol in Deacon's Symbolic Species, *Language Sciences* **29**(1) (2007), 88–101. <https://philarchive.org/rec/DEVWPM-4>.
- [499] T. Viéville, An improved biologically plausible trajectory generator, Research report, RR-4539, Inria, 2002. <https://hal.inria.fr/inria-00072049>.
- [500] T. Viéville, Neurosym - Mnemosyne team meeting, 2021. https://docs.google.com/presentation/d/189Q166S1h4TYCGbldt-nGHtLROqm-ZrEtyQ1w6zhAxc/edit?usp=drive_web&ouid=111495962261220832381&usp=embed_facebook.
- [501] T. Viéville, Que se passe-t-il dans les cerveaux des cons ?, *Binaire* (2021). <https://hal.inria.fr/hal-03512294>.
- [502] T. Viéville and C. Mercier, Representation of belief in relation to randomness, Research Report, RR-9493, Inria & Labri, Univ. Bordeaux, 2022. <https://hal.inria.fr/hal-03886219>.
- [503] T. Viéville and C. Mercier, Where is Aristotle in our brain? On biologically plausible reasoning embedded in neuronal computation., *Cognitive Neurodynamics* **0** (2023), submitted.
- [504] T. Viéville, D. Lingrand and F. Gaspard, Implementing a multi-model estimation method, *International Journal of Computer Vision* (2001). <https://hal.inria.fr/inria-00000172>.
- [505] A. Voelker, E. Crawford and C. Eliasmith, Learning large-scale heteroassociative memories in spiking neurons, in: *Unconventional Computation and Natural Computation*, 2014.

- [506] A.R. Voelker, A short letter on the dot product between rotated Fourier transforms, *arXiv:2007.13462 [cs, q-bio]* (2020), arXiv: 2007.13462. <http://arxiv.org/abs/2007.13462>.
- [507] J. Voogt and N.P. Roblin, A comparative analysis of international frameworks for 21st century competences: Implications for national curriculum policies, *Journal of Curriculum Studies* **44**(3) (2012), 299–321, Publisher: Routledge _eprint: <https://doi.org/10.1080/00220272.2012.668938>.
- [508] H. Wang, D. Dou and D. Lowd, Ontology-Based Deep Restricted Boltzmann Machine, in: *Database and Expert Systems Applications*, S. Hartmann and H. Ma, eds, Lecture Notes in Computer Science, Vol. 9827, Springer International Publishing, Cham, 2016, pp. 431–445. ISBN 978-3-319-44402-4 978-3-319-44403-1.
- [509] J.X. Wang, Z. Kurth-Nelson, D. Tirumala, H. Soyer, J.Z. Leibo, R. Munos, C. Blundell, D. Kumaran and M. Botvinick, Learning to reinforcement learn, *arXiv:1611.05763 [cs, stat]* (2017), arXiv: 1611.05763. <http://arxiv.org/abs/1611.05763>.
- [510] J.X. Wang, Z. Kurth-Nelson, D. Kumaran, D. Tirumala, H. Soyer, J.Z. Leibo, D. Hassabis and M. Botvinick, Prefrontal cortex as a meta-reinforcement learning system, *Nature Neuroscience* **21**(6) (2018), 860–868, Number: 6. <http://www.nature.com/articles/s41593-018-0147-8>.
- [511] M. Wang, L. Qiu and X. Wang, A Survey on Knowledge Graph Embeddings for Link Prediction, *Symmetry* **13**(3) (2021), 485, Number: 3 Publisher: Multidisciplinary Digital Publishing Institute. <https://www.mdpi.com/2073-8994/13/3/485>.
- [512] M.E. Webb, D.R. Little and S.J. Cropper, Insight Is Not in the Problem: Investigating Insight in Problem Solving across Task Types, *Frontiers in Psychology* **7** (2016). <https://www.frontiersin.org/article/10.3389/fpsyg.2016.01424>.
- [513] D. Widdows and T. Cohen, Reasoning with Vectors: A Continuous Model for Fast Robust Inference, *Logic Journal of IGPL* (2014).
- [514] G.A. Wiggins, A preliminary framework for description, analysis and comparison of creative systems, *Knowledge-Based Systems* **19**(7) (2006), 449–458. <https://www.sciencedirect.com/science/article/pii/S0950705106000645>.
- [515] G.A. Wiggins, A preliminary framework for description, analysis and comparison of creative systems, *Knowledge-Based Systems* **19**(7) (2006), 449–458. <https://www.sciencedirect.com/science/article/pii/S0950705106000645>.
- [516] G.A. Wiggins, Searching for computational creativity, *New Generation Computing* **24**(3) (2006), 209–222.
- [517] J. Wiley, Expertise as mental set: The effects of domain knowledge in creative problem solving, *Memory & Cognition* **26**(4) (1998), 716–730, Number: 4.
- [518] J.M. Wing, Computational thinking, *Communications of the ACM* **49**(3) (2006), 33–35.
- [519] S. Woltering and Q. Shi, On the Neuroscience of Self-Regulation in Children With Disruptive Behavior Problems: Implications for Education, *Review of Educational Research* **86**(4) (2016), 1085–1110, Publisher: American Educational Research Association.
- [520] H. Xiao, M. Huang and X. Zhu, From one point to a manifold: Knowledge graph embedding for precise link prediction, *arXiv preprint arXiv:1512.04792* (2015).
- [521] M. Xu, *Understanding graph embedding methods and their applications*, 2020.
- [522] A. Yadav, H. Hong and C. Stephenson, Computational Thinking for All: Pedagogical Approaches to Embedding 21st Century Problem Solving in K-12 Classrooms, *TechTrends* **60**(6) (2016), 565–568.
- [523] J. Yu, P. Tseng, N.G. Muggleton and C.-H. Juan, Being watched by others eliminates the effect of emotional arousal on inhibitory control, *Frontiers in Psychology* **6** (2015), 4. <https://www.ncbi.nlm.nih.gov/pmc/articles/PMC4299288/>.
- [524] R.B. Zajonc, Social Facilitation, *Science* (1965), Publisher: American Association for the Advancement of Science.
- [525] T. Zander, M. Öllinger and K.G. Volz, Intuition and Insight: Two Processes That Build on Each Other or Fundamentally Differ?, *Frontiers in Psychology* **7** (2016), 1395.
- [526] K. Zawadzka and P.A. Higham, Judgments of learning index relative confidence, not subjective probability, *Memory & Cognition* **43**(8) (2015), 1168–1179.
- [527] P.D. Zelazo, A. Carter, J.S. Reznick and D. Frye, Early Development of Executive Function: A Problem-Solving Framework, *Review of General Psychology* **1**(2) (1997), 198–226.
- [528] J.C. Zemla and J.L. Austerweil, Estimating Semantic Networks of Groups and Individuals from Fluency Data, *Computational Brain & Behavior* **1**(1) (2018), 36–58.
- [529] W. Zhang and H. Liu, Toward a Reliable Collection of Eye-Tracking Data for Image Quality Research: Challenges, Solutions, and Applications, *IEEE Transactions on Image Processing* **26**(5) (2017), 2424–2437, Conference Name: IEEE Transactions on Image Processing.
- [530] W. Zhang, Z. Sjoerds and B. Hommel, Metacontrol of human creativity: The neurocognitive mechanisms of convergent and divergent thinking, *NeuroImage* **210** (2020), 116572. <https://www.sciencedirect.com/science/article/pii/S1053811920300598>.
- [531] Z. Zhang, Y. Lei and H. Li, Approaching the Distinction between Intuition and Insight, *Frontiers in Psychology* **7** (2016), 1195.
- [532] W. Zhu, Q. Qiu, J. Huang, R. Calderbank, G. Sapiro and I. Daubechies, LDMNet: Low Dimensional Manifold Regularized Neural Networks, *arXiv:1711.06246 [cs]* (2017), arXiv: 1711.06246 version: 1. <http://arxiv.org/abs/1711.06246>.
- [533] E.A. Zilli and M.E. Hasselmo, Modeling the role of working memory and episodic memory in behavioral tasks, *Hippocampus* **18**(2) (2008), 193–209.
- [534] J. Zwickel and M. L.-H. Vö, How the presence of persons biases eye movements, *Psychonomic Bulletin & Review* **17**(2) (2010), 257–262.
- [535] (16) (PDF) Multi-scale brain networks. https://www.researchgate.net/publication/307545285_Multi-scale_brain_networks.
- [536] The associative basis of the creative process. - PsycNET. <https://content.apa.org/record/1963-06161-001>.
- [537] Document sans titre. https://docs.google.com/document/u/0/d/1AItngxaXy3WpkJTgYgYN4nuZVAVvIX6s2yh3a7mU9yE/edit?usp=embed_facebook.
- [538] The ICAP Framework: the potential and the pitfall. <https://www.educationandlearning.nl/news/the-icap-framework-the-potential-and-the-pitfall>.
- [539] The Ludo Game Model Ontology Specification. <https://ns.inria.fr/ludo/v1/docs/gamemodel.html>.

- [540] A Survey of Ontologies and Their Applications in e-Learning Environments | www.semantic-web-journal.net. <http://www.semantic-web-journal.net/content/survey-ontologies-and-their-applications-e-learning-environments>.
- [541] protegeproject/snap-sparql-query, Protégé Project, 2020, original-date: 2015-03-10T21:56:19Z. <https://github.com/protegeproject/snap-sparql-query>.
- [542] protegeproject/protege, Protégé Project, 2021, original-date: 2013-08-20T01:26:26Z. <https://github.com/protegeproject/protege>.

Appendix A. Hypothesis testing regarding symbol similarity

The design choice of a symbol implementation as a random normal unary vector, as reviewed in subsection 2.1 allows us to define a hypothesis to decide whether the \mathcal{H}_0 hypothesis $\mathbf{x} \cdot \mathbf{y} = 0$ can be rejected.

In our case, we approximate the chi-square distribution average of $\mathbf{x} \cdot \mathbf{y}$ by a normal distribution of the same standard-deviation, which is a conservative choice as shown in Fig. 10.




Fig. 10. Comparison between a chi-square distribution in black (numerically drawn from 10^5 samples) and the normal distribution of same mean and standard-deviation, in red: The choice is conservative because much more samples have values closed to zero in the former case. More precisely the kurtosis is of about 6 (i.e. the sharpness estimation with respect to a normal distribution using 4-th order momenta).

We can consider a two-tailed “z-test” with the alternative hypothesis \mathcal{H}_0 , which states that $\mathbf{x} \cdot \mathbf{y} \neq 0$. Here, the z-score²⁴, with d samples and a known standard deviation with an order of magnitude $O(1/d)$, is the following:

$$z \equiv \sqrt{d} (\mathbf{x} \cdot \mathbf{y}).$$

It follows an almost distribution, which can be easily verified numerically, as shown in Fig. 11 (left column). For two vectors that are not independent but have an angular dependency, we can numerically observe, in Fig. 11 (right column), the similarity dependency as a function of the vector’s relative orientation. This obvious fact is quite important, allowing us to develop a macroscopic simulation of VSA operations.

This makes it possible, on the one hand, to consider, for instance, a threshold:

$$\theta \stackrel{\text{def}}{=} \pm 2\sigma,$$

along with considering this z-score to have a confidence interval better than 99%, and to relate the similarity estimation to an angular dependence between two vectors, as detailed in Fig. 11. To the best of our knowledge, this obvious implementation has not yet been made explicit, and it is used in subsection 5.3, as detailed in section 4, allowing us to propose to simulate the different operations defined later in this paper at a macroscopic scale.

²⁴Given a distribution, the z-score for d samples is defined as

$$z \stackrel{\text{def}}{=} \frac{\bar{X} - \mu}{\sigma/\sqrt{d}},$$

where the expected mean is $\mu = 0$, the a priori standard deviation is $\sigma = O(1/d)$, and the experimental mean $\bar{X} = (\mathbf{x} \cdot \mathbf{y})$ is obtained from the dot product.




Fig. 11. Numerical observations of the similarity defined by the dot product of two random vectors for $d = 100$ in the upper row and $d = 1000$ in the lower row. The left column shows the histogram of the z-score ($\sqrt{d}(\mathbf{x} \cdot \mathbf{y})$) for two normal vectors, in comparison with a normal distribution. These experimental distributions have a kurtosis of about 10; this is lower than the kurtosis of a normal distribution, which is expected to have a kurtosis of 3. The right column shows the z-score as a function of the angle $a \stackrel{\text{def}}{=} \widehat{\mathbf{x}, \mathbf{y}} = \arccos(\mathbf{x} \cdot \mathbf{y})$, making it possible to visualize the dispersion with respect to the expected cosine profile.

Appendix B. On VSA data structures

This section revisits the literature, emphasizing the properties of the data structures; it discusses in more detail their computational properties and limitations and links them to usual programming language data structures.

1 B.1. Unordered set or bundling 1

2
3 We first consider an unordered set \mathcal{S} of N symbols grounded to values $\{\mathbf{s}_1, \dots, \mathbf{s}_i, \dots, \mathbf{s}_N\}$, and we would like to be
4 able to store them in such a way that we can check if a given symbol is in the set. Very simply, we ground \mathcal{S} to the
5 vector \mathbf{s} :

$$6 \quad \mathbf{s} \stackrel{\text{def}}{=} \sum_i \mathbf{s}_i, \quad 6$$

7 which provides a solution, because given a symbol \mathbf{s}_i , we obviously observe that $\mathbf{s}_i \cdot \mathbf{s} \simeq 1$ if it corresponds to
8 a certain symbol \mathbf{s}_i , and it is almost 0 otherwise, because random vectors are almost orthogonal, as previously
9 explained. This is called bundling [443] or superposition. 9

10 Furthermore, the representation intrinsically includes a notion of transitivity: If a set includes another subset, by
11 construction, it includes the subset elements. More precisely, 11

$$12 \quad \mathbf{s} \stackrel{\text{def}}{=} \sum_i \mathbf{s}_i \text{ and } \mathbf{s}_i \stackrel{\text{def}}{=} \sum_j \mathbf{s}_{ij} \Rightarrow \mathbf{s} \stackrel{\text{def}}{=} \sum_{ij} \mathbf{s}_{ij}, \quad 12$$

13 and thus, $\mathbf{s}_{ij} \cdot \mathbf{s} > 0$ for all subset elements. 13

14 This obviously generalizes to weighted symbols $\hat{\mathbf{s}}_i$, i.e., symbols with modality weighting. In that case, $\mathbf{s}_i \cdot \mathbf{s} \simeq \tau$
15 makes it possible to retrieve the belief weight. This is equivalent to inputting a symbol \mathbf{s}_i that is approximately
16 similar to a given symbol \mathbf{s}_i , thus indicating an approximate similarity; however, it neither allows us to retrieve the
17 exact value of \mathbf{s}_i nor indicates if a positive value below 1 corresponds to a weighted symbol that has been exactly
18 retrieved or to a symbol approximation. 18

19 This has an interesting biological interpretation: \mathcal{S} has features in common with a Hopfield network or other
20 related attractor networks, where information has been stored in a distributed way while activating the map with an
21 input makes it possible to determine whether the symbol is stored or not. This is also called self-associative. The
22 main difference with auto-associative, or clean-up memory, is that in Hopfield network attractor networks converge
23 to the exact stored value, providing a mechanism of associative memory, which is now developed while introducing
24 superposition, allowing us to better understand the need for a more sophisticated mechanism. 24

25 Let us provide an analogy with programming data structures, explicitizing the similarities and differences between
26 what is proposed here and what is available in common programming languages²⁵. This unordered set representation
27 corresponds to a “set” container (e.g., a `std::unordered_set` in C++ or a `set()` in Python) that has only an
28 insertion method and a membership test function, without the capability to intrinsically enumerate the elements, as
29 formerly discussed. 29

30 B.1.1. Symbol enumeration 30

31 At this stage, this structure does not allow us to directly enumerate all symbols \mathbf{s}_i , because from \mathbf{s} , it is not possible
32 to decode the superposed vectors. In [122], for instance, where data structures are defined using superposition, the
33 intrinsic memory enumeration of the stored information is not addressed. We thus need an external mechanism to
34 select all elements and perform an operation on each one. However, at the implementation level, in NENGO [164],
35 an explicit list of the defined vocabulary $\{\dots, \mathbf{s}_i, \dots\}$ is maintained, and the way to select the elements is to test
36 $(\mathbf{s}^T \mathbf{s}_i)$ for each element of the vocabulary. This select operator has a complexity of $O(K)$, where K is the size of
37 the vocabulary. Later in this paper, we will also propose a biologically plausible indexing mechanism, in order, for
38 instance, to manipulate sequences. 38

39 B.2. Associative map 39

40 We now consider an unordered associative memory, or “map,” of N correspondences $\{\mathbf{s}_1 \rightarrow \mathbf{o}_1, \dots, \mathbf{s}_i \rightarrow$
41 $\mathbf{o}_i, \dots, \mathbf{s}_N \rightarrow \mathbf{o}_N\}$ between subjects and objects. To this end, we use the binding operation $B_{\mathbf{s}_i}$, defined in Appendix C,
42 with a pseudo-inverse, i.e., an unbinding operator, $B_{\mathbf{s}_i}^\sim$: 42

$$43 \quad \mathbf{m} \stackrel{\text{def}}{=} \sum_i B_{\mathbf{s}_i}^\sim \mathbf{o}_i, \quad 43$$

44 so that 44

45
46
47
48
49
50
51 ²⁵We will do the same for other cognitive structures because we think that it illustrates the computing capability of the cognitive object. 51

$$B_{s_{\bullet}} \mathbf{m} \simeq \sum_{i, s_{\bullet} = s_i} \mathbf{o}_i + \mathbf{unknown},$$

where $\mathbf{unknown} \stackrel{\text{def}}{=} \sum_{s_{\bullet} \neq s_i} B_{s_{\bullet}} B_{s_i} \mathbf{o}_i$ is an ‘‘unknown’’ vector, i.e., a vector that has, in the general case, no similarity with the other vectors.

In other words, the unbinding operation makes it possible to retrieve up to an orthogonal vector $\mathbf{unknown}$ the set, i.e., the additive superposition of all objects \mathbf{o}_i associated with a given subject s_{\bullet} , while $B_{s_{\bullet}} \mathbf{m} = \mathbf{unknown}$ if none.

Then using a similarity operation:

$$B_{s_{\bullet}} \mathbf{m} \cdot \mathbf{o}_{\bullet} = \delta_{s_{\bullet} \rightarrow \mathbf{o}_{\bullet}} + v(O(1/d^{1/4}))$$

allows to check whether the value \mathbf{o}_{\bullet} is associated to the key s_{\bullet} . Here $v(O(1/d^{1/4}))$ comes from the unbinding operation uncertainty.

This is done up to a level of noise of $O(1/d^{1/4})$, as derived in Appendix C (while the dot-product with the unknown vector is of negligible magnitude with respect to the former source of uncertainty), which is rather high with respect to the similarity precision, which is $O(1/d)$, as observed numerically [443]; however, in biological neuronal networks, where the dimension is an order of magnitude higher, this is no longer a limitation because d is high.

This allows us to detect if the information is in the table in one step if this is the case. However, as in the previous case, no mechanism allows to explicitly retrieve the value of \mathbf{o}_i , or to generate the enumeration of the map subjects or objects.

In the literature, the notion of clean-up memory corresponds to auto-associative memory that retrieves an exact ‘‘clean-up’’ value of an existing symbol, given an approximate or noisy input of this symbol [472]. A step further, the notion of hetero-associative memory corresponds to storing input-output relationships [505]. It must be noted that in the NENGO simulator of the Neural Engineering Framework (NEF) hetero-associative memory the biologically plausible implementation is not directly based on the present binding/bundling algebraic mechanism but an input/output architecture with suitable connections is used instead. Each input unit has an encoding vector in which input weights are tuned to fire for a specific key and drive a connected output vector that is optimized to estimate the value associated with the related key [505]. An associative memory of structured knowledge has been studied in details, for an holographic reduced representation by [469], quantifying, depending on the design parameters, the memory performances.

This algebraic construction also makes it possible to retrieve the subjects associated with a given object, because of the commutator $\mathbf{B}_{\leftrightarrow}$, such that

$$\mathbf{B}_{\leftrightarrow} \mathbf{B}_{\mathbf{o}_i} \mathbf{s}_i = \mathbf{B}_{\mathbf{s}_i} \mathbf{o}_i,$$

yielding

$$\mathbf{m}_{\leftrightarrow} \stackrel{\text{def}}{=} \mathbf{B}_{\leftrightarrow} \mathbf{m} = \sum_i B_{\mathbf{o}_i} \mathbf{s}_i,$$

which is now the numerical grounding of the reciprocal map $\{\mathbf{o}_1 \rightarrow \mathbf{s}_1, \dots, \mathbf{o}_i \rightarrow \mathbf{s}_i \dots \mathbf{o}_N \rightarrow \mathbf{s}_N\}$.

The algebraic construction also offers the notion of the identity vector \mathbf{i} , with $\mathbf{B}_{\mathbf{i}} = \mathbf{I}$, so that

$$\mathbf{s}_i = \mathbf{i} \rightarrow B_{\mathbf{s}_i} \mathbf{o}_i = \mathbf{o}_i.$$

In other words, the binding reduces to a superposition. Theoretical details underlying the implementation of such associative memories are available in [472].

As for the previous structure, this obviously generalizes to weighted symbols \hat{s}_i and an approximate input $\mathbf{s}_{\bullet} \simeq \hat{\mathbf{s}}_i$, allowing us to retrieve the object \mathbf{o}_i weighted by either the modality weighting or the input approximation, indistinctly.

There are several solutions used to define such binding, unbinding, and commutator operators. A proposed solution is developed in Appendix C after the work in [203], which was completed by [335]. This design choice is guided by the fact that we need to avoid spurious inferences: With a binding commutative operator (such as the convolution operator), $\mathbf{B}_{\mathbf{o}_i} \mathbf{s}_i$ would equal $\mathbf{B}_{\mathbf{s}_i} \mathbf{o}_i$, which could generate nonsense deductions (e.g., for a driver-vehicle map, this would mean that if Ming-Yue drives a bicycle, then the bicycle drives Ming-Yue unless some additional mechanism is considered to avoid such nonsense). The proposed VTB algebra avoids such caveats (see [443] for a

recent comparison of different VSAs)²⁶. A commutative binding operator can be used for auto-associative memory [472] or if key and values do not belong to the same symbol set, e.g., considering “symbol id” and “symbol value” [122].

This associative memory mechanism has an interesting biological interpretation: It implements an associative memory in the biological sense, with the association stored in a distributed way, and activating the associative memory with an input \mathbf{s}_i allows us to retrieve the associated symbol. This is what happens in several biological mechanisms, as reviewed, for instance, in [159].

In particular, a structure of the form

$$\mathbf{m} \stackrel{\text{def}}{=} \sum_n B_{\mathbf{s}_i} \mathbf{s}_i$$

that maps an object onto itself allows the retrieval of an exact symbol from an approximate input, solving the caveats induced by using only a superposition mechanism that was presented previously. This is exactly what is expected in an associative encoder (e.g., a Hopfield network); if a symbol is close to an existing symbol, the associative memory will output a weighted version of the symbol.

At the computer programming level, this corresponds to a “map” container (e.g., a Map in JavaScript or a dictionary() in Python), again with only insertion and retrieval methods, and without intrinsic iterators.

To take this a step further, we can propose a complementary functionality, defining an additional symbol “something” whose numerical grounding is fixed to any new random vector σ that is never used elsewhere. This allows us to enhance the information to be obtained as follows: Each time a piece of information $\mathbf{s}_i \rightarrow \mathbf{o}_i$ is added, we also add $\mathbf{s}_i \rightarrow \sigma$ and $\sigma \rightarrow \mathbf{o}_i$, i.e., we make explicit the fact that \mathbf{s}_i and \mathbf{o}_i are defined in this table, which can be retrieved in one step, without the need to enumerate the different elements. In such a case,

$$\mathbf{m}_{\mathbf{s}_i} \stackrel{\text{def}}{=} \sum_{i, \mathbf{s}_j = \mathbf{s}_i} \mathbf{o}_i = P_{\sigma^\perp} B_{\mathbf{s}_i} \mathbf{m} + \mathbf{unknown},$$

where $P_{\sigma^\perp} \stackrel{\text{def}}{=} \mathbf{I} - \sigma \sigma^T$ is the projection onto the orthogonal of σ , i.e., we must eliminate the symbol “something” from the expected values.

B.3. Associative network

We also can consider for N correspondences $\{\mathbf{s}_1 \rightarrow \mathbf{o}_1, \dots, \mathbf{s}_i \rightarrow \mathbf{o}_i, \dots, \mathbf{s}_N \rightarrow \mathbf{o}_N\}$ between subjects and objects, an associative network of the form:

$$\mathbf{M} \stackrel{\text{def}}{=} \sum_i \mathbf{o}_i \mathbf{s}_i^T,$$

which is no more a vector, but a matrix, allowing one to explicitly retrieve the object since:

$$\mathbf{M} \mathbf{s}_i = \|\mathbf{s}_i\|^2 \mathbf{o}_i + \nu((N-1)/d),$$

as obtained from obvious algebra.

This corresponds to a macroscopic implementation of associative networks, as proposed, e.g. in [122]. With respect to the previous associative map we recover directly the object value up to a scale and additive noise, beyond only testing if it is in the map or not.

It is worth noticing that \mathbf{M}^T allows to retrieve keys associated with a given value, while we also can consider a “multi-map” i.e. associate the bundling of several values to a given key.

B.4. Indexed and chained list

B.4.1. Construction of indexes

In order to define an indexed list, we need indexes, i.e., a mechanism that generates ordinal values. Our main purpose here is to make explicit that what has been developed using convolution operators [275] still holds with VTB. We fix the symbol grounding of the “zero” symbol ν_0 , which is never used elsewhere, and define the following recursively:

²⁶An alternative to VTB algebra is called MBAT algebra; it requires matrix inversion instead of transposition, and thus it is less efficient.

$$v_{n+1} \stackrel{\text{def}}{=} B_{v_0} v_n,$$

i.e., the $(n+1)$ -th ordinal value is obtained by binding the n -th, and we easily obtain, from a few algebra operations,

$$B_{v_p} v_q = B_{v_q} v_p = B_{v_{p+q}} v_0, \quad B_{v_p} v_q^\sim = B_{v_q^\sim} v_p \simeq B_{v_{p-q}} v_0.$$

In particular, $v_{n-1} \simeq B_{v_0^\sim} v_n$, so that the definition holds for $n \in \mathcal{Z}$.

Here, we only consider the minimal material needed to build an indexed list; numerical information in the brain is a much more complex subject [365] beyond the scope of this work.

In fact, what has not been noticed previously is the fact that the accumulation of binding operations leads to an important increase of noise, more precisely:

$$v_n = (B_{v_0})^n v_0 + v(O(n/d^{1/4}))$$

so that for as soon as $n^4 > d$ the noise order of magnitude is higher than 1, i.e., the value order of magnitude. However, this is not a problem in practice because as soon as we do not repeat the calculation twice, i.e., we do not redraw the values, but keep trace of the previous pre-calculated values, so that each “number” has a unique vector as identifier.

B.4.2. Indexed list

We can now define an indexed list or array, often called a vector, since the previous mechanism allows us to generate a “counter” that can be incremented or decremented using the binding or unbinding operator.

To this end, an associative map indexed by these ordinals can be managed as a list whose values can be enumerated. Such a representation is also present at several cognitive levels when considering temporal sequences, actions, or any enumeration. This is also the tool that allows us to enumerate all elements of a symbol set \mathcal{S} , which was defined previously, or the subjects of an associative map.

To make this mechanism explicit, let us consider a list $\mathbf{l} \stackrel{\text{def}}{=} \sum_i B_{v_i} \mathbf{l}_i$, and a variable index \mathbf{k} . A construct of the form

```

for  $\mathbf{k} \leftarrow v_0$ ; while  $\|B_{\mathbf{k}} \mathbf{l}\| > 0$ ; next  $\mathbf{k} \leftarrow B_{v_0} \mathbf{k}$  do
   $\mathbf{l}_i \leftarrow B_{\mathbf{k}} \mathbf{l}$ 
  ..
end for

```

allows us to enumerate²⁷ all elements, this being indeed only an algorithmic ersatz to illustrate the mechanism beyond the biologically plausible implementation of sequential memory organization.

At the biological plausibility level, following [159], we may consider that the brain can have three kinds of memory: associative, sequential, and hierarchical (called schematic by the author of [159]) memory. All three memory types are present and required for cognitive processes. The VSA approach provides both associative and sequential memory. Let us consider the third type of memory, which has not, to the best of our knowledge, been addressed with regard to VSAs.

At the computer programming level, this corresponds to an extensible “array” (e.g., a `std::vector` in C++ or `java.util.AbstractList` in Java), with basic edition and retrieval methods available.

B.4.3. Chained list

We can also define a chained list using an associative memory of the form

```

first  $\rightarrow$  second
second  $\rightarrow$  third
...
last  $\rightarrow$  END + first

```

where every value of the list acts as a key to the value of its successor in the list, thus enumerating the values. END

²⁷In fact, considering $\mathbf{l} \stackrel{\text{def}}{=} \sum_i B_{v_i} \mathbf{l}_i + B_{v_{-1}} \lambda$, where λ is the list length, which is updated when an element is added or deleted, would improve the algorithmic ersatz implementation, which is not the issue here.

is a predefined specific symbol that makes it possible to know when the list ends that we can superpose to a pointer to the first value in case we need to iterate through the entire list again.

We also could have considered multiple binding²⁸, as proposed in [335].

Appendix C. Using VTB algebra

At the mesoscopic level, symbols represent a numerical grounding to real or complex vectors of dimension d , with each numerical grounding corresponding to some distributed activity of a spiking neuronal assembly and each algebraic operation corresponding to some transformation of this activity.

Let us review and further develop one of the algebras used to manipulate such symbols at an abstract level in this paper: vector-derived transformation binding (VTB) algebra. We follow [203] and complete the developments in that paper by deriving the different operations at the component level, yielding an optimal implementation and making explicit the computational complexity and related first-order noise. This is in particular used in section 4 to derive the macroscopic computations.

We also have to reconsider the binding output magnitude since vector magnitudes correspond to a belief value, as discussed in section 2.2.

We consider that $d \stackrel{\text{def}}{=} (d')^2$ for some integer d' ; thus, it is a quadratic number and we start from the standard definition of the VTB binding operation:

$$\mathbf{z} \stackrel{\text{def}}{=} \mathbf{B}_y \mathbf{x},$$

where \mathbf{B}_y is a block-diagonal matrix defined as follows:

$$\mathbf{B}_y \stackrel{\text{def}}{=} \begin{bmatrix} \mathbf{B}'_y & 0 & \dots & 0 \\ 0 & \mathbf{B}'_y & \dots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & \mathbf{B}'_y \end{bmatrix}, \text{ with } \mathbf{B}'_y \stackrel{\text{def}}{=} \sqrt{d'} \begin{bmatrix} y_1 & y_2 & \dots & y_{d'} \\ y_{d'+1} & y_{d'+2} & \dots & y_{2d'} \\ \vdots & \vdots & \ddots & \vdots \\ y_{d-d'+1} & y_{d-d'+2} & \dots & y_d \end{bmatrix},$$

or equivalently²⁹, for $i = 1 \dots d$,

$$\begin{cases} [\mathbf{z}]_i \stackrel{\text{def}}{=} \mathbf{B}_y \mathbf{x} = \sqrt{d'} \sum_{k=1}^{k=d'} [\mathbf{y}]_{k+\beta(i)} [\mathbf{x}]_{k+\alpha(i)}, \\ [\mathbf{B}_y]_{ij} \stackrel{\text{def}}{=} \sqrt{d'} \delta_{i \leq d'} \text{ and } j \leq d' [\mathbf{y}]_{k+\beta(i)-\alpha(i)}, \end{cases} \quad (1)$$

written $\begin{cases} \alpha(i) \stackrel{\text{def}}{=} d' ((i-1) \text{ div } d'), \\ \beta(i) \stackrel{\text{def}}{=} d' ((i-1) \text{ mod } d'), \end{cases}$

with the matrix multiplication explicitized as a sum, which can be easily verified. Here, $[\mathbf{z}]_k$ stands for the k -th coordinate of the vector \mathbf{z} , and $\delta_{\mathcal{P}}$ is 1 if \mathcal{P} is true; otherwise, it is 0. This is our basic definition, and reformulating the VTB operation using (1) will allow us to better understand its properties.

This operation is bi-linear in \mathbf{x} and \mathbf{y} , and thus it is distributive with respect to addition and the scalar product.

Since \mathbf{y} and \mathbf{x} are random vectors $[\mathbf{z}]_i$, in (1) is estimated up to a standard-deviation³⁰ of $O(1/d^{1/4})$ which is an order of magnitude higher than for similarity estimation, which related standard-deviation was of $O(1/d)$. This also

²⁸In such a case, a list of the form $l = [v_1, v_2, \dots]$ is encoded without associative memory as

$$\mathbf{l} = B_{\text{value}} \mathbf{v}_1 + B_{\text{next}} (B_{\text{value}} \mathbf{v}_2 + B_{\text{next}} (\dots + B_{\text{next}} (\text{list-end}))),$$

allowing us to obtain by unbinding the list's head value and its tail value, and allowing us to detect its end. This corresponds, for instance, to the `rdf:first`, `rdf:rest`, and `rdf:nil` symbols of the RDF representation. However, as discussed in Appendix C, chaining unbinding operations is not numerically very robust due to the additional residual noise.

²⁹All algebraic derivations reported here are straightforward and were verified using a piece of symbolic algebra code available at <https://raw.githubusercontent.com/vthierry/onto2spa/main/figures/VTB-algebra.mpl>.

³⁰Each component $[\mathbf{z}]_i$ corresponds to the computation of a dot-product between two d' dimensional vectors, yielding a standard-deviation of $O(1/d')$, renormalized by $\sqrt{d'} = d^{1/4}$, leading to the final order of magnitude. As for similarity estimation, chi-square distribution is approximated by a normal distribution of the same standard-deviation, which is known as a conservative choice.

explains the relatively limited numerical performances of simulations with $d < 10^3$, as reported, for instance, in [443].

The $\sqrt{d'}$ renormalization factor allows \mathbf{z} to have a unary order of magnitude³¹. However, the magnitude is not exactly one, but³²:

$$\|\mathbf{B}_y \mathbf{x}\| \simeq \begin{cases} \|\mathbf{y}\| \|\mathbf{x}\| & \text{if } \mathbf{y} \perp \mathbf{x} \\ \sqrt{2} \|\mathbf{y}\| \|\mathbf{x}\| & \text{if } \mathbf{y} \parallel \mathbf{x} \end{cases}$$

which is of importance in our context since the magnitude of the vector corresponds to the τ value.

At the algorithmic implementation level, the calculation of \mathbf{z} is performed in³³ $O(d^{\frac{3}{2}})$ operations, and the $\mathbf{y}_{k+\beta[i]}$ and $\mathbf{x}_{k+\alpha[i]}$ indexing can be tabulated in two fixed look-up tables $\beta[i]$ and $\alpha[i]$, avoiding any additional calculations. Furthermore, the fact that $\sqrt{d'}$ is an integer makes it possible to limit numerical approximations in order to improve numerical conditioning. This will be verified for all other explicit formulae later in this paper. We make explicit these formulae in detail not to re-implement these operations, which are already available in the NENGO simulator, but to study in detail their complexity and their precision, with the goal of proposing a macroscopic algorithmic ersatz of these operations.

This can be compared to the fastest binding operation, which is convolution implemented via the fast Fourier transform [443], and thus it has a complexity of $O(d \log(d))$:

	d = 10	d = 100	d = 500	d = 1000	d = 10000
VTB	$10^{1.5}$	10^3	10^4	$10^{4.5}$	10^6
Convolution	$10^{1.4}$	$10^{2.6}$	$10^{3.5}$	$10^{3.8}$	10^5
Ratio = $\frac{\sqrt{d}}{\log(d)}$	$\simeq 1$	$\simeq 2$	$\simeq 3.5$	$\simeq 4.5$	$\simeq 10$

However, at the implementation level, we are going to observe that due to compiler and on-line processor optimization, the average computation time is an order of magnitude lower, because the VTB binding formula in eq. (1) is easy to optimize.

As stated in [203] and reviewed in [335], the key point is that this binding operation generates a new vector \mathbf{z} that is almost orthogonal to \mathbf{x} and \mathbf{y} :

$$(\mathbf{B}_y \mathbf{x}) \cdot \mathbf{x} \simeq 0,$$

and this operation is neither commutative,

$$(\mathbf{B}_x \mathbf{y}) \cdot (\mathbf{B}_y \mathbf{x}) \simeq 0,$$

nor associative³⁴, in the following sense:

$$(\mathbf{B}_{(\mathbf{B}_z \mathbf{y})} \mathbf{x}) \cdot ((\mathbf{B}_z \mathbf{B}_y) \mathbf{x}) \simeq 0.$$

³¹More precisely, two random normalized vectors of dimension d drawn from a random normal distribution of independent samples verify that $\mathbf{x} \cdot \mathbf{y} \sim \mathcal{N}(0, 1/d')$, as described in subsection 2.1. Then, applying a permutation on all indices on a random vector \mathbf{x} yields another random vector, which is not correlated with any vector \mathbf{y} if \mathbf{x} is not. Thus, when computing the components $[\mathbf{z}]_i$ in (1) for two general random vectors \mathbf{x} and \mathbf{y} , we compute the dot product of two random vectors of dimension d' renormalized by $\sqrt{d'}$, and thus this dot product comes from the distribution $\mathcal{N}(0, 1)$; this corresponds to drawing a random vector unary on average.

³²We can easily derive:

$$\begin{aligned} \|\mathbf{B}_y \mathbf{x}\|^2 &= d' \sum_{i=1}^d (\sum_{k=1}^{k=d'} [\mathbf{y}]_{k+\beta(i)} [\mathbf{x}]_{k+\alpha(i)}) (\sum_{l=1}^{l=d'} [\mathbf{y}]_{l+\beta(i)} [\mathbf{x}]_{l+\alpha(i)}) \\ &= d' \sum_{ikl} [\mathbf{y}]_{k+\beta(i)} [\mathbf{x}]_{k+\alpha(i)} [\mathbf{y}]_{l+\beta(i)} [\mathbf{x}]_{l+\alpha(i)} \\ &= d' \sum_{ik} ([\mathbf{y}]_{k+\beta(i)} [\mathbf{x}]_{k+\alpha(i)})^2 + \text{noise}, \end{aligned}$$

the 1st line being obtained by substitution from the definition, the 2nd line by expansion, and the 3rd line being obtained by considering that if $k \neq l$ we are multiply four almost independent random distribution which product expectation cancel in average (i.e., formally: $E[Y_k X_k Y_l X_l] = E[Y_k]E[X_k]E[Y_l]E[X_l] \simeq 0$ by construction). If $\mathbf{y} \perp \mathbf{x}$ we are left with numerically approximating the mean of the square of normal distribution, i.e., its second momentum, equal to 1. If $\mathbf{y} \parallel \mathbf{x}$ we are left with numerically approximating the mean of the fourth power of a normal distribution, i.e., its fourth momentum, equal to 2 (it is known that if X is centered normal variable of unary standard deviation, then $E[X^{2n}] = (2 - 1)!!$ where !! denotes the double factorial, i.e., the product of all numbers down to 1 which have the same parity as the argument.)

³³Each of the d components $[\mathbf{z}]_i$ requires a dot product of size $d' = \sqrt{d}$ that is not factorizable in the general case, since involving different elements of the vectors as readable on the matrix form.

³⁴Of course, as a product of matrices, the combination of three bindings or two binding operations and a vector is associative, but the operator \mathbf{B} itself is not, as made explicit in the formula.

These properties ensure that we do not infer spurious derivations.

To take this a step further, in the real case, the random matrix is almost orthogonal, i.e.,

$$\mathbf{B}_y^\top \mathbf{B}_y \simeq \mathbf{I},$$

for the same reasons evoked above³⁵.

We thus define

$$\mathbf{B}_{y\sim} \stackrel{\text{def}}{=} \mathbf{B}_y^\top \text{ with } [y\sim]_i \stackrel{\text{def}}{=} [y]_{\sigma(i)},$$

with

$$\sigma(i) \stackrel{\text{def}}{=} 1 + d' ((i - 1) \bmod d') + (i - 1) \operatorname{div} d'.$$

In other words, $\mathbf{B}_{y\sim}^\top$ has the same structure as \mathbf{B}_y , except that the vector coordinates are subject to a permutation $\sigma(i)$, which is idempotent ($\sigma(\sigma(i)) = i$) and thus its own inverse, so that if $\mathbf{z}' \stackrel{\text{def}}{=} \mathbf{B}_{y\sim} \mathbf{x}$, we obtain

$$[z']_i = \sqrt{d'} \sum_{k=1}^{k=d'} [y]_{\sigma(k+\beta(i))} [x]_{(k+\alpha(i))}$$

(where $\beta(i)$ and $\alpha(i)$ are the indexing defined to calculate $\mathbf{B}_y \mathbf{x}$ explicitly), and this makes it possible to define a left unbinding operation:

$$\mathbf{B}_{y\sim} (\mathbf{B}_y \mathbf{x}) = \mathbf{B}_y^\top \mathbf{B}_y \mathbf{x} = \mathbf{x} + \text{noise} \simeq \mathbf{x}.$$

From similar derivations as detailed in footnote³², also verified at the numerical level, we obtain for the magnitude:

$$\|\mathbf{B}_{y\sim} \mathbf{B}_y \mathbf{x}\| \simeq \begin{cases} \sqrt{2} \|\mathbf{y}\|^2 \|\mathbf{x}\| & \text{if } \mathbf{y} \perp \mathbf{x} \\ \sqrt{5} \|\mathbf{y}\|^2 \|\mathbf{x}\| & \text{if } \mathbf{y} \parallel \mathbf{x}, \end{cases}$$

which is to be considered to properly normalize unbinding operations at the mesoscopic level.

The right identity vector \mathbf{i} such that $\mathbf{B}_i = \mathbf{I}$ can be written explicitly as follows:

$$[i]_i = \frac{1}{\sqrt{d'}} \delta_{i=\sigma(i)}.$$

In other words, we get i_B by “unfolding” the identity matrix I'_d line by line, writing a 1, then d times 0, then another 1, and so on.

Considering the mirroring matrix $\mathbf{B}_{\leftrightarrow}$, which is defined as

$$[\mathbf{B}_{\leftrightarrow}]_{ij} \stackrel{\text{def}}{=} \delta_{j=\sigma(i)}$$

(which is thus not block-diagonal in the way that a matrix of the form \mathbf{B}_y is), so that:

$$\mathbf{B}_{\leftrightarrow} \mathbf{x} = \mathbf{x}\sim,$$

we obtain

$$\mathbf{B}_{\leftrightarrow} \mathbf{B}_y \mathbf{x} = \mathbf{B}_x \mathbf{y}, \text{ while } \mathbf{B}_{\leftrightarrow} \mathbf{B}_{\leftrightarrow} = \mathbf{I} \text{ and } \mathbf{B}_{\leftrightarrow}^\top = \mathbf{B}_{\leftrightarrow},$$

which makes it possible to define a right unbinding operation:

$$(\mathbf{B}_x \sim \mathbf{B}_{\leftrightarrow}) (\mathbf{B}_y \mathbf{x}) = \mathbf{B}_x \sim \mathbf{B}_x \mathbf{y} \simeq \mathbf{y},$$

and expand nested binding operations:

$$\mathbf{B}_{\mathbf{B}_y} \mathbf{x} = \mathbf{B}_{\leftrightarrow} \mathbf{B}_x \mathbf{B}_y.$$

³⁵From (1), we derive

$$\begin{aligned} [\mathbf{B}_y^\top \mathbf{B}_y]_{ij} &= \sum_{k=1}^{d'} [\mathbf{B}_y]_{ki} [\mathbf{B}_y]_{kj} \\ &= d' \sum_{k=1}^{d'} [y]_{k+\beta(i)-\alpha(i)} [y]_{k+\beta(j)-\alpha(j)} \\ &= d' \sum_{l=1}^{d'} [y]_l [y]_{k+(\beta(j)-\beta(i))-(\alpha(j)-\alpha(i))} \\ &= d' \sum_{l=1}^{d'} [y]_l [y]_{k+d'((j-i) \operatorname{div} d') - ((j-i) \operatorname{div} d')}. \end{aligned}$$

- $[\mathbf{B}_y^\top \mathbf{B}_y]_{ii} = \sum_{l=1}^{d'} [y]_l^2 = 1 + \text{noise}$; and

- $[\mathbf{B}_y^\top \mathbf{B}_y]_{ij, i \neq j} = 0 + \text{noise}$, because it is easy to verify that $((j-i) \operatorname{div} d') - ((j-i) \operatorname{div} d') \neq 0$ when $i \neq j$, so that the dot product of d' random components of $[y]_l$ with d' other random components yields approximately normal noise.

This could extend the actual binding algebra considering the dual operator \sim .

Unfortunately, $\mathbf{B}_{\leftrightarrow}$ is not a binding matrix, i.e., it is not of the form \mathbf{B}_z for some vector z , which is easily verified by the fact that some components that must be equal to 0 for a binding matrix are equal to 1 in $\mathbf{B}_{\leftrightarrow}$. Furthermore, the left or right multiplication of a binding matrix by this mirroring matrix does not yield a binding matrix, because of the same observation; components that must be equal to 0 for a binding matrix are equal to 1 in $\mathbf{B}_{\leftrightarrow}$.

Beyond [203], the authors of [335] introduced a vector composition operator \odot to make explicit the composition of two binding operations, namely,

$$\mathbf{B}_v = \mathbf{B}_y \mathbf{B}_x \Leftrightarrow v \stackrel{\text{def}}{=} y \odot x,$$

which can be explicitly written as follows³⁶:

$$[v]_i = \sqrt{d'} \sum_{k=1}^{k=d'} [y]_{(i-1)d'+k} [x]_{1+d'(k-1)+(i-1) \bmod d'}.$$

At the algebraic level, the key point is that the product of two binding matrices is still a binding matrix. As a consequence, this composition operator is bi-linear, and thus it is distributive with respect to addition; it is not commutative, but it is associative and commutes with the inversion as follows:

$$(y \odot x) \sim = x \sim \odot y \sim,$$

while $x \sim \odot x \simeq \mathbf{i}$; all these results can be easily derived by considering usual matrix properties. This allows us to combine two binding matrices without an explicit matrix product in $O(d^{\frac{3}{2}})$ operations only. At the numeric level, since v is up to a $\sqrt{d'}$ factor, the dot product of segments of random vectors of dimension d' , we obtain the same order of magnitude of noise level, as discussed previously. Altogether this can enrich the actual binding algebra to obtain more elegant formulas, in particular when combinations of binding operations are used.

Using VTB algebra in the complex case

All of the developments described in this section generalize to complex numbers. Although it is not directly used here, such a generalization is of general interest because complex implementations of VSA frameworks have also been considered [443]. Furthermore, it is also of interest to see if our macroscopic implementation could be easily adapted to the complex case.

Stating that two resources are semantically equivalent if the unary vectors are aligned can be written in the complex case as follows³⁷:

³⁶Since \mathbf{B}_y and \mathbf{B}_x are block-diagonal matrices, it is easy to verify that \mathbf{B}_v is a block-diagonal matrix with a $d' \times d'$ block $\mathbf{B}_v' = \mathbf{B}_y' \mathbf{B}_x'$ using the notation from the beginning of this section, and we can explicitly write that

$$[\mathbf{B}_v']_{ij} = \sqrt{d'} \sqrt{d'} \sum_{k=1}^{d'} [y]_{k+(i-1)d'} \text{div } d' [x]_{(k-1)d'+j},$$

from which we obtain the desired formula.

³⁷If we are in the real case x and $y \in \mathcal{R}^d$, with $\|x\|_2 = \|y\|_2 = 1$, then the equality is written as

$$x = y \Leftrightarrow x \cdot y = \sum_i x_i y_i = \cos(\widehat{x \ y}) = 1 \Leftrightarrow \widehat{x \ y} = 0 \pmod{2\Pi},$$

i.e., both unary vectors have the same direction; in other words, they are aligned. If we are in the complex case x and $y \in \mathcal{C}^d$, let us consider the canonical embedding in \mathcal{R}^{2d} , i.e., we consider the real (*Re*) and imaginary (*Im*) parts as two real coordinates, denoting by \vec{x} the corresponding vector:

$$x \stackrel{\text{def}}{=} (x_1, x_2, \dots)^T \Leftrightarrow \vec{x} \stackrel{\text{def}}{=} (Re(x_1), Im(x_1), Re(x_2), Im(x_2), \dots)^T,$$

where z^* is the conjugate of a complex number z , while $\langle x|y \rangle$ stands for the complex inner product:

$$\begin{aligned} \langle x|y \rangle &\stackrel{\text{def}}{=} \sum_i x_i y_i^* \\ &= \sum_i (Re(x_i) Re(y_i) + Im(x_i) Im(y_i)) + I (Re(x_i) Im(y_i) - Im(x_i) Re(y_i)) \\ &= \vec{x} \cdot \vec{y} + I \vec{x}^* \cdot \vec{y}, \end{aligned}$$

so that $Re(\langle x|y \rangle) = \vec{x} \cdot \vec{y}$ and $\|x\| = \sqrt{\langle x|x \rangle} = \|\vec{x}\| - 2 = \sqrt{\vec{x} \cdot \vec{x}}$, and since vectors are unary,

$$\langle x|y \rangle = 1 \Leftrightarrow \vec{x} \cdot \vec{y} = 1 \Leftrightarrow \vec{x} = \vec{y} \Leftrightarrow x = y,$$

making explicit the obvious fact that unary real or complex vectors are equal if and only if their inner product equals one, while we consider the “angle” of two complex vectors as the angle of their $2d$ real embedding, i.e.,

$$\mathbf{x} \simeq \mathbf{y} \Leftrightarrow \langle \mathbf{x} | \mathbf{y} \rangle \simeq 1,$$

while the orientation is usually defined as

$$\widehat{\mathbf{x} | \mathbf{y}} \stackrel{\text{def}}{=} \arccos(\text{Re}(\langle \mathbf{x} | \mathbf{y} \rangle)),$$

as explained in the previous footnote.

Provided that the space dimension d is large enough, two randomly chosen different complex vectors \mathbf{x} and \mathbf{y} ³⁸ will also be approximately orthogonal in the sense that

$$\mathbf{x} \neq \mathbf{y} \Leftrightarrow \langle \mathbf{x} | \mathbf{y} \rangle \simeq 0.$$

As a consequence, the VTB matrix is almost a unitary matrix, i.e.,

$$\mathbf{B}_y^* \mathbf{B}_y \simeq \mathbf{I},$$

considering the conjugate transpose.

All other algebraic operations are common to both real and complex linear algebra, and this is also the case for other VSA binding operators.

More than just a confirmation, these derivations allow us to observe that using a complex representation would be interesting if the conjugate of a vector could have a semantic interpretation. In that case, if, say, \mathbf{x} and \mathbf{y}^* are similar, then $\langle \mathbf{x} | \mathbf{y} \rangle \simeq I$, as easily verified from the previous derivations.

$$\widehat{\mathbf{x} | \mathbf{y}} \stackrel{\text{def}}{=} \arccos(\text{Re}(\langle \mathbf{x} | \mathbf{y} \rangle)).$$

³⁸Considering again the canonical embedding in \mathcal{R}^{2d} and the fact that

$$\langle \mathbf{x} | \mathbf{y} \rangle = \vec{\mathbf{x}} \cdot \vec{\mathbf{y}} + I \vec{\mathbf{x}}^* \cdot \vec{\mathbf{y}},$$

because $\vec{\mathbf{x}}$ and thus $\vec{\mathbf{x}}^*$ and $\vec{\mathbf{y}}$ are random vectors, their dot product almost vanishes; thus, the real and imaginary parts of $\langle \mathbf{x} | \mathbf{y} \rangle$ also almost vanish.

[I]:	[{b y: c x: [a b]} {b y: c x: [b a]}]
[P]:	[B_(c) ([a b]_<1.4±0>)_<1.4±0.044> B_(c) ([a b]_<1.4±0>)_<1.4±0.044>]_<2±0.088>
[R]:	[B_(c) (a)_<2±0.062> B_(c) (b)_<2±0.062>]_<2.8±0.12>
[I]:	[{name: a tau: 0.5 sigma: 0.1} []] {name: a tau: 0.5 sigma: 0.1}]
[P]:	[a_<1±0.2>]_<1±0.2>
[R]:	a_<1±0.2>
[I]:	{b y: a x: {u y: a x: [{name: c tau: 2 sigma: 0.1}]}}
[P]:	B_(a) (B_(a^)) ([c_<2±0.1>]_<2±0.1>)_<2±0.066>)_<2±0.065>
[R]:	c_<8±0.23>
[I]:	{b y: c x: {b y: c x: {b y: c x: {u y: c x: {u y: c x: {u y: c x: a}}}}}}
[P]:	B_(c) (B_(c) (B_(c^)) (B_(c^)) (B_(c^)) (a)_<1±0.031>)_<1±0.032>)_<1±0.032>)_<1±0.032>)_<1±0.032>)_<1±0.032>)_<1±0.032>
[R]:	a_<1±0.19>

Table 2: Four symbolic reduction examples.

- The [I] line corresponds to the Input of the symbolic expression in weak JSON syntax.
 - The [P] line corresponds to the Parsed expression.
 - The [R] line corresponds to the Reduced expression.
- Bindings are represented as a list between [], Binding using the usual syntax, while the $\langle \tau \pm \sigma \rangle$ construct allows to specify the belief value, when not equal to the default $\langle 1 \pm 0 \rangle$ value.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51

Dimension:	100	400	1024	2500	4096	10000
Mesoscopic bias and standard-deviation estimation over 1000 samples						
$\mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	0.00041±0.1	-0.002±0.052	-7.9e-05±0.031	-0.00014±0.02	-0.00062±0.015	0.00061±0.0097
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	-0.0007±0.24	-0.0068±0.11	0.004±0.071	0.0016±0.042	-0.0002±0.035	0.0013±0.022
$\mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	0.0005±0.14	0.0014±0.072	0.0011±0.045	0.00016±0.028	0.00025±0.023	0.0006±0.014
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	-0.0007±0.24	-0.0068±0.11	0.004±0.071	0.0016±0.042	-0.0002±0.035	0.0013±0.022
Macroscopic prediction of $\tau \pm \sigma$ (i.e. standard-deviation)						
$\mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	1±0.11	1±0.081	1±0.063	1±0.051	1±0.045	1±0.036
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	1±0.23	1±0.16	1±0.13	1±0.1	1±0.09	1±0.072
$\mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	1±0.11	1±0.081	1±0.063	1±0.051	1±0.045	1±0.036
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	1±0.23	1±0.16	1±0.13	1±0.1	1±0.09	1±0.072
Standard-deviation over-prediction						
$\mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	1.1	1.5	2	2.6	2.9	3.7
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{x} \cdot \mathbf{x}$	0.98	1.5	1.8	2.4	2.6	3.2
$\mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	0.82	1.1	1.4	1.8	2	2.5
$\mathbf{B}_y \sim \mathbf{B}_y \mathbf{y} \cdot \mathbf{y}$	0.98	1.5	1.8	2.4	2.6	3.2

Table 3: Mesoscopic versus macroscopic noise estimation.

- The 1st bloc corresponds to mesoscopic bias and standard-deviation estimation over 1000 samples, of basic expression similarities, at different vector space dimensions. The mesoscopic noise standard-deviation is estimated by computing dot-products over $N = 1000$ samples.
- The 2nd bloc corresponds to the macroscopic prediction of the mesoscopic standard-deviation estimation, as developed in this paper.
- The 3rd bloc shows the ratio between macroscopic / mesoscopic standard-deviation, showing the overestimation, while the order of magnitude is preserved.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
511
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51

Dimension:	100	400	1024	2500	4096	10000
$\ \mathbf{B}_y \mathbf{x}\ ^2$	1 ± 0.14	1 ± 0.073	1 ± 0.043	1 ± 0.027	1 ± 0.023	1 ± 0.014
$\ \mathbf{B}_y \sim \mathbf{B}_y \mathbf{x}\ ^2$	2.1 ± 0.51	2 ± 0.25	2 ± 0.15	2 ± 0.095	2 ± 0.081	2 ± 0.049
$\ \mathbf{B}_y \mathbf{y}\ ^2$	2.1 ± 0.2	2 ± 0.1	2 ± 0.059	2 ± 0.039	2 ± 0.033	2 ± 0.02
$\ \mathbf{B}_y \sim \mathbf{B}_y \mathbf{y}\ ^2$	5.3 ± 1.2	5.2 ± 0.64	5.1 ± 0.36	5.1 ± 0.25	5.1 ± 0.2	5.1 ± 0.13

Table 4

Mesoscopic computation of VTB binding magnitudes, over $N = 1000$ samples: mean \pm standard-deviation is shown. This allows to verify what has been derived in Appendix C, regarding this aspect.