

# A Robust A Posteriori Error Estimate for Elliptic Non-Homogeneous Equations

Rodolfo Araya, Patrick Le Tallec

### ▶ To cite this version:

Rodolfo Araya, Patrick Le Tallec. A Robust A Posteriori Error Estimate for Elliptic Non-Homogeneous Equations. [Research Report] RR-3279, INRIA. 1997. inria-00073410

# HAL Id: inria-00073410 https://inria.hal.science/inria-00073410

Submitted on 24 May 2006

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



INSTITUT NATIONAL DE RECHERCHE EN INFORMATIQUE ET EN AUTOMATIQUE

# A Robust A Posteriori Error Estimate for Elliptic Non-Homogeneous Equations

R. Araya & P. Le Tallec

N 3279

October 1997

\_\_\_\_\_ THÈME 4 \_\_\_\_\_





# A Robust A Posteriori Error Estimate for Elliptic Non-Homogeneous Equations

R. Araya\* & P. Le Tallec<sup>†</sup>

Thème 4 — Simulation et optimisation de systèmes complexes Projet M3N

Rapport de recherche n° 3279 — October 1997 — 47 pages

**Abstract:** In this paper we present a new *a posteriori* error estimate for strongly heterogeneous elasticity problems. This new approach is based on a simple modification of the well known residual estimate, but with the nice property that it is correctly dimensionalised with respect to the physical data.

**Key-words:** A posteriori error estimate, Poisson's equation, linear elasticity, residuals, heterogeneity.

(Résumé : tsvp)

<sup>\*</sup> INRIA, Domaine de Voluceau- Rocquencourt- B.P. 105- Le Chesnay Cedex (France) e-mail: Rodolfo.Araya@inria.fr

<sup>†</sup> Université Paris-Dauphine and INRIA, Domaine de Voluceau-Rocquencourt-B.P. 105-Le Chesnay Cedex (France) e-mail: Patrick.Le\_Tallec@inria.fr

# Un Estimateur d'Erreur A Posteriori Robuste pour les Problèmes Elliptiques Non Homogènes

**Résumé**: Dans ce travail on présente un nouvel estimateur d'erreur *a posteriori* pour des problèmes d'élasticité avec coefficients élastiques fortement hétérogènes. La nouvelle approche, qui est une variation de l'estimateur par résidu, a la propriété d'être correctement dimensioné par rapport aux données physiques .

Mots-clé : Estimateur d'erreur a posteriori, équation de Poisson, problème elliptiques fortement hétérogènes, residus.

# Contents

1	Introduction	4
2	Model problem and notation2.1 The continuous problem2.2 Finite element discretization2.3 Edges and vertices2.4 Bubble functions	6 7
3	A posteriori error estimates 3.1 Construction of the estimate	<b>12</b> 12
4	The elasticity problem	20
5	Numerical results	23
6	Conclusions	44

## 1 Introduction

Recent accidents have clearly demonstrated that reliable a posteriori error estimates and mesh adaption techniques were imperatively needed when computing large scale structures. From the theoretical point of view, this problem can apparently be solved either by using consistent residual estimates or by solving local auxiliary equilibrium problems at the element level. When used on real industrial problems, these theoretical strategies are faced with three main difficulties:

- the constitutive materials are usually anisotropic and heterogeneous,
- most engineering codes use second order or higher order elements, for which the theoretical tools are harder to implement and to derive,
- conforming mesh refinement is limited by many engineering and geometric constraints.

The purpose of this report is to describe and study a new version of local a posteriori error estimates. This estimate uses a weighted measure of element and interface residuals, and can be proved to be correctly dimensionalised with respect to the physical data, and to be uniformly valid with respect to material heterogeneities. For simplicity, the technique is introduced and analyzed for a simple Poisson type equation discretized by triangular or tetrahedric finite element grids. It is then tested numerically on more generic elasticity problems involving, for example, reinforced heterogeneous beams.

For more details on error estimates see [2] and the extensive bibliography cited therein. Other importants works are [4], [5], [11], [19], [22], [23], [24] and [25].

# 2 Model problem and notation

## 2.1 The continuous problem

Let  $\Omega$  be a bounded domain of  $\mathbb{R}^n$  (n= 2 or 3), with Lipschitz continuous boundary  $\Gamma = \Gamma_D \cup \Gamma_N$ ,  $\Gamma_D \cap \Gamma_N = \emptyset$ . Let  $f \in L^2(\Omega)$  and  $g \in H^{-1/2}(\Gamma_D)$  be given data, and consider the following model problem

(P) 
$$\begin{cases} -\operatorname{div}(\kappa \nabla u) = f & \text{in } \Omega, \\ u = 0 & \text{on } \Gamma_D, \\ \kappa \frac{\partial u}{\partial n} = g & \text{on } \Gamma_N. \end{cases}$$

Here, the scalar coefficient  $\kappa$  is supposed to be piecewise constant. In the simplest case, this means that the domain  $\Omega$  is split into two subdomains  $\Omega_1$  and  $\Omega_2$  with interface  $\Gamma_{12}$  (see Fig 1) and that we have

$$\kappa := \left\{ \begin{array}{ll} \kappa_1 & \text{ on } \Omega_1, \\ \kappa_2 & \text{ on } \Omega_2, \end{array} \right.$$

with  $\kappa_1, \kappa_2 > 0$ .




Figure 1:  $\Omega = \Omega_1 \cup \Gamma_{12} \cup \Omega_2$ .

The standard weak formulation of the problem (P) (see [10]) is then:  $Find \ u \in H \ such \ that$ 

$$a(u,v) = \langle F, v \rangle , \forall v \in \mathcal{H},$$
 (2.1)

where

$$H := \{v \in H^1(\Omega) / v = 0 \text{ on } \Gamma_D\},$$

$$a(u,v) := \int_{\Omega_1} \kappa_1 \nabla u \cdot \nabla v + \int_{\Omega_2} \kappa_2 \nabla u \cdot \nabla v,$$
  
$$< F, v > := \int_{\Omega} f v + \int_{\Gamma_N} g v.$$

This space is endowed with the natural energy norm

$$||v||_{e,\Omega} := \sqrt{a(v,v)} = \{ \sum_{T \in \mathcal{T}_b} (\sqrt{\kappa_T} |v|_{1,2,T})^2 \}^{1/2} , \forall v \in \mathcal{H},$$
 (2.2)

with  $|v|_{1,2,T}$  denoting the usual semi-norm

$$|v|_{1,2,T}^2 = \int_T |\nabla v|^2 d\Omega.$$

### 2.2 Finite element discretization

Let h be a positive discretization parameter, and consider a triangulation  $\mathcal{T}_h$  of  $\bar{\Omega}$ , that is a partition of  $\bar{\Omega}$  into non degenerate triangles T (resp. tetrahedra in dimension n=3), with diameter bounded by h, and such that each pair of elements  $T_1$  and  $T_2$  of  $\mathcal{T}_h$  are either disjoint or share a vertex, an edge or a complete face. We denote by  $h_T$  the diameter of T, by  $\rho_T$  the diameter of the circle (resp. sphere) inscribed in T and we set

$$\sigma_T := \frac{h_T}{\rho_T} \, .$$

We assume that the family of triangulations  $(\mathcal{T}_h)_h$  is shape regular, i.e. there exists a constant  $\sigma$ , independent of h, such that

$$\sigma_T \leq \sigma \qquad , \forall T \in \mathcal{T}_h \,. \tag{2.3}$$

On each element T we then introduce a local finite element space  $\mathbb{P}_k(T)$  of polynomial functions defined on the element T and with degree less than or equal to k. With this notation, we define the finite element space  $H_h$  by

$$H_h := \{ v_h \in \mathcal{C}(\Omega) / v_h = 0 \text{ on } \Gamma_D, \forall T \in \mathcal{T}_h, v_h|_T \in \mathbb{P}_k(T) \} \quad (k \ge 1).$$

Then the approximate problem of (2.1) is:

Find  $u_h \in H_h$  such that

$$a(u_h, v_h) = \langle F, v_h \rangle \quad , \forall v_h \in \mathcal{H}_h . \tag{2.4}$$

## 2.3 Edges and vertices

For any  $T \in \mathcal{T}_h$  we denote by  $\mathcal{E}(T)$  and  $\mathcal{N}(T)$  the set of its faces and vertices, respectively (see [20]), and set

$$\mathcal{E}_{h,\Omega} := \bigcup_{T \in \mathcal{T}_h} \mathcal{E}(T) \quad , \quad \mathcal{N}_{h,\Omega} := \bigcup_{T \in \mathcal{T}_h} \mathcal{N}(T) \, .$$

We split  $\mathcal{E}_{h,\Omega}$  and  $\mathcal{N}_{h,\Omega}$  into

$$\mathcal{E}_{h,\Omega} = (\mathcal{E}_h \setminus \mathcal{E}_{12}) \cup \mathcal{E}_{12} \cup \mathcal{E}_N \cup \mathcal{E}_D$$
 ,  $\mathcal{N}_{h,\Omega} = \mathcal{N}_h \cup \mathcal{N}_N \cup \mathcal{N}_D$ ,

with

$$\mathcal{E}_{N} := \{ E \in \mathcal{E}_{h,\Omega} / E \subset \Gamma_{N} \} , \quad \mathcal{E}_{D} := \{ E \in \mathcal{E}_{h,\Omega} / E \subset \Gamma_{D} \} ,$$

$$\mathcal{E}_{12} := \{ E \in \mathcal{E}_{h,\Omega} / E \subset \Gamma_{12} \} ,$$

$$\mathcal{N}_{N} := \{ x \in \mathcal{N}_{h,\Omega} / x \in \Gamma_{N} \} , \quad \mathcal{N}_{D} := \{ x \in \mathcal{N}_{h,\Omega} / x \in \Gamma_{D} \} .$$

Given an  $E \in \mathcal{E}_{h,\Omega}$  we denote by  $\mathcal{N}(E)$  the set of its vertices. For  $T \in \mathcal{T}_h$ ,  $E \in \mathcal{E}_{h,\Omega}$  and  $x \in \mathcal{N}_{h,\Omega}$  we define their neighborhoods (see Fig. 2)


$$w_T := \bigcup_{\mathcal{E}(T) \cap \mathcal{E}(T') \neq \emptyset} T', \ w_E := \bigcup_{E \in \mathcal{E}(T')} T', \ w_x := \bigcup_{x \in \mathcal{N}(T')} T',$$

$$\tilde{w}_T := \bigcup_{\mathcal{N}(T) \cap \mathcal{N}(T') \neq \emptyset} T', \ \tilde{w}_E := \bigcup_{\mathcal{N}(E) \cap \mathcal{N}(T') \neq \emptyset} T',$$

and for  $E \in \mathcal{E}_{12}$  we define the interface neighborhood

$$s_E := \{ E' \in \mathcal{E}_{h,\Omega} / E' \subset \Gamma_{12} \text{ and } \mathcal{N}(E) \cap \mathcal{N}(E') \neq \emptyset \}.$$

**Remark** Condition (2.3) implies that the ratios  $h_T/h_E$ ,  $T \in \mathcal{T}_h$ ,  $E \in \mathcal{E}(T)$ , and  $h_T/h_{T'}$ ,  $T, T' \in \mathcal{T}_h$ ,  $\mathcal{N}(T) \cap \mathcal{N}(T') \neq \emptyset$ , are bounded from below and from above by constants which only depend on  $\sigma$ .






Figure 2:  $w_T$  and  $\tilde{w}_T$ , respectively.

## 2.4 Bubble functions

For each element  $T \in \mathcal{T}_h$  we can define the element bubble function  $b_T$  by

$$b_T := \begin{cases} 27\lambda_{T,1}\lambda_{T,2}\lambda_{T,3} & \text{on } T, \\ 0 & \text{on } \Omega \backslash T, \end{cases}$$

in two dimensions, and by

$$b_T := \begin{cases} 256\lambda_{T,1}\lambda_{T,2}\lambda_{T,3}\lambda_{T,4} & \text{on } T, \\ 0 & \text{on } \Omega \backslash T, \end{cases}$$

in three dimensions. Above  $\lambda_{T,j}(M)$  denote the *j barycentric coordinates* of the point M in T. Similarly, to each face  $E \in \mathcal{E}_{h,\Omega}$ , we can define the face bubble function

$$b_E := \begin{cases} 4\lambda_{T_i,1}\lambda_{T_i,2} & \text{on } T_i, i = 1, 2\\ 0 & \text{on } \Omega \backslash w_E, \end{cases}$$

if  $E \in \mathcal{E}_h$  and  $w_E = T_1 \cup T_2$ , or

$$b_E := \begin{cases} 4\lambda_{T,1}\lambda_{T,2} & \text{on } T \\ 0 & \text{on } \Omega \backslash w_E, \end{cases}$$

if  $E \in \mathcal{E}_N \cup \mathcal{E}_D$  and  $w_E = T$ . The above definition of  $b_E$  assumes that we are in two space dimensions, and that in each triangle  $T_i$ , the edge E is associated to

the vertices with local numbers 1 and 2. In three dimensions, the construction of  $b_E$  is the same within the replacement of the quadratic product  $4\lambda_{T_i,1}\lambda_{T_i,2}$  by the cubic product  $27\lambda_{T_i,1}\lambda_{T_i,2}\lambda_{T_i,3}$ .

By construction, we have the followings properties of the bubble functions  $b_T$  and  $b_E$ 

**Lemma 1** Let  $T \in \mathcal{T}_h$  and  $E \in \mathcal{E}_{h,\Omega}$  be arbitrary, then

supp 
$$b_T \subset T$$
,  $0 \le b_T \le 1$ ,  $\max_{x \in T} b_T(x) = 1$ , (2.5)

supp 
$$b_E \subset w_E$$
,  $0 \le b_E \le 1$ ,  $\max_{x \in E} b_E(x) = 1$ . (2.6)

Moreover, using standard discrete norm equivalence arguments, we can prove

**Lemma 2** For any local function  $f \in \mathbb{P}_{k-2}(T)$  or  $g \in \mathbb{P}_{k-1}(E)$ , there exist positive constants  $C_1, C_2, C_3, C_4, C_5$ , with  $C_1$  and  $C_2$  only depending on the polynomial degree k and  $C_3, C_4$  or  $C_5$  depending both of k and of the shape regularity  $\sigma$ , such that

$$C_{1} \|f\|_{0,2,T}^{2} \leq \int_{T} b_{T} f^{2} \leq C_{2} \|f\|_{0,2,T}^{2},$$

$$C_{1} \|g\|_{0,2,E}^{2} \leq \int_{E} b_{E} g^{2} \leq C_{2} \|g\|_{0,2,E}^{2},$$

$$\int_{T} |\nabla (b_{T} f)|^{2} \leq C_{3} h_{T}^{-2} \int_{T} f^{2},$$

$$\int_{T \in w_{E}} |\nabla (b_{E} g)|^{2} \leq C_{4} h_{E}^{-1} \int_{E} g^{2},$$

$$\int_{T \in w_{E}} |b_{E} g|^{2} \leq C_{5} h_{E} \int_{E} g^{2}.$$

**Proof** All proofs make a linear change of variable  $x = B\hat{x} + b$  from the present element T or face E on the unit reference element  $\hat{T}$  or face  $\hat{E}$ .

With such change of variable, we first have with obvious notation

$$\int_T b_T f^2 dx = \int_{\hat{T}} \hat{b}_T \hat{f}^2 |\frac{dx}{d\hat{x}}| d\hat{x} , \forall \hat{f} \in \mathbb{P}_{k-2}(\hat{T}),$$

$$\int_T f^2 dx = \int_{\hat{T}} \hat{f}^2 |\frac{dx}{d\hat{x}}| d\hat{x} , \forall \hat{f} \in \mathbb{P}_{k-2}(\hat{T}).$$

But, by construction,  $\hat{b}_T$  is strictly positive inside  $\hat{T}$ . Hence,  $\int_{\hat{T}} \hat{b}_T \hat{f}^2 d\hat{x}$  defines a norm on  $\mathbb{P}_{k-2}(\hat{T})$ , and thus is equivalent to any other norm on  $\mathbb{P}_{k-2}(\hat{T})$  and in particular to the L<sup>2</sup>-norm. We therefore have

$$C_2 \int_{\hat{T}} \hat{f}^2 d\hat{x} \ge \int_{\hat{T}} \hat{b}_T \hat{f}^2 d\hat{x} \ge C_1 \int_{\hat{T}} \hat{f}^2 d\hat{x},$$

which once multiplied by the constant value  $|\frac{dx}{d\hat{x}}| = |B|$  yields the desired equivalence. The proof is absolutely similar for  $\int_E b_E g^2$ . Observe that since  $|b_T| \leq 1$  and  $|b_E| \leq 1$ , we have that both  $C_1$  and  $C_2$  are less or equal to 1. For k=1 on triangles, we have for example  $C_1=C_2=\frac{9}{20}$ .

Similarly, a direct change of variables yields

$$\int_{T} |\nabla (b_{T}f)|^{2} dx = \int_{\hat{T}} |\hat{\nabla} (\hat{b}_{T}\hat{f}) \cdot B^{-1}|^{2} |\frac{dx}{d\hat{x}}| d\hat{x} 
\leq \sigma^{2} h_{T}^{-2} |\frac{dx}{d\hat{x}}| \int_{\hat{T}} |\hat{\nabla} (\hat{b}_{T}\hat{f})|^{2} d\hat{x}.$$

Again, the last term defines a norm on  $\mathbb{P}_{k-2}(\hat{T})$  and hence

$$\left|\frac{dx}{d\hat{x}}\right| \int_{\hat{T}} |\hat{\nabla}(\hat{b}_T \hat{f})|^2 d\hat{x} \le C_k \left|\frac{dx}{d\hat{x}}\right| \int_{\hat{T}} \hat{f}^2 d\hat{x} \le C_k \int_T f^2 dx.$$

We also have in the same way

$$\int_{T} |\nabla(b_{E}g)|^{2} dx \leq \sigma^{2} h_{T}^{-2} |\frac{dx}{d\hat{x}}| \int_{\hat{T}} |\hat{\nabla}(\hat{b}_{E}\hat{g})|^{2} d\hat{x} 
\leq C'_{k} \sigma^{2} h_{T}^{-2} |\frac{dx}{d\hat{x}}| \int_{\hat{E}} \hat{g}^{2} d\hat{l} , \forall \hat{g} \in \mathbb{P}_{k-1}(\hat{E}) 
\leq C'_{k} \sigma^{2} h_{T}^{-2} |\frac{dx}{d\hat{x}}| |\frac{d\hat{l}}{dl}| \int_{E} g^{2} dl 
\leq C'_{k} \sigma^{2} h_{T}^{-2} h_{E}^{3} \sigma^{2} h_{E}^{-2} \int_{E} g^{2} dl 
\leq C_{4} h_{E}^{-1} \int_{E} g^{2} dl , \forall g \in \mathbb{P}_{k-1}(E),$$

and the rest of the lemma follows ■

**Lemma 3** There exists a projection operator  $R_h: H \to H_h$  such that for all  $v \in H$ 

$$||v - R_h v||_{0,2,T} \leq C_6 h_T |v|_{1,2,\tilde{w}_T \cap \Omega_i} ||v - R_h v||_{0,2,E} \leq C_7 h_E^{1/2} |v|_{1,2,\tilde{w}_E \cap \Omega_i}, \forall i = 1, 2$$
(2.7)

where  $T \in \mathcal{T}_h$ ,  $E \in \mathcal{E}_N \cup \mathcal{E}_h$  and the positive constants  $C_6, C_7$  are independent on h.

**Proof** Such result is a nontrivial extension of a local projection result proved in [8]. It requires that the local distance  $||v - R_h v||$  be controlled only by the local norm of |v| not on the full patch  $\tilde{w}_T$ , but on its restriction  $\tilde{w}_T \cap \Omega_i$  on the subdomain  $\Omega_i$ . The proof [17], to be outlined in a forthcoming paper, uses a local average of  $v_h$  around each node in order to define the values of  $R_h v$  at each node

# 3 A posteriori error estimates

#### 3.1 Construction of the estimate

The purpose of this section is to propose a local explicit evaluation of the error between the exact solution u of our original problem (P) and the approximate solution  $u_h$  of the finite element problem (2.4). This error estimate should be easy to compute, should only involve the data and the approximate solution  $u_h$ , and its efficiency should be independent of the choice of the physical parameters  $\kappa_i$ . As classically observed in the literature (see [1], [4], [6] and [7]), the dual energy norm of the residual gives a good indication of the error. The challenge is then to obtain an explicit local approximation of this norm, uniformly valid with respect to the coefficients  $\kappa_i$ .

For this purpose, on each face  $E \in \mathcal{E}_h$  separating the elements  $T_1$  and  $T_2$ , we first introduce weighting factors  $\alpha(T_i, E)$ , i = 1, 2, which satisfy

$$\alpha(T_1, E) + \alpha(T_2, E) = 1,$$
 (3.1)

$$\frac{\alpha(T_1, E)^2}{\kappa_{T_1}} + \frac{\alpha(T_2, E)^2}{\kappa_{T_2}} \le \frac{1}{\kappa_{T_i}}, \forall i = 1, 2, \tag{3.2}$$

where  $\kappa_{T_i}$  denotes the restriction of the physical coefficient  $\kappa$  to the element  $T_i$ . A good choice of coefficients is to take

$$\alpha(T_i, E) = \frac{\kappa_{T_i}}{\kappa_{T_1} + \kappa_{T_2}},$$

which obviously satisfies

$$\frac{\alpha(T_1, E)^2}{\kappa_{T_1}} + \frac{\alpha(T_2, E)^2}{\kappa_{T_2}} = \frac{1}{\kappa_{T_1} + \kappa_{T_2}}.$$

Next, we introduce the piecewise projections  $f_T$  and  $g_E$  of right hand sides f and g on each element or face subspace  $\mathbb{P}_{k-2}(T), T \in \mathcal{T}_h$  or  $\mathbb{P}_{k-1}(E), E \in \mathcal{E}_{h,\Omega}$  defined by

$$\int_{T} f_{T}q = \int_{T} fq , \forall q \in \mathbb{P}_{k-2}(T), f_{T} \in \mathbb{P}_{k-2}(T), \qquad (3.3)$$

$$\int_{E} g_{E}q = \int_{E} gq , \forall q \in \mathbb{P}_{k-1}(E), g_{E} \in \mathbb{P}_{k-1}(E), \qquad (3.4)$$

and the weighted element residuals  $\eta_{R,T}$  given by

$$\eta_{R,T} := \left\{ \frac{h_T^2}{\kappa_T} ||f_T + \kappa_T \Delta u_h||_{0,2,T}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \frac{h_E}{\kappa_T} ||g_E - \kappa_T \partial_n u_h||_{0,2,E}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_h} \frac{\alpha(T, E)^2}{\kappa_T} h_E ||[\kappa_T \partial_n u_h]||_{0,2,E}^2 \right\}^{1/2}.$$
(3.5)

Observe that the value of  $\eta_{R,T}$  scales exactly like the solution energy norm when changing the physical scales or units. Above, we have used the standard notation for jumps in normal derivatives

$$[\kappa_T \partial_n u_h] = \kappa_{T_1} \partial_n u_h - \kappa_{T_2} \partial_n u_h.$$

With this notation we can prove

**Theorem 4** There exist two positive constants  $\bar{C}$  and  $\underline{C}$ , independent of h and  $\kappa$ , such that

$$||u - u_h||_{e,\Omega} \leq \bar{C} \left\{ \sum_{T \in \mathcal{T}_h} \eta_{R,T}^2 + \sum_{T \in \mathcal{T}_h} \frac{h_T^2}{\kappa_T} ||f_T - f||_{0,2,T}^2 + \sum_{E \in \mathcal{E}_N} \frac{h_E}{\kappa_T} ||g_E - g||_{0,2,E}^2 \right\}^{1/2}$$

$$(3.6)$$

and

$$\eta_{R,T} \leq \underline{C} \Big\{ ||u - u_h||_{e,w_T}^2 + \sum_{T' \subset w_T} \frac{h_{T'}^2}{\kappa_{T'}} ||f_T - f||_{0,2,T'}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \frac{h_E}{\kappa_T} ||g_E - g||_{0,2,E}^2 \Big\}^{1/2}.$$

$$(3.7)$$

#### Proof

As usual, the proof is split into three parts: an algebraic manipulation of the residual, the derivation of the upper bound (3.6), and of the lower bound (3.7).

#### Step 1: residual transform.

By construction of the continuous and discrete problems (2.1) and (2.4), and after integration by parts on each element T, we can write for any v in H

$$a(u - u_h, v) = \int_{\Omega} fv + \int_{\Gamma_N} gv - a(u_h, v)$$

$$= \int_{\Omega} fv + \int_{\Gamma_N} gv - (\int_{\Omega_1} \kappa_1 \nabla u_h \cdot \nabla v + \int_{\Omega_2} \kappa_2 \nabla u_h \cdot \nabla v)$$

$$= \sum_{T \in \mathcal{T}_h} \int_T (f + \kappa_T \Delta u_h)v + \sum_{E \in \mathcal{E}_N} \int_E (g - \kappa \partial_n u_h)v$$

$$- \sum_{E \in \mathcal{E}_h} \int_E [\kappa \partial_n u_h]v.$$
(3.8)

Then using the fact that  $a(u - u_h, v_h) = 0$ ,  $\forall v_h \in H_h$  and the partition of unity (3.1), we obtain

$$a(u - u_h, v) = \sum_{T \in \mathcal{T}_h} \int_T (f + \kappa \Delta u_h)(v - v_h) + \sum_{E \in \mathcal{E}_N} \int_E (g - \kappa \partial_n u_h)(v - v_h)$$

$$- \sum_{E \in \mathcal{E}_h} \int_E [\kappa \partial_n u_h](v - v_h)$$

$$= \sum_{T \in \mathcal{T}_h} \left\{ \int_T \frac{1}{\sqrt{\kappa_T}} (f + \kappa_T \Delta u_h) \sqrt{\kappa_T}(v - v_h) + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \int_E \frac{1}{\sqrt{\kappa_T}} (g - \kappa_T \partial_n u_h) \sqrt{\kappa_T}(v - v_h) - \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_h} \int_E \frac{\alpha(T, E)}{\sqrt{\kappa_T}} [\kappa \partial_n u_h] \sqrt{\kappa_T}(v - v_h) \right\}.$$
(3.9)

#### Step 2: upper bound.

Let us now take  $v_h = R_h v$ . Using (2.2), (2.7) and the Cauchy-Schwarz inequality, the residual (3.9) can then be bounded by

$$a(u - u_h, v) \le \sum_{i} \sum_{T \in \mathcal{T}_h \cap \Omega_i} \left( C_6 \frac{h_T}{\sqrt{\kappa_i}} ||f + \kappa_i \Delta u_h||_{0, 2, T} \sqrt{\kappa_i} |v|_{1, 2, \tilde{w}_T \cap \Omega_i} \right)$$

$$\begin{split} &+C_{7} \sum_{E \in \mathcal{E}_{N} \cap \mathcal{E}(T)} \frac{h_{E}^{1/2}}{\sqrt{\kappa_{i}}} ||g - \kappa_{i} \partial_{n} u_{h}||_{0,2,E} \sqrt{\kappa_{i}} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{i}} \\ &+C_{7} \sum_{E \in (\mathcal{E}_{h} \setminus \mathcal{E}_{12}) \cap \mathcal{E}(T)} \frac{\alpha(T,E) h_{E}^{1/2}}{\sqrt{\kappa_{i}}} ||[\kappa_{i} \partial_{n} u_{h}]||_{0,2,E} \sqrt{\kappa_{i}} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{i}} \Big) \\ &+C_{7} \sum_{E \in \mathcal{E}_{12}} \sum_{E \subset T_{i} \subset \Omega_{i}} \frac{\alpha(T_{i},E) h_{E}^{1/2}}{\sqrt{\kappa_{i}}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \sqrt{\kappa_{i}} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{i}} \Big) \\ &\leq \bar{C} \Big\{ \sum_{T \in \mathcal{T}_{h}} \frac{h_{T}^{2}}{\kappa_{T}} ||f + \kappa_{T} \Delta u_{h}||_{0,2,T}^{2} + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_{N}} \frac{h_{E}}{\kappa_{T}} ||g - \kappa_{T} \partial_{n} u_{h}||_{0,2,E}^{2} \Big) \\ &+ \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_{h}} \frac{\alpha(T,E)^{2} h_{E}}{\kappa_{T}} ||[\kappa \partial_{n} u_{h}]||_{0,2,E}^{2} \Big\}^{1/2} \\ &\cdot \Big\{ \sum_{i} (\sum_{T \in \mathcal{T}_{h} \cap \Omega_{i}} \kappa_{i} |v|_{1,2,\tilde{w}_{T} \cap \Omega_{i}}^{2} + \sum_{E \in ((\mathcal{E}_{h} \setminus \mathcal{E}_{12}) \cup \mathcal{E}_{N}) \cap \Omega_{i}} \kappa_{i} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{i}}^{2} \Big) \\ &+ \sum_{E \in E_{12}} (\kappa_{1} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{1}}^{2} + \kappa_{2} |v|_{1,2,\tilde{w}_{E} \cap \Omega_{2}}^{2} \Big)^{1/2} \\ &\leq \bar{C} \Big\{ \sum_{T \in \mathcal{T}_{h}} \eta_{R,T}^{2} + \frac{h_{T}^{2}}{\kappa_{T}} ||f_{T} - f||_{0,2,T}^{2} + \sum_{E \in \mathcal{E}_{N} \cap \mathcal{E}(T)} \frac{h_{E}}{\kappa_{T}} ||g_{E} - g||_{0,2,E}^{2} \Big\}^{1/2} ||v||_{\ell,\Omega} , \end{split}$$

where

$$\bar{C} := \max\{C_6, \sqrt{2}C_7, C_\sigma\}.$$

Here  $C_{\sigma}$  is a positive constant which counts the number of times a given element of the triangulation of  $\Omega_i$  is recovered by neighborhoods  $\tilde{w}_T$  or  $\tilde{w}_E$ . To obtain (3.6), we just have to take  $v = u - u_h$  and divide each term of the above inequality by  $||u - u_h||_{e,\Omega}$ , completing then the proof of step 2.

#### Step 3. Inverse bound.

Let us consider the local bubble test function  $v_T := (f_T + \kappa_T \Delta u_h)b_T$ . Then using the equivalence of norms on  $\mathbb{P}_{k-2}(T)$ , we obtain

$$\int_{T} (f_T + \kappa_T \Delta u_h) v_T \ge C_1 ||f_T + \kappa_T \Delta u_h||_{0,2,T}^2.$$
 (3.10)

On the other hand, since the support of the function  $v_T$  is included in T, we have after integrating by parts and using the fact that u is a solution of the continuous problem

$$\int_{T} (f_{T} + \kappa_{T} \Delta u_{h}) v_{T} = \int_{T} f v_{T} + \int_{T} \kappa_{T} \Delta u_{h} v_{T} + \int_{T} (f_{T} - f) v_{T} 
= \int_{\Omega} f v_{T} + \int_{\Gamma_{N}} g v_{T} - \int_{\Omega} \kappa \nabla u_{h} \cdot \nabla v_{T} + \int_{T} (f_{T} - f) v_{T} 
= \int_{T} \kappa_{T} \nabla (u - u_{h}) \cdot \nabla v_{T} + \int_{T} (f_{T} - f) v_{T} 
\leq \sqrt{\kappa_{T}} |u - u_{h}|_{1,2,T} \sqrt{\kappa_{T}} ||\nabla v_{T}||_{0,2,T} + ||f_{T} - f||_{0,2,T} ||v_{T}||_{0,2,T}.$$

By using now the discrete inverse inequalities on  $\mathbb{P}_{k-2}(T)$  and the equivalence of  $L^2$  norms on  $\mathbb{P}_{k-2}(T)$ 

$$||\nabla v_T||_{0,2,T} \leq \sqrt{C_3} h_T^{-1} ||f_T + \kappa_T \Delta u_h||_{0,2,T}, ||v_T||_{0,2,T}^2 \leq C_2 ||f_T + \kappa_T \Delta u_h||_{0,2,T}^2,$$

we get

$$\int_{T} (f_{T} + \kappa_{T} \Delta u_{h}) v_{T} \leq ||u - u_{h}||_{e,T} \sqrt{C_{3}} h_{T}^{-1} \kappa_{T}^{1/2} ||f_{T} + \kappa_{T} \Delta u_{h}||_{0,2,T} 
+ \sqrt{C_{2}} ||f_{T} - f||_{0,2,T} ||f_{T} + \kappa_{T} \Delta u_{h}||_{0,2,T} 
\leq ||f_{T} + \kappa_{T} \Delta u_{h}||_{0,2,T} \left( \sqrt{C_{3}} h_{T}^{-1} \kappa_{T}^{1/2} ||u - u_{h}||_{e,T} 
+ \sqrt{C_{2}} ||f - f_{T}||_{0,2,T} \right).$$

Hence, combining the two inequalities, we finally obtain

$$||f_T + \kappa_T \Delta u_h||_{0,2,T} \le C_8 \left\{ h_T^{-1} \kappa_T^{1/2} ||u - u_h||_{e,T} + ||f_T - f||_{0,2,T} \right\}, \quad (3.11)$$

with

$$C_8 := \frac{\max\{\sqrt{C_2}, \sqrt{C_3}\}}{C_1}.$$

Next, we consider an arbitrary boundary face  $E \in \mathcal{E}_N$  and define

$$v_E := (g_E - \kappa_T \partial_n u_h) b_E.$$

From our norm equivalence in  $\mathbb{P}_{k-1}(E)$ , we first have

$$\int_{E} (g_E - \kappa_T \partial_n u_h) v_E \ge C_1 ||g_E - \kappa_T \partial_n u_h||_{0,2,E}^2.$$
(3.12)

On the other hand, after integration by part, and using the construction of u,  $v_E$  and our basic inverse inequalities, we obtain

$$\begin{split} &\int_{E} (g_{E} - \kappa_{T} \partial_{n} u_{h}) v_{E} \\ &= \int_{E} (g - \kappa_{T} \partial_{n} u_{h}) v_{E} + \int_{E} (g_{E} - g) v_{E} \\ &= \int_{\Omega} f v_{E} + \int_{\Gamma_{N}} g v_{E} - \int_{\Omega} \kappa_{T} \nabla u_{h} \cdot \nabla v_{E} - \sum_{T' \in w_{E}} \int_{T'} (f + \kappa \Delta u_{h}) v_{E} + \int_{E} (g_{E} - g) v_{E} \\ &= \int_{w_{E}} \kappa_{T} \nabla (u - u_{h}) \cdot \nabla v_{E} - \sum_{T' \in w_{E}} \int_{T'} (f + \kappa \Delta u_{h}) v_{E} + \int_{E} (g_{E} - g) v_{E} \\ &\leq \sqrt{\kappa_{T}} |u - u_{h}|_{1,2,w_{E}} \sqrt{\kappa_{T}} ||\nabla v_{E}||_{0,2,w_{E}} + \sum_{T' \in w_{E}} ||f + \kappa \Delta u_{h}||_{0,2,T'} ||v_{E}||_{0,2,T'} \\ &+ ||g_{E} - g||_{0,2,E} ||v_{E}||_{0,2,E} \\ &\leq ||u - u_{h}||_{e,w_{E}} \sqrt{C_{4} h_{E}^{-1/2} \kappa_{T}^{1/2}} ||g_{E} - \kappa_{T} \partial_{n} u_{h}||_{0,2,E} \\ &+ \sqrt{C_{5} h_{E}^{1/2}} \sum_{T' \in w_{E}} ||f + \kappa \Delta u_{h}||_{0,2,T'} ||g_{E} - \kappa_{T} \partial_{n} u_{h}||_{0,2,E} \\ &\leq ||g_{E} - \kappa_{T} \partial_{n} u_{h}||_{0,2,E} \left(\sqrt{C_{4} h_{E}^{-1/2} \kappa_{T}^{1/2}} ||u - u_{h}||_{e,w_{E}} \\ &+ \sqrt{C_{5} h_{E}^{1/2}} \sum_{T' \in w_{E}} ||f + \kappa \Delta u_{h}||_{0,2,T'} + \sqrt{C_{5}} ||g_{E} - g||_{0,2,E} \right). \end{split}$$

Thus, by combining the above two inequalities, we finally get

$$||g_{E} - \kappa_{T} \partial_{n} u_{h}||_{0,2,E} \leq C_{9} \left\{ h_{E}^{-1/2} \kappa_{T}^{1/2} ||u - u_{h}||_{e,w_{E}} + h_{E}^{1/2} \sum_{T' \subset w_{E}} (||f - f_{T'}||_{0,2,T'} + ||f_{T'} + \kappa \Delta u_{h}||_{0,2,T'}) + ||g_{E} - g||_{0,2,E} \right\}.$$

$$(3.13)$$

with

$$C_9 = \frac{\max\{\sqrt{C_4}, \sqrt{C_5}\}}{C_1}$$

Finally, let us consider an internal face  $E \in \mathcal{E}_h$  separating the elements  $T_1$  and  $T_2$  and define

$$v_E := \left(\frac{\alpha^2(T_1, E)}{\kappa_{T_1}} + \frac{\alpha^2(T_2, E)}{\kappa_{T_2}}\right)^{1/2} (\kappa_{T_1} \partial_n u_h - \kappa_{T_2} \partial_n u_h) b_E.$$

From the equivalence of L<sup>2</sup> norms on  $\mathbb{P}_{k-1}(E)$ , we first have

$$\int_{E} (\kappa_{T_{1}} \partial_{n} u_{h} - \kappa_{T_{2}} \partial_{n} u_{h}) v_{E} \ge C_{1} \left( \frac{\alpha^{2}(T_{1}, E)}{\kappa_{T_{1}}} + \frac{\alpha^{2}(T_{2}, E)}{\kappa_{T_{2}}} \right)^{1/2} ||[\kappa \partial_{n} u_{h}]||_{0, 2, E}^{2}.$$
(3.14)

On the other hand, by integration by parts, using the fact that the support of  $v_E$  is included in  $w_E$ , the construction of u and the equivalence of norms

$$\begin{split} &\int_{E} (\kappa_{T_{1}} \partial_{n} u_{h} - \kappa_{T_{2}} \partial_{n} u_{h}) v_{E} \\ &= \sum_{T \subset w_{E}} \int_{T} (f + \kappa_{T} \Delta u_{h}) v_{E} - \int_{\Omega} f v_{E} - \int_{\Gamma_{N}} g v_{E} + \int_{\Omega} \kappa \nabla u_{h} \cdot \nabla v_{E} \\ &= \sum_{T \subset w_{E}} \int_{T} (f + \kappa_{T} \Delta u_{h}) v_{E} - \sum_{i} \int_{w_{E} \cap \Omega_{i}} \kappa_{i} \nabla (u - u_{h}) \cdot \nabla v_{E} \\ &\leq \sum_{i} \sqrt{\kappa_{i}} |u - u_{h}|_{1,2,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} ||\nabla v_{E}||_{0,2,w_{E} \cap \Omega_{i}} \\ &+ ||(f + \kappa \Delta u_{h})||_{0,2,w_{E} \cap \Omega_{i}} ||v_{E}||_{0,2,w_{E} \cap \Omega_{i}} \\ &\leq \sum_{i} \sqrt{\kappa_{i}} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{C_{4}} h_{E}^{-1/2} ||v_{E}||_{0,2,E} \\ &+ ||f + \kappa \Delta u_{h}||_{0,2,w_{E} \cap \Omega_{i}} ||v_{E}||_{0,2,w_{E} \cap \Omega_{i}} \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \\ &+ \sqrt{C_{5}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} ||f + \kappa \Delta u_{h}||_{0,2,w_{E} \cap \Omega_{i}} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right) \\ &\leq \sqrt{h_{E}} ||\kappa_{1} \partial_{n} u_{h} - \kappa_{2} \partial_{n} u_{h}||_{0,2,E} \left(\sum_{i} \sqrt{C_{4}} h_{E}^{-1} ||u - u_{h}||_{e,w_{E} \cap \Omega_{i}} \sqrt{\kappa_{i}} \left(\frac{\alpha_{1}^{2}}{\kappa_{1}} + \frac{\alpha_{2}^{2}}{\kappa_{2}}\right)^{1/2} \right)$$

$$+\sqrt{C_5} \left(\frac{\alpha_1^2}{\kappa_1} + \frac{\alpha_2^2}{\kappa_2}\right)^{1/2} \sum_{T' \in w_E} ||f_{T'} + \kappa \Delta u_h||_{0,2,T'}$$

$$+\sqrt{C_5} \left(\frac{\alpha_1^2}{\kappa_1} + \frac{\alpha_2^2}{\kappa_2}\right)^{1/2} \sum_{T' \in w_E} ||f - f_{T'}||_{0,2,T'} \right).$$

By construction of coefficients  $\alpha_i$ , we have that

$$\sqrt{\kappa_i} \left(\frac{\alpha_1^2}{\kappa_1} + \frac{\alpha_2^2}{\kappa_2}\right)^{1/2} \le 1$$

and hence by using the above inequalities and (3.11) we obtain

$$\left(\frac{\alpha^{2}(T_{1}, E)}{\kappa_{T_{1}}} + \frac{\alpha^{2}(T_{2}, E)}{\kappa_{T_{2}}}\right)^{1/2} ||[\kappa \partial_{n} u_{h}]||_{0,2,E} \\
\leq C_{10} \left(h_{E}^{-1/2} ||u - u_{h}||_{e,w_{E}} + \sum_{T' \subset w_{E}} h_{E}^{1/2} \frac{1}{\sqrt{\kappa_{T'}}} ||f - f_{T'}||_{0,2,T'}\right) (3.15)$$

with

$$C_{10} := \frac{\max\{\sqrt{C_4}, C_8\sqrt{C_5}, 2\sqrt{C_5}\}}{C_1}.$$

Then from (3.11), (3.13) and (3.15), we get that there exists a positive constant  $\underline{C}$  such that

$$\eta_{R,T} \leq \underline{C} \Big\{ ||u - u_h||_{e,w_T}^2 + \sum_{T' \subset w_T} \frac{h_{T'}^2}{\kappa_{T'}} ||f_T - f||_{0,2,T'}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \frac{h_E}{\kappa_T} ||g_E - g||_{0,2,E}^2 \Big\}^{1/2} \blacksquare$$

## 4 The elasticity problem

We now try to extend the previous approach to linear elasticity problems. Let  $\Omega$  an Lipschitz, bounded domain of  $\mathbb{R}^n$  with an interior boundary denoted  $\Gamma_{12}$ . This boundary represents the interface between two elastic, isotropic and homogeneous materials, noted  $\Omega_1$  and  $\Omega_2$ , respectively (see Fig 3). Let  $\Gamma := \partial \Omega$  such that  $\Gamma = \Gamma_D \cup \Gamma_N$ ,  $\Gamma_D \cap \Gamma_N = \emptyset$ , with  $\partial \Omega_i \cap \Gamma_D \neq \emptyset$ , i = 1, 2. This means for the time being that we assume that each subdomain is fixed on part of its boundary. This assumption will be useful to relate the  $H^1$  semi-norm used in the local interpolation (2.7) and the local energy norm. It can be relaxed if we can prove this interpolation result directly with the  $|\epsilon(\mathbf{v})|_{0,2}$  norm. In this framework, we consider the following elasticity problem

(P) 
$$\begin{cases} -\operatorname{div} \boldsymbol{\sigma} = \mathbf{f} & \text{in } \Omega, \\ \mathbf{u} = 0 & \text{on } \Gamma_D, \\ \boldsymbol{\sigma} \cdot \mathbf{n} = \mathbf{g} & \text{on } \Gamma_N, \end{cases}$$

where  $\mathbf{f} \in L^2(\Omega)^n$  and  $\mathbf{g} \in L^2(\Gamma_D)^n$  are the external forces and  $\boldsymbol{\sigma}$  is the stress tensor. Assuming isotropy, this tensor satisfies the constitutive law

$$\boldsymbol{\sigma} = (\sigma_{ij}) := \begin{cases} \lambda_1 \epsilon_{pp}(\mathbf{u}) \delta_{ij} + 2\mu_1 \epsilon_{ij}(\mathbf{u}) & \text{on } \Omega_1, \\ \lambda_2 \epsilon_{pp}(\mathbf{u}) \delta_{ij} + 2\mu_2 \epsilon_{ij}(\mathbf{u}) & \text{on } \Omega_2, \end{cases}$$

with  $\lambda_i, \mu_i > 0$  the Lame's coefficients of the material  $\Omega_i$  and  $\epsilon_{ij}(\mathbf{u}) := \frac{1}{2}(u_{i,j} + u_{j,i})$  the components of the linearized strain tensor  $\epsilon(\mathbf{u})$  associated to  $\mathbf{u}$ .




Figure 3:  $\Omega = \Omega_1 \cup \Gamma_{12} \cup \Omega_2$ .

The standard weak formulation of the problem (P) is then: Find  $\mathbf{u} \in \mathbf{H}$  such that

$$a(\mathbf{u}, \mathbf{v}) = \langle F, \mathbf{v} \rangle , \forall \mathbf{v} \in \mathbf{H}$$
 (4.1)

**INRIA** 

where

$$\mathbf{H} := \{ \mathbf{v} \in \mathrm{H}^{1}(\Omega)^{n} / \mathbf{v} = \mathbf{0} \text{ on } \Gamma_{D} \}$$

$$a(\mathbf{u}, \mathbf{v}) := \int_{\Omega_{1}} \boldsymbol{\sigma}_{1}(\mathbf{u}) : \boldsymbol{\epsilon}(\mathbf{v}) + \int_{\Omega_{2}} \boldsymbol{\sigma}_{2}(\mathbf{u}) : \boldsymbol{\epsilon}(\mathbf{v})$$

$$< F, \mathbf{v} > := \int_{\Omega} \mathbf{f} \cdot \mathbf{v} + \int_{\Gamma_{N}} \mathbf{g} \cdot \mathbf{v}.$$

Let  $\mathbf{H}_h$  the finite element space defined by

$$\mathbf{H}_h := \left\{ \mathbf{v}_h \in \mathcal{C}(\Omega)^n \, / \, \mathbf{v}_h = \mathbf{0} \text{ on } \Gamma_D \, , \forall T \in \mathcal{T}_h \, , \mathbf{v}_h|_T \in \mathbb{P}_k(T)^n \, \right\} \quad (k \ge 1) \, .$$

Then the approximate problem of (4.1) is again: Find  $\mathbf{u}_h \in \mathbf{H}_h$  such that

$$a(\mathbf{u}_h, \mathbf{v}_h) = \langle F, \mathbf{v}_h \rangle , \forall \mathbf{v}_h \in \mathbf{H}_h.$$
 (4.2)

We define the energy norm by:

$$||\mathbf{v}||_{\epsilon,\Omega} := \{||\mathbf{v}||_{\epsilon,\Omega_1}^2 + ||\mathbf{v}||_{\epsilon,\Omega_2}^2\}^{1/2}$$

$$= \{\int_{\Omega_1} \boldsymbol{\sigma}_1(\mathbf{v}) : \boldsymbol{\epsilon}(\mathbf{v}) + \int_{\Omega_2} \boldsymbol{\sigma}_2(\mathbf{v}) : \boldsymbol{\epsilon}(\mathbf{v})\}^{1/2} , \forall \mathbf{v} \in \mathbf{H}. \quad (4.3)$$

By the Korn's inequality, since  $\partial\Omega_i \cap \Gamma_D$  has a non empty measure, there exist two positive constants  $C_{\Omega_1}$  and  $C_{\Omega_2}$ , depending only on the geometry of  $\Omega_1$  and  $\Omega_2$ , respectively, such that

$$||\mathbf{v}||_{1,2,\Omega_i} \le C_{\Omega_i}||\boldsymbol{\epsilon}(\mathbf{v})||_{0,2,\Omega_i} \quad \forall \mathbf{v} \in \mathbf{H}, \ i = 1, 2.$$
 (4.4)

Finally, there exits an interpolation operator (see Lemma 2)  $R_h : \mathbf{H} \to \mathbf{H}_h$  such that for all  $\mathbf{v} \in \mathbf{H}$ 

$$||\mathbf{v} - R_h \mathbf{v}||_{0,2,T} \leq C_7 h_T |\mathbf{v}|_{1,2,\tilde{w}_T \cap \Omega_i}$$

$$||\mathbf{v} - R_h \mathbf{v}||_{0,2,E} \leq C_8 h_E^{1/2} |\mathbf{v}|_{1,2,\tilde{w}_E \cap \Omega_i}$$

$$(4.5)$$

where  $T \in \mathcal{T}_h$ ,  $E \in \mathcal{E}_N \cup \mathcal{E}_h$  and the positive constants  $C_7, C_8$  are independent of h.

With the above definitions we prove exactly the same results as in section 3. We only have to pay attention to:

- replace  $\sqrt{\kappa_T}$  by  $\sqrt{E_T}$  where  $E_T$  is the Young modulus of the material that composes the element T,
- use the property  $0 < \nu < 0.5$  for to ensure that  $1 < 1 + \nu < 3/2$ ,
- In the proof of step 3 we find a factor  $\frac{1}{1-2\nu_i}$  that we include in a constant. It's clear that if a material is quasi-incompressible then this constant explodes. This means that our developpement is valid only for compressible materials. In fact, for practical purpose we assume that  $0 < \nu \le 0.45$ .

Altogether, defining the *local residual* by

$$\eta_{R,T} := \left\{ \frac{h_T^2}{E_T} ||\mathbf{f}_T + \nabla \cdot \boldsymbol{\sigma}(\mathbf{u}_h)||_{0,2,T}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \frac{h_E}{E_T} ||\mathbf{g}_E - \boldsymbol{\sigma}(\mathbf{u}_h) \cdot \mathbf{n}||_{0,2,E}^2 \right. \\
+ \left. \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_h} \frac{\alpha(T, E)^2}{E_T} h_E ||[\boldsymbol{\sigma}(\mathbf{u}_h) \cdot \mathbf{n}]||_{0,2,E}^2 \right\}^{1/2}, \tag{4.6}$$

we can prove

**Theorem 5** There exist two positive constants  $\bar{C}$  and  $\underline{C}$ , independent of h and  $E_i$ , (i = 1, 2) but depending on the compressibility factor  $\frac{1}{1-2\nu_i}$ , such that

$$||\mathbf{u} - \mathbf{u}_{h}||_{e,\Omega} \leq \bar{C} \Big\{ \sum_{T \in \mathcal{T}_{h}} \eta_{R,T}^{2} + \sum_{T \in \mathcal{T}_{h}} \frac{h_{T}^{2}}{E_{T}} ||\mathbf{f}_{T} - \mathbf{f}||_{0,2,T}^{2} + \sum_{E \in \mathcal{E}_{N}} \frac{h_{E}}{E_{T}} ||\mathbf{g}_{E} - \mathbf{g}||_{0,2,E}^{2} \Big\}^{1/2},$$

$$(4.7)$$

$$\eta_{R,T} \leq \underline{C} \Big\{ ||\mathbf{u} - \mathbf{u}_h||_{e,w_T}^2 + \sum_{T' \subset w_T} \frac{h_{T'}^2}{E_{T'}} ||\mathbf{f}_T - \mathbf{f}||_{0,2,T'}^2 + \sum_{E \in \mathcal{E}(T) \cap \mathcal{E}_N} \frac{h_E}{E_T} ||\mathbf{g}_E - \mathbf{g}||_{0,2,E}^2 \Big\}^{1/2} \,.$$

$$(4.8)$$

**Remark** There is an extensive work relating a posteriori estimates and linear elasticity, for example [3], [12], [13], [14], [15], [16], [18], [21].

## 5 Numerical results

In this section we apply the results of section 4 to the elasticity problem

$$-\operatorname{div} \boldsymbol{\sigma} = \mathbf{0} \quad \text{in } \Omega,$$

$$\mathbf{u} = \mathbf{0} \quad \text{on } \Gamma_{1},$$

$$\boldsymbol{\sigma}(\mathbf{u}) \cdot \mathbf{n} = \mathbf{P} \quad \text{on } \Gamma_{2},$$

$$u_{x} = 0 \quad \text{on } \Gamma_{3},$$

$$\boldsymbol{\sigma}(\mathbf{u}) \cdot \mathbf{n} = \mathbf{0} \quad \text{on } \Gamma_{4},$$

with  $\mathbf{P} := (0, -0.1)^T$  and  $\mathbf{u} := (u_x, u_y)^T$ . We try here to monitor the evolution of the residual as the mesh is refined.

**Remark** We follow [13] in order to obtain a optimal mesh refinement procedure, i.e. if  $\varepsilon_0$  is the accuracy required by the user, we say that the mesh  $\mathcal{T}^*$  is *optimal* if its elements number  $N^*$  is minimum and it provides a global error  $\varepsilon^*$  equal to  $\varepsilon_0$ .

In this framework, for each element  $T \in \mathcal{T}$ , we compute a refinement factor:

$$r_T = \frac{h_T^*}{h_T}$$

where  $h_T$  is the size of the element T of  $\mathcal{T}$ , and  $h_T^*$  the size of the elements of  $\mathcal{T}^*$  within the T area (in 2D case).

If no strong gradients appear in the solution, then a priori error estimates indicate that the local contribution to the error should scale like

$$\frac{\eta_T^*}{\eta_T} = \left(\frac{h_T^*}{h_T}\right)^p = r_T^p$$

where p depends on the element type (p=1 for linear elements, p=2 for quadratics elements).

Thus we have the following minimization problem:

$$\min N^* = \sum_T \left(\frac{1}{r_T}\right)^{dim} \quad \text{ with } \quad \sum_T r_T^2 \eta_T^2 = \varepsilon_0^2 \,.$$

In the 2D case, this problem admits the explicit solution:

$$r_T = \frac{\varepsilon_0^{1/p}}{\eta_T^{1/(p+1)} \left[ \sum_T \eta_T^{2/(p+1)} \right]^{1/2p}}.$$

The new mesh is then obtained by a metric controlled Delaunay mesh generator [9] constrained to generate local equilateral triangles of size  $r_T h_T$ .

Through the section  $\Omega_1$  and  $\Omega_4$  represent two isotropic materials with  $E_1=5, E_2=15000$  (Young's moduli),  $\nu_1=0.45, \nu_2=0.3$  (Poisson's coefficients), and  $\Omega_2$ ,  $\Omega_3$  are two orthotropic materials with elastic coefficients given by

$$\begin{pmatrix} 2000 & 50 & 0 \\ 50 & 51 & 0 \\ 0 & 0 & 2 \end{pmatrix} \quad \text{and} \quad \begin{pmatrix} 51 & 50 & 0 \\ 50 & 2000 & 0 \\ 0 & 0 & 2 \end{pmatrix},$$

respectively. In the first example (Fig 1), we only consider a unique isotropic material on the whole domain.





Figure 1: Example 1.

This problem is discretized using  $P_1$  elements (3 nodes triangles), but the same type of results is valid for quadrilaterals (we have tested the same examples using  $Q_2$  quadrilaterals). In the Figs 2-3 we can see the initial and adapted meshes and the distribution of the estimator  $\eta$  in these meshes.







Figure 2: Initial mesh (118 elements) and distribution of the error estimator  $\eta$  in the Example 1.







Figure 3: Final adapted mesh (571 elements) and distribution of the error estimator  $\eta$  in the Example 1.

In Fig 4 we present the isovalues of the solution of Example 1 and in Fig 5 we shown the Von Mises stress field for the same example.






Figure 4: Isovalues of the displacement (tangential and normal) for the Example 1.





Figure 5: Global and partial view of Von Mises stress field for the Example 1.

INRIA

Finally we show a comparison between the approximate solution in the initial mesh, the adapted mesh and our reference solution (calculated in a uniformly refined mesh).







Figure 6: Comparison between the differents solutions of the Example 1 in a diagonal cut.






Figure 7: Residual error for the example 1.

Example 2 (Fig 8) considers a soft material 1 neighboring a more rigid isotropic material 4, discretized with the same finite element than in Example 1.





Figure 8: Example 2.

The explanation of the figures in examples 2 and 3 is the same as in Example 1.







Figure 9: Initial mesh (146 elements) and distribution of the error estimator  $\eta$  in the Example 2.







Figure 10: Final adapted mesh (1804 elements) and distribution of the error estimator  $\eta$  in the Example 2.






Figure 11: Isovalues of the displacement (tangential and normal) for the Example 2.





Figure 12: Global and partial view of Von Mises stress field for the Example 2.

INRIA







Figure 13: Comparison between the differents solutions of the Example 2 in a diagonal cut.



The data for Example 3 are given on Fig 15. This represents a more realistic beam section reinforced by a rod and an anisotropic layer.





Figure 15: Example 3.

 ${\rm INRIA}$ 







Figure 16: Initial mesh (384 elements) and distribution of the error estimator  $\eta$  in the Example 3.







Figure 17: Final adapted mesh (1143 elements) and distribution of the error estimator  $\eta$  in the Example 3.






Figure 18: Isovalues of the displacement (tangential and normal) for the Example 3.





Figure 19: Global and partial view of Von Mises stress field for the Example 3.

INRIA







Figure 20: Comparison between the differents solutions of the Example 3 in a first diagonal cut.






Figure 21: Comparison between the differents solutions of the Example 3 in a second diagonal cut.




Figure 22: Residual error for the example 3.

The larger residuals appears here on the anisotropic material and next to the singularities. Recall that the proposed residual is not adapted to anisotropic situations.

## 6 Conclusions

We have derived and analyzed a local *a posteriori* error estimate for heterogeneous elastic bodies of residual type. The first numerical tests are encouraging for compressible isotropic materials.

Further work is needed to handle anisotropic heterogeneous bodies because we cannot proof the same type of results that for the isotropic case; nevertheless the numerical tests give the idea that our error estimate might work even in this framework. If this is not the case, it seems that one would have then to use some kind of generalization of the equilibration residual technique.

Indeed, the local H<sup>1</sup> norm appearing in the inverse inequality for estimating  $\nabla v_T$  will no longer be uniformly equivalent to the local energy norm. We feel then that the local energy norm of the residual can only be properly obtained by solving a local Neumann problem as advocated in [2].

**Acknowledgment.** The support by FIRTECH CS of the first author is gratefully acknowledged.

## References

- [1] M. Ainsworth and J.T. Oden. A unified approach to a posteriori error estimation using element residual methods. Numerische Mathematik, 65:23–50, 1993.
- [2] M. Ainsworth and J.T. Oden. A posteriori error estimation in finite element analysis. Computer Methods in Applied Mechanics and Engineering, 142:1–88, 1997.
- [3] M. Ainsworth, J.T. Oden, and W. Wu. A posteriori error estimation for h-p approximations in elastostatics. Applied Numerical Mathematics, 14:23–54, 1994.

- [4] I. Babuška and R. Rodríguez. The problem of the selection of an a posteriori error indicator based on smoothening techniques. International Journal for Numerical Methods in Engineering, 36:539-567, 1993.
- [5] I. Babuška, T. Strouboulis, and S.K. Gangaraj. Practical aspects of a posteriori estimation and adaptive control of the pollution error for reliable finite element analysis. Technical Report 96-30, TICAM, Texas, 1996.
- [6] I. Babuška, T. Strouboulis, C.S. Upadhyay, and S.K. Gangaraj. A model study of element residual estimators for linear elliptic problems: The quality of the estimators in the interior of meshes of triangles and quadrilaterals. *Computers & Structures*, 57:1009–1028, 1995.
- [7] P.L. Baehmann, M.S. Shephard, and J.E. Flaherty. A posteriori error estimation for triangular and tetrahedral quadratic elements using interior residuals. International Journal for Numerical Methods in Engineering, 34:979–996, 1992.
- [8] C. Bernardi and V. Girault. A local regularization operator for triangular and quadrilateral finite elements. Technical Report 95036, UPMC, Paris, 1995.
- [9] H. Borouchaki and P. Laug. The bl2d mesh generator: beginner's guide, user's guide and programmer's manual. Technical Report RT-0194, IN-RIA, 1996.
- [10] Ph. G. Ciarlet. The finite element method. North-Holland, Amsterdam, 1978.
- [11] K. Eriksson and C. Johnson. An adaptative finite element method for linear elliptic problems. *Mathematics of Computation*, 50(182):361–383, 1988.
- [12] C. Johnson and P. Hansbo. Adaptative finite elements methods in computational mechanics. Computer Methods in Applied Mechanics and Engineering, 101:143–181, 1992.

- [13] P. Ladeveze, J.P. Pelle, and Ph. Rougeot. Error estimation and mesh optimization for classical finite elements. *Engineering Computations*, 8:69–80, 1991.
- [14] P. Ladezeve and D. Leguillon. Error estimate procedure in the finite element method and applications. Siam Journal of Numerical Analysis, 20:485–509, 1983.
- [15] C.K. Lee and S.H. Lo. Automatic adaptive refinement finite element procedure for 3D stress analysis. Finite Elements in Analysis and Design, 25:135–166, 1997.
- [16] R. Mücke and J.R. Whiteman. A posteriori error estimates and adaptivity for finite element solutions in finite elasticity. International Journal for Numerical Methods in Engineering, 38:775-795, 1995.
- [17] S. Nepomnyaschikh. A local projection operator. personal communication.
- [18] B.A. Szabó. The p and h-p versions of the finite element method in solid mechanics. Computer Methods in Applied Mechanics and Engineering, 80:185-195, 1990.
- [19] R. Verfürth. A posteriori error estimation and adaptive mesh-refineent techniques. Journal of Computational and Applied Mathematics, 50:67–83, 1994.
- [20] R. Verfürth. A review of a posteriori error estimation and adaptative mesh-refinement techniques. Wiley and Teubner, Chichester-Stuttgart, 1996.
- [21] N. Wiberg, L. Zeng, and X. Li. Error estimation and adaptivity in elastodynamics. Computer Methods in Applied Mechanics and Engineering, 101:369–395, 1992.
- [22] O. Zienkiewicz and J.Z. Zhu. A simple error estimator and adaptative procedure for practical engineering analysis. *International Journal for Numerical Methods in Engineering*, 24:333–357, 1987.

- [23] O. Zienkiewicz and J.Z. Zhu. The superconvergent patch recovery and a posteriori error estimates. Part 1: The recovery technique. International Journal for Numerical Methods in Engineering, 33:1331-1364, 1992.
- [24] O. Zienkiewicz and J.Z. Zhu. The superconvergent patch recovery and a posteriori error estimates. Part 2: Error estimates and adaptivity. International Journal for Numerical Methods in Engineering, 33:1365–1382, 1992.
- [25] O. Zienkiewicz and J.Z. Zhu. The superconvergent patch recovery (SPR) and adaptive finite element refinement. Computer Methods in Applied Mechanics and Engineering, 101:207–224, 1992.



Unit´e de recherche INRIA Lorraine, Technopôle de Nancy-Brabois, Campus scientifique,
615 rue du Jardin Botanique, BP 101, 54600 VILLERS LÈS NANCY
Unit´e de recherche INRIA Rennes, Irisa, Campus universitaire de Beaulieu, 35042 RENNES Cedex
Unit´e de recherche INRIA Rhône-Alpes, 655, avenue de l'Europe, 38330 MONTBONNOT ST MARTIN
Unit´e de recherche INRIA Rocquencourt, Domaine de Voluceau, Rocquencourt, BP 105, 78153 LE CHESNAY Cedex
Unit´e de recherche INRIA Sophia-Antipolis, 2004 route des Lucioles, BP 93, 06902 SOPHIA-ANTIPOLIS Cedex

Éditeur INRIA, Domaine de Voluceau, Rocquencourt, BP 105, 78153 LE CHESNAY Cedex (France) ISSN 0249-6399