



Parallel Computational Acoustics Library - Reference Manual

Frédéric Magoulès, François-Xavier Roux

► To cite this version:

Frédéric Magoulès, François-Xavier Roux. Parallel Computational Acoustics Library - Reference Manual. [Intern report] A02-R-074 || magoules02c, 2002, 129 p. inria-00099431

HAL Id: inria-00099431

<https://inria.hal.science/inria-00099431>

Submitted on 26 Sep 2006

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Parallel Computational Acoustics Library
Reference Manual*
by F. Magoulès and F.-X. Roux

June 13, 2002

Contents

1 Modules	17
1.1 block_size	17
1.2 direct_symmetric	17
1.3 direct_unsymmetric	17
1.4 facet_struct	18
1.5 factorized_matrix_struct	18
1.6 feti_data	19
1.7 feti_param	20
1.8 interf_descriptor_struct	20
1.9 interf_mesh_struct	22
1.10 load_curve_struct	22
1.11 mesh_feti_struct	23
1.12 mesh_struct	23
1.13 model	24
1.14 mpif	25
1.15 nodal_list_struct	25
1.16 outfil	26
1.17 realloc	26
1.18 region_property_struct	27
1.19 solver_param	27
1.20 sparse_matrix_struct	28

* Generated by adoC, awk documenting C, June 13, 2002

2 Functions	29
2.1 add_interf_matrix	29
2.2 add_interf_matrix_structure	29
2.3 add_sparse_sym_matrix	30
2.4 add_sparse_sym_struct	30
2.5 add_sparse_unsym_matrix	31
2.6 add_sparse_unsym_struct	31
2.7 assemble_bc	32
2.8 assemble_facet_bc	32
2.9 assemble_impedance	33
2.10 assemble_interf_matrix	33
2.11 assemble_nodal_bc	34
2.12 bcast_acoustic_property	35
2.13 bcast_admittance_property	35
2.14 bcast_facet	36
2.15 bcast_infinite_property	36
2.16 bcast_load_curve	37
2.17 bcast_model_attribute	37
2.18 bcast_model_parameters	38
2.19 bcast_nodal_list	38
2.20 bcast_solver_parameters	39
2.21 build_diag	39
2.22 build_dirich_aug	40
2.23 build_interf_matrix_structure	40
2.24 build_interface	41
2.25 build_matrix_structure	41
2.26 build_node_eq	42
2.27 build_rev_geometry	42
2.28 build_rev_nodid	43
2.29 build_sparse_sym_struct	43
2.30 build_sparse_unsym_struct	44
2.31 build_topology	44
2.32 calpd	45
2.33 cmk_number	45
2.34 condens_1	45

2.35	condens_2	46
2.36	condens_3	47
2.37	copy_block	47
2.38	dirichlet_bc	48
2.39	distribute_model	48
2.40	echo_facet	49
2.41	echo_mesh	49
2.42	echo_mesh_femview	49
2.43	echo_model	50
2.44	echo_nodal_list	50
2.45	equation_setup	51
2.46	extent_i1	51
2.47	extent_r2	52
2.48	extract_submesh	52
2.49	facet_rhs	53
2.50	factorize_numeric	53
2.51	factorize_symbolic	54
2.52	feti_abort	54
2.53	feti_finalize	55
2.54	feti_init	55
2.55	fill_sym_sparse	56
2.56	fill_unsym_sparse	56
2.57	frontal numb	57
2.58	full_schur_b	57
2.59	full_blo	58
2.60	full_fwbw	58
2.61	full_ldlt	59
2.62	full_ldlt_b	59
2.63	full_ldu	59
2.64	full_ldu_b	60
2.65	full_schur_b_sparse	60
2.66	full_sto	61
2.67	full_unsto	61
2.68	galerkin_error	62
2.69	galerkin_meshsize	62

2.70	galerkin_tau	63
2.71	gather_nodid	63
2.72	gather_sol	64
2.73	global_eq_mask	64
2.74	global_solution	65
2.75	globaldotproduct	65
2.76	globalsum	66
2.77	globalsumc	66
2.78	globalsumi	67
2.79	half_schur_b	67
2.80	half_blo	68
2.81	half_fwbw	68
2.82	half_mm_b	69
2.83	half_schur_b_sparse	69
2.84	half_sto	70
2.85	half_unsto	70
2.86	ilu_0	70
2.87	ilu_preconditioner	71
2.88	imprim	71
2.89	imprim2	72
2.90	init_model	72
2.91	initialize	73
2.92	inivec	73
2.93	input_data	74
2.94	interf_full_sym_struct	74
2.95	interf_full_unsym_struct	75
2.96	interf_sparse_sym_struct	75
2.97	interf_sparse_unsym_struct	76
2.98	interface_assemb	76
2.99	interface_average	77
2.100	interface_equation	77
2.101	interface_exchange	78
2.102	interface_init	78
2.103	interface_jump	78
2.104	interface_jump2	79

2.105 interface_mesh_equation	80
2.106 interface_mesh_geometry	80
2.107 interface_mesh_topology	81
2.108 interface_node	81
2.109 interface_signe	82
2.110 invD_times_U	82
2.111 invL_times_U	83
2.112 invL_times_sparsU	83
2.113 invUt_times_sparsU	83
2.114 jacobi_convergence	84
2.115 jacobi_optimized	85
2.116 L_times_invD	85
2.117 L_times_invU	86
2.118 LdLt_tri_block_numeric	86
2.119 LdLt_tri_block_symbolic	86
2.120 Ldlt_tri_dirich	87
2.121 LdU_tri_block_numeric	87
2.122 LdU_tri_block_symbolic	88
2.123 LdU_tri_dirich	88
2.124 mask_to_list	89
2.125 merge_nodal_list	89
2.126 mtxv	90
2.127 mtxv_par	90
2.128 mxvadd	91
2.129 nodal_list_equation	91
2.130 opti_number	92
2.131 output_results	92
2.132 point_front	93
2.133 post_process	93
2.134 print_vector	94
2.135 proband	94
2.136 probit	95
2.137 problem_form	95
2.138 problo	96
2.139 proplot	96

2.140	pt_extract	97
2.141	read_mesh	97
2.142	realloc_c1	98
2.143	realloc_c2	98
2.144	realloc_i1	99
2.145	realloc_i2	99
2.146	realloc_r1	100
2.147	realloc_r2	100
2.148	ren_sym_sparse	100
2.149	ren_unsym_sparse	101
2.150	renum_eq_mpc	101
2.151	renum_facet	102
2.152	renum_nodal_list	102
2.153	solve_rhs	103
2.154	son_3d	103
2.155	sort_list	104
2.156	sparse_fwbw	104
2.157	sparse_matrix_equalization	105
2.158	sparse_matrix_equalization2	105
2.159	sparse_prod	106
2.160	split_mesh	106
2.161	stoprun	107
2.162	sym_approx_schur_cpmt	107
2.163	sym_build_schur_cpmt	108
2.164	sym_condens	108
2.165	sym_direct_solve	109
2.166	sym_extract	110
2.167	sym_fill_tridiag_sparse	110
2.168	sym_fwbw_tri_dirichlet	111
2.169	sym_multi_level1_feti	111
2.170	sym_multi_level2_feti	112
2.171	sym_proax	113
2.172	sym_renumb_matrix_bc	114
2.173	sym_tridiag_struct	114
2.174	symfwbw_tri_dirichlet	115

2.175 symunsym_sparse_mask	115
2.176 un_condens	116
2.177 un_extract	116
2.178 unsym_approx_schur_cpmt	117
2.179 unsym_build_schur_cpmt	118
2.180 unsym_direct_solve	118
2.181 unsym_fill_tridiag_sparse	119
2.182 unsym_fwbw_tri_dirichlet	119
2.183 unsym_multi_level1_feti	120
2.184 unsym_multi_level2_feti	120
2.185 unsym_proax	121
2.186 unsym_renumb_matrix_bc	122
2.187 unsym_tridiag_struct	122
2.188 unsymfwbw_tri_dirichlet	123
2.189 unsymunsym_sparse_mask	123
2.190 update_facet	124
2.191 Update_Nodal_List	124
2.192 update_region	125
2.193 write_field	125
2.194 write_field_femview	126
2.195 write_matrix	126
2.196 write_meshfield_femvtk	127
2.197 zorthodir_solver	127
2.198 zorthodir_solver_par	128

Index

Alphabetical

add_interf_matrix, 29
add_interf_matrix_structure, 29
add_sparse_sym_matrix, 30
add_sparse_sym_struct, 30
add_sparse_unsym_matrix, 31
add_sparse_unsym_struct, 31
assemble_bc, 32
assemble_facet_bc, 32
assemble_impedance, 33
assemble_interf_matrix, 33
assemble_nodal_bc, 34
bcast_acoustic_property, 35
bcast_admittance_property, 35
bcast_facet, 36
bcast_infinite_property, 36
bcast_load_curve, 37
bcast_model_attribute, 37
bcast_model_parameters, 38
bcast_nodal_list, 38
bcast_solver_parameters, 39
block_size, 17
build_diag, 39
build_dirich_aug, 40
build_interf_matrix_structure , 40
build_interface, 41
build_matrix_structure, 41
build_node_eq, 42
build_rev_geometry, 42
build_rev_nodid, 43
build_sparse_sym_struct, 43
build_sparse_unsym_struct, 44
build_topology, 44
calpd, 45
cmk_number, 45
condens_1, 45
condens_2, 46
condens_3, 47
copy_block, 47
direct_symmetric, 17
direct_unsymmetric, 17
dirichlet_bc, 48
distribute_model, 48
echo_facet, 49
echo_mesh, 49
echo_mesh_femview, 49
echo_model, 50
echo_nodal_list, 50
equation_setup, 51
extent_i1, 51
extent_r2, 52
extract_submesh, 52
facet_rhs, 53
facet_struct, 18
factorize_numeric, 53
factorize_symbolic, 54
factorized_matrix_struct, 18
feti_abort, 54
feti_data, 19
feti_finalize, 55
feti_init, 55
feti_param, 20
fill_sym_sparse, 56
fill_unsym_sparse, 56
frontal_numb, 57
full_blo, 58
full_fwbw, 58
full_ldlt, 59
full_ldlt_b, 59
full_ldu, 59
full_ldu_b, 60
full_schur_b, 57
full_schur_b_sparse, 60
full_sto, 61
full_unsto, 61
galerkin_error, 62
galerkin_meshsize, 62
galerkin_tau, 63
gather_nodid, 63
gather_sol, 64
global_eq_mask, 64
global_solution, 65
globaldotproduct, 65
globalsum, 66
globalsumc, 66
globsumi, 67
half_blo, 68
half_fwbw, 68
half_mm_b, 69
half_schur_b, 67
half_schur_b_sparse, 69
half_sto, 70
half_unsto, 70
ilu_0, 70
ilu_preconditioner, 71
imprim, 71
imprim2, 72
init_model, 72
initialize, 73

```

inivec, 73
input_data, 74
interf_descriptor_struct, 20
interf_full_sym_struct, 74
interf_full_unsym_struct, 75
interf_mesh_struct, 22
interf_sparse_sym_struct, 75
interf_sparse_unsym_struct, 76
interface_assemb, 76
interface_average, 77
interface_equation, 77
interface_exchange, 78
interface_init, 78
interface_jump, 78
interface_jump2, 79
interface_mesh_equation, 80
interface_mesh_geometry, 80
interface_mesh_topology, 81
interface_node, 81
interface_signe, 82
invD_times_U, 82
invL_times_sparsU, 83
invL_times_U, 83
invUt_times_sparsU, 83
jacobi_convergence, 84
jacobi_optimized, 85
L_times_invD , 85
L_times_invU, 86
LdLt_tri_block_numeric, 86
LdLt_tri_block_symbolic, 86
Ldlt_tri_dirich, 87
LdU_tri_block_numeric, 87
LdU_tri_block_symbolic, 88
LdU_tri_dirich, 88
load_curve_struct, 22
mask_to_list, 89
merge_nodal_list, 89
mesh_feti_struct, 23
mesh_struct, 23
model, 24
mpif, 25
mtxv, 90
mtxv_par, 90
mxvadd, 91
nodal_list_equation, 91
nodal_list_struct, 25
opti_number, 92
outfil, 26
output_results, 92
point_front, 93
post_process, 93
print_vector, 94
proband, 94
probit, 95
problem_form , 95
problo, 96
problot, 96
pt_extract, 97
read_mesh, 97
realloc, 26
realloc_c1, 98
realloc_c2, 98
realloc_i1, 99
realloc_i2, 99
realloc_r1, 100
realloc_r2, 100
region_property_struct, 27
ren_sym_spars, 100
ren_unsym_spars, 101
renum_eq_mpc, 101
renum_facet, 102
renum_nodal_list, 102
solve_rhs, 103
solver_param, 27
son_3d, 103
sort_list, 104
sparse_fwbw, 104
sparse_matrix_equalization, 105
sparse_matrix_equalization2, 105
sparse_matrix_struct, 28
sparse_prod, 106
split_mesh, 106
stoprun, 107
sym_approx_schur_cpmt, 107
sym_build_schur_cpmt, 108
sym_condens, 108
sym_direct_solve, 109
sym_extract, 110
sym_fill_tridiag_spars, 110
sym_fwbw_tri_dirichlet, 111
sym_multi_level1_feti, 111
sym_multi_level2_feti, 112
sym_proax, 113
sym_renumb_matrix_bc, 114
sym_tridiag_struct, 114
symfbw_tri_dirichlet, 115
symunsym_sparses_mask, 115
un_condens, 116
un_extract, 116
unsym_approx_schur_cpmt, 117
unsym_build_schur_cpmt, 118
unsym_direct_solve, 118
unsym_fill_tridiag_spars, 119
unsym_fwbw_tri_dirichlet, 119

```

```

unsym_multi_level1_feti, 120
unsym_multi_level2_feti, 120
unsym_proax, 121
unsym_renumb_matrix_bc, 122
unsym_tridiag_struct, 122
unsymfbw_tri_dirichlet, 123
unsymunsym_sparse_mask, 123
update_facet, 124
Update_Nodal_List, 124
update_region, 125
write_field, 125
write_field_femview, 126
write_matrix, 126
write_meshfield_femvtk, 127
zorthodir_solver, 127
zorthodir_solver_par, 128

Files
add_interf_matrix.f90
    add_interf_matrix, 29
add_interf_matrix_struct.f90
    add_interf_matrix_structure, 29
add_sparse_sym_matrix.f90
    add_sparse_sym_matrix, 30
add_sparse_sym_struct.f90
    add_sparse_sym_struct, 30
add_sparse_unsym_matrix.f90
    add_sparse_unsym_matrix, 31
add_sparse_unsym_struct.f90
    add_sparse_unsym_struct, 31
assemble_bc.f90
    assemble_bc, 32
assemble_facet_bc.f90
    assemble_facet_bc, 32
assemble_impedance.f90
    assemble_impedance, 33
assemble_interf_matrix.f90
    assemble_interf_matrix, 33
assemble_nodal_bc.f90
    assemble_nodal_bc, 34
bcast_acoustic_property.f90
    bcast_acoustic_property, 35
bcast_admittance_property.f90
    bcast_admittance_property, 35
bcast_facet.f90
    bcast_facet, 36
bcast_infinite_property.f90
    bcast_infinite_property, 36
bcast_load_curve.f90
    bcast_load_curve, 37
bcast_model_attribute.f90
    bcast_model_attribute, 37

bcast_model_parameters.f90
    bcast_model_parameters, 38
bcast_nodal_list.f90
    bcast_nodal_list, 38
bcast_solver_parameters.f90
    bcast_solver_parameters, 39
block_size.f90
    block_size, 17
build_diag.f90
    build_diag, 39
build_dirich_aug.f90
    build_dirich_aug, 40
build_interf_matrix_struct.f90
    build_interf_matrix_structure , 40
build_interface.f90
    build_interface, 41
build_matrix_struct.f90
    build_matrix_structure, 41
build_node_eq.f90
    build_node_eq, 42
build_rev_geometry.f90
    build_rev_geometry, 42
build_rev_nodid.f90
    build_rev_nodid, 43
build_sparse_sym_struct.f90
    build_sparse_sym_struct, 43
build_sparse_unsym_struct.f90
    build_sparse_unsym_struct, 44
build_topology.f90
    build_topology, 44
calpd.f90
    calpd, 45
cmk_number.f90
    cmk_number, 45
condens_1.f90
    condens_1, 45
condens_2.f90
    condens_2, 46
condens_3.f90
    condens_3, 47
copy_block.f90
    copy_block, 47
direct_symmetric.f90
    direct_symmetric, 17
direct_unsymmetric.f90
    direct_unsymmetric, 17
dirichlet_bc.f90
    dirichlet_bc, 48
distribute_model.f90
    distribute_model, 48
echo_facet.f90
    echo_facet, 49

```

```

echo_mesh.f90
  echo_mesh, 49
echo_mesh_femview.f90
  echo_mesh_femview, 49
echo_model.f90
  echo_model, 50
echo_nodal_list.f90
  echo_nodal_list, 50
equation_setup.f90
  equation_setup, 51
extent_i1.f90
  extent_i1, 51
extent_r2.f90
  extent_r2, 52
extract_submesh.f90
  extract_submesh, 52
facet_rhs.f90
  facet_rhs, 53
facet_struct.f90
  facet_struct, 18
factorize_numeric.f90
  factorize_numeric, 53
factorize_symbolic.f90
  factorize_symbolic, 54
factorized_matrix_struct.f90
  factorized_matrix_struct, 18
feti_abort.f90
  feti_abort, 54
feti_data.f90
  feti_data, 19
feti_finalize.f90
  feti_finalize, 55
feti_init.f90
  feti_init, 55
feti_param.f90
  feti_param, 20
fill_sym_sparse.f90
  fill_sym_sparse, 56
fill_unsym_sparse.f90
  fill_unsym_sparse, 56
frontal numb.f90
  frontal numb, 57
full_blo.f90
  full_blo, 58
full_fwbw.f90
  full_fwbw, 58
full_dlt.f90
  full_dlt, 59
full_dlt_b.f90
  full_dlt_b, 59
full_ldu.f90
  full_ldu, 59
full_ldu_b.f90
  full_ldu_b, 60
full_Schur_b.f90
  full_schur_b, 57
full_schur_b_sparse.f90
  full_schur_b_sparse, 60
full_sto.f90
  full_sto, 61
full_unsto.f90
  full_unsto, 61
galerkin_error.f90
  galerkin_error, 62
galerkin_meshsize.f90
  galerkin_meshsize, 62
galerkin_tau.f90
  galerkin_tau, 63
gather_nodid.f90
  gather_nodid, 63
gather_sol.f90
  gather_sol, 64
global_eq_mask.f90
  global_eq_mask, 64
global_solution.f90
  global_solution, 65
globaldotproduct.f90
  globaldotproduct, 65
globalsum.f90
  globalsum, 66
globalsumc.f90
  globalsumc, 66
globalsumi.f90
  globalsumi, 67
half_blo.f90
  half_blo, 68
half_fwbw.f90
  half_fwbw, 68
half_mm_b.f90
  half_mm_b, 69
half_Schur_b.f90
  half_schur_b, 67
half_schur_b_sparse.f90
  half_schur_b_sparse, 69
half_sto.f90
  half_sto, 70
half_unsto.f90
  half_unsto, 70
ilu_0.f90
  ilu_0, 70
ilu_preconditioner.f90
  ilu_preconditioner, 71
imprim.f90
  imprim, 71

```

```

imprim2.f90
    imprim2, 72
init_model.f90
    init_model, 72
initialize.f90
    initialize, 73
inivec.f90
    inivec, 73
input_data.f90
    input_data, 74
interf_descriptor_struct.f90
    interf_descriptor_struct, 20
interf_full_sym_struct.f90
    interf_full_sym_struct, 74
interf_full_unsym_struct.f90
    interf_full_unsym_struct, 75
interf_mesh_struct.f90
    interf_mesh_struct, 22
interf_sparse_sym_struct.f90
    interf_sparse_sym_struct, 75
interf_sparse_unsym_struct.f90
    interf_sparse_unsym_struct, 76
interface_assemb.f90
    interface_assemb, 76
interface_average.f90
    interface_average, 77
interface_equation.f90
    interface_equation, 77
interface_exchange.f90
    interface_exchange, 78
interface_init.f90
    interface_init, 78
interface_jump.f90
    interface_jump, 78
interface_jump2.f90
    interface_jump2, 79
interface_mesh_equation.f90
    interface_mesh_equation, 80
interface_mesh_geometry.f90
    interface_mesh_geometry, 80
interface_mesh_topology.f90
    interface_mesh_topology, 81
interface_node.f90
    interface_node, 81
interface_signe.f90
    interface_signe, 82
invD_times_U.f90
    invD_times_U, 82
invL_times_sparsu.f90
    invL_times_sparsU, 83
invL_times_U.f90
    invL_times_U, 83
invut_times_sparsu.f90
    invUt_times_sparsU, 83
jacobi_convergence.f90
    jacobi_convergence, 84
jacobi_optimized.f90
    jacobi_optimized, 85
l_times_invD.f90
    L_times_invD, 85
l_times_invU.f90
    L_times_invU, 86
ldlt_tri_block_numeric.f90
    LdLt_tri_block_numeric, 86
ldlt_tri_block_symbolic.f90
    LdLt_tri_block_symbolic, 86
ldlt_tri_dirich.f90
    Ldlt_tri_dirich, 87
ldu_tri_block_numeric.f90
    LdU_tri_block_numeric, 87
ldu_tri_block_symbolic.f90
    LdU_tri_block_symbolic, 88
ldu_tri_dirich.f90
    LdU_tri_dirich, 88
load_curve_struct.f90
    load_curve_struct, 22
mask_to_list.f90
    mask_to_list, 89
merge_nodal_list.f90
    merge_nodal_list, 89
mesh_feti_struct.f90
    mesh_feti_struct, 23
mesh_struct.f90
    mesh_struct, 23
model.f90
    model, 24
mpif.f90
    mpif, 25
mtxv.f90
    mtxv, 90
mtxv_par.f90
    mtxv_par, 90
mxvadd.f90
    mxvadd, 91
nodal_list_equation.f90
    nodal_list_equation, 91
nodal_list_struct.f90
    nodal_list_struct, 25
opti_number.f90
    opti_number, 92
outfil.f90
    outfil, 26
output_results.f90
    output_results, 92

```

```

point_front.f90
  point_front, 93
post_process.f90
  post_process, 93
print_vector.f90
  print_vector, 94
probond.f90
  probond, 94
probit.f90
  probit, 95
problem_form.f90
  problem_form , 95
problo.f90
  problo, 96
problot.f90
  problot, 96
pt_extract.f90
  pt_extract, 97
read_mesh.f90
  read_mesh, 97
realloc.f90
  realloc, 26
realloc_c1.f90
  realloc_c1, 98
realloc_c2.f90
  realloc_c2, 98
realloc_i1.f90
  realloc_i1, 99
realloc_i2.f90
  realloc_i2, 99
realloc_r1.f90
  realloc_r1, 100
realloc_r2.f90
  realloc_r2, 100
region_property_struct.f90
  region_property_struct, 27
ren_sym_sparse.f90
  ren_sym_sparse, 100
ren_unsym_sparse.f90
  ren_unsym_sparse, 101
renum_eq_mpc.f90
  renum_eq_mpc, 101
renum_facet.f90
  renum_facet, 102
renum_nodal_list.f90
  renum_nodal_list, 102
solve_rhs.f90
  solve_rhs, 103
solver_param.f90
  solver_param, 27
son_3D.f90
  son_3d, 103
sort_list.f90
  sort_list, 104
sparse_fwbw.f90
  sparse_fwbw, 104
sparse_matrix_equalization.f90
  sparse_matrix_equalization, 105
sparse_matrix_equalization2.f90
  sparse_matrix_equalization2, 105
sparse_matrix_struct.f90
  sparse_matrix_struct, 28
sparse_prod.f90
  sparse_prod, 106
split_mesh.f90
  split_mesh, 106
stoprun.f90
  stoprun, 107
sym_approx_schur_cpmt.f90
  sym_approx_schur_cpmt, 107
sym_build_schur_cpmt.f90
  sym_build_schur_cpmt, 108
sym_condens.f90
  sym_condens, 108
sym_direct_solve.f90
  sym_direct_solve, 109
sym_extract.f90
  sym_extract, 110
sym_fill_tridiag_sparse.f90
  sym_fill_tridiag_sparse, 110
sym_fwbw_tri_dirichlet.f90
  sym_fwbw_tri_dirichlet, 111
sym_multi_level1_feti.f90
  sym_multi_level1_feti, 111
sym_multi_level2_feti.f90
  sym_multi_level2_feti, 112
sym_proax.f90
  sym_proax, 113
sym_renumb_matrix_bc.f90
  sym_renumb_matrix_bc, 114
sym_tridiag_struct.f90
  sym_tridiag_struct, 114
symfwbw_tri_dirichlet.f90
  symfwbw_tri_dirichlet, 115
symunsym_sparse_mask.f90
  symunsym_sparse_mask, 115
un_condens.f90
  un_condens, 116
un_extract.f90
  un_extract, 116
unsym_approx_schur_cpmt.f90
  unsym_approx_schur_cpmt, 117
unsym_build_schur_cpmt.f90
  unsym_build_schur_cpmt, 118

```

```

unsym_direct_solve.f90
  unsym_direct_solve, 118
unsym_fill_tridiag_sparse.f90
  unsym_fill_tridiag_sparse, 119
unsym_fwbw_tri_dirichlet.f90
  unsym_fwbw_tri_dirichlet, 119
unsym_multi_level1_feti.f90
  unsym_multi_level1_feti, 120
unsym_multi_level2_feti.f90
  unsym_multi_level2_feti, 120
unsym_proax.f90
  unsym_proax, 121
unsym_renumb_matrix_bc.f90
  unsym_renumb_matrix_bc, 122
unsym_tridiag_struct.f90
  unsym_tridiag_struct, 122
unsymfwbw_tri_dirichlet.f90
  unsymfwbw_tri_dirichlet, 123
unsymunsym_sparse_mask.f90
  unsymunsym_sparse_mask, 123
update_facet.f90
  update_facet, 124
update_nodal_list.f90
  Update_Nodal_List, 124
update_region.f90
  update_region, 125
write_field.f90
  write_field, 125
write_field_femview.f90
  write_field_femview, 126
write_matrix.f90
  write_matrix, 126
write_meshfield_femvtk.f90
  write_meshfield_femvtk, 127
zorthodir_solver.f90
  zorthodir_solver, 127
zorthodir_solver_par.f90
  zorthodir_solver_par, 128

```

Sorted

Functions

```

add_interf_matrix, 29
add_interf_matrix_structure, 29
add_sparse_sym_matrix, 30
add_sparse_sym_struct, 30
add_sparse_unsym_matrix, 31
add_sparse_unsym_struct, 31
assemble_bc, 32
assemble_facet_bc, 32
assemble_impedance, 33
assemble_interf_matrix, 33
assemble_nodal_bc, 34
bcast_acoustic_property, 35
bcast_admittance_property, 35
bcast_facet, 36
bcast_infinite_property, 36
bcast_load_curve, 37
bcast_model_attribute, 37
bcast_model_parameters, 38
bcast_nodal_list, 38
bcast_solver_parameters, 39
build_diag, 39
build_dirich_aug, 40
build_interf_matrix_structure , 40
build_interface, 41
build_matrix_structure, 41
build_node_eq, 42
build_rev_geometry, 42
build_rev_nodid, 43
build_sparse_sym_struct, 43
build_sparse_unsym_struct, 44
build_topology, 44
calpd, 45
cmk_number, 45
condens_1, 45
condens_2, 46
condens_3, 47
copy_block, 47
dirichlet_bc, 48
distribute_model, 48
echo_facet, 49
echo_mesh, 49
echo_mesh_femview, 49
echo_model, 50
echo_nodal_list, 50
equation_setup, 51
extent_x1, 51
extent_x2, 52
extract_submesh, 52
facet_rhs, 53
factorize_numeric, 53
factorize_symbolic, 54
feti_abort, 54
feti_finalize, 55
feti_init, 55
fill_sym_sparse, 56
fill_unsym_sparse, 56
frontal_numb, 57
full_blo, 58
full_fwbw, 58
full_ldlt, 59
full_ldlt_b, 59
full_ldu, 59
full_ldu_b, 60

```

full_schur_b, 57
 full_schur_b_sparse, 60
 full_sto, 61
 full_unsto, 61
 galerkin_error, 62
 galerkin_meshsize, 62
 galerkin_tau, 63
 gather_nodid, 63
 gather_sol, 64
 global_eq_mask, 64
 global_solution, 65
 globaldotproduct, 65
 globalsum, 66
 globalsumc, 66
 globalsumi, 67
 half_blo, 68
 half_fwbw, 68
 half_mm_b, 69
 half_schur_b, 67
 half_schur_b_sparse, 69
 half_sto, 70
 half_unsto, 70
 ilu_0, 70
 ilu_preconditioner, 71
 imprim, 71
 imprim2, 72
 init_model, 72
 initialize, 73
 inivec, 73
 input_data, 74
 interf_full_sym_struct, 74
 interf_full_unsym_struct, 75
 interf_sparse_sym_struct, 75
 interf_sparse_unsym_struct, 76
 interface_assemb, 76
 interface_average, 77
 interface_equation, 77
 interface_exchange, 78
 interface_init, 78
 interface_jump, 78
 interface_jump2, 79
 interface_mesh_equation, 80
 interface_mesh_geometry, 80
 interface_mesh_topology, 81
 interface_node, 81
 interface_signe, 82
 invD_times_U, 82
 invL_times_sparsU, 83
 invL_times_U, 83
 invUt_times_sparsU, 83
 jacobi_convergence, 84
 jacobi_optimized, 85
 L_times_invD , 85
 L_times_invU, 86
 LdLt_tri_block_numeric, 86
 LdLt_tri_block_symbolic, 86
 Ldlt_tri_dirich, 87
 LdU_tri_block_numeric, 87
 LdU_tri_block_symbolic, 88
 LdU_tri_dirich, 88
 mask_to_list, 89
 merge_nodal_list, 89
 mtxv, 90
 mtxv_par, 90
 mxvadd, 91
 nodal_list_equation, 91
 opti_number, 92
 output_results, 92
 point_front, 93
 post_process, 93
 print_vector, 94
 proband, 94
 probit, 95
 problem_form , 95
 problo, 96
 proplot, 96
 pt_extract, 97
 read_mesh, 97
 realloc_c1, 98
 realloc_c2, 98
 realloc_i1, 99
 realloc_i2, 99
 realloc_r1, 100
 realloc_r2, 100
 ren_sym_sparse, 100
 ren_unsym_sparse, 101
 renum_eq_mpc, 101
 renum_facet, 102
 renum_nodal_list, 102
 solve_rhs, 103
 son_3d, 103
 sort_list, 104
 sparse_fwbw, 104
 sparse_matrix_equalization, 105
 sparse_matrix_equalization2, 105
 sparse_prod, 106
 split_mesh, 106
 stoprun, 107
 sym_approx_schur_cpmt, 107
 sym_build_schur_cpmt, 108
 sym_condens, 108
 sym_direct_solve, 109
 sym_extract, 110
 sym_fill_tridiag_sparse, 110

sym_fwbw_tri_dirichlet, 111
 sym_multi_level1_feti, 111
 sym_multi_level2_feti, 112
 sym_proax, 113
 sym_renumb_matrix_bc, 114
 sym_tridiag_struct, 114
 symfbw_tri_dirichlet, 115
 symunsym_sparse_mask, 115
 un_condens, 116
 un_extract, 116
 unsym_approx_schur_cpmt, 117
 unsym_build_schur_cpmt, 118
 unsym_direct_solve, 118
 unsym_fill_tridiag_sparse, 119
 unsym_fwbw_tri_dirichlet, 119
 unsym_multi_level1_feti, 120
 unsym_multi_level2_feti, 120
 unsym_proax, 121
 unsym_renumb_matrix_bc, 122
 unsym_tridiag_struct, 122
 unsymfbw_tri_dirichlet, 123
 unsymunsym_sparse_mask, 123
 update_facet, 124
 Update_Nodal_List, 124
 update_region, 125
 write_field, 125
 write_field_femview, 126
 write_matrix, 126
 write_meshfield_femvtk, 127
 zorthodir_solver, 127
 zorthodir_solver_par, 128

Modules

block_size, 17
 direct_symmetric, 17
 direct_unsymmetric, 17
 facet_struct, 18
 factorized_matrix_struct, 18
 feti_data, 19
 feti_param, 20
 interf_descriptor_struct, 20
 interf_mesh_struct, 22
 load_curve_struct, 22
 mesh_feti_struct, 23
 mesh_struct, 23
 model, 24
 mpif, 25
 nodal_list_struct, 25
 outfil, 26
 realloc, 26
 region_property_struct, 27
 solver_param, 27
 sparse_matrix_struct, 28

1 Modules

1.1 block_size

NAME

block_size

SYNOPSIS

```
MODULE block_size
```

DESCRIPTION

Block size for factorization of matrices used in the direct solver.

ARGUMENTS

n1 – integer
n2 – integer

1.2 direct_symmetric

NAME

direct_symmetric

SYNOPSIS

```
MODULE direct_symmetric
```

DESCRIPTION

Direct method module for symmetric complex matrix.

ARGUMENTS

ldu_Robin – factorized matrix structure
ldu_Dirichlet – factorized matrix structure

MODULES

```
USE factorized_matrix_struct
```

1.3 direct_unsymmetric

NAME

direct_unsymmetric

SYNOPSIS

```
MODULE direct_unsymmetric
```

DESCRIPTION

Direct method module for unsymmetric complex matrix.

ARGUMENTS

lDU_Robin – factorized matrix structure
lDU_Dirichlet – factorized matrix structure

MODULES

USE factorized_matrix_struct

1.4 facet_struct**NAME**

facet_struct

SYNOPSIS

MODULE **facet_struct**

DESCRIPTION

Facet structure module.

ARGUMENTS

numb_facets – integer (= number of facets)
numb_quad – integer (= number of 4-node facets)
numb_tria – integer (= number of 3-node facets)
p_geometry – integer array (= pointer of facet connectivity per nodes)
geometry – integer array (= facet connectivity per nodes)
facet_id – integer array (= id of facet)
type_facet – integer array (= type of facet)
id_mat – integer array (= material associated with facet)
id_curve – integer array (= load curve associated with facet)
value – complex array (= average surface value)

1.5 factorized_matrix_struct**NAME**

factorized_matrix_struct

SYNOPSIS

MODULE **factorized_matrix_struct**

DESCRIPTION

Block tridiagonal sparse matrix structure.

ARGUMENTS

neq – integer (dimension of the matrix)
sparse_size – integer (total number of non zero entries in sparse structure)
nfront – integer (= number of fronts of the tridiagonal structure)
nfront_clamp – integer (= number of last clamped fronts i.e. clamped degrees of freedom)
low_sparse_size – integer (= total size for storage of lower diagonal blocks)
upp_sparse_size – integer (= total size for storage of upper diagonal blocks)
profile_size – integer (= total size for storage of half dense diagonal blocks)
maxdim – integer (= maximum dimension of diagonal blocks)
bc numb – integer
 p_row – integer array (= pointer of first entry of each row)
 p_diag – integer array (= pointer of first entry of each row in diagonal block)
 p_upp – integer array (= pointer of first entry of each row in upper block)
 p_ext – integer array (= pointer of first entry of each row in external block)
column numb – integer array (= column number of non zero entry in sparse structure)
 p_front – integer array (= pointer of fronts)
 new2old – integer array (= equation number correspondance)
 p_dia_bloc – integer array (= pointer of half dense diagonal blocks)
 bc mask – integer array
 coef – complex array (= sparse matrix coefficients)
 dia_blo – complex array (= half dense diagonal blocks)

1.6 **feti_data**

NAME

feti-data

SYNOPSIS

```
MODULE feti_data
```

DESCRIPTION

Data structures for complex FETI solver.

ARGUMENTS

```

subdom – mesh feti structure
Dirich – nodal list structure
interfine – interface descriptor structure
mesh_interfine – interface mesh structure
transp – sparse matrix structure
feti_rhs – complex array
feti_solution – complex array

```

MODULES

```

USE mesh_feti_struct
USE nodal_list_struct
USE interf_descriptor_struct
USE interf_mesh_struct
USE sparse_matrix_struct

```

1.7 **feti_param**

NAME

feti_param

SYNOPSIS

```
MODULE feti_param
```

DESCRIPTION

FETI parameters.

ARGUMENTS

```

typre – integer
feti_max_numb_it – integer
feti_numb_dir – integer
numb_restart – integer
feti_eps – real
eps_stagn – real

```

1.8 **interf_descriptor_struct**

NAME

interf_descriptor_struct

SYNOPSIS

```
MODULE interf_descriptor_struct
```

DESCRIPTION

Interface structure. The inner and outer data structures are for the case of non conforming grids or multi-level interface management. In case of conforming interfaces they are identical to the interface data structure.

ARGUMENTS

subdom numb – integer (= subdomain number)
numb_subdom – integer (= number of subdomains)
subdom_neq – integer (= number of equations in subdomain)
numb_neighb – integer (= number of neighbouring subdomains)
list_neighb – integer array (= list of neighbouring subdomains)
signe – integer array (= sign of interface)
interf_nodes – integer (= number of interface nodes in subdomain)
p_intf_nodes – integer array (= pointer of interface nodes)
list_intf_nodes – integer array (= list of interface nodes)
interf_neq – integer (= number of interface equations in subdomain)
p_intf_eq – integer array (= pointer of interface equations)
list_intf_eq – integer array (= list of interface equations)
weight – real array (= weighting factor)
weightd – real array (= weighting factor)
inn_interf_neq – integer (= number of inner interface equations)
p_list_inn – integer array (= pointer of inner interface equations)
list_inn – integer array (= list of inner interface equations)
buff_inn – complex array (= sending buffer of values for inner interface equations)
out_interf_neq – integer (= number of outer interface equations)
p_list_out – integer array (= pointer of outer interface equations)
list_out – integer array (= list of outer interface equations)
buff_out – complex array (= sending buffer of values for outer interface equations)
global_numb_elements – integer (= global number of element)
elem2dom – integer array (= global element to subdomain allocation array)
local_numb_elements – integer (= local number of element)
l2g_elem – integer array (= local to global element number correspondance)

1.9 interf_mesh_struct

NAME

interf_mesh_struct

SYNOPSIS

```
MODULE interf_mesh_struct
```

DESCRIPTION

Interface mesh structure. The inner and outer data structures are for the case of non conforming grids or multi-level interface management. In case of conforming interfaces they are identical to the interface data structure.

ARGUMENTS

- numb_nodes** – integer (= number of nodes)
- numb_neighb** – integer (= number of neighbouring subdomains)
- list_neighb** – integer array (= list of neighbouring subdomains)
- numb_elements** – integer (= number of elements)
- p_elem** – integer array (= pointer of interface elements)
- type_elem** – integer array
- elem_region** – integer array
- elem_signe** – integer array
- p_node_id** – integer array (= pointer of interface nodes)
- node_id** – integer array (= list of interface nodes)
- p_geometry** – integer array (= pointer of nodes in each element)
- geometry** – integer array (= list of nodes in each element)
- neq** – integer (= number of equations) – pointer of equations attached to each node + list
- eq_id** – integer array
- eq_neighb** – integer array
- p_node_eq** – integer array
- node_eq** – integer array
- type_dof** – integer array (= pointed list of types of dof)
- p_topology** – integer array (= pointer of interface equations)
- topology** – integer array (= list of interface equations)

1.10 load_curve_struct

NAME

load_curve_struct

SYNOPSIS

```
MODULE load_curve_struct
```

DESCRIPTION

Load curve structure.

ARGUMENTS

```

id_curve – integer
numb_points – integer
      var – real array
      factor – real array

```

1.11 mesh_feti_struct

NAME

mesh_feti_struct

SYNOPSIS

```
MODULE mesh_feti_struct
```

DESCRIPTION

Mesh structure.

ARGUMENTS

```

numb_elements – integer (= number of elements)
numb_nodes – integer (= number of nodes)
      neq – integer (= number of equations)
      p_node_eq – integer array (= pointer of node to equation correspondence)
      node_eq – integer array (= list of equations associated with each node)
      type_dof – integer array (= type of equations associated with each node)
l2g_elem – integer array (= local to global element number correspondence)
l2g_node – integer array (= local to global node number correspondence)

```

1.12 mesh_struct

NAME

mesh_struct

SYNOPSIS

```
MODULE mesh_struct
```

DESCRIPTION

Mesh structure.

ARGUMENTS

numb_connect – number of connected parts
numb_regions – number of elementary regions
numb_acou_regions – number of acoustic regions
numb_admit_regions – number of admittance regions
numb_infinite_regions – number of infinite regions
 numb_nodes – number of nodes
 space_dim – number of coordinates per node
 node_id – external node id
coordinates – coordinates of nodes
 tolerance – relative precision tolerance for coordinates
 min_nodid – minimum node id
 max_nodid – maximum node id
 rev_node_id – internal node id
numb_elements – number of elements
 numb_hexa – number of 8-node solid elements
 numb_tetra – number of 4-node solid elements
numb_admit_quad – number of 4-node admittance elements
numb_admit_quad – number of 3-node admittance elements
numb_infinite_quad – number of 4-node infinite elements
numb_infinite_tria – number of 3-node infinite elements
 geometry – pointed list of nodes in each element
 p_geometry – pointer to geometry array
rev_geometry – pointed list of elements each node belongs to
p_rev_geometry – pointer to rev_geometry array
 elem_id – id of element
 elem_region – internal id of region of element
elem_region_id – external id of region of element
neighb_region – internal id of neighboring region
 type_elem – type of element
 neq – number of equations
 node_eq – pointed list of equations attached to each node
 type_dof – pointed list of types of dof attached to each node
p_node_eq – pointer to node_eq and type_dof arrays
 topology – pointed list of equations in each element
p_topology – pointer of element connectivity per equations
primal_field – acoustic pressure
 dual_field – normal velocity

1.13 **model**

NAME

model

SYNOPSIS

```
MODULE model
```

DESCRIPTION

Data structures used for model.

ARGUMENTS

see module

MODULES

```
USE mesh_struct
USE nodal_list_struct
USE facet_struct
USE sparse_matrix_struct
USE load_curve_struct
USE region_property_struct
```

1.14 mpif**NAME**

mpif

SYNOPSIS

```
SUBROUTINE mpif
```

DESCRIPTION

FETI communicator declaration and mpif as a module

ARGUMENTS

```
max_count - parameter integer
FETI_COM - integer
COUPLE_COM - integer INCLUDES INCLUDE 'mpif.h'
```

1.15 nodal_list_struct**NAME**

nodal_list_struct

SYNOPSIS

```
MODULE nodal_list_struct
```

DESCRIPTION

Nodal list structure.

ARGUMENTS

- neq** – integer (= dimension of problem)
- numb** – integer (= number of entries in the list)
- list_id** – integer (= external id of the list)
- type_list** – integer (= type of the list)
- node_id** – integer array (= list of nodes)
- type_dof** – integer array (= type of dof for each entry)
- value** – complex array (= values)
- id_curve** – integer array (= curve number associated to each entry)
- id_mat** – integer array (= material number)
- eq_id** – integer array (= list of listed equations)
- mask** – integer array (= mask array equal zero if not a listed equation)

1.16 `outfil`**NAME**

outfil

SYNOPSIS

```
MODULE outfil
```

DESCRIPTION

Output unit structure.

ARGUMENTS

- P6** – integer (= output unit)
- print_matrix** – integer
 - print_rhs** – integer
- print_solution** – integer
- print_mesh** – integer

1.17 `realloc`**NAME**

realloc

SYNOPSIS

```
MODULE realloc
```

DESCRIPTION

Functions for memory allocation.

ARGUMENTS

```
SUBROUTINE realloc_i1
SUBROUTINE extent_i1
SUBROUTINE realloc_r1
SUBROUTINE realloc_c1
SUBROUTINE realloc_i2
SUBROUTINE realloc_r2
SUBROUTINE extent_r2
SUBROUTINE realloc_c2
```

1.18 region_property_struct

NAME

region_property_struct

SYNOPSIS

```
MODULE region_property_struct
```

DESCRIPTION

Module of acoustic, admittance and infinite element material.

ARGUMENTS

density	- real
id_curve_density	- integer
celerity	- complex
id_curve_celerity	- integer
impedance	- complex
id_curve_impedance	- integer
origin	- real array
axes	- real array
adist	- real
bdist	- real
cdist	- real
order	- integer
tolerance	- real

1.19 solver_param

NAME

solver-param

SYNOPSIS

```
MODULE solver_param
```

DESCRIPTION

Solver parameters module.

ARGUMENTS

```

type_galerkin – integer
symmetric_matrix – integer
    type_solver – integer
    type_precond – integer
    max_numb_it – integer
        numb_dir – integer
    out_of_core – integer
    type_opt – integer
        nsd – integer
        epsilon – real
    numb_freq – integer
    frequency – real array

```

1.20 sparse_matrix_struct**NAME**

sparse_matrix_struct

SYNOPSIS

```
MODULE sparse_matrix_struct
```

DESCRIPTION

Sparse matrix structure.

ARGUMENTS

```

neq – integer (= dimension of the matrix)
sparse_size – integer (= total number of non zero entries)
    p_row – integer array (= position of first entry of each row)
    column_numb – integer array (= column number of each non zero entry)
        coef – complex array (= non zero entries)
    symmetric – integer (= symmetric matrix flag)

```

2 Functions

2.1 add_interf_matrix

NAME

add_interf_matrix

SYNOPSIS

```
SUBROUTINE add_interf_matrix
```

DESCRIPTION

Add interface sparse matrix to impedance sparse matrix.

ARGUMENTS

None

MODULES

USE model
USE feti_data
USE solver_param
USE outfil
USE direct_unsymmetric

2.2 add_interf_matrix_structure

NAME

add_interf_matrix_structure

SYNOPSIS

```
SUBROUTINE add_interf_matrix_structure
```

DESCRIPTION

Add interface sparse matrix data structure.

ARGUMENTS

None

MODULES

USE model
USE feti_data

2.3 add_sparse_sym_matrix

NAME

add_sparse_sym_matrix

SYNOPSIS

```
SUBROUTINE add_sparse_sym_matrix (a,b,b2a_eqid)
```

DESCRIPTION

Add symmetric interface sparse matrix to impedance matrix.

ARGUMENTS

- a** – sparse matrix structure
- b** – sparse matrix structure
- b2a_eqid** – integer array

MODULES

- USE outfil
- USE realloc
- USE sparse_matrix_struct

2.4 add_sparse_sym_struct

NAME

add_sparse_sym_struct

SYNOPSIS

```
SUBROUTINE add_sparse_sym_struct (a,b,b2a_eqid)
```

DESCRIPTION

Add symmetric interface sparse matrix structure.

ARGUMENTS

- a** – sparse matrix structure
- b** – sparse matrix structure
- b2a_eqid** – integer array

MODULES

- USE outfil
- USE realloc
- USE sparse_matrix_struct

2.5 add_sparse_unsym_matrix

NAME

add_sparse_unsym_matrix

SYNOPSIS

```
SUBROUTINE add_sparse_unsym_matrix (a,b,b2a_eqid)
```

DESCRIPTION

Add unsymmetric interface sparse matrix to impedance matrix.

ARGUMENTS

- a** – sparse matrix structure
- b** – sparse matrix structure
- b2a_eqid** – integer array

MODULES

- USE outfil
- USE realloc
- USE sparse_matrix_struct

2.6 add_sparse_unsym_struct

NAME

add_sparse_unsym_struct

SYNOPSIS

```
SUBROUTINE add_sparse_unsym_struct (a,b,b2a_eqid)
```

DESCRIPTION

Add unsymmetric interface sparse matrix structure.

ARGUMENTS

- a** – sparse matrix structure
- b** – sparse matrix structure
- b2a_eqid** – integer array

MODULES

- USE outfil
- USE realloc
- USE sparse_matrix_struct

2.7 assemble_bc

NAME

assemble_bc

SYNOPSIS

```
SUBROUTINE assemble_bc (dom,acou_mat,dim_neumann,Neumann,
& dim_fneumann,FNeumann,rhs,frequency,dim_lc,&
& LC)
```

DESCRIPTION

Assemble right hand side.

ARGUMENTS

dom	- mesh structure
acout_mat	- region property structure array
dim_neumann	- integer
Neumann	- nodal list structure array
dim_fneumann	- integer
FNeumann	- facet structure array
rhs	- complex array
frequency	- real
dim_lc	- integer
LC	- load curve structure array

MODULES

```
USE mesh_struct
USE nodal_list_struct
USE facet_struct
USE region_property_struct
USE load_curve_struct
USE outfil
```

2.8 assemble_facet_bc

NAME

assemble_facet_bc

SYNOPSIS

```
SUBROUTINE assemble_facet_bc (dom,acou_mat,FNeumann,rhs,frequency,&
& dim_lc,LC)
```

DESCRIPTION

Assemble contribution of facet Neumann boundary conditions to right hand side.

ARGUMENTS

dom – mesh structure
acou_mat – region property structure array
FNeumann – facet structure
rhs – complex array
frequency – real
dim_lc – integer
LC – load curve structure array

MODULES

USE mesh_struct
 USE facet_struct
 USE region_property_struct
 USE load_curve_struct
 USE outfil

2.9 assemble_impedance

NAME

assemble_impedance

SYNOPSIS

```
SUBROUTINE assemble_impedance (dom,a,frequency,acou_mat,admi_mat, &
& inf_mat,typegalerkin)
```

DESCRIPTION

Assemble impedance sparse matrix on domain.

ARGUMENTS

dom – mesh structure
a – sparse matrix structure
frequency – real
acou_mat – region property structure array
admi_mat – region property structure array
inf_mat – region property structure array
typegalerkin – integer

MODULES

USE sparse_matrix_struct
 USE mesh_struct
 USE region_property_struct
 USE outfil

2.10 assemble_interf_matrix

NAME

assemble_interf_matrix

SYNOPSIS

```
SUBROUTINE assemble_interf_matrix (dom, mesh_intf, b, frequency,      &
&                                acou_mat, type_sol, subdom_numb)
```

DESCRIPTION

Assemble interface sparse matrix

ARGUMENTS

dom	- mesh structure
mesh_intf	- interface mesh structure
b	- sparse matrix structure
frequency	- real
acou_mat	- region property structure array
type_sol	- integer
subdom_numb	- integer

MODULES

```
USE sparse_matrix_struct
USE interf_mesh_struct
USE mesh_struct
USE region_property_struct
USE outfil
```

WARNINGS

The alpha and beta parameters are the parameters used in the continuous relation $(\alpha u + \beta \partial^2 \tau u)$ which gives after discretization $(\alpha M - \beta K)$.

2.11 **assemble_nodal_bc**

NAME

assemble_nodal_bc

SYNOPSIS

```
SUBROUTINE assemble_nodal_bc (dom, acou_mat, Neumann, rhs, frequency,  &
&                            dim_lc, LC)
```

DESCRIPTION

Assemble contribution of nodal Neumann boundary conditions to right hand side.

ARGUMENTS

dom – mesh structure
acou_mat – region property structure array
Neumann – nodal list structure
rhs – complex array
frequency – real
dim_lc – integer
lc – load curve structure array

MODULES

USE mesh_struct
 USE nodal_list_struct
 USE region_property_struct
 USE load_curve_struct
 USE outfil

2.12 bcast_acoustic_property

NAME

bcast_acoustic_property

SYNOPSIS

SUBROUTINE **bcast_acoustic_property** (**mat**)

DESCRIPTION

Broadcast acoustic region property to all processes.

ARGUMENTS

mat – region property structure

MODULES

USE region_property_struct
 USE mpif

2.13 bcast_admittance_property

NAME

bcast_admittance_property

SYNOPSIS

SUBROUTINE **bcast_admittance_property** (**mat**)

DESCRIPTION

Broadcast admittance region property to all processes.

ARGUMENTS

mat – region property structure

MODULES

USE region_property_struct
USE mpif

2.14 bcast_facet

NAME

bcast_facet

SYNOPSIS

```
SUBROUTINE bcast_facet (bc,intf)
```

DESCRIPTION

Broadcast facet list to all processes and extract.

ARGUMENTS

bc – facet structure
intf – interface descriptor structure

MODULES

USE facet_struct
USE interf_descriptor_struct
USE outfil
USE mpif

2.15 bcast_infinite_property

NAME

bcast_infinite_property

SYNOPSIS

```
SUBROUTINE bcast_infinite_property (mat)
```

DESCRIPTION

Broadcast infinite element region property to all processes.

ARGUMENTS

mat – region property structure

MODULES

USE region_property_struct
USE mpif

2.16 bcast_load_curve

NAME

bcast_load_curve

SYNOPSIS

```
SUBROUTINE bcast_load_curve (lc)
```

DESCRIPTION

Broadcast load curve to all processes.

ARGUMENTS

lc – load curve structure

MODULES

USE load_curve_struct
USE outfil
USE mpif

2.17 bcast_model_attribute

NAME

bcast_model_attribute

SYNOPSIS

```
SUBROUTINE bcast_model_attribute (attribute)
```

DESCRIPTION

Broadcast model attribute to all processes.

ARGUMENTS

attribute – character string

MODULES

USE mpif

2.18 bcast_model_parameters

NAME

bcast_model_parameters

SYNOPSIS

```
SUBROUTINE bcast_model_parameters (n1,n2,n3,n4,n5)
```

DESCRIPTION

Broadcast model parameters to all processes.

ARGUMENTS

- n1** – integer
- n2** – integer
- n3** – integer
- n4** – integer
- n5** – integer

MODULES

```
USE solver_param
USE outfil
USE mpif
```

2.19 bcast_nodal_list

NAME

bcast_nodal_list

SYNOPSIS

```
SUBROUTINE bcast_nodal_list (bc,intf,opt)
```

DESCRIPTION

Broadcast nodal list to all processes and extract.

ARGUMENTS

- bc** – nodal list structure
- intf** – interface descriptor structure
- opt** – integer

MODULES

```
USE nodal_list_struct
USE interf_descriptor_struct
USE outfil
USE mpif
```

2.20 bcast_solver_parameters

NAME

bcast_solver_parameters

SYNOPSIS

```
SUBROUTINE bcast_solver_parameters
```

DESCRIPTION

Broadcast solver parameters to all processes.

ARGUMENTS

None

MODULES

USE solver_param
 USE block_size
 USE outfil
 USE mpif

2.21 build_diag

NAME

build_diag

SYNOPSIS

```
SUBROUTINE build_diag (neq,dim,p_row,column numb,coef,diag)
```

DESCRIPTION

Define diagonal coefficients of sparse matrix

ARGUMENTS

neq – integer
dim – integer
p_row – integer array
column numb – integer array
coef – complex array
diag – complex array

MODULES

USE outfil

2.22 build_dirich_aug

NAME

build_dirich_aug

SYNOPSIS

```
SUBROUTINE build_dirich_aug (intf_mesh,Dirichlet,Dirich_aug,      &
                           &                                listintf)
```

DESCRIPTION

Compute Schur complement matrix.

ARGUMENTS

- intf_mesh** – interface mesh structure
- Dirichlet** – factorized matrix structure
- Dirich_aug** – factorized matrix structure
- listintf** – nodal list structure

MODULES

```
USE solver_param
USE outfil
USE interf_mesh_struct
USE nodal_list_struct
USE realloc
USE factorized_matrix_struct
```

2.23 build_interf_matrix_structure

NAME

build_interf_matrix_structure

SYNOPSIS

```
SUBROUTINE build_interf_matrix_structure
```

DESCRIPTION

Build interface sparse matrix data structure.

ARGUMENTS

None

MODULES

USE model
USE feti_data
USE solver_param
USE outfil

2.24 build_interface**NAME**

build_interface

SYNOPSIS

SUBROUTINE build_interface

DESCRIPTION

Build subdomain interface.

ARGUMENTS

None

MODULES

USE outfil
USE mpif
USE feti_data
USE model
USE feti_param

2.25 build_matrix_structure**NAME**

build_matrix_structure

SYNOPSIS

SUBROUTINE build_matrix_structure

DESCRIPTION

Build sparse matrix data structure.

ARGUMENTS

None

MODULES

USE model
USE solver_param

2.26 build_node_eq

NAME

build_node_eq

SYNOPSIS

```
SUBROUTINE build_node_eq (dom,inf_mat)
```

DESCRIPTION

Build correspondance between nodes and equations.

ARGUMENTS

dom – mesh structure
inf_mat – region property structure array

MODULES

USE mesh_struct
USE region_property_struct
USE realloc
USE outfil

2.27 build_rev_geometry

NAME

build_rev_geometry

SYNOPSIS

```
SUBROUTINE build_rev_geometry (dom)
```

DESCRIPTION

Build pointed list of elements each node belongs to.

ARGUMENTS

dom – mesh structure

MODULES

USE outfil
USE realloc
USE mesh_struct

2.28 build_rev_nodid

NAME

build_rev_nodid

SYNOPSIS

```
SUBROUTINE build_rev_nodid (dom)
```

DESCRIPTION

Build external to internal node number correspondance and change list of nodes in each element accordingly.

ARGUMENTS

dom – mesh structure

MODULES

USE outfil
USE mesh_struct

2.29 build_sparse_sym_struct

NAME

build_sparse_sym_struct

SYNOPSIS

```
SUBROUTINE build_sparse_sym_struct (dom,a)
```

DESCRIPTION

Build sparse matrix structure.

ARGUMENTS

dom – mesh structure
a – sparse matrix structure

MODULES

USE outfil
USE realloc
USE mesh_struct
USE sparse_matrix_struct

2.30 build_sparse_unsym_struct

NAME

build_sparse_unsym_struct

SYNOPSIS

```
SUBROUTINE build_sparse_unsym_struct (dom,a)
```

DESCRIPTION

Build sparse matrix structure.

ARGUMENTS

dom – mesh structure
a – sparse matrix structure

MODULES

USE outfil
 USE realloc
 USE mesh_struct
 USE sparse_matrix_struct

2.31 build_topology

NAME

build_topology

SYNOPSIS

```
SUBROUTINE build_topology (dom)
```

DESCRIPTION

Build list of equations in each element, i.e. .build topology of elements using list of nodes per element and list and type of equations per node.

ARGUMENTS

dom – mesh structure

MODULES

USE mesh_struct
 USE outfil
 USE realloc

2.32 calpd

NAME

calpd

SYNOPSIS

```
SUBROUTINE calpd (pl,pc,pd,n,nza)
```

DESCRIPTION

Determine the cpd pointer which point to the address inside a of the diagonal coefficient of the matrix. The matrix has a general structure.

ARGUMENTS

- pl** – integer array
- pc** – integer array
- pd** – integer array
- n** – integer
- nza** – integer

2.33 cmk_number

NAME

cmk_number

SYNOPSIS

```
SUBROUTINE cmk_number (nodes,p_graph,graph,list)
```

DESCRIPTION

Renumber graph via reverse Cuthill-Mac Kee algorithm.

ARGUMENTS

- nodes** – integer
- p_graph** – integer array
- graph** – integer array
- list** – integer array

MODULES

USE outfil

2.34 condens_1

NAME

condens_1

SYNOPSIS

```
SUBROUTINE condens_1 (lda,dim1,dim2,a,d,e,f,ie0,if0,nop)
```

DESCRIPTION

Compute the Schur complement matrix $[D^{-1}U^{-t}F]^t$ with LDU the Gauss-Jordan factorisation of the matrix A .

ARGUMENTS

- lda** – integer
- dim1** – integer
- dim2** – integer
 - a** – complex array
 - d** – complex array
 - e** – complex array
 - f** – complex array
 - ie0** – integer array
 - if0** – integer array
 - nop** – real

MODULES

```
USE block_size
```

2.35 condens_2

NAME

condens_2

SYNOPSIS

```
SUBROUTINE condens_2 (lda,dim1,dim2,a,e,ie0,nop)
```

DESCRIPTION

Compute $[L^{-1}E]$ matrix where LDU is the Gauss-Jordan factorisation of the matrix A .

ARGUMENTS

- lda** – integer
- dim1** – integer
- dim2** – integer
 - a** – complex array
 - e** – complex array
 - ie0** – integer array
 - nop** – real

MODULES

```
USE block_size
```

2.36 condens_3

NAME

condens_3

SYNOPSIS

```
SUBROUTINE condens_3 (lda, dim1, dim2, e, f, c, ie0, if0, nop)
```

DESCRIPTION

Compute the Schur complement matrix $C = C - [FU^{-1}d^{-1}][L^{-1}E]$ where $[L^{-1}E]$ and $[FU^{-1}d^{-1}]$ have already been computed.

ARGUMENTS

lda	- integer
dim1	- integer
dim2	- integer
e	- complex array
f	- complex array
c	- complex array
ie0	- integer array
if0	- integer array
nop	- real

MODULES

USE block_size

2.37 copy_block

NAME

copy_block

SYNOPSIS

```
SUBROUTINE copy_block (lda, dim1, dim2, a, b)
```

DESCRIPTION

Copy one block of a matrix.

ARGUMENTS

lda	- integer
dim1	- integer
dim2	- integer
a	- complex array
b	- complex array

MODULES

USE outfil

2.38 dirichlet_bc

NAME

dirichlet_bc

SYNOPSIS

```
SUBROUTINE dirichlet_bc (frequency,dim_lc,lc,bc)
```

DESCRIPTION

Build Interpolate Dirichlet boundary condition.

ARGUMENTS

frequency – real
dim_lc – integer
 lc – load curve structure array
 bc – nodal list structure

MODULES

USE load_curve_struct
USE nodal_list_struct
USE outfil

2.39 distribute_model

NAME

distribute_model

SYNOPSIS

```
SUBROUTINE distribute_model
```

DESCRIPTION

Distribute domain decomposed model.

ARGUMENTS

None

MODULES

USE model
USE feti_data
USE outfil

2.40 echo_facet

NAME

echo_facet

SYNOPSIS

```
SUBROUTINE echo_facet (P6,bc)
```

DESCRIPTION

Print facets data structure.

ARGUMENTS

P6 – integer (= output unit)
bc – facet structure

MODULES

USE facet_struct

2.41 echo_mesh

NAME

echo_mesh

SYNOPSIS

```
SUBROUTINE echo_mesh (P6,dom,subdom_numb)
```

DESCRIPTION

Print mesh data structure.

ARGUMENTS

P6 – integer (output unit)
dom – mesh structure
subdom_numb – integer

MODULES

USE mesh_struct

2.42 echo_mesh_femview

NAME

echo_mesh_femview

SYNOPSIS

```
SUBROUTINE echo_mesh_femview (dom,subdom numb, numb_subdom, elem2dom,&
& title, directory)
```

DESCRIPTION

Write mesh geometrical data in a FEMVIEW file.

ARGUMENTS

dom – mesh structure subdom_numb – integer numb_subdom – integer elem2dom – integer array title – character string directory – character string
--

MODULES

USE mesh_struct

2.43 echo_model

NAME

echo_model

SYNOPSIS

```
SUBROUTINE echo_model (subdom_numb, numb_subdom)
```

DESCRIPTION

Print all model data structures.

ARGUMENTS

subdom_numb – integer numb_subdom – integer
--

MODULES

USE model
USE outfil

2.44 echo_nodal_list

NAME

echo_nodal_list

SYNOPSIS

```
SUBROUTINE echo_nodal_list (P6,bc)
```

DESCRIPTION

Print nodal list structure.

ARGUMENTS

P6 – integer (= output unit)
bc – nodal list structure

MODULES

USE nodal_list_struct

2.45 equation_setup**NAME**

equation-setup

SYNOPSIS

```
SUBROUTINE equation_setup
```

DESCRIPTION

Setup system of equations associated with model.

ARGUMENTS

None

MODULES

USE model
 USE solver_param
 USE outfil

2.46 extent_i1**NAME**

extent_i1

SYNOPSIS

```
SUBROUTINE extent_i1 (tab,inc_dim1,ierr)
```

DESCRIPTION

Extension of multi-dimensional integer pointer.

ARGUMENTS

tab – integer array
inc_dim1 – integer
ierr – integer

2.47 extent_r2

NAME

extent_r2

SYNOPSIS

```
SUBROUTINE extent_r2 (tab,dim1,inc_dim2,ierr)
```

DESCRIPTION

Extension of multi-dimensional real pointer.

ARGUMENTS

tab – real array
dim1 – integer
inc_dim2 – integer
ierr – integer

2.48 extract_submesh

NAME

extract_submesh

SYNOPSIS

```
SUBROUTINE extract_submesh (dom,intf,target_subdom)
```

DESCRIPTION

Extract subdomain submesh and send it to associated process. Build topology of elements using list of nodes per element and list and type of equations per node.

ARGUMENTS

dom – mesh structure
intf – interface descriptor structure
target_subdom – integer

MODULES

```
USE mesh_struct
USE interf_descriptor_struct
USE outfil
USE mpif
USE realloc
```

2.49 facet_rhs

NAME

facet_rhs

SYNOPSIS

```
SUBROUTINE facet_rhs (dom,bc)
```

DESCRIPTION

Compute specific values for non homogeneous Robin conditions. P1 discretization is used at the nodes of facets.

ARGUMENTS

dom – mesh structure
bc – facet structure

MODULES

```
USE mesh_struct
USE facet_struct
USE outfil
```

2.50 factorize_numeric

NAME

factorize_numeric

SYNOPSIS

```
SUBROUTINE factorize_numeric
```

DESCRIPTION

Numerical factorization of local matrices.

ARGUMENTS

None

MODULES

USE outfil
USE solver_param

2.51 factorize_symbolic

NAME

factorize_symbolic

SYNOPSIS

SUBROUTINE **factorize_symbolic**

DESCRIPTION

Symbolic factorization of local matrices.

ARGUMENTS

None

MODULES

USE outfil
USE solver_param

2.52 feti_abort

NAME

feti_abort

SYNOPSIS

SUBROUTINE **feti_abort**

DESCRIPTION

Abort FETI.

ARGUMENTS

None

MODULES

USE mpif
USE outfil

2.53 feti_finalize

NAME

feti_finalize

SYNOPSIS

SUBROUTINE feti_finalize

DESCRIPTION

Close FETI communication space and output file.

ARGUMENTS

None

MODULES

USE mpif
USE outfil**2.54 feti_init**

NAME

feti_init

SYNOPSIS

SUBROUTINE feti_init (subdom_numb, numb_subdom)

DESCRIPTION

Create FETI communication space, get subdomain number and number of subdomains and open output file.

ARGUMENTS

subdom_numb – integer
numb_subdom – integer

MODULES

USE model
USE outfil
USE mpif
USE feti_data
USE feti_param

2.55 fill_sym_sparse

NAME

fill_sym_sparse

SYNOPSIS

```
SUBROUTINE fill_sym_sparse (neq,sparse_size,rowp,col,inicoef,      &
&                           new2old,p_row,col_numb,coef)
```

DESCRIPTION

Filling of renumbered lower triangular part of the symmetric sparse structure stored row by row from the upper triangular symmetric one.

ARGUMENTS

- rowp** – pointer of rows of the upper triangular part of the initial matrix
- col** – list of column indices of rows of the initial matrix
- inicoef** – list of entries of the initial matrix
- new2old** – new to old correspondance
- p_row** – pointer of rows of the lower triangular part of the symmetric matrix
- col_numb** – list of column indices of rows of the renumbered matrix
- coef** – list of entries of the renumbered matrix

MODULES

USE outfil

2.56 fill_unsym_sparse

NAME

fill_unsym_sparse

SYNOPSIS

```
SUBROUTINE fill_unsym_sparse(neq,sparse_size,rowp,col,inicoef,      &
&                           new2old,p_row,col_numb,coef)
```

DESCRIPTION

Filling of renumbered unsymmetric sparse structure stored by row

ARGUMENTS

rowp – pointer of rows of the initial matrix
col – list of column indices of rows of the initial matrix
inicoef – list of entries of the initial matrix
new2old – new to old correspondance
p_row – pointer of rows of the renumbered matrix
col_numb – list of column indices of rows of the renumbered matrix
coef – list of entries of the renumbered matrix

MODULES

USE outfil

2.57 frontal_numb

NAME

frontal_numb

SYNOPSIS

```
SUBROUTINE frontal_numb (nodes,p_graph,graph,i0,list,profile,indic,&
& connect)
```

DESCRIPTION

Frontal renumbering of graph.

ARGUMENTS

nodes – integer
p-graph – integer array
graph – integer array
i0 – integer
list – integer array
profile – real
indic – integer array
connect – integer array

2.58 full_schur_b

NAME

full_schur_b

SYNOPSIS

```
SUBROUTINE full_schur_b (lda,nrow,ncol,u,l,s,n2)
```

DESCRIPTION

Compute Schur complement: $S = A - LU$ using a block algorithm.

ARGUMENTS

lda – integer (= dimension of matrix A)
nrow – integer
ncol – integer
u(nrow,ncol) – complex array (= the upper band)
l(ncol,nrow) – complex array (= the lower band)
s(ncol,ncol) – complex array (= the Schur complement)
n2 – integer

2.59 full_blo

NAME

full_blo

SYNOPSIS

```
SUBROUTINE full_blo (lda,n,a,full_a)
```

DESCRIPTION

Store a dense diagonal block.

ARGUMENTS

lda – integer
n – integer
a – complex array
full_a – complex array

2.60 full_fwbw

NAME

full_fwbw

SYNOPSIS

```
SUBROUTINE full_fwbw (n,a,y,x)
```

DESCRIPTION

Compute dense matrix forward-backward substitution for a dense unsymmetric complex matrix.

ARGUMENTS

n – integer
a – complex array
y – complex array
x – complex array

2.61 full_ldlt

NAME

full_ldlt

SYNOPSIS

`SUBROUTINE full_ldlt (lda,n,a,d)`

DESCRIPTION

Compute symmetric Gauss Jordan factorization of dense matrix. The lower triangular part only is computed.

ARGUMENTS

- lda** – integer
- n** – integer
- a** – complex array
- d** – complex array

MODULES

`USE block_size`**2.62 full_ldlt_b**

NAME

full_ldlt_b

SYNOPSIS

`SUBROUTINE full_ldlt_b (lda,n,a,d)`

DESCRIPTION

Compute symmetric Gauss Jordan factorization of symmetric dense matrix.

ARGUMENTS

- lda** – integer
- n** – integer
- a** – complex array
- d** – complex array

2.63 full_ldu

NAME

full_ldu

SYNOPSIS

```
SUBROUTINE full_ldu (lda,n,a,d)
```

DESCRIPTION

Compute Gauss-Jordan factorization of dense matrix.

ARGUMENTS

- lda** – integer
- n** – integer
- a** – complex array
- d** – complex array

MODULES

USE block_size

2.64 full_ldu_b

NAME

full_ldu_b

SYNOPSIS

```
SUBROUTINE full_ldu_b (lda,n,a,d)
```

DESCRIPTION

Compute Gauss-Jordan factorization of dense matrix.

ARGUMENTS

- lda** – integer
- n** – integer
- a** – complex array
- d** – complex array

MODULES

USE block_size

2.65 full_schur_b_sparse

NAME

full_schur_b_sparse

SYNOPSIS

```
SUBROUTINE full_schur_b_sparse (nrow,ncol,iu0,u,j10,l,s,lda,n1,n2)
```

DESCRIPTION

Compute Schur complement: $S = A - LU$ using a block algorithm.

ARGUMENTS

nrow	- integer
ncol	- integer
iu0	- integer
	u - complex array
	jl0 - integer array
	l - complex array
	s - complex array
lda	- integer
n1	- integer
n2	- integer

2.66 full_sto

NAME

full_sto

SYNOPSIS

```
SUBROUTINE full_sto (lda,n,mat,nblo)
```

DESCRIPTION

Store a full block.

ARGUMENTS

lda	- integer
n	- integer
mat	- complex array
nblo	- integer

2.67 full_unsto

NAME

full_unsto

SYNOPSIS

```
SUBROUTINE full_unsto (n,mat,nblo)
```

DESCRIPTION

Un-store a dense block.

ARGUMENTS

n – integer
mat – complex array
nblo – integer

2.68 galerkin_error

NAME

galerkin_error

SYNOPSIS

```
SUBROUTINE galerkin_error (subdom_numb,frequency)
```

DESCRIPTION

Compute the finite element error analysis.

ARGUMENTS

subdom_numb – integer
frequency – real

MODULES

USE model
 USE outfil
 USE realloc
 USE feti_data
 USE feti_param
 USE mpif

2.69 galerkin_meshsize

NAME

galerkin_meshsize

SYNOPSIS

```
SUBROUTINE galerkin_meshsize (dom,x,h)
```

DESCRIPTION

Compute the Galerkin meshsize-value.

ARGUMENTS

dom – mesh structure
x – real (= hexaedrom nodes coordinates)
h – real (= mesh size)

MODULES

```
USE mesh_struct
USE outfil
```

2.70 galerkin_tau

NAME

galerkin_tau

SYNOPSIS

```
SUBROUTINE galerkin_tau (k,h,tau)
```

DESCRIPTION

Compute Galerkin tau-value.

ARGUMENTS

k – real (= wavenumber of the Helmholtz equation)
h – real (= mesh size)
tau – real (= tau_{k2}-GLS or tau_{k4}-GGLS coefficient)

MODULES

```
USE outfil
```

2.71 gather_nodid

NAME

gather_nodid

SYNOPSIS

```
SUBROUTINE gather_nodid (numb_nodes,l2g_node,node_id,
&                      glob_numb_nodes,glob_node_id)           &
```

DESCRIPTION

Gather subdomain node ids.

ARGUMENTS

numb_nodes – integer
l2g_node – integer array
node_id – integer array
glob_numb_nodes – integer
glob_node_id – integer array

2.72 gather_sol

NAME

gather_sol

SYNOPSIS

```
SUBROUTINE gather_sol (numb_nodes,12g_node,p_node_eq,type_dof,
&                      node_eq,min_dof,max_dof,glob numb_nodes,dof,&
&                      neq,v,glob neq,glob v)
```

DESCRIPTION

Gather subdomain solutions.

ARGUMENTS

numb_nodes	- integer
12g_node	- integer array
p_node_eq	- integer array
type_dof	- integer array
node_eq	- integer array
min_dof	- integer
max_dof	- integer
glob numb_nodes	- integer
	dof - integer array
	neq - integer
	v - complex array
glob neq	- integer
	glob v - complex array

2.73 global_eq_mask

NAME

global_eq_mask

SYNOPSIS

```
SUBROUTINE global_eq_mask(numb_nodes,12g_node,p_node_eq,type_dof, &
&                         min_dof,max_dof,glob numb_nodes,dof)
```

DESCRIPTION

Build mask of equations in subdomain.

ARGUMENTS

```

numb_nodes – integer
l2g_node – integer array
p_node_eq – integer array
type_dof – integer array
min_dof – integer
max_dof – integer
glob_numb_nodes – integer
dof – integer array

```

2.74 global_solution

NAME

global_solution

SYNOPSIS

```
SUBROUTINE global_solution (intf,dom,glob_dom,v,glob_v)
```

DESCRIPTION

Gather global mesh and solution field.

ARGUMENTS

```

intf – interface descriptor structure
dom – mesh structure
glob_dom – mesh structure
v – complex array
glob_v – complex array

```

MODULES

```

USE mesh_struct
USE interf_descriptor_struct
USE outfil
USE mpif
USE realloc

```

2.75 globaldotproduct

NAME

globaldotproduct

SYNOPSIS

```
SUBROUTINE globaldotproduct (uv,u,v,intf)
```

DESCRIPTION

Global dot-product.

ARGUMENTS

uv – complex
u – complex array
v – complex array
intf – interface descriptor structure

MODULES

USE mpif
USE interf_descriptor_struct
USE outfil

2.76 globalsum**NAME**

globalsum

SYNOPSIS

SUBROUTINE **globalsum** (buf,n)

DESCRIPTION

Sum the vector buf(n) accross the network.

ARGUMENTS

buff – real array
n – integer

MODULES

USE mpif

2.77 globalsumc**NAME**

globalsumc

SYNOPSIS

SUBROUTINE **globalsumc** (buf,n)

DESCRIPTION

Sum the vector buf(n) accross the network.

ARGUMENTS

buff – complex array
n – integer

MODULES

USE mpif
 USE outfil

2.78 globalsumi

NAME

globalsumi

SYNOPSIS

```
SUBROUTINE globalsumi (buf,n)
```

DESCRIPTION

Sum the vector buf(n) accross the network.

ARGUMENTS

buf – integer array
n – integer

MODULES

USE mpif

2.79 half_schur_b

NAME

half_schur_b

SYNOPSIS

```
SUBROUTINE half_schur_b (lda,nrow,ncol,u,l,s,n2)
```

DESCRIPTION

Compute upper triangular part of Schur complement matrix $S = A - LU$ using a block algorithm.

ARGUMENTS

lda – integer
nrow – integer
ncol – integer
u – complex array
l – complex array
s – complex array
n2 – integer

2.80 **half_blo**

NAME

half_blo

SYNOPSIS

```
SUBROUTINE half_blo (lda,n,a,half_a)
```

DESCRIPTION

Store the lower triangular part of matrix A row by row.

ARGUMENTS

lda – integer
n – integer
a – complex array
half_a – complex array

2.81 **half_fwbw**

NAME

half_fwbw

SYNOPSIS

```
SUBROUTINE half_fwbw (n,a,y,x)
```

DESCRIPTION

Compute dense matrix forward-backward substitution in the case of only the upper triangular part of symmetric matrix A is stored column by column.

ARGUMENTS

n – integer
a – complex array
y – complex array
x – complex array

2.82 half_mm_b

NAME

half_mm_b

SYNOPSIS

```
SUBROUTINE half_mm_b (ncol,nrow,l,ldl,u,ldu,s,lds)
```

DESCRIPTION

Compute upper triangular part of Schur complement matrix $S = A - LU$.

ARGUMENTS

ncol	– integer
nrow	– integer
l(ncol,nrow)	– complex array (= the lower band)
ldl	– integer
u(nrow,ncol)	– complex array (= the upper band)
ldu	– integer
s(ncol,ncol)	– complex array (= the Schur complement)
lds	– integer (= the dimension of matrix A)

2.83 half_schur_b_sparse

NAME

half_schur_b_sparse

SYNOPSIS

```
SUBROUTINE half_schur_b_sparse (nrow,ncol,i0,u,l,s,lda,n1,n2)
```

DESCRIPTION

Compute upper triangular part of Schur complement matrix $S = A - LU$ using a block algorithm.

ARGUMENTS

nrow	– integer
ncol	– integer
i0(ncol)	– integer array (= the position of the last non zero entry in columns of u and rows of l)
u(nrow,ncol)	– complex array (= the upper band)
l(ncol,nrow)	– complex array (= the lower band)
s(lda,ncol)	– complex array (= the Schur complement)
lda	– integer
n1	– integer
n2	– integer

2.84 half_sto

NAME

half_sto

SYNOPSIS

```
SUBROUTINE half_sto (lda,n,mat,nblo)
```

DESCRIPTION

Store the lower triangular part of matrix A row by row.

ARGUMENTS

lda – integer
n – integer
mat – complex array
nblo – integer

2.85 half_unsto

NAME

half_unsto

SYNOPSIS

```
SUBROUTINE half_unsto (n,half_mat,nblo)
```

DESCRIPTION

Un-store the upper triangular part of matrix A column by column.

ARGUMENTS

n – integer
half_mat – complex array
nblo – integer

2.86 ilu_0

NAME

ilu_0

SYNOPSIS

```
SUBROUTINE ilu_0 (neq,sparse_size,p_row,column numb,coef,lu,p_diag)
```

DESCRIPTION

Preconditioner of a general matrix with ilu(0).

ARGUMENTS

- neq** – integer
- sparse_size** – integer
- p_row** – integer array
- column numb** – integer array
- coef** – complex array
- lu** – sparse matrix structure
- p_diag** – integer array

MODULES

```
USE sparse_matrix_struct
USE outfil
```

2.87 `ilu_preconditioner`**NAME**

ilu_preconditioner

SYNOPSIS

```
SUBROUTINE ilu_preconditioner (coef,pl,pc,pd,n,nza,ierr)
```

DESCRIPTION

ilu(0) preconditioner.

ARGUMENTS

- coef** – complex array
- pl** – integer array
- pc** – integer array
- pd** – integer array
- n** – integer
- nza** – integer
- ierr** – integer

2.88 `imprim`**NAME**

imprim

SYNOPSIS

```
SUBROUTINE imprim (frequency,subdom_numb,numb_subdom)
```

DESCRIPTION

Print the matrix of domain.

ARGUMENTS

frequency – real
subdom_numb – integer
numb_subdom – integer

MODULES

USE model
 USE outfil

2.89 `imprim2`**NAME**

imprim2

SYNOPSIS

```
SUBROUTINE imprim2 (frequency,subdom_numb,numb_subdom)
```

DESCRIPTION

Print the matrix of interface.

ARGUMENTS

frequency – real
subdom_numb – integer
numb_subdom – integer

MODULES

USE model
 USE feti_data
 USE outfil

2.90 `init_model`**NAME**

init_model

SYNOPSIS

```
SUBROUTINE init_model (subdom_numb)
```

DESCRIPTION

Initialize domain data.

ARGUMENTS

subdom_numb – integer

MODULES

USE model

2.91 initialize**NAME**

initialize

SYNOPSIS

SUBROUTINE **initialize**

DESCRIPTION

Initialize all model nodal data structures.

ARGUMENTS

None

MODULES

USE model

USE solver_param

USE outfil

2.92 inivec**NAME**

inivec

SYNOPSIS

SUBROUTINE **inivec** (**lx**,**x**)

DESCRIPTION

Pseudo random initialization.

ARGUMENTS

lx – integer

x – complex array

2.93 input_data

NAME

input_data

SYNOPSIS

SUBROUTINE **input_data**

DESCRIPTION

Input domain data.

ARGUMENTS

None

MODULES

USE model
 USE solver_param
 USE block_size
 USE outfil

2.94 interf_full_sym_struct

NAME

interf_full_sym_struct

SYNOPSIS

SUBROUTINE **interf_full_sym_struct** (**intf_mesh**,**a**)

DESCRIPTION

Build symmetric interface full matrix structure.

ARGUMENTS

intf_mesh – interface mesh structure
a – sparse matrix structure

MODULES

USE outfil
 USE realloc
 USE interf_mesh_struct
 USE sparse_matrix_struct

2.95 interf_full_unsym_struct

NAME

interf_full_unsym_struct

SYNOPSIS

```
SUBROUTINE interf_full_unsym_struct (intf_mesh,a)
```

DESCRIPTION

Build symmetric interface full matrix structure.

ARGUMENTS

intf_mesh – interface mesh structure
a – sparse matrix structure

MODULES

USE outfil
 USE realloc
 USE interf_mesh_struct
 USE sparse_matrix_struct

2.96 interf_sparse_sym_struct

NAME

interf_sparse_sym_struct

SYNOPSIS

```
SUBROUTINE interf_sparse_sym_struct (intf_mesh,a)
```

DESCRIPTION

Build symmetric interface sparse matrix structure.

ARGUMENTS

intf_mesh – interface mesh structure
a – sparse matrix structure

MODULES

USE outfil
 USE realloc
 USE interf_mesh_struct
 USE sparse_matrix_struct

2.97 interf_sparse_unsym_struct

NAME

interf_sparse_unsym_struct

SYNOPSIS

```
SUBROUTINE interf_sparse_unsym_struct (intf_mesh,a)
```

DESCRIPTION

Build unsymmetric interface sparse matrix structure.

ARGUMENTS

intf_mesh – interface mesh structure
a – sparse matrix structure

MODULES

USE outfil
USE realloc
USE interf_mesh_struct
USE sparse_matrix_struct

2.98 interface_assemb

NAME

interface_assemb

SYNOPSIS

```
SUBROUTINE interface_assemb (intf,unassemb,assemb)
```

DESCRIPTION

Assemble a field along the interface.

ARGUMENTS

intf – interface descriptor structure
unassemb – complex array
assemb – complex array

MODULES

USE interf_descriptor_struct
USE outfil

2.99 interface_average

NAME

interface_average

SYNOPSIS

```
SUBROUTINE interface_average (intf,unassemb,assemb)
```

DESCRIPTION

Average a field along the interface

ARGUMENTS

- intf** – interface descriptor structure
- unassemb** – complex array (= unassembled field as input)
- assemb** – complex array (= averaged field along the interface as output)

MODULES

USE interf_descriptor_struct

2.100 interface_equation

NAME

interface_equation

SYNOPSIS

```
SUBROUTINE interface_equation (dom,intf)
```

DESCRIPTION

Detect interface equations.

ARGUMENTS

- dom** – mesh structure
- intf** – interface descriptor structure

MODULES

- USE outfil
- USE mesh_struct
- USE interf_descriptor_struct
- USE mpif
- USE realloc

2.101 interface_exchange

NAME

interface_exchange

SYNOPSIS

```
SUBROUTINE interface_exchange (intf)
```

DESCRIPTION

Exchange interface data with neighbouring subdomains.

ARGUMENTS

intf – interface descriptor structure

MODULES

USE mpif
USE interf_descriptor_struct
USE outfil

2.102 interface_init

NAME

interface_init

SYNOPSIS

```
SUBROUTINE interface_init (intf)
```

DESCRIPTION

Initialize interface structure.

ARGUMENTS

intf – interface descriptor structure

MODULES

USE interf_descriptor_struct
USE realloc
USE outfil

2.103 interface_jump

NAME

interface_jump

SYNOPSIS

```
SUBROUTINE interface_jump (intf,v,w)
```

DESCRIPTION

Compute the jump of a field along the interface.

ARGUMENTS

- intf** – interface descriptor structure
- v** – complex array (= local field as input)
- w** – complex array (= jump of v as output)

MODULES

```
USE interf_descriptor_struct
```

2.104 interface_jump2

NAME

interface_jump2

SYNOPSIS

```
SUBROUTINE interface_jump2 (intf,k,v,lambda,g)
```

DESCRIPTION

Compute interface gradient.

ARGUMENTS

- intf** – interface descriptor structure
- k** – sparse matrix structure
- v** – complex array
- lambda** – complex array
- g** – complex array

MODULES

```
USE interf_descriptor_struct
```

```
USE sparse_matrix_struct
```

```
USE outfil
```

SEE ALSO

`interface_jump.f90`

2.105 interface_mesh_equation

NAME

interface_mesh_equation

SYNOPSIS

```
SUBROUTINE interface_mesh_equation (dom,intf,mesh_intf)
```

DESCRIPTION

Build interface equation per node.

ARGUMENTS

dom – mesh structure
intf – interface descriptor structure
mesh_intf – interface mesh structure

MODULES

USE outfil
 USE interf_descriptor_struct
 USE interf_mesh_struct
 USE facet_struct
 USE mesh_struct
 USE mpif
 USE realloc

2.106 interface_mesh_geometry

NAME

interface_mesh_geometry

SYNOPSIS

```
SUBROUTINE interface_mesh_geometry (dom,intf,mesh_intf)
```

DESCRIPTION

Detect interface facets.

ARGUMENTS

dom – mesh structure
intf – interface descriptor structure
mesh_intf – interface mesh structure

MODULES

```
USE outfil
USE interf_descriptor_struct
USE facet_struct
USE mesh_struct
USE interf_mesh_struct
USE mpif
USE realloc
```

2.107 interface_mesh_topology

NAME

interface_mesh_topology

SYNOPSIS

```
SUBROUTINE interface_mesh_topology (mesh_intf)
```

DESCRIPTION

Build list of equations in each element.

ARGUMENTS

mesh_intf – interface mesh structure

MODULES

```
USE interf_mesh_struct
USE outfil
USE realloc
```

2.108 interface_node

NAME

interface_node

SYNOPSIS

```
SUBROUTINE interface_node (intf)
```

DESCRIPTION

Detect interface nodes.

ARGUMENTS

intf – interface descriptor structure

MODULES

USE outfil
 USE interf_descriptor_struct
 USE mpif
 USE realloc

2.109 interface_signe

NAME

interface_signe

SYNOPSIS

```
SUBROUTINE interface_signe (intf)
```

DESCRIPTION

Sign sub-domains and interfaces.

ARGUMENTS

intf – interface descriptor structure

MODULES

USE interf_descriptor_struct
 USE outfil
 USE mpif

2.110 invD_times_U

NAME

invD_times_U

SYNOPSIS

```
SUBROUTINE invD_times_U (lda,nrow,d,ncol,u)
```

DESCRIPTION

Compute $[D]^{-1}U$.

ARGUMENTS

lda – integer
nrow – integer
d – complex array
ncol – integer
u – complex array

2.111 invL_times_U

NAME

invL_times_U

SYNOPSIS

SUBROUTINE **invL_times_U** (lda,nrow,ldlt,ncol,u)

DESCRIPTION

Compute $[L]^{-1}U$.

ARGUMENTS

lda – integer
nrow – integer
ldlt – complex array
ncol – integer
u – complex array

2.112 invL_times_sparsU

NAME

invL_times_sparsU

SYNOPSIS

SUBROUTINE **invL_times_sparsU** (n,ldlt,lda,ncol_u,i0,u,n1,n2)

DESCRIPTION

Compute $[L]^{-1}U$

ARGUMENTS

n – integer
ldlt – complex array
lda – integer
ncol_u – integer
i0 – integer array
u – complex array
n1 – integer
n2 – integer

2.113 invUt_times_sparsU

NAME

invUt_times_sparsU

SYNOPSIS

```
SUBROUTINE invUt_times_sparsU (n,ldu,lda,ncol_u,i0,u,n1,n2)
```

DESCRIPTION

Compute $[U]^{-t}U$.

ARGUMENTS

n	- integer
ldu	- complex array
lda	- integer
ncol_u	- integer
i0	- integer array
u	- complex array
n1	- integer
n2	- integer

2.114 jacobi_convergence

NAME

jacobi_convergence

SYNOPSIS

```
SUBROUTINE jacobi_convergence (omega,omega_moins,omega_plus,k_max,&
& p1,q1,p2,q2,rho_max)
```

DESCRIPTION

Compute maximum value of convergence rate of jacobi algorithm.

ARGUMENTS

omega	- real
omega_moins	- real
omega_plus	- real
k_max	- real
p1	- real
q1	- real
p2	- real
q2	- real
rho_max	- real

MODULES

USE outfil

2.115 jacobi_optimized

NAME

jacobi-optimized

SYNOPSIS

```
SUBROUTINE jacobi_optimized (type_optimized,omega,h,L,
&                                alpha_left,alpha_right,
&                                beta_left,beta_right)
```

DESCRIPTION

Compute optimized coefficient of jacobi algorithm.

ARGUMENTS

type_optimized	- integer
omega	- real
h	- real
L	- real
alpha_left	- complex
alpha_right	- complex
beta_left	- complex
beta_right	- complex

MODULES

```
USE mesh_struct
USE outfil
```

2.116 L_times_invD

NAME

L-times-invD

SYNOPSIS

```
SUBROUTINE L_times_invD (lda,nrow,d,ncol,u)
```

DESCRIPTION

Compute $L[D]^{-1}$.

ARGUMENTS

lda	- integer
nrow	- integer
d	- complex array
ncol	- integer
u	- complex array

2.117 L_times_invU

NAME

L_times_invU

SYNOPSIS

```
SUBROUTINE L_times_invU (lda,nrow,ldu,ncol,l)
```

DESCRIPTION

Compute $L[U]^{-1}$.

ARGUMENTS

- lda** – integer (= the dimension of matrix A)
- nrow** – integer
- ldu** – complex array (= the ldu factorization of diagonal block)
- ncol** – integer
- l** – complex array (= the lower band)

2.118 LdLt_tri_block_numeric

NAME

LdLt_tri_block_numeric

SYNOPSIS

```
SUBROUTINE LdLt_tri_block_numeric
```

DESCRIPTION

Numerical factorization using tridiagonal block LdLt algorithm.

ARGUMENTS

None

MODULES

```
USE solver_param
USE feti_data
USE model
USE outfil
USE direct_symmetric
```

2.119 LdLt_tri_block_symbolic

NAME

LdLt_tri_block_symbolic

SYNOPSIS

```
SUBROUTINE LdLt_tri_block_symbolic
```

DESCRIPTION

Symbolic factorization for block tridiagonal LDL^t algorithm.

ARGUMENTS

None

MODULES

- USE model
- USE outfil
- USE solver_param
- USE feti_data
- USE direct_symmetric

2.120 Ldlt_tri_dirich

NAME

Ldlt_tri_dirich

SYNOPSIS

```
SUBROUTINE Ldlt_tri_dirich (nop,ldu)
```

DESCRIPTION

Block tridiagonal factorization of a sparse symmetric matrix with reverse Cuthill Mac Kee numbering. Case of Dirichlet conditions for the last block.

ARGUMENTS

- nop** – real
- ldu** – factorized matrix structure

MODULES

- USE solver_param
- USE outfil
- USE factorized_matrix_struct

2.121 LdU_tri_block_numeric

NAME

LdU_tri_block_numeric

SYNOPSIS

```
SUBROUTINE LdU_tri_block_numeric
```

DESCRIPTION

Numerical factorization using tridiagonal block *LDU* algorithm.

ARGUMENTS

None

MODULES

- USE solver_param
- USE feti_data
- USE model
- USE outfil
- USE direct_unsymmetric

2.122 LdU_tri_block_symbolic**NAME**

LdU_tri_block_symbolic

SYNOPSIS

```
SUBROUTINE LdU_tri_block_symbolic
```

DESCRIPTION

Symbolic factorization for block tridiagonal LdU algorithm.

ARGUMENTS

None

MODULES

- USE model
- USE outfil
- USE solver_param
- USE feti_data
- USE direct_unsymmetric

2.123 LdU_tri_dirich**NAME**

LdU_tri_dirich

SYNOPSIS

```
SUBROUTINE LdU_tri_dirich (nop,ldu)
```

DESCRIPTION

Block tridiagonal factorization of a sparse symmetric matrix with reverse Cuthill Mac Kee numbering.

ARGUMENTS

nop – real
ldu – factorized matrix structure

MODULES

USE solver_param
 USE outfil
 USE factorized_matrix_struct

2.124 mask_to_list**NAME**

mask_to_list

SYNOPSIS

```
SUBROUTINE mask_to_list (dim,mask,ntrue,list,P6)
```

DESCRIPTION

Build concatenated list from a mask array.

ARGUMENTS

dim – integer
mask – integer array
ntrue – integer
list – integer array
P6 – integer

2.125 merge_nodal_list**NAME**

merge_nodal_list

SYNOPSIS

```
SUBROUTINE merge_nodal_list (neq,dim_bc,bc,tot)
```

DESCRIPTION

Build concatenated boundary condition.

ARGUMENTS

- neq** – integer
- dim_bc** – integer
- bc** – nodal list structure array
- tot** – nodal list structure

MODULES

USE ...

2.126 mtxv**NAME**

mtxv

SYNOPSIS

```
SUBROUTINE mtxv (n,m,a,x,y)
```

DESCRIPTION

Conjugate matrix-vector product: $y = A^*x$.

ARGUMENTS

- n** – integer
- m** – integer
- a** – complex array
- x** – complex array
- y** – complex array

2.127 mtxv_par**NAME**

mtxv_par

SYNOPSIS

```
SUBROUTINE mtxv_par (n,m,a,x,y,intf)
```

DESCRIPTION

Parallel conjugate matrix-vector product: $y = A^*x$.

ARGUMENTS

n – integer
m – integer
a – complex array
x – complex array
y – complex array
intf – interface descriptor structure

MODULES

```
USE interf_descriptor_struct
USE outfil
```

2.128 mxvadd

NAME

mxvadd

SYNOPSIS

```
SUBROUTINE mxvadd (n,m,a,x,y)
```

DESCRIPTION

Add matrix-vector product: $y = y + Ax$.

ARGUMENTS

n – integer
m – integer
a – complex array
x – complex array
y – complex array

2.129 nodal_list_equation

NAME

nodal_list_equation

SYNOPSIS

```
SUBROUTINE nodal_list_equation (dom,bc)
```

DESCRIPTION

Build list and mask of boundary equations.

ARGUMENTS

dom – mesh structure
bc – nodal list structure

MODULES

```
USE mesh_struct
USE nodal_list_struct
USE realloc
USE outfil
```

2.130 opti_number

NAME

opti_number

SYNOPSIS

```
SUBROUTINE opti_number (nodes,p_graph,graph,list_opt)
```

DESCRIPTION

Renumber subgraph via Cuthill-Mac Kee algorithm.

ARGUMENTS

- nodes** – integer
- p_graph** – integer array
- graph** – integer array
- list_opt** – integer array

MODULES

```
USE outfil
```

2.131 output_results

NAME

output_results

SYNOPSIS

```
SUBROUTINE output_results (frequency,freq_numb)
```

DESCRIPTION

Print results.

ARGUMENTS

- frequency** – real
- freq_numb** – integer

MODULES

USE outfil
 USE model
 USE feti_data
 USE mpif

2.132 point_front

NAME

point_front

SYNOPSIS

```
SUBROUTINE point_front (neq,p_row,sparse_size,col_numb,new2old,      &
&                      nfront,p_front,nclamp,nfront_clamp)
```

DESCRIPTION

Build pointer of fronts of block tridiagonal sparse matrix.

ARGUMENTS

neq – integer
p_row – integer array (= pointer of rows of unsymmetric matrix)
sparse_size – integer
col_numb – integer array (= list of column indices of rows of unsymmetric matrix)
new2old – integer array (= new to old correspondance)
nfront – integer
p_front – integer array (= pointer of fronts)
nclamp – integer
nfront_clamp – integer

MODULES

USE outfil

2.133 post_process

NAME

post_process

SYNOPSIS

```
SUBROUTINE post_process
```

DESCRIPTION

Post process results.

ARGUMENTS

None

MODULES

USE solver_param
USE model

2.134 print_vector**NAME**

print_vector

SYNOPSIS

```
SUBROUTINE print_vector (n,v)
```

DESCRIPTION

Print vector.

ARGUMENTS

n – integer
v – complex array

MODULES

USE outfil

2.135 proband**NAME**

proband

SYNOPSIS

```
SUBROUTINE proband (n,i1,i2,prow1,prow2,lmorse,ncol,a,x,y)
```

DESCRIPTION

Compute product by a rectangular sub-block of a symmetric sparse matrix.

ARGUMENTS

n – integer
i1 – integer
i2 – integer
prow1 – integer array
prow2 – integer array
lmorse – integer
ncol – integer array
a – complex array
x – complex array
y – complex array

2.136 probit

NAME

probit

SYNOPSIS

```
SUBROUTINE probit (intf,w,bitw)
```

DESCRIPTION

Compute the local right-hand-side associated with a Neumann boundary condition on the interface.

ARGUMENTS

intf – interface descriptor structure
w – complex array
bitw – complex array

MODULES

```
USE interf_descriptor_struct
USE outfil
```

2.137 problem_form

NAME

problem_form

SYNOPSIS

```
SUBROUTINE problem_form (frequency,subdom_numb,numb_subdom,typesol,&
& symm,k_opt,typegalerkin)
```

DESCRIPTION

Form the matrix of domain.

ARGUMENTS

frequency – real
subdom_numb – integer
numb_subdom – integer
typesol – integer
symm – integer
k_opt – integer
typegalerkin – integer

MODULES

USE model
 USE outfil
 USE feti_data

2.138 problo

NAME

problo

SYNOPSIS

```
SUBROUTINE problo (n,i1,i2,prow1,prow2,lmorse,ncol,a,x,y)
```

DESCRIPTION

Compute product by a sub-block of a sparse matrix.

ARGUMENTS

n – integer
i1 – integer
i2 – integer
prow1 – integer array
prow2 – integer array
lmorse – integer
ncol – integer array
a – complex array
x – complex array
y – complex array

2.139 problot

NAME

problot

SYNOPSIS

```
SUBROUTINE problot (n,i1,i2,prow1,prow2,lmorse,ncol,a,x,y)
```

DESCRIPTION

Compute product by a transposed sub-block of a sparse matrix.

ARGUMENTS

n	- integer
i1	- integer
i2	- integer
prow1	- integer array
prow2	- integer array
lmorse	- integer
ncol	- integer array
a	- complex array
x	- complex array
y	- complex array

2.140 pt_extract**NAME**

pt_extract

SYNOPSIS

```
SUBROUTINE pt_extract (n,i1,i2,j0,prow1,prow2,lmorse,ncol,a,dim2,  &
&                      dim1,blo)
```

DESCRIPTION

Extract transposed renumbered block associated to rows i1 to i2 and delimited by pointers prow1 et prow2 from sparse matrix stored by row.

ARGUMENTS

n	- integer
i1	- integer
i2	- integer
j0	- integer
prow1	- integer array
prow2	- integer array
lmorse	- integer
ncol	- integer array
a	- complex array
dim2	- integer
dim1	- integer
blo	- complex array

2.141 read_mesh**NAME**

read_mesh

SYNOPSIS

```
SUBROUTINE read_mesh (file_num,dom,max_numb_f,numb_f,f)
```

DESCRIPTION

Input mesh in free format.

ARGUMENTS

file_num	- integer
dom	- mesh structure
max_numb_f	- integer
numb_f	- integer
f	- facet structure array

MODULES

USE mesh_struct
USE facet_struct
USE realloc
USE outfil

2.142 **realloc_c1**

NAME

realloc_c1

SYNOPSIS

```
SUBROUTINE realloc_c1 (tab,dim1,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional complex pointer in the case where the pointer has been allocated.

ARGUMENTS

tab	- complex array
dim1	- integer
ierr	- integer

2.143 **realloc_c2**

NAME

realloc_c2

SYNOPSIS

```
SUBROUTINE realloc_c2 (tab,dim1,dim2,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional complex pointer in the case where the pointer has been allocated.

ARGUMENTS

tab – complex array
dim1 – integer
dim2 – integer
ierr – integer

2.144 realloc_i1**NAME**

realloc_i1

SYNOPSIS

```
SUBROUTINE realloc_i1 (tab,dim1,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional integer pointer in the case where the pointer has been allocated.

ARGUMENTS

tab – integer array
dim1 – integer
ierr – integer

2.145 realloc_i2**NAME**

realloc_i2

SYNOPSIS

```
SUBROUTINE realloc_i2 (tab,dim1,dim2,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional integer pointer in the case where the pointer has been allocated.

ARGUMENTS

tab – integer array
dim1 – integer
dim2 – integer
ierr – integer

2.146 realloc_r1

NAME

realloc_r1

SYNOPSIS

```
SUBROUTINE realloc_r1 (tab,dim1,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional real pointer in the case where the pointer has been allocated.

ARGUMENTS

tab – real array
dim1 – integer
ierr – integer

2.147 realloc_r2

NAME

realloc_r2

SYNOPSIS

```
SUBROUTINE realloc_r2 (tab,dim1,dim2,ierr)
```

DESCRIPTION

Reallocation of multi-dimensional real pointer in the case where the pointer has been allocated.

ARGUMENTS

tab – real array
dim1 – integer
dim2 – integer
ierr – integer

2.148 ren_sym_sparse

NAME

ren_sym_sparse

SYNOPSIS

```
SUBROUTINE ren_sym_sparse (neq,sparse_size,rowp,col,new2old,p_row, &
& col numb)
```

DESCRIPTION

Construction of renumbered lower triangular part of the symmetric sparse structure stored row by row from the upper triangular symmetric one.

ARGUMENTS

rowp – pointer of rows of the upper triangular part of the initial matrix
col – list of column indices of rows of the initial matrix
new2old – new to old correspondance
p_row – pointer of rows of the lower triangular part of the symmetric matrix
col numb – list of column indices of rows of the renumbered matrix
... – ...

MODULES

USE outfil

2.149 ren_unsym_sparse**NAME**

ren_unsym_sparse

SYNOPSIS

```
SUBROUTINE ren_unsym_sparse (neq,sparse_size,rowp,col,new2old,      &
&                           p_row,col_numb)
```

DESCRIPTION

Construction of renumbered unsymmetric sparse structure stored row by row.

ARGUMENTS

rowp – pointer of rows of the initial matrix
col – list of column indices of rows of the initial matrix
new2old – new to old correspondance
p_row – pointer of rows of the unsymmetric matrix
col numb – list of column indices of rows of the renumbered matrix

MODULES

USE outfil

2.150 renum_eq_mpc**NAME**

renum_eq_mpc

SYNOPSIS

```
SUBROUTINE renum_eq_mpc (dom,dim_mpc,mpc)
```

DESCRIPTION

Change equation numbering to take into account multi-point constraints.

ARGUMENTS

dom – mesh structure
dim_mpc – integer
mpc – nodal list structure array

MODULES

USE outfil
 USE mesh_struct
 USE Nodal_List_struct

2.151 renum_facet

NAME

renum_facet

SYNOPSIS

```
SUBROUTINE renum_facet (dom,bc)
```

DESCRIPTION

Replace external to internal node number in list of nodes of facet.

ARGUMENTS

dom – mesh structure
bc – facet structure

MODULES

USE mesh_struct
 USE facet_struct

2.152 renum_nodal_list

NAME

renum_nodal_list

SYNOPSIS

```
SUBROUTINE renum_nodal_list (dom,bc)
```

DESCRIPTION

Replace external to internal node number in nodal list.

ARGUMENTS

dom – mesh structure
bc – nodal list structure

MODULES

USE mesh_struct
USE nodal_list_struct

2.153 `solve_rhs`**NAME**

solve_rhs

SYNOPSIS

```
SUBROUTINE solve_rhs (subdom_numb)
```

DESCRIPTION

Solve problem for a single right hand side.

ARGUMENTS

subdom_numb – integer

MODULES

USE solver_param
USE model
USE outfil
USE realloc
USE feti_data
USE feti_param
USE mpif

2.154 `son_3d`**NAME**

son_3d

SYNOPSIS

```
PROGRAM son_3d
```

DESCRIPTION

FETI demonstration code.

ARGUMENTS

None

MODULES

USE solver_param

2.155 sort_list

NAME

sort_list

SYNOPSIS

```
SUBROUTINE sort_list (dim,list)
```

DESCRIPTION

Sort list of interger in increasing ordering.

ARGUMENTS

dim – integer
list – integer array

2.156 sparse_fwbw

NAME

sparse_fwbw

SYNOPSIS

```
SUBROUTINE sparse_fwbw (neq,sparse_size,p_row,column_numb,a,      &
&                         p_diag,b,z)
```

DESCRIPTION

Sparse forward-backward solution of $Ax = b$ with $A = LU$.

ARGUMENTS

```

neq - integer
sparse_size - integer
p_row - integer array
column_numb - integer array
a - complex array
p_diag - integer array
b - complex array
z - complex array

```

2.157 sparse_matrix_equalization

NAME

sparse_matrix_equalization

SYNOPSIS

```
SUBROUTINE sparse_matrix_equalization (b,a)
```

DESCRIPTION

Equalize sparse matrix.

ARGUMENTS

```

b - sparse matrix structure
a - sparse matrix structure

```

MODULES

```

USE sparse_matrix_struct
USE realloc
USE outfil

```

2.158 sparse_matrix_equalization2

NAME

sparse_matrix_equalization2

SYNOPSIS

```
SUBROUTINE sparse_matrix_equalization2 (b,a)
```

DESCRIPTION

Equalize sparse matrix.

ARGUMENTS

- b** – sparse matrix structure
- a** – sparse matrix structure

MODULES

USE sparse_matrix_struct

2.159 sparse_prod

NAME

sparse_prod

SYNOPSIS

```
SUBROUTINE sparse_prod (a,x,y)
```

DESCRIPTION

Compute sparse matrix vector product in the case of a symmetric matrix with upper triangular part stored by rows.

ARGUMENTS

- a** – sparse matrix structure
- x** – complex array
- y** – complex array

MODULES

USE sparse_matrix_struct

2.160 split_mesh

NAME

split_mesh

SYNOPSIS

```
SUBROUTINE split_mesh (numb_subdom)
```

DESCRIPTION

Build elements to subdomain correspondance.

ARGUMENTS

numb_subdom – integer

MODULES

USE model
 USE feti_data
 USE outfil

2.161 stoprun

NAME

stoprun

SYNOPSIS

SUBROUTINE **stoprun**

DESCRIPTION

Abort run.

ARGUMENTS

None

MODULES

USE outfil

2.162 sym_approx_schur_cpmt

NAME

sym_approx_schur_cpmt

SYNOPSIS

SUBROUTINE **sym_approx_schur_cpmt** (**a**,**ainit**,**reg**,**intf**,**intf_mesh**,**Diri**, &
Dir)

DESCRIPTION

Compute Schur complement.

ARGUMENTS

a – sparse matrix structure
ainit – sparse matrix structure
reg – sparse matrix structure
intf – interface descriptor structure
intf_mesh – interface mesh structure
Diri – nodal list structure
Dir – nodal list structure

MODULES

```
USE mpif
USE solver_param
USE feti_data
USE sparse_matrix_struct
USE direct_symmetric
USE interf_mesh_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE outfil
USE realloc
```

2.163 sym_build_schur_cpmt

NAME

sym_build_schur_cpmt

SYNOPSIS

```
SUBROUTINE sym_build_schur_cpmt (ainit,reg,intf,intf_mesh,Diri,      &
&                                Dir)
```

DESCRIPTION

Compute Schur complement.

ARGUMENTS

ainit	- sparse matrix structure
reg	- sparse matrix structure
intf	- interface descriptor structure
intf_mesh	- interface mesh structure
Diri	- nodal list structure
Dir	- nodal list structure

MODULES

```
USE mpif
USE solver_param
USE feti_data
USE sparse_matrix_struct
USE direct_symmetric
USE interf_mesh_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE outfil
```

2.164 sym_condens

NAME

sym_condens

SYNOPSIS

```
SUBROUTINE sym_condens (lda,dim1,dim2,a,d,b,c,bt,i0,nop)
```

DESCRIPTION

Compute the Schur complement: $C = C - [L^{-1}B]^t[L^{-1}B]$ where L is the lower triangular part of the Choleski factorisation of A .

ARGUMENTS

lda	- integer
dim1	- integer
dim2	- integer
a	- complex array
d	- complex array
b	- complex array
c	- complex array
bt	- complex array
i0	- integer array
nop	- real

MODULES

```
USE block_size
```

2.165 sym_direct_solve

NAME

sym_direct_solve

SYNOPSIS

```
SUBROUTINE sym_direct_solve (y,x)
```

DESCRIPTION

Forward-backward substitution using tridiagonal block LdU factorization.

ARGUMENTS

y	- complex array
x	- complex array

MODULES

```
USE model
USE direct_symmetric
```

2.166 sym_extract

NAME

sym_extract

SYNOPSIS

```
SUBROUTINE sym_extract (n,i1,i2,j0,prow1,prow2,lmorse,ncol,a,lda,  &
&                      dim2,blo)
```

DESCRIPTION

Extract block associated to rows i1 to i2 and delimited by pointers prow1 et prow2 from sparse matrix stored by row.

ARGUMENTS

n	- integer
i1	- integer
i2	- integer
j0	- integer
prow1	- integer array
prow2	- integer array
lmorse	- integer
ncol	- integer
a	- complex array
lda	- integer
dim2	- integer
blo	- complex array

2.167 sym_fill_tridiag_sparse

NAME

sym_fill_tridiag_sparse

SYNOPSIS

```
SUBROUTINE sym_fill_tridiag_sparse (a,ldu)
```

DESCRIPTION

Fill renumbered matrix with storage of lower triangular part.

ARGUMENTS

a	- sparse matrix structure
ldu	- factorized matrix structure

MODULES

```
USE sparse_matrix_struct
USE factorized_matrix_struct
```

2.168 sym_fwbw_tri_dirichlet

NAME

sym_fwbw_tri_dirichlet

SYNOPSIS

```
SUBROUTINE sym_fwbw_tri_dirichlet (y,x)
```

DESCRIPTION

Forward-backward substitution using tridiagonal block *LDU* factorization.

ARGUMENTS

y – complex array
x – complex array

MODULES

USE model
 USE direct_symmetric

2.169 sym_multi_level1_feti

NAME

sym_multi_level1_feti

SYNOPSIS

```
SUBROUTINE sym_multi_level1_feti (rhs,solution,a,a_init,          &
&                                Dirichlet,interfine,typre,numb_dir,  &
&                                max_numb_it,numb_restart,epsilon,    &
&                                epstagn,multi_rhs)
```

DESCRIPTION

Level-1 FETI solution with multi-Krylov projection.

ARGUMENTS

```

rhs - complex array
solution - complex array
      a - sparse matrix structure
      a_init - sparse matrix structure
Dirichlet - nodal list structure
interfine - interface descriptor structure
      typre - integer
      numb_dir - integer
max_numb_it - integer
numb_restart - integer
      epsilon - real
      epstagn - real
multi_rhs - integer

```

MODULES

```

USE mpif
USE direct_symmetric
USE factorized_matrix_struct
USE sparse_matrix_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE outfil

```

2.170 **sym_multi_level2_feti**

NAME

sym_multi_level2_feti

SYNOPSIS

```

SUBROUTINE sym_multi_level2_feti (rhs,solution,a,a_init,b,
&                                Dirichlet,interfineP,typre,
&                                numb_dir,max_numb_it,numb_restart,
&                                epsilon,epstagn,multi_rhs)

```

DESCRIPTION

Solution of interface problem using a Jacobi algorithm.

ARGUMENTS

```

rhs - complex array
solution - complex array
    a - sparse matrix structure
    a_init - sparse matrix structure
Dirichlet - nodal list structure
interfineP - interface descriptor structure
    typre - integer
    numb_dir - integer
max_numb_it - integer
numb_restart - integer
    epsilon - real
    epstagn - real
multi_rhs - integer

```

MODULES

```

USE mpif
USE direct_symmetric
USE factorized_matrix_struct
USE sparse_matrix_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE feti_data
USE outfil

```

2.171 sym_proax

NAME

sym_proax

SYNOPSIS

```
SUBROUTINE sym_proax (neq,p_row,sparse_size,column numb,coef,x,y)
```

DESCRIPTION

Compute sparse matrix vector product in the case of a symmetric matrix with upper triangular part stored by rows.

ARGUMENTS

```

neq - integer
p_row - integer array
sparse_size - integer
column numb - integer array
coef - complex array
x - complex array
y - complex array

```

2.172 sym_renumb_matrix_bc

NAME

sym_renumb_matrix_bc

SYNOPSIS

```
SUBROUTINE sym_renumb_matrix_bc (a,ldu)
```

DESCRIPTION

Build renumbered matrix with storage of lower triangular part.

ARGUMENTS

a – sparse matrix structure
ldu – factorized matrix structure

MODULES

USE sparse_matrix_struct
 USE nodal_list_struct
 USE outfil
 USE realloc
 USE factorized_matrix_struct

2.173 sym_tridiag_struct

NAME

sym_tridiag_struct

SYNOPSIS

```
SUBROUTINE sym_tridiag_struct (ldu)
```

DESCRIPTION

Build block tridiagonal sparse matrix structure of symmetric matrix renumbered via Cuthill Mac Kee.

ARGUMENTS

ldu – factorized matrix structure

MODULES

USE solver_param
 USE outfil
 USE realloc
 USE factorized_matrix_struct

2.174 symfwbw_tri_dirichlet

NAME

symfwbw_tri_dirichlet

SYNOPSIS

```
SUBROUTINE symfwbw_tri_dirichlet (y,x,ldu)
```

DESCRIPTION

Forward-backward substitution with tridiagonal block sparse matrix. Case of Dirichlet conditions for the last block.

ARGUMENTS

- y** – complex array
- x** – complex array
- ldu** – factorized matrix structure

MODULES

```
USE solver_param
USE outfil
```

2.175 symunsym_sparse_mask

NAME

symunsym_sparse_mask

SYNOPSIS

```
SUBROUTINE symunsym_sparse_mask (neq, rowp, lcol, col, p_row,           &
&                                sparse_size, col_numb, mask)
```

DESCRIPTION

Construction of the un-symmetric sparse structure from the upper triangular part of the symmetric one stored row by row.

ARGUMENTS

- rowp** – pointer of rows of upper triangular part of symmetric matrix
- col** – list of column indices of rows of upper triangular part
- p_row** – pointer of rows of unsymmetric matrix
- col_numb** – list of column indices of rows of unsymmetric matrix
- mask** – mask of eliminated equations

MODULES

```
USE outfil
```

2.176 un_condens

NAME

un_condens

SYNOPSIS

```
SUBROUTINE un_condens (lda, dim1, dim2, a, d, e, f, c, v, ie0, if0, nop)
```

DESCRIPTION

Compute the Schur complement $C = C - [U^{-t}F]^t d^{-1} [L^{-1}E]$ LDU is the Gauss-Jordan factorisation of A .

ARGUMENTS

lda	- integer
dim1	- integer
dim2	- integer
a	- complex array
d	- complex array
e	- complex array
f	- complex array
c	- complex array
v	- complex array
ie0	- integer array
if0	- integer array
nop	- real

2.177 un_extract

NAME

un_extract

SYNOPSIS

```
SUBROUTINE un_extract(n, i1, i2, j0, prow1, prow2, lmorse, ncol, a, lda,    &
&                      dim2, blo)
```

DESCRIPTION

Extract block associated to rows $i1$ to $i2$ and delimited by pointers $prow1$ et $prow2$ from sparse matrix stored by row

ARGUMENTS

```

n - integer
i1 - integer
i2 - integer
j0 - integer
prow1 - integer array
prow2 - integer array
lmorse - integer
ncol - integer array
      a - complex array
lda - integer
dim2 - integer
blo - complex array

```

2.178 unsym_approx_schur_cpmt

NAME

unsym_approx_schur_cpmt

SYNOPSIS

```
SUBROUTINE unsym_approx_schur_cpmt(a,ainit,reg,intf,intf_mesh,      &
&                                         Diri,Dir)
```

DESCRIPTION

Compute Schur complement.

ARGUMENTS

```

a - sparse matrix structure
ainit - sparse matrix structure
reg - sparse matrix structure
intf - interface descriptor structure
intf_mesh - interface mesh structure
Diri - nodal list structure
Dir - nodal list structure

```

MODULES

```

USE mpif
USE solver_param
USE feti_data
USE sparse_matrix_struct
USE direct_unsymmetric
USE interf_mesh_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE outfil
USE realloc

```

2.179 unsym_build_schur_cpmt

NAME

unsym_build_schur_cpmt

SYNOPSIS

```
SUBROUTINE unsym_build_schur_cpmt (ainit,reg,intf,intf_mesh,Diri, &
& Dir)
```

DESCRIPTION

Compute Schur complement

ARGUMENTS

- ainit** – sparse matrix structure
- reg** – sparse matrix structure
- intf** – interface descriptor structure
- intf_mesh** – interface mesh structure
- Diri** – nodal list structure
- Dir** – modal list structure

MODULES

- USE mpif
- USE solver_param
- USE feti_data
- USE sparse_matrix_struct
- USE direct_unsymmetric
- USE interf_mesh_struct
- USE interf_descriptor_struct
- USE nodal_list_struct
- USE outfil
- USE realloc

2.180 unsym_direct_solve

NAME

unsym_direct_solve

SYNOPSIS

```
SUBROUTINE unsym_direct_solve (y,x)
```

DESCRIPTION

Forward-backward substitution using tridiagonal block LdU factorization

ARGUMENTS

y – complex array
x – complex array

MODULES

USE model
 USE direct_unsymmetric

2.181 unsym_fill_tridiag_sparse

NAME

unsym_fill_tridiag_sparse

SYNOPSIS

```
SUBROUTINE unsym_fill_tridiag_sparse (a,ldu)
```

DESCRIPTION

Fill renumbered matrix

ARGUMENTS

a – sparse matrix structure
ldu – factorized matrix structure

MODULES

USE sparse_matrix_struct
 USE factorized_matrix_struct

2.182 unsym_fwbw_tri_dirichlet

NAME

unsym_fwbw_tri_dirichlet

SYNOPSIS

```
SUBROUTINE unsym_fwbw_tri_dirichlet(y,x)
```

DESCRIPTION

Forward-backward substitution using tridiagonal block LdU factorization.

ARGUMENTS

y – complex array
x – complex array

MODULES

USE model
USE direct_unsymmetric

2.183 unsym_multi_level1_feti

NAME

unsym_multi_level1_feti

SYNOPSIS

```
SUBROUTINE unsym_multi_level1_feti(rhs,solution,a,a_init,      &
&                                     Dirichlet, interfine,typre,      &
&                                     numb_dir,max_numb_it,numb_restart,  &
&                                     epsilon,epstagn,multi_rhs)
```

DESCRIPTION

Level-1 FETI solution with multi-Krylov projection

ARGUMENTS

- rhs** – complex array
- solution** – complex array
- a** – sparse matrix structure
- a_init** – sparse matrix structure
- Dirichlet** – nodal list structure
- interfine** – interface descriptor structure
- typre** – integer
- numb_dir** – integer
- max_numb_it** – integer
- numb_restart** – integer
- epsilon** – real
- epstagn** – real
- multi_rhs** – integer

MODULES

USE mpif
USE direct_unsymmetric
USE factorized_matrix_struct
USE sparse_matrix_struct
USE interf_descriptor_struct
USE nodal_list_struct
USE outfil

2.184 unsym_multi_level2_feti

NAME

unsym_multi_level2_feti

SYNOPSIS

```
SUBROUTINE unsym_multi_level2_feti (rhs,solution,a,a_init,b,      &
&                                     Dirichlet,interfine,      typre,      &
&                                     numb_dir,max_numb_it,numb_restart,  &
&                                     epsilon,epstagn,multi_rhs)
```

DESCRIPTION

Level-2 FETI solution with multi-Krylov projection.

ARGUMENTS

rhs	- complex array
solution	- complex array
a	- sparse matrix structure
a_init	- sparse matrix structure
Dirichlet	- nodal list structure
interfineP	- interface descriptor structure
typre	- integer
numb_dir	- integer
max_numb_it	- integer
numb_restart	- integer
epsilon	- real
epstagn	- real
multi_rhs	- integer

MODULES

```
USE mpif
USE direct_unsymmetric
USE factorized_matrix_struct
USE sparse_matrix_struct
USE interf_descriptor_struct
USE interf_mesh_struct
USE nodal_list_struct
USE outfil
```

2.185 unsym_proax

NAME

unsym_proax

SYNOPSIS

```
SUBROUTINE unsym_proax (neq,p_row,sparse_size,column_numb,coef,x,y)
```

DESCRIPTION

Compute sparse matrix vector product in the case of an unsymmetric matrix stored by rows.

ARGUMENTS

```

neq - integer
p_row - integer array
sparse_size - integer
column_numb - integer array
coef - complex array
x - complex array
y - complex array

```

2.186 unsym_renumb_matrix_bc

NAME

unsym_renumb_matrix_bc

SYNOPSIS

```
SUBROUTINE unsym_renumb_matrix_bc (a,ldu)
```

DESCRIPTION

Build renumbered matrix.

ARGUMENTS

```

a - sparse matrix structure
nrow - factorized matrix structure

```

MODULES

```

USE sparse_matrix_struct
USE nodal_list_struct
USE outfil
USE realloc
USE factorized_matrix_struct

```

2.187 unsym_tridiag_struct

NAME

unsym_tridiag_struct

SYNOPSIS

```
SUBROUTINE unsym_tridiag_struct(ldu)
```

DESCRIPTION

Build block tridiagonal sparse matrix structure of unsymmetric matrix renumbered via Cuthill Mac Kee.

ARGUMENTS

ldu – factorized matrix struct

MODULES

USE solver_param
 USE outfil
 USE realloc
 USE factorized_matrix_struct

2.188 unsymfwbw_tri_dirichlet

NAME

unsymfwbw_tri_dirichlet

SYNOPSIS

```
SUBROUTINE unsymfwbw_tri_dirichlet (y,x,ldu)
```

DESCRIPTION

Forward-backward substitution with tridiagonal block sparse matrix. Case of Dirichlet conditions for the last block.

ARGUMENTS

y – complex array
x – complex array
ldu – factorized matrix structure

MODULES

USE solver_param
 USE outfil
 USE factorized_matrix_struct

2.189 unsymunsym_sparse_mask

NAME

unsymunsym_sparse_mask

SYNOPSIS

```
SUBROUTINE unsymunsym_sparse_mask(neq,rowp,1col,col,p_row,           &
&                                     sparse_size,col numb,mask)
```

DESCRIPTION

Construction of the non-symmetric sparse structure with elimination of non diagonal entries of clamped rows and columns.

ARGUMENTS

rowp – pointer of rows of non symmetric matrix
col – list of column indices of rows
p_row – pointer of rows of compressed matrix
col_numb – list of column indices of rows of compressed matrix
mask – mask of eliminated equations

MODULES

USE outfil

2.190 update_facet

NAME

update_facet

SYNOPSIS

SUBROUTINE **update_facet** (dom,bc)

DESCRIPTION

Find facets material number.

ARGUMENTS

dom – mesh structure
bc – facet structure

MODULES

USE mesh_struct
 USE facet_struct
 USE outfil

2.191 Update_Nodal_List

NAME

Update_Nodal_List

SYNOPSIS

SUBROUTINE **Update_Nodal_List** (dom,bc)

DESCRIPTION

Find neighboring elements of boundary nodes

ARGUMENTS

dom – mesh structure
bc – nodal list structure

MODULES

```
USE mesh_struct
USE nodal_list_struct
USE realloc
USE outfil
```

2.192 update_region

NAME

update_region

SYNOPSIS

```
SUBROUTINE update_region (dom,acou_mat,admi_mat,inf_mat)
```

DESCRIPTION

Change region id to internal region number for elements and build internal region number of adjacent element.

ARGUMENTS

- dom** – mesh structure
- acou_mat** – region property structure array
- admi_mat** – region property structure array
- inf_mat** – region property structure array

MODULES

```
USE mesh_struct
USE region_property_struct
USE outfil
```

2.193 write_field

NAME

write_field

SYNOPSIS

```
SUBROUTINE write_field (file_num,dom,field)
```

DESCRIPTION

Print field entries node by node

ARGUMENTS

- file_num** – integer
- dom** – mesh structure
- field** – complex array

MODULES

USE outfil
 USE mesh_struct

2.194 write_field_femview

NAME

write_field_femview

SYNOPSIS

```
SUBROUTINE write_field_femview (file_num,dom,field)
```

DESCRIPTION

Write the complex components of pressure in a FEMVIEW file

ARGUMENTS

file_num – integer
dom – mesh structure
field – complex array

MODULES

USE outfil
 USE mesh_struct

2.195 write_matrix

NAME

write_matrix

SYNOPSIS

```
SUBROUTINE write_matrix (a,frequency,subdom numb,numb_subdom,      &
&                           directory)
```

DESCRIPTION

Print complex sparse matrix.

ARGUMENTS

a – sparse matrix structure
frequency – real
subdom numb – integer
numb_subdom – integer
directory – character string

MODULES

```
USE outfil
USE sparse_matrix_struct
```

2.196 write_meshfield_femvtk

NAME

write_meshfield_femvtk

SYNOPSIS

```
SUBROUTINE write_meshfield_femvtk (file_num,dom,field)
```

DESCRIPTION

Write the complex components of pressure in a VTK file

ARGUMENTS

```
file_num - integer
dom - mesh structure
field - complex array
```

MODULES

```
USE outfil
USE mesh_struct
```

2.197 zorthodir_solver

NAME

zorthodir_solver

SYNOPSIS

```
SUBROUTINE zorthodir_solver (rhs,x,a,Dirichlet,type_precond,
&                                numb_dir,max_num_it,epsilon,
&                                subdom_numb) &
```

DESCRIPTION

Iterative solution of complex problem by Orthodir algorithm with restarts.

ARGUMENTS

```

rhs - complex array
x - complex array
a - sparse matrix structure
Dirichlet - nodal list structure
type_precond - integer
    numb_dir - integer
    max_numb_it - integer
    epsilon - real
subdom_numb - integer

```

MODULES

```

USE sparse_matrix_struct
USE nodal_list_struct
USE outfil

```

2.198 zorthodir_solver_par

NAME

zorthodir-solver-par

SYNOPSIS

```

SUBROUTINE zorthodir_solver_par (rhs,x,a,Dirichlet,intf,
&                                type_precond,numb_dir,max_numb_it,epsilon,&
&                                subdom_numb)

```

DESCRIPTION

Parallel Iterative solution of complex problem by Orthodir algorithm with restarts.

ARGUMENTS

```

rhs - complex array
x - complex array
a - sparse matrix structure
Dirichlet - nodal list structure
intf - interface descriptor structure
type_precond - integer
    numb_dir - integer
    max_numb_it - integer
    epsilon - real
subdom_numb - integer

```

MODULES

```

USE sparse_matrix_struct
USE nodal_list_struct
USE interf_descriptor_struct
USE outfil

```

Acknowledgements

The authors acknowledge partial financial support by the European Community under the Enhancing Access to Research Infrastructure action of the Improving Human Potential programme, contract number HPRI-1999-CT-0026.