



HAL
open science

Representing human and machine dictionaries in Markup languages

Lothar Lemnitzer, Laurent Romary, Andreas Witt

► **To cite this version:**

Lothar Lemnitzer, Laurent Romary, Andreas Witt. Representing human and machine dictionaries in Markup languages. Ulrich Heid. Dictionaries. An International Encyclopedia of Lexicography. Supplementary volume: Recent developments with special focus on computational lexicography, Mouton de Gruyter, 2010. inria-00441215v1

HAL Id: inria-00441215

<https://inria.hal.science/inria-00441215v1>

Submitted on 15 Dec 2009 (v1), last revised 16 Dec 2009 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Lothar Lemnitzer, Laurent Romary, Andreas Witt

Representing human and machine dictionaries in Markup languages (SGML, XML)

1 Introduction

5 Mankind has been using, in a long history of preserving and storing knowledge, a wide range of media for this purpose. Over the centuries, clay tablets, papyri, parchment, paper and, most recently, all kinds of discs have been used to store and therefore preserve information which was, at their times, supposed to be worthy of preservation. Reference works have always been an integral part of this development (cf. McArthur, 1988).

10 Nowadays we are facing another media revolution with a period of synchronous use of so called “analog” media – e.g. paper and print – and “digital media” –e.g. hard discs, CD-ROMs and other storage media for digital data.

Producers and publishers of reference works such as dictionaries must cope with this situation. Economic as well as other reasons demand that a) existing “paper and print” dictionaries be digitized for their use on a desktop or over the internet – the so-called (retro-
15)digitization of existing print dictionaries – and b) new dictionaries be produced in a way that there use in all kinds of (old and new) devices is anticipated.

Dictionaries can be seen, in a somewhat simplified view - as collections of entries. These entries are highly structured objects where the various text components bear neither the same semantic nor the same internal organization. In paper and print dictionaries, typographic (e.g.
20 font weight) as well as non typographic means (e.g. bracketing) are used to convey this structural information to the user. With the advent of the new media and the digitization of dictionaries, a tendency to separate the logical structure and the layout characteristics of dictionary entries has taken place. The common way of doing this is to mark-up the various parts of the texts, i.e. to insert additional information in order to signify the semantics of these
25 parts. The media specific layout of the articles and their parts is added by means of style-sheets (see sect. 5.1).

In the following section, we will describe typical entry structures to be found in traditional paper and print dictionaries and illustrate this with two examples of dictionaries which have recently been digitized.

30 In section 3 we will shortly introduce mark-up languages which are suitable to model the tree-like structure of dictionary entries and to describe the semantics of the individual components. Document grammars, also called schemata, i.e. specialized mechanisms to constraint the structure the annotations, will be introduced as well.

Two document models for dictionary articles are currently in use and can be seen as

35 (quasi-)standards for the modeling of print articles: a) the Guidelines of the Text Encoding Initiative (TEI, Sperberg-McQueen, C.M./Burnard 2004), in particular chapter 12, and b) the ISO 1951 standard for printed dictionaries.

While the TEI Guidelines have a long tradition, enjoy a high reputation in the field of academic dictionary projects and are supported by a large community with examples of good practice, schemas, tools etc., this is not the case with ISO 1951. As we will explain in section 40 5, this standard still suffers from conceptual shortcomings. It might however play a role in dictionary publishing in the future, the more if the conceptual shortcomings will be amended.

The resp. standards are described in section 4.

Most recently, another ISO standard, called “Lexical Markup Framework”, was released. 45 While this framework is clearly oriented towards the presentation of dictionaries for natural language processing, it can and should also be related to the TEI and ISO 1951 standards. LMF is therefore shortly described in section 4 as well.

Section 5 is devoted to transformation tools and scenarios. Once a dictionary article is modeled as a tree-like-structure, and the individual elements are given an explicit semantics, 50 these articles can be transformed in various ways to either a) transform them into other trees by re-arranging the parts or deleting some elements or b) derive a media-specific representation format from the source. We will describe XSLT as one special purpose programming language to specify and perform such transformations. Furthermore, we will use a simple mapping from TEI encoding to ISO 1951 encoding as one example.

Markup languages and schemata in particular can also be used to control the dictionary compilation process. The use of a) well defined article structures and b) pre-defined vocabularies can be enforced by the use of (article) schemata. We will explain how this works, using again the examples introduced in section 2. 55

This article closes with some concluding remarks and a bibliography.

60

2 The tree-like structure of dictionaries and dictionary entries

At first sight, dictionary entries appear to the reader’s eye as a sequence of words and symbols. This holds for most printed as well as electronic dictionaries (see the examples in figure 1 and 2, excerpted from printed dictionaries).

65 At second sight, one might detect a non-linear structure underlying this sequence. This structure resembles the mathematical model of a tree, i.e. an ordered, directed, and acyclic graph.

There are typographical as well as non-typographical signals that indicate where a segment

of a dictionary article starts and where it ends. Indeed, it is essential for the efficient use of a
 70 dictionary article to understand this underlying hierarchical structure. Learned users of
 dictionary articles such as given in example 1 and 2 can easily find their way to the
 information which they need in a certain situation.

More formally, the typical dictionary article consists of a sequence of segments in a fixed
 order, each segment conveying a unique piece of information about the object which is
 75 described in this article – typically a lexical entity of some kind (morpheme, word, phrase
 etc.).

Another feature of the dictionary entry structure is not so obvious to the user. Most
 dictionary articles are organized hierarchically. An entry may consist of several sub-parts,
 each of which conveys information about different homographs of a headword (alternatively,
 80 homographs could be represented two or more independent entries). It may consist of a
 description of the form, function and grammatical features of the linguistic sign as well as of
 numerous senses, each of which may in turn be composed of some sub-senses etc.

On this more abstract level, we can model a dictionary entry as a tree with a root (which
 represents the full entry), intermediate levels (e.g. forms section, semantic section) and the
 85 individual segments at the leaves.

In the following we introduce (fragments of) two sample entries that will be referred to in
 the remainder of this article. The print dictionaries from which these articles are excerpted
 have been digitized, encoded and annotated using XML in conformance with the TEI
 Guidelines (see below).

90 **Bahn- ...- hof**, der, *Halle, Gebäude am Halteplatz von Eisenbahnzügen*: am B. sein; jmdn.
 Am B. erwarten, vom B. abholen, zum B. bringen; auf welchem B. kommt er an?; wie weit ist
 es bis zum B.?; der Zug rollte aus dem B.; im Gedränge des Bahnhofes; Neupräg. salopp ich
 verstehe immer nur B. (*ich verstehe gar nichts*); Neupräg. großer B. *festlicher Empfang*: der
 berühmte Gast wurde mit großem B. empfangen; von einem großen B. absehen

95 Figure 1: Entry for the headword *Bahnhof* ('railway station') excerpted from the Wörterbuch der deutschen
 Gegenwartssprache (=WDG), 6. Vol., ed. by Ruth Klappenbach und Wolfgang Steinitz, Berlin 1962-1977,
 online at: www.dwds.de. The entry is slightly abridged to make it easier to read.

100 **Ski** m., seit Anfang 20 Jh. meist *Schi*, ‚Scheeschuh‘, Übernahme (Anfang 19. Jh.) von
 gleichbed. norw. *ski*, aus anord. *sk.* ‚Scheit, Schneeschuh‘; s. das im Dt. etymologisch
 entsprechende *Scheit*.

Fig 2: an entry from: Wolfgang Pfeifer: Etymologisches Wörterbuch des Deutschen. 2. Aufl. Akademie

Verlag 1993. Online available at: www.dwds.de)

105 While digitizing these articles, as well as the rest of both dictionaries, a XML encoded version of these entries has been produced. The markup used to annotate these dictionaries is an adaptation of the TEI guidelines for printed dictionaries. The results are shown in fig. 5 and 6. The abstract entry structure has been specified by a RELAX NG schema (see section 6 below).

110 The entries consist of different parts. Both entries have a form section and a sense section. The form section contains information about the spelling of the headword (i.e. Bahnhof, Ski), including variants (e.g. Schi), its part of speech as well as the gender (e.g. ‘m.’) and additional grammatical information. The sense section groups all readings of the headword, in a hierarchical manner, i.e. there are main senses and sub-senses. The meaning description of
 115 ex. 1 makes use of a definition (e.g. ‘Gebäude am Halteplatz von Eisenbahnzügen’, tr. building located at regular stop points of railway trains), usage examples (e.g. vom Bahnhof abholen, tr. to pick up at the railway station) and citations.

In the second example the entry also contains an etymology section which informs the reader, in textual style, about the history of the described lexical unit, e.g. Norwegian and
 120 Old-Nordic.

The description above makes the tree-like structure of the dictionary entries obvious. However, at one point the article deviates from the strict hierarchical and acyclic model: there is a cross-reference in the etymology section of the second example (i.e. ‘s. das im Dt. etymologisch entsprechende *Scheit*’, tr. see the etymologically related German word *Scheit*),
 125 which points to another article in the same dictionary. Standards for dictionary (article) encoding take care of these so called “meso-structure” or “cross-reference structure” in dictionaries by providing reference mechanisms to uniquely identifiable elements (i.e. articles of even particular parts of it).

As we have seen, dictionary entries are highly structured objects where the various text
 130 components bear neither the same semantic nor the same internal organization. At the same time, representing a dictionary in digital format should preserve the linearity of its content, which is essential for human legibility. We thus need a *mark-up language* that copes with both aspects, while enabling adequate processability by machines.

135 3 SGML and XML

The eXtensible Markup Language (XML) has been designed by the World Wide Web

Consortium (W3C) in the end of the 1990ies to fulfill exactly the abovementioned needs in the context of web-based applications. It was elaborated as a simplification of the older Standard Generalized Markup Language (SGML), an ISO standard for structured documents published in 1988 (ISO 8879), as well as a generalization of mechanisms already present in the HTML language for presentation of online information.

XML basically introduces a syntax for marking up sections of a document by means of *opening* and *closing tags*, which form, together with the enclosed content what is called an *element*. For instance, if one wants to mark up in a dictionary entry that the string “f” should be tagged as belonging to the category “gen” (for gender), the following example is a so-called *well-formed* XML fragment:

```
<gen>f</gen>
```

In this example, “<gen>” is the opening tag, “</gen>” the closing tag and “f” the actual (here textual) content of the element. Note that there can also be empty elements, for instance “<pb/>” for indicating page breaks within a document, and elements with mixed contents, i.e. elements which contain child elements as well as textual content on the same level.

Furthermore, XML allows such bracketing information to be hierarchically embedded within one another to form complex marked-up structures. For instance, a structure grouping information about a meaning (<sense>) in a dictionary entry, based on a definition (<def>), and a cited example (<cit>, together with <q> for the cited text and <bibl> for the corresponding bibliographical source) may be sketched as follows (for reason of simplicity, the content of the elements is represented by placeholders, see fig. 5 for a full-fledged example):

```
<sense>
  <def>...</def>
  <cit>
    <q>...</q>
    <bibl>...</bibl>
  </cit>
</sense>
```

Finally, the XML syntax allows one to add further information to a tagged section by means of so-called *attributes*, which appear within the opening tag of an XML element. Such attributes may either be specific to the encoding scheme, for instance to number the meanings in a dictionary entry as in:

170 `<sense n="1">...</sense>`

or generic to all XML applications when defined directly by the W3C consortium (indicated by means of a prefix to the element and attribute names; in the case described here, the prefix ‘xml:’ is used conventionally), as is the case for the indication of the working language as follows:

175 `<q xml:lang="fr"> Le langage des fleurs et des choses muettes!</q>`


or to provide unique identifier for any XML element (for instance entries in a dictionary) within a document, as follows:

`<entry xml:id="ent2352"> ...</entry>`

180 If ‘xml:id’ is of the data type ‘identifier’ (ID), the software which processes the document has to ensure that the same value of this type is assigned only once within a document. In other words: the value of ‘id’ has to be unique.

185 The important underlying characteristic of XML is that all marked-up content is forming a strict hierarchy, which in turn, from a computational point of view may be represented as a tree structure. For instance, the `<sense>` example above may be outlined as in figure 3, to delineate its underlying tree structure.

As it is the case in dictionary example ‘ski’ that contains a link to another dictionary entry, it is also possible in XML documents to deviate the strict tree-like structure. The attributes ‘id’ and ‘idref’ (i.e. reference to an id) are a way to handle this issue of cross-references.



190 Figure 3: tree representation of the above XML fragment

195 Contrary to the situation in relational databases, the actual possible structures for such documents are not strictly limited to one single tree, but may vary according to design choices, for instance when one wants to iterate over senses in a dictionary, or make senses to occur recursively within other senses. This is why the corresponding documents are often referred to as *semi-structured* in the literature (cf. Buneman, 1997).

In order to control which structures are allowed in the context of a given application, it is necessary to design a document grammar or *schema*, which will state which elements under which conditions may occur in a document. There are indeed several technical settings to do so which have been either defined specifically by the W3C consortium (DTD or W3C XML schemas) or within other standardization bodies such as ISO (e.g. RelaxNG schemas). Such schema (or document grammar) languages are based on the same principles, which can be summarized as follows:

- They restrict the number of so-called *valid* documents by stating which elements, attributes and data types are allowed;
- They define the *content model* of each element by indicating which element and text nodes, are allowed as its *children* and in which order and how many times they may appear;
- For attributes as well as for leaf elements (i.e. elements not containing further elements), they provide mechanisms to constrain their content to specific data types (e.g. number, date, URI) or lists of possible values.

Different schema languages allow to express different types of constraints.

In the examples above, e.g., it would be desirable to express the following constraint: ‘a gender element is only allowed if the value of the part of speech element or attribute equals “noun”’. However, in most schema languages it is not possible to model interactions between parts of the document where the value of one element or attribute puts constraints on the structure or the values of other elements. Nevertheless, there are schema languages which can impose such constraints and therefore restrict the set of well-formed (entry) structures, e.g. Schematron (ISO 19757-3)

The main issue at hand when designing an XML schema is to identify which information is relevant for, on the one hand, a proper identification of the content to be represented, and, on the other hand, to match the usage that one wants to achieve with the information. For instance, if one would only want to present information as web pages, with no intention whatsoever to provide stable and reusable representation, it may be tempting to just adopt the basic HTML syntax. For instance, one would thus indicate that part of speech information is to be presented in bold face by using the following HTML representation:

```
<b>noun</b>
```

On the contrary, if more than one possible usage is anticipated for the dictionary content, and above all one is determined to give a dedicated semantic to tags to be used, a more

230 explicit syntax (like the one of the TEI, see below) is to be adopted. This would make the
previous example look like:

```
<pos>noun</pos>
```

where “<pos>” refers to the well-known linguistic concept of “part of speech”.

235 The idea here is to abstract away from visual representations of dictionary entries, given
that XML comes with specific technical environments (CSS or XSLT stylesheets) dedicated
to the actual presentation or transformation of semi-structured documents.

4 Standardized approaches for XML-based representations of dictionary-entries

240 The most relevant document model for the digital representation of dictionary articles is
currently the dictionary component of the modular annotation scheme defined by the Text
Encoding Initiative (TEI, Sperberg-McQueen, C.M./Burnard 2004). As an alternative, another
standard dealing with the representation format for printed dictionaries , ISO standard 1951,
has emerged. Moreover, in 2008 ISO published the Lexical Markup Framework (LMF) as “a
common model for the creation and use of electronic lexical resources” (ISO 24613). While
LMF in general is described elsewhere in this volume (ch. 99) this section begins with a short
245 presentation of LMF’s Machine readable dictionary extension.

4.1 Lexical Markup Framework (LMF)

The ISO-standard LMF defines a meta-format for lexical data. LMS’s core package
explains the basic hierarchy of information of a lexical entry. Additionally, LMF defines,
amongst others, an extension for the representation of machine readable dictionaries.

250 Since LMF defines a meta-model for lexical entries it provides an abstract representation
format for lexical information. LMF’s main application area is NLP dictionaries but the ISO
standard also defines an extension for machine readable dictionaries. Fig. 4 shows an LMF
representation of the example entry “Ski” that makes use of the MDR extension.

```
255 <LexicalEntry>
  <Lemma id="l1">
    <FormRepresentation>
      <feat orthographyName="GermanVariantD" />
      <feat writtenForm="Ski" />
    </FormRepresentation>
    <FormRepresentation>
      <feat orthographyName="GermanVariantB" />
      <feat writtenForm="Schi" />
    </FormRepresentation>
  </Lemma>
  <Equivalent>
    <feat lang="German" />
    <feat writtenForm="Schneeschuh" />
  </Equivalent>
  <etymology>
    <etymon id="l2">
```

```

275 <form>
    <orth xml:lang="norwegian">ski</orth>
    <pos>commonNoun</pos>
</form>
280 <sense>
    <gloss>device for sliding on snow</gloss>
    <note>aus anord. sk.. ,Scheit,
    Schneeschuh`; s. das im Dt. etymologisch
    entsprechende Scheit.</note>
</sense>
</etymon>
    <etymologicalLink source="l2" target="l1">
    <etymologicalClass>loan word
    </etymologicalClass>
285 </etymologicalLink>
</etymology>
</LexicalEntry>

```

Figure 4: The dictionary entry presented in fig. 2 encoded using the LMF

290 The given XML representation is a linearization of a more general model, in LMF normally visualized as a diagram in the Unified Modeling Language (UML) format. The lemma ‘Ski’ is given with its two alternative spellings and with the ‘equivalent’ lemma that is included in the original dictionary entry. Moreover, the example provides ample etymological information. The treatment of the latter within LMF is described in more detail by Susanne
295 Alt (2006).

4.2. TEI specification for printed dictionaries

The Text Encoding Initiative (TEI; www.tei-c.org) is the most prominent international endeavour in the humanities, and probably beyond, to provide a set of reference guidelines for the representation of digital textual information. Initiated in 1987 as a forum of
300 major text archives worldwide, it has been an early adopter of SGML, than XML, and issued so far five editions of its guidelines, providing more than 500 elements for representing prose, poetry, drama, manuscript and of course, dictionary content. The TEI has evolved step by step to become a real infrastructure for specifying and customizing textual formats, while allowing a quick entry into its technology (Romary 2009). It is based on a specification language (ODD
305 – One Document Does it all), from which is generated, on the one hand, the full textual documentation, and on the other hand, the actual formal specification in several schema languages (DTD, RelaxNG, W3C).

One important mechanism available in the TEI infrastructure is a class management system allowing elements to be grouped together when they either bear a joint semantics or when
310 they occur in similar structural contexts. Classes are essential for providing an abstract entry point (e.g. all elements providing grammatical information in a dictionary entry) for the

specification of a given construct, onto which one can easily customize its own profile (e.g. for my own dictionary, I just need *part of speech* and *gender*).

The “print dictionary” chapter of the TEI guidelines has been designed, right from the beginning (Ide & Véronis, 1995) as a generic model which could, in turn, be customized to deal with the variety of form and structure that print dictionaries or born digital machine readable dictionaries may take. It has also been a compromise between providing a highly structured format for controlling dictionary content, and accounting for the variety of possible surface forms, especially in older dictionaries. This is why all elements belonging to the TEI dictionary chapter may occur within two main construct:

- An `<entryFree>` element, where each component is tagged independently from one another in the order they appear in the printed text;
- An `<entry>` element, which provides a highly structured organisation of content, somehow closer to a database-like organisation.

As an example, the freely organised representation of the beginning of our “Bahnhof” example would look as follows:

```
<entryFree><orth>Bahn- ...- hof</orth>, <gen>der</gen>, <def>Halle,
Gebäude am Halteplatz von Eisenbahnzügen</def>: <q>am B. sein</q>; <q>jmdn.
Am B. erwarten</q>...</entryFree>
```

Whereas the fully structured representation is depicted in figure 5.

```
<entry xml:id="E_b_437">
<form type="headword">
  <orth extent="suffix">-hof</orth>
  <gramGrp>
    <pos value="N"/>
    <gram type="determiner">der</gram>
  </gramGrp>
</form>
<sense xml:id="S_b_234" level="0">
  <def xml:id="N_b_140">Halle, Gebäude am Halteplatz von
Eisenbahnzügen</def>
  <cit type="example">
    <quote>am B. sein</quote>
  </cit>
  <cit type="example">
    <quote>jmdn. am B. erwarten, vom B. abholen, zum B. bringen</quote>
  </cit>
  <cit type="example">
    <quote>auf welchem B. kommt er an?</quote>
  </cit>
  <cit type="example">
    <quote>wie weit ist es bis zum B.?</quote>
  </cit>
  <cit type="example">
    <quote>der Zug rollte aus dem B.</quote>
  </cit>
  <cit type="example">
    <quote>im Gedränge des Bahnhofes</quote>
  </cit>
```

```

360   </cit>
<cit type="example">
  <usg type="reg">salopp</usg>
  <quote>ich verstehe immer nur B.</quote>
  <quote type="paraphrase">ich verstehe gar nichts</quote>
365 </cit>
</sense>
</entry>

```

Figure 5: The dictionary entry presented in fig. 1 encoded using TEI

One of the advantages of having these two possibilities at hand is that it is possible to use these in a row, in the context of a dictionary encoding workflow. It is thus possible to see <entryFree> as an element that will allow an initial surface mark-up of content preceding a second more elaborate encoding which will carve out the underlying structure from the same content.

We can now present in more details the major characteristics of the TEI dictionary principles. As mentioned in chapter 93, the TEI is conformant to the semasiological view on lexical structures and actually maps rather precisely onto the LMF model, which has been introduced in the preceding section. This view is reflected in the TEI model through the provision of two main constructs:

- A <form> element, grouping together all descriptive elements (phonetic, orthographic, grammatical) of a surface realisation of the dictionary entry;
- A <sense> element, which organises, both sequentially and hierarchically, the various meanings associated to the entry

This high-level distinction between information about the formal aspects of the described linguistic sign and the content or meaning aspects nicely reflects the widely used practice in producing lexical descriptions in the form of dictionary entry. A typical entry in a semasiological dictionary starts with an account of the formal features of the lexical sign, which are shared by all its senses.

In the case that the formal and / or etymological features of a linguistic sign vary even if the headword is the same, the TEI provides the <hom>-element to split an entry into two or more homographs.

The description of the individual senses or readings follows. Within a sense description, of course a part of the form description can be further specified or constrained. For example, a lexical unit which can in general be used in the plural form might not be used as such in a particular sense.

395

The <form>-element can be used to group the following types of information: spelling of a word, including alternative spellings (<orth>-element, see *Ski/Schi* in the entry example in fig. 1 and 6), other information related to the use of the word in written discourse, e.g. syllabification; pronunciation(s) of a word (<pron>-element) and other information related to the use of the word in spoken discourse, e.g. word stress; grammatical information, e.g. part of speech, gender, inflection, to mention only a few prominent examples. Each piece of information can be further qualified with a “usage”-marker (the <usg>-element). The scope of a description can thus be constrained to a certain regional variety or a certain diachronic stage of the described language. Grammatical features of the described linguistic sign, e.g. part of speech, inflections, subcategorization, can be grouped into a grammatical-group structure (the <gramGrp>-element). Iteration as well as nesting of the <gramGrp>-elements allow the dictionary writer to group features which are functionally related so that the change of one feature implies the change of the other feature. As an example, take a look at the gender and inflection of the German lexical unit “Gischt” (engl. “spin drift”). The gender varies, without a corresponding change in the meaning of the word. Since the inflection of the word depends on the gender, and it changes accordingly. For both inflectional paradigms there is a restriction on the use of the plural. This can be modelled, using the TEI specification, as follows:

```

415 <form type="headword">
    <orth extent="full">Gischt</orth>
    <gramGrp>
    <pos value="N"/>
    <gramGrp>
420 <gram type="determiner">der</gram>
    <gram type="genitive">-es</gram>
    <gram type="plural">-e</gram>
    </gramGrp>
425 <usg type="plev">auch</usg>
    <gramGrp>
    <gram type="determiner">die</gram>
    <gram type="genitive">-</gram>
    <gram type="plural">-e</gram>
430 </gramGrp>
    <gram type="singular-preferred">Pl. ungebräuchl.</gram>
    </gramGrp>
    </form>

```

The <sense>-element assumes a similar function, i.e. grouping of elements which are related and together describe a particular sense (or reading) of the lexical unit. Prominent information types are definitions (<def>-element), citations (<cit>-elements) and usage examples, often taken from corpora (<example>-element).

In fig. 5 we see an entry with one sense and one sub-sense. The sub-sense is embedded into the main sense. The sub-sense is further qualified by a usage-marker indicating the register of the use of the phrase (“salopp” ~ “colloquial”). Definitions as well as examples are given as a meaning description. Note that the example which is used to illustrate the subsense is itself accompanied by a paraphre. The latter explains the meaning of the phrase.

In fig. 6, a TEI-encoding of the second dictionary introduced in section 2 is presented.

```

445 <entry xml:id="E_S_646">
    <form type="headword">
      <orth extent="full" rend="sep:comma">Ski</orth>
      <usg type="time">seit Anfang 20. Jh. meist</usg>
450 <orth extent="full">Schi</orth>
      <gramGrp>
        <pos value="N"/>
        <gen value="masculine">m.</gen>
      </gramGrp>
    </form>
455 <sense xml:id="S_S_646" level="0">
      <def>Schneeschuh</def>
      </sense>
      <etym xml:id="W_S_646">
460 Übernahme (Anfang 19. Jh.) von gleichbed. norw. ski, aus anord. skið
      <def>Scheit, Schneeschuh</def> s. das im Dt. etymologisch entsprechende
      <ref type="dict" target="E_S_165">Scheit</ref>
      </etym>
    </entry>

```

Figure 6: The dictionary entry presented in fig. 1 encoded using the TEI

465

4.3. (LR) ISO 1951 [4-5pp]

ISO standard 1951 was initially designed in the seventies¹ to cope for the variety of codes used in printed dictionaries. It evolved in the nineties² to deal more widely with layout aspects of dictionaries. Following the natural trend to deal with the electronic encoding of print dictionaries, an attempt at putting together a more comprehensive model for these was made in the latest release dated in 2007³. Introducing explicitly in its scope the notion of representation of information, ISO 1951:2007 thus states: “it specifies a formal generic structure independent of the publishing media”. Even if ISO 1951 does not actually provide a useful encoding scheme for the representation of print dictionaries, its underlying kinship with the TEI makes it an interesting example to be described, both in order to identify its

475

¹ ISO 1951:1973 Lexicographical symbols particularly for use in classified defining vocabularies

² ISO 1951:1997 Lexicographical symbols and typographical conventions for use in terminography

³ ISO 1951:2007 Presentation/representation of entries in dictionaries -- Requirements, recommendations and information

weaknesses in providing a real generic model for dictionary representation and also observe some of the design choices at meso- and micro-structural levels. It is also a good reference point for eliciting transformation mechanisms, as we will see in section NNNN.

480 Figures 7 and 8 present an encoding of the entry for ‘Bahnhof’ and ‘Ski’ that we introduced previously in this chapter, which is based on an inferred XML representation made by the authors of this chapter⁴. The actual data categories exemplified here only represent a small fraction of the actual set described in ISO 1951, which covers all major information units needed for dictionary encoding. The examples provided here also allow one to perceive the general principles underlying the organisation of dictionary entries according to ISO 1951
485 principles.

```

490 <DictionaryEntry>
    <HeadwordCtn>
        <Headword>Bahn</Headword>
        <Headword>-hof</Headword>
        <PartOfSpeech value="N"/>
        <Note type="linguisticNote">der</Note>
    </HeadwordCtn>
495 <SenseGrp>
    <Definition>Halle, Gebäude am Halteplatz von Eisenbahnzügen</Definition>
    <Example>am B. sein</Example>
    ...
    <ExampleCtn>
500 <Register>salopp</Register>
    <Example>ich verstehe immer nur B.</Example>
    <Gloss>ich verstehe gar nichts</Gloss>
    </ExampleCtn>
505 </SenseGrp>
</DictionaryEntry>

```

Figure 7: The dictionary entry presented in fig. 1 encoded using the ISO 1951

```

510 <DictionaryEntry>
    <HeadwordCtn>
        <Headword>Ski</Headword>
        <TemporalUsage>seit Anfang 20. Jh. meist</TemporalUsage>
        <Headword>Schi</Headword>
515 <PartOfSpeech value="N"/>
        <GrammaticalGender>m.</GrammaticalGender>
    </HeadwordCtn>
    <SenseGrp>
        <Definition>Schneeschuh</Definition>
    </SenseGrp>
520 <Etymology> Übernahme (Anfang 19. Jh.) von gleichbed. norw. ski, aus anord. skīð
        <Definition>Scheit, Schneeschuh</Definition> s. das im Dt. etymologisch
        entsprechende <SeeAlso>

```

⁴ ISO 1951 actually provides no full XML schema corresponding to the examples provided in the text, nor does it point to a maintained repository where such information could be found.

525 `<Ptr href="E_S_165"/>Scheit`
`</SeeAlso>`
`</Etymology>`
`</DictionaryEntry>`

Figure 8: The dictionary entry presented in fig. 2 encoded using the ISO 1951

530

The ISO 1951 model is indeed based upon three generic mechanisms (called “compositional elements” to organise information within dictionary entries. These are:

- Containers, which allows one to refine a given data category (e.g. example) with complementary information (e.g. register, grammatical constraint) to contextualise the intended representation. In the example provided in figure 7, gloss information is given for the sentence “Ich verstehe immer nur B.”;
- Blocks, which provide a means to further decompose a given representational structure (e.g. a sense) into more precise sub-components (e.g. sense variations according to register information);
- Groups, which correspond to information compounds within a dictionary entry. There are indeed only two groups in the actual ISO 1951 specification, namely, SenseGroup and HomographGroup.

540 Containers are actually an essential mechanism for information modelling in general since it allows one to consider in a uniform manner all constructs related to a specific data category, allowing the occurrence of the category itself (Example) or its corresponding container (ExampleCtn) in exactly the same contexts.

550 On the contrary, blocks and groups (to a lesser extent) are less to be recommended in semi-structural information design since they are artificially preventing the actual recursivity of the corresponding construct. For instance, it is important in a dictionary structure, as elicited in the LMF, to account for the recursive nature of senses. In this respect, elements in ISO 1951 such as TranslationBlock or HomographGroup seem to be superfluous with regards SenseGroup, which could indeed be used as the unique (and recursive) structuring element for senses. This is in particular demonstrated by the fact that many occurrences of TranslationBlock in ISO 1951 appear as unique child of a SenseGroup.

555 As a whole ISO 1951 suffers from an incomplete design which makes it hardly usable in concrete applications. The need for such a standard is also not obvious in the context where the TEI has provided a well-maintained framework for representing print dictionaries since

twenty years and that many electronic dictionary projects have actually implemented it. We would actually think that the next revision of the standard should integrate the TEI tagset as the reference one for implementing the proposed model.

5 Processing XML-annotated dictionaries

5.1. XSLT Style-sheets

The World Wide Web Consortium has provided an XML-based “Stylesheet and Transformation Language” (cf. Kay, 2007). XSLT is a declarative language which is used to transform XML encoded documents into other (semi-structured) document. According to the W3C recommendation, “a transformation expressed in XSLT describes rules for transforming zero or more source trees into one or more result trees”. A transformation is achieved by a set of template rules. These rules associate a pattern, which matches nodes in the source tree (i.e. elements, attributes, textual nodes etc.) with a “sequence constructor”. In other words, XSLT relies on a formalism which addresses elements in a tree by the path which leads from the root of the tree (or any other node in that tree) to this node. For this purpose XSLT builds on XPath, a formal language which has also been provided by W3C (cf. Berglund et al., 2007). Nodes and sets of nodes are manipulated by sequence constructors. With such constructors, nodes can be, a.o.: a) be moved from one place in the source tree to another place in the target tree; b) deleted from the target tree. Additionally, new nodes can be inserted into the target tree.

Thus, XSLT transformations can be used to a) convert information in a lexical database to media-specific representation formats. Concerning (mobile) devices for which the transfer of data is expensive or the display is small, the publisher could decide to reduce an article to some essential pieces of information, e.g. grammar and definition(s). Other information of a more illustrative kind such as citations could be deleted from the target tree.

On web pages, complex articles could be presented in a compressed version and unfolded by the user who wants to see and consult more comprehensive articles. This has indeed been done on the website which feature the “Wörterbuch der deutschen Gegenwartssprache” (www.dwds.de); b) apply text compression techniques for a paper and print dictionary, where space is an expensive asset, and to do without this compression in a medium where nearly infinite storage space is available. For example, in a printed dictionary, inflectional information for nouns might be presented by the inflectional suffixes for the genitive singular and nominative plural, which has been done for decades now in paper dictionaries of the German language (e.g. *Bahnhof* <-es, -höfe>). In an electronic version of the dictionary the

whole paradigm, comprising of eight paradigmatic forms, could be presented in tabular form;
 c) filter certain parts of an article, e.g to provide data in response to a user request; d) convert
 information between formatting standards. A case of this kind is presented in the following
 595 section.

5.2.XSLT Style-sheets for converting TEI to ISO 1951

This section focuses on illustrating the transformation possibilities offered by XSLT in the
 specific case of transforming TEI encoding structures into ISO 1951 representations.
 600 Although not exhaustive, the transformation examples presented here cover most of the
 situations that can be encountered when doing similar processing on, say TEI based
 structures, either for filtering (as result to a query), transformation (to any other format), or
 presentation (e.g. in XHTML) purposes.

The rules (or templates in XSLT words) presented here are intended to be used within an
 605 XSLT stylesheet canvas for taking TEI compliant entries as input and generating ISO 1951 as
 output. To this aim, the root element of the stylesheet will appear as follows:

```

  610 <xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:tei="http://www.tei-c.org/ns/1.0" version="1.0">
  <xsl:output encoding="UTF-8" method="xml"/>
  ...
  </xsl:stylesheet>
  
```

where, beside the namespace declaration needed for the XSLT instructions proper, the TEI
 namespace is declared (prefix: tei) to map onto all encountered TEI elements. We can also
 615 note how the first child element of <xsl:stylesheet> (xsl:output) states that the output result
 will be XML data with characters encoded in the UTF-8 (8-bit framed Unicode encoding).

In the simplest case, an XSLT transformation will take a simple element, usually
 corresponding to an elementary data category, and isomorphically bring its content into the
 equivalent (in our ISO 1951 transformation use case) or associated (when presenting the
 620 content in XHTML for instance) construct. For example:

```

  625 <xsl:template match="tei:gen">
  <GrammaticalGender>
  <xsl:apply-templates/>
  </GrammaticalGender>
  </xsl:template>
  
```

transforms the <gen> element from the TEI namespace into an ISO 1951
 <GrammaticalGender> element.

The same type of transformations not only apply at the level of elementary data categories,

630 but also, in a very simple manner, for mesoscopic objects as in the following example transforming the generic (and recursive) <sense> element in the TEI into the group <SenseGrp>:

635

```
<xsl:template match="tei:sense">
  <SenseGrp>
    <xsl:apply-templates/>
  </SenseGrp>
</xsl:template>
```

640 As is the case in any recursive transformation, and can already be felt here, such rules presuppose that all transformations occurring before or after the actual firing of the rule are adequately described.

Some slightly more elaborated rules may be needed when data categories between the two models to be mapped do not exactly match, i.e. the underlying representation models do not have the same level of granularity. In such cases, specific tests (respectively, constraint
645 generations) have to be implemented in the corresponding templates.

The two cases actually occur in our TEI to ISO 1951 example. Typically, both models do not account for the indication of headword in a dictionary in the same manner. The TEI introduces a generic <form> element that can be, through the appropriate use of the ‘type’ attribute, be further constrained to indicate whether the actual object being represented is the
650 headword or an inflected form. On the contrary ISO 1951 has a specific element (or rather container <HeadwordCtn>) to this purpose. The corresponding rule, with a test on the ‘type’ attribute thus appears as follows:

655

```
<xsl:template match="tei:form[@type='headword']">
  <HeadwordCtn>
    <xsl:apply-templates/>
  </HeadwordCtn>
</xsl:template>
```

660 We also observe this case for the generic TEI element providing usage constraints, which, depending on its type attribute (e.g. ‘time’, ‘reg’) would map to specific ISO 1951 elements (resp. <TemporalUsage>, <Register>).

Conversely, whereas the TEI has a generic <gram> element for supplementary grammatical features (in our “Bahnhof” example, the provision of the appropriate determiner), ISO 1951 relies on a general purpose <Note> element to encompass such cases.
665 The transformation rule appears in such cases as follows:

```
<xsl:template match="tei:gram">
  <Note type="linguisticNote">
    <xsl:apply-templates/>
```

670 </Note>
</xsl:template>

The type of situations presented so far actually cover nine out of ten templates in a full TEI to ISO 1951 stylesheet. This shows how uncomplicated it is to derive such stylesheets by lexicographers, as opposed to the computational overhead that would result from the use of a
675 more traditional programming framework. Still, there are cases where additional types of transformations are needed to cope with more in-depth discrepancies between the two models.

Just to illustrate this on one specific case, let us consider the generation of container constructs in ISO 1951 out of the generic citation object (<cit>) in TEI. This combines two specific aspects. On the one hand, <cit> is typed when used to represent examples proper (as
680 opposed to, for instance, translations). On the other hand, <cit> systematically contains a generic <quote> element for the embedded portion of exemplifying text, which may, or not, be accompanied by additional refinements. The mapping onto an example container (<ExampleCtn>) or a simple example element (<Example>) will depend on a specific test on the number of children that the <cit> element contains. The corresponding rules shows as
685 follows:

```
690 <xsl:template match="tei:cit[@type='example']">
  <xsl:choose>
    <xsl:when test="child::*[2]">
      <ExampleCtn>
        <xsl:apply-templates/>
      </ExampleCtn>
    </xsl:when>
    <xsl:otherwise>
      <xsl:apply-templates/>
    </xsl:otherwise>
  </xsl:choose>
695 </xsl:template>
```

Furthermore, the embedded <quote> element, since it is indeed a generic quotation object
700 in the TEI framework, has to be further tested, to ensure that it actually maps onto an <Example> element. The corresponding rule would thus look like:

```
705 <xsl:template match="tei:cit[@type='example']/tei:quote">
  <Example>
    <xsl:apply-templates/>
  </Example>
</xsl:template>
```

As a whole, one can see that beyond the technicalities of XSLT, the drafting of a mapping
710 stylesheet proves to be the best tool for the precise comparison of two models having similar scopes, as is the case for the TEI and ISO 1951. Moreover, it produces an actual tangible

result that can be used in several interoperability scenarios when the interface between the two models is actually at stakes.

6. The use of schemata for consistency control

715 We have seen so far that markup languages are an excellent tool to separate the layout features of a text, e.g. a dictionary article, from its logical structures. Furthermore, with well-chosen names for elements and attributes, it is possible to make the meaning of the containing elements and attribute values explicit. With the mechanism of assigning namespaces to elements and attributes, it is even possible to provide separate pages with explicit definitions for the elements and attributes, an additional information source to which other developers
720 and users can refer. We have uses examples of namespaces in the XSLT examples provided in section 5.2. The label “tei:”, which prefixes elements and attributes, is linked to an information page about the element and attribute examples (`xmlns:tei="http://www.tei-c.org/ns/1.0"` in the example above).

In this context it is worth mentioning an initiative of ISO to provide a “Data Category
725 Registry” (cf. ISO12620:2009) through which canonical definitions should be provided to the most widely used linguistic categories (e.g. parts of speech, semantic cases, lexicographic field labels). In the future it will be possible to refer to a certain category in this registry by prefixing an element name (e.g. “pos”) with a namespace signifier for the DCR. Everyone reading the document can thus look up the canonical definition of the signified concept.

730 Document grammars like XML schemata or Relax NG schemata can also be used to control consistency during the compilation of dictionary articles. We will illustrate this with the example of the (Relax NG) schema (cf. ISO/IEC 19757-2) which is being used in the (retro-)digitization and revision of the “Wörterbuch der deutschen Gegenwartssprache”. It is well-known that the feature of (grammatical gender) of nouns can be expressed in different
735 ways. One can use (at least in German dictionaries) the determiner which precedes the noun in the nominative singular (‘der’, ‘die’ and ‘das’, resp.) or the Latin names of the genders (‘Maskulinum’, ‘Femininum’, ‘Neutrum’). The latter could be abbreviated in several ways (e.g. ‘f.’, ‘fem.’ ‘femin.’ for the feminine gender), and this is what is often done in paper and print dictionaries, mainly to save space.

740 In the following, we present the content model of the “gramGrp” (= grammar group) element, specified in the Relax NG schema.

```
grammatical-description = element gramGrp {
    ...
    , (grammatical-atom-pos *
```

```

745 & grammatical-atom-number ?
      & grammatical-atom-gender *
      & grammatical-atom *
      & usage-description *
      & (pronunciation-description
750 | diminutive-description
      | abbreviation-description
      | variant-headword-description
      | irregular-orthography-description
      ) *
755 ...
      ) *
      }

```

Let us have a closer look at the “grammatical-atom-gender” item which is highlighted in the above extract.

760 The abstract label “grammatical-atom-gender” is mapped to an element name “gen” which contains the gender values on an abstract as well as on the surface level

```

      grammatical-atom-gender = element gen {
        attribute value
765 { 'masculine' } , ('m.' )
        |(attribute value
          { 'feminine' } , ('f.' )
        |( attribute value
          { 'neuter' } , ('n.' )
770 }

```

The attribute values (‘masculine’ etc.) can later be matched to the corresponding categories of the “Data Category Registry” (see above). The schema, on the other hand, restricts the set of possible surface values to exactly one per category. Thus, the fragment presented below is valid,

```

780 <gramGrp>
      <pos value="N"/>
      <gen value="masculine">m.</gen>
    </gramGrp>

```

while the following, slightly revised fragment is not valid.

785

```
<gramGrp>
  <pos value="N"/>
  <gen value="masculine">masc.</gen>
</gramGrp>
```

790

Of course, it is the responsibility of the dictionary producer to ensure that the data are validated and unwanted abbreviations as in the second example are detected and corrected. Such a validator⁵ can and should of course be a component of a lexicographer's workbench. The schema is only a means to enforce a consistent encoding. It is most efficient in situations where closed vocabularies – as values of attributes or as textual content of elements – can be predefined.

795

When it comes to deriving a representation of the data for a particular medium, either the long form, i.e. the value of the attribute ('masculine'), or the abbreviated textual content of the element ('m') could be selected.

800

With schemata we therefore have a powerful tool which supports the process of the production of lexical entries by maintaining consistency over a probably very large portion of text.

7. Conclusion

805

We have seen that SGML and, more importantly, XML are adequate means for the encoding of the digitized versions of paper and print dictionaries. Entries in such dictionaries can be modelled as trees, i.e. as a hierarchically ordered set of functional text segments. On the other hand, the sequential order of these segments has to be preserved. With XML, tree-like structures can be modelled. Document grammars or schemata are used to constrain the number of valid document instances. Transformation languages like XSLT are a powerful and easy to handle means to serialize the functional text segments in various ways, depending on the type of media through which the data should be presented to the user.

810

Furthermore, transformations can be defined to convert data between different encoding standards.

While the TEI specification is well-known and widely used with the encoding of academic dictionaries, ISO 1951 might, despite its conceptual shortcomings, gain some influence in the

⁵ An example of a command based RELAG NG validator which can also be embedded in other software is jing, cf. jing:2008

world of commercial dictionary publishing.

815 With the tools and formalisms we have described here, it is possible to store lexical information in such a way it can be distributed over a large variety of media and visualised on many kinds of devices.

8. Literature

Alt, S. (2006), Data structures for etymology: towards an etymological lexical network,
820 *Bulag* n° 31, 2006

Berglund, A. et al. (2007), XPath Language 2.0. URL: <http://www.w3.org/TR/xpath20/>

Bray, T./Paoli, J./Sperberg-McQueen, C.M./Maler, E./Yergeau, F. (2004), Extensible Markup Language (XML) 1.0 (third edition). URL: <http://www.w3.org/TR/2004/REC-xml-20040204/>.

825 Peter Buneman (1997), Semistructured data, Symposium on Principles of Database Systems archive, Proceedings of the sixteenth ACM SIGACT-SIGMOD-SIGART symposium on Principles of database systems, Tucson, Arizona, United States, 117 – 121.

Clark, J. (ed., 1999) XSL Transformations (XSLT). Version 1.0. W3C Recommendation. <http://www.w3.org/TR/1999/REC-xslt-19991116>.

830 Clément, L./de la Clergerie, É. (2005), MAF: A morphosyntactic annotation framework. In: Proceedings of the 2nd Language and Technology Conference (LT'05), Poznan, 90–94.

Dublin Core Metadata Initiative (2006)

<http://dublincore.org/>

Ejarvec, T./Ide, N. (1999) Markup Enhancement: Converting CEE dictionaries into TEI, and beyond. In: Kiefer, F./Kiss, G./Pajzs, J. (eds.) Papers in Computational Lexicography COMPLEX'99 Linguistics Institute, Hungarian Academy of Sciences, Budapest, pp. 211-217

Goldfarb, C./Rubinsky, Y. (1991), The SGML Handbook. Oxford:OUP.

Ide, N./Kilgarriff, A. /Romary, L. (2000), A Formal Model of Dictionary Structure and Content. In: Proc. Euralex 2000, pp. 113-126.

840 Ide, N./Véronis, J. (1995), Encoding dictionaries. In: Computing and the Humanities, 29(1995)1-3, pp. 1-25

Ide, N./Véronis, J. (1995), Encoding dictionaries. In: Ide, N./Véronis, J. (eds.), The Text Encoding Initiative: Background and Context. Kluwer Academic Publishers:Dordrecht, pp. 167-180.

845 Ide, N./Véronis, J./Armstrong-Warwick, S./Calzolari, N. (1992) Principles for encoding machine-readable dictionaries. In: H. Tommola, K. Varantola, T. Salmi-Tolonen, Y. Schopp (eds) Proc. 5th Euralex International Conference, Tampere, Finland,

Studia Translatologica, Ser. a, 2, pp. 239-246

850 ISO 12620:2009, ISO TC 37 Terminology and Other Language and Content Resources:
Data Category Registry. URL: <http://www.isocat.org/>

ISO 19757-3 Information technology -- Document Schema Definition Languages (DSDL)
- Part 3: Rule-based validation -- Schematron

855 ISO 24613:2006. Language resource management— Lexical markup framework (LMF)
(2006). URL: http://www.tc37sc4.org/new_doc/ISO_TC37-4_N130_rev9_LMF_15March2006.pdf

ISO 8879:1986, Information processing -- Text and office systems -- Standard Generalized
Markup Language (SGML)

ISO/IEC 1951, ...

860 ISO/IEC 19757-2, Relax NG. URL: <http://www.relaxng.org/>
jing:2008, jing RELAX NG validator in Java. URL: <http://www.thaiopensource.com/jing.html>

Kay, M. (ed., 2007), XSLT 2.0. W3C Recommendation. URL:
<http://www.w3.org/TR/xslt20/>

865 McArthur, Tom (1988), *Worlds of Reference. Lexicography, Learning and Language from the Clay Tablet to the Computer*, Cambridge et al.

Romary, L. (2009), Questions & Answers for TEI Newcomers, In: *Jahrbuch für Computerphilologie* 10, Mentis Verlag - <http://hal.archives-ouvertes.fr/hal-00348372/fr/>

Sperberg-McQueen, C.M./Burnard, L. (2004), *TEI P4 guidelines for electronic text encoding and interchange - XML-compatible edition*. URL: <http://www.tei-c.org/P4X/>.

870 TEI (1999), *A Gentle Introduction to SGML*. URL: <http://quod.lib.umich.edu/cgi/t/tei/tei-idx?type=HTML&rgn=DIV1&byte=71769>

Tutin, A./Véronis, J. (1998) *Electronic Dictionary Encoding: Customizing the TEI Guidelines*. In: *Proc. Euralex 1998*.