

Supporting Heterogeneity in Data Driven Sensor Network Macroprogramming

Mahanth K. Gowda, Animesh Pathak

▶ To cite this version:

Mahanth K. Gowda, Animesh Pathak. Supporting Heterogeneity in Data Driven Sensor Network Macroprogramming. Second student research symposium on High Performance Computing (HPC 2009), Dec 2009, Kochi, India. inria-00458907

HAL Id: inria-00458907 https://inria.hal.science/inria-00458907

Submitted on 22 Feb 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Supporting Heterogeneity in Data Driven Sensor Network Macroprogramming


Mahanth K Gowda Institute of Technology, BHU, India

Animesh Pathak INRIA Paris-Rocquencourt, France



Introduction

Support for heterogeneity has been incorporated within a Macroprogramming framework. Policies for handling runtime and data routing for communication between nodes in a heterogeneous network were designed and implemented. Then, Macroprogramming support was added to compile Macroprograms and generate code for the heterogeneous network



ATaG for building temperature management

Heterogeneous Network Description

Our heterogeneous network consists of:-

- Sun SPOT sensor nodes
- PCs (ex. Laptops and Desktops)
- Base Stations (PCs attached with Sun SPOTs configured as base-stations)

There were two types of network:-

- IP based (for communication from PC to PC or Base Station)
- IEEE 802.15.14 based (from SPOT to SPOT or Base Station)



Target Heterogeneous Network

Challenges

- How to execute an integrated application on nodes with different lower level protocols for communication and task execution?
- How to write an efficient macroprogram compiler to generate appropriate code for nodes in the heterogeneous network, depending upon their type?

Routing Overview

The network is organized as a two level hierarchy

- at the lower laver, we have Sun SPOTs.
- at the higher laver, we have both Base stations and PCs

Target nodes for data delivery are specified through the Logical Neighborhood (LN) specification

For heterogeneous network routing, we divide **LN** into

- RegionScope Part that specifies physical scope (Room no, Floor
- LNScope the entire LN specification
- Routing at the lower layer is done with matching for LNScope in the routing table
- · Routing at the higher laver is done with matching for RegionScope. Upon such a matching, the routing is delegated to the lower layer in that corresponding region.





Illustration of Routing

Compilation Framework



Phases in Compilation

- Inputs: ATaG. Target Network Description, Imperative Code.
- Outputs: Deployable code for nodes in the network.

The various modules in the framework:

- ATaGParser: Parses the ATaG application specification.
- · Instantiated Task Graph Generator: Instantiates copies of each unique task in ATaG specification, ready for assignment.
- Task Allocator: Assigns the instantiated tasks to nodes in the network.
- Deployable Code Generator: Assigned Tasks are plugged into appropriate runtime templates corresponding to nodes. This creates code ready for deployment.

Integration with our Macroprogramming toolkit (Srijan)



ATaG specification with Srijan

Srijan is a toolkit to.

- Specify macroprograms
- . Compile them, and
- Deploy the generated code.

The work with supporting heterogeneity in data driven macroprogramming is successfully integrated with Srijan. We now have a Macroprogramming toolkit to specify, compile and deploy code on a heterogeneous network.

Experimental Results

With the toolkit, we were able to specify a WSN application, compile and deploy successfully on a network consisting of 2 Sun SPOTs, 2 Base stations(A laptop attached to a Sun SPOT configured as base station) and 1 PC (laptop). Code was generated for larger networks too.

Conclusion

- · LN routing algorithm was modified for rapid routing in higher layers of heterogeneous network.
- · Macroprogram compilation was reworked to support heterogeneous networks as targets for code deployment.
- · Currently ,work on energy optimizations in the routing protocol is under progress.

This work was partly supported by the EC FP7 CONNECT Project