



HAL
open science

Behavior Abstraction in Malware Analysis - Extended Version

Philippe Beaucamps, Isabelle Gnaedig, Jean-Yves Marion

► **To cite this version:**

Philippe Beaucamps, Isabelle Gnaedig, Jean-Yves Marion. Behavior Abstraction in Malware Analysis - Extended Version. 2010. inria-00509486v1

HAL Id: inria-00509486

<https://inria.hal.science/inria-00509486v1>

Preprint submitted on 23 Oct 2010 (v1), last revised 23 Oct 2010 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Behavior Abstraction in Malware Analysis

Extended version^{*}

Philippe Beaucamps, Isabelle Gnaedig, Jean-Yves Marion

INPL - INRIA Nancy Grand Est - Nancy-Université - LORIA
Campus Scientifique - BP 239 F54506 Vandoeuvre-lès-Nancy Cedex

Email: {Philippe.Beaucamps, Isabelle.Gnaedig,
Jean-Yves.Marion}@loria.fr

Abstract. We present an approach for malware detection combining both structural and behavioral approaches by working on an abstract representation of the behavior of a program. Our technique consists in abstracting traces of a program, by rewriting given subtraces into abstract symbols representing their functionality. Capture of traces is made dynamically by code instrumentation in order to handle packed or self-modifying malware. Suspicious behaviors are detected by comparing the trace abstractions to reference malicious behaviors. The expressive power of abstraction allows us to handle general suspicious behaviors rather than specific malware code and then, to detect malware mutations. We present and discuss an implementation validating our approach.

1 Introduction

Detection techniques of computer malware have traditionally relied on a combination of both static and dynamic analysis. A shortcoming of static analysis, however, is the general intractability of knowing in advance the program code. Packing and obfuscation techniques typically capitalize on this intractability to prevent the reconstruction of the program code. Alternatively, structural and behavioral techniques, which are more robust and reliable, may be used to guard against code protection and code transformation. These techniques rely on the analysis of the program structure and its behavior rather than the program binary code. This ensures an independence from basic syntactic modifications or from packing techniques and hence offers more resilient detection.

Structural techniques analyze the control flow graph representing the program, by assuming that its structure remains untouched. They compare it to control flow graphs of known malware using static analysis [10], sub-graph isomorphism [9], tree automata [6] or similarity measures [12,4,18]. Unfortunately, these techniques are not resilient to functional polymorphism, of which malware variants are a form. Such polymorphism alters the way some behavior is carried out and often impacts the structure of the control flow graph.

^{*} This work has been partially supported by the High Security Lab of the LORIA in Nancy: <http://lhs.loria.fr>

Conversely, behavioral approaches, first introduced in Cohen’s seminal work [11], monitor system calls and their arguments and have traditionally relied on the use of finite state machines [19,22]. Recent approaches [20] deal with functional polymorphism by preprocessing execution traces and transforming them into a high-level representation which captures their semantic meaning. But as these approaches deal with the execution trace being observed, they analyze a single behavior at a time. Subsequently, [16] proposed to use attribute automata but the cost is an exponential time complexity procedure.

Other behavioral approaches also use model checking techniques to track data [5,17,23]: they define behavioral signatures as temporal logic formulae, defined on a syntactic level. But none of these approaches considers functional polymorphism. Moreover they do not tackle either the problem of constructing a high-level view of the program, which limits their applicability.

Our goal here is to provide a generic framework for malware detection, abstract enough to be independent of the implementation of programs, resilient to variants and relying on general suspicious behaviors rather than on specific malware code. Unlike the approaches cited before, where only one trace at a time is observed, we intend to consider a set of traces representing the whole behavior of a program.

For this purpose, we present an approach combining both structural and behavioral approaches by working on an abstract representation of the behavior of a program. We propose a strong theoretical setting underpinned by the theory of formal languages and based on string rewriting systems and finite state automata. Abstraction is carried out with respect to behavior patterns defined as string rewriting systems. Behavioral detection is then carried out by automata intersection.

More precisely, execution traces of a program describe the capture of specific data such as program instructions, system calls with their arguments, or file systems and network interactions. The set of execution traces is then represented as an automaton, giving a structural view of the program with respect to the captured data: nodes are program locations and edges are transitions labelled by this data. An abstraction of this trace automaton is then constructed, with respect to a set of predefined behavior patterns defined as regular languages and describing high-level properties or actions such as a file operation, a hook installation or a data leak. This gives a representation independent of the program implementation. Finally, the abstract trace automaton is intersected with a malware database, composed of signatures representing known malicious behaviors.

Our technique offers two detection scenarios: identifying a program as suspicious when it performs some malicious action, like keylogging, or more particularly, detecting a behavior similar to a known malware. The model we use, combining string rewriting systems and finite state automata, allows us to detect very efficiently malicious behaviors with high level descriptions, that is in linear time. Detection speed can be tuned by setting the right tier of abstraction level. So the behavioral detection model we propose could be used inside a firewall for example.

After presenting the background in Section 2, we define behavior patterns in Section 3. Section 4 presents the abstraction mechanism of trace languages. Section 5 explains how to represent trace languages by trace automata and gives complexity bounds for computing abstractions. Section 6 formalizes the detection problem with its cost. Section 7 presents the implementation of our approach together with experiments. We conclude in Section 8.

2 Background

Let Σ be some finite alphabet. We denote by Σ^* the set of finite words on Σ . Subsets of Σ^* are called finite languages on Σ . The empty word is denoted by ϵ .

Let Σ' be some finite alphabet. The projection homomorphism which maps words of Σ^* to words of Σ'^* is denoted by $u|_{\Sigma'}$ for any $u \in \Sigma^*$ and is defined, for $a \in \Sigma$, by: $a|_{\Sigma'} = a$ if $a \in \Sigma'$ and $a|_{\Sigma'} = \epsilon$ otherwise. This definition is homeomorphically extended to the projection homomorphism on Σ' , noted $L|_{\Sigma'}$, of a language L on Σ .

A finite state automaton \mathcal{A} on an alphabet Σ is a tuple (Q, δ, q_0, F) where Q is a finite set of states, $\delta : Q \times \Sigma \rightarrow Q$ is a transition relation, $q_0 \in Q$ is an initial state, and $F \subseteq Q$ is the set of final states. A run of \mathcal{A} on a finite word $w = a_0 a_1 \cdots a_n$ is a sequence of states $r = q_0 q_1 \cdots q_{m \leq n+1}$ such that: $\forall i \leq n, q_{i+1} \in \delta(q_i, a_i)$. The run r is successful if $m = n + 1$ and $q_m \in F$; in this case, w is said to be recognized by \mathcal{A} . The set of finite words for which there exists a successful run of \mathcal{A} is the language recognized by \mathcal{A} and is denoted by $\mathcal{L}(\mathcal{A})$. Languages which are recognized by some finite state automaton \mathcal{A} are called regular. The size of a finite state automaton A , denoted by $|A|$, is defined as the number of states of A .

For a given binary relation \rightarrow , we denote by \rightarrow^* its reflexive transitive closure.

A string rewriting system (SRS in short) is a triple (Σ, V, \rightarrow) , where V is a set of variables and \rightarrow a binary relation on $(\Sigma \cup V)^*$. A regular SRS is a 4-uple $(\Sigma, V, S, \rightarrow)$, where $S \in V$ and the relation \rightarrow is generated by rules of the form $a \rightarrow A$, $aA \rightarrow B$ and $\epsilon \rightarrow A$, with $a \in \Sigma$, $A, B \in V$. The language recognized by a regular SRS is the set $\{u|u \in \Sigma^*, u \rightarrow^* S\}$. Languages recognized by a SRS are exactly the regular languages. The size of a regular SRS R , denoted by $|R|$, is defined as the number of variables of V .

3 Behaviors

We now introduce a model of abstract machine from which we define notions of machine trace and behavior. An abstract machine \mathcal{M} consists of the triple $(\mu_0, IP_0, \rightarrow)$ where (μ_0, IP_0) is an initial configuration of \mathcal{M} and \rightarrow is a transition function from *Configurations* to *Configurations*, where *Configurations* denotes the set of configurations of \mathcal{M} .

A configuration of \mathcal{M} is a couple (μ, IP) where:

- $\mu : \text{Addresses} \rightarrow \text{Data}$ represents the memory of \mathcal{M} . *Addresses* is the set of addresses of \mathcal{M} and *Data* is a set of values; both are subsets of \mathbb{N} ,

– $IP \in \text{Addresses}$ is the instruction pointer.

Thus, we have $(\mu, IP) \rightarrow (\mu', IP')$ if the machine \mathcal{M} executes the instruction at address IP in memory μ . The memory μ' is the memory obtained after executing the instruction beginning at $\mu(IP)$ and IP' is the address of the next instruction to execute. A program is a set of instructions. An *execution* of an abstract machine \mathcal{M} is a finite sequence:

$$(\mu_0, IP_0) \rightarrow (\mu_1, IP_1) \rightarrow \dots \rightarrow (\mu_n, IP_n).$$

In our scenario, the configuration (μ_0, IP_0) is the initial configuration. A program is loaded into μ_0 at the address pointed by the instruction pointer IP_0 . So, at the beginning of an execution, a program is executed inside an initial environment (also) given by μ_0 . Then, the program is run. At each step, we see interactions with the "outside" through the memory. Though our model of abstract machine can only represent single-threaded programs, this formalization of communications is enough for our purpose.

The reader will notice that we focus on abstract machines rather than on programming languages. There are several reasons for this. First of all, our model allows us to talk about programming languages with several levels of abstraction. Second, in the context of malware, programs are generally self-modifying. Programs are treated as data objects and elements of *Data* are regarded as instructions. A program text is variable, which is not the usual point of view in semantics, see for example Gunter's textbook [15]. Moreover, low level instructions, like in the x86 case, are not of fixed size and a program can modify its code by instruction misalignment. So we think that our model of abstract machine is a right approach to underpin our study on malware behavior detection.

As said before, dynamic analysis and detection rely on capture and analysis of execution data. This data may be the sequence of instructions being executed, the sequence of system calls (i.e. calls to system code), etc. Other approaches may capture yet higher-level actions of a program, for instance network interactions, file system accesses, inter process communications (IPC), register usage statistics or any data that can be used to characterize a behavior. Our framework aims at dealing with any kind of the above data using an alphabet Σ .

We first formalize the capture of some execution data, represented by elements of Σ , in the machine \mathcal{M} .

Definition 1 (Capture operator). A capture operator wrt Σ is an operator $\pi : \text{Configurations} \rightarrow \Sigma \cup \{\epsilon\}$ which associates to some configuration the captured data, if any, and ϵ otherwise.

Note that in the general case, captured data of a configuration c_n may depend on the history of the execution i.e. on configurations $c_{i_1} \dots c_{i_k}$ for $i_1 \dots i_k \in [1..n-1]$ at previous times. This is needed for example to compute register usage statistics or to capture non atomic behaviors (for instance "smtp connection" which is the combination of a network connection and reception of the message "220 .* SMTP Ready"). For the sake of simplicity, for defining π , we do not consider $c_{i_1} \dots c_{i_k}$.

From now on, in our examples, we consider more specifically the operator capturing system calls.

Definition 2 (Execution trace). *Let \mathcal{M} be a machine, $e = c_1 \dots c_n$ an execution of \mathcal{M} and π a capture operator wrt Σ . Then $\pi(c_1) \dots \pi(c_n) \in \Sigma^*$ is the execution trace of the execution e of \mathcal{M} wrt π , denoted $\pi(e)$.*

In the following, we will call trace language of a machine \mathcal{M} with respect to the capture operator π , the set of execution traces of \mathcal{M} with respect to π . We denote it by $Traces_\pi(\mathcal{M})$, or simply $Traces(\mathcal{M})$ when π is clear from the context. We can now formally define the notion of behavior we want to detect in a program, with respect to some capture operator.

Definition 3 (Behavior pattern). *A regular behavior pattern \mathcal{B} is a regular language on Σ . We call simple behavior pattern an element of \mathcal{B} .*

A behavior pattern does not necessarily describe a malicious behavior in itself. It can describe an innocuous behavior – e.g. creating a process, opening a file, sending a mail – or a relevant behavior sequence, possibly modulo shuffling of independent actions. It can also represent a behavior which is shared by different malicious codes.

Example 1. Throughout this paper, we consider the example of the Allapple worm, a polymorphic network worm. A simplified excerpt of its code is given in Figure 5 of Appendix B. It contains three behavior patterns: the ping of a remote host, the opening of a Netbios connection (used for Windows shares) and the scanning of local drives. An example of execution trace of this excerpt is the following sequence of system calls:

```
...GetLogicalDriveStrings.GetDriveType.FindFirstFile.FindFirstFile.
FindNextFile...
```

This trace exhibits the behavior pattern which describes the scanning of local drives: `GetLogicalDriveStrings.GetDriveType.FindFirstFile`.

4 Trace abstraction

Given some machine, recall that our goal is to abstract its execution traces, by replacing concrete behavior patterns by more abstract representations, expressing their functionality.

Of course, this process could be repeated, like in Martignoni et al’s layered architecture [20]. A first layer would look up behavior patterns defined in terms of raw analysis data. A second layer would look up behavior patterns defined in terms of patterns from the first layer, and so on. Each new layer would be handled in the exact same way as the previous layers, except that the set of patterns and the alphabet (describing the underlying data) would be different for each layer. However, we will show in this section that our formalism encompasses the case of multiple layers.

In this section, we formally define the abstraction of a program trace wrt a behavior pattern. We start with a simple behavior pattern, then generalize this

abstraction to a regular behavior pattern and finally to a set of regular behavior patterns. We show that this abstraction can be viewed as a string rewriting process where each behavior pattern is replaced by a new specific symbol.

4.1 Abstracting with respect to a simple behavior pattern

Let $t \in \mathcal{B}$ be a simple behavior pattern for some \mathcal{B} . Let \mathcal{M} be a machine and $u \in \text{Traces}_\pi(\mathcal{M})$ an execution trace of \mathcal{M} for some π . Identifying occurrences of the pattern t in the trace u boils down to matching t to some subword of u .

Let $\lambda \notin \Sigma$ be a new symbol denoting the abstraction of our pattern t . We define $\Sigma' = \Sigma \cup \{\lambda\}$. Trace abstraction of u with respect to pattern t of Σ^* is defined by rewriting u with the string rewriting system R on Σ'^* , where R is composed of a single rewrite rule: $R = \{t \rightarrow \lambda\}$.

Let \rightarrow_t denote the rewriting relation induced by R , which rewrites substrings:

$$\forall u, v \in \Sigma'^*, u \text{ rewrites into } v, \text{ which is written } u \rightarrow_t v \text{ iff} \\ \exists u' \in \Sigma'^*, \exists u'' \in \Sigma'^*, \begin{cases} u = u' \cdot t \cdot u'' \\ v = u' \cdot \lambda \cdot u'' \end{cases}$$

In the context of malware analysis and malware detection, we are interested in traces where every occurrence of the pattern t has been replaced by the symbol λ . Thus abstraction of a trace is nothing but normalization of that trace with respect to the SRS R . Note that the normal form of a trace is not unique since R is generally not confluent.

Example 2. Returning to our excerpt of the Allapple.A worm, suppose we are interested in detecting the previously defined behavior of scanning local drives. Then $t = \text{GetLogicalDriveStrings.GetDriveType.FindFirstFile}$, and we define the abstraction symbol $\lambda = \text{SCAN_DRIVES}$. The execution trace in Example 1 is thus abstracted into:

`...SCAN_DRIVES.FindFirstFile.FindNextFile...`

The abstraction process of a trace can be generalized to a language of traces.

Definition 4 (Abstract trace language). *Let t be a simple behavior pattern, and \rightarrow_t its associated rewriting relation. The abstract form of the trace language L wrt t , denoted by $L \downarrow_t$, is defined by:*

$$L \downarrow_t = \{v \in \Sigma'^* \mid \exists u \in L, u \rightarrow_t^* v \text{ and } \nexists w \in \Sigma'^*, v \rightarrow_t w\}.$$

This abstraction is finally supported by the following theorem:

Theorem 1. *Let t be a simple behavior pattern and L be a trace language. If L is regular, then so is $L \downarrow_t$.*

The proofs of all theorems of the paper are given in Appendix A.

4.2 Abstracting with respect to a regular behavior pattern

In the previous section, a behavior pattern was simple in the sense that it was identified by a single word. However a behavior may often be achieved in different ways and malware writers may capitalize on this to perform functional polymorphism. For instance, creating a file may be processed using different sequences of instructions: detection will only be interested in the functionality expressed by these sequences, not in their implementation details. Thus, we now consider the case of a behavior pattern defined as a language, and more specifically as a regular language, as presented in Definition 3.

Normalization now consists in rewriting a trace language with the rules rewriting any simple pattern of a behavior pattern \mathcal{B} into λ , where \mathcal{B} is a regular language on Σ^* .

Relation $\rightarrow_{\mathcal{B}}$ is the rewriting relation induced by the regular SRS $(\Sigma, V, S, \rightarrow)$ recognizing \mathcal{B} , with the additional rewriting rule $S \rightarrow \lambda$, and defined on $(\Sigma' \cup V)^*$. Using the reflexive transitive closure of this relation, we extend trace language abstraction to abstraction with respect to a regular behavior pattern. The trace language L is normalized with $\rightarrow_{\mathcal{B}}$ into the abstract trace language denoted by $L \downarrow_{\mathcal{B}}$.

Theorem 2. *Let \mathcal{B} be a regular behavior pattern and L a trace language. If L is regular, then so is $L \downarrow_{\mathcal{B}}$.*

Example 3. One could extend the previous pattern `SCAN_DRIVES` to account for alternative system calls, e.g. calling `FindFirstFileEx` instead of `FindFirstFile`: `SCAN_DRIVES = GetLogicalDriveStrings.GetDriveType.(FindFirstFile+FindFirstFileEx)`. The corresponding SRS is given in Appendix B.

Regular patterns also prove useful to allow detection of behaviors interleaved with other unrelated or irrelevant actions. For instance, file writes may often be interleaved with other interactions with the system, e.g. string manipulation functions. When the behavior pattern is represented by an automaton, these actions are consumed by adding loops on actions that are not matched by any other transition.

4.3 Abstracting with respect to a set of regular behavior patterns

Finally, we generalize abstraction to a set of behavior patterns. Indeed, in practice, a suspicious behavior can be expressed as the combination of several behavior patterns \mathcal{B}_i , each of them abstracting into a distinct symbol λ_i . Each behavior pattern may be expressed both in terms of symbols from the alphabet Σ and in terms of abstraction symbols λ_i . Multi-layered abstraction, as considered in [20], is therefore encompassed in our model.

Let $\Gamma = \{\lambda_i\}_{1 \leq i \leq n}$ be a set of new symbols distinct from Σ . We now define $\Sigma' = \Sigma \cup \Gamma$. Let $\mathcal{C} = \{\mathcal{B}_i \mid \mathcal{B}_i \in \Sigma'^*\}_{1 \leq i \leq n}$ be a finite set of regular behavior patterns respectively associated to symbols λ_i .

As a relation $\rightarrow_{\mathcal{B}_i}$ is defined on $(\Sigma' \cup V_i)^*$, the relation $\rightarrow_{\mathcal{C}} = \bigcup_{1 \leq i \leq n} \rightarrow_{\mathcal{B}_i}$ is defined on $(\Sigma' \cup \bigcup_{1 \leq i \leq n} V_i)^*$. We extend trace language normalization to a set of regular behavior patterns, and the trace language L is now normalized with $\rightarrow_{\mathcal{C}}$ into the abstract trace language $L \downarrow_{\mathcal{C}}$.

Again, preservation of regularity is ensured, which is a fundamental property of our approach.

Theorem 3. *Let \mathcal{C} be a finite set of regular behavior patterns. If L is regular, then so is $L \downarrow_{\mathcal{C}}$.*

4.4 Projecting the abstract trace language on Γ

Once a trace language has been normalized wrt some set of behavior patterns, details that have not been processed by the normalization have to be pruned. A completely abstracted trace language is indeed expected to be defined on Γ , in order to be compared afterwards to reference abstract behaviors. This pruning operation is easily performed by projecting the abstract trace language on Γ .

Definition 5 (Γ -abstract trace language). *Let \mathcal{C} be a set of regular behavior patterns. Let L be a trace language for some machine \mathcal{M} . $\hat{L} = L \downarrow_{\mathcal{C}}|_{\Gamma}$ is called the Γ -abstract trace language of \mathcal{M} with respect to \mathcal{C} .*

Once the abstraction is complete, the simplified traces describe functionality-related actions and are consequently more robust and less complex. As they represent several different implementations of the same behavior, they allow to deal with functional polymorphism.

We can then compare the language of Γ -abstracted traces to the behavior of some known malware or to some generic malicious behavior defined on Γ .

5 Trace abstraction with finite state automata

The trace language $Traces_{\pi}(\mathcal{M})$ of a machine \mathcal{M} is generally undecidable or at least non-regular. Therefore, in the general case, no automaton can precisely describe it. However one can build a regular approximation of this trace language, which is usually twofold:

- the trace language is over-approximated, when replacing for instance $a^n \cdot b^n$ sequences (stemming from program loops for instance) by $a^* \cdot b^*$ sequences or when coping with obfuscation or dynamic analysis shortcomings. The resulting automaton then contains spurious traces (false positives).
This can be formalized in the following way. If $Traces_{\pi}(\mathcal{M})$ is over-approximated by L , then: $Traces_{\pi}(\mathcal{M}) \subseteq L$.
- the trace language is under-approximated when some hidden code path is not discovered or when some uninteresting path is discarded. The resulting automaton then misses some traces (false negatives).
This can be formalized in the following way. If $Traces_{\pi}(\mathcal{M})$ is under-approximated by L , then: $L \subseteq Traces_{\pi}(\mathcal{M})$.

Thus, an optimal trace automaton for \mathcal{M} must satisfy the following requirements: minimize error rates, i.e. false positives and false negatives, during detection and minimize the complexity of the automaton, hence the following definition.

Definition 6 (Trace automaton). *Given a machine \mathcal{M} , a trace automaton for \mathcal{M} wrt Σ is a finite-state automaton A on Σ such that:*

$$\exists S \subseteq \Sigma^*, S \subseteq \text{Traces}_\pi(\mathcal{M}) \wedge S \subseteq \mathcal{L}(A).$$

Thus a trace automaton represents a regular approximation of the trace language of some machine.

In order to construct the trace automaton of a machine, one may either use a collection of captured traces or reconstruct the program machine code from its binary representation. In the first case, the automaton is built in such a way that the captured traces correspond to a path in the trace automaton. In the second case, the machine code of the program can be reconstructed by a combination of static and dynamic analysis: it is then projected on the trace alphabet and the trace automaton is inferred from the code structure.

Example 4. Figure 1 shows a trace automaton for the Allapple.A excerpt representing the ping of a remote host and the scanning of local drives.




Fig. 1. Trace automaton for the Allapple.A excerpt

By Theorem 3, the abstraction problem for a regular trace language now boils down to computing an automaton recognizing the abstraction of this language. Construction of this automaton, we call abstract trace automaton, is described in the proofs of the following theorems. It consists in modifying the initial trace automaton by adding new transitions using the left hand sides of the rewriting rules and then intersecting it with an automaton recognizing the normal forms with respect to our rewrite system.

Thus, the abstract trace automaton may be more complex than the initial one, as shown on the Allapple.A worm example. If we abstract the trace automaton with respect to the `SCAN_DRIVES` pattern we defined, along with a new pattern `PING = IcmpSendEcho` describing the ping of a remote host, we obtain the automaton in Figure 2. The corresponding SRS is given in Appendix B.




Fig. 2. Abstract trace automaton for the Allapple.A excerpt

Theorem 4. Let A be a trace automaton and \mathcal{B} be a regular behavior pattern recognized by a regular SRS $R_{\mathcal{B}}$. Then an automaton of size $O(|A|)$ recognizing $\mathcal{L}(A) \downarrow_{\mathcal{B}}$ can be constructed in time $O(|A|^3 \cdot |R_{\mathcal{B}}|^2)$ and space $O(|A|^2 \cdot |R_{\mathcal{B}}|^2)$.

These complexity bounds do not change when abstracting with respect to a set of behavior patterns.

Theorem 5. Let A be a trace automaton and $\mathcal{C} = \{\mathcal{B}_i\}_{1 \leq i \leq n}$ be a set of behavior patterns recognized by regular SRSs $\{R_{\mathcal{B}_i}\}_{1 \leq i \leq n}$. Let $|\mathcal{C}| = \sum_{1 \leq i \leq n} |R_{\mathcal{B}_i}|$.

Then an automaton of size $O(|A|)$ recognizing $\mathcal{L}(A) \downarrow_{\mathcal{C}}$ can be constructed in time $O(|A|^3 \cdot |\mathcal{C}|^2)$ and space $O(|A|^2 \cdot |\mathcal{C}|^2)$.

The projection on Γ is linear in the number of transitions and thus does not impact complexity results.

The final abstraction of the Allapple.A excerpt, for $\Gamma = \{\text{PING}, \text{SCAN_DRIVES}\}$, is depicted in Figure 3.



Fig. 3. Γ -abstract automaton for the Allapple.A excerpt

6 Application to malware detection

Using the abstraction framework defined in Section 4, malware detection now consists in computing the abstract trace language of some machine and comparing it to a database of malicious behaviors defined on Γ . These malicious behaviors either describe generic behaviors, e.g. sending spam or logging keystrokes, or behaviors of specific malware. According to our abstraction formalism, malicious behaviors are sets of particular combinations of behavior patterns abstractions.

Definition 7. A malicious behavior on Γ , or signature, is a language on Γ .

More specifically, a malicious behavior describes combinations of patterns, possibly interleaved with additional patterns which are irrelevant in these combinations. For instance, we define the signature for the Allapple worm as the following regular language, which explicitly allows interleaving of patterns that do not match the upcoming pattern.

$$\text{LOCAL_COM_SERVER} \cdot (\Gamma \setminus \{\text{PING}\})^* \cdot \text{PING} \cdot (\Gamma \setminus \{\text{NETBIOS_CONNECTION}\})^* \cdot \text{NETBIOS_CONNECTION}$$

The automaton representing the signature of Allapple is given in Figure 4. Note that the `SCAN_DRIVES` pattern, which is present in the Γ -abstract trace automaton of the Allapple.A excerpt, does not appear here because the signature describes a common discriminating behavior exhibited by all samples of Allapple.




Fig. 4. Allapple signature

Definition 8. Let L_m be a malicious behavior on Γ . A machine \mathcal{M} with Γ -abstract trace language \widehat{L} exhibits the malicious behavior L_m iff there exists $v \in L_m$ and $u \in \widehat{L}$ s.t. $u = u_1vu_2$, where $u_1, u_2 \in \Gamma^*$.

Thus, \mathcal{M} exhibits the behavior L_m if some subword of an abstract trace of \widehat{L} is in L_m . Our *malicious database* is then a set \mathcal{D} of malicious behaviors. A machine \mathcal{M} is *malicious wrt* \mathcal{D} if it exhibits some malicious behavior of \mathcal{D} .

When the Γ -abstract trace language of \mathcal{M} is represented by an automaton A and L_m by an automaton A_m , \mathcal{M} exhibits the behavior L_m when the following holds. Let A'_m be the automaton recognizing the set of words containing a subword in L_m : A'_m is constructed from A_m by adding loops labelled by symbols of Γ on the initial state and the final states of A_m . Then \mathcal{M} exhibits the behavior L_m iff $\mathcal{L}(A) \cap \mathcal{L}(A'_m) \neq \emptyset$.

The malicious database is then represented by an automaton $A_{\mathcal{D}}$ which is the union of the automata A_m representing the signatures and may be minimized.

Theorem 6. Let \mathcal{D} be a set of regular malicious behaviors on Γ , recognized by an automaton $A_{\mathcal{D}}$. Let \mathcal{M} be a machine with Γ -abstract trace automaton A .

Then deciding whether \mathcal{M} is malicious wrt \mathcal{D} takes time: $O(|A_{\mathcal{D}}|^2 \cdot |A|^2)$.

Note that infection could be defined more intuitively and more generally in the following way: behavior patterns, instead of representing building blocks of

a malicious behavior, could directly represent a malicious behavior, which would then be defined on Σ .

Definition 9. *Let \mathcal{C} be a set of behavior patterns. Let \mathcal{M} be a machine with a trace language L . The machine \mathcal{M} is malicious if $L \downarrow_{\mathcal{C}} \neq \{\epsilon\}$.*

With the above detection model, we lose the expressive power of abstraction and the robustness of our detection model. But on the other hand, detection is performed by the sole process of normalization.

7 Implementation and experiments

7.1 Setting up the detection environment

We implemented the presented techniques in a tool which is able to capture the execution trace of a given program, to build its trace automaton, to abstract it with respect to a set of predefined behavior patterns and to compare it to a malware database.

Trace automata In order to avoid static analysis shortcomings and to ignore unreachable code, we use dynamic analysis to construct a trace automaton for some program loaded into a machine. The program is instrumented using Pin [3], which allows us to collect system calls and their arguments while the program is running. However, in order to reduce the size of captured traces and to capture the behavior of a program at a source code level, we only collect library calls made by the program code. Other instrumentation tools, like Dynamorio [1], could have been utilized with similar results. Collected system calls are restricted to the system calls occurring in behavior patterns. Instrumentation allows us to perform low-level analysis of the execution and to have a tight control over the program. In particular, our instrumentation tool handles threads, child processes and hooks, and features a simple data flow analyzer which relates system call data to previously used data.

When an execution trace has been captured, we construct a trace automaton by associating a state to each different Instruction Pointer (IP) responsible for making a system call. Threads are handled by associating a state to a set of instruction pointers. When additional execution traces are captured, they can be used to complete the trace automaton. Trace automata are manipulated using the OpenFST library [2].

Set of behavior patterns Behavior patterns are defined after observing malicious execution traces and extracting basic sequences likely to be part of a malicious behavior. These patterns often define usual interactions of the program with the system or the network. Once extracted, a sequence either defines a new behavior pattern or extends an existing pattern.

Malware database The malware database is a collection of malicious behaviors, which is built from a set of generic signatures along with signatures of known malware, constructed using their Γ -abstract trace automata. The resulting database automaton is minimized in order to speed up detection.

7.2 Experiments

To test our detection method, samples of malicious programs were collected using a honeypot¹ and identified using Kaspersky Antivirus.

We defined 40 behavior patterns, extended to allow data constraints expressing properties verified by the arguments of the system calls. These constraints are compatible with our formalism and amount to adding transitions to the trace automaton denoting verification of a constraint (see Appendix C.1). Examples of such patterns include writing to system files, persisting oneself in the Windows registry or browsing drives and files (see Appendix C.2).

Three experimentation scenarios were defined. In a first setting, we define signatures for given malware families, by analysis and Γ -abstraction of a few samples. Samples from different variants of each family are then compared to the signatures: several of these variants are new, i.e. they were not considered when defining the signatures. This allows us to test applicability of our approach and its robustness against mutation. In a second setting, a more general signature is defined for a common malicious behavior encountered in different malware families. Several malicious samples are then tested, in order to find out which samples exhibit this behavior. This allows us to test the expressive power of behavior abstraction. In a third setting, sane applications are tested, to ensure that the rate of false positives is low.

We tested the above settings on known malware families, among which Allapple, Virut, Agent, Rbot, Afcare and Mimail. In particular, our honeypot shows that Allapple, Virut and Agent are currently among the most active worms, which makes their analysis particularly relevant. Most samples were successfully matched to the defined signatures, while failures stemmed from technical shortcomings of our implementation or of dynamic analysis. Experiments results of the previous scenarii are given in Appendix C, along with a complete abstraction example for the Agent.ah worm.

8 Conclusion and future work

In this paper, we have presented a new malware detection approach combining structural and behavioral techniques, where malicious programs are identified using abstract representations of malicious behaviors. Programs to analyze, represented as trace languages, are abstracted by rewriting with respect to elementary behavior patterns, defined as regular string rewriting systems. Abstractions are then compared to a database of abstract malicious behaviors, which describe combinations of the former patterns.

¹ The honeypot of the Loria's High Security Lab.

Abstraction is the key notion of our approach. Providing an abstracted form of program behaviors and signatures allows us to be independent of the program implementation, to handle similar behaviors in a generic way and thus to be robust with respect to existing and future variants. The strength of our technique lies also in the fact that abstract malicious behaviors are combinations of elementary patterns: this allows us to efficiently summarize and compact the possible combinations likely to compose suspicious behaviors. Moreover, malicious behaviors are easy to update since they are expressed in terms of basic blocks. Behavior patterns themselves, as they describe basic functionalities, are easier to update than if they had described more complex behaviors.

We plan to extend our approach in several directions. The first one is concerned with data flow analysis. The behavior patterns we define are unable to express that the system calls they match are actually related. Data flow information would allow to address this question. While this issue is not very relevant when matching local behaviors (eg. writing data to a file), it becomes more important when specifying wider behaviors which spread over large execution sequences. Work is in progress to handle data flow by using model checking with temporal logic formulae with parameters.

The second extension is concerned with interleaved behavior patterns. When two behavior patterns are interleaved in an execution trace, our approach can only match one pattern out of the two since, while rewriting the first one, the second will be consumed. Although interleaving does not occur very often in practice, since common behavior patterns are small and not very prone to interleaving, we intend to propose non-consuming approaches to pattern abstraction.

Also, we would like to improve the construction of a trace automaton approximating a trace language. When it is built from execution traces, meaningless paths are created by interference between relevant paths. This increases the matching possibilities between the abstract trace automaton and the malicious signatures, which impacts the precision of the detection. A solution would be to duplicate function calls in the automaton when appropriate.

Lastly, captured traces do not give an exhaustive view of all possible executions and some interesting behaviors may only be observed when some conditions are met. We could use existing tools identifying these conditions. Sage [14] and BitScope [8] use symbolic execution to systematically discover new execution paths. Moser et al. [21] also address this problem in the malware context by monitoring how certain inputs impact the control flow and by instrumenting these inputs to drive the execution.

References

1. DynamoRIO. <http://dynamorio.org>.
2. OpenFST. <http://www.openfst.org/>.
3. Pin. <http://www.pintool.org>.
4. Martin Apel, Christian Bockermann, and Michael Meier. Measuring similarity of malware behavior. In *IEEE Conference on Local Computer Networks*, pages 891–898. IEEE, October 2009.

5. J. Bergeron, M. Debbabi, J. Desharnais, MM. Erhioui, Y. Lavoie, and N. Tawbi. Static detection of malicious code in executable programs. In *Symposium on Requirements Engineering for Information Security*, 2001.
6. Guillaume Bonfante, Matthieu Kaczmarek, and Jean-Yves Marion. Architecture of a morphological malware detector. *Journal in Computer Virology*, 2008.
7. Ronald V. Book and Friedrich Otto. *String-rewriting systems*. Springer-Verlag, London, UK, 1993.
8. David Brumley, Cody Hartwig, Zhenkai Liang, James Newsome, Dawn Song, and Heng Yin. Automatically identifying trigger-based behavior in malware. *Botnet Detection*, 36:65–88, 2008.
9. Danilo Bruschi, Lorenzo Martignoni, and Mattia Monga. Detecting self-mutating malware using control-flow graph matching. In *Conference on Detection of Intrusions and Malware & Vulnerability Assessment*, volume 4064 of *Lecture Notes in Computer Science*, pages 129–143. Springer, 2006.
10. Mihai Christodorescu, Somesh Jha, Sanjit A. Seshia, Dawn Song, and Randal E. Bryant. Semantics-aware malware detection. In *IEEE Symposium on Security and Privacy*, pages 32–46. IEEE Computer Society, 2005.
11. Fred Cohen. Computer viruses: Theory and experiments. *Computers and Security*, 6(1):22–35, 1987.
12. Thomas Dullien and Rolf Rolles. Graph-based comparison of executable objects. In *Symposium sur la Sécurité des Technologies de l'Information et des Télécommunications*, 2005.
13. Javier Esparza, Peter Rossmann, and Stefan Schwoon. A uniform framework for problems on context-free grammars. *Bulletin of the EATCS*, 72:169–177, 2000.
14. Patrice Godefroid, Michael Y. Levin, and David Molnar. Automated whitebox fuzz testing. In *Network Distributed Security Symposium*. Internet Society, 2008.
15. Carl A. Gunter. *Semantics of Programming Languages: Structures and Techniques*. MIT Press, 1992.
16. Grégoire Jacob, Hervé Debar, and Eric Filiol. Malware behavioral detection by attribute-automata using abstraction from platform and language. In *International Symposium on Recent Advances in Intrusion Detection*, volume 5758 of *Lecture Notes in Computer Science*, pages 81–100. Springer, 2009.
17. Johannes Kinder, Stefan Katzenbeisser, Christian Schallhart, and Helmut Veith. Detecting malicious code by model checking. In *Conference on Detection of Intrusions and Malware & Vulnerability Assessment*, volume 3548 of *Lecture Notes in Computer Science*, pages 174–187. Springer, 2005.
18. Christopher Kruegel, Engin Kirda, Darren Mutz, William Robertson, and Giovanni Vigna. Polymorphic worm detection using structural information of executables. In *International Symposium on Recent Advances in Intrusion Detection*, volume 3858 of *Lecture Notes in Computer Science*, pages 207–226. Springer, 2005.
19. Baudouin Le Charlier, Abdelaziz Mounji, and Morton Swimmer. Dynamic detection and classification of computer viruses using general behaviour patterns. In *International Virus Bulletin Conference*, pages 1–22, 1995.
20. Lorenzo Martignoni, Elizabeth Stinson, Matt Fredrikson, Somesh Jha, and John C. Mitchell. A layered architecture for detecting malicious behaviors. In *International symposium on Recent Advances in Intrusion Detection*, volume 5230 of *Lecture Notes in Computer Science*, pages 78–97. Springer, 2008.
21. Andreas Moser, Christopher Kruegel, and Engin Kirda. Exploring multiple execution paths for malware analysis. In *IEEE Symposium on Security and Privacy*, pages 231–245. IEEE Computer Society, 2007.

22. R. Sekar, M. Bendre, D. Dhurjati, and P. Bollineni. A fast automaton-based method for detecting anomalous program behaviors. In *IEEE Symposium on Security and Privacy*, pages 144–155. IEEE Computer Society, 2001.
23. Prabhat K. Singh and Arun Lakhotia. Static verification of worm and virus behavior in binary executables using model checking. In *Information Assurance Workshop*, pages 298–300. IEEE Press, 2003.
24. Ferucio Laurentiu Tiplea and Erkki Mäkinen. On the complexity of a problem on monadic string rewriting systems. *Journal of Automata, Languages and Combinatorics*, 7(4):599–609, 2002.

A Proofs

Theorems 1, 2 and 3 follow from Theorems 4 and 5.

Theorem 4. *Let A be a trace automaton and \mathcal{B} be a regular behavior pattern recognized by a regular SRS $R_{\mathcal{B}}$. Then an automaton of size $O(|A|)$ recognizing $\mathcal{L}(A) \downarrow_{\mathcal{B}}$ can be constructed in time $O(|A|^3 \cdot |R_{\mathcal{B}}|^2)$ and space $O(|A|^2 \cdot |R_{\mathcal{B}}|^2)$.*

Proof. Let $R_{\mathcal{B}} = (\Sigma', V, \rightarrow, S)$, where $\Sigma' = \Sigma \cup \{\lambda\}$. Suppose that L is a regular language. We denote by $post^*(L)$ the set of successors of elements of L by $\rightarrow_{\mathcal{B}}$:

$$post^*(L) = \{u \in (\Sigma' \cup V)^* \mid \exists v \in L, v \rightarrow_{\mathcal{B}}^* u\}.$$

Regularity of $post^*(L)$ when L is regular was proved by Book and Otto in [7]: methods for the construction of an automaton recognizing $post^*(L)$ are proposed in [13,24].

Now, $L \downarrow_{\mathcal{B}}$ is the set of words of $post^*(L)$ which are in normal form. Let $lhs(\rightarrow)$ be the set of left members of the rules of \rightarrow . Then, a word $u \in (\Sigma' \cup V)^*$ is in normal form if no subword of u matches a word of $lhs(\rightarrow)$, i.e.: $u \notin (\Sigma' \cup V)^* .lhs(\rightarrow) .(\Sigma' \cup V)^*$.

Thus, in the case where $L = \mathcal{L}(A)$, we get:

$$\mathcal{L}(A) \downarrow_{\mathcal{B}} = post^*(\mathcal{L}(A)) \cap \overline{(\Sigma' \cup V)^* .lhs(\rightarrow) .(\Sigma' \cup V)^*}$$

Esparza et al. proposed in [13] a method constructing an automaton A' recognizing $post^*(\mathcal{L}(A))$ in time $O(|R_{\mathcal{B}}|^2 \cdot |A|^3)$ and space $O(|R_{\mathcal{B}}|^2 \cdot |A|^2)$. A' has the same number of states as A , but is defined on $\Sigma' \cup V$.

On another hand, one may build an automaton recognizing the set $(\Sigma' \cup V)^* .lhs(\rightarrow) .(\Sigma' \cup V)^*$ in the following way.

First we need to construct a deterministic automaton recognizing $lhs(\rightarrow)$. Rules of \rightarrow have the form $a \rightarrow B$, $aA \rightarrow B$ or $S \rightarrow \lambda$, with $a \in \Sigma'$, $A \in V$, $B \in V$. Therefore we partition $lhs(\rightarrow)$ as $\{S\} \cup \bigcup_{1 \leq i \leq n} a_i V_i$, with $a_i \in \Sigma'$, $V_i \subseteq V \cup \{\epsilon\}$,

the a_i being mutually distinct. Start with an automaton containing an initial state i , a final state f and the transition $i \xrightarrow{S} f$. For each partition $a_i V_i$, add a new state s_i and transitions $i \xrightarrow{a_i} s_i$ and $s_i \xrightarrow{A} f$, with $A \in V_i$ and $A \neq \epsilon$. If $\epsilon \in V_i$, then define s_i as a final state. There are at most $|\Sigma'|$ partitions (one for each a_i) so the constructed automaton has $O(1)$ states and $O(|V|)$ transitions, which takes space $O(|V|)$. Furthermore, there are $O(|V|^2)$ rules of \rightarrow and each rule must be read in order to partition $lhs(\rightarrow)$, so this takes time $O(|V|^2)$.

From this automaton, we build a complete, deterministic automaton recognizing $(\Sigma' \cup V)^* .lhs(\rightarrow) .(\Sigma' \cup V)^*$. For each non final state s_i coming from

the partition $a_i V_i$, add transitions $s_i \xrightarrow{a} i$, for each $a \in (\Sigma' \cup V) \setminus V_i$. Finally, add a $\Sigma' \cup V$ loop on each final state. For each state, at most $|\Sigma' \cup V|$ transitions are added, so this step takes time $O(|V|)$ and space $O(|V|)$. The resulting automaton still has $O(1)$ states. Finally, by inverting the set of final states, we get its complement with the same number of states and transitions, in constant time and $O(|V|)$ space.

This whole procedure therefore constructs in time $O(|V|^2)$ and space $O(|V|)$ an automaton A'' with $O(1)$ states, which recognizes $\overline{(\Sigma' \cup V)^* .lhs(\rightarrow) . (\Sigma' \cup V)^*}$.

Finally, computing the intersection on alphabet $\Sigma' \cup V$ of two automata with respectively s and s' states takes time $O(s^2 \cdot s'^2 \cdot |V|^2)$ and space $O(s^2 \cdot s'^2 \cdot |V|)$ and yields an automaton with $s \cdot s'$ states.

Hence, with $s = |A'| = |A|$ and $s' = |A''| = O(1)$, the intersection of A' and A'' takes time $O(|A|^2 \cdot |V|^2)$ and space $O(|A|^2 \cdot |V|)$ and yields an automaton with $O(|A|)$ states.

Adding this all up, since we have $|V| = |R_{\mathcal{B}}|$, we get the following overall time complexity:

$$O(|R_{\mathcal{B}}|^2 \cdot |A|^3) + O(|R_{\mathcal{B}}|^2) + O(|A|^2 \cdot |R_{\mathcal{B}}|^2)$$

Similarly, the overall space complexity is:

$$O(|R_{\mathcal{B}}|^2 \cdot |A|^2) + O(|R_{\mathcal{B}}|) + O(|A|^2 \cdot |R_{\mathcal{B}}|)$$

Theorem 5. *Let A be a trace automaton and $\mathcal{C} = \{\mathcal{B}_i\}_{1 \leq i \leq n}$ be a set of behavior patterns recognized by regular SRSs $\{R_{\mathcal{B}_i}\}_{1 \leq i \leq n}$. Let $|\mathcal{C}| = \sum_{1 \leq i \leq n} |R_{\mathcal{B}_i}|$.*

Then an automaton of size $O(|A|)$ recognizing $\mathcal{L}(A) \downarrow_{\mathcal{C}}$ can be constructed in time $O(|A|^3 \cdot |\mathcal{C}|^2)$ and space $O(|A|^2 \cdot |\mathcal{C}|^2)$.

Proof. Let $R_{\mathcal{B}_i} = (\Sigma \cup \{\lambda_i\}, V_i, \rightarrow_i, S_i)$.

Let $V = \bigcup_{1 \leq i \leq n} V_i$ and S a new variable distinct from variables of V .

Let $\rightarrow_{\mathcal{C}} = \bigcup_{1 \leq i \leq n} (\rightarrow_i \cup \{S_i \rightarrow \lambda_i\})$.

Apply the proof of Theorem 4 to the regular SRS:

$$R_{\mathcal{C}} = (\Sigma \cup \{\lambda_i\}_{1 \leq i \leq n}, V, \rightarrow_{\mathcal{C}}, S)$$

The number of variables of $R_{\mathcal{C}}$ is precisely $|\mathcal{C}| = \sum_{1 \leq i \leq n} |R_{\mathcal{B}_i}|$, hence the result.

Theorem 6. *Let \mathcal{D} be a set of regular malicious behaviors on Γ , recognized by an automaton $A_{\mathcal{D}}$. Let \mathcal{M} be a machine with Γ -abstract trace automaton A .*

Then deciding whether \mathcal{M} is malicious wrt \mathcal{D} takes time: $O(|A_{\mathcal{D}}|^2 \cdot |A|^2)$.

Proof. Define A'_D to be the automaton built from A_D recognizing the set of words containing a subword in $\mathcal{L}(A_D)$ (note that $|A'_D| = O(|A_D|)$).

Then deciding whether \mathcal{M} is malicious with respect to \mathcal{D} boils down to testing emptiness of $\mathcal{L}(A'_D) \cap \mathcal{L}(A)$.

Intersecting both automata takes time $O(|A'_D|^2 \cdot |A|^2) = O(|A_D|^2 \cdot |A|^2)$ and yields an automaton of size $O(|A'_D| \cdot |A|)$. Testing emptiness of the resulting automaton is linear in its size, hence the result.

B Allapple.A example

```
void scan_dir(const char* dir) {
    HANDLE hFind;
    char szFilename[2048];
    WIN32_FIND_DATA findData;

    sprintf(szFilename, "%s\\%s", dir, " *.*");
    hFind = FindFirstFile(szFilename, &findData);
    if (hFind == INVALID_HANDLE_VALUE) return;
    do {
        sprintf(szFilename, "%s\\%s", dir, findData.cFileName);
        if (findData.dwFileAttributes & FILE_ATTRIBUTE_DIRECTORY)
            scan_dir(szFilename);
        else { ... }
    } while (FindNextFile(hFind, &findData));
    FindClose(hFind);
}

void main(int argc, char** argv) {
    HANDLE hIcmp;
    const char* icmpData = "Babcdef...";
    char reply[128];

    /* Behavior pattern: ping of a remote host */
    hIcmp = IcmpCreateFile();
    for(int i = 0; i < 2; ++i)
        IcmpSendEcho(hIcmp, ipaddr, icmpData, 10, NULL, reply, 128,
                    1000);
    IcmpCloseHandle(hIcmp);

    /* Behavior pattern: Netbios connection */
    SOCKET s = socket(AF_INET, SOCK_STREAM, 0);
    struct sockaddr_in sin = {AF_INET, ipaddr, htons(139)/* Netbios
    */};
    if (connect(s, (SOCKADDR*)&sin, sizeof(sin)) != SOCKET_ERROR) {
        ...
    }

    /* Behavior pattern: scanning of local drives */
    char buffer[1024];
    GetLogicalDriveStrings(sizeof(buffer), buffer);
    const char* szDrive = buffer;
    while (*szDrive) {
        if (GetDriveType(szDrive) == DRIVE_FIXED)
            scan_dir(szDrive);
        szDrive += strlen(szDrive) + 1;
    }
}
```

Fig. 5. Excerpt of the Allapple.A worm

<p style="text-align: center;"> <code>FindFirstFile</code> $\rightarrow A$ <code>FindFirstFileEx</code> $\rightarrow A$ <code>GetDriveType.A</code> $\rightarrow B$ <code>GetLogicalDriveStrings.B</code> $\rightarrow \text{SCAN_DRIVES}$ <code>IcmpSendEcho</code> $\rightarrow \text{PING}$ </p>

Fig. 6. SRS describing the patterns `SCAN_DRIVES` and `PING`

C Experiments

C.1 Behavior patterns with data constraints

In order to yield more relevant data, we define *behavior patterns with data constraints*. These patterns add constraints on system call arguments. For instance, instead of simply detecting a call to `NtOpenFile`, we may want to detect that the opened file is a system file by adding a constraint on the argument representing the file path. Similarly, instead of detecting any access to the registry, we may add a constraint on the key being accessed by requiring that it represents the `Run` key used for malware persistence. Enforcing these constraints is made possible by the capture of system call arguments. And more importantly, the extended patterns do not actually alter our formalism since it simply amounts to defining new symbols describing the validation of these constraints: the trace automata are finally modified by adding transitions labelled with these symbols whenever the specified constraints are verified.

C.2 Examples of behavior patterns

We describe some of the behavior patterns used in abstraction:

- writing to system files, which corresponds either to opening a file in a system directory and writing to that file, or to copying a file to a system directory;
- persisting oneself in the Windows registry, which corresponds to adding a subkey in the `Run` registry key or modifying the `AppInit_DLLs` registry subkey;
- browsing drives and files, which corresponds to retrieving the list of drives and scanning their files;
- communicating on IRC, which corresponds to sending IRC messages on a network connection, such as the mandatory “`NICK <mynickname>`”;
- looking for existing antiviruses, by checking registry entries and system services;
- setting up a system hook, using antidebug tricks, enumerating processes, querying access rights, e.g. to check for administrator rights. . .

C.3 Complete abstraction example of Agent.ah

Figure 7 shows the trace automaton of a thread of the Agent.ah email worm. It is restricted to system calls occurring in the behavior patterns. The trace automaton is then abstracted with respect to our set of 40 behavior patterns. Three of them were matched:

- TEST_IF_ADMIN: Tests if the user has administrator rights.
TEST_IF_ADMIN = IsNtAdmin + (OpenThreadToken + OpenProcessToken) .
AllocateAndInitializeSid [nSubAuthorityCount = 2, dwSubAuthority0 = 0x20, dwSubAuthority1 = 0x220] . AccessCheck
- ACQUIRE_DEBUG_PRIVILEGES: Asks for debugging privileges, in order to access process space of the running processes.
ACQUIRE_DEBUG_PRIVILEGES = LookupPrivilegeValue [lpName = "SeDebugPrivilege"] . (NtAdjustPrivilegesToken [NewState->Privileges[0]. Attributes = 2] + AdjustTokenPrivileges [NewState->Privileges[0]. Attributes = 2])
- ENUM_PROCESSES: enumerate running processes.
ENUM_PROCESSES = EnumProcesses + CreateToolhelp32Snapshot [dwFlags & 2 != 0] . Process32First

The resulting Γ -abstract trace automaton is shown in figure 8.

C.4 Results

In the first scenario, we constructed a signature for Allapple (Figure 4) and abstracted samples from the variants Allapple.a, Allapple.b, Allapple.d and Allapple.e. Three of them were successfully matched to the signature. The fourth variant made use of Windows services, which our instrumentation tool does not currently handle. The same scenario was repeated for Virut, with its variants Virut.ai, Virut.ak, Virut.ao, Virut.n, Virut.q and Virut.r. Detection was again successful for four of them, although another technical shortcoming was encountered, stemming from the inability of our tool to instrument injected code called in remote threads.

For the second scenario, the signature is a generic malicious behavior describing malware replication, defined by the following patterns:

- injection of its own code in foreign live processes;
- duplication on logical drives;
- duplication on network shares;
- creating a local COM server;
- registering an OLE component.

We then analyzed 39 variants from 16 malware families, among which: Agent, Mi-mail, Avron, Drefir. . . Samples of these variants were abstracted and compared to the previous behavior. Twenty of these variants were identified as exhibiting this behavior.

For the last scenario, we abstracted traces of common applications, among which: Notepad, Firefox, VLC. . . All of them failed to exhibit a malicious behavior from the previous experiments.




Fig. 7. Agent.ah partial trace automaton




Fig. 8. Agent.ah Γ -abstract trace automaton