

In B	rief			
bal				
Recover <b>3</b>	) human boo	<b>ly pose</b> from	monocular <i>in</i>	nage silhouette
– 3D pose	= joint angles			
use eithe	r individual in	nages or vide	o sequences	
ontribu	tions			
"Model-free	e" learning ba	sed approach	l	
no explic against re	it 3D model obust silhouet	— recovers tte descriptors	3D pose by	direct regressio
Sparse ker	nel regressor	trained using	human motio	on capture data
Regressior	based filterir	ng for resolvin	g reconstruct	ion ambiguities
Mean error	s of only 4-6 $^\circ$	per joint ang	le on test seq	uences
ethod				
Silhouette	➤ Descriptor	vector - BVN	A regressor →	3D pose vector
Cilh	ouotto	Docorir	tore	
Silh	ouette	Descrip	otors	
Silh hy Silh	ouettes	Descrip	otors	
Silh hy Silh • Relative	Ouettes ouettes ely simple and	<b>Descrip</b>	<b>btors</b>	
Silh hy Silh • Relative • Capture • Insensi	Ouettes ouettes ely simple and e most of the tive to surface	<b>Descrip</b> d low-level available pose e attributes (cl	<b>othing colour</b>	, texture)
Silh hy Silh • Relative • Capture • Insensit	Ouettes Ouettes ely simple and e most of the tive to surface	<b>Descrip</b> d low-level available pose e attributes (cl	<b>Distors</b> e information othing colour	, texture)
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu	Ouettes Ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d	<b>Descrip</b> d low-level available pose e attributes (cl by backgroun etails and dep	<b>Distors</b> e information othing colour d subtraction oth ordering a	, texture) / shadows are hidden
Silh Silh Silh Silh Silh Relative Capture Insensi Freque Ambigu	Ouettes Ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d	<b>Descrip</b> d low-level available pose e attributes (cl by backgroun etails and dep	otors e information othing colour d subtraction oth ordering a	, texture) / shadows are hidden
Silh Silh My Silh • Relative • Capture • Insensi • Freque • Ambigu	Ouettes Ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d ncoding ontext Hi	Descrip Descrip d low-level available pose e attributes (cl by backgroun etails and dep of local stoaram	otors e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh Silh Angle Silh	ouettes ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d encoding ontext Hi	Descrip Descrip d low-level available pose attributes (cl by backgroun etails and dep of local istogram	otors e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu	ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d encoding ontext Hi	Descrip Descrip d low-level available pose e attributes (cl by backgroun etails and dep of local istogram	otors e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu	ouettes ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d ontext Hi	Descrip Descrip d low-level available pose attributes (cl by backgroun etails and dep of local stogram	otors e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu	ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d encoding ontext Hi	Descrip d low-level available pose attributes (cl by backgroun etails and dep of local stogram	e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu obust e hape Co	ouettes ouettes ouettes ely simple and e most of the tive to surface htly distorted ity: internal d oncoding ontext H	Descrip Descrip d low-level available pose e attributes (cl by backgroun etails and dep of local stogram	e information othing colour d subtraction oth ordering a shape — s	, texture) / shadows are hidden
Silh Any Silh • Relative • Capture • Insensit • Freques • Ambigut obust e hape Co	ouettes ouettes ouettes ely simple and onst of the tive to surface htly distorted ity: internal d ontext Hi ontext Hi	Descrip Descrip d low-level available pose attributes (cl by backgroun etails and dep of local stogram	e information othing colour d subtraction oth ordering a shape — s (d) distribution in SC space	, texture) / shadows are hidden (e) vector quantize to get histogram
Silh hy Silh • Relative • Capture • Insensi • Freque • Ambigu Obust e hape C	ouettes ouettes ely simple and e most of the tive to surface htly distorted hity: internal d encoding ontext Hi coding	Descrip d low-level available pose e attributes (cl by backgroun etails and dep of local stogram	e information othing colour d subtraction oth ordering a shape — s (d) distribution in SC space	, texture) / shadows are hidden

#### Iraining and Test Data 3

- For the movements, we use real human motion capture data captures *typical* human movements, not just *possible* ones
- Synthesize silhouettes with POSER human modeller (Curious Labs) — somewhat artificial, but gives ground truth for testing, allows a wide range of training viewpoints.
- Also tested on real sequences of other people (without ground truth)

# **3D Human Pose from Silhouettes by Relevance Vector Regression**

# Ankur Agarwal and Bill Triggs

GRAVIR-INRIA-CNRS, Grenoble, France

# **Nonlinear Regression Model**

ven input: shape context histogram vector x esired output: 3D human pose vector y

$$\mathbf{y} = \mathbf{A}\mathbf{f}(\mathbf{x}) + \boldsymbol{\epsilon} \equiv \sum_{k=1}^{p} \mathbf{a}_{k} \phi_{k}(\mathbf{x}) + \boldsymbol{\epsilon}$$

 $f(\mathbf{x}) = (\phi_1(\mathbf{x}) \cdots \phi_p(\mathbf{x}))^\top$ : vector of scalar basis functions  $\phi_k(\mathbf{x})$  $\mathbf{A} \equiv (\mathbf{a}_1 \ \mathbf{a}_2 \ \cdots \ \mathbf{a}_p)$ : matrix of weight vectors  $\mathbf{a}_k$  to be learned : residual error vector

### Penalized Least Squares

timate A, given a set of training pairs  $\{(\mathbf{y}_i, \mathbf{x}_i) | i = 1 \dots n\}$ :

$$\mathbf{A} := \arg\min_{\mathbf{A}} \left\{ \sum_{i=1}^{n} \|\mathbf{A}\mathbf{f}(\mathbf{x}_{i}) - \mathbf{y}_{i}\|^{2} + R(\mathbf{A}) \right\}$$

i enter only via *feature vectors*  $\mathbf{f}_k(\mathbf{x}_i) = \phi_k(\mathbf{x}_i)$ .  $R(\mathbf{A})$  is a regularizer on  $\mathbf{A}$  to control overfitting

dge Regression:  $R(\mathbf{A}) = \lambda \|\mathbf{A}\|^2$ 

#### The Relevance Vector Machine

A Bayesian-motivated approach to regression and classification Uses a singular *power-law prior* to aggressively prune unneeded weights, giving *sparse solutions* A.

Regularizer:

$$R(\mathbf{A}) = \nu \sum_{a} \log \|a\|$$

 $-\nu$  is the pruning / shrinkage strength

-a can be the components, the columns, or the rows of A

#### **RVM Training Algorithm**

Initialize A with ridge regression. Initialize the running scale estinates  $a_{scale} = ||\mathbf{a}||$  for the components or vectors  $\mathbf{a}$ .

Approximate the  $\nu \log \|\mathbf{a}\|$  penalty terms with "quadratic bridges"  $(a/a_{scale})^2$  + const (the gradients match at  $a_{scale}$ );

Solve the resulting linear least squares problem in A;

Remove any components a that have become zero, update the cale estimates  $a_{scale} = ||\mathbf{a}||$ , and continue from 1 until convergence.

#### near bases

 $f(\mathbf{x}) \equiv \mathbf{x} \Rightarrow$  the RVM selects relevant silhouette *features*.













right leg left arm

- torso and neck -

#### Kernel bases

•  $\mathbf{f}(\mathbf{x}) = (K(\mathbf{x}, \mathbf{x}_1) \cdots K(\mathbf{x}, \mathbf{x}_n))^{\top}$  where  $K(\mathbf{x}, \mathbf{x}_i)$  is a kernel function instantiated at training examples  $\mathbf{x}_i$ 

• RVM selects relevant training *examples*, here only 6%





## Summary of Regressors' Performance

http://lear.inrialpes.fr {Ankur.Agarwal,Bill.Triggs}@inrialpes.fr

## **Pose from Static Images**

#### **Reconstruction on test sequence**

Spiral walking sequence not included in training data. Gaussian kernel regressor. Mean angular error per d.o.f =  $6.0^{\circ}$ 



### Sample reconstructions from real images



Original (middle) and new (bottom) viewpoints

# 6

# **Dynamics**

# **State-Sensitive Observation Update**

- ing state prediction

### Results



# Conclusion

- silhouettes

Work supported by European projects VIBES, LAVA and PASCAL





### **Pose from Video Sequences**

#### **Tracking Framework**

• Tracking reduces glitches caused by silhouette ambiguities

• Regression based filtering for dynamical prediction and observation update (x: 3D pose state, z: Silhouette descriptor)

• A second order global dynamical model suffices:

 $\check{\mathbf{x}}_t \equiv (\mathbf{I} + \mathbf{A})(2\mathbf{x}_{t-1} - \mathbf{x}_{t-2}) + \mathbf{B}\mathbf{x}_{t-1}$ 

Nonlinear kernel regressor "selects" observation update to apply us-

• Our full regression model also includes an explicit  $\check{\mathbf{x}}_t$  term to represent the direct contribution of the dynamics



• "Model free" methods for recovering 3D human pose from monocular

• Direct nonlinear regression of pose again robust shape descriptors • Tested different regression methods: ridge regression, RVM, SVM • Pose recovery from static images and image sequences