

Prescriptive and descriptive obligations in dynamic epistemic deontic logic

Guillaume Aucher, Guido Boella, Leendert van Der Torre

▶ To cite this version:

Guillaume Aucher, Guido Boella, Leendert van Der Torre. Prescriptive and descriptive obligations in dynamic epistemic deontic logic. AI Approaches to the Complexity of Legal Systems, Dec 2009, Rotterdam, Netherlands. pp.150-161. inria-00556080v1

HAL Id: inria-00556080 https://inria.hal.science/inria-00556080v1

Submitted on 17 Jan 2011 (v1), last revised 8 Sep 2013 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Prescriptive and Descriptive Obligations in Dynamic Epistemic Deontic Logic

Guillaume Aucher¹, Guido Boella², and Leendert van der Torre¹

¹University of Luxembourg. e-mail: guillaume.aucher@uni.lu, leon.vandertorre@uni.lu

² Università di Torino - Italy. email: guido@di.unito.it

Abstract. Normative sentences can be used to change or to describe the normative system, known as prescriptive and descriptive obligations respectively. In applications of deontic logic it is important to distinguish these two uses of normative sentences. In this paper we show how they can be distinguished and analysed in a dynamic epistemic deontic logic.

1 Introduction

Alchourrón and Bulygin [1,2] discuss the possibility of a logic of norms, which they distinguish from the logic of normative propositions. Roughly, the distinction between norms and normative propositions is that the former are prescriptive whereas the latter are descriptive. In the second sense, the sentence 'it is obligatory to keep right on the streets' is a description of the fact that a certain normative system contains an obligation to keep right on the streets. In the first sense this statement is the obligation of traffic law itself. This distinction goes back to an old philosophical problem discussed by Von Wright [15, 14], who was hesitant to call deontic formulas 'logical truths,' because "it seems to be a matter of extra-logical decision when we shall say that 'there are' or 'are not' such and such norms." Makinson [10] turns this fundamental problem into the central challenge in deontic logic, which led to new developments over the past decade such as deontic update semantics [13], input/output logic [11], imperative based deontic logic [8], and more.

The relevance of the distinction between prescriptive and descriptive obligations, and the related fundamental problem that norms do not have truth values, is not only theoretical and conceptual, but it has important practical implications for normative multi-agent systems. For example, assume that you ask the librarian of your university to get a journal paper available on the Springer web-site. The library has a list of journals published by Springer containing the journals for which the library has free access (either a journal of this list is on open access or the university subscribed to it). This list is updated every month but the librarian did not check it for some time, and so he does not know if the requested journal is on the list, although he should actually know it. He then logs on the journal and tries to download the paper. We consider two kinds of events corresponding to two different uses of obligations.

Descriptive use The Springer web-site informs the librarian that he should not pay to download any paper of this journal. As a result, the librarian now knows that this journal was on the list of journals for which the library has free access.

Prescriptive use The Springer web-site informs the librarian that he should not pay to download any paper of this journal because a new regulation has been issued by Springer today according to which the journal is now on open access.

As we see in this example, modeling the distinction between prescriptive and descriptive use of norms is useful for designing normative multi-agent systems. In this paper we therefore study the following question:

- How can the distinction between prescriptive and descriptive use of obligation be captured in a dynamic epistemic deontic logic?

We are going to introduce a general and expressive Dynamic Epistemic Deontic Logic [3] combining a simplified version of Castañeda's deontic logic [6] with a dynamic epistemic logic. This logic can express the conditional character of norms, study the interaction between epistemic and deontic notions, and model norm dynamics. These three features are fundamental to normative systems (and the representation of legal systems), and also to multi-agent systems as far as those are intended to model real life. First, in normative systems it is necessary to express realistic regulations, which have a conditional character. Secondly, communication is an essential part of normative and multi-agent systems, and this raises the issue of what it is permitted, prohibited or obliged to know by agents, for example, when modelling privacy regulations. Thirdly, normative multi-agent systems have a dynamic character, as witnessed by the second definition of normative multi-agent system provided in [5]. These last two issues, communication and dynamics are both useful for distinguishing when existing norms are communicated from the case where a norm is actually put into existence by a declaration, i.e., Alchourrón's distinction between the descriptive and prescriptive use of norms.

The paper is structured as follow. In Section 2 we introduce an epistemic deontic logic. In Section 3 we extend the logic by introducing update operators which change beliefs and norms, and show how the distinction between descriptive and prescriptive norms can be made in our logic if we map this distinction to the context of communication.

2 Epistemic Deontic Logic (EDL)

2.1 Propositions vs practitions

Because of its clear and natural distinction between propositions and practitions and its modal-like character, the well known deontic logic of Castañeda [6] lends itself very well to the introduction of an epistemic logic. Starting from a linguistic analysis, the insight of Castañeda's well known approach to deontic logic is to acknowledge the grammatical duality of expressions depending whether they are within or without the scope of deontic operators [6]. This leads him formally to introduce two sets of propositional letters: Φ^{ϕ} called propositions which cannot alone be the foci of deontic operators, unlike Φ^{α} called practitions. The former are usually expressed grammatically in the indicative form and the latter are usually expressed grammatically in the infinitive/subjunctive form. For example, "John is slowing down" in the indicative form is a proposition, but the same sentence in "it is obligatory that John slows down" in subjunctive/infinitive form is a practition. He then defines more general propositions \mathcal{L}_{DL}^{ϕ} and practitions \mathcal{L}_{DL}^{ϕ} as follows.

$$\mathcal{L}_{DL}^{\phi}: \phi ::= p \mid \phi \wedge \phi \mid \neg \phi \mid O\alpha$$

$$\mathcal{L}_{DL}^{\alpha}: \alpha ::= \beta \mid \neg \alpha \mid \alpha \wedge \alpha \mid \alpha \wedge \phi \mid \phi \wedge \alpha$$

where β ranges over Φ^{α} and p over Φ^{ϕ} . We define the language $\mathcal{L}_{DL} = \mathcal{L}_{DL}^{\phi} \cup \mathcal{L}_{DL}^{\alpha}$, whose formulas are generally denoted ϕ^* . In the sequel, $P\alpha$ is an abbreviation for $\neg O \neg \alpha$. $O\alpha$ reads ' α is obligatory' and $P\alpha$ reads ' α is permitted'.

We now propose a semantics based on modal logic which is equivalent to the one of Castañeda, in the sense that any 'Castañeda'-model [6] can be transformed into a DL-model satisfying the same formulas, and vice versa.

Definition 1. A DL-model M is a tuple M=(W,D,V) where W is a non-empty set of possible worlds, D is a serial accessibility relation on W and V is a valuation which assigns to each propositional letter $p^* \in \Phi^{\phi} \cup \Phi^{\alpha}$ a subset of W, such that for all $w \in W$, all $p \in \Phi^{\phi}$,

$$V(p) \cap (D(w) \cup \{w\}) = D(w) \cup \{w\} \text{ or } \emptyset$$
 (*)

Let M = (W, D, V) be a DL-model, $w \in W$ and $\phi^* \in \mathcal{L}_{DL}$. (M, w) is called a pointed DL-model. We define $M, w \models \phi^*$ inductively as follows.

$$\begin{array}{lll} M,w\models p^* & \textit{iff} & w\in V(p^*)\\ M,w\models \phi^*\wedge \psi^* & \textit{iff} & M,w\models \phi^* \; \textit{and} \; M,w\models \psi^*\\ M,w\models \neg\phi^* & \textit{iff} & \textit{not} \; M,w\models \phi^*\\ M,w\models O\alpha & \textit{iff} \; \; \textit{for all} \; v\in D(w), \; M,v\models \alpha. \end{array}$$

Condition (*) above ensures formally that conditional norms of the form "it is obligatory that if John knows that he drives above the speed limit then he slows down" $(O(p \to \alpha))$ are equivalent to "if John knows that he drives above the speed limit then it is obligatory that he slows down" $(p \to O\alpha)$:

$$\models O(p \to \alpha) \leftrightarrow (p \to O\alpha).$$

More generally, condition (*) allows us to show that any deontic formula with practition(s) $\mathcal{L}_{DL}^{\alpha}$ involving proposition(s) is actually equivalent to a deontic

¹ A relation R is serial iff $R(w) \neq \emptyset$ for all $w \in W$.

formula with 'pure' practitions $\mathcal{L}_{DL}^{\alpha'}$, i.e. a formula of $\mathcal{L}_{DL}' = \mathcal{L}_{DL}^{\phi} \cup \mathcal{L}_{DL}^{\alpha'}$:

$$\mathcal{L}_{DL}^{\alpha'}:\alpha:=\beta\mid\neg\alpha\mid\alpha\wedge\alpha$$

where β ranges over Φ^{α} .

Proposition 1. Let $\phi \in \mathcal{L}_{DL}$. There is $\phi' \in \mathcal{L}'_{DL}$ such that $\models \phi \leftrightarrow \phi'$.

In other words, instead of dealing with formulas of \mathcal{L}_{DL} , we could equivalently deal only with formulas of \mathcal{L}'_{DL} .

2.2 Adding beliefs

Just as practitions are the foci of deontic operators, propositions are dually the foci of knowledge operators, as pointed out by Castañeda [7]. An expression ϕ in the scope of a belief operator $B\phi$ is always in the indicative form and never in the subjunctive/infinitive form, even if $B\phi$ is in the scope of a deontic operator O. We extend Castañeda [7]'s intuition to the context of epistemic permissions and obligations. In a deontic setting the reading of the term knowledge or belief can also be twofold: either as a proposition or as a practition. On the one hand, in the sentence "it is obligatory that John knows / for John to know that he is driving too fast" the verb 'to know' is the focus of a deontic operator and is in the subjunctive/infinitive form. On the other hand, the sentence "John knows that he is driving too fast' alone describes a circumstance and the interpretation of the verb 'to know' in the indicative form matches the one usually studied in epistemic logic. The former use of the term knowledge within the scope of a deontic operator is not studied in epistemic logic. For these reasons we enrich the language \mathcal{L}_{DL} with two knowledge modalities, one for propositions and the other for practitions. This yields the following language $\mathcal{L}_{EDL} = \mathcal{L}_{EDL}^{\phi} \cup \mathcal{L}_{EDL}^{\alpha}$ whose formulas are generally denoted ϕ^* .

$$\begin{split} \mathcal{L}_{EDL}^{\phi} : \phi ::= p \mid \neg \phi \mid \phi \wedge \phi \mid B\phi \mid O\alpha \\ \mathcal{L}_{EDL}^{\alpha} : \alpha ::= \beta \mid \neg \alpha \mid \alpha \wedge \alpha \mid \alpha \wedge \phi \mid \phi \wedge \alpha \mid B'\phi \end{split}$$

where p ranges over Φ^{ϕ} and β over Φ^{α} . As argued above we do not allow formulas of the form $B\alpha$ or $B'\alpha$ because they are linguistically meaningless, which is actually in line with Castañeda [7]. $B\phi$ reads 'the agent believes ϕ '.

Definition 2. An EDL-model M is a tuple M = (W, D, R, R', V) where W is a non-empty set of possible worlds, R, R' and D are accessibility relations on W, D being serial, and V is a valuation such that:

for all
$$w \in W$$
, all $v, v' \in D(w) \cup \{w\}$, (M, v) is RD-bisimilar to (M, v') .² $(**)$

² Two pointed models (M, v) and (M', v') are RD-bisimilar if there is a relation on $W \times W'$ satisfying the base condition for Φ^{ϕ} and the back and forth conditions for R and D (see Blackburn et al. [4] for details).

The truth conditions for B and B' are given by:

$$\begin{array}{ll} M,w \models B\phi & \textit{iff} & \textit{for all } v \in R(w), \ M,v \models \phi \\ M,w \models B'\phi & \textit{iff} & \textit{for all } v \in R'(w), \ M,v \models \phi \end{array}$$

 $M \models \phi \text{ if for all } w \in W, M, w \models \phi. (M, w) \text{ is called a pointed } EDL\text{-model}.$

Note that condition (**) is a generalization of condition (*) to the epistemic setting: the worlds of $D(w) \cup \{w\}$ are not only 'propositionally bisimilar' as in (*), but also 'epistemically (and deontically) bisimilar'.

We do not assume any logical property for our notion of belief (such as consistency or introspection) because it is not really relevant for the topic of this paper. For the same reason, the operator B stands alternatively for knowledge or for belief.

Just as for \mathcal{L}_{DL} , we can show that the language \mathcal{L}_{EDL} is actually 'equivalent' to the language $\mathcal{L}'_{EDL} = \mathcal{L}^{\phi}_{EDL} \cup \mathcal{L}^{\alpha'}_{EDL}$ with 'pure' practitions $\mathcal{L}^{\alpha'}_{EDL}$:

$$\mathcal{L}_{EDL}^{\alpha'}:\alpha::=\beta\mid\neg\alpha\mid\alpha\wedge\alpha\mid B'\phi$$

Proposition 2. Let $\phi \in \mathcal{L}_{EDL}$. There is $\phi' \in \mathcal{L}'_{EDL}$ such that $\models \phi \leftrightarrow \phi'$.

In other words, instead of dealing with formulas of \mathcal{L}_{EDL} , we could equivalently deal only with formulas of \mathcal{L}'_{EDL} .

Theorem 1. The semantics of \mathcal{L}_{EDL} is sound and complete with respect to the decidable logic \mathcal{L}_{EDL} axiomatized as follows:

```
\begin{array}{lll} A_1 & All \ propositional \ tautologies \ based \ on \ \varPhi^\phi \cup \varPhi^\alpha \\ A_2 & \vdash (\phi \to O\alpha) \leftrightarrow O(\phi \to \alpha) \\ A_3 & \vdash O\alpha \to \neg O \neg \alpha \\ A_4 & \vdash O(\alpha \to \alpha') \to (O\alpha \to O\alpha') \\ A_5 & \vdash B^*(\phi^* \to \psi^*) \to (B^*\phi^* \to B^*\psi^*) \\ R_1 & If \vdash \alpha \ then \ \vdash O\alpha \\ R_2 & If \vdash \phi^* \ then \ \vdash B^*\phi^* \\ R_3 & If \vdash \phi^* \to \psi^* \ and \ \vdash \phi^* \ then \ \vdash \psi^* \end{array}
```

where B^* stands for B or B'.

Note that axioms A_1 to A_4 and rules R_1 and R_3 provide an alternative axiomatization of Castañeda's language \mathcal{L}_{DL} .

2.3 Example

Our logic can express conditional norms because it inherits from the properties of Castañeda's deontic logic (such as $\vdash (\phi \to O\alpha) \leftrightarrow O(\phi \to \alpha)$). Due to its combination of the deontic and epistemic notions, it can also express the knowledge-based obligations of [12]. But because our combination is quite general, we can also express *epistemic norms*.

Example 1 (Journal example). Assume that the librarian does not know whether the journal requested is on the list of journals to which the library has free access $(\neg B \neg JinList \land \neg B JinList)$. As a matter of fact, according to the library regulations, he should know whether it is a journal to which the library has free access (n_1) . Besides, he should also know that if it is a journal for which the library has free access then he should not to pay to download any paper of this journal (n_2) . These two epistemic norms are formalized as follows:

$$n_1 = O(B' \ JinList \lor B' \neg \ JinList)$$

 $n_2 = OB'(\ JinList \to O \neg pay)$

where *JinList* stands for 'the *J*ournal requested is *in* the *List* of journals for which the library has free access' and *pay* stands for 'pay Springer to download any paper of the journal'.

This situation is depicted in the EDL-model M of Figure 1, where JinListstands for the proposition 'the journal is in the list of journals for which the library has free access' and pay for the practition 'pay Springer to download any paper of the journal'. The dotted arrows correspond to the deontic accessibility relation D and the plain arrows correspond to accessibility relations R and R'. Reflexive arrows are omitted, which means that for all $v \in M$, we have that $v \in R(v), v \in R'(v)$ and $v \in D(v)$. w corresponds to the actual world. We therefore have $M, w \models (\neg B \ JinList \land \neg B \neg \ JinList) \land O(B' \ JinList \lor B' \neg \ JinList)$: the librarian does not know whether the requested journal is on the list of journals free of charge for the library although he should know whether this is the case. $M, w \models B(JinList \rightarrow O \neg pay) \land B(\neg JinList \rightarrow (\neg Opay \land \neg O \neg pay))$: the librarian knows that if the journal is in the list then he should not pay to download any paper of the journal and he knows that if it is not in the list then he might or might not have to pay to download papers of the journal (because the journal is then on limited access and some papers might be available for free whereas some others might not).




Fig. 1. Journal example

Dynamic Epistemic Deontic Logic (DEDL) 3

Changing norms and beliefs

We now want to add dynamics to the picture by means of communicative acts made to the agent. The content of these communicative acts can affect the situation in two ways: either it affects the epistemic realm (represented in a EDL-model by the relation R) or it affects the normative realm (represented in a EDL-model by the relations R' and D). This leads us to enrich the language \mathcal{L}_{EDL} with two dynamic operators $[\phi!]$ and $[\phi^*!!]$, yielding the language \mathcal{L}_{DEDL} , whose formulas are generally denoted ϕ^* :

$$\mathcal{L}_{DEDL}^{\phi}: \phi ::= p \mid \neg \phi \mid \phi \wedge \phi \mid B\phi \mid O\alpha \mid [\phi!]\phi \mid [\phi^*!!]\phi$$

$$\mathcal{L}_{DEDL}^{\alpha}: \alpha ::= \beta \mid \neg \alpha \mid \alpha \wedge \alpha \mid \alpha \wedge \phi \mid \phi \wedge \alpha \mid B'\phi \mid [\phi!]\alpha \mid [\phi^*!!]\alpha$$

where p ranges over Φ^{ϕ} , β over Φ^{α} .

 $[\psi!]\phi$ reads 'after learning ψ , ϕ holds', and $[\psi^*!!]\phi$ reads 'after the promulgation/enforcement of ψ^* , ϕ holds'. Note that it is possible that $\psi^* \in \mathcal{L}_{EDL}^{\phi}$ because propositions can affect the normative realm via R'. The semantics of these dynamic operators is inspired by Kooi [9] and defined as follows.

Definition 3. Let M=(W,D,R,R',V) be an EDL-model, $\phi \in \mathcal{L}_{EDL}^{\phi}$ and $\psi^* \in \mathcal{L}_{EDL}$. We define the EDL-models $M * \psi!$ and $M * \psi^*!!$ as follows.

$$-M * \psi! = (W, D, R!, R', V) \text{ where for all } w \in W,$$

$$R!(w) = R(w) \cap ||\psi||.$$

$$-M * \psi^*!! = (W, D!!, R, R'!!, V)$$
 where for all $w \in W$.

$$R!(w) = R(w) + ||\psi||.$$

$$- M * \psi^*!! = (W, D!!, R, R'!!, V) \text{ where for all } w \in W,$$

$$R'!!(w) = \begin{cases} R'(w) \cap ||\psi^*|| & \text{if } \psi^* \in \mathcal{L}_{EDL}^{\phi} \\ R'(w) & \text{otherwise.} \end{cases}$$

$$D!!(w) = \begin{cases} D(w) \cap ||\psi^*|| & \text{if } \psi^* \in \mathcal{L}_{EDL}^{\alpha} \text{ and } M, w \models P\psi^* \\ D(w) & \text{otherwise.} \end{cases}$$

where $||\phi^*|| = \{v \in M \mid M, v \models \phi^*\}$. The truth conditions:

$$\begin{array}{ll} M,w \models [\psi !] \phi^* & \textit{iff} & M * \psi !,w \models \phi^* \\ M,w \models [\psi^* !!] \phi^* & \textit{iff} & M * \psi^* !!,w \models \phi^*. \end{array}$$

Just as for \mathcal{L}_{EDL} and \mathcal{L}_{DL} , we can show that the language \mathcal{L}_{DEDL} is actually 'equivalent' to the language $\mathcal{L}'_{DEDL} = \mathcal{L}^{\phi}_{DEDL} \cup \mathcal{L}^{\alpha'}_{DEDL}$ with 'pure' practitions $\mathcal{L}_{DEDL}^{lpha'}$:

$$\mathcal{L}_{DEDL}^{\alpha'}:\alpha::=\beta\mid\neg\alpha\mid\alpha\wedge\alpha\mid B'\phi\mid[\phi!]\alpha\mid[\phi^*!!]\alpha$$

where p ranges over Φ^{ϕ} and β over Φ^{α}

Proposition 3. Let $\phi \in \mathcal{L}_{DEDL}$. There is $\phi' \in \mathcal{L}'_{DEDL}$ such that $\models \phi \leftrightarrow \phi'$.

In other words, instead of dealing with formulas of \mathcal{L}_{DEDL} , we could equivalently deal only with formulas of \mathcal{L}'_{DEDL} .

3.2 Examples

Changing beliefs: $[\phi!]$. Our logic is a dynamic epistemic logic, which allows to express communicative acts changing the beliefs of agents.

Example 2. Let us take up Example 1. A colleague of the librarian informs him that the journal is actually on the list of journals free of charge for the library because the university subscribed to this journal.

$$M, w \models JinList \land [JinList!]B JinList$$

After the communicative act the librarian knows that the journal is on the list of journals for which the library has free access. The resulting situation is depicted in Figure 2.




Fig. 2. Update by JinList!

Changing norms: $[\phi!!]$. Our logic is a dynamic deontic logic, which allows to express communicative acts changing the norms.

Example 3. Let us take up Example 1 again. When the librarian tries to download the journal paper, the Springer web-site informs him that this journal is now on open access since today. This event can be modeled by the communicative act $[\neg pay!!]$:

$$M, w \models [\neg pay!!](O \neg pay \land BO \neg pay)$$

After this communicative act, one should not pay to download any paper of the journal and the librarian knows this. This resulting situation is depicted in Figure 3. The only difference with the EDL-model of Figure 1 is that there is no dotted arrow from the bottom world to the top world on the right.

4 How to model prescriptive and descriptive obligations

Alchourrón and Bulygin [1,2] discussed the *possibility* of a logic of norms, which they distinguish from the logic of normative propositions. Alchourrón explains the distinction with the following box metaphor.




Fig. 3. Update by $\neg pay!!$

"We may depict the difference between the descriptive meaning (normative propositions) and the prescriptive meaning (norm) of deontic sentences by means of thinking the obligatory sets as well as the permitted sets as different boxes ready to be filled. When the authority α uses a deontic sentence prescriptively to norm an action, his activity belongs to the same category as putting something into a box. When α , or someone else, uses the deontic sentence descriptively his activity belongs to the same category as making a picture of α putting something into a box. A proposition is like a picture of reality, so to assert a proposition is like making a picture of reality. On the other hand to issue (enact) a norm is like putting something in a box. It is a way of creating something, of building a part of reality (the normative qualification of an action) with the purpose that the addressees have the option to perform the authorized actions while performing the commanded actions." [1]

In our logic we can distinguish Alchourrón's distinction between descriptive and prescriptive norms. We map this distinction to the context of communication. The descriptive communicative act of the Springer web-site announcing that he should not pay can be modeled by the communicative act $[O\neg pay!]$. Note that informing about the existence of a norm can enable the audience to know more information: for example, if the librarian should not pay for downloading any paper of a journal then he knows that this journal is on the list of journals for which the library has free access. The prescriptive communicative act of the librarian being informed that the journal is now on open access can be modeled by the communicative act $[\neg pay!!]$.

This mapping allows to understand the role of agent systems in deontic logic, since a traditional problem can be solved by stating it in terms of interaction among agents.

Example 4. Let us take up Example 1. Concerning the descriptive character of norms, we model the action of communicating that there is a norm obliging not to pay to download any paper as the announcement of the obligation $O\neg pay!$. The resulting situation is the same as the one depicted in Figure 2. After such announcement to the librarian, not only he believes that he should not pay to download any paper of the journal but also that the journal is in the list of

journals for which the library has free access:

$$M, w \models \neg B \ JinList \land [O \neg pay!](BO \neg pay \land B \ JinList)$$

The inference $[O\neg pay!]B\ JinList$ is possible if one should not pay Springer to download any paper of a journal which is in the list:

$$JinList \rightarrow O \neg pay$$

Note that pay is a practition, since it is in the scope of a deontic operator.

Concerning the prescriptive character of obligation, we model the action of putting a norm into existence, for example, by the Springer web-site announcing that from now on one should not pay to download any paper of the journal as the announcement of the practition $\neg pay!!$. The resulting situation is depicted in Figure 3. Note that, in this case, even if $JinList \to O \neg pay$, we cannot derive that the librarian knows that the journal is in the list. This is intuitively correct: the new norm has just been introduced today so there has not been enough time to update the list (it is updated every month).

$$M, w \models \neg B \ JinList \land [\neg pay!!](O \neg pay \land \neg B \ JinList).$$

5 Conclusions

Distinguishing the prescriptive and descriptive use of language is a classical challenge from deontic logic with practical consequences. If one agent tells another agent that he is obliged to do something, but the second agent would like to disagree, then the second agent should know whether the agent is creating a norm for him, or whether he is describing an existing normative system. In the first case he may disagree by responding that the agent is not authorized to create obligations for him, in the second case he may argue that the norm does not apply to him, or that the norm does not exist. Several formal systems therefore distinguish between prescriptive and descriptive obligations, but thus far the distinction was not analyzed in more detail, and the two kinds of obligations were not related to each other in an integrated framework.

In this paper, we give a more detailed analysis by modeling besides the normative system also the epistemic states of the agents, and how norms can be changed over time. Few articles in deontic logic deal with the interaction among deontic and epistemic notions, though they often entertain a tight relationship. Citizens must often know their obligations, e.g., people should know that it is forbidden to speed. Moreover, some obligations hold only in an epistemic context, e.g., John is obliged to slow down if he knows that he is driving over the speed limit [12]. To specify such examples of autonomous agents acting within a normative system, there is a need for the logical formalization of these relationships. To model the interaction between epistemic and normative notions in a dynamic setting we introduced a general Dynamic Epistemic Deontic Logic. The logic extends a simplified version of Castañeda's deontic logic of practitions and propositions with epistemic and dynamic update operators.

Further research concerns making the logic multi-agent, to study the implications of our approach for contrary to duties and deontic detachment.

References

- C. Alchourrón. Philosophical foundations of deontic logic and the logic of defeasible conditionals. In J.-J. Meyer and R. Wieringa, editors, *Deontic Logic in Computer Science: Normative System Specification*, pages 43–84. John Wiley & Sons, 1993.
- C. E. Alchourron and E. Bulygin. The expressive conception of norms. In R. Hilpinen, editor, New studies in deontic logic, pages 95–124. D. Reidel, Dordrecht, 1981.
- 3. G. Aucher, G. Boella, and L. van der Torre. Dynamic epistemic deontic logic for privacy regulations. Technical report, University of Luxembourg, 2009.
- 4. Patrick Blackburn, Maarten de Rijke, and Yde Venema. *Modal Logic*, volume 53 of *Cambridge Tracts in Computer Science*. Cambridge University Press, 2001.
- G. Boella, H. Verhagen, and L. van der Torre. Introduction to the special issue on normative multiagent systems. In *Journal of Autonomous Agents and Multi Agent* Systems, pages 1–10. Springer, 2008.
- 6. Hector-Neri Castañeda. The paradoxes of Deontic Logic: the simplest solution to all of them in one fell swoop, pages 37–86. Synthese library. 1981.
- Hector-Neri Castañeda. Knowledge and epistemic obligation. Philosophical perspectives, 2:211–233, 1988.
- 8. Jörg Hansen. Imperatives and deontic logic: On the semantic foundations of deontic logic. PhD thesis, University of Leipzig, Germany, 2008.
- 9. Barteld Kooi. Probabilistic dynamic epistemic logic. Journal of Logic, Language and Information, 12(4):381–408, 2003.
- D. Makinson. On a fundamental problem of deontic logic. In P. McNamara and H. Prakken, editors, Norms, Logics and Information Systems. New Studies on Deontic Logic and Computer Science, pages 29–54. IOS Press, 1999.
- 11. D. Makinson and L. van der Torre. Input-output logics. *Journal of Philosophical Logic*, 29(4):383–408, 2000.
- 12. Eric Pacuit and Rohit Parikh. The logic of knowledge based obligation. *Synthese*, 149(2), 2006.
- L. van der Torre and Y. Tan. An update semantics for deontic reasoning. In P. McNamara and H. Prakken, editors, Norms, Logics and Information Systems. New Studies on Deontic Logic and Computer Science, pages 73–90. IOS Press, 1999.
- 14. G. H. von Wright. Deontic logic as i see it. In P. McNamara and H. Prakken, editors, Norms, Logics and Information Systems. New Studies on Deontic Logic and Computer Science, page 15—25. IOS Press, 1999.
- 15. G.H. von Wright. On the logic of norms and actions. In R. Hilpinen, editor, New Studies in Deontic Logic: Norms, Actions and the Foundations of Ethics, pages 3–35. D.Reidel, 1981.