



Exponential convergence of an observer based on partial field measurements for the wave equation

Dominique Chapelle, Nicolae Cîndea, Maya de Buhan, Philippe Moireau

► To cite this version:

Dominique Chapelle, Nicolae Cîndea, Maya de Buhan, Philippe Moireau. Exponential convergence of an observer based on partial field measurements for the wave equation. Mathematical Problems in Engineering, 2012, 2012, pp.12. 10.1155/2012/581053 . inria-00619504v1

HAL Id: inria-00619504

<https://inria.hal.science/inria-00619504v1>

Submitted on 6 Sep 2011 (v1), last revised 4 Dec 2012 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



INSTITUT NATIONAL DE RECHERCHE EN INFORMATIQUE ET EN AUTOMATIQUE

Exponential convergence of an observer based on partial field measurements for the wave equation

Dominique Chapelle — Nicolae Cîndea — Maya De Buhan — Philippe Moireau

N° 7728

Septembre 2011

Observation, Modeling, and Control for Life Sciences



Exponential convergence of an observer based on partial field measurements for the wave equation

Dominique Chapelle*, Nicolae Cîndea†, Maya De Buhan‡,
Philippe Moireau§

Theme : Observation, Modeling, and Control for Life Sciences
Computational Sciences for Biology, Medicine and the Environment
Équipes-Projets macs

Rapport de recherche n° 7728 — Septembre 2011 — 7 pages

Abstract: We analyze an observer strategy based on partial – i.e. in a subdomain – measurements of the solution of a wave equation, in order to compensate for unknown initial conditions. We prove the exponential convergence of this observer under a non-standard observability condition, whereas using measurements of the time-derivative of the solution would lead to a standard observability condition arising in stabilization and exact controllability. Nevertheless, we directly relate our specific condition to the classical geometric control condition.

Key-words: observer, filtering, nudging, observability condition, exponential stability, wave equation, second-order evolution equation

* dominique.chapelle@inria.fr

† nicolae.cindea@inria.fr

‡ maya.de_buhan@inria.fr

§ philippe.moireau@inria.fr

Convergence exponentielle d'un observateur utilisant des mesures partielles pour l'équation des ondes

Résumé : Nous analysons un observateur formulé pour l'équation des ondes et utilisant des mesures de la solution dans un sous-domaine afin de compenser des conditions initiales inconnues. Nous démontrons la convergence exponentielle de cet observateur moyennant une condition d'observabilité non-standard, alors qu'une mesure de la dérivée en temps de la solution conduirait à la forme standard de la condition d'observabilité apparaissant en stabilisation et contrôlabilité exacte. Néanmoins, nous établissons un lien direct entre notre condition spécifique et la condition de contrôle géométrique classique.

Mots-clés : observateur, filtrage, nudging, condition d'observabilité, stabilité exponentielle, équation des ondes, équation du second ordre en temps

1 Introduction

Let Ω be a bounded domain of \mathbb{R}^n ($1 \leq n \leq 3$) with a Lipschitz boundary $\partial\Omega$. We consider the following wave equation

$$\begin{cases} \ddot{u}(x, t) - \Delta u(x, t) = 0, & (x, t) \in \Omega \times (0, \infty) \\ u(x, t) = 0, & (x, t) \in \partial\Omega \times (0, \infty) \\ u(x, 0) = u_0(x), \quad \dot{u}(x, 0) = v_0(x), & x \in \Omega \end{cases} \quad (1)$$

and we recall that if $(u_0, v_0) \in H_0^1(\Omega) \times L^2(\Omega)$ then $(u, \dot{u}) \in C((0, T); H_0^1(\Omega)) \times C((0, T); L^2(\Omega))$ for any $T > 0$, see e.g. [4].

In the observer framework of this paper, we assume that the initial condition (u_0, v_0) is unknown, albeit that we have a perfect measurement of the solution in $\omega \subset \Omega$ an open and non-empty subset of Ω . Our objective is to propose an observer which approximates the system (1) using this partial measurement

$$z(t) = u(\cdot, t)|_{\omega}, \quad t \geq 0. \quad (2)$$

To that purpose we define the operator

$$\mathcal{L}_{\omega} : H^1(\omega) \rightarrow H_0^1(\Omega), \quad \mathcal{L}_{\omega}\phi = \psi, \quad (3)$$

where ψ is the solution of the following elliptic equation

$$\begin{cases} \Delta\psi = 0, & \text{in } \Omega \setminus \omega \\ \psi = 0, & \text{on } \partial\Omega \\ \psi = \phi, & \text{in } \overline{\omega} \end{cases} \quad (4)$$

namely, a harmonic lifting operator. As a candidate observer, we will consider the following first-order system

$$\begin{cases} \dot{\hat{u}}(x, t) = \hat{v}(x, t) + \gamma \mathcal{L}_{\omega}(z(t) - \hat{u}(\cdot, t)|_{\omega}), & (x, t) \in \Omega \times (0, \infty) \\ \dot{\hat{v}}(x, t) - \Delta \hat{u}(x, t) = 0, & (x, t) \in \Omega \times (0, \infty) \\ \hat{u}(x, t) = 0, & (x, t) \in \partial\Omega \times (0, \infty) \\ \hat{u}(x, 0) = \hat{v}(x, 0) = 0, & x \in \Omega \end{cases} \quad (5)$$

with $\gamma > 0$ a gain parameter. Note that this system amounts to a modification of the wave equation written in a first-order form, with a correction term based on the discrepancy between the measurement and the observer primary variable. This strategy is the direct adaptation to the wave equation of the “Schur Displacement Feedback” filtering methodology originally proposed in [8] for elasticity-like formulations. Of course this type of approach can be categorized as a Luenberger observer [6] – also sometimes referred to as “nudging” [1] – applied on an evolution PDE.

2 Exponential convergence of the observer system

In order to establish that (5) is an adequate observer for (1), we should study the decay of the error

$$\begin{pmatrix} \tilde{u}(\cdot, t) \\ \tilde{v}(\cdot, t) \end{pmatrix} = \begin{pmatrix} u(\cdot, t) - \hat{u}(\cdot, t) \\ \dot{u}(\cdot, t) - \hat{v}(\cdot, t) \end{pmatrix}, \quad t \geq 0.$$

It is easy to see that this error satisfies the following system

$$\begin{cases} \dot{\tilde{u}}(x, t) = \tilde{v}(x, t) - \gamma \mathcal{L}_\omega(\tilde{u}|_\omega)(x, t), & (x, t) \in \Omega \times (0, \infty) \\ \dot{\tilde{v}}(x, t) = \Delta \tilde{u}(x, t), & (x, t) \in \Omega \times (0, \infty) \\ \tilde{u}(x, t) = 0, & (x, t) \in \partial\Omega \times (0, \infty) \\ \tilde{u}(x, 0) = u_0(x), \quad \tilde{v}(x, 0) = v_0(x), & x \in \Omega \end{cases} \quad (6)$$

and we will prove the exponential decay of the associated energy, namely,

$$\tilde{E}(t) = \frac{1}{2} \left(\int_{\Omega} |\nabla \tilde{u}(x, t)|^2 \, d\Omega + \int_{\Omega} |\tilde{v}(x, t)|^2 \, d\Omega \right). \quad (7)$$

Proposition 2.1. *Assume that we have the observability condition*

$$\int_0^T \|u(\cdot, t)\|_{H^1(\omega)}^2 dt \geq C \left(\|u_0\|_{H^1(\Omega)}^2 + \|v_0\|_{L^2(\Omega)}^2 \right), \\ \forall (u_0, v_0) \in H_0^1(\Omega) \times L^2(\Omega), \quad (8)$$

for some $T > 0$, then there exist strictly positive constants M and μ such that

$$\tilde{E}(t) \leq M e^{-\mu t} \tilde{E}(0), \quad \forall t > 0. \quad (9)$$

Proof. Let us consider the space H_ω^1 defined by $H^1(\omega)$ equipped with the norm

$$\|\phi\|_{H_\omega^1}^2 = \langle \nabla(\mathcal{L}_\omega \phi), \nabla(\mathcal{L}_\omega \phi) \rangle_{L^2(\Omega)}.$$

It is straightforward to see that this norm is equivalent to the usual norm of $H^1(\omega)$, since \mathcal{L}_ω is a lifting operator with Dirichlet boundary conditions and we can then adapt the proof of the Poincaré inequality. We now define

$$B_0 : H_\omega^1 \rightarrow H_0^1(\Omega), \quad B_0 \phi = \mathcal{L}_\omega \phi, \quad (10)$$

a bounded operator. The adjoint of B_0 (via Riesz representation) is then

$$B_0^* : H_0^1(\Omega) \rightarrow H_\omega^1, \quad B_0^* \psi = \psi|_\omega, \quad (11)$$

as can be shown by a simple manipulation on the definition (10). We now introduce the state space operators

$$A : \mathcal{D}(\Delta) \times H_0^1(\Omega) \rightarrow H_0^1(\Omega) \times L^2(\Omega), \quad A = \begin{pmatrix} 0 & I \\ \Delta & 0 \end{pmatrix}, \quad (12)$$

with $\mathcal{D}(\Delta) = \{\psi \in H_0^1(\Omega) \text{ s.t. } \Delta \psi \in L^2(\Omega)\}$, and

$$B : H_\omega^1 \rightarrow H_0^1(\Omega) \times L^2(\Omega), \quad B = \begin{pmatrix} B_0 \\ 0 \end{pmatrix}. \quad (13)$$

With these notations, the error system (6) can be rewritten as

$$\begin{cases} \begin{pmatrix} \dot{\tilde{u}}(t) \\ \dot{\tilde{v}}(t) \end{pmatrix} = (A - \gamma BB^*) \begin{pmatrix} \tilde{u}(t) \\ \tilde{v}(t) \end{pmatrix}, & t > 0 \\ \begin{pmatrix} \tilde{u}(0) \\ \tilde{v}(0) \end{pmatrix} = \begin{pmatrix} u_0 \\ v_0 \end{pmatrix} \end{cases} \quad (14)$$

Therefore, the exponential decay of the energy (7) is equivalent to the following observability inequality, see e.g. Theorem 2.3 in [5]

$$\int_0^T \left\| B^* \begin{pmatrix} u(t) \\ \dot{u}(t) \end{pmatrix} \right\|_{H_\omega^1}^2 dt \geq C \left(\|u_0\|_{H_0^1(\Omega)}^2 + \|v_0\|_{L^2(\Omega)}^2 \right),$$

$$\forall (u_0, v_0) \in H_0^1(\Omega) \times L^2(\Omega), \quad (15)$$

where u is the solution of the original wave equation (1), and for some strictly positive constants T and C , and of course this condition is directly equivalent to (8). \square

However, the observability condition (8) is somewhat non-standard, which has to do with the fact that we are considering an observer formulation instead of a stabilization (or exact controllability) problem. Nevertheless, the following proposition directly relates our observability condition with classical results.

Proposition 2.2. *Assume that the geometric control condition of Bardos, Lebeau and Rauch [2] is satisfied for some $\check{\omega}$ strict subset of ω such that $\text{dist}(\Omega \setminus \omega, \check{\omega}) > 0$. Then the observability condition (8) holds for some time $T > 0$.*

Proof. Since the geometric control condition holds, we have the classical observability condition [2]

$$\int_0^{\check{T}} \int_{\check{\omega}} |\dot{u}(x, t)|^2 d\Omega dt \geq C \left(\|u_0\|_{H^1(\Omega)}^2 + \|v_0\|_{L^2(\Omega)}^2 \right),$$

$$\forall (u_0, v_0) \in H_0^1(\Omega) \times L^2(\Omega), \quad (16)$$

for some time $\check{T} > 0$. We will show that this entails (8) by an argument inspired from [9]. Let $\psi \in C_c^\infty(\overline{\Omega})$ be a cutoff function defined by

$$\psi(x) = \begin{cases} 0, & \text{if } x \in \Omega \setminus \omega \\ 1, & \text{if } x \in \check{\omega} \end{cases}$$

and $0 \leq \psi(x) \leq 1$ for every $x \in \overline{\Omega}$. Denote also $\phi(t) = t^2(\check{T} - t)^2$. Then, by repeated integrations by parts we obtain

$$\begin{aligned} 0 &= \int_0^{\check{T}} \int_\omega \phi \psi (\ddot{u} - \Delta u) u d\Omega dt \\ &= \int_0^{\check{T}} \int_\omega \ddot{\phi} \psi \frac{|u|^2}{2} d\Omega dt - \int_0^{\check{T}} \int_\omega \phi \psi |\dot{u}|^2 d\Omega dt + \int_0^{\check{T}} \int_{\partial\omega} \phi \frac{\partial \psi}{\partial n} \frac{|u|^2}{2} d\Gamma dt \\ &\quad - \int_0^{\check{T}} \int_\omega \phi \Delta \psi \frac{|u|^2}{2} d\Omega dt + \int_0^{\check{T}} \int_\omega \phi \psi |\nabla u|^2 d\Omega dt. \end{aligned}$$

The definition of ψ entails $(\partial \psi / \partial n)|_{\partial\omega} = 0$, hence

$$\begin{aligned} \int_0^{\check{T}} \int_\omega \phi \psi |\dot{u}|^2 d\Omega dt &= \int_0^{\check{T}} \int_\omega \phi \psi |\nabla u|^2 d\Omega dt + \int_0^{\check{T}} \int_\omega \ddot{\phi} \psi \frac{|u|^2}{2} d\Omega dt \\ &\quad - \int_0^{\check{T}} \int_\omega \phi \Delta \psi \frac{|u|^2}{2} d\Omega dt. \end{aligned}$$

The above identity combined with the properties of the cutoff functions ϕ and ψ provides, for any strictly positive ε , the existence of a constant $C > 0$ such that

$$C \int_{\varepsilon}^{\check{T}-\varepsilon} \int_{\check{\omega}} |\dot{u}|^2 d\Omega dt \leq \int_0^{\check{T}} \int_{\omega} |\nabla u|^2 d\Omega dt + \int_0^{\check{T}} \int_{\omega} |u|^2 d\Omega dt. \quad (17)$$

Substituting $\check{T} + 2\varepsilon$ for \check{T} in all the above computations gives

$$C \int_{\varepsilon}^{\check{T}+\varepsilon} \int_{\check{\omega}} |\dot{u}|^2 d\Omega dt \leq \int_0^{\check{T}+2\varepsilon} \|u(\cdot, t)\|_{H^1(\omega)}^2 dt.$$

We proceed by making the change of variable $\tau = t - \varepsilon$ in the left-hand side integral, yielding

$$C \int_0^{\check{T}} \int_{\check{\omega}} |\dot{u}(x, \tau + \varepsilon)|^2 d\Omega d\tau \leq \int_0^{\check{T}+2\varepsilon} \|u\|_{H^1(\omega)}^2 dt. \quad (18)$$

Noting that $u(x, t+\varepsilon)$ satisfies the wave equation with initial data $(u(x, \varepsilon), \dot{u}(x, \varepsilon))$ and applying (16) with this shifted solution, we obtain

$$\int_0^{\check{T}} \int_{\check{\omega}} |\dot{u}(x, t + \varepsilon)|^2 d\Omega dt \geq C \left(\|u(\varepsilon)\|_{H^1(\Omega)}^2 + \|\dot{u}(\varepsilon)\|_{L^2(\Omega)}^2 \right). \quad (19)$$

Combining (18), (19) and the fact that the energy of the solution of the wave equation is exactly conserved over time, we have the observability inequality (8) for any T strictly greater than \check{T} . \square

Note that this proof requires a geometric control condition slightly stronger than that directly associated with the measurement domain ω , since $\check{\omega}$ is a strict subset. However, micro-local analysis – see [3], albeit based for our specific case on the H^1 norm – may provide an alternative approach to circumvent this restriction.

As a final remark, we emphasize that the standard observability condition (16) would be directly applicable to establish the exponential convergence of an observer formulation based on the measurement of the “velocity” \dot{u} in the subset, as used in “Direct Velocity Feedback” Luenberger observer strategies [7]. In our case, the specific difficulty comes from the fact that we assume that we measure u itself, and that we do not wish to differentiate this measurement in time, typically to avoid amplifying the measurement errors which always arise in practice. Note that in our approach such errors – disregarded in this short note – would simply entail an additional source term in the observer equations.

References

- [1] D. Auroux and J. Blum. A nudging-based data assimilation method: the Back and Forth Nudging (BFN) algorithm. *Nonlinear Processes Geophysics*, 15:305–319, 2008.
- [2] C. Bardos, G. Lebeau, and J. Rauch. Sharp sufficient conditions for the observation, control, and stabilization of waves from the boundary. *SIAM J. Control Optim.*, 30(5):1024–1065, 1992.

- [3] N. Burq and P. Gérard. Condition nécessaire et suffisante pour la contrôlabilité exacte des ondes. *C. R. Acad. Sci. Paris, Série I*, t. 325:749–752, 1997.
- [4] R. Dautray and J.-L. Lions. *Mathematical Analysis and Numerical Methods for Science and Technology. Vol. 5*. Springer-Verlag, Berlin, 1992.
- [5] Kangsheng Liu. Locally distributed control and damping for the conservative systems. *SIAM J. Control Optim.*, 35(5):1574–1590, 1997.
- [6] D. G. Luenberger. An introduction to observers. *IEEE Transactions on Automatic Control*, 16:596–602, 1971.
- [7] P. Moireau, D. Chapelle, and P. Le Tallec. Joint state and parameter estimation for distributed mechanical systems. *Computer Methods in Applied Mechanics and Engineering*, 197:659–677, 2008.
- [8] P. Moireau, D. Chapelle, and P. Le Tallec. Filtering for distributed mechanical systems using position measurements: Perspectives in medical imaging. *Inverse Problems*, 25(3):035010 (25pp), 2009. doi:10.1088/0266-5611/25/3/035010.
- [9] X. Zhang. Explicit observability estimate for the wave equation with potential and its application. *Proceedings: Mathematical, Physical and Engineering Sciences*, 456(1997):pp. 1101–1115, 2000.



Centre de recherche INRIA Paris – Rocquencourt
Domaine de Voluceau - Rocquencourt - BP 105 - 78153 Le Chesnay Cedex (France)

Centre de recherche INRIA Bordeaux – Sud Ouest : Domaine Universitaire - 351, cours de la Libération - 33405 Talence Cedex

Centre de recherche INRIA Grenoble – Rhône-Alpes : 655, avenue de l'Europe - 38334 Montbonnot Saint-Ismier

Centre de recherche INRIA Lille – Nord Europe : Parc Scientifique de la Haute Borne - 40, avenue Halley - 59650 Villeneuve d'Ascq

Centre de recherche INRIA Nancy – Grand Est : LORIA, Technopôle de Nancy-Brabois - Campus scientifique

615, rue du Jardin Botanique - BP 101 - 54602 Villers-lès-Nancy Cedex

Centre de recherche INRIA Rennes – Bretagne Atlantique : IRISA, Campus universitaire de Beaulieu - 35042 Rennes Cedex

Centre de recherche INRIA Saclay – Île-de-France : Parc Orsay Université - ZAC des Vignes : 4, rue Jacques Monod - 91893 Orsay Cedex

Centre de recherche INRIA Sophia Antipolis – Méditerranée : 2004, route des Lucioles - BP 93 - 06902 Sophia Antipolis Cedex

Éditeur

INRIA - Domaine de Voluceau - Rocquencourt, BP 105 - 78153 Le Chesnay Cedex (France)

<http://www.inria.fr>

ISSN 0249-6399